

PROCORE™ EDGE SERIES

Intelligent Charging System
For Conventional, Opportunity,
and Fast Charging Operations

Product Variations:
440 / 480V: 6-30kW
600V: 6-30kW
380 / 400V: 6-15kW



KEY FEATURES



- + **Universal Compatibility:** Supports all major battery types, including Lead Acid, Li-ion, Ni-MH, and Sodium-ion.
- + **Auto Mode Selection:** Automatically switches between battery chemistries - no operator interaction required.
- + **Easy Installation:** The only UL-approved charger that can be de-rated to fit smaller breakers—making installation simple even in facilities with limited power capacity.
- + **Easy Maintenance:** Only three replaceable parts, all easily changed with a common tool kit.
- + **App-Enabled:** Configure, diagnose, and program via Bluetooth.
- + **Advanced Cooling:** Optimized active thermal management for extended module life and charger reliability.
- + **Real-Time Status:** integrated LED stack light bar providing real-time charging information and health status.
- + **High-Frequency Charging:** The only HF charger supporting 48-96V in one module.
- + **Power Supply:** low- AC-ripple output protects sensitive battery chemistries.

OVERVIEW

From small operations to large-scale fleets, ProCore Edge provides a scalable, future-proof charging solution backed by over 25 years of battery management expertise, an industry-leading 5-year warranty, and the most advanced power study tools available.

MOBILE ACCESS & CONTROL

With a mobile app for programming, diagnostics, and configuration, ProCore Edge removes the need for specialized service tools— everything from configuration to data downloads is handled seamlessly via Bluetooth. Advanced thermal management enhances battery longevity, while intelligent power management enables optimal charging for both heavy-duty lead-acid and high-efficiency lithium applications.

Mobile app allows detailed data analytics, diagnostics, and remote software updates



TECHNICAL SPECIFICATIONS

ProCore Edge 24/36/48V

Output Power Rating	6 kW	9 kW	12 kW	15 kW	18 kW	21 kW	24 kW	27 kW	30 kW
Max Output Current (A)	128/128/104	192/192/156	256/256/208	320/320/260	384/384/313	448/448/365	512/512/417	576/576/469	640/640/521
Full Load Amp Draw 480 VAC (A)	9	14	19	24	25	29	33	37	41
Circuit Breaker at 480 VAC	15	14	25	30	35	40	45	50	60
Cabinet	8	20	C	C	D	D	D	D	D

ProCore Edge 48/72/80/96V*

Output Power Rating	9 kW	12 kW	15 kW	18 kW	21 kW	24 kW	27 kW	30 kW
Max Output Current (A)	120/111/100	160/148/133	200/185/167	240/222/200	280/259/233	320/296/267	360/333/300	400/370/333
Full Load Amp Draw 480 VAC (A)	14	19	24	26	30	35	30	43
Circuit Breaker at 480 VAC	20	25	30	35	40	45	50	60
Cabinet	B	C	C	D	D	D	D	D

*96V Li-Ion applications only

Cabinet Dimension			
Type	Bays	Dimensions (inches)	Dimensions (mm)
B	3	8.6"h X 21"w X 14.7"d	472h X 533w X 373d
C	5	24.8"h X 21"w X 14.7"d	630h X 533w X 373d
D	10	40"h X 21"w X 14.8"d	1028h X 537w X 375d

PROCORE EDGE

Engineered for unmatched performance, ProCore Edge features a multi-voltage, multi-chemistry modular design that delivers flexibility, reliability, and scalability. Configurable from 24V to 96V, its power can be easily expanded by adding modules as needed.


SINGLE CONTROLLER SERVING ALL CHEMISTRIES

With charge algorithms configured for each battery and type, optimizing performance of Lead Acid, Li-ion, Ni-MH, and Sodium-ion

LED COLOR-CODED LIGHT BAR

Status indicator light bar provides visibility across facility

LED INTERFACE



User-friendly LED interface shows real-time charging status



FLEXIBLE INSTALLATION OPTIONS

Can be pole-mounted, wall-mounted, or installed free-standing on a charger stand

MULTI-VOLTAGE MODULAR DESIGN

Supports 24–48V and 48–96V charging. The modular design scales power as needed, continues operating during a module failure, and balances load for enhanced reliability and extended lifespan

INSTALLATIONS

