

SVS 100

Compact Single-Port Intelligent Charger



Technical Specifications

Power Rating	10kW
Utility Requirements	480 / 600 VAC, 3-phase
Full Load Amp Draw	15A / 12A MAX
Max Circuit Breaker Rating	20A / 15A
Power Factor	0.98
Efficiency	91%
Battery Voltage Range	24V - 80V
Max Output Current	250A
Weight	388 LBS
Dimensions	39.4"H X 22"W X 19.3"D



The PosiCharge SVS100 delivers up to 10 kW of efficient single-port power in a compact, outdoor-rated design—ideal for small electric belt loaders, carts, and people movers. Built with high-performance IGBT technology, it withstands harsh environments while supporting a wide range of battery voltages, types, and capacities.

When paired with a PosiCharge BMID, the SVS100 intelligently adjusts charge profiles based on real-time battery voltage and temperature data, ensuring maximum safety, faster charging, and extended battery life. Charging session data can also be captured to monitor vehicle and battery performance.

KEY FEATURES:

- Compatible with all PosiCharge BMIDs for adaptive charging and data capture
- Supports multiple vehicles and battery types on one charger
- Adaptive charge rate with automatic start/stop
- High-efficiency IGBT technology
- Anti-arcing disconnect and auto-thermal shutdown
- Compact, easy to install, and low maintenance
- Cost-effective solution for small or remote fleets
- Euro and Burton output connector options