

xh

Spencer Tipping

June 20, 2014

# Contents

<b>I</b>	<b>design</b>	<b>2</b>
1	constraints	3
2	xh-script	13
3	xh-script syntax	18
4	runtime	20
<b>II</b>	<b>base implementation</b>	<b>25</b>
5	self-replication	26
6	html introspection	29
<b>III</b>	<b>self-hosting implementation</b>	<b>32</b>
7	computational abstraction	33

**Part I**

**design**

# Chapter 1

## constraints

xh is designed to be a powerful and ergonomic interface to multiple systems, many of which are remote. As such, it's subject to programming language, shell, and distributed-systems constraints:

1. *realprog* xh will be used for real programming. (*initial assumption*)
2. *shell* xh will be used as a shell. (*initial assumption*)
3. *distributed* xh will be used to manage any machine on which you have a login, which could be hundreds or thousands. (*initial assumption*)
4. *noroot* You will not always have root access to machines you want to use, and they may have different architectures. (*initial assumption*)
5. *ergonomic* xh should approach the limit of ergonomic efficiency as it learns more about you. (*initial assumption*)
6. *security* xh should never compromise your security, provided you understand what it's doing. (*initial assumption*)
7. *webserver* It should be possible to write a "hello world" HTTP server on one line.
  - *initial assumption*
  - *realprog 1*
  - *shell 2*
8. *liveprev* It should be possible to preview the evaluation of any well-formed expression without causing side-effects.
  - *initial assumption*
  - *shell 2*
  - *ergonomic 5*

- *nodebug 11*
9. *notslow* xh should never cause an unresolvable performance problem that could be worked around by using a different language.
    - *initial assumption*
    - *realprog 1*
    - *ergonomic 5*
  10. *unreliable* Connections between machines may die at any time, and remain down for arbitrarily long. xh must never become unresponsive when this happens, and any data coming from those machines should block until it is available again (i.e. xh's behavior should be invariant with connection failures).
    - *initial assumption*
    - *realprog 1*
    - *shell 2*
    - *distributed 3*
  11. *nodebug* Debugging should require little or no effort; all error cases should be trivially obvious.
    - *initial assumption*
    - *realprog 1*
    - *distributed 3*
    - *ergonomic 5*
  12. *database* An xh instance should trivially function as a database; there should be no distinction between data in memory and data on disk.
    - *initial assumption*
    - *realprog 1*
    - *ergonomic 5*
    - *nodebug 11*
    - *no-oom 19*
    - *notslow 9*
  13. *prediction* xh should use every keystroke to build/refine a model it uses to predict future keystrokes and commands. (*ergonomic 5*)
  14. *history* The likelihood that xh forgets anything from your command history should be inversely proportional to the amount of effort required to retype/recreate it.
    - *ergonomic 5*

- *prediction* 13
15. *anonymous* xh must provide a way to accept input and execute commands without updating its prediction model. (*security* 6)
  16. *pastebin* xh should be able to submit an encrypted version of its current state to HTTP services like Github gists or pastebin.
    - *ergonomic* 5
    - *security* 6
    - *unreliable* 10
    - *selfinstall* 52
    - *wwwinit* 53
  17. *likeshell* xh-script needs to feel like a regular shell for most purposes. (*shell* 2)
  18. *imperative* xh-script should be fundamentally imperative.
    - *realprog* 1
    - *shell* 2
    - *likeshell* 17
  19. *no-oom* xh must never run out of memory or swap pages to disk, regardless of what you tell it to do.
    - *realprog* 1
    - *shell* 2
    - *notslow* 9
    - *ergonomic* 5
  20. *nonblock* xh must respond to every keystroke within 20ms; therefore, SSH must be used only for nonblocking RPC requests (i.e. the shell always runs locally).
    - *shell* 2
    - *notslow* 9
    - *ergonomic* 5
  21. *remotestuff* All resources, local and remote, must be uniformly accessible; i.e. autocomplete, filename substitution, etc, must all just work (up to random access, which is impossible without FUSE or similar).
    - *shell* 2
    - *distributed* 3
    - *ergonomic* 5

- 22. *prefix* xh-script uses prefix notation. (*shell 2*)
- 23. *quasiquote* xh-script quasiquotes values by default. (*shell 2*)
- 24. *unquote* xh-script defines an unquote operator.
  - *shell 2*
  - *quasiquote 23*
- 25. *datastruct* The xh runtime provides real, garbage-collected data structures. (*realprog 1*)
- 26. *quotestruct* Every xh data structure has a quoted form.
  - *datastruct 25*
  - *shell 2*
  - *nodebug 11*
  - *liveprev 8*
- 27. *printstruct* Every xh data structure can be losslessly serialized.
  - *shell 2*
  - *distributed 3*
  - *database 12*
  - *quotestruct 26*
  - *varsinrc 55*
  - *imagemerging 58*
- 28. *immutable* Data structures have no identity and therefore are immutable.
  - *distributed 3*
  - *printstruct 27*
- 29. *opaques* xh-script must have access to machine-specific opaque resources like PIDs and file handles.
  - *realprog 1*
  - *shell 2*
- 30. *mutablesyms* Each xh instance should implement a mutable symbol table with weak reference support, subject to semi-conservative distributed garbage collection.
  - *immutable 28*
  - *opaques 29*
  - *no-oom 19*

- *heap* 46
31. *stateown* Every piece of mutable state, including symbol tables, must have at most one authoritative copy (mutable state ownership within xh is managed by a CP system, and the state itself is trivially CP).
    - *unreliable* 10
    - *opaques* 29
    - *mutablesyms* 30
    - *threadmobility* 49
  32. *checkpoint* An xh instance should be able to save checkpoints of itself in case of failure. If you do this, xh becomes an AP system.
    - *unreliable* 10
    - *stateown* 31
  33. *lazy* xh's evaluator must support some kind of laziness.
    - *realprog* 1
    - *no-oom* 19
    - *remotestuff* 21
    - *notslow* 9
  34. *printlazy* Lazy values must have well-defined quoted forms and be losslessly serializable.
    - *quotestruct* 26
    - *printstruct* 27
    - *lazy* 33
    - *threadmobility* 49
    - *heap* 46
  35. *introspectlazy* All lazy values must be subject to introspection to identify why they haven't been realized.
    - *nodebug* 11
    - *notslow* 9
    - *unreliable* 10
    - *nonblock* 20
    - *lazy* 33
    - *threadscheduler* 48
  36. *abstract* xh must be able to partially evaluate expressions that contain unknown quantities.



- *liveprev* 8
  - *lazy* 33
  - *introspectlazy* 35
  - *printlazy* 34
37. *code=data* xh-script code should be a reasonable data storage format.
- *shell* 2
  - *abstract* 36
38. *selfparse* xh-script must contain a library to parse itself. (*code=data* 37)
39. *homoiconic* xh-script must be homoiconic.
- *code=data* 37
  - *selfparse* 38
  - *selfhost* 43
  - *abstractstruct* 45
40. *xh2c* xh should be able to compile any function to C, compile it if the host has a C compiler, and transparently migrate execution into this process.
- *realprog* 1
  - *threadmobility* 49
  - *notslow* 9
41. *xh2perl* xh should be able to compile any function to Perl rather than interpreting its execution.
- *realprog* 1
  - *noroot* 4
  - *notslow* 9
42. *xh2js* xh should be able to compile any function to Javascript so that browser sessions can transparently become computing nodes.
- *realprog* 1
  - *distributed* 3
  - *notslow* 9
43. *selfhost* xh should follow a bootstrapped self-hosting runtime model.
- *xh2c* 40
  - *xh2perl* 41
  - *xh2js* 42

- *abstractstruct* 45
44. *dynamiccompiler* xh-script should be executed by a profiling/tracing dynamic compiler that automatically compiles certain pieces of code to alternative forms like Perl or C. (*notslow* 9)
  45. *abstractstruct* The xh compiler should optimize data structure representations for the backend being targeted.
    - *notslow* 9
    - *threadmobility* 49
    - *dynamiccompiler* 44
  46. *heap* xh needs to implement its own heap and memory manager, and swap values to disk without blocking.
    - *realprog* 1
    - *no-oome* 19
    - *database* 12
    - *inperl* 56
  47. *threading* xh should implement its own threading model to accommodate blocked IO requests.
    - *shell* 2
    - *distributed* 3
    - *webserver* 7
    - *lazy* 33
    - *heap* 46
  48. *threadscheduler* xh threads should be subject to scheduling that reflects the user's priorities.
    - *shell* 2
    - *distributed* 3
    - *lazy* 33
    - *threading* 47
  49. *threadmobility* Running threads must be transparently portable between machines and compiled backends.
    - *distributed* 3
    - *threading* 47
    - *dynamiccompiler* 44
    - *abstractstruct* 45

- *threadscheduler* 48
50. *refaffinity* All machine-specific references must encode the machine for which they are defined.
- *opaques* 29
  - *threadmobility* 49
51. *uniqueid* Every xh instance must have a unique ID, ideally one that can be typed easily.
- *ergonomic* 5
  - *refaffinity* 50
52. *selfinstall* xh needs to be able to self-install on remote machines with no intervention (assuming you have a passwordless SSH connection).
- *distributed* 3
  - *noroot* 4
53. *wwwinit* You should be able to upload your xh image to a website and then install it with a command like this: `curl me.com/xh | perl`.
- *distributed* 3
  - *noroot* 4
54. *selfmodifying* Your settings should be present as soon as you download your image, so the image must be self-modifying and contain your settings.
- *distributed* 3
  - *ergonomic* 5
  - *prediction* 13
  - *selfinstall* 52
  - *wwwinit* 53
55. *varsinrc* Your settings should be able to contain any value you can create from the REPL (with the caveat that some are defined only with respect to a specific machine).
- *realprog* 1
  - *shell* 2
  - *ergonomic* 5
  - *datastruct* 25
  - *wwwinit* 53
56. *inperl* xh should probably be written in Perl 5.

- *distributed* 3
  - *noroot* 4
  - *selfinstall* 52
  - *wwwinit* 53
  - *selfmodifying* 54
57. *perlcoreonly* xh can't have any dependencies on CPAN modules, or anything else that isn't in the core library.
- *distributed* 3
  - *noroot* 4
  - *selfinstall* 52
58. *imagemerging* It should be possible to address variables defined within xh images (as files or network locations).
- *selfmodifying* 54
  - *varsinrc* 55
59. *sshrpc* xh's RPC protocol must work via stdin/out communication over an SSH channel to a remote instance of itself.
- *distributed* 3
  - *security* 6
  - *selfinstall* 52
  - *nonblock* 20
  - *remotestuff* 21
60. *rpcmulti* xh's RPC protocol must support request multiplexing.
- *distributed* 3
  - *notslow* 9
  - *nonblock* 20
  - *remotestuff* 21
  - *lazy* 33
  - *sshrpc* 59
61. *hostswitch* Two xh servers on the same host should automatically connect to each other. This allows a server-only machine to act as a VPN.
- *distributed* 3
  - *noroot* 4
  - *sshrpc* 59

- *transitive* 63
62. *domainsockets* xh should create a UNIX domain socket to listen for other same-machine instances.
- *security* 6
  - *hostswitch* 61
63. *transitive* xh's network topology should forward requests transitively.
- *distributed* 3
  - *noroot* 4
  - *sshrpc* 59
64. *routing* xh should implement a network optimizer that responds to observations it makes about latency and throughput.
- *notslow* 9
  - *sshrpc* 59
  - *transitive* 63

# Chapter 2

## xh-script

These constraints are based on the ones in [chapter 1](#).

1. *xhs.eval-identities* Evaluation of any expression may happen at any time; the only scheduling constraint is the realization of lazy expressions, whose status is visible by looking at their quoted forms. Therefore, the evaluator is, to some degree, associative, commutative, and idempotent.
  - *initial assumption*
  - *distributed 3* above
  - *nodebug 11* above
  - *liveprev 8* above
  - *nonblock 20* above
  - *lazy 33* above
  - *introspectlazy 35* above
  - *abstract 36* above
2. *xhs.relational* Relational evaluation is possible by using `amb`, which returns any of the given presumably-equivalent values. `xh-script` is relational and invertible, though inversion is not always lossless and may produce perpetually-unresolved unknowns representing degrees of freedom.
  - *initial assumption*
  - *nodebug 11* above
  - *lazy 33* above
  - *introspectlazy 35* above
  - *abstract 36* above
  - *selfhost 43* above
  - *abstractstruct 45* above

- *threadscheduler* 48 above
  - *xhs.eval-identities* 1
3. *xhs.bestfirst* Due to functions like *amb*, evaluation proceeds as a best-first search through the space of values. You can influence this search by defining the abstraction relation for a particular class of expressions.
    - *notslow* 9 above
    - *xhs.relational* 2
  4. *xhs.nocut* Unlike Prolog, *xh* defines no cut primitive. You should use abstraction to locally grade the search space instead.
    - *nodebug* 11 above
    - *xhs.eval-identities* 1
    - *xhs.bestfirst* 3
  5. *xhs.unquote-structure* Unquoting is structure-preserving with respect to parsing; that is, it will never force a reparsing if its argument has already been parsed.
    - *initial assumption*
    - *realprog* 1 above
    - *unquote* 24 above
    - *notslow* 9 above
    - *abstract* 36 above
  6. *xhs.stackscope* All scoping is done by passing a second argument to *unquote*; this enables variable resolution during the unquoting operation.
    - *initial assumption*
    - *unquote* 24 above
    - *mutablesyms* 30 above
    - *xhs.eval-identities* 1
  7. *xhs.noshadow* Variable shadowing is impossible.
    - *xhs.eval-identities* 1
    - *xhs.stackscope* 6
  8. *xhs.unquote-parse* Unquoting and structural parsing are orthogonal operations provided by *unquote* and *read*, respectively.
    - *quotestruct* 26 above
    - *introspectlazy* 35 above
    - *xhs.eval-identities* 1

- *xhs.unquote-structure* 5
9. *xhs.runtimereceiver* Whether via RPC or locally, statements issued to an xh runtime can be interpreted as messages being sent to a receiver; the reply is sent along whatever continuation is specified. The runtime doesn't differentiate between local and remote requests, including those made by functions.
    - *imperative* 18 above
    - *threading* 47 above
    - *threadmobility* 49 above
    - *stateown* 31 above
  10. *xhs.namespaces* Functions and variables exist in separate namespaces.
    - *likeshell* 17 above
    - *unquote* 24 above
    - *xhs.stackscope* 6
    - *xhs.runtimereceiver* 9
  11. *xhs.fnliterals* Function literals are self-invoking when used as messages. (*xhs.namespaces* 10)
  12. *nocallcc* Continuations are simulated in terms of lazy evaluation, but are never first-class.
    - *dynamiccompiler* 44 above
    - *introspectlazy* 35 above
    - *abstract* 36 above
    - *xhs.runtimereceiver* 9
  13. *xhs.transientdefs* Some definitions are "transient," in which case they are used to resolve blocked lazy values but then may be discarded at any point.
    - *distributed* 3 above
    - *no-oom* 19 above
    - *lazy* 33 above
    - *xhs.runtimereceiver* 9
  14. *xhs.globaldefs* Global definitions can apply to values at any time, and to values on different machines (i.e. their existence is broadcast).
    - *lazy* 33 above
    - *xhs.transientdefs* 13



15. *xhs.nomacros* Syntactic macros cannot exist because invocation commutes with expansion, but functions may operate on terms whose values are undefined.
  - *xhs.eval-identities* 1
  - *xhs.unquote-structure* 5
16. *xhs.noerrors* Errors cannot exist, but are represented by lazy values that contain undefined quantities that will never be realized. These undefined quantities are the unevaluated backtraces to the error-causing subexpressions.
  - *nodebug* 11 above
  - *lazy* 33 above
  - *abstract* 36 above
  - *xhs.eval-identities* 1
17. *xhs.destructuring* Any value can be used as a destructuring bind pattern.
  - *initial assumption*
  - *xhs.relational* 2
18. *xhs.ambdestructure* (*amb*) can be used to destructure values, and it behaves as a disjunction.
  - *initial assumption*
  - *xhs.relational* 2
  - *xhs.destructuring* 17
19. *xhs.dof* Degrees of freedom within an inversion are represented by abstract values that will prevent the result from being realized. They are visible as unknowns within the quoted form.
  - *initial assumption*
  - *xhs.relational* 2
20. *xhs.se-axioms* Side effects and axioms are the same thing in xh. Once it commits to a side-effect, it must always assume that it happened (since it did). In particular, this means that imperative forms like (*def*) are actually ways to assume new ground truths.
  - *initial assumption*
  - *imperative* 18
  - *xhs.relational* 2
  - *xhs.globaldefs* 14

21. *xhs.virtualization* Every side effect can be replaced by a temporary assumption that models the effect. If you do this, you're replacing an axiom with a hypothesis.
- *initial assumption*
  - *xhs.se-axioms 20*

## Chapter 3

# xh-script syntax

Design constraints for the syntax in particular.

1. *syn.reversibleparsing* The parser for xh is losslessly reversible: comment data, whitespace, and any other aspect of valid xh code is encoded in the parsed representation. (*initial assumption*)
2. *syn.tags* Lists, vectors, and maps can each be tagged by immediately prefixing the opening brace with a word. (*initial assumption*)
  - *initial assumption*
  - *realprog 1*
  - *ergonomic 5*
3. *syn.splice* A quoted form prefixed with @ causes list splicing to occur, just like Common Lisp's ,@ and Clojure's ~@. Technically @ is a distributive, right-associative prefix expansion operator (sort of like \$ in some ways), so you can layer it to expand multiple layers of lists. Any non-lists are treated as lists of a single item; @ will never block evaluation.
  - *initial assumption*
  - *likeshell 17*
4. *syn.escaping* Any character can be prefixed with \ to cause it to be interpreted as a string. The only exception is that some escape sequences are interpreted, including \n, \t, and similar.
  - *initial assumption*
  - *likeshell 17*
5. *syn.hashcomments* Comments begin with # preceded either by whitespace or the beginning of a line. Unlike in many languages, comment data is available in the parsed representation of xh source code.
  - *likeshell 17*
  - *syn.reversibleparsing 1*

6. *syn.stringquoting* Single-quoted and double-quoted strings have exactly the semantics they do in Perl or bash; that is, single-quoted strings are oblivious to most unquoting features, whereas double-quoted strings are interpolated. (*likeshell 17*)
7. *syn.stringexpressions* Within a double-quoted string, you need to prefix any interpolating () group with a \$ to make it active.
  - *nodebug 11*
  - *likeshell 17*
8. *syn.toplevelexpressions* Outside words and quoted strings, () does not require a \$ prefix to interpolate. Put differently, the \$ is required if and only if you are interpolating by same-word string concatenation.
  - *realprog 1*
  - *ergonomic 5*
9. *syn.flattoplevel* xh's toplevel grammar is based on Tcl, not Lisp; this means that you don't need to wrap each statement in parentheses. Line breaks are significant unless preceded with \ or inside a list. Unlike bash and tcl, all sub-lists are parsed as in Lisp; that is, this toplevel syntax applies only at the outermost level.
  - *initial assumption*
  - *likeshell 17*
  - *ergonomic 5*

# Chapter 4

## runtime

xh-script operates within a hosting environment that manages things like memory allocation and thread/evaluation scheduling. Beyond this, we also need a quoted-value format that's more efficient than doing a bunch of string manipulation (*xhr.representation* 6, *xhr.flatcontainers* 7, *xhr.deduplication* 9).

1. *xhr.priorityqueue* Evaluation always happens as a process of pulling expressions from a priority queue.
  - *initial assumption*
  - *xhs.relational* 2
  - *xhs.bestfirst* 3
2. *xhr.prioritytracing* Every expression in the queue knows its “origin” for scheduling purposes.
  - *xhs.bestfirst* 3
  - *xhr.priorityqueue* 1
3. *xhr.staticinline* Function compositions should be added as derived definitions to minimize the number of symbol-table lookups per unit rewriting distance.
  - *initial assumption*
  - *notslow* 9
  - *xhs.relational* 2
4. *xhr.latency* The runtime should provide low enough latency that it can be used as the graph-solving backend for RPC routing.
  - *initial assumption*
  - *notslow* 9
  - *routing* 64

5. *xhr.valuecache* To guarantee low latency, the runtime should emit transient values for solutions it finds. These become cached bindings that can be kicked out under memory pressure, but reduce the load on the optimizer.
  - *initial assumption*
  - *notslow 9*
  - *xhr.latency 4*
6. *xhr.representation* Every quasiquoted form with variant pieces should be represented as a separate instantiable class.
  - *initial assumption*
  - *quasiquote 23*
  - *notslow 9*
  - *xhs.eval-identities 1*
7. *xhr.flatcontainers* Quasiquoted structures are profiled for the distributions of their children (upon expansion); for strongly nonuniform distributions, specialized flattened container types are generated.
  - *initial assumption*
  - *quasiquote 23*
  - *notslow 9*
  - *xhs.eval-identities 1*
  - *xhr.staticinline 3*
  - *xhr.representation 6*
8. *xhr.flatlimit* Containers should be flattened until the type-encoding overhead is minimized for the given (possibly-contextful) distribution of values. In practice, this probably means using PPM and Huffman coding with an initial noise floor to prevent short-run overfitting.
  - *initial assumption*
  - *notslow 9*
  - *xhr.flatcontainers 7*
9. *xhr.deduplication* Every independent value within a quasiquoted form should be referred to by a structural signature, in our case SHA-256. This trivially causes strings, and by extension execution paths, to be deduplicated. Because we assume no hash collisions, xh string values have no defined instance affinity (apropos of *refaffinity 50*).
  - *heap 46*
  - *xhr.staticinline 3*

- *xhr.representation* 6
  - *xhr.hinting* 11
10. *xhr.pointerentropy* 256 bits is sufficient to encode any pointer.
- *initial assumption*
  - *uniqueid* 51
  - *refaffinity* 50
  - *xhr.deduplication* 9
11. *xhr.hinting* Expressions should be hinted with tags that track and influence their paths through the search space. The optimizer uses machine learning against these tags to predict successful search strategies.
- *initial assumption*
  - *notslow* 9
  - *xhs.bestfirst* 3
  - *xhs.nocut* 4
12. *xhr.hashing* The runtime should use some type of masked hashing strategy (or other decision tree) to minimize the expected resolution time for each expression.
- *initial assumption*
  - *xhr.hinting* 11
13. *xhr.transientprediction* Many functions will end up returning lazy values, and most of the time those lazy values will eventually be realized. The runtime should have some expectation of which lazy sub-values will be realized, and with what probability; this influences its search strategy in the future.
- *initial assumption*
  - *notslow* 9
  - *xhs.transientdefs* 13
  - *xhs.bestfirst* 3
  - *xhr.hinting* 11
14. *xhr.override* The user must be able to completely override any strategy preferences the runtime has. The runtime can be arbitrarily wrong and the user can be arbitrarily right.
- *initial assumption*
  - *xhs.bestfirst* 3
  - *xhr.hinting* 11

- *xhr.transientprediction* 13
15. *xhr.externalstrategy* The xh runtime does not itself define the evaluation strategy, nor does it internally observe things; this is done as part of the evaluation functions in the standard library. The only thing the xh runtime provides is a scheduled/prioritized event loop.
    - *initial assumption*
    - *abstract* 36
    - *code=data* 37
    - *xhr.override* 14
  16. *xhr.evaluatorapi* Evaluator functions are straightforward to write, and the standard library includes several designed for different use cases (e.g. local, distributed, profiling). Any significantly nontrivial aspect of it is factored off into an API.
    - *initial assumption*
    - *xhr.override* 14
    - *xhr.externalstrategy* 15
  17. *xhr.evaluatorbase* The runtime is itself subject to evaluation (since it's self-hosting), and the base evaluator is implemented in Perl, C, or Javascript. This base evaluator runs locally; the distributed evaluator runs on top of it.
    - *initial assumption*
    - *xh2perl* 41
    - *xh2c* 40
    - *xh2js* 42
    - *inperl* 56
    - *selfhost* 43
    - *xhr.override* 14
    - *xhr.evaluatorapi* 16
  18. *xhr.cryptographic* Any function can be modeled as a cipher and subject to forms of cryptanalysis to discover structure. The worst case is a truly random mapping that requires each permutation to be evaluated independently. (This is relevant for code synthesis, which is an inversion of the evaluator.)
    - *initial assumption*
    - *xhs.relational* 2



19. *xhr.uniformityreduction* Entropy can be reduced by biasing otherwise uniform distributions of (amb) alternatives, possibly by looking at context. This can be done using real-world data, if any exists. (*xhr.cryptographic* 18)
20. *xhr.separability* Entropy can be reduced by identifying input separability or other such structure. This is done through cryptanalysis. (*xhr.cryptographic* 18)

# **Part II**

## **base implementation**

# Chapter 5

## self-replication

Listing 5.1 boot/xh-header

```
1  #!/usr/bin/env perl
2  #<body style='display:none'><script id='self' type='xh'>
3  BEGIN {eval(our $xh_bootstrap = q{
4  # xh | https://github.com/spencertipping/xh
5  # Copyright (C) 2014, Spencer Tipping
6  # Licensed under the terms of the MIT source code license
7  use 5.014;
8  package xh;
9  our %modules;
10 our @module_ordering;
11 our %eval_numbers = (1 => '$xh_bootstrap');
12
13 sub with_eval_rewriting(&) {
14     my @result = eval {$_[0]->(@_[1..$_#])};
15     die $@ =~ s/\(eval (\d+)\)/$eval_numbers{$1}/egr if $@;
16     @result;
17 }
18
19 sub named_eval {
20     my ($name, $code) = @_;
21     $eval_numbers{$1 + 1} = $name if eval('__FILE__') =~ /\(eval (\d+)\)/;
22     with_eval_rewriting {eval $code; die $@ if $@};
23 }
24
25 our %compilers = (
26     pl => sub {
27         my $package = $_[0] =~ s/\./::/gr;
28         eval {named_eval $_[0], "{package ::$package;\n$_[1]\n}";
29         die "error compiling module $_[0]: $@" if $@;
```

```

30 },
31 html => sub {});
32
33 sub defmodule {
34     my ($name, $code, @args) = @_;
35     chomp($modules{$name} = $code);
36     push @module_ordering, $name;
37     my ($base, $extension) = split /\.(\\w+$)/, $name;
38     die "undefined module extension '$extension' for $name"
39         unless exists $compilers{$extension};
40     $compilers{$extension}->($base, $code, @args);
41 }
42
43 chomp($modules{bootstrap} = $::xh_bootstrap);
44 undef $::xh_bootstrap;

```

At this point we need a way to reproduce the image. Since the bootstrap code is already stored, we can just wrap it and each defined module into an appropriate BEGIN block.

**Listing 5.2** boot/xh-header (continued)

```

1 sub serialize_module {
2     my ($module) = @_;
3     my $contents = $modules{$module};
4     my $terminator = '_';
5     $terminator .= '_' while $contents =~ /^$terminator$/m;
6     join "\n", "BEGIN {xh::defmodule('$module', <<'$_')}",
7         $contents,
8         $terminator;
9 }
10
11 sub image {
12     join "\n", "#!/usr/bin/env perl",
13         "<body style='display:none'><script type='xh'>",
14         "BEGIN {eval(our \$xh_bootstrap = <<'$_')}",
15         $modules{bootstrap},
16         '_',
17         map(serialize_module($_), grep !/\.html$/, @module_ordering),
18         "</" . "script>",
19         map(serialize_module($_), grep /\.html$/, @module_ordering),
20         "xh::main::main;\n__DATA__";
21 }
22 }}

```

Here's a quick test implementation of `xh::main::main`; its purpose is to make sure replication works. This won't be present in real images:

**Listing 5.3** src/test/main.pl

```
1 BEGIN {xh::defmodule('xh::main.pl', <<'_' )}
2 sub main {
3     print ::xh::image;
4 }
5 -
```

## Chapter 6

# html introspection

xh images can be opened as self-inspecting HTML files. This strategy of embedding xh module definitions in comments isn't very elegant, but it makes the Javascript parser easier to write. (A better system would be to have the Javascript parse everything in a single `<script>` tag, then build all of the HTML that way; but due to browser security restrictions, this would break local viewing.)

**Listing 6.1** src/introspect/dependencies.html

```
1 BEGIN {xh::defmodule('js-dependencies.html', <<'_')}  
2 <script>  
3 -- include deps/jquery.min.js  
4 -- include deps/caterwaul.min.js  
5 -- include deps/caterwaul.std.min.js  
6 -- include deps/caterwaul.ui.min.js  
7 </script>  
8 -
```

**Listing 6.2** src/introspect/css.html

```
1 BEGIN {xh::defmodule('css.html', <<'_')}  
2 <style>  
3 /*BEGIN {xh::defmodule('introspection.css', <<'_')}*/  
4 @import url(http://fonts.googleapis.com/css?family=Abel|Fira+Mono);  
5 body {background: #080808;  
6     color: #eae8e4;  
7     margin: auto;  
8     max-width: 600px;  
9     overflow-y: scroll;  
10    padding-left: 14px;  
11    border-left: solid 1px #383736}  
12
```

```

13 h1 {font-family: 'Abel', monospace;
14     font-weight: normal;
15     font-size: 20px;
16     color: #878177;
17     margin: 0}
18
19 h1:hover, h1.active {color: #eae8e4}
20 h1 .suffix {color: #878177}
21 h1 .suffix:before {content: '.'; color: #878177}
22
23 pre {font-family: 'Fira Mono', monospace;
24     font-size: 10px}
25
26 .module {border-top: solid 1px #383736;
27     overflow: hidden}
28 .module pre {margin: 0}
29
30 #dom {margin: 20px 0}
31 #dom a {font-family: 'Abel', sans-serif;
32     text-decoration: none;
33     color: #878177}
34 #dom a:hover {color: #eae8e4}
35 .title {color: #f89421}
36 /*_*/
37 </style>
38 -

```

**Listing 6.3** src/introspect/dom.html

```

1 BEGIN {xh::defmodule('dom.html', <<'_'>)}
2 <div id='dom'>
3 <a href='https://github.com/spencertipping/xh'>
4   github.com/spencertipping/<span class='title'>xh</span></a>
5 </div>
6 -

```

**Listing 6.4** src/introspect/js.html

```

1 BEGIN {xh::defmodule('introspection.html', <<'_'>)}
2 <script>
3 /*BEGIN {xh::defmodule('introspection.js', <<'_'>)}*/
4 $(caterwaul(':all'))(function () {
5   $.fn.toggle_vertically(v) = $(this).each(toggle)
6   -where [toggle(t = $(this).stop()) =
7     cs /~animate/ {top: v ? 0 : -h}
8     -then- t /~animate/ {height: v ? h : 0, opacity: +v}
9     -where [cs = t.children().stop() /~css/ {position: 'relative'},

```

```

10         h = cs.first().height()]],
11
12     $('body').empty() /~prepend/ jquery[head /append(css)]
13         /~append/ dom
14         /~append/ ui_for(parsed_modules)
15         /~css/ {display: 'block'},
16     where [
17         css = $('style'),
18         dom = $('#dom'),
19         self = +$('script, style') *[$(x).html()] /seq /~join/ '\n',
20         parse_modules(ls) = xs -se [ls *!process_line -seq] -where [
21             xs = {__ordering: []},
22             name = null,
23             text = '',
24             process_line(s) = /^(?:\/*)?BEGIN.*defmodule\('([^\']+)'/ .exec(s)
25                 -re [it ? name /eq[it[1]] -then- text /eq['']]
26                 : /^(?:\/*)?_+(?:\/*\/*)?$/ .test(s)
27                 ? name -ocq- 'bootstrap.pl'
28                 -then- xs[name] /eq [text /~substr/ 1]
29                 -then- xs.__ordering /~push/ name
30                 : text += '\n#{s}']],
31
32         parsed_modules = self.split(/\n/) /!parse_modules,
33         ui_for(modules) = ui -se [sections *!ui /~append/ x] -seq] -where [
34             ui = jquery in div.modules,
35             toggle() = $(this).toggleClass('active').next().stop()
36                 /~toggle_vertically/ $(this).hasClass('active'),
37             module_name(x) = jquery [span.prefix /text(pieces[0])
38                 + span.suffix /text(pieces[1])]
39                 -where [pieces = x.split(/\./, 2)],
40             sections = seq in
41                 modules.__ordering
42                 *[jquery in h1 /append(x /!module_name)
43                     /css({cursor: 'pointer'})
44                     /click(toggle)
45                     + div.module(pre /text(modules[x]))
46                     /toggle_vertically(false)]]]]));
47     /*_*/
48 </script>
49 -

```



**Part III**

**self-hosting implementation**

## Chapter 7

# computational abstraction

1. *ca.structured* All compilation is run through a structured programming layer that has abstractions for numeric operations and basic control flow. Shortcuts for higher-level operations are provided to leverage platform-specific optimized libraries.
  - *initial assumption*
  - *xh2c* 40
  - *xh2perl* 41
  - *xh2js* 42
2. *ca.varwidthint* Integer operations have signed and unsigned variants, and exist at any bit width. *xh* doesn't restrict to 32/64 bits (or other common values) because not all backends, e.g. Perl and Javascript, support all bit widths natively.
  - *initial assumption*
  - *inperl* 56
3. *ca.float* Floating-point operations are defined for 32-bit and 64-bit floats. These are present on every sane platform. (*initial assumption*)
4. *ca.flatmemory* We can't assume that the underlying backend provides any data structures for us; we just address memory as a flat bunch of bytes. It's necessary to do this because we implement our own memory paging.
  - *notslow* 9
  - *no-oom* 19
5. *ca.harvard* Data memory is separate from instructions; this abstraction has no homoiconicity at all. It's ok to do this here because all code at this level is backend-specific and machine generated. The only exception to this is that you can refer to function pointers, but they're assumed to be untyped and opaque.

- *initial assumption*
  - *xh2c* 40
  - *xh2perl* 41
  - *xh2js* 42
  - *ca.flatmemory* 4
6. *ca.usergc* All garbage collectors are implemented in xh-script and compiled into the flat memory model.
- *initial assumption*
  - *realprog* 1
  - *imperative* 18
  - *xh2c* 40
  - *xh2perl* 41
  - *xh2js* 42
  - *ca.flatmemory* 4
  - *ca.harvard* 5
7. *ca.lazygc* Garbage collectors are lazy, since the heap is useful as a cache and is swapped to disk.
- *no-oom* 19
  - *xhs.relational* 2
  - *xhs.bestfirst* 3
  - *xhs.transientdefs* 13
  - *xhs.globaldefs* 14
  - *ca.flatmemory* 4
8. *ca.gclocality* GC is a strictly local process; all values sent over RPCs are quoted. The only exception is for mutable resources, which can be referred to remotely by acquiring a unique reference to it. When those references are no longer referred to, the remote instance notifies the owner. If the remote instance drops offline, any references it holds are invalidated.
- *distributed* 3
  - *unreliable* 10
  - *remotestuff* 21
  - *printstruct* 27
  - *immutable* 28
  - *stateown* 31
  - *ca.usergc* 6

9. *ca.userprofiling* Profiling is implemented as an xh-script library and is compiled into each backend automatically.
  - *initial assumption*
  - *xh2c* 40
  - *xh2perl* 41
  - *xh2js* 42
  - *notslow* 9
  - *xhs.relational* 2
10. *ca.compiledinstances* Every image compiled into a backend becomes a connected xh instance with an independently-managed heap, symbol table, etc. Communication is done via the usual RPC protocol.
  - *initial assumption*
  - *notslow* 9