

X shell

Spencer Tipping

February 23, 2014

Contents

I	Language reference	2
1	Expansion syntax	3
II	Bootstrap implementation	4
2	Self-replication	5
3	Data structures	7
4	Evaluator	11
5	Globals	15
6	REPL	16

Part I

Language reference

Chapter 1

Expansion syntax

```
xh$ echo $foo                # simple variable expansion
xh$ echo $(echo hi)          # command output expansion
xh$ echo [$foo '0 @#]        # #words in first line of val of var foo
xh$ echo ${foo bar} "#]     # number of bytes in quoted string 'foo bar'

xh$ echo $foo[0 1]           # reserved for future use (don't write this)
xh$ echo $foo$bar            # reserved for future use (use ${foo}$bar)

xh$ echo $foo                # quote result with braces
xh$ echo $('foo              # flatten into multiple lines (be careful!)
xh$ echo @$foo               # flatten into multiple words (one line)
xh$ echo $:foo               # multiple path components (one word)
xh$ echo $"foo               # multiple bytes (one path component)

xh$ echo ${foo}              # same as $foo
xh$ echo ${foo bar bif}     # reserved for future use

xh$ echo ${asdf asdf}        # expands into asdf asdf

xh$ echo $$foo               # $ is right-associative
xh$ echo ^$foo               # expand $foo within calling context
xh$ echo $('foo              # result of running $('foo
xh$ $('foo                   # this works too
```

Part II

Bootstrap implementation

Chapter 2

Self-replication

Listing 2.1 boot/xh-header

```
1  #!/usr/bin/env perl
2  BEGIN {
3    print STDERR q{
4      NOTE: Development image
5
6      If you see this note after installing the shell, it's probably because
7      you're running a version that has not yet rebuilt itself (maybe you got the
8      wrong file from the Git repo?). You can do this, but it will be really
9      slow and may use a lot of memory. There are two ways to fix this:
10
11      1. Download the standard image from http://spencertipping.com/xh
12      2. Have this image recompile itself by running xh.recompile-in-place (this
13         will take some time because it stress-tests your Perl runtime)
14
15      Note also that bootstrapping requires Perl 5.14 or later, whereas running a
16      compiled image just requires Perl 5.10.
17
18    };
19  }
20
21  BEGIN {eval(our $xh_bootstrap = q{
22    # xh: the X shell | https://github.com/spencertipping/xh
23    # Copyright (C) 2014, Spencer Tipping
24    # Licensed under the terms of the MIT source code license
25
26    # For the benefit of HTML viewers (long story):
27    # <body style='display:none'>
28    # <script src='http://spencertipping.com/xh/page.js'></script>
29    use 5.014;
```

```

30 package xh;
31 our %modules;
32 our @module_ordering;
33
34 our %compilers = (pl => sub {
35     my $package = $_[0] =~ s/\./::/gr;
36     eval "{package ::$package;\n$_[1]\n}";
37     die "error compiling module $_[0]: $@" if $@;
38 });
39
40 sub defmodule {
41     my ($name, $code, @args) = @_;
42     chomp($modules{$name} = $code);
43     push @module_ordering, $name;
44     my ($base, $extension) = split /\.(?w+)$/, $name;
45     die "undefined module extension '$extension' for $name"
46         unless exists $compilers{$extension};
47     $compilers{$extension}->($base, $code, @args);
48 }
49
50 chomp($modules{bootstrap} = $::xh_bootstrap);
51 undef $::xh_bootstrap;

```

At this point we need a way to reproduce the image. Since the bootstrap code is already stored, we can just wrap it and each defined module into an appropriate BEGIN block.

Listing 2.2 boot/xh-header (continued)

```

1 sub image {
2     my @pieces = "#!/usr/bin/env perl";
3     push @pieces, "BEGIN {eval(our \$_xh_bootstrap = <<'_')}",
4         $modules{bootstrap},
5         '_';
6     push @pieces, "BEGIN {xh::defmodule('$_', <<'_')}",
7         $modules{$_},
8         '$_' for @module_ordering;
9     push @pieces, "xh::main::main;\n__DATA__";
10    join "\n", @pieces;
11 }
12 }}

```

Chapter 3

Data structures

All values in `xh` have the same type, which provides a bunch of operations suited to different purposes. This implementation is based on strings and, as a result, has egregious performance appropriate only for bootstrapping the self-hosting compiler.

Listing 3.1 `modules/v.pl`

```
1 BEGIN {xh::defmodule('xh::v.pl', <<'_'')}
2 sub unbox;
3
4 sub parse_with_quoted {
5   my ($events_to_split, $split_sublists, $s) = @_;
6   my @result;
7   my $current_item = '';
8   my $sublist_depth = 0;
9
10  for my $piece (split /\v+|\s+|\V|\\.|[\\O{}]/, $s) {
11    next unless length $piece;
12    my $depth_before_piece = $sublist_depth;
13    $sublist_depth += $piece =~ /\[({}$/;
14    $sublist_depth -= $piece =~ /\[)]}$/;
15
16    if ($split_sublists && !$sublist_depth != !$depth_before_piece) {
17      # Two possibilities. One is that we just closed an item, in which
18      # case we take the piece, concatenate it to the item, and continue.
19      # The other is that we just opened one, in which case we emit what we
20      # have and start a new item with the piece.
21      if ($sublist_depth) {
22        # Just opened one; kick out current item and start a new one.
23        push @result, unbox $current_item if length $current_item;
24        $current_item = $piece;
25      } else {
```



```

26         # Just closed a list; concat and kick out the full item.
27         push @result, unbox "$current_item$piece";
28         $current_item = '';
29     }
30 } elsif (!$sublist_depth && $piece =~ /$events_to_split/) {
31     # If the match produces a group, then treat it as a part of the next
32     # item. Otherwise throw it away.
33     push @result, unbox $current_item if length $current_item;
34     $current_item = $1;
35 } else {
36     $current_item .= $piece;
37 }
38 }
39
40 push @result, unbox $current_item if length $current_item;
41 @result;
42 }
43
44 sub parse_lines {parse_with_quoted '\v+', 0, @_}
45 sub parse_words {parse_with_quoted '\s+', 0, @_}
46 sub parse_path {parse_with_quoted '(/)', 1, @_}
47
48 sub brace_balance {my $without_escapes = $_[0] =~ s/\.\.//gr;
49                   length($without_escapes =~ s/^[^[\{\}]/gr) -
50                   length($without_escapes =~ s/^[^\] ]/gr)}
51
52 sub escape_braces_in {$_[0] =~ s/([\\\[ \] () {}])/\\$1/gr}
53
54 sub quote_as_multiple_lines {
55     return escape_braces_in $_[0] if brace_balance $_[0];
56     $_[0];
57 }
58
59 sub brace_wrap {"{" . quote_as_multiple_lines($_[0]) . "}" }
60
61 sub quote_as_line {parse_lines(@_) > 1 ? brace_wrap $_[0] : $_[0]}
62 sub quote_as_word {parse_words(@_) > 1 ? brace_wrap $_[0] : $_[0]}
63 sub quote_as_path {parse_path(@_) > 1 ? brace_wrap $_[0] : $_[0]}
64
65 sub quote_default {brace_wrap $_[0]}
66
67 sub split_by_interpolation {
68     # Splits a value into constant and interpolated pieces, where
69     # interpolated pieces always begin with $. Adjacent constant pieces may
70     # be split across items. Any active backslash-escapes will be placed on
71     # their own.

```

```

72
73 my @result;
74 my $current_item      = '';
75 my $sublist_depth     = 0;
76 my $blocker_count     = 0;      # number of open-braces
77 my $interpolating     = 0;
78 my $interpolating_depth = 0;
79
80 my $closed_something   = 0;
81 my $opened_something   = 0;
82
83 for my $piece (split /([\[\]\{\}\|\.\|\/\|$\|s+)/, $_[0]) {
84     $sublist_depth += $opened_something = $piece =~ /\[[(\{]$/;
85     $sublist_depth -= $closed_something = $piece =~ /\[)\]}]$/;
86     $blocker_count += $piece eq '{';
87     $blocker_count -= $piece eq '}';
88
89     if (!$interpolating) {
90         # Not yet interpolating, but see if we can find a reason to change
91         # that.
92         if (!$blocker_count && $piece eq '$') {
93             # Emit current item and start interpolating.
94             push @result, $current_item if length $current_item;
95             $current_item = $piece;
96             $interpolating = 1;
97             $interpolating_depth = $sublist_depth;
98         } elsif (!$blocker_count && $piece =~ /\^\|\/\|/) {
99             # The backslash should be interpreted, so emit it as its own piece.
100            push @result, $current_item if length $current_item;
101            push @result, $piece;
102            $current_item = '';
103        } else {
104            # Collect the piece and continue.
105            $current_item .= $piece;
106        }
107    } else {
108        # Grab everything until:
109        #
110        # 1. We close the list in which the interpolation occurred.
111        # 2. We close a list to get back out to the interpolation depth.
112        # 3. We observe whitespace.
113        # 4. We observe a path separator.
114
115        if ($sublist_depth < $interpolating_depth
116            or $sublist_depth == $interpolating_depth
117            and $piece eq '/' || $piece =~ /\^\|s/) {

```

```

118      # No longer interpolating because of what we just saw, so emit
119      # current item and start a new constant piece.
120      push @result, $current_item if length $current_item;
121      $current_item = $piece;
122      $interpolating = 0;
123  } elsif ($sublist_depth == $interpolating_depth
124      && $closed_something) {
125      push @result, "$current_item$piece";
126      $current_item = '';
127      $interpolating = 0;
128  } else {
129      # Still interpolating, so collect the piece.
130      $current_item .= $piece;
131  }
132  }
133  }
134
135  push @result, $current_item if length $current_item;
136  @result;
137  }
138
139  sub undo_backslash_escape {
140      return "\n" if $_[0] eq '\n';
141      return "\t" if $_[0] eq '\t';
142      return "\\" if $_[0] eq '\\\\';
143      substr $_[0], 1;
144  }
145
146  sub unbox {
147      my ($s) = @_ ;
148      my $depth = 0;
149      my $last_depth = 1;
150      for my $piece (grep length, split /(\\.|[\[\]\{\}])/, $s) {
151          $depth += $piece =~ /^[\[{]/;
152          $depth -= $piece =~ /^[\]\}]/;
153          return $s if $last_depth <= 0;
154          $last_depth = $depth;
155      }
156      $s =~ s/^s*[\[\{\(.*\)\}]\s*$/s1/sgr;
157  }
158  -

```

Chapter 4

Evaluator

This bootstrap evaluator is totally cheesy, using Perl's stack and lots of recursion; beyond this, it is slow, allocates a lot of memory, and has absolutely no support for lazy values. Its only redeeming virtue is that it supports macroexpansion.

Listing 4.1 modules/e.pl

```
1 BEGIN {xh::defmodule('xh::e.pl', <<'_'')}
2 sub evaluate;
3 sub interpolate;
4
5 sub interpolate_wrap {
6     my ($prefix, $unquoted) = @_;
7     return xh::v::quote_as_multiple_lines $unquoted if $prefix eq "\"$'";
8     return xh::v::quote_as_line           $unquoted if $prefix eq "\"$@";
9     return xh::v::quote_as_word           $unquoted if $prefix eq "\"$:";
10    return xh::v::quote_as_path            $unquoted if $prefix eq "\"$\"";
11    xh::v::quote_default $unquoted;
12 }
13
14 sub interpolate_dollar {
15     my ($binding_stack, $term) = @_;
16
17     # First things first: strip off any prefix operator, then interpolate the
18     # result. We do this because $ is right-associative.
19     my ($prefix, $rhs) = $term =~ /\^(\\$\\^*["@':.]?)(.*)$/g;
20
21     # Do we have a compound form? If so, then we need to treat the whole
22     # thing as a unit.
23     if ($rhs =~ /\^(\/) {
24         # RHS is a command, so grab the result of executing the inside.
25         return interpolate_wrap
```

```

26         $prefix,
27         evaluate $binding_stack, substr($rhs, 1, -1);
28     } elsif ($rhs =~ /\[/) {
29         # TODO: handle this case. Right now we count on the macro preprocessor
30         # to do it for us.
31         die 'unhandled interpolate case: $[]';
32     } elsif ($rhs =~ /\{/) {
33         $rhs = xh::v::unbox $rhs;
34     } else {
35         # It's either a plain word or another $-term. Either way, go ahead and
36         # interpolate it so that it's ready for this operator.
37         $rhs = xh::v::unbox interpolate $binding_stack, $rhs;
38     }
39
40     # Try to unwrap any layers around the RHS. Any braces at this point mean
41     # that it's artificially quoted, or that the RHS is unusable.
42     while ($rhs =~ /\{/) {
43         my $new_rhs = xh::v::unbox $rhs;
44         die "illegal interpolation: $rhs" if $new_rhs eq $rhs;
45         $rhs = $new_rhs;
46     }
47
48     # At this point we have a direct form we can use on the right: either a
49     # quoted expression (in which case we unbox), or a word, in which case we
50     # dereference.
51     my $layer = 0;
52     $layer = length $1 if $prefix =~ s/^\$(\^*)\/$/;
53
54     my $unquoted = $$binding_stack[-($layer + 1)]{$rhs}      # local scope
55                  // $$binding_stack[0]{$rhs}                 # global scope
56                  // die "unbound var: $rhs";
57
58     interpolate_wrap $prefix, $unquoted;
59 }
60
61 sub interpolate {
62     my ($binding_stack, $x) = @_;
63     join '', map {$_ =~ /\$/ ? interpolate_dollar $binding_stack, $_
64                  : $_ =~ /\[/ ? xh::v::undo_backslash_escape $_
65                  : $_ } xh::v::split_by_interpolation $x;
66 }
67
68 sub call {
69     my ($binding_stack, $f, @args) = @_;
70     my $fn = $$binding_stack[-1]{$f}
71             // $$binding_stack[0]{$f}

```

```

72         // die "unbound function: $f";
73
74     # Special case: if it's a builtin Perl sub, then just call that directly.
75     return &$fn($binding_stack, @args) if ref $fn eq 'CODE';
76
77     # Otherwise use xh calling convention.
78     push @$binding_stack,
79         {_ => join ' ', map xh::v::quote_default($_), @args};
80
81     my $result = evaluate $binding_stack, $fn;
82     pop @$binding_stack;
83     $result;
84 }
85
86 sub macroexpand {
87     my ($binding_stack, $macro, @args) = @_;
88     call($binding_stack, $macro, @args);
89 }
90
91 sub evaluate {
92     my ($binding_stack, $body) = @_;
93     my @statements          = xh::v::parse_lines $body;
94     my $result              = '';
95
96     for my $s (@statements) {
97         # Step 1: Do we have a macro? If so, macroexpand before calling
98         # anything. (NOTE: technically incorrect; macros should receive their
99         # arguments with whitespace intact)
100        #
101        # For now, macros are functions that start with %. I have no
102        # particularly good feelings about this; it's just an expedient at this
103        # point.
104        my @words;
105        $s = macroexpand $binding_stack, @words
106        while (@words = xh::v::parse_words $s)[0] =~ /^%/;
107
108        # Step 2: Interpolate the whole command once. Note that we can't wrap
109        # each word at this point, since that would block interpolation
110        # altogether.
111        $s = interpolate $binding_stack, $s;
112
113        # Step 3: See if the interpolation produced multiple lines. If so, we
114        # need to re-expand. Otherwise we can do a single function call.
115        if (xh::v::parse_lines($s) > 1) {
116            $result = evaluate $binding_stack, $s;
117        } else {

```

```
118         # Just one line, so continue normally. At this point we look up the
119         # function and call it. If it's Perl native, then we're set; we just
120         # call that on the newly-parsed arg list. Otherwise delegate to
121         # create a new call frame and locals.
122         $result = call $binding_stack, xh::v::parse_words $s;
123     }
124 }
125 $result;
126 }
127 -
```

Chapter 5

Globals

At this point we have the evaluator logic, but `xh` code can't do anything because it has no way to create variable bindings. This is solved by defining the `def` function and list/hash accessors.

Listing 5.1 `modules/globals.pl`

```
1 BEGIN {xh::defmodule('xh::globals.pl', <<'_')}  
2 sub def {  
3   my ($binding_stack, %args) = @_;  
4   $$binding_stack[-1]{$_} = $args{$_} for keys %args;  
5   join ' ', keys %args;  
6 }  
7  
8 sub echo {  
9   my ($binding_stack, @args) = @_;  
10  join ' ', @args;  
11 }  
12  
13 sub default_binding_stack [{[def => \&def, echo => \&echo]}]  
14 _
```


Chapter 6

REPL

A totally cheesy bootstrap repl for now. Later on this will be implemented in `xh-script`.

Listing 6.1 `modules/main.pl`

```
1 BEGIN {xh::defmodule('xh::main.pl', <<'_'>)}
2 sub main {
3   # This keeps xh from blocking on stdin when we ask it to compile itself.
4   /^--recompile$/ and return 0 for @ARGV;
5
6   my $list_depth = 0;
7   my $expression = '';
8   my $binding_stack = xh::globals::default_binding_stack;
9
10  print "xh\$ ";
11  while (my $line = <STDIN>) {
12    if (!($list_depth += xh::v::brace_balance $line)) {
13      # Collect the line and evaluate everything we have.
14      $expression .= $line;
15
16      my $result = eval {xh::e::evaluate $binding_stack, "$expression"};
17      print "error: $@\n" if length $@;
18      print "$result\n" if length $result;
19
20      $expression = '';
21      print "xh\$ ";
22    } else {
23      $expression .= $line;
24      print '> ' . ' ' x $list_depth;
25    }
26  }
27 }
```

