

```

module HuttonChap17 where
open import Haskell.Prelude
open import Haskell.Law.Equality using (sym; begin_;  $\equiv$ {_}_; step- $\equiv$ ;  $\dashv$ ; cong)

```

## 1. SYNTAX AND SEMANTICS

```

module SyntaxAndSemantics where
  data Expr : Set where
    Val : Int → Expr
    Add : Expr → Expr → Expr
  {-# COMPILE AGDA2HS Expr #-}

  eval : Expr → Int
  eval (Val n) = n
  eval (Add e1 ex) = eval e1 + eval ex
  {-# COMPILE AGDA2HS eval #-}

```

## 2. ADDING A STACK

```

module AddingAStack where
  open SyntaxAndSemantics
  Stack = List Int
  {-# COMPILE AGDA2HS Stack #-}

  push : Int → Stack → Stack
  push n s = n :: s
  {-# COMPILE AGDA2HS push #-}

  add : Stack → Stack
  add [] = []
  add (x :: []) = []
  add (x :: y :: s) = y + x :: s
  {-# COMPILE AGDA2HS add #-}

  module DefineEval' where
    postulate
      eval' : Expr → Stack → Stack
      eval'  $\equiv$  eval : (e : Expr) → (s : Stack) → eval' e s  $\equiv$  eval e :: s

    eval'-val : (n : Int) → (s : Stack) → eval' (Val n) s  $\equiv$  push n s
    eval'-val n s =
      begin
        eval' (Val n) s
         $\equiv$  { eval'  $\equiv$  eval (Val n) s } -- Specification
        eval (Val n) :: s
         $\equiv$  { } -- Apply eval
        n :: s
         $\equiv$  { } -- Unapply push
        push n s
      ■

    eval'-add : (x y : Expr) → (s : Stack)
      → eval' (Add x y) s  $\equiv$  add (eval' y (eval' x s))

```

```

eval'-add x y s =
  begin
    eval' (Add x y) s
  ≡⟨ eval'≡eval (Add x y) s ⟩ -- Specification
    eval (Add x y) :: s
  ≡⟨ ⟩ -- Apply eval
    eval x + eval y :: s
  ≡⟨ ⟩ -- Unapply add
    add (eval y :: eval x :: s)
  ≡⟨ cong (λ s → add (eval y :: s)) (sym (eval'≡eval x s)) ⟩ -- Induction
    add (eval y :: eval' x s)
  ≡⟨ cong add (sym (eval'≡eval y (eval' x s))) ⟩ -- Induction
    add (eval' y (eval' x s))
  ■

```

```

eval' : Expr → Stack → Stack
eval' (Val n) s = push n s
eval' (Add el er) s = add (eval' er (eval' el s))
{-# COMPILE AGDA2HS eval' #-}

```

```

eval'≡eval : (e : Expr) → (s : Stack) → eval' e s ≡ eval e :: s
eval'≡eval (Val n) s = refl
eval'≡eval (Add x y) s =
  begin
    eval' (Add x y) s
  ≡⟨ ⟩ -- Apply eval'
    add (eval' y (eval' x s))
  ≡⟨ cong (λ s → add (eval' y s)) (eval'≡eval x s) ⟩ -- Induction
    add (eval' y (eval x :: s))
  ≡⟨ cong add (eval'≡eval y (eval x :: s)) ⟩ -- Induction
    add (eval y :: eval x :: s)
  ≡⟨ ⟩ -- Unapply add and eval
    eval (Add x y) :: s
  ■

```

Since  $\text{eval}'\ e\ s$  is the same as  $\text{eval}\ e\ ::\ s$ , this is evidence that  $\text{eval}'\ e\ s$  is a non-empty list:

```

open import Haskell.Prim using (NonEmpty; itsNonEmpty)

eval'-nonempty : (e : Expr) → (s : Stack) → NonEmpty (eval' e s)
eval'-nonempty e s rewrite eval'≡eval e s = itsNonEmpty

```

Since we know that  $\text{eval}'\ e\ []$  is always non-empty, it is allowed to apply head to it in order to get an equivalent definition of  $\text{eval}$ :

```

eval1 : Expr → Int
eval1 e = head (eval' e []) ∷ eval'-nonempty e [] ∷
{-# COMPILE AGDA2HS eval1 #-}

```

### 3. ADDING A CONTINUATION

```

module AddingAContinuation where
  open SyntaxAndSemantics
  open AddingAStack
  Cont = Stack → Stack
  {-# COMPILE AGDA2HS Cont #-}

module DefineEval'' where
  postulate
    eval'' : Expr → Cont → Cont
    eval''≡eval' : (e : Expr) → (c : Cont) → (s : Stack)
      → eval'' e c s ≡ c (eval' e s)

  eval''-val : (n : Int) → (c : Cont) → (s : Stack)
    → eval'' (Val n) c s ≡ c (push n s)
  eval''-val n c s =
    begin
      eval'' (Val n) c s
    ≡⟨ eval''≡eval' (Val n) c s ⟩ -- Postulate
      c (eval' (Val n) s)
    ≡⟨ ⟩ -- Apply eval'
      c (push n s)
    ≡⟨ ⟩ -- Unapply ∘
      (c ∘ push n) s
    ■

  eval''-add : (x y : Expr) → (c : Cont) → (s : Stack)
    → eval'' (Add x y) c s ≡ eval'' x (eval'' y (c ∘ add)) s
  eval''-add x y c s =
    begin
      eval'' (Add x y) c s
    ≡⟨ eval''≡eval' (Add x y) c s ⟩
      c (eval' (Add x y) s)
    ≡⟨ ⟩ -- Apply eval'
      c (add (eval' y (eval' x s)))
    ≡⟨ ⟩ -- Unapply ∘
      (c ∘ add) (eval' y (eval' x s))
    ≡⟨ sym (eval''≡eval' y (c ∘ add) (eval' x s)) ⟩ -- Induction y
      eval'' y (c ∘ add) (eval' x s)
    ≡⟨ sym (eval''≡eval' x (eval'' y (c ∘ add)) s) ⟩ -- Induction x
      eval'' x (eval'' y (c ∘ add)) s
    ■

  eval'' : Expr → Cont → Cont
  eval'' (Val n) c = c ∘ push n
  eval'' (Add x y) c = eval'' x (eval'' y (c ∘ add))
  {-# COMPILE AGDA2HS eval'' #-}

  eval''≡eval' : (e : Expr) → (c : Cont) → (s : Stack)
    → eval'' e c s ≡ c (eval' e s)
  eval''≡eval' (Val x) c s = refl

```

```

eval''≡eval' (Add x y) c s =
  begin
    eval'' (Add x y) c s
  ≡⟨⟩ -- Apply eval''
    eval'' x (eval'' y (c ∘ add)) s
  ≡⟨ eval''≡eval' x (eval'' y (c ∘ add)) s ⟩ -- Induction
    eval'' y (c ∘ add) (eval' x s)
  ≡⟨ eval''≡eval' y (c ∘ add) (eval' x s) ⟩ -- Induction
    (c ∘ add) (eval' y (eval' x s))
  ≡⟨⟩ -- Apply add
    c (eval' (Add x y) s)
  ■

```

Thus `eval'` is simply redefined as follows:

```

eval'1 : Expr → Cont
eval'1 e = eval'' e id
{-# COMPILE AGDA2HS eval'1 #-}

```

## 4. DEFUNCTIONALISING

```
module Defunctionalising where
  open SyntaxAndSemantics
  open AddingAStack
  open AddingAContinuation
  haltC : Cont
  haltC = id
  {-# COMPILE AGDA2HS haltC #-}

  pushC : Int → Cont → Cont
  pushC n c = c ∘ push n
  {-# COMPILE AGDA2HS pushC #-}

  addC : Cont → Cont
  addC c = c ∘ add
  {-# COMPILE AGDA2HS addC #-}

  data Code : Set where
    HALT : Code
    PUSH : Int → Code → Code
    ADD : Code → Code
  {-# COMPILE AGDA2HS Code deriving Show #-}

  exec : Code → Cont
  exec HALT = haltC
  exec (PUSH n c) = pushC n (exec c)
  exec (ADD c) = addC (exec c)
  {-# COMPILE AGDA2HS exec #-}

  comp' : Expr → Code → Code
  comp' (Val n) c = PUSH n c
  comp' (Add x y) c = comp' x (comp' y (ADD c))
  {-# COMPILE AGDA2HS comp' #-}

  comp : Expr → Code
  comp e = comp' e HALT
  {-# COMPILE AGDA2HS comp #-}

  exec-comp'≡eval'' : (e : Expr) → (c : Code)
    → exec (comp' e c) ≡ eval'' e (exec c)
  exec-comp'≡eval'' (Val n) c = refl
  exec-comp'≡eval'' (Add x y) c =
    begin
      exec (comp' (Add x y) c)
    ≡⟨ -- Apply comp'
      exec (comp' x (comp' y (ADD c)))
    ≡⟨ exec-comp'≡eval'' x (comp' y (ADD c)) ⟩ -- Induction
      eval'' x (exec (comp' y (ADD c)))
    ≡⟨ cong (eval'' x) (exec-comp'≡eval'' y (ADD c)) ⟩ -- Induction
      eval'' x (eval'' y (exec (ADD c)))
    ≡⟨ -- Apply exec
      eval'' x (eval'' y (addC (exec c)))
    ≡⟨ -- Unapply eval''
      eval'' (Add x y) (exec c)
```

■

```

exec-comp≡eval' : (e : Expr) → (s : Stack) → exec (comp e) s ≡ eval' e s
exec-comp≡eval' e s =
  begin
    exec (comp e) s
  ≡⟨⟩ -- Apply comp
    exec (comp' e HALT) s
  ≡⟨ cong (_$ s) (exec-comp'≡eval'' e HALT) ⟩
    eval'' e (exec HALT) s
  ≡⟨⟩ -- Apply exec
    eval'' e id s
  ≡⟨ eval''≡eval' e id s ⟩
    id (eval' e s)
  ≡⟨⟩ -- Apply id
    eval' e s
  ■

```

Alternatively, explicitly with lists:

```

data Op : Set where
  PUSHOP : Int → Op
  ADDOP   : Op
{-# COMPILE AGDA2HS Op #-}

Prog = List Op
{-# COMPILE AGDA2HS Prog #-}

execute : Prog → Cont
execute [] = haltC
execute (PUSHOP n :: os) = pushC n (execute os)
execute (ADDOP :: os) = addC (execute os)
{-# COMPILE AGDA2HS execute #-}

compile' : Expr → Prog → Prog
compile' (Val n) p = PUSHOP n :: p
compile' (Add x y) p = compile' x (compile' y (ADDOP :: p))
{-# COMPILE AGDA2HS compile' #-}

compile : Expr → Prog
compile e = compile' e []
{-# COMPILE AGDA2HS compile #-}

```

```

execute-compile'≡eval'' : (e : Expr) → (p : Prog)
  → execute (compile' e p) ≡ eval'' e (execute p)
execute-compile'≡eval'' (Val n) p = refl
execute-compile'≡eval'' (Add x y) p =
  begin
    execute (compile' (Add x y) p)
  ≡⟨⟩ -- Apply compile'
    execute (compile' x (compile' y (ADDOP :: p)))
  ≡⟨ execute-compile'≡eval'' x (compile' y (ADDOP :: p)) ⟩ -- Induction
    eval'' x (execute (compile' y (ADDOP :: p)))
  ≡⟨ cong (eval'' x) (execute-compile'≡eval'' y (ADDOP :: p)) ⟩ -- Induction
    eval'' x (eval'' y (execute $ ADDOP :: p))
  ≡⟨⟩ -- Apply execute
    eval'' x (eval'' y (addC (execute p)))
  ≡⟨⟩ -- apply addC
    eval'' x (eval'' y ((execute p) ◦ add))
  ≡⟨⟩ -- Unapply eval''
    eval'' (Add x y) (execute p)
  ■

```

```

execute-compile≡eval' : (e : Expr) → (s : Stack)
  → execute (compile e) s ≡ eval' e s
execute-compile≡eval' e s =
  begin
    execute (compile e) s
  ≡⟨⟩ -- Apply compile
    execute (compile' e []) s
  ≡⟨ cong (_$ s) (execute-compile'≡eval'' e []) ⟩
    eval'' e (execute []) s
  ≡⟨⟩ -- Apply execute
    eval'' e haltC s
  ≡⟨ eval''≡eval' e haltC s ⟩
    haltC (eval' e s)
  ≡⟨⟩ -- Apply haltC ≡ id
    eval' e s
  ■

```

```

execute-compile≡eval : (e : Expr) → (s : Stack)
  → execute (compile e) s ≡ eval e :: s
execute-compile≡eval e s =
  begin
    execute (compile e) s
  ≡⟨ execute-compile≡eval' e s ⟩
    eval' e s
  ≡⟨ eval'≡eval e s ⟩
    eval e :: s
  ■

```

## 5. COMBINING THE STEPS

```

module CombiningTheSteps where
  open SyntaxAndSemantics using (Expr; Val; Add; eval)
  open AddingAStack using (Stack)
  module DefineComp where
    postulate
      Code : Set
      exec : Code → Stack → Stack
      comp : Expr → Code
      comp' : Expr → Code → Code
      exec-comp≡eval : (e : Expr) → (s : Stack)
        → exec (comp e) s ≡ eval e :: s
      exec-comp'≡eval : (e : Expr) → (c : Code) → (s : Stack)
        → exec (comp' e c) s ≡ exec c (eval e :: s)
      {- Postulates discovered for exec-comp'-val -}
      PUSH : Int → Code → Code
      exec-push : (n : Int) → (c : Code) → (s : Stack)
        → exec (PUSH n c) s ≡ exec c (n :: s)
      {- Postulates discovered for exec-comp'-add -}
      ADD : Code → Code
      exec-add : (n m : Int) → (c : Code) → (s : Stack)
        → exec (ADD c) (m :: n :: s) ≡ exec c (n + m :: s)
      {- Postulates discovered for exec-comp -}
      HALT : Code
      exec-halt : (s : Stack) → exec HALT s ≡ s

  exec-comp'-val : (n : Int) → (c : Code) → (s : Stack)
    → exec (comp' (Val n) c) s ≡ exec (PUSH n c) s
  exec-comp'-val n c s =
    begin
      exec (comp' (Val n) c) s
    ≡⟨ exec-comp'≡eval (Val n) c s ⟩ -- Postulate
      exec c (eval (Val n) :: s)
    ≡⟨ ⟩ -- Apply eval
      exec c (n :: s)
    ≡⟨ sym (exec-push n c s) ⟩ -- Unapply exec
      exec (PUSH n c) s
    ■

  exec-comp'-add : (x y : Expr) → (c : Code) → (s : Stack)
    → exec (comp' (Add x y) c) s ≡ exec (comp' x (comp' y (ADD c))) s
  exec-comp'-add x y c s =
    begin
      exec (comp' (Add x y) c) s
    ≡⟨ exec-comp'≡eval (Add x y) c s ⟩ -- Postulate
      exec c (eval (Add x y) :: s)
    ≡⟨ ⟩ -- Apply eval
      exec c (eval x + eval y :: s)
    ≡⟨ sym (exec-add (eval x) (eval y) c s) ⟩ -- Unapply exec
      exec (ADD c) (eval y :: eval x :: s)
    ≡⟨ sym (exec-comp'≡eval y (ADD c) (eval x :: s)) ⟩ -- Induction
      exec (comp' y (ADD c)) (eval x :: s)
    ≡⟨ sym (exec-comp'≡eval x (comp' y (ADD c)) s) ⟩
      exec (comp' x (comp' y (ADD c))) s
    ■

```



```

exec-comp : (e : Expr) → (s : Stack)
  → exec (comp e) s ≡ exec (comp' e HALT) s
exec-comp e s =
  begin
    exec (comp e) s
  ≡⟨ exec-comp≡eval e s ⟩ -- Postulate
    eval e :: s
  ≡⟨ sym (exec-halt (eval e :: s)) ⟩ -- Unapply exec
    exec HALT (eval e :: s)
  ≡⟨ sym (exec-comp'≡eval e HALT s) ⟩ -- Unapply exec
    exec (comp' e HALT) s

```

■

```

data Code : Set where
  HALT : Code
  PUSH : Int → Code → Code
  ADD : Code → Code

```

```

comp' : Expr → Code → Code
comp' (Val n) c = PUSH n c
comp' (Add x y) c = comp' x $ comp' y $ ADD c

```

```

comp : Expr → Code
comp e = comp' e HALT

```

```

exec : Code → Stack → Stack
exec HALT s = s
exec (PUSH n c) s = exec c (n :: s)
exec (ADD _) [] = []
exec (ADD _) (_ :: []) = []
exec (ADD c) (m :: n :: s) = exec c (n + m :: s)

```

## EXERCISE 1.

```

module Exercise1 where
data Exprx : Set where
  Valx : Int → Exprx
  Addx : Exprx → Exprx → Exprx
  Throwx : Exprx
  Catchx : Exprx → Exprx → Exprx
{-# COMPILE AGDA2HS Exprx #-}

evalx : Exprx → Maybe Int
evalx (Valx n) = Just n
evalx (Addx x y) = do
  n ← evalx x
  m ← evalx y
  return $ n + m
evalx Throwx = Nothing
evalx (Catchx x h) = case evalx x of λ where
  (Just n) → Just n
  Nothing → evalx h
{-# COMPILE AGDA2HS evalx #-}

```