

Chapter 14

```
import Data.Foldable (Foldable (..))
```

EXERCISE 1: Complete the following instance declaration from `Data.Monoid` to make a pair type into a monoid provided the two component types are monoids:

```
data Pair a b = Pair a b

instance (Semigroup a, Semigroup b) => Semigroup (Pair a b) where
  (<>) :: Pair a b -> Pair a b -> Pair a b
  Pair x1 y1 <> Pair x2 y2 = Pair (x1 <> x2) (y1 <> y2)

instance (Monoid a, Monoid b) => Monoid (Pair a b) where
  mempty :: Pair a b
  mempty = Pair mempty mempty
```

EXERCISE 2: In a similar manner, show how a function type `a -> b` can be made into a monoid provided that the result type `b` is a monoid.

```
newtype Hom a b = Hom (a -> b)

instance (Semigroup b) => Semigroup (Hom a b) where
  (<>) :: Hom a b -> Hom a b -> Hom a b
  Hom f <> Hom g = Hom $ \x -> f x <> g x

instance (Monoid b) => Monoid (Hom a b) where
  mempty :: Hom a b
  mempty = Hom $ const mempty
```

EXERCISE 3: Show how the `Maybe` type can be made foldable and traversable, by giving explicit definitions for `fold`, `foldMap`, `foldr`, `foldl` and `traverse`.

First, wrap the type since these definitions are already provided in the standard library:

```
newtype M a = M (Maybe a)
```

Also define a `Functor` for this new type otherwise we cannot define a `Traversable` instance:

```
instance Functor M where
  fmap :: (a -> b) -> M a -> M b
  fmap f (M (Just x)) = M $ Just $ f x
  fmap _ (M Nothing) = M Nothing
```

Finally define the instances for `Foldable` and `Traversable`:

```

instance Foldable M where
  fold :: (Monoid m) => M m -> m
  fold (M (Just x)) = x
  fold (M Nothing) = mempty

  foldMap :: (Monoid m) => (a -> m) -> M a -> m
  foldMap f (M (Just x)) = f x
  foldMap _ (M Nothing) = mempty

  foldr :: (a -> b -> b) -> b -> M a -> b
  foldr f y (M (Just x)) = f x y
  foldr _ x (M Nothing) = x

  foldl :: (b -> a -> b) -> b -> M a -> b
  foldl f x (M (Just y)) = f x y
  foldl _ x (M Nothing) = x

instance Traversable M where
  traverse :: (Applicative f) => (a -> f b) -> M a -> f (M b)
  traverse f (M (Just x)) = M . Just <$> f x
  traverse _ (M Nothing) = pure $ M Nothing

```