



Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator
Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

Semantic Analysis

Ettore Speziale

Politecnico di Milano



Contents

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

1 Introduction

2 The bison Parser Generator

- Reverse Polish Notation Calculator
- Infix Notation Calculator
- Operator-related Stuffs

3 Advice

4 Bibliography



Contents

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

1 Introduction

2 The bison Parser Generator

- Reverse Polish Notation Calculator
- Infix Notation Calculator
- Operator-related Stuffs

3 Advice

4 Bibliography



Syntax

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

“The study of the rules whereby words or other elements of sentence structure are combined to form grammatical sentences.”

The American Heritage Dictionary



Syntactic Analysis I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

Given an input text we need to determine its *structure*:

- how statements are linked together
- operator precedence rules
- ...

The structure is defined by mean of a *grammar*.

Syntactic analysis is performed over *words*:

- the input is a tokenized stream
- usually a lexical analyzer prepares input for the semantic analysis



Syntactic Analysis II

Semantic
Analysis

Ettore
Speziale

Introduction


The bison
Parser
Generator

Reverse Polish
Notation
Calculator
Infix Notation
Calculator
Operator-related
Stuffis

Advice

Bibliography

Structure of an algebraic expression





Semantic Analysis

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator


Reverse Polish
Notation
Calculator
Infix Notation
Calculator
Operator-related
Stuffs

Advice


Bibliography

It is the evaluation of the meaning of each (terminal and non-terminal) symbol, achieved by *decorating the Abstract Syntax Tree*:

Syntactic analysis



Semantic analysis





Contents

Semantic
Analysis

Ettore
Speziale

Introduction

The **bison**
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

1 Introduction

2 The **bison** Parser Generator

- Reverse Polish Notation Calculator
- Infix Notation Calculator
- Operator-related Stuffs

3 Advice

4 Bibliography



Parsing

Semantic
Analysis

Ettore
Speziale

Introduction

The `bison`
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

A *parser* is a program that performs syntactic analysis.
Typically:

- LL descending parsing, can be constructed by hand (`c-parser.c` in GCC sources) or automatically (ANTLR Java parsers generator)
- LR ascending parsing, usually too complex to be constructed manually

Common duty: **building the Abstract Syntax Tree.**



bison

Semantic
Analysis

Ettore
Speziale

Introduction

The **bison**
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

The standard tool to generate LR parsers is bison:

- free implementation of yacc
- strongly coupled with flex
- actually a LALR(1) parser generator

Getting bison

Available in your distribution repositories:

Debian `aptitude install bison`

Fedora `yum install bison`



Parser Building

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator
Infix Notation
Calculator
Operator-related
Stuffis


Advice

Bibliography

A parser consume **tokens**:

- a scanner must produces tokens
- natural choice is flex

Using bison and flex together





A Simple Example

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuff

Advice

Bibliography

Let's try to build a reverse polish notation calculator.

Grammar

$$S \rightarrow E | \epsilon$$

$$E \rightarrow \text{NUMBER}$$

$$E \rightarrow EE + | EE *$$

Don't worry about terminals:

- it is a scanner duty



The bison Input File

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

The bison input file resemble the one of flex:

C definitions header
inclusions, var
declarations,
...

definitions tokens,
precedences,
...

grammar rules rules and
semantic
actions

user code main and
service
functions

bison input file ^a

```
%{  
/* C definitions */  
%}  
/* Definitions */  
%%  
/* Grammar rules */  
%%  
/* User code */
```

^aC89-style comments can
appear in any of the sections.



Do You Remember flex? I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

We must provide a scanner to bison:

- just implement the `yylex` function
- maybe better to exploit `flex`

`scanner.l` global section

```
%option noyywrap
%{
#include "rpn.tab.h"
#define UNKNOWN -1
%}
DIGIT [0-9]
BLANK [ \n\r\t]
%%
```



Do You Remember flex? II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

scanner.l rules section

```
{BLANK}  
{DIGIT}+ { return NUMBER; }  
"+" { return OP_PLUS; }  
"*" { return OP_MUL; }  
. {  
    yyerror("Unknown char");  
    return UNKNOWN;  
}
```

There is no need to add extra C code:

- flex is only used to tokenize the input



Parser Definition I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Let's start with a parser that *recognize* reverse polish notation expressions:

rpn.y definitions section

```
%{  
#include <stdio.h>  
%}  
%token  NUMBER  
%token  OP_PLUS  
%token  OP_MUL  
%%
```

The %token directive allows to define words read by the parser.



Parser Definition II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

Syntax for grammar definition is straightforward:

rpn.y grammar section

```
calculus: /* Empty */  
         | expression  
         ;  
expression: NUMBER  
          | expression expression OP_PLUS  
          | expression expression OP_MUL  
          ;  
%%
```



Parser Definition III

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator
Infix Notation
Calculator
Operator-related
Stuff

Advice

Bibliography

The last section contains:

- the error handling function `yyerror`
- the program entry point `main`

rpn.y C code

```
int yyerror(char* msg) {  
    printf("%s\n", msg);  
    return 0;  
}  
  
int main(int argc, char* argv[]) {  
    return yyparse();  
}
```



Compiling sources I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

From the parser (rpn.y file) we build:

- the parser itself (rpn.tab.c)
- a description of tokens (rpn.tab.h)

Parser and scanner generation

```
$ bison -d rpn.y  
$ flex scanner.l
```



Compiling sources II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

To get the final executable compile and link:

Get your own polish parser

```
$ gcc rpn.tab.c lex.yy.c
```

I am lazy:

Using make ¹

```
YFLAGS=-d
rpn: rpn.o scanner.o
clean:

    rm -f rpn y.tab.h *.o
```

¹ Filenames are slightly different.



Adding semantic I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Beside each rule it is possible to add a code-block performing a semantic action:

- the semantic action is executed in the context of the associated rule

Rules full syntax

```
lhs: rhs_1 { ... }  
    | rhs_2 { ... } rhs_3 { ... }
```

The lhs rule is an alternative:

- each alternative is independent from the other
- the first contains a semantic action
- the second contains two semantic actions



Adding semantic II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Semantic actions are executed just after the preceding rule.
Given:

```
lhs: rhs { ... }
```

The parser:

- 1 recognizes rhs
- 2 executes the semantic action
- 3 recognizes lhs

The action is placed at rule tail:

- it is executed *every time* lhs is recognized



Adding semantic III

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

Given:

`lhs: rhs1 { ... } rhs2 { ... }`

The parser:

- 1 recognizes `rhs1`
- 2 executes the first semantic action
- 3 recognizes `rhs2`
- 4 executes the second semantic action
- 5 recognizes `lhs`

Semantic actions not at the tail of a rule are called *actions in the middle*.



Adding semantic IV

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

This is a **logical** view of semantic action execution:

- the execution of semantic actions **can be postponed** due to ambiguity



Semantic Values I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

A variable is associated to every symbol:

- an `int` by default
- no distinction between terminal and non-terminal
- type customizable via `%union` directive ²

Inside actions is possible to use these vars:

- accessed through `$n` notation
- index are 1-based
- the left-hand side semantic variable is `$$`
- counting includes semantic actions



Semantic Values II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Variables enumeration

Given:

```
lhs: rhs1 { ... } rhs2 { ... }
```

We have:

Component	Variable
lhs	\$\$
rhs1	\$1
{ ... }	\$2
rhs2	\$3
{ ... }	\$4



Semantic Values III

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Obviously inside a semantic action we can access only variables associated to preceding rules:

- rhs-vars mostly accessed in read-mode ³

With an exception: the \$\$ variable:

- it is a *synthesized* attribute
- always written
- available only in the semantic action ⁴

Default semantic action:

- { \$\$ = \$1; }

²More on this on next lesson.

³LALR parsing is bottom-up.

⁴The code block at rule tail.



Add and Multiply I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

We must assign a semantic value to terminals:

```
scanner.l scanning naturals
```

```
{DIGIT}+ {  
    yylval = atoi(yytext);  
    return NUMBER;  
}
```

The `yylval` variable is declared by bison:

- must be filled with the semantic value of the terminal



Add and Multiply II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuff

Advice

Bibliography

Sums and products must be performed by the parser:

rpn.y computing actions

```
expression:
    NUMBER { $$ = $1; }
    | expression expression OP_PLUS {
        $$ = $1 + $2;
    }
    | expression expression OP_MUL {
        $$ = $1 * $2;
    }
    ;
%%
```



Add and Multiply III

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

At last print the expression evaluation:

rpn.y reporting action

```
calculus:
    /* Empty */
    | expression {
        printf("Result: \u00d7%d\n", $1);
    }
;
```



Ambiguity I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Consider the grammar of infix expressions:

Grammar

$$S \rightarrow E | \epsilon$$

$$E \rightarrow \text{NUMBER}$$

$$E \rightarrow E + E | E * E$$

It has a big problem: it is **ambiguous**!



Ambiguity II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator


Operator-related
Stuff

Advice


Bibliography

Let's try to generate $2 * 2 + 2$:

Produce $+$ first



Produce $*$ first



The grammar ambiguity between $+$ and $*$ rules generates a semantic ambiguity:

- what are the $+$ and $*$ precedences?



How To Resolve Ambiguity I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice


Bibliography

From theory, we can rewrite the grammar in a non ambiguous form:

Unambiguous grammar

$$\begin{aligned} S &\rightarrow E|\epsilon \\ E &\rightarrow E + T | T \\ T &\rightarrow \text{NUMBER} \\ T &\rightarrow T * \text{NUMBER} \end{aligned}$$

Unique tree





How To Resolve Ambiguity II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography

Since tokens are the same, we build only the parser:

infix.y rules⁵

```
expression:
    term { $$ = $1; }
    | expression OP_PLUS term {
        $$ = $1 + $3;
    }
term:
    NUMBER { $$ = $1; }
    | term OP_MUL NUMBER {
        $$ = $1 * $3;
    }
```

⁵Scaffolding is unchanged.



Precedence

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Another way to handle operator precedence is to tell bison the precedence relation:

Precedence with bison ^a

```
%left TOKEN_1 TOKEN_2
%left TOKEN_3
```

^aPrecedences declared inside definitions section.

- TOKEN_1 and TOKEN_2 have the same precedence
- both have lower precedence than TOKEN_3



Associativity I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography


An operator \oplus can be:

left-associative $a \oplus b \oplus c = (a \oplus b) \oplus c$


right-associative $a \oplus b \oplus c = a \oplus (b \oplus c)$

Associativity reflects on parsing:

AST of left-associative \oplus



AST of right-associative \oplus





Associativity II

Semantic
Analysis

Ettore
Speziale

Introduction

The `bison`
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Inside a `bison` file it is possible to declare the associativity of operators:

- operators are *tokens*

`bison` directives for operators associativity

Syntax	Meaning
<code>%left TOKEN</code>	TOKEN is left-associative
<code>%right TOKEN</code>	TOKEN is right-associative



Ambiguous Infix Calculator I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Declaring operator precedences allows to write ambiguous rules:

`infix-ambiguous.y` rules

```
expression:
    NUMBER { $$ = $1; }
    | expression OP_PLUS expression {
        $$ = $1 + $3;
    }
    | expression OP_MUL expression {
        $$ = $1 * $3;
    }
```



Ambiguous Infix Calculator II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Disambiguation is performed by bison consulting operator precedences:

Unambiguous tokens

```
%token  NUMBER
%token  OP_PLUS
%token  OP_MUL
```

Ambiguous tokens

```
%token  NUMBER
%left   OP_PLUS
%left   OP_MUL
```



Context-dependent Precedence I

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Sometimes a character has a dual meaning:

- the `-` identifies both subtraction and unary minus

First of all, let's modify the infix scanner to recognize `-`:

```
infix-scanner.l minus token
```

```
"-" { return OP_MINUS; }
```




Context-dependent Precedence II

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuff

Advice

Bibliography

In the parser we introduce:

- the subtraction token `OP_MINUS`
- the unary minus `OP_UNARY_MINUS`

The latter is a *fake* token used to declare a precedence.

`infix-minus.y` minus token

```
%token NUMBER
%left OP_PLUS OP_MINUS
%left OP_MUL
%left OP_UNARY_MINUS
```



Context-dependent Precedence III

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

In the rules section we can force the right precedence:

infix-minus.y minus rules

```
expression:
```

```
...
```

```
| expression OP_MINUS expression {  
    $$ = $1 - $3;  
}
```

```
...
```

```
| OP_MINUS expression  
    %prec OP_UNARY_MINUS {  
    $$ = -$2;  
}
```



Contents

Semantic
Analysis

Ettore
Speziale

Introduction

The `bison`
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

1 Introduction

2 The `bison` Parser Generator

- Reverse Polish Notation Calculator
- Infix Notation Calculator
- Operator-related Stuffs

3 Advice

4 Bibliography



Parse-First

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

Using bison requires both:

- writing the grammar
- adding semantic actions

Write the grammar first!

- try some examples
- if they are recognized, add semantic actions



Simple Grammars

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

As in coding, follow some conventions while writing grammars:

- terminals (tokens) are uppercase
- not-terminals are lowercase
- ...

This keeps the grammar readable!



Contents

Semantic
Analysis

Ettore
Speziale

Introduction

The `bison`
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator

Operator-related
Stuffs

Advice

Bibliography

1 Introduction

2 The `bison` Parser Generator

- Reverse Polish Notation Calculator
- Infix Notation Calculator
- Operator-related Stuffs

3 Advice

4 Bibliography



Bibliography

Semantic
Analysis

Ettore
Speziale

Introduction

The bison
Parser
Generator

Reverse Polish
Notation
Calculator

Infix Notation
Calculator
Operator-related
Stuffs

Advice

Bibliography



GNU.

GNU bison Info Pages.
info bison, 2006.



Formal Languages and Compilers Group.
Software Compilers.

<http://compilergroup.elet.polimi.it>, 2010.