



Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

# Control in ACSE

Ettore Speziale

Politecnico di Milano



# Contents

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

**1** Introduction

**2** Jumps

**3** While Statement

**4** Advice

**5** Bibliography



# Contents

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

**1** Introduction

2 Jumps

3 While Statement

4 Advice

5 Bibliography



# Control Statements

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

Control statements allows to customize the execution trace at run-time:

- if
- while
- for
- ...

They are implemented through *jumps*:

- special instructions
- allow to select the next instruction to execute at run-time



# Contents

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

1 Introduction

2 Jumps

3 While Statement

4 Advice

5 Bibliography



# Where to Jump? I

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement



Advice

Bibliography

ACSE is a syntax-directed translator:

- instructions emission constrained by source code ordering

But jumps are specials:





# Where to Jump? II

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

## Forward jumps:

- conditionals, loop exits
- when we generate the jump we only know that we must jump (jump target not yet emitted)

## Backward jumps:

- found in loops
- when we generate the jump we know where to jump (we have already emitted the code where we want to jump)



# Where to Jump? III

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

To address jump translation:

- physical address vs logical location

*Labels* represent logical locations.

## Addresses

Consider a `while` statement containing 4 instructions:

**physical address** 4 instructions after loop head

**logical address** the statement following the loop





# Labels

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

The `axe_engine.h` contains APIs for label management:

## Label management APIs

Function	Meaning
<code>newLabel</code>	create a label
<code>assignLabel</code>	bind a label to a logical address <sup>1</sup>
<code>assignNewLabel</code>	combined operation

Binding to physical addresses performed by ACSE.

---

<sup>1</sup>Fixing.



# Exploiting Labels

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

Two scenarios:

## Forward jump

- 1 create a label *lbl* when a jump is needed
- 2 jump to *lbl*
- 3 fix *lbl* when the corresponding statement is reached

## Backward jump

- 1 create and fix label at jump target
- 2 emit jump to *lbl* when the jump statement must be generated



# Fall-through Path

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice


Bibliography

Usually branches have two outgoing edges:

**jump** points to the label associated with the jump instruction

**fall-through** points to the next statement

## Branch paths





# Contents

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

1 Introduction

2 Jumps

**3 While Statement**

4 Advice

5 Bibliography



# A Real Control Structure I

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

Consider the while statement:


while grammar rule

```
while_statement:
```

```
    WHILE LPAR exp RPAR code_block;
```


What we have:

Naked while



What we would have:

Theoretical flow





# A Real Control Structure II

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

Once `exp` has been evaluated we can:

- exit the loop
- enter the loop

We need a *conditional jump* to handle such case:

- two paths: taken and not taken

At the end of the `code_block` we need to re-evaluate the loop condition:

- unconditional branch to `exp` evaluation

All what we need is **emitting jumps**!



# While Layout I

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps


While  
Statement

Advice

Bibliography

By reserving spaces for jumps the code layout is:

## Code segment layout





# While Layout II

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement


Advice

Bibliography

Edges targets three instructions:

- the fall-through edge is implicit
- can be eliminated
- we need only two labels

## Removing useless labels







# While Layout III

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps


While  
Statement

Advice


Bibliography

Since the BEQ jumps predicates over the zero bit, we must enforce its evaluation:

exp is an immediate



exp is an intermediate





# While Sources

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

The `exp` type is known at compile-time:

- `while_statement` customization performed at compile-time

On sources (`Acse.y`):

- lookup the `while_statement` rule
- the `WHILE` token is *typed*

We need:

- an action in the middle to generate the loop exit jump
- an action to generate the backward jump and marking the statement end label



# Contents

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

1 Introduction

2 Jumps

3 While Statement

4 Advice

5 Bibliography



# Handling Constructs

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

All programming languages are built around few simple constructs:

- many constructs just “syntactic sugar”

Better to type rules related to complex constructs:

- keep code clean!

Try starting with a scheme:

- to get an overview
- some minds work better with pictures

Do not redo work:

- read the ACSE headers
- some code already present (e.g. `collections.h`)



# Contents

Control in  
ACSE

Ettore  
Speziale

Introduction

Jumps

While  
Statement

Advice

Bibliography

1 Introduction

2 Jumps

3 While Statement

4 Advice

**5 Bibliography**



# Bibliography

Control in  
ACSE

Ettore  
Speciale

Introduction

Jumps

While  
Statement

Advice

Bibliography



A. Di Biagio and G. Agosta.

Advanced Compiler System for Education.

<http://compilergroup.elet.polimi.it>, 2008.



Formal Languages and Compilers Group.

Software Compilers.

<http://compilergroup.elet.polimi.it>, 2010.