

EXPERIMENT – 6

AIM: - Write a program to implement error detection and correction using HAMMING code concept. Make a test run to input data stream and verify error correction feature.

[illegible]

CODE: -

```
def calcRedundantBits(m):
    #Use the formula  $2^r \geq m+r$ 
    for i in range(m):
        if  $2^{i+1} \geq m+i+1$ :
            return i

def posRedundantBits(data, r):
    # Redundancy bits are placed at the positions
    j = 0
    k = 1
    m = len(data)
    res = ''
    #If position is power of 2 then insert '0' Else append the data
    for i in range(1, m+r+1):
        if  $i == 2^j$ :
            res = res + '0'
            j += 1
        else:
            res = res + data[-1 * k]
            k += 1
    #The result is reversed since positions are counted backwards. (m + r + 1 ... 1)
    return res[::-1]

def calcParityBits(arr, r):
    n = len(arr)
    # For finding rth parity bit, iterate over
```

```

#0tor    -1
foriinrange(r):
    val = 0
    forjinrange(1,n+1):

        #Ifpositionhas1inithsignificant
        #positionthenBitwiseORthearray value
        # to find parity bit value.
        if(j & (2**i) == (2**i)):
            val=val^int(arr[-1*j])
            #-1*jisgivensincearrayis reversed

    #StringConcatenation
    # (0ton    - 2^r)+paritybit+(n    - 2^r + 1 to n)
    arr=arr[:n-(2**i)]+str(val)+arr[n-(2**i)+1:]
returnarr

def detectError(arr, nr):
    n=len(arr)
    res = 0

    # Calculate parity bits again
    for i in range(nr):
        val = 0
        for j in range(1, n + 1):
            if(j & (2**i) == (2**i)):
                val=val^int(arr[-1*j])

        # Create a binary no by appending
        # parity bits together.

        res = res + val*(10**i)

    # Convert binary to decimal
    return int(str(res), 2)

# Enter the data to be transmitted
data = '1011001'

# Calculate the no of Redundant Bits Required
m = len(data)
r = calcRedundantBits(m)

# Determine the positions of Redundant Bits
arr = posRedundantBits(data, r)

# Determine the parity bits
arr = calcParityBits(arr, r)

```

```

# Data to be transferred
print("Data transferred is " + arr)

# Stimulate error in transmission by changing
# a bit value.
# 10101001110 -> 11101001110, error in 10th position.

arr = '10101001110'
print("Error Data is " + arr)
correction = detectError(arr, r)
if(correction==0):
    print("There is no error in the received message.")
else:
    print("The position of error is ",len(arr)-correction+1,"from the left")

```

OUTPUT: -

```

main.py
1- def calcRedundantBits(m):
2-     # Use the formula 2^r - 1 >= m + r + 1
3-     for i in range(m):
4-         if(2**i >= m + i + 1):
5-             return i
6-
7- def posRedundantBits(data, r):
8-     # Redundancy bits are placed at the positions
9-     j = 0
10-    k = 1
11-    m = len(data)
12-    res = ""
13-    # If position is power of 2 then insert '0' Else append the data
14-    for i in range(1, m+r+1):
15-        if(i == 2**j):
16-            res = res + '0'
17-            j += 1
18-        else:
19-            res = res + data[-1 * k]
20-            k += 1
21-    # The result is reversed since positions are counted backwards, (m + r - 1 ... 1)
22-    return res[::-1]
23-
24-
25- def calcParityBits(arr, r):
26-    n = len(arr)
27-    # For finding rth parity bit, iterate over
28-    # 0 to r - 1
29-    for i in range(r):
30-        val = 0
31-        for j in range(1, n + 1):
32-
33-            # If position has 1 in ith significant
34-            # position then bitwise OR the array value
35-            # to find parity bit value.
36-            if(j & (2**i)) == (2**i):

```

Output

```

Data transferred is 10101001110
Error Data is 1010111101
The position of error is 4 from the left

=== Code Execution Successful ===

```

RESULT: -

The code for HAMMING CODE have been executed successfully and the output is verified.