GIRIJA S P 230701092 CSE E

// Banker's Algorithm

EXP NO:9 Bankers Deadlock Avoidance algorithms

PROGRAM

```
#include <stdio.h>
#include <stdbool.h>
int main() {
    int n, m; // n = number of processes, m = number of resources
    printf("Enter the number of processes: ");
    scanf("%d", &n);
    printf("Enter the number of resources: ");
    scanf("%d", &m);
    int allocation[n][m], max[n][m], need[n][m], available[m];
    bool finish[n];
    int safeSeq[n];
    // Input Allocation Matrix
    printf("Enter Allocation Matrix:\n");
    for (int i = 0; i < n; i++) {
        printf("P%d: ", i);
for (int j = 0; j < m; j++) {
    scanf("%d", &allocation[i][j]);</pre>
    // Input Max Matrix
    printf("Enter Max Matrix:\n");
    for (int i = 0; i < n; i++) {
         printf("P%d: ", i);
         for (int j = 0; j < m; j++) {
    scanf("%d", &max[i][j]);
    need[i][j] = max[i][j] - allocation[i][j]; // Calculating Need Matrix
    // Input Available Resources
    printf("Enter Available Resources:\n");
         scanf("%d", &available[i]);
```

```
// Input Available Resources
printf("Enter Available Resources:\n");
for (int i = 0; i < m; i++) {
    scanf("%d", &available[i]);
// Banker's Algorithm
int count = 0;
for (int i = 0; i < n; i++) finish[i] = false;
while (count < n) {
   bool found = false;
    for (int i = 0; i < n; i++) {
        if (!finish[i]) {
            bool canAllocate = true;
            for (int j = 0; j < m; j++) {
                if (need[i][j] > available[j]) {
                    canAllocate = false;
                    break;
            if (canAllocate) {
                for (int j = 0; j < m; j++)
                    available[j] += allocation[i][j];
                safeSeq[count++] = i;
                finish[i] = true;
                found = true;
    if (!found) {
        printf("\nSystem is NOT in a safe state.\n");
        return 0;
// If we reach here, system is in safe state
printf("\nThe SAFE Sequence is:\n");
    printf("P%d", safeSeq[i]);
    if (i != n - 1) printf(" -> ");
printf("\n");
return 0;
```

```
[cse81@localhost ~]$ ./a.out
Enter the number of processes: 5
Enter the number of resources: 3
Enter Allocation Matrix:
P0: 0 1 0
P1: 2 0 0
P2: 3 0 2
P3: 2 1 1
P4: 0 0 2
Enter Max Matrix:
P0: 7 5 3
P1: 3 2 2
P2: 9 0 2
P3: 2 2 2
P4: 4 3 3
Enter Available Resources:
3 3 2
The SAFE Sequence is:
P1 -> P3 -> P4 -> P0 -> P2 [cse81@localhost ~]$
```