### **Inter process Communication**

#### Description of 3 types of IPC's and the structures used

# 1. Shared Memory

Constants for shared memory

```
SHMMNI /* Max. number of shared memories open at a time*/
SHMMIN /* Min. size of shared memory */
SHMMAX /* Max. size of shared memory */
SHMSEG /* Max. size of shared Memory Segments per process */
```

All these are configurable by the user using the control panel applet.

# Data structures for shared memory

The ntpid and ntmpid is used here because ipc's are used across processes and the handle value doesn't make sense across process. Handle value is valid only in the process region that created it. So this handle needs to be duplicated before using. To duplicate the handle we need to specify the handle and the process that created it.

## 2. Semaphores

# Constants used for semaphore

```
SEMMNI /* max semaphores that can be open */
SEMMSL /* max number of semaphores per id (process) */
SEMMNS /* max number of semaphores in system */
SEMOPM /* max number of operations per semop call */
SEMVMX /* semaphore maximum value */
These values can again be configurable using control panel applet.
```

# Data structures for semaphores

```
struct Psem
{
  long refcount;
  HANDLE handle;
  HANDLE event;
  DWORD ntpid;
```

```
HANDLE mutex;
DWORD ntmpid;
...
};
```

These fields defined within the structure are specific to UWIN. The rest (...) are standard and provided by UNIX.

# 3. Message Queues

# Constants for message queues

```
MSGMNI /* Max. number of messages (msgid) */
MSGMAX /* Max. size of message (bytes) */
MSGMNB /* Max. size of a message queue */
```

# Data structures for message queues

```
struct Pmsq
{
             refcount;
  long
            handle;
  HANDLE
  HANDLE event;
  DWORD
             ntpid;
  HANDLE mutex;
  DWORD ntmpid;
  long
              first; /* offset to the first message in the queue */
              last; /* offset to the last message in the queue */
  long
              next; /* offset to the location where a new msg can be stored */
  long
};
```

#### Note

Any changes to the data made in the memory mapped file is signaled through the event .The memory mapped file is defined in /temp/.ipc. Mutex is used to make the operations atomic.

## Message structure

This message queue is by default 1MB. The message structure is defined as follows.


```
struct Message
{
  long reclen; /* number of bytes current block can store */
  long msize; /* block is free (0) or allocated (1) */
  long next; /* offset to the next msg in the queue */
  long type; /* type of message as supplied by the application */
  char msg[4]; /* data as supplied by the application */
};
```

When more than one consecutive block are free, they are merged into a single free block.

There can be more than one free block at any given time which are not contiguous.

The *Message* structure resides in the memory mapped file.

## Layout of memory mapped file



The guard band is used to make the search circular starting from the offset present in the *next*.

#### Deletion in the message queue

If there are no messages in the queue, it returns error or waits till a message arrives (depending on the IPC\_NOWAIT flag).

If there are messages, each of them is compared with the type to see if that is being requested by the application.

If a match is found, the message is sent to the application and the memory block is freed up.

#### Note

One message queue is created per id.

## Functions /Macros used

msgnext() : Finds the location of the next available message in the message queue (utilizes the guard band to loop back to the beginning of the memory).