


## Learning the topology of a bayesian network from a database of cases using the K2 algorithm

A Bayesian belief-network structure is a directed acyclic graph in which nodes represent domain variables and arcs between nodes represent probabilistic dependencies [1]. Given a database of records, it is interesting to construct a probabilistic network which can provide insights into probabilistic dependencies existing among the variables in the database. Such network can be further used to classify future behaviour of the modelled system [1]. Although researchers have made substantial advances in developing the theory and application of belief networks, the actual construction of these networks often remains a difficult, time consuming task. An efficient method for determining the relative probabilities of different belief-network structures, given a database of cases and a set of explicit assumptions is described in [1] and [2].



The K2 algorithm [2] can be used to learn the topology of a Bayes network [1], i.e. of finding the most probable belief-network structure, given a database.

**Part 1** After having studied the problem in the suggested literature ([1]-[2]), Implement the algorithm in R and check its performances with the test data set given in [2].

**Part 2** Implement and test the K2 algorithm with the test data sets ([2]). Investigate if it is possible to code it inside the `bnstruct` R package [3]-[4].

## Bibliography

- [1] G. F. Cooper and E. Herskovits, *A Bayesian Method for the Induction of Probabilistic Networks from Data*, Machine Learning **9**, (1992) 309
- [2] C. Ruiz, *Illustration of the K2 Algorithm for learning Bayes Net Structures*, [http://web.cs.wpi.edu/~cs539/s11/Projects/k2\\_algorithm.pdf](http://web.cs.wpi.edu/~cs539/s11/Projects/k2_algorithm.pdf)
- [3] A. Franzin et al., *bnstruct: an R package for Bayesian Network structure learning in the presence of missing data*, Bioinformatics **33(8)** (2017) 1250
- [4] F. Sambo and A. Franzin, *bnstruct: an R package for Bayesian Network Structure Learning with missing data*, December 12, 2016