CDMA and Stealthy Communication Protocols in Underwater Environments

Introduction

Wireless communication is an essential component of many underwater systems, allowing devices to transmit information without requiring a physical connection. Such communication could be beneficial in locating and retrieving REMUS, particularly if the system incorporates stealthy communication techniques. However, underwater transmissions may be detected by unintended receivers, potentially revealing the presence or location of a communicating device. Code Division Multiple Access (CDMA) and other stealthy communication protocols offer potential methods of reducing transmission detectability. Understanding their mechanisms and limitations is important when considering their applications in underwater systems.

Underwater Acoustic Communication

Underwater communication generally relies on acoustic signals rather than conventional radio frequency (RF) transmissions. This is largely because water absorbs and dissipates electromagnetic waves, particularly at frequencies commonly used for wireless communication. Acoustic waves can propagate over much longer distances, which may be suboptimal for low distance communication with the REMUS. However, reducing transmission power and selecting a good acoustic frequency may help limit the distance over which a signal can be detected. Acoustic waves are also subject to environmental limitations. Li et al. (2025) identify limited bandwidth, significant propagation delays, and multipath interference as major challenges. Multipath interference occurs when a transmitted signal reaches a receiver through several paths, often due to reflections off the water's surface or seafloor. The receiver consequently receives multiple delayed versions of the original signal, making it more difficult to reconstruct the transmitted information.

Code Division Multiple Access (CDMA)

CDMA allows multiple devices to communicate over the same frequency band simultaneously using different identifying codes. Unlike methods that assign users separate frequencies or transmission times, CDMA distinguishes transmissions through code-based signal separation. This is commonly accomplished using Direct Sequence Spread Spectrum (DSSS), in which a signal is combined with a pseudorandom code to distribute its energy across a wider bandwidth. Each information bit is represented by a sequence of shorter elements called chips. A receiver with the appropriate code can correlate the incoming signal with the expected sequence to recover the transmitted information. Stojanovic (2000) discusses the advantages of spread-spectrum CDMA in underwater acoustic networks, particularly under challenging channel conditions.

CDMA describes a multiple-access technique, while DSSS describes the process of spreading a signal across a wider bandwidth. Spread-spectrum signaling can therefore be useful even when

multiple-access capabilities are unnecessary, as may be the case with the REMUS and the ROV if there is only one ROV.

Distributing a signal's energy across a wider bandwidth is also relevant to LPD communications. By reducing the signal power concentrated within a narrow frequency range, a transmission may become more difficult to distinguish from background noise using certain detection methods. An intended receiver can use the known spreading code to recover the information through correlation. However, CDMA does not guarantee that a transmission remains undetectable. Signal strength, environmental conditions, and receiver capabilities all influence whether an unintended observer can identify the transmission.

CDMA also faces limitations in underwater environments. One challenge is the near-far problem, where a stronger signal interferes with the reception of a weaker signal. Multipath propagation may further disrupt the correlation process by introducing delayed versions of transmitted signals. Yang and Yang (2009) investigated interference suppression in underwater acoustic CDMA, demonstrating the importance of accounting for these channel conditions.

Short-Range and Stealthy Communication

Beyond CDMA, another consideration for stealthy underwater communication is limiting the exposure of transmissions to unintended receivers. In a system consisting of an ROV and REMUS, communication would ideally occur over a relatively short distance without revealing either device's location to distant observers. Unlike larger underwater networks, this system would not necessarily benefit from protocols involving multiple intermediate devices. Instead, the primary concern is maintaining a reliable two-way communication channel while minimizing the detectability of transmitted signals.

One approach involves reducing unnecessary transmissions through controlled communication intervals. Rather than continuously transmitting information, the devices may exchange data only when necessary, reducing the amount of time acoustic signals are present in the environment. Communication protocols may also minimize unnecessary acknowledgments and repeated transmissions, although doing so can affect reliability. These methods do not make individual signals undetectable, but they can reduce the overall opportunities for interception.

Another consideration is the relationship between communication range and detection range. Although acoustic transmissions may be intended for communication over only a few hundred feet, unintended receivers with greater sensitivity may still detect them at longer distances. Consequently, establishing a short-range communication channel does not necessarily guarantee that its transmissions remain confined to that distance. The effectiveness of stealthy communication ultimately depends on the acoustic environment and the capabilities of potential receivers.

Applications and Limitations

An important consideration is the distinction between communication confidentiality and stealth. Encryption prevents unauthorized interpretation of transmitted information, but does not necessarily conceal the existence of a signal. If the goal of the REMUS retrieval is to be covert, then it is important for the signals to decay at long distances. An observer may still identify an acoustic transmission even without understanding its contents. Consequently, encryption alone does not address the risk of revealing the presence or location of an underwater device.

For an ROV attempting to locate and retrieve an unresponsive REMUS, these distinctions are particularly relevant. Protocols designed for extensive networks may offer limited benefits when only a few devices are available. Additionally, if REMUS is dead, where the receiver does not have any power source (limiting batteries is advantageous for the safety of the REMUS sub) and cannot transmit, communication techniques requiring an active response would not directly assist in the initial detection process. While spread-spectrum techniques may be relevant to communication between operational devices, locating an unresponsive vehicle and maintaining a stealthy communication channel remain separate challenges.

Conclusion

CDMA and other stealthy communication techniques offer potential methods of reducing the detectability of underwater transmissions. Through spread-spectrum signaling, CDMA may make acoustic communications more difficult to distinguish from background noise while maintaining the ability to recover transmitted information. Additional methods, such as limiting unnecessary transmissions, may further reduce opportunities for interception. However, environmental conditions, signal propagation, and receiver sensitivity prevent these techniques from guaranteeing undetectable communication. In the case of an ROV attempting to communicate with REMUS over a short distance, these limitations must be considered alongside the need for a reliable two-way connection. Furthermore, if REMUS is unable to receive or transmit information due to lack of battery power or storage capabilities, establishing such a connection may not be possible.

References

Li, Z., Chitre, M., & Stojanovic, M. (2024). Underwater acoustic communications. *Nature Reviews Electrical Engineering*, *2*(2), 83–95. https://doi.org/10.1038/s44287-024-00122-w

Yang, T.-C., & Yang, W.-B. (2009). Interference suppression for code-division multiple-access communications in an underwater acoustic channel. *The Journal of the Acoustical Society of America*, *126*(1), 220–228. https://doi.org/10.1121/1.3147484

Sozer, E. M., Stojanovic, M., & Proakis, J. G. (2000). Underwater acoustic networks. *IEEE Journal of Oceanic Engineering*, *25*(1), 72–83. https://doi.org/10.1109/48.820738