

Arrays

This lecture will

- Explain how Java arrays can store and manipulate collections of data
- Introduce the enhanced `for` loop
- Introduce simple algorithms for searching and sorting arrays
- Explain multi-dimensional arrays

Collections of data items

- We often need to refer to collections of elements of the same type, e.g. a table of employee details or salaries
- It is inconvenient to write a collection of 5 integers as:

```
int dataItem1;
int dataItem2;
int dataItem3;
int dataItem4;
int dataItem5;
```


- Java stores a collection of elements of the same type in an **array**
- We can manipulate the array as a whole, or manipulate its individual elements

Declaring an array

- To declare an array of 5 integers called `myArray`, we

```
int[] myArray = new int[5];
```

- We pronounce `int[]` as "an array of int"
- Variable `myArray` is a reference to an area of memory containing a collection of 5 integers:



Array indexing and literal arrays

- We specify an individual array element with an **index**, e.g. `myArray[3]`
- Indices are numbered from zero; the last index is one less than the number of elements in the array
- We can also initialise an array using a **literal array expression**, by specifying the elements in curly brackets:

```
int[] myArray = {1, 3, 5, 7, 9};
```

- The compiler calculates how many array elements there are (5 in this case, numbered from `myArray[0]` to `myArray[4]`)

How many elements in an array?

- We can find out the number of elements in `myArray` by writing `myArray.length`
- This is better than using a literal value, for reasons of software maintenance:

```
for (int i=0; i<5; i++)
    myArray[i] = i * 10;
```

- Alternatively, create arrays that contain a user-specified number of elements:

```
int numItems=keyboard.readInt("How many? ");
int[] myArray=new int[numItems];
```

BAD

Using a for loop to process an array

- We often use a `for` loop to process each array element:

```
for (int i=0; i<myArray.length; i++)
    myArray[i] = i * 10;
```

- We specify an element using `myArray[i]`, where `i` is an integer in the range of valid indices.
- An `ArrayIndexOutOfBoundsException` will be thrown if `i` is outside this range.
- A common mistake is to write:

```
for (int i=0; i<=myArray.length; i++)
    myArray[i] = i * 10;
```

WRONG

A table of integers

```
import sheffield.*;
public class SimpleTable {
    public static void main(String[] args) {

        EasyReader keyboard = new EasyReader();
        int items=keyboard.readInt("How many elements? ");
        int[] myArray = new int[items];

        for (int i=0; i<items; i++)
            myArray[i]=
                keyboard.readInt("Enter number "+(i+1)+" : ");

        System.out.println("Your numbers were:");
        for (int i=0; i<items; i++)
            System.out.println(myArray[i]);
    }
}
```

```
Enter the number of items: 3
Enter number 1: 45
Enter number 2: 37
Enter number 3: 23
Your numbers were:
45
37
23
```

Because people count from 1

A simpler table

```
import sheffield.*;
public class SimplerTable {
    public static void main(String[] args) {
        EasyReader keyboard = new EasyReader();
        int items=keyboard.readInt("How many words? ");

        String[] myArray = new String[items];
        for (int i=0; i<items; i++)
            myArray[i]= keyboard.
                readString("Enter word "+(i+1)+" : ");

        System.out.println("Your words were:");
        for (String element : myArray)
            System.out.println(element);
    }
}
```

An enhanced for loop

The enhanced for loop

- Is used to access values of an array in turn without a counter

```
for (type variable_name : array_name)
    loop_body;
```

- The *type* is the type of the elements in the array
- Steps through the elements from 0 to the end in that order
- Will only work when you are looking at elements of an array not for setting their values

Using an expression as an array index

```
public class TestArrayExpressions {
    public static void main (String[] args) {
        int x=1, y=10;
        int[] dataItem = new int[5];
        dataItem[2] = 5;
        dataItem[0] = dataItem[2] * 2;
        dataItem[x+2] = 3*4;
        dataItem[3-2] = 65;
        dataItem[2+(x*6+98)/52] = 2+x*y;
        for (int d : dataItem)
            System.out.println(d);
    }
}
```

10	dataItem[0]
65	dataItem[1]
5	dataItem[2]
12	dataItem[3]
13	dataItem[4]

```
10
65
5
12
13
```

Searching

- Very often, we need to search an array in order to find a particular data item
- In **linear search**, we start at the beginning of the array, and check each element in sequence to determine whether it matches the one we are looking for
- If we know the array is in sorted order, it is more efficient to use a nonlinear searching technique such as **binary search**

Linear search of an array

```
public class ArrayLinearSearch {
    public static void main (String[] args) {

        int[] dataItem = {24,5,6,23,42,45,2,42,1,8};
        int position = 0;
        int target = 42;
        while ((position<dataItem.length)
            &&(dataItem[position]!=target))
            position++;
        System.out.print(target);
        if ( position < dataItem.length )
            System.out.println(" at index " + position);
        else
            System.out.println(" not found");
    }
}
```

```
42 at index 4
```

Searching for multiple occurrences

```
public class ArrayLinearSearch {
    public static void main (String[] args) {

        int[] dataItem = {24,5,6,23,42,45,2,42,1,8};
        int position = 0;
        int target = 42;

        for (int i=0; i<dataItem.length; i++) {
            if ( dataItem[i]==target )
                System.out.println(target+" at index "+i);
        }
    }
}
```

42 at index 4
42 at index 7

- You know how many times to go around the loop so it must be a **for** loop

Binary search

- Binary search can be used on an ordered array
- Start looking in the middle, and discard half of the remaining array until the target is found

1st iteration

1	2	5	6	8	23	24	42	45	48
---	---	---	---	---	----	----	----	----	----

2nd iteration

1	2	5	6	8	23	24	42	45	48
---	---	---	---	---	----	----	----	----	----

- In this example, we find the target number (42) in two iterations; linear search would take 8 iterations

❗ **Does this improvement come at any cost?**

Binary search in Java

```
//ArrayBinarySearch
int[] dataItem = {1,2,5,6,8,23,24,42,45,48};
int target = 42;
int first = 0;
int last = dataItem.length-1;
int middle = 0;
boolean found = false;

while ( first <= last && !found ) {
    middle = (first+last)/2;
    if ( dataItem[middle]>target )
        last = middle-1;
    else if ( dataItem[middle]<target )
        first = middle+1;
    else
        found = true;
}

System.out.print (target );
if (found) System.out.println(" at index " + middle);
else System.out.println(" not found");
```

It doesn't matter what value you give **middle** initially but Java likes it to have some value

Sorting

- Consider how you might sort a list of numbers:
 - repeat
 - find the largest number in the list to be sorted
 - cross it off the list to be sorted and add to a new list until all the numbers have been crossed off
- This is called a **selection sort**.
- We could apply the algorithm directly, but it is wasteful of memory to use two arrays.
- Instead we use a single array and consider it to be divided into sorted and unsorted parts.

Algorithm for selection sort

initialise the unsorted part as the whole array and the sorted part as empty

repeat

find the largest number in the unsorted part of the array

swap the largest number with the last number in the unsorted part of the array

reduce the size of the unsorted part by one

until there is only one number left in the unsorted part

Selection sort in Java

```
public class SelectionSort {
    public static void main(String[] args) {
        int[] dataItem = {24, 5, 6, 23, 42, 45, 2, 42, 1, 8};
        System.out.println("Unsorted data:");
        for (int d : dataItem) System.out.print(d + " ");
        System.out.println();
        for (int lastUnsorted=dataItem.length-1; lastUnsorted>0; lastUnsorted--) {
            int positionOfLargest=lastUnsorted;
            for (int i=0; i<lastUnsorted; i++) {
                if (dataItem[i] > dataItem[positionOfLargest])
                    positionOfLargest = i;
            }
            if ( positionOfLargest != lastUnsorted ) {
                int temp = dataItem[positionOfLargest];
                dataItem[positionOfLargest] = dataItem[lastUnsorted];
                dataItem[lastUnsorted] = temp;
            }
        }
        System.out.println("Sorted data:");
        for (int d : dataItem) System.out.print(d + " ");
        System.out.println();
    }
}
```

Selection sort in Java

```
for (int lastUnsorted = dataItem.length-1; lastUnsorted>0; lastUnsorted--) {
    //Find largest in unsorted part
    int positionOfLargest=lastUnsorted;
    for (int i=0; i<lastUnsorted; i++) {
        if (dataItem[i] > dataItem[positionOfLargest])
            positionOfLargest = i;
    }

    // Swap largest with last unsorted
    if ( positionOfLargest != lastUnsorted ) {
        int temp = dataItem[positionOfLargest];
        dataItem[positionOfLargest] =
            dataItem[lastUnsorted];
        dataItem[lastUnsorted] = temp;
    }
}
```

Multidimensional arrays


- Arrays can have more than one dimension.
- The most useful are two dimensional (2-D), which have **rows** and **columns**.

```
int[][] grid = new int[3][3];
```

- The array `grid` is of type `int[][]`, pronounced “array of array of int”.
- So, `grid` is actually a one-dimensional array of one-dimensional arrays.

Visualising a 2-dimensional array

```
int[][] grid = new int[3][3];
```



Visualising a 2-dimensional array as a matrix

```
int[][] grid = new int[3][3];
```

grid[0][0]	grid[0][1]	grid[0][2]
grid[1][0]	grid[1][1]	grid[1][2]
grid[2][0]	grid[2][1]	grid[2][2]

Processing a 2-dimensional array

- To process a 2-D array, we use a nested loop:

```
for (int r=0; r<grid.length; r++)
    for (int c=0; c<grid[r].length; c++)
        grid[r][c]=0;
```

- We use `r` to count rows (there are `grid.length` rows) and `c` to count columns in each row (there are `grid[r].length` columns).
- We can also initialise multidimensional arrays by writing the elements of each row in curly brackets:

```
int[][] grid = {{0,1,2},{3,4,5},{6,7,8}};
```

The enhanced for loop with 2D arrays

- The enhanced for loop works with 2D arrays too, if we remember that multidimensional Java arrays are represented as arrays of arrays:

```
int[][] numbers = {{1,2,3},{4,5,6},{7,8,9}};
for (int[] row : numbers) {
    for (int n : row)
        System.out.print(n+" ");
    System.out.println();
}
```

Don't use
' ' here

- The output is:

```
1 2 3
4 5 6
7 8 9
```

2D arrays with different length rows

- The declaration of a 2D array need not specify the length of each row so this is also OK

```
int[][] numbers = {{1,2,3,4},{5,6},{7,8,9}};
for (int[] row : numbers) {
    for (int n : row)
        System.out.print(n+" ");
    System.out.println();
}
```

- The output is:

```
1 2 3 4
5 6
7 8 9
```

2D arrays with different length rows for words

```
public class Mary {
    public static void main (String [] args ) {
        String[][] poem =
            { {"Mary","had","a","little","lamb"},
              {"It","had","a","touch","of","colic"},
              {"She","gave","it","brandy","twice",
               "a","day"},
              {"And","now","its","alcoholic"} };
        for (String[] line : poem) {
            for (String word : line)
                System.out.print(word + ' ');
            System.out.println();
        }
    }
}
```

Columns and Rows

- `int[] ints = new int[5];`
creates an array with space for 5 integers
- `String[] strings = new String[5];`
creates an array with space for pointers to 5 Strings
- `char[][] chars = new char[3][5];`
does not create an array of 5 arrays of 3 characters, it
creates an array of **3** arrays each of **5** characters

Rows and columns example

```
public class RowsAndColumns {
    public static void main (String [] args) {
        char [][] letters = new char[2][26];
        System.out.println("No of Rows = "+letters.length);
        System.out.println("No of Columns = "+letters[0].length);

        for (int c = 0; c < 26; c++)
            letters [0][c] = (char)('A'+c);
        for (int c = 0; c < 26; c++)
            letters [1][c] = Character.toLowerCase(letters[0][c]);

        for (char[] row : letters) {
            for (char c : row) System.out.print(c+" ");
            System.out.println();
        }
    }
}
```

```
No of Rows = 2
No of Columns = 26
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
a b c d e f g h i j k l m n o p q r s t u v w x y z
```

2D Arrays


```
char [][] letters;
```

- Creates space for a pointer to an array


letters 

```
char [][] letters = new char[2][26];
```

- Creates space for a pointer to an array and the array itself

letters 


- Any component of the array can be referred to by the array name and indices



3D Arrays

```
char[][][] cube =  
    new char[3][3][2];
```

- Used in many applications including computer graphics.



Rows and Columns and Layers

```
//Cuboid
char [][][] letters = new char[2][3][5];
System.out.println("No of Layers = "+letters.length);
System.out.println("No of Rows = "+letters[0].length);
System.out.println("No of Columns = "+letters[0][0].length);
char next = 'A';
for (int a = 0; a<2; a++)
    for (int b=0; b<3; b++)
        for (int c=0; c<5; c++) {
            letters[a][b][c]=next;    next =
        }
System.out.println("-----");
for (char[][] first : letters) {
    for (char[] second : first) {
        for (char third : second)
            System.out.print(third+" ");
        System.out.println();
    }
    System.out.println("-----");
}
```

```
No of Layers = 2
No of Rows = 3
No of Columns = 5
-----
A B C D E
F G H I J
K L M N O
-----
P Q R S T
U V W X Y
Z [ \ ] ^
-----
```

Remember this..

Change the print statement in the **Simple.java** program to:

```
system.out.println("Hello " + args[0]);
```

Compile the program as usual but run it with

```
U:...myjava> java Simple XXXX
```

```
public class Exerciselc {
    public static void main(String[] args) {
        System.out.println("Hello "+args[0]);
    }
}
```

```
U:..myjava>java Exerciselc Siobhan
Hello Siobhan
U:..myjava>java Exerciselc
Exception in thread main java.lang.ArrayIndexOutOfBoundsException: 0
    at Exerciselc.main(Exerciselc.java:3)
```


Summary of key points

- Arrays allow us to store and manipulate collections of data
- They are declared using `new`
`int[] myArray = new int[5];`
- Or using their contents
`int[] myArray = {1, 2, 3};`
- To access individual elements of an array, we use `an index` in the range 0 to one less than the number of elements in the array (`myArray.length`)
- For loops, provide a mechanism for sequentially accessing the elements of an array including the `enhanced for` loop
`for (int i : myArray)...`
- Arrays can be searched and sorted
- We can declare and use multidimensional arrays but be careful which dimension is which

