









-3/16in - 130 ADJUSTER SCREW 5/64in [2.0mm] HEX 3 PLACES 1.00in [25.4mm] TYP

NOTE:

1) THE MOUNT BASE INCLUDES (2) Ø 2mm ALIGNMENT PIN FEATURES FOR SETTING A PRECISION LOCATION AND ANGLE. A STANDARD "DIN 7-m6 GROUND DOWEL PIN (Ø2.002mm TO Ø2.008mm X 0.050" +/-0.005" DEEP) IS RECOMMENDED. 2) THE RECOMMENDED TOLERANCE FOR THE LOCATION OF THE DOWEL PIN HOLES AND MOUNTING THREADED HOLE IS ±0.003in

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

	DRAWING PROJECTION			THORLARS www.thorlabs.com		
		NAME	DATE			
	REDRAWN	GM	19/MAR/14	POLARIS Ø 1/2" MIRROR MOUNT		
	APPROVAL	BD	01/APR/14	MATERIAL N/A		REV
	COPYRIGHT © 2014 BY THORLABS			14/7		E
	VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			POLARIS-K05	0.024 kg	