Practical 6.1: Write a JSP page that displays the current date and time.

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>
<%@ page import="java.util.Date" %>
<!DOCTYPE html>
<html>
<head><meta charset="UTF-8"><title>JSP Current Time</title></head>
<body>
   <h1>Current Server Time</h1>
   <p>
      <%
         Date currentTime = new Date();
      %>
      <%= currentTime %>
   </p>
</body>
</html>
```

Practical 6.2 Write JSP files that accept a number from the HTML form and displays whether it's even or odd

EvenOdd.html

```
<html>
<head>
<title>TODO supply a title</title>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width">
</head>
<body>
<form method="get" action="EvenOdd.jsp">
<input type ="text" name="t1" value="">
<input type ="submit" value="ok">
</form>
</body></html>
```

EvenOdd.jsp code:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>JSP Page</title>
</head>
<body>
<h1>Even Odd Example</h1>
<%
int i, n;
n=Integer.parseInt(request.getParameter("t1"));
if(n%2==0)
            out.print(n+" is even");
 else
            out.print(n+" is odd");
%>
</body>
</html>
```

Practical 7.1 Write JSP files that accept a number from the HTML form and display it's factorial.

Fact.html

```
<html>
<head>
<title>TODO supply a title</title>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width">
</head>
<body>
<form method="get" action="Fact.jsp">
<input type ="text" name="t1" value="">
<input type ="submit" value="ok">
</form>
</body></html>
```

Fact.jsp code:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>JSP Page</title>
</head>
<body>
<h1>Factorial Example</h1>
<%
        int i, n, fact=1;
        n=Integer.parseInt(request.getParameter("t1"));
        for(i=1;i<=n;i++)
                fact=fact*i;
        out.print("<br>factorial of"+n+"is"+fact);
%>
</body></html>
```

Practical 7.2 Write JSP files that accept a number from the HTML form and display its Multiplication Table.

Mult.html

```
<html>
<head>
<title>TODO supply a title</title>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width">
</head>
<body>
<form method="get" action="Mult.jsp">
<input type ="text" name="t1" value="">
<input type ="submit" value="ok">
</form>
</body></html>
```

Mult.jsp code:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>JSP Page</title>
</head>
<body>
<h1>Multiplication Table</h1>
<%
        int i,n,m,fact=1;
        out.print("<br>multiplication Table");
            for(i=1;i<=10;i++)
        {
                m=n*i;
                out.print("<br>"+n+"*"+i+"="+m);
             }
%>
</body></html>
```

Practical 8.1 Write a JSP page, which displays three text boxes for Department Number, Department Name and Location. On click of the submit button call another JSP page which will enter the values in the database with the help of PreparedStatement class. Also use jspInit() and jspDestroy() to open and close the connection. (Register.jsp).

DeptForm.jsp

```
<html>
<Head><title>Department Form</title>
</head>
<body>
<form method=GET action="http://localhost:8080/Register1.jsp">
<table>
<tr><td>DepartmentNo:  </td><td> <input type=text
name=txtNo></td></tr>
<tr><td>DepartmentName: </td><td><input type=text
name=txtName></td></tr>
<tr><td>Location:</td><td> <input type=text name=txtLoc></td></tr>
</table>
<input type=submit name=Submit>
<input type=reset name=Reset>
</Form>
</body>
</Html>
```

Register1.jsp

```
<%@ page import="java.sql.*" %>
<%! String a,b,c,d,e,f,Query; %>
<%! Connection con;
Statement st;
PreparedStatement ps; %>
<%! int i,num; %>

<%!
public void jspInit()
{
try
{
Class.forName("sun.jdbc.odbc.JdbcOdbcDriver");
con=DriverManager.getConnection("jdbc:odbc:ty289");
st=con.createStatement();
Query="insert into Dept values(?,?,?)";
```

```
ps=con.prepareStatement(Query);
}
catch(Exception e){System.out.println("Error: "+e.getMessage());}
}
%>
<%
a=(String)request.getParameter("txtNo");
b=(String)request.getParameter("txtName");
c=(String)request.getParameter("txtLoc");
ps.setInt(1,Integer.parseInt(a));
ps.setString(2,b);
ps.setString(3,c);
ps.executeUpdate();
con.commit();
ResultSet rs=st.executeQuery("select * from Dept");
%>
<html><body>
<table border=1>
<tr><th>Dept No </th><th>Dept Name</th><th>Location</th></tr>
<%
        while(rs.next())
        {
%>
        <tr>
<%      for(int j=0;j<=2;j++)
        {
                Object obj=rs.getObject(j+1);
%>
        <td><%=obj.toString()%></td>
<%
        }
        }
%>
</tr>
</table>
<%!
        public void jspDestroy()
{   try
        {
                ps.close();
        st.close();
```

```
        }
        catch(Exception e){System.out.println("Error: "+e.getMessage());}
}%>
</body>
</html>
```

Practical 8.2 Write a JSP page to accept two numbers (m,n) from the user, on click of the submit button display on a new JSP page all prime numbers between m and n. If the number m is not less than n (m<n), it should redirect to a different error page having link to the JSP form.

Index.html code:

```
<html>
<head>
<title>TO DO supply a title</title>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width">
</head>
<body>
<form method="get" action="prime.jsp" name="form2">
Enter first number:      <input type ="text" name="t1" value=""><br>
Enter second number:  <input type ="text" name="t2" value="">
<input type ="submit" value="ok">
</form>
</body>
</html>
```

Prime.jsp code:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title> JSP Page </title>
</head>
<body>
<h1>Hello World!</h1>
<%int i,j,m,n,flag;
        m=Integer.parseInt(request.getParameter("t1"));
        n=Integer.parseInt(request.getParameter("t2"));
        if(m>n)
        {
%>
<jsp:forward page="Error.jsp"/>
<%
}
else
```

```
{
        for(i=m;i<=n;i++)
        {
                flag=0;
                for(j=2;j<i;j++)
                {
                        if(i%j==0)
                        {
                                flag=1;
                                break;
                        }
                }//if j
                if(flag==0)
                        out.print(""+i);
        }//if i
}//else
%>
</body>
</html>
```

Error.jsp

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>jsp Page</title>
</head>
<body>
<h1>Hello World!</h1>
<a href="index1.html">go to form</a>
</body>
</html>
```