```
USERFRIENDLY COMMANDS IN SQL:
1. TO CLEAR SCREEN : CLEAR SCREEN;

2. TO SEE ALL TABLES: SELECT * FROM TAB;

3. TO SEE TABLE STRUCTURE: DESC TABLE_NAME;

4. TO SAVE VALUES IN TABLE:
   AFTER EVERY INSERT TYPE AT PROMPT : COMMIT;

5. TO EXECUTE PREVIOUSLY EXECUTED COMMAND: /

6. TO UNDO THE PREVIOISULY EXECUTED COMMAND: ROLLBACK



SELECT * FROM TABLE_NAME;

INSERT INTO TABLE_NAME VALUES(...., ....,...);

CREATE TABLE DEMO
(
ID INT,
NAME VARCHAR(10)
);

STATIC METHOD:
INSERT INTO DEMO VALUES(1,'AMIT');
INSERT INTO DEMO VALUES(2,'SAMIT');
INSERT INTO DEMO VALUES(3,'RAJ');
INSERT INTO DEMO VALUES(4,'POOJA');

DYNAMIC METHOD:
INSERT INTO DEMO VALUES(&ID,'&NAME');


CREATE TABLE DEMO1
(
 ID INT NOT NULL,
 NAME VARCHAR(10)
);

INSERT INTO DEMO1 VALUES(&ID,'&NAME');

CREATE TABLE DEMO2
(
 ID INT UNIQUE,
 NAME VARCHAR(10)
);

INSERT INTO DEMO2 VALUES(&ID,'&NAME');

CREATE TABLE DEMO3
  (
   ID INT NOT NULL,
   NAME VARCHAR(10),
```

```
  AGE INT CHECK(AGE>=18)
 );

INSERT INTO DEMO3 VALUES(&ID,'&NAME',&AGE);




SELECT *          - ATTRIBUTES
FROM TABLE_NAME - TABLES
WHERE CONDITION; - CONDITION
```