

Dissecting Different Flavors of Generic Programming in One Haskell Universe

Presented to Galois

Sean Leather

Utrecht University

August 27, 2013

What is Generic Programming?

What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

- Java/C# generics

What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

- Java/C# generics
- C++ templates

What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

- Java/C# generics
- C++ templates
- Ada generic packages

What is Generic Programming?

The goal is often the same.

A higher level of abstraction than “normally” available

What is Generic Programming?

The goal is often the same.

A higher level of abstraction than “normally” available

The technique is also often the same.

Some form of parameterization and instantiation

Examples of Generic Programming

Java/C#:

```
public class Stack<T>
{
    public void push(T item) {...}
    public T pop() {...}
}
```

Examples of Generic Programming

C++:

```
template<typename T, typename Compare>
T& min(T& a, T& b, Compare comp) {
    if (comp(b, a))
        return b;
    return a;
}
```

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

In Haskell:

- Both forms already exist.

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

In Haskell:

- Both forms already exist.
- We don't call them generics because they're native to the language.

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

In Haskell:

- Both forms already exist.
- We don't call them generics because they're native to the language.

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

In Haskell:

- Both forms already exist.
- We don't call them generics because they're native to the language.

Datatype-generic programming:

- Abstract over the *structure of a datatype*

Generic Programming in Haskell

In other words:

- Java-style generics \approx parametric polymorphism
- C++ templates \approx ad-hoc polymorphism

In Haskell:

- Both forms already exist.
- We don't call them generics because they're native to the language.

Datatype-generic programming:

- Abstract over the *structure of a datatype*
- Also known as “polytypism” and “shape-/structure-polymorphism”

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)
- **Fields**: types for each constructor (≥ 0)

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)
- **Fields**: types for each constructor (≥ 0)

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)
- **Fields**: types for each constructor (≥ 0)

Non-syntactic features:

- Recursion

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)
- **Fields**: types for each constructor (≥ 0)

Non-syntactic features:

- Recursion
- Nesting

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)
- **Fields**: types for each constructor (≥ 0)

Non-syntactic features:

- Recursion
- Nesting

Datatypes

```
data D p = Alt1 | Alt2 Int p
```

A datatype can have:

- **Parameters**: type variables (≥ 0)
- **Alternatives**: unique constructors (≥ 0)
- **Fields**: types for each constructor (≥ 0)

Non-syntactic features:

- Recursion
- Nesting

There are other features of datatypes, but we will consider only the above as a foundation for looking at the structure.

Structure of Datatypes: Sums

First structural element: alternatives.

```
data AltEx2 = A1 Int | A2 Char
```

Structure of Datatypes: Sums

First structural element: alternatives.

```
data AltEx2 = A1 Int | A2 Char
```

Note that the above is similar to a standard type:

```
data Either a b = Left a | Right b
```

Structure of Datatypes: Sums

First structural element: alternatives.

```
data AltEx2 = A1 Int | A2 Char
```

Note that the above is similar to a standard type:

```
data Either a b = Left a | Right b
```

And we can, in fact, model `AltEx2` as:

```
type AltEx'2 = Either Int Char
```

with the following “smart” constructors:

```
a1 :: Int → AltEx'2  
a1 = Left
```

```
a2 :: Char → AltEx'2  
a2 = Right
```

Structure of Datatypes: Sums

When talking about alternatives in structural sense, we often call them **sums**. `Either` is the basic binary sum type. For conciseness, we use this (identical) binary sum type:

```
data a :+: b = L a | R b
```

Structure of Datatypes: Sums

When talking about alternatives in structural sense, we often call them **sums**. `Either` is the basic binary sum type. For conciseness, we use this (identical) binary sum type:

```
data a :+: b = L a | R b
```

What about a type with < 2 alternatives?

```
data AltEx3 = B1 Int | B2 Char | B3 Float
```


Structure of Datatypes: Sums

When talking about alternatives in structural sense, we often call them **sums**. `Either` is the basic binary sum type. For conciseness, we use this (identical) binary sum type:

```
data a :+: b = L a | R b
```

What about a type with < 2 alternatives?

```
data AltEx3 = B1 Int | B2 Char | B3 Float
```

The simplest solution is to nest one binary sum inside another:

```
type AltEx'3 = Int :+: (Char :+: Float)
```

Note that:

$$b_3 :: \text{Float} \rightarrow \text{AltEx}'_3$$
$$b_3 = R \circ R$$

Structure of Datatypes: Products

Next: fields.

```
data FldEx2 = FldEx2 Int Char
```

Structure of Datatypes: Products

Next: fields.

```
data FldEx2 = FldEx2 Int Char
```

Again, note the similarity to a standard type, the pair:

```
data (,) a b = (,) a b
```

Structure of Datatypes: Products

Next: fields.

```
data FldEx2 = FldEx2 Int Char
```

Again, note the similarity to a standard type, the pair:

```
data (,) a b = (,) a b
```

And again, we model `FldEx2` similarly:

```
type FldEx'2 = (,) Int Char
```

with the smart constructor:

```
fldEx'2 :: Int → Char → FldEx'2  
fldEx'2 = (,)
```

Structure of Datatypes: Products

The pair type is the basic binary **product** type. For symmetry with sums, we will use the following type:

```
data a :×: b = a :×: b
```

Structure of Datatypes: Products

The pair type is the basic binary **product** type. For symmetry with sums, we will use the following type:

```
data a :×: b = a :×: b
```

And more than two fields...

```
data FldEx3 = FldEx3 Int Char Float
```

Structure of Datatypes: Products

The pair type is the basic binary **product** type. For symmetry with sums, we will use the following type:

```
data a × b = a × b
```

And more than two fields...

```
data FldEx3 = FldEx3 Int Char Float
```

... are modeled by nested binary products:

```
type FldEx'3 = Int × (Char × Float)
```

with the smart constructor:

```
fldEx'3 :: Int → Char → Float → FldEx'3  
fldEx'3 x y z = x × (y × z)
```

Structure of Datatypes: Sums of Products

To “sum” it all up, recall the first datatype example:

```
data D p = Alt1 | Alt2 Int p
```


Structure of Datatypes: Sums of Products

To “sum” it all up, recall the first datatype example:

```
data D p = Alt1 | Alt2 Int p
```

We can define an identical type using the sum and product types we have just discussed:

```
type RepD p = U :+: Int :×: p
```

Structure of Datatypes: Sums of Products

To “sum” it all up, recall the first datatype example:

```
data D p = Alt1 | Alt2 Int p
```

We can define an identical type using the sum and product types we have just discussed:

```
type RepD p = U :+: Int :×: p
```

Notes:

- We use the “unit” type `data U = U` (identical to the standard type `()`) to represent an alternative without fields.

Structure of Datatypes: Sums of Products

To “sum” it all up, recall the first datatype example:

```
data D p = Alt1 | Alt2 Int p
```

We can define an identical type using the sum and product types we have just discussed:

```
type RepD p = U :+: Int :×: p
```

Notes:

- We use the “unit” type `data U = U` (identical to the standard type `()`) to represent an alternative without fields.
- `:+:` is **infix** 5, and `:×:` is **infix** 6, so we can write `RepD` naturally, without unnecessary parentheses.

Structure of Datatypes: Isomorphism

So, we think we can model datatypes. But how do we know Rep_D accurately models D ?

Structure of Datatypes: Isomorphism

So, we think we can model datatypes. But how do we know Rep_D accurately models D ?

We define an **isomorphism**: two total functions that convert between types.

Structure of Datatypes: Isomorphism

So, we think we can model datatypes. But how do we know Rep_D accurately models D ?

We define an **isomorphism**: two total functions that convert between types.

```
fromD :: D p → RepD p
fromD Alt1          = L U
fromD (Alt2 i p)    = R (i :: p)

toD :: RepD p → D p
toD (L U)           = Alt1
toD (R (i :: p)) = Alt2 i p
```

Structure of Datatypes: Isomorphism

So, we think we can model datatypes. But how do we know Rep_D accurately models D ?

We define an **isomorphism**: two total functions that convert between types.

```
fromD :: D p → RepD p
fromD Alt1          = L U
fromD (Alt2 i p)    = R (i :: p)

toD :: RepD p → D p
toD (L U)           = Alt1
toD (R (i :: p))    = Alt2 i p
```

This allows us to convert terms between (1) the familiar datatype and (2) the **structure representation** used for generic operations.

Structure of Datatypes: Constructors

Oh, but there's one more thing...

Structure of Datatypes: Constructors

Oh, but there's one more thing...

You may have noticed the representation lacked any information about the constructors (e.g. the names).

Structure of Datatypes: Constructors

Oh, but there's one more thing...

You may have noticed the representation lacked any information about the constructors (e.g. the names).

That's easily repaired with another datatype:

```
data C a = C String a
```

Structure of Datatypes: Constructors

Oh, but there's one more thing...

You may have noticed the representation lacked any information about the constructors (e.g. the names).

That's easily repaired with another datatype:

```
data C a = C String a
```

We modify the representation to store constructor names:

```
type RepD p = C U :+: C (Int ×: p)  
fromD Alt1      = L (C "Alt1" U)  
fromD (Alt2 i p) = R (C "Alt2" (i ×: p))
```

Structure of Datatypes: Constructors

Oh, but there's one more thing...

You may have noticed the representation lacked any information about the constructors (e.g. the names).

That's easily repaired with another datatype:

```
data C a = C String a
```

We modify the representation to store constructor names:

```
type RepD p = C U :+: C (Int ×: p)  
fromD Alt1      = L (C "Alt1" U)  
fromD (Alt2 i p) = R (C "Alt2" (i ×: p))
```

We could also put additional metadata (e.g. fixity) into C.

Generic Functions

Okay, so we have a structure representation. But what can we *do* with it?

Generic Functions

Okay, so we have a structure representation. But what can we *do* with it?

Generic functions

- Defined on each possible case of the structure representation

Generic Functions

Okay, so we have a structure representation. But what can we *do* with it?

Generic functions

- Defined on each possible case of the structure representation
- Work for every datatype that has an isomorphism with a structure representation

Generic Functions

Okay, so we have a structure representation. But what can we *do* with it?

Generic functions

- Defined on each possible case of the structure representation
- Work for every datatype that has an isomorphism with a structure representation

Generic Functions

Okay, so we have a structure representation. But what can we *do* with it?

Generic functions

- Defined on each possible case of the structure representation
- Work for every datatype that has an isomorphism with a structure representation

Example: `show :: a → String`

Generic Functions: `show`

We define a `show` function for each possible structure case.

Generic Functions: `show`

We define a `show` function for each possible structure case.

Unit:

```
showU :: U → String
```

```
showU U = ""
```

Generic Functions: `show`

We define a `show` function for each possible structure case.

Unit:

```
showU :: U → String  
showU U = ""
```

Constructor name:

```
showC :: (a → String) → C a → String  
showC showa (C nm a) =  
  "(" ++ nm ++ " " ++ showa a ++ ")"
```

Generic Functions: `show`

We define a `show` function for each possible structure case.

Unit:

```
showU :: U → String  
showU U = ""
```

Constructor name:

```
showC :: (a → String) → C a → String  
showC showa (C nm a) =  
  "(" ++ nm ++ " " ++ showa a ++ ")"
```

Binary product:

```
show× :: (a → String) → (b → String) → a × b → String  
show× showa showb (a × b) = showa a ++ " " ++ showb b
```

Generic Functions: `show`

We define a `show` function for each possible structure case.

Unit:

```
showU :: U → String  
showU U = ""
```

Constructor name:

```
showC :: (a → String) → C a → String  
showC showa (C nm a) =  
  "(" ++ nm ++ " " ++ showa a ++ ")"
```

Binary product:

```
show× :: (a → String) → (b → String) → a :× b → String  
show× showa showb (a :× b) = showa a ++ " " ++ showb b
```

Binary sum:

```
show+ :: (a → String) → (b → String) → a :+ b → String  
show+ showa _ (L a) = showa a  
show+ _ showb (R b) = showb b
```

Generic Functions: `show`

We can define a `show` function for `RepD` (assuming `showInt`):

```
showRepD :: (p → String) → RepD p → String
showRepD showp =
  show+ (showC showU) (showC (show× showInt showp))
```

Generic Functions: `show`

We can define a `show` function for `RepD` (assuming `showInt`):

```
showRepD :: (p → String) → RepD p → String
showRepD showp =
    show+ (showC showU) (showC (show× showInt showp))
```

The `show` function for `D` is just a hop away:

```
showD :: (p → String) → D p → String
showD showp = showRepD showp ∘ fromD
```


Generic Functions: `show`

```
showRepD :: (p → String) → RepD p → String  
showRepD showp =  
  show+ (showC showU) (showC (show× showInt showp))
```

Some observations:

- This is a sort of predictable pattern (or recipe) for defining `show` functions on structure representations.

Generic Functions: `show`

```
showRepD :: (p → String) → RepD p → String  
showRepD showp =  
  show+ (showC showU) (showC (show× showInt showp))
```

Some observations:

- This is a sort of predictable pattern (or recipe) for defining `show` functions on structure representations.
- The functions are recursive but not in the usual way because the argument types differ.

Generic Functions: `show`

```
showRepD :: (p → String) → RepD p → String  
showRepD showp =  
  show+ (showC showU) (showC (show× showInt showp))
```

Some observations:

- This is a sort of predictable pattern (or recipe) for defining `show` functions on structure representations.
- The functions are recursive but not in the usual way because the argument types differ.
- Each datatype can have a unique structure representation, and we want to support all combinations, *generically*.

Generic Functions, Generically

In order to jump into “true” genericity (where the structure is a parameter instead of a pattern), we need several additional things:

Generic Functions, Generically

In order to jump into “true” genericity (where the structure is a parameter instead of a pattern), we need several additional things:

- **Polymorphic recursion** – functions with a common scheme that reference each other and allow types to change in the calls

Generic Functions, Generically

In order to jump into “true” genericity (where the structure is a parameter instead of a pattern), we need several additional things:

- **Polymorphic recursion** – functions with a common scheme that reference each other and allow types to change in the calls

Generic Functions, Generically

In order to jump into “true” genericity (where the structure is a parameter instead of a pattern), we need several additional things:

- **Polymorphic recursion** – functions with a common scheme that reference each other and allow types to change in the calls

```
showU ::      U      → String
showC :: ... ⇒ C a    → String
show+ :: ... ⇒ a :+: b → String
...
```

- A common encoding for isomorphisms

Generic Functions, Generically

In order to jump into “true” genericity (where the structure is a parameter instead of a pattern), we need several additional things:

- **Polymorphic recursion** – functions with a common scheme that reference each other and allow types to change in the calls

```
showU ::      U      → String
showC :: ... ⇒ C a    → String
show+ :: ... ⇒ a :+: b → String
...
```

- A common encoding for isomorphisms

Generic Functions, Generically

In order to jump into “true” genericity (where the structure is a parameter instead of a pattern), we need several additional things:

- **Polymorphic recursion** – functions with a common scheme that reference each other and allow types to change in the calls

```
showU ::      U      → String
showC :: ... ⇒ C a    → String
show+ :: ... ⇒ a :+: b → String
...
```

- A common encoding for isomorphisms

```
data T      = ...  -- User-defined datatype
type RepT = ...  -- Structure representation
from  :: T → RepT
to    :: RepT → T
```

Polymorphic Recursion

There are several ways to encode polymorphic recursion. We will use type classes.

Polymorphic Recursion

There are several ways to encode polymorphic recursion. We will use type classes.

- Standard classes already use polymorphic recursion for deriving instances: `Show`, `Eq`, etc.

Polymorphic Recursion

There are several ways to encode polymorphic recursion. We will use type classes.

- Standard classes already use polymorphic recursion for deriving instances: `Show`, `Eq`, etc.
- The class declaration specifies the type signature.

Polymorphic Recursion

There are several ways to encode polymorphic recursion. We will use type classes.

- Standard classes already use polymorphic recursion for deriving instances: `Show` , `Eq` , etc.
- The class declaration specifies the type signature.
- Each recursive case is specified by an instance of the class.

Polymorphic Recursion

There are several ways to encode polymorphic recursion. We will use type classes.

- Standard classes already use polymorphic recursion for deriving instances: `Show` , `Eq` , etc.
- The class declaration specifies the type signature.
- Each recursive case is specified by an instance of the class.

Polymorphic Recursion

There are several ways to encode polymorphic recursion. We will use type classes.

- Standard classes already use polymorphic recursion for deriving instances: `Show`, `Eq`, etc.
- The class declaration specifies the type signature.
- Each recursive case is specified by an instance of the class.

A simplified definition of the `Show` class:

```
class Show a where  
  show :: a → String
```

Polymorphic Recursion

The instances for each structure representation case:

Polymorphic Recursion

The instances for each structure representation case:

Unit:

```
instance Show U where  
  show = showU
```

Polymorphic Recursion

The instances for each structure representation case:

Unit:

```
instance Show U where  
  show = showU
```

Constructor name:

```
instance Show a  $\Rightarrow$  Show (C a) where  
  show = showC show
```

Polymorphic Recursion

The instances for each structure representation case:

Unit:

```
instance Show U where  
  show = showU
```

Constructor name:

```
instance Show a  $\Rightarrow$  Show (C a) where  
  show = showC show
```

Binary product:

```
instance (Show a, Show b)  $\Rightarrow$  Show (a  $\times$  b) where  
  show = show $\times$  show show
```

Polymorphic Recursion

The instances for each structure representation case:

Unit:

```
instance Show U where  
  show = showU
```

Constructor name:

```
instance Show a  $\Rightarrow$  Show (C a) where  
  show = showC show
```

Binary product:

```
instance (Show a, Show b)  $\Rightarrow$  Show (a  $\times$  b) where  
  show = show $\times$  show show
```

Binary sum:

```
instance (Show a, Show b)  $\Rightarrow$  Show (a  $+$  b) where  
  show = show+ show show
```

Polymorphic Recursion

Now, recall `showRepD` :

```
showRepD :: (p → String) → RepD p → String  
showRepD showp =  
  show+ (showC showU) (showC (show× showInt showp))
```

Polymorphic Recursion

Now, recall `showRepD` :

```
showRepD :: (p → String) → RepD p → String
showRepD showp =
  show+ (showC showU) (showC (show× showInt showp))
```

Compare to the new version that is now possible:

```
show'RepD :: Show p ⇒ RepD p → String
show'RepD = show
```

Encoding Isomorphisms

To define the `show` function for `D`, we still need to define another function:

$$\begin{aligned} \text{show}'_D &:: \text{Show } p \Rightarrow D \, p \rightarrow \text{String} \\ \text{show}'_D &= \text{show}'_{\text{Rep}_D} \circ \text{from}_D \end{aligned}$$

Encoding Isomorphisms

To define the `show` function for `D`, we still need to define another function:

$$\begin{aligned} \text{show}'_D &:: \text{Show } p \Rightarrow D \text{ } p \rightarrow \text{String} \\ \text{show}'_D &= \text{show}'_{\text{Rep}_D} \circ \text{from}_D \end{aligned}$$

Next goal:

- Define one `show` function that knows how to convert any type `T` to its structure representation type `RepT`, given an isomorphism between `T` and `RepT`.

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype T and its structure representation Rep_T :

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype T and its structure representation Rep_T :

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype T and its structure representation Rep_T :

$\text{from} :: T \rightarrow \text{Rep}_T$

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype T and its structure representation Rep_T :

$\text{from} :: T \rightarrow \text{Rep}_T$

$\text{to} :: \text{Rep}_T \rightarrow T$

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype `T` and its structure representation `RepT`:

`from :: T → RepT`

`to :: RepT → T`

- Each requires two types, so each instance must have two types (unlike the `Show` instances which needed only the structure representation type).

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype T and its structure representation Rep_T :

$\text{from} :: T \rightarrow \text{Rep}_T$

$\text{to} :: \text{Rep}_T \rightarrow T$

- Each requires two types, so each instance must have two types (unlike the `Show` instances which needed only the structure representation type).
- Rep_T is precisely determined by T , so really we only need one unique type and a second type derivable from the first.

Encoding Isomorphisms

We define a class of function pairs.

- We again use a type class, but with the addition of a *type family*.
- Each function pair implements an isomorphism between a datatype T and its structure representation Rep_T :

$\text{from} :: T \rightarrow \text{Rep}_T$

$\text{to} :: \text{Rep}_T \rightarrow T$

- Each requires two types, so each instance must have two types (unlike the `Show` instances which needed only the structure representation type).
- Rep_T is precisely determined by T , so really we only need one unique type and a second type derivable from the first.
- In this case, a (1) multiparameter type class with a functional dependency and a (2) type class with a type family are equally expressive. (It's a matter of taste, really.)

Encoding Isomorphisms

The type class:

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```

Encoding Isomorphisms

The type class:

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```

- `Rep` is a type family or, more precisely, an associated type synonym.

Encoding Isomorphisms

The type class:

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```

- `Rep` is a type family or, more precisely, an associated type synonym.
- Think of `Rep` as a function on types. Given a unique type (index) `T`, you get a type (synonym) `Rep T`.

Encoding Isomorphisms

The type class:

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```

- `Rep` is a type family or, more precisely, an associated type synonym.
- Think of `Rep` as a function on types. Given a unique type (index) `T`, you get a type (synonym) `Rep T`.
- Note that `Rep T` need not be different from `Rep U` even though `T` and `U` are different.

Encoding Isomorphisms

The type class:

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```

- `Rep` is a type family or, more precisely, an associated type synonym.
- Think of `Rep` as a function on types. Given a unique type (index) `T`, you get a type (synonym) `Rep T`.
- Note that `Rep T` need not be different from `Rep U` even though `T` and `U` are different.
- Concretely: two datatypes may have the same representation.

Encoding Isomorphisms

We need `Generic` instances for every datatype that we want to use with generic functions.

Encoding Isomorphisms

We need `Generic` instances for every datatype that we want to use with generic functions.

The instance for `D` uses definitions that we've already seen:

```
instance Generic (D p) where  
  type Rep (D p) = RepD p  
  from = fromD  
  to   = toD
```

Encoding Isomorphisms

We need `Generic` instances for every datatype that we want to use with generic functions.

The instance for `D` uses definitions that we've already seen:

```
instance Generic (D p) where  
  type Rep (D p) = RepD p  
  from = fromD  
  to   = toD
```

- Other instances are defined similarly.

Encoding Isomorphisms

We need `Generic` instances for every datatype that we want to use with generic functions.

The instance for `D` uses definitions that we've already seen:

```
instance Generic (D p) where  
  type Rep (D p) = RepD p  
  from = fromD  
  to   = toD
```

- Other instances are defined similarly.
- In fact, `Rep T`, `from`, and `to` are precisely determined by the definition of `T`, so these instances can be automatically generated (e.g. using Template Haskell or a preprocessor).

The Generic `show` Function

Finally:

```
gshow :: (Show (Rep a), Generic a) => a -> String
gshow = show o from
```

GP in General

- Datatype-generic programming:

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here
 - ▶ Generic Deriving – GHC \geq 7.2, similar to Instant Generics

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here
 - ▶ Generic Deriving – GHC \geq 7.2, similar to Instant Generics
 - ▶ EMGM – maintained by me

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here
 - ▶ Generic Deriving – GHC \geq 7.2, similar to Instant Generics
 - ▶ EMGM – maintained by me
 - ▶ Regular – folds, etc.

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here
 - ▶ Generic Deriving – GHC \geq 7.2, similar to Instant Generics
 - ▶ EMGM – maintained by me
 - ▶ Regular – folds, etc.
 - ▶ Multirec – mutually recursive datatypes, folds, etc.

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here
 - ▶ Generic Deriving – GHC \geq 7.2, similar to Instant Generics
 - ▶ EMGM – maintained by me
 - ▶ Regular – folds, etc.
 - ▶ Multirec – mutually recursive datatypes, folds, etc.
 - ▶ Scrap Your Boilerplate (SYB) – GHC, traversals, queries

GP in General

- Datatype-generic programming:
 - ▶ Datatype is the parameter
 - ▶ Instantiation gives you a large class of generic functions
- Many generic functions:
 - ▶ Pretty-printing (`show`) and parsing (`read`)
 - ▶ Compression, serialization, and the reverse
 - ▶ Comparison, equality
 - ▶ Folds (catamorphisms), unfolds (anamorphisms), maps, zips, zippers
 - ▶ Traversals, updates, queries
- Many different libraries:
 - ▶ Instant Generics – presented here
 - ▶ Generic Deriving – GHC \geq 7.2, similar to Instant Generics
 - ▶ EMGM – maintained by me
 - ▶ Regular – folds, etc.
 - ▶ Multirec – mutually recursive datatypes, folds, etc.
 - ▶ Scrap Your Boilerplate (SYB) – GHC, traversals, queries
 - ▶ ...

References

Generic Programming in Haskell:

- Johan Jeuring, Sean Leather, José Pedro Magalhães, Alexey Rodriguez Yakushev. *Libraries for Generic Programming in Haskell*. AFP 2008. pp. 165-229, 2009.
- Generic Deriving:
<http://www.haskell.org/haskellwiki/GHC.Generics>