

# Dissecting Different Flavors of Generic Programming in One Haskell Universe

Presented to Galois

Sean Leather

Utrecht University

August 27, 2013

# What is Generic Programming?

# What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

# What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

- Java/C# generics

# What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

- Java/C# generics
- C++ templates

# What is Generic Programming?

In programming languages, the adjective “generic” is heavily overloaded.

- Java/C# generics
- C++ templates
- Ada generic packages

# What is Generic Programming?

The goal is often the same.

A higher level of abstraction than “normally” available

# What is Generic Programming?

The goal is often the same.

A higher level of abstraction than “normally” available

The technique is also often similar.

Some form of parameterization and instantiation



# Examples of Generic Programming

Java/C#:

```
public class Stack<T>
{
    public void push(T item) {...}
    public T pop() {...}
}
```

# Examples of Generic Programming

Java/C#:

```
public class Stack<T>
{
    public void push(T item) {...}
    public T pop() {...}
}
```

In other words:

- Java-style generics  $\approx$  parametric polymorphism

# Examples of Generic Programming

C++:

```
template<typename T, typename Compare>
T& min(T& a, T& b, Compare comp) {
    if (comp(b, a))
        return b;
    return a;
}
```

# Examples of Generic Programming

C++:

```
template<typename T, typename Compare>
T& min(T& a, T& b, Compare comp) {
    if (comp(b, a))
        return b;
    return a;
}
```

In other words:

- C++ templates  $\approx$  ad-hoc polymorphism

# Generic Programming in Haskell

“Generic programming”:

- For other languages, the term tends to be used for late additions.

# Generic Programming in Haskell

“Generic programming”:

- For other languages, the term tends to be used for late additions.
- Parametric and ad-hoc polymorphism were available in Haskell from the beginning.

# Generic Programming in Haskell

“Generic programming”:

- For other languages, the term tends to be used for late additions.
- Parametric and ad-hoc polymorphism were available in Haskell from the beginning.

# Generic Programming in Haskell

“Generic programming”:

- For other languages, the term tends to be used for late additions.
- Parametric and ad-hoc polymorphism were available in Haskell from the beginning.

In Haskell, we have come to use “generic programming” for **datatype-generic programming** (a.k.a. “polytypism” or “shape/structure polymorphism”).



# Datatype-Generic Programming

What is datatype-generic programming?

- Parameterize a function over the *structure* of datatypes

# Datatype-Generic Programming

What is datatype-generic programming?

- Parameterize a function over the *structure* of datatypes
- Instantiate the function with a particular type

# Datatype-Generic Programming

What is datatype-generic programming?

- Parameterize a function over the *structure* of datatypes
- Instantiate the function with a particular type

# Datatype-Generic Programming

What is datatype-generic programming?

- Parameterize a function over the *structure* of datatypes
- Instantiate the function with a particular type

The result is a function that

- **works with many types** (polymorphism) but

# Datatype-Generic Programming

What is datatype-generic programming?

- Parameterize a function over the *structure* of datatypes
- Instantiate the function with a particular type

The result is a function that

- **works with many types** (polymorphism) but
- **uses knowledge of the type** (unlike parametric) and

# Datatype-Generic Programming

What is datatype-generic programming?

- Parameterize a function over the *structure* of datatypes
- Instantiate the function with a particular type

The result is a function that

- **works with many types** (polymorphism) but
- **uses knowledge of the type** (unlike parametric) and
- **need not be redefined for every type** (unlike ad-hoc).

# Generic Functions

## Applications

- Pretty-printing (e.g. `show`), parsing (e.g. `read`)

# Generic Functions

## Applications

- Pretty-printing (e.g. `show`), parsing (e.g. `read`)
- Compression, serialization, marshalling (and their inverses)



# Generic Functions

## Applications

- Pretty-printing (e.g. `show`), parsing (e.g. `read`)
- Compression, serialization, marshalling (and their inverses)
- Comparison, equality

# Generic Functions

## Applications

- Pretty-printing (e.g. `show`), parsing (e.g. `read`)
- Compression, serialization, marshalling (and their inverses)
- Comparison, equality
- (Co-)recursion, map, zip, zippers

# Generic Functions

## Applications

- Pretty-printing (e.g. `show`), parsing (e.g. `read`)
- Compression, serialization, marshallng (and their inverses)
- Comparison, equality
- (Co-)recursion, map, zip, zippers
- Traversals, queries, updates

# Generic Platforms

Many different implementations:

- Preprocessors:

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell
- Libraries

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell
- Libraries
  - ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time



# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell
- Libraries
  - ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time
  - ▶ Uniplate – similar to SYB but faster and less expressive

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell
- Libraries
  - ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time
  - ▶ Uniplate – similar to SYB but faster and less expressive
  - ▶ EMGM – fast sums-of-products

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell
- Libraries
  - ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time
  - ▶ Uniplate – similar to SYB but faster and less expressive
  - ▶ EMGM – fast sums-of-products
  - ▶ Regular – recursion schemes

# Generic Platforms

Many different implementations:

- Preprocessors:
  - ▶ PolyP
  - ▶ Generic Haskell
- Libraries
  - ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time
  - ▶ Uniplate – similar to SYB but faster and less expressive
  - ▶ EMGM – fast sums-of-products
  - ▶ Regular – recursion schemes
  - ▶ Multirec – mutually recursive datatypes

# Generic Platforms

Many different implementations:

- Preprocessors:

- ▶ PolyP
- ▶ Generic Haskell

- Libraries

- ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time
- ▶ Uniplate – similar to SYB but faster and less expressive
- ▶ EMGM – fast sums-of-products
- ▶ Regular – recursion schemes
- ▶ Multirec – mutually recursive datatypes
- ▶ Generic Deriving – available in GHC  $\geq 7.2$ , similar to Instant Generics

# Generic Platforms

Many different implementations:

- Preprocessors:

- ▶ PolyP
- ▶ Generic Haskell

- Libraries

- ▶ Scrap Your Boilerplate (SYB) – included with GHC for a long time
- ▶ Uniplate – similar to SYB but faster and less expressive
- ▶ EMGM – fast sums-of-products
- ▶ Regular – recursion schemes
- ▶ Multirec – mutually recursive datatypes
- ▶ Generic Deriving – available in GHC  $\geq 7.2$ , similar to Instant Generics
- ▶ (and many, many more)

# Generic Flavors

The implementations can be grouped into flavors depending on how they view the structure of a datatype.

# Generic Flavors

The implementations can be grouped into flavors depending on how they view the structure of a datatype.

Some flavors (or views):

**Spine** A constructor is a sequence of types.

Example: SYB



# Generic Flavors

The implementations can be grouped into flavors depending on how they view the structure of a datatype.

Some flavors (or views):

**Spine** A constructor is a sequence of types.

Example: SYB

**Sums-of-products** A datatype is a collection of alternative tuples of types.

Example: Generic Deriving

# Generic Flavors

The implementations can be grouped into flavors depending on how they view the structure of a datatype.

Some flavors (or views):

**Spine** A constructor is a sequence of types.

Example: SYB

**Sums-of-products** A datatype is a collection of alternative tuples of types.

Example: Generic Deriving

**Fixed-point** A datatype is a sums-of-products with recursive points.

Example: Multirec

# Dissecting a Datatype: Sums-of-Products

```
data Tsum = A1 | A2
```

A datatype can have:

- **Alternatives:** unique constructors ( $\geq 0$ )

# Dissecting a Datatype: Sums-of-Products

```
data Tprod = P2 Char Int
```

A datatype can have:

- **Fields**: types for each constructor ( $\geq 0$ )

# Dissecting a Datatype: Sums-of-Products

Other features that are modeled:

- Constant types: each type in a field
- Parameters: type variables ( $\geq 0$ )

# Dissecting a Datatype: Sums-of-Products

Other features that are modeled:

- Constant types: each type in a field
- Parameters: type variables ( $\geq 0$ )

Features that are not modeled:

- Recursion
- Nesting (though it can be)

# Modeling a Sum

To model (nested) alternatives:

```
data Either a b = Left a | Right b
```

# Modeling a Sum

To model (nested) alternatives:

```
data Either a b = Left a | Right b
```

For syntactic elegance:

```
data a :+: b = L a | R b
```



# Modeling a Product

To model (nested) fields:

```
data (,) a b = (,) a b
```

# Modeling a Product

To model (nested) fields:

```
data (,) a b = (,) a b
```

For syntactic elegance:

```
data a :×: b = a :×: b
```

# Modeling Other Structures

A constructor without fields:

```
data U = U
```

# Modeling Other Structures

A constructor without fields:

```
data U = U
```

A constructor name:

```
data C a = C String a
```

# Modeling Other Structures

A constructor without fields:

```
data U = U
```

A constructor name:

```
data C a = C String a
```

A field type:

```
data K a = K a
```

# Modeling Other Structures

A constructor without fields:

```
data U = U
```

A constructor name:

```
data C a = C String a
```

A field type:

```
data K a = K a
```

Note: There are other features of datatypes, but we consider only the above.

# Modeling an Example

An example datatype:

```
data E a = E1 | E2 a (E a) Int
```

# Modeling an Example

An example datatype:

```
data E a = E1 | E2 a (E a) Int
```

The corresponding **structure representation type**:

```
type RepE a = C U :+: C (K a :×: K (E a) :×: K Int)
```



# Modeling an Example

An example datatype:

```
data E a = E1 | E2 a (E a) Int
```

The corresponding **structure representation type**:

```
type RepE a = C U :+: C (K a :×: K (E a) :×: K Int)
```

Notes:

- `:+:` is **infixr 5** and `:×:` is **infixr 6**.
- Operators nest to the right.

# Converting Between Types: Isomorphism

- Generic functions work on the sums-of-products model.

# Converting Between Types: Isomorphism

- Generic functions work on the sums-of-products model.
- But first we need to convert between the model and the actual value of the datatype.

# Converting Between Types: Isomorphism

- Generic functions work on the sums-of-products model.
- But first we need to convert between the model and the actual value of the datatype.
- We define an **isomorphism**: two total, dual functions.

# Converting Between Types: Isomorphism

- Generic functions work on the sums-of-products model.
- But first we need to convert between the model and the actual value of the datatype.
- We define an **isomorphism**: two total, dual functions.

# Converting Between Types: Isomorphism

- Generic functions work on the sums-of-products model.
- But first we need to convert between the model and the actual value of the datatype.
- We define an **isomorphism**: two total, dual functions.

```
from_E :: E a → Rep_E a
from_E E1      = L (C "E1" U)
from_E (E2 x e i) = R (C "E2" ((K x) :×: (K e) :×: (K i)))
```

# Converting Between Types: Isomorphism

- Generic functions work on the sums-of-products model.
- But first we need to convert between the model and the actual value of the datatype.
- We define an **isomorphism**: two total, dual functions.

```
fromE :: E a → RepE a
fromE E1           = L (C "E1" U)
fromE (E2 x e i) = R (C "E2" ((K x) :×: (K e) :×: (K i)))
```

```
toE :: RepE a → E a
toE (L (C "E1" U))           = E1
toE (R (C "E2" ((K x) :×: (K e) :×: (K i)))) = E2 x e i
```

# Converting Between Types: Isomorphism

For convenience, we join the representation type and isomorphism in a type class `Generic` with an associated type synonym `Rep`.

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```



# Converting Between Types: Isomorphism

For convenience, we join the representation type and isomorphism in a type class `Generic` with an associated type synonym `Rep`.

```
class Generic a where  
  type Rep a  
  from :: a → Rep a  
  to   :: Rep a → a
```

The instance for `E`:

```
instance Generic (E a) where  
  type Rep (E a) = RepE a  
  from = fromE  
  to   = toE
```

# Generic Functions

A **generic function**

- Is defined on each case of the structure representation and

# Generic Functions

A **generic function**

- Is defined on each case of the structure representation and
- Works for every datatype that has a structure representation and isomorphism.

# Generic Functions

A **generic function**

- Is defined on each case of the structure representation and
- Works for every datatype that has a structure representation and isomorphism.

# Generic Functions

A **generic function**

- Is defined on each case of the structure representation and
- Works for every datatype that has a structure representation and isomorphism.

Example: `showRep a :: a → String`

- We define a `show` function for each case.

# Defining `show`

Unit:

```
showU :: U → String
```

```
showU U = ""
```

# Defining `show`

Unit:

```
showU :: U → String  
showU U = ""
```

Constructor name:

```
showC :: (a → String) → C a → String  
showC showa (C nm a) = "(" ++ nm ++ " " ++ showa a ++ ")"
```

# Defining `show`

Unit:

```
showU :: U → String  
showU U = ""
```

Constructor name:

```
showC :: (a → String) → C a → String  
showC showa (C nm a) = "(" ++ nm ++ " " ++ showa a ++ ")"
```

Field:

```
showK :: (a → String) → K a → String  
showK showa (K a) = showa a
```



# Defining `show`

Binary sum:

$$\text{show}_+ :: (a \rightarrow \text{String}) \rightarrow (b \rightarrow \text{String}) \rightarrow a :+ b \rightarrow \text{String}$$
$$\text{show}_+ \text{ show}_a - (\text{L } a) = \text{show}_a a$$
$$\text{show}_+ - \text{show}_b (\text{R } b) = \text{show}_b b$$

# Defining `show`

Binary sum:

```
show+ :: (a → String) → (b → String) → a :+: b → String
show+ showa (L a) = showa a
show+ showb (R b) = showb b
```

Binary product:

```
show× :: (a → String) → (b → String) → a :×: b → String
show× showa showb (a :×: b) = showa a ++ " " ++ showb b
```

# Defining `show`

Recall:

```
type RepE a = C U :+: C (K a :×: K (E a) :×: K Int)
```

We can define a `show` function (assuming `showInt`):

```
showRepE :: (a → String) → ((a → String) → E a → String)  
           → RepE a → String
```

```
showRepE showa showE =  
  show+ (showC showU)  
        (showC (show× (showK showa)  
                      (show× (showK (showE showa)) (showK showInt))))))
```

# Defining `show`

```
showRepE :: (a → String) → ((a → String) → E a → String)
              → RepE a → String

showRepE showa showE =
  show+ (showC showU)
        (showC (show× (showK showa)
                      (show× (showK (showE showa)) (showK showInt))))))
```

The `showE` function itself is just an isomorphism away:

```
showE :: (a → String) → E a → String
showE showa = showRepE showa showE ∘ fromE
```

# Defining `show`

```
showRepE :: (a → String) → ((a → String) → E a → String)
           → RepE a → String

showRepE showa showE =
  show+ (showC showU)
        (showC (show× (showK showa)
                      (show× (showK (showE showa)) (showK showInt))))))
```

Some observations:

- This is **not** a generic function.

# Defining `show`

```
showRepE :: (a → String) → ((a → String) → E a → String)  
          → RepE a → String  
  
showRepE showa showE =  
  show+ (showC showU)  
        (showC (show× (showK showa)  
                      (show× (showK (showE showa)) (showK showInt))))))
```

Some observations:

- This is **not** a generic function.
- It is defined on the structure of `E`, not on datatypes in general.

# Defining `show`

```
showRepE :: (a → String) → ((a → String) → E a → String)
           → RepE a → String

showRepE showa showE =
  show+ (showC showU)
        (showC (show× (showK showa)
                      (show× (showK (showE showa)) (showK showInt))))))
```

Some observations:

- This is **not** a generic function.
- It is defined on the structure of `E`, not on datatypes in general.
- It demonstrates a predictable pattern for defining the generic function.

# Defining `show`

Consider these typical expressions and their types:

```
showC showU :: C U → String  
show× (showK showInt) (showK showChar) :: (K Int :×: K Char) → String
```

- `show?` functions call other `show?` functions.



# Defining `show`

Consider these typical expressions and their types:

```
showC showU :: C U → String  
show× (showK showInt) (showK showChar) :: (K Int :×: K Char) → String
```

- `show?` functions call other `show?` functions.
- They can be considered recursive but not in the usual way.

# Defining `show`

Consider these typical expressions and their types:

```
showC showU :: C U → String
show× (showK showInt) (showK showChar) :: (K Int → K Char) → String
```

- `show?` functions call other `show?` functions.
- They can be considered recursive but not in the usual way.
- **Polymorphic recursion** – functions with different types that have a common scheme that reference each other

# Defining `show`

There are several ways to encode polymorphic recursion. We use type classes.

# Defining `show`

There are several ways to encode polymorphic recursion. We use type classes.

- The class declaration specifies the type signature.

# Defining `show`

There are several ways to encode polymorphic recursion. We use type classes.

- The class declaration specifies the type signature.
- Each recursive (type) case is specified by an instance of the class.

# Defining `show`

There are several ways to encode polymorphic recursion. We use type classes.

- The class declaration specifies the type signature.
- Each recursive (type) case is specified by an instance of the class.

# Defining `show`

There are several ways to encode polymorphic recursion. We use type classes.

- The class declaration specifies the type signature.
- Each recursive (type) case is specified by an instance of the class.

A simplified definition of the `Show` class:

```
class Show a where  
  show :: a → String
```

# Defining `show`

Some of the instances for each structure representation case:



# Defining `show`

Some of the instances for each structure representation case:

Constructor name:

```
instance Show a  $\Rightarrow$  Show (C a) where  
  show = showC show
```

# Defining `show`

Some of the instances for each structure representation case:

Constructor name:

```
instance Show a  $\Rightarrow$  Show (C a) where  
  show = showC show
```

Binary sum:

```
instance (Show a, Show b)  $\Rightarrow$  Show (a :+: b) where  
  show = show+ show show
```

# Defining `show`

Some of the instances for each structure representation case:

Constructor name:

```
instance Show a  $\Rightarrow$  Show (C a) where  
  show = showC show
```

Binary sum:

```
instance (Show a, Show b)  $\Rightarrow$  Show (a :+: b) where  
  show = show+ show show
```

The remaining instances are straightforward.

# Defining `show`

Now, compare:

```
showRepE :: (a → String) → ((a → String) → E a → String)
              → RepE a → String

showRepE showa showE =
  show+ (showC showU)
        (showC (show× (showK showa)
                      (show× (showK (showE showa)) (showK showInt))))))
```

# Defining `show`

Now, compare:

```
showRepE :: (a → String) → ((a → String) → E a → String)
              → RepE a → String

showRepE showa showE =
  show+ (showC showU)
        (showC (show× (showK showa)
                      (show× (showK (showE showa)) (showK showInt))))))
```

To:

```
showRepE :: (Show a, Show (E a)) ⇒ RepE a → String
showRepE = show
```

# Defining `show`

Finally, we can use a slightly different `Show` class to support generic functions for any type that has a representation.

# Defining `show`

Finally, we can use a slightly different `Show` class to support generic functions for any type that has a representation.

**class** `Show` **where**

`show :: a → String`

**default** `show :: (Generic a, Show (Rep a)) ⇒ a → String`

`show = show ∘ from`

- This uses the `DefaultSignatures` language extension: if type `a` has the instances `Show (Rep a)` and `Generic a`, then the given definition is used.

# Defining `show`

Finally, we can use a slightly different `Show` class to support generic functions for any type that has a representation.

**class** `Show` **a where**

`show :: a → String`

**default** `show :: (Generic a, Show (Rep a)) ⇒ a → String`

`show = show ∘ from`

- This uses the `DefaultSignatures` language extension: if type `a` has the instances `Show (Rep a)` and `Generic a`, then the given definition is used.

The instance for `E`:

**instance** `Show a ⇒ Show (E a)`



# Sums-of-Products and Beyond

We presented a sums-of-products view.

- We used Haskell2010 plus a few GHC language extensions:

```
{-# LANGUAGE TypeFamilies #-}  
{-# LANGUAGE TypeOperators #-}  
{-# LANGUAGE FlexibleContexts #-}  
{-# LANGUAGE DefaultSignatures #-}
```

# Sums-of-Products and Beyond

We presented a sums-of-products view.

- We used Haskell2010 plus a few GHC language extensions:

```
{-# LANGUAGE TypeFamilies #-}  
{-# LANGUAGE TypeOperators #-}  
{-# LANGUAGE FlexibleContexts #-}  
{-# LANGUAGE DefaultSignatures #-}
```

- Typically, a GP library does not support another view.

# Sums-of-Products and Beyond

We presented a sums-of-products view.

- We used Haskell2010 plus a few GHC language extensions:

```
{-# LANGUAGE TypeFamilies #-}  
{-# LANGUAGE TypeOperators #-}  
{-# LANGUAGE FlexibleContexts #-}  
{-# LANGUAGE DefaultSignatures #-}
```

- Typically, a GP library does not support another view.
- But we can, with a few more extensions:

```
{-# LANGUAGE FlexibleInstances #-}  
{-# LANGUAGE MultiParamTypeClasses #-}  
{-# LANGUAGE OverlappingInstances #-}
```

# The Uniplate View

- Uniplate uses a simplified spine view.

# The Uniplate View

- Uniplate uses a simplified spine view.
- The spine is the sequence of fields in a constructor.

# The Uniplate View

- Uniplate uses a simplified spine view.
- The spine is the sequence of fields in a constructor.
- SYB models the “full” spine, i.e. all fields (which can naturally have different types).

# The Uniplate View

- Uniplate uses a simplified spine view.
- The spine is the sequence of fields in a constructor.
- SYB models the “full” spine, i.e. all fields (which can naturally have different types).
- Uniplate models only a list of the (recursive) children (which have the same type).

# Defining `descend`

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.



# Defining `descend`

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.
- `descend` performs a traversal of the children and applies a function to each one.

# Defining descend

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.
- `descend` performs a traversal of the children and applies a function to each one.
- We use the following signature:

```
class Uniplate a where  
  descend :: (a → a) → a → a
```

# Defining descend

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.
- `descend` performs a traversal of the children and applies a function to each one.
- We use the following signature:

```
class Uniplate a where  
  descend :: (a → a) → a → a
```

- Note that we must traverse every field to determine whether that field is a child or not. (`Uniplate` does this in an ad-hoc way.)

# Defining descend

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.
- `descend` performs a traversal of the children and applies a function to each one.
- We use the following signature:

```
class Uniplate where  
  descend :: (a → a) → a → a
```

- Note that we must traverse every field to determine whether that field is a child or not. (`Uniplate` does this in an ad-hoc way.)
- Our generic function must support:

# Defining descend

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.
- `descend` performs a traversal of the children and applies a function to each one.
- We use the following signature:

```
class Uniplate a where  
  descend :: (a → a) → a → a
```

- Note that we must traverse every field to determine whether that field is a child or not. (Uniplate does this in an ad-hoc way.)
- Our generic function must support:
  - ▶ Polymorphic recursion on the structure (as usual) *and*

# Defining descend

- We define the function `descend` from `Uniplate` to demonstrate that our library can model the simplified spine view.
- `descend` performs a traversal of the children and applies a function to each one.
- We use the following signature:

```
class Uniplate a where  
  descend :: (a → a) → a → a
```

- Note that we must traverse every field to determine whether that field is a child or not. (Uniplate does this in an ad-hoc way.)
- Our generic function must support:
  - ▶ Polymorphic recursion on the structure (as usual) *and*
  - ▶ A function parameter whose type matches only some of the fields.

# Defining `descend'`

Consequently, we use a signature with different types for the function parameter and the structure representation:

```
class Uniplate' a r where  
  descend' :: (r → r) → a → a
```

# Defining `descend'`

Consequently, we use a signature with different types for the function parameter and the structure representation:

```
class Uniplate' a r where  
  descend' :: (r → r) → a → a
```

- We need the function parameter type (`r`) in the `Uniplate'` class.



# Defining `descend'`

Consequently, we use a signature with different types for the function parameter and the structure representation:

```
class Uniplate' a r where  
  descend' :: (r → r) → a → a
```

- We need the function parameter type (`r`) in the `Uniplate'` class.
- We will come back to `Uniplate` later.

# Defining `descend'`

Most of the instances are straightforward:

```
instance Uniplate' U where  
  descend' _ U = U
```

# Defining `descend'`

Most of the instances are straightforward:

```
instance Uniplate' U a where  
  descend' _ U = U
```

```
instance Uniplate' a r  $\Rightarrow$  Uniplate' (C a) r where  
  descend' f (C nm a) = C nm (descend' f a)
```

# Defining `descend'`

Most of the instances are straightforward:

```
instance Uniplate' U a where  
  descend' _ U = U
```

```
instance Uniplate' a r  $\Rightarrow$  Uniplate' (C a) r where  
  descend' f (C nm a) = C nm (descend' f a)
```

```
instance (Uniplate' a r, Uniplate' b r)  $\Rightarrow$  Uniplate' (a :+: b) r where  
  descend' f (L a) = L (descend' f a)  
  descend' f (R b) = R (descend' f b)
```

# Defining `descend'`

Most of the instances are straightforward:

```
instance Uniplate' U a where  
  descend' _ U = U
```

```
instance Uniplate' a r  $\Rightarrow$  Uniplate' (C a) r where  
  descend' f (C nm a) = C nm (descend' f a)
```

```
instance (Uniplate' a r, Uniplate' b r)  $\Rightarrow$  Uniplate' (a :+: b) r where  
  descend' f (L a) = L (descend' f a)  
  descend' f (R b) = R (descend' f b)
```

```
instance (Uniplate' a r, Uniplate' b r)  $\Rightarrow$  Uniplate' (a : $\times$ : b) r where  
  descend' f (a : $\times$ : b) = descend' f a : $\times$ : descend' f b
```

# Defining descend'

It is the `K` instance that is interesting.

# Defining `descend'`

It is the `K` instance that is interesting.

Because there is a fall-back instance:

```
instance Uniplate' (K a) r where  
  descend' _ (K a) = K a
```

# Defining `descend'`

It is the `K` instance that is interesting.

Because there is a fall-back instance:

```
instance Uniplate' (K a) r where  
  descend' _ (K a) = K a
```

And an instance where we apply the function parameter:

```
instance Uniplate' (K a) a where  
  descend' f (K a) = K (f a)
```

- Note the matching types `a` in the header.



# Defining `descend'`

It is the `K` instance that is interesting.

Because there is a fall-back instance:

```
instance Uniplate' (K a) r where  
  descend' _ (K a) = K a
```

And an instance where we apply the function parameter:

```
instance Uniplate' (K a) a where  
  descend' f (K a) = K (f a)
```

- Note the matching types `a` in the header.
- Overlapping instances implies type equality.

# Defining `descend'`

It is the `K` instance that is interesting.

Because there is a fall-back instance:

```
instance Uniplate' (K a) r where  
  descend' _ (K a) = K a
```

And an instance where we apply the function parameter:

```
instance Uniplate' (K a) a where  
  descend' f (K a) = K (f a)
```

- Note the matching types `a` in the header.
- Overlapping instances implies type equality.
- This is the “trick” that allows us to determine when to choose this instance.

# Defining descend

Coming back to an improved `Uniplate` class:

```
class Uniplate a where
```

```
  descend :: (a → a) → a → a
```

```
  default descend :: (Generic a, Uniplate' (Rep a) a) ⇒ (a → a) → a → a
```

```
  descend f = to ∘ descend' f ∘ from
```

- We again use `DefaultSignatures` to simplify instantiation.

# Defining descend

Coming back to an improved `Uniplate` class:

```
class Uniplate a where
```

```
  descend :: (a → a) → a → a
```

```
  default descend :: (Generic a, Uniplate' (Rep a) a) ⇒ (a → a) → a → a
```

```
  descend f = to ∘ descend' f ∘ from
```

- We again use `DefaultSignatures` to simplify instantiation.
- The types of the function parameter and generic parameter are the same.

# Defining descend

Coming back to an improved `Uniplate` class:

```
class Uniplate a where
```

```
  descend :: (a → a) → a → a
```

```
default descend :: (Generic a, Uniplate' (Rep a) a) ⇒ (a → a) → a → a  
descend f = to ∘ descend' f ∘ from
```

- We again use `DefaultSignatures` to simplify instantiation.
- The types of the function parameter and generic parameter are the same.
- They only differ “behind the scenes.”

# Uniplate View and Beyond

We presented a traversal function

- From Uniplate (which is not a sums-of-products library)

# Uniplate View and Beyond

We presented a traversal function

- From Uniplate (which is not a sums-of-products library)
- In a library with a sums-of-products view

# Uniplate View and Beyond

We presented a traversal function

- From Uniplate (which is not a sums-of-products library)
- In a library with a sums-of-products view
- Extended with overlapping instances (and type equality in particular).



# Uniplate View and Beyond

We presented a traversal function

- From Uniplate (which is not a sums-of-products library)
- In a library with a sums-of-products view
- Extended with overlapping instances (and type equality in particular).

# Uniplate View and Beyond

We presented a traversal function

- From Uniplate (which is not a sums-of-products library)
- In a library with a sums-of-products view
- Extended with overlapping instances (and type equality in particular).

With a bit more work, we can also define functions that work on all fields and not just the recursive children, e.g.:

```
topDown :: C b a  $\Rightarrow$  (a  $\rightarrow$  a)  $\rightarrow$  b  $\rightarrow$  b
```

- For a class `C` that supports matching on any type `T` for which there is an instance `C T T`

# Uniplate View and Beyond

We presented a traversal function

- From Uniplate (which is not a sums-of-products library)
- In a library with a sums-of-products view
- Extended with overlapping instances (and type equality in particular).

With a bit more work, we can also define functions that work on all fields and not just the recursive children, e.g.:

```
topDown :: C b a  $\Rightarrow$  (a  $\rightarrow$  a)  $\rightarrow$  b  $\rightarrow$  b
```

- For a class `C` that supports matching on any type `T` for which there is an instance `C T T`
- Similar to the function `everywhere'` in SYB

# The Fixed-Point View

- We can use the type equality trick to model the fixed-point view in our library.

# The Fixed-Point View

- We can use the type equality trick to model the fixed-point view in our library.
- The fixed-point view typically extends the sums-of-products view with an explicit indicator of recursive points in the structure.

# The Fixed-Point View

- We can use the type equality trick to model the fixed-point view in our library.
- The fixed-point view typically extends the sums-of-products view with an explicit indicator of recursive points in the structure.
- In the basic sums-of-products view, recursion occurs on the structure but not on the datatype.

# The Fixed-Point View

- We can use the type equality trick to model the fixed-point view in our library.
- The fixed-point view typically extends the sums-of-products view with an explicit indicator of recursive points in the structure.
- In the basic sums-of-products view, recursion occurs on the structure but not on the datatype.
- In the basic fixed-point view, we define one case of a generic function on the recursive points structural element.

# The Fixed-Point View

- We can use the type equality trick to model the fixed-point view in our library.
- The fixed-point view typically extends the sums-of-products view with an explicit indicator of recursive points in the structure.
- In the basic sums-of-products view, recursion occurs on the structure but not on the datatype.
- In the basic fixed-point view, we define one case of a generic function on the recursive points structural element.
- In our library, we pass the top-level type `T` through the type cases.



# The Fixed-Point View

- We can use the type equality trick to model the fixed-point view in our library.
- The fixed-point view typically extends the sums-of-products view with an explicit indicator of recursive points in the structure.
- In the basic sums-of-products view, recursion occurs on the structure but not on the datatype.
- In the basic fixed-point view, we define one case of a generic function on the recursive points structural element.
- In our library, we pass the top-level type `T` through the type cases.
- The case at which we can match on `T` is the recursive point.

# Defining fold

- We define the function `fold` (catamorphism).

# Defining fold

- We define the function `fold` (catamorphism).
- `fold` iterates from the root of a value to its leaves and builds up a new result based on the recursive structure of the input.

# Defining fold

- We define the function `fold` (catamorphism).
- `fold` iterates from the root of a value to its leaves and builds up a new result based on the recursive structure of the input.
- We use the following signature:

```
class Fold a where  
  fold :: Alg (Rep a) r → a → r
```

# Defining fold

- We define the function `fold` (catamorphism).
- `fold` iterates from the root of a value to its leaves and builds up a new result based on the recursive structure of the input.
- We use the following signature:

**class** Fold a **where**

`fold :: Alg (Rep a) r → a → r`

- Given an algebra and a value, compute the result of applying the algebra to the structure of the value.

# Defining Alg

The algebra of the fold is a type family:

```
type family Alg a r
```

```
type instance Alg U           r = r
```

```
type instance Alg (K a)      r = Either a r → r
```

```
type instance Alg (C a)      r = Alg a r
```

```
type instance Alg (a :+: b)  r = (Alg a r, Alg b r)
```

```
type instance Alg (K a :×: b) r = Either a r → Alg b r
```

- `Alg` is indexed on the representation type of the input type `a`.

# Defining Alg

The algebra of the fold is a type family:

```
type family Alg a r
```

```
type instance Alg U           r = r
```

```
type instance Alg (K a)       r = Either a r → r
```

```
type instance Alg (C a)       r = Alg a r
```

```
type instance Alg (a :+: b)    r = (Alg a r, Alg b r)
```

```
type instance Alg (K a :×: b) r = Either a r → Alg b r
```

- `Alg` is indexed on the representation type of the input type `a`.
- The type `r` is the result of the fold.

# Defining Alg

The algebra of the fold is a type family:

```
type family Alg a r
```

```
type instance Alg U           r = r
```

```
type instance Alg (K a)       r = Either a r → r
```

```
type instance Alg (C a)       r = Alg a r
```

```
type instance Alg (a :+: b)    r = (Alg a r, Alg b r)
```

```
type instance Alg (K a :×: b) r = Either a r → Alg b r
```

- `Alg` is indexed on the representation type of the input type `a`.
- The type `r` is the result of the fold.
- `K` types can be either non-recursive (`a`) or recursive (`r`) points.



# Defining Alg

For the example type:

```
type RepE a = C U :+: C (K a :×: K (E a) :×: K Int)
```

The algebra type is:

```
type instance Alg (Rep (E a)) r =  
  (r, Either a r → Either (E a) r → Either Int r → r)
```

- `E a` is the recursive point, even though it does not appear so in the type.

# Defining Alg

For the example type:

```
type RepE a = C U :+: C (K a :×: K (E a) :×: K Int)
```

The algebra type is:

```
type instance Alg (Rep (E a)) r =  
  (r, Either a r → Either (E a) r → Either Int r → r)
```

- `E a` is the recursive point, even though it does not appear so in the type.
- The instances of the generic function ensure the separation of non-recursive and recursive `K` cases.

# Defining Fold'

We again define a helper generic function:

```
class Fold' a t where
```

```
  fold' :: proxy t → Alg (Rep t) r → Alg a r → a → r
```

- `a` is the structure type.

# Defining Fold'

We again define a helper generic function:

```
class Fold' a t where
```

```
  fold' :: proxy t → Alg (Rep t) r → Alg a r → a → r
```

- `a` is the structure type.
- `t` is the recursive type.

# Defining Fold'

We again define a helper generic function:

```
class Fold' a t where
```

```
  fold' :: proxy t → Alg (Rep t) r → Alg a r → a → r
```

- `a` is the structure type.
- `t` is the recursive type.
- The “proxy” provides proof of `t` while preventing the instances of `Fold'` from using it.

# Defining Fold'

The instances that do not have recursion:

**instance** Fold' U t **where**

fold' \_ \_ alg U = alg

**instance** Fold' a t  $\Rightarrow$  Fold' (C a) t **where**

fold' p palg alg (C \_ a) = fold' p palg alg a

**instance** (Fold' a t, Fold' b t)  $\Rightarrow$  Fold' (a :+: b) t **where**

fold' p palg (alg, \_) (L a) = fold' p palg alg a

fold' p palg (\_, alg) (R b) = fold' p palg alg b

# Defining Fold'

The fall-back `K` instance:

```
instance Fold' (K a) t where  
  fold' p _ alg (K a) = alg (Left a)
```

# Defining Fold'

The fall-back `K` instance:

```
instance Fold' (K a) t where  
  fold' p _ alg (K a) = alg (Left a)
```

The recursive `K` instance:

```
instance Fold t  $\Rightarrow$  Fold' (K t) t where  
  fold' p palg alg (K t) = alg (Right (fold palg t))
```



# Defining Fold'

The fall-back `:×` instance:

```
instance Fold' b t  $\Rightarrow$  Fold' (K a : $\times$ : b) t where  
  fold' p palg alg (K a : $\times$ : b) = fold' p palg (alg (Left a)) b
```

# Defining Fold'

The fall-back `:×` instance:

```
instance Fold' b t  $\Rightarrow$  Fold' (K a : $\times$ : b) t where  
  fold' p palg alg (K a : $\times$ : b) = fold' p palg (alg (Left a)) b
```

The recursive `:×` instance:

```
instance (Fold t, Fold' b t)  $\Rightarrow$  Fold' (K t : $\times$ : b) t where  
  fold' p palg alg (K a : $\times$ : b) = fold' p palg (alg (Right (fold palg a))) b
```

# Defining fold

The improved `Fold` class:

```
class Fold a where
```

```
  fold :: Alg (Rep a) r → a → r
```

```
  default fold :: (Generic a, Fold' (Rep a) a) ⇒ Alg (Rep a) r → a → r
```

```
  fold alg x = fold' (Just x) alg alg (from x)
```

- We use `Maybe` as a simple proxy.

# Defining fold

The improved `Fold` class:

```
class Fold a where
```

```
  fold :: Alg (Rep a) r → a → r
```

```
  default fold :: (Generic a, Fold' (Rep a) a) ⇒ Alg (Rep a) r → a → r
```

```
  fold alg x = fold' (Just x) alg alg (from x)
```

- We use `Maybe` as a simple proxy.
- The algebra is needed twice: the second argument is pattern-matched by the instances of `Fold'`.

# Fold and Beyond

We presented a generic recursive pattern in a library that would not typically have it.

- We can also define many other (co-)recursive functions, including the generic zipper.

# Fold and Beyond

We presented a generic recursive pattern in a library that would not typically have it.

- We can also define many other (co-)recursive functions, including the generic zipper.
- The unfortunate aspect of `Alg` is that we must use `Either` since, in the type family, we cannot distinguish overlapping instances.

# Fold and Beyond

We presented a generic recursive pattern in a library that would not typically have it.

- We can also define many other (co-)recursive functions, including the generic zipper.
- The unfortunate aspect of `Alg` is that we must use `Either` since, in the type family, we cannot distinguish overlapping instances.
- We believe this can be fixed with the new ordered overlapping instances in GHC.

# Conclusions

- We believe generic programming is easy to understand if looked at from the right perspective.



# Conclusions

- We believe generic programming is easy to understand if looked at from the right perspective.
- We are still searching for that optimal view.

# Conclusions

- We believe generic programming is easy to understand if looked at from the right perspective.
- We are still searching for that optimal view.
- The library presented here is quite simple.

# Conclusions

- We believe generic programming is easy to understand if looked at from the right perspective.
- We are still searching for that optimal view.
- The library presented here is quite simple.
- Yet, with a few tricks, it is also quite powerful.

# Conclusions

- We believe generic programming is easy to understand if looked at from the right perspective.
- We are still searching for that optimal view.
- The library presented here is quite simple.
- Yet, with a few tricks, it is also quite powerful.
- We have also done this work in the more complicated Generic Deriving library.

# References

- Johan Jeuring, Sean Leather, José Pedro Magalhães, Alexey Rodriguez Yakushev. *Libraries for Generic Programming in Haskell*. AFP 2008. pp. 165-229, 2009.
- Generic Deriving:  
<http://www.haskell.org/haskellwiki/GHC.Generics>
- Generic Deriving Extras:  
<https://github.com/spl/generic-deriving-extras>