

CSE105/209A: Modern Algorithmic Toolbox,*

PSET-1

Instructions: Deadline in **7 days from day of posting, 11:59pm**. Prepare a pdf of your solutions, with your name and ucsc id number. Feel free to discuss solutions with your colleagues (other students), explore the internet, read and be inspired from the textbooks etc. But what you type should be typed by you and you only in latex. In algorithms, we appreciate brevity and accuracy: your solutions should be to the point, often one or two sentences suffice to provide all necessary details and descriptions. Unnecessarily long answers will not get full credit. You will submit your pdf either on canvas or gradescope, more details to follow.

Ex.1 (20pts) (Graphs and Matrices)

Throughout this exercise we think of the adjacency representation of an undirected graph G with n vertices and m edges. Each entry $A[i, j]$ in the adjacency matrix A is 1 **if and only if** the edge (i, j) is present (if the edge (i, j) is not present, let's say the entry is 0). All diagonal entries in A are 0 since there are no self-loops.

1. For a cycle on 5 nodes, write down explicitly its adjacency matrix. Compute and write down A^2, A^3 .

$$A = \begin{pmatrix} 0 & 1 & 0 & 0 & 1 \\ 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 \\ 1 & 0 & 0 & 1 & 0 \end{pmatrix} \quad (1)$$

$$A^2 = \begin{pmatrix} 2 & 0 & 1 & 1 & 0 \\ 0 & 2 & 0 & 1 & 1 \\ 1 & 0 & 2 & 0 & 1 \\ 1 & 1 & 0 & 2 & 0 \\ 0 & 1 & 1 & 0 & 2 \end{pmatrix}$$

$$A^3 = \begin{pmatrix} 0 & 3 & 1 & 1 & 3 \\ 3 & 0 & 3 & 1 & 1 \\ 1 & 3 & 0 & 3 & 1 \\ 1 & 1 & 3 & 0 & 3 \\ 3 & 1 & 1 & 3 & 0 \end{pmatrix}$$

*PI: Vaggos Chatziafratis

2. For a path on 5 nodes, write down explicitly its adjacency matrix. Compute and write down A^2, A^3 .

$$A = \begin{pmatrix} 0 & 1 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 \\ 0 & 0 & 0 & 1 & 0 \end{pmatrix}$$

$$A^2 = \begin{pmatrix} 1 & 0 & 1 & 0 & 0 \\ 0 & 2 & 0 & 1 & 0 \\ 1 & 0 & 2 & 0 & 1 \\ 0 & 1 & 0 & 2 & 0 \\ 0 & 0 & 1 & 0 & 1 \end{pmatrix}$$

$$A^3 = \begin{pmatrix} 0 & 2 & 0 & 1 & 0 \\ 2 & 0 & 3 & 0 & 1 \\ 0 & 3 & 0 & 3 & 0 \\ 1 & 0 & 3 & 0 & 2 \\ 0 & 1 & 0 & 2 & 0 \end{pmatrix}$$

3. Generally, suppose you are given a cycle on n nodes. Start from A and keep multiplying it with itself until you get matrix $B = A^k$ for some integer number k . What is the smallest value of k such that all of B 's non-diagonal entries are non-zero? (Hint: maybe different answer for odd or even n .)

solution

If the cycle has an even number of nodes, the nondiagonals will never become all nonzero. every node cycles between being reachable and not reachable in the cycle.

if a cycle has an odd number of nodes, the nondiagonals will take $n - 1$ steps to be all nonzero. It takes at least $n - 1$ steps to ensure the direct neighbors of the starting vertex are always occupied at least once on all subsequent walk lengths.

4. Generally, suppose you are given a path on n nodes. Start from A and keep multiplying it with itself until you get matrix $C = A^k$ for some integer number k . What is the smallest value of k such that all of B 's non-diagonal entries are non-zero? (Hint: maybe different answer for odd or even n , or maybe not...)

solution

Note a path is bipartite. Every step goes from right to left, or left to right, thus it is impossible for one to reach every node on even or odd step lengths.

5. **BONUS:** How would your answers above change if the graphs were directed instead?

solution

the solutions that are false remain false. the odd numbered cycle also becomes false since there is only one path at every step.

For this exercise, we don't require a formal proof, but we want to see some sufficiently justified explanation for your responses based on what we discussed in class.

Ex.2 (20pts) (BFS, but slower)

Imagine you are given a graph G with adjacency matrix A , but you forgot how to implement the BFS algorithm. But luckily you have access to MatMul, a programming language that only allows you to do matrix multiplications, and check any entry that you want from A or the subsequent multiplications with itself.

1. How would you check whether there is a node of degree 2023 in the graph?

solution

square the adjacency matrix, then check along the diagonal if there is a value of 2023. Paths of length two that reach back to the original node are in direct correspondance with the degree of the vertex.

2. How would you count the triangles in the graph?

solution

as discussed in class, cubing the matrix, summing the trace then dividing by 6 results in the triangle count. the diagonal along the matrix after cubing the matrix gives the paths of length 3 back to the original node, which is a triangle. these triangles are sextuple counted since each triangle has 3 vertices, and the paths can go in two directions.

3. How would you check whether or not the graph is connected?

solution

Ex.3 (20pts) (Bipartite and Traces)

Prove that an undirected graph is bipartite if and only if the following holds:

$$\text{trace}(A^{2k+1}) = 0, \forall k \in \mathbf{N} = \{0, 1, 2, 3, \dots\}$$

solution

$\text{trace}(A^{2k+1}) = 0$ is equivalent to saying there are no odd length cycles. also note that two coloring is the same as bipartiteness. if there is an odd length cycle, then that cycle cannot be two colored because of the parity.

Ex.4 (20pts) (Other Motifs) See Figure 1 that shows two motif equations that relate properties of the adjacency matrix A (more specifically, entries of its square A^2) and hidden patterns in the graph. We ask you to prove these two motif equations. Here the patterns shown at the right-hand-side of the equations are:

- K_4 : this is the clique on 4 nodes, that is the graph where every edge between two nodes is present.
- $\diamond$: this is the diamond symbol, that is the graph on 4 nodes, where exactly one edge is missing (as shown, the one connecting the top and bottom vertices.)
- C_4 : this is the cycle on 4 nodes (i.e., a square).

$$\sum_{(u,v) \in E} \binom{(A^2)_{u,v}}{2} = 6(\#K_4) + (\#\diamond)$$

$$\sum_{(u,v) \notin E} \binom{(A^2)_{u,v}}{2} = (\#\diamond) + 2(\#C_4)$$

Figure 1: Two Motif Equations.

Ex.5 (20pts) (Strassen's algorithm) Devise a divide and conquer algorithm that multiplies a matrix A and a matrix B (both of them are n -by- n) in time $O(n^{\log_2 7})$. This improves over the naive $O(n^3)$ algorithm we learned in high-school.

Your answer should be a clear exposition of the steps needed to perform the multiplication, and also a proof for its runtime. If it helps feel free to assume that n is a power of 2.