DRÄXLMAIER

SCHÄFER



Crimping Machine EPS 6000-SC

Crimp Force Monitoring System BB07i4

High Quality Standards in Wire Processing

Extension for crimping machines

For quality assurance in wire production, Schäfer offers the latest generation of the BB07i crimp force monitor. The optional system can be installed in almost all crimping machines and fully automatic crimping machines from Schäfer and integrated into the control system. The parameters and the measured values are output via a touch display within the STI control system or via the user interface of the WireStar machine software.



Functionality of the system

Crimp quality is monitored during cable production by comparing the measured force with a reference, for example to detect missing strands or insulation in the crimp connection. A difference from the teached-in reference curve triggers an error message from the machine or, if a bad part cutter is installed, leads to cutting of the wire. This ensures that faulty cables cannot be used in further production.

Advantages for cable production

In summary, the BB07i4 crimp force monitor with SDS100 sensor offers the following advantages in cable production:

- True force measurement
- High measuring accuracy
- Reproducible measured values
- Fast production changeover
- Easy upgrade in EPS crimping machines
- Extensive statistical evaluations

DEMIREL
CRIMP TECHNIK



971-150 B CRIMPMATIC

Crimping press in a revised design with high torsional rigidity, frequency-controlled drive, and tool holder for all common applicators as well as heavy-duty column tools for processing loose piece and banded terminals.

OPTIONS

- Adapter plate for UT 135.78 mm
- Tool clamping system for tools 938
- Integrated crimp force monitoring (Komax or OES)
- DCC system 970/971
- Paper winder and mounting kit
- Standard maintenance unit
- 2-hand safety circuit
- OPC-Hardware
- OPC-Software
- Erweiterte Maschinensoftware (unter Anderem: Headroom und Split-Cycle)

Internal