

# Palindrome Index

Given a string of lowercase letters, determine the index of the character whose removal will make the string a palindrome. If the string is already a palindrome, then print **-1**. There will always be a valid solution.

## Input Format

The first line contains  $T$  (the number of test cases).  
The  $T$  subsequent lines of test cases each contain a single string to be checked.

## Constraints

$1 \leq T \leq 20$   
 $1 \leq \text{length of string} \leq 100005$   
All characters are Latin lower case indexed.

## Output Format

Print the *zero-indexed* position (integer) of a character whose deletion will result in a palindrome; if there is no such character (i.e.: the string is already a palindrome), print **-1**. Any correct answer will be accepted; e.g.: for a string such as **bc**bc****, we can either remove *b* at index **0** or *c* at index **3**—both answers are acceptable.

## Sample Input

```
3
aaab
baa
aaa
```

## Sample Output

```
3
0
-1
```

## Explanation

*Test Case 1(aaab):* Removing *b* at index **3** results in a palindrome, so we print **3**.  
*Test Case 2(baa):* Removing *b* at index **0** results in a palindrome, so we print **0**.  
*Test Case 3(aaa):* This string is already a palindrome, so we print **-1**; however, **0**, **1**, and **2** are also all acceptable answers, as the string will still be a palindrome if any one of the characters at those indices are removed.

## Custom Checker logic

<https://gist.github.com/shashank21j/58df3865a95bf960092c>