



All Domains > Algorithms > Dynamic Programming > The Maximum Subarray

Badge Progress



Points: 2300.44 Rank: 1301

The Maximum Subarray



by sh4d0wkn1ght

Problem

Submissions

Leaderboard

Discussions

Editorial

Topics

Given an array $A = \{a_1, a_2, \dots, a_N\}$ of N elements, find the maximum possible sum of a

1. Contiguous subarray
2. Non-contiguous (not necessarily contiguous) subarray.

Empty subarrays/subsequences should not be considered.

This Youtube video by Ben Wright might be useful to understand the *Kadane algorithm* for the maximum subarray in a 1-D sequence.

Algorithms: Maximum Contiguous Subarray Problem $O(\dots)$  



Input Format

First line of the input has an integer T . T cases follow.

Each test case begins with an integer N . In the next line, N integers follow representing the elements of array A .

Constraints:

- $1 \leq T \leq 10$
- $1 \leq N \leq 10^5$
- $-10^4 \leq a_i \leq 10^4$

The subarray and subsequences you consider should have at least one element.

Output Format

Two, space separated, integers denoting the maximum contiguous and non-contiguous subarray. At least one integer

should be selected and put into the subarrays (this may be required in cases where all elements are negative).

Sample Input

```
2
4
1 2 3 4
6
2 -1 2 3 4 -5
```

Sample Output

```
10 10
10 11
```

Explanation

In the first case:

The max sum for both contiguous and non-contiguous elements is the sum of ALL the elements (as they are all positive).

In the second case:

[2 -1 2 3 4] --> This forms the contiguous sub-array with the maximum sum.

For the max sum of a not-necessarily-contiguous group of elements, simply add all the positive elements.

Copyright © 2016 HackerRank.
All Rights Reserved

Related Topics



[Dynamic Programming Basics](#)




Submissions: 19781

Max Score: 50

Difficulty: Easy

[More](#)

Current Buffer (saved locally, editable)  

Java 8   

```
1 import java.io.*;
2 import java.util.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named
7         Solution. */
8     }
9 }
```

Line: 1 Col: 1

 [Upload Code as File](#)

☐ [Test against custom input](#)

[Run Code](#)

[Submit Code](#)

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Privacy Policy](#) | [Request a Feature](#)