

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  struct Node {
5      int data;
6      struct Node* left;
7      struct Node* right;
8  };
9
10 struct Node* create(int x) {
11     struct Node* new = malloc(sizeof(struct Node));
12     new->data = x;
13     new->left = new->right = NULL;
14     return new;
15 }
16 struct Node* insert(struct Node* root, int x){
17     if (root == NULL) return create(x); if (x < root->data)
18     root->left = insert(root->left, x); else root->right = insert(root->right, x);
19     return root;
20 }
21 void preorder(struct Node* root) {
22     if (root) {
23         printf("%d ", root->data);
24         preorder(root->left);
25         preorder(root->right);
26     }
27 }

```

Preorder: 10 5 15

=== Code Execution Successful ===

```

main.c
11 struct Node* new = malloc(sizeof(struct Node));
12 new->data = x;
13 new->left = new->right = NULL;
14 return new;
15 }
16 struct Node* insert(struct Node* root, int x){
17     if (root == NULL) return create(x); if (x < root->data)
18     root->left = insert(root->left, x); else root->right = insert(root->right, x);
19     return root;
20 }
21 void preorder(struct Node* root) {
22     if (root) {
23         printf("%d ", root->data);
24         preorder(root->left);
25         preorder(root->right);
26     }
27 }
28 int main() {
29     struct Node* root = NULL;
30     root = insert(root, 10);
31     insert(root, 5);
32     insert(root, 15);
33     printf("Preorder: ");
34     preorder(root);
35     return 0;
36 }

```

Output

Preorder: 10 5 15

=== Code Execution Successful ===