

llam vel, wis-
tas luero, pretium at, lobor-
um, erat ligna aliquet magna, vitae ornare odio metus a
i ac orci et nisl hendrerit mollis. Suspendisse ut massa.
e. Pellentesque a nulla. Cum sociis natoque penatibus
arturient montes, nasceretur ridiculus mus. Aliquam
illa ullamcorper vestibulum turpis. Pellentesque

*smod sodales, sollicitudin vel, wis-
m lacus libero, pretium at, lobor-
aliquet, tortor sed accumsan
vitae ornare odio metus a
Suspendisse ut massa.
iis natoque penatibus
lus mus. Aliquam
is. Pellentesque*

Nam dui ligula, fringilla a, euismod sodales, sollicitudin
Morbi autor lorem non justo. Nam lacus pharetra et, tortor sed accu
tis vitae, ultricies et, tenebrosa. Sed id, tunc, tortor, sed accu
bibendum, erat, ligula aliquet magna, vitae ornare odio metus
ni. Morbi ac oras, et nisi hendrerit mollis. Suspendisse ut massa
s nec ante. Pellentesque a nulla. Cum sociis natoque penatibus
ernis dis parturient montes, nascetur ridiculus mus. Aliquam
urna. Nulla ullamcorper vestibulum turpis, et, et, et, et,
s mauris.

illa a, euismod sodales, sollicitudin vel. wisi.
justo. Nam lacus libero, pretium at, lobor-
c Donec aliquet, tortor sed accumsan
magna, vitae ornare odio. Luctus a
rit mollis. Suspendisse ut massa.
Cum sociis natoque penatibus
tur ridiculus mus. Aliquam
alum turpis. Pellentesque

tcolorbox

Nam dui ligu-
Morbi auctor lo-
tis vitae, ultricies e-
bibendum, erat ligula
mi. Morbi ac orci et nisi.
Cras nec ante. Pellentesque a
et magnis dis parturient
tincidunt.

Facit *mauris.*

ullamcorper

din vel, wisi;
at, labor-
umsan
is a
2.
mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse u-
Cras nec ante. Pellentesque a nulla. Cum sociis natoque pen-
et magnis dis parturient montes, nascetur ridiculus mus. Aliquae
tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque
versus luctus mauris.

tcolorbox 3.94

Nam dui ligula, fringilla a, euismod sodales, s-
Morbi auctor lorem non justo. Nam lacus libero, p-
tis vitae, ultricies et, tellus. Donec aliquet, tortor
bibendum, erat ligula aliquet magna, vitae ornare od-
3.94

APPENDIX 3.9

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. P.

tcolorbox 3.9

A close-up photograph of a purple and white striped fabric surface, showing a small dark insect-like object in the center.

tcolorbox 3.9

Manual for version 3.94 (2016/07/14)

olorbox 3.9

Thomas F. Stur

tcolorbox

tcolorbox 3.9

², euismod sodales, sollicitudin vel, wis.
io. Nam lacus libero, pretium at, lobor-
Donec aliquet, tortor sed accumsan
egna, vitae ornare odio metus a
mollis. Suspendisse ut massa.
in sociis natoque posu-
bit

colorbox 3.94

*Nam dui ligula, fringilla a,
Morbi auctor lorem non justo.
tis vitae, ultricies et, tellus. Do
bibendum erat ligula aliquet mag-
as nec ante. Pellentesque a nulla. Cum
agnis dis parturient montes, nascetur u-
nt urna. Nulla ullamcorper vestibulum
us Mauris.*

3.94
(2016/07/14)

olorbox 3.94

Thomas F. Sturm

<i>llicitudin vel, wisi: etium at, lobor- ed accumsan o metus a massa. ibus n</i>	<i>tcolorbox 3.5 Nam dui ligula, l Morbi auctor lorem tis vitae, ultricies et, v bibendum, erat ligula ah mi. Morbi ac orci et nisl he Cras nec ante. Pellentesque a n et magnis dis parturient montes, n tincidunt urna. Nulla ullamcorper ve cursus luctus mauris.</i>
---	--

*Nam dui ligula, fringilla a, euismod sodales, sollicitudin
Morbi auctor lorem non justo. Nam lacus libero, pretium
tis vitae, ultricies et, tellus. Donec aliquet, tortor sed
bibendum, erat ligula aliquet magna, vitae ornare odio
mi. Morbi ac orci et nisl hendrerit mollis. Sed
Cras nec ante. Pellentesque a nulla.
et magnis dis partur.*

Cover code

```
% \usepackage{incgraph}
\begin{incontext}
\begin{tikzpicture}
\definecolorseries{boxcol}{rgb}{last}{blue}{red}
\resetcolorseries[28]{boxcol}
\coordinate (A) at (0,0); \coordinate (B) at (21,29.7);
\path[use as bounding box] (A) rectangle coordinate (C) (B);
\node[transform shape,xslant=0.7,rotate=-10,xshift=0cm] at (C) {%
\begin{tcbraster}[raster columns=4,title=tcolorbox \version,
fonttitle=\small\bfseries,raster width=50cm]
\foreach \b in {1,...,28} {\begin{tcolorbox}[enhanced,
watermark text=\thetcbasternum,
colframe=boxcol!30!white,
colback=boxcol!25!white!30!white,
colbacktitle=boxcol!!+!50!black!30!white,
colupper=black!30!white]\lipsum[2]\end{tcolorbox}}
\end{tcbraster}%
};
\node at (C) {%
\begin{tcbitemize}[title=tcolorbox \version,fonttitle=\small\bfseries,
enhanced jigsaw,opacityback=0.5,opacitybacktitle=0.75,
halign=center,valign=center,arc=5mm,
raster width=16cm,raster column skip=8mm,raster halign=center,
raster force size=false,
raster row 1/.style={height=6cm},
raster row 2/.style={width=6cm,height=4cm},
raster column 1/.style={flushright title,
frame style={left color=yellow!50!black,right color=green!50!black},
title style={left color=yellow!50!blue,right color=blue!50!green!50!black},
interior style={left color=yellow!70,right color=green!70},
underlay={\draw[line width=6mm,line cap=round,black!60]
([shift={(0.4,-0.15)}]frame.north east)
--([shift={(0.4,0.15)}]frame.south east); }},
raster column 2/.style={%
frame style={left color=green!50!black,right color=yellow!50!black},
title style={left color=blue!50!green!50!black,right color=yellow!50!blue},
interior style={left color=green!70,right color=yellow!70}}]
\tcbitem[fontupper=\Huge\bfseries,sharp corners=east,
underlay={\draw[line width=6mm,line cap=round,black!60]
([shift={(0.4,0.30)}]frame.north east)-- coordinate(A) +(0,0.2);
\draw[line width=1mm,line cap=round,black!60](A) -- +(30:1.5cm);
\draw[line width=1mm,line cap=round,black!60](A) -- +(150:1.5cm);}]
tcolorbox
\tcbitem[fontupper=\large\bfseries,sharp corners=west]
Manual for \version \version \(\datum)
\tcbitem[sharp corners=northeast]
\tcbitem[sharp corners=northwest] Thomas F.~Sturm
\end{tcbitemize}%
};
\end{tikzpicture}
\end{incontext}
```

The **tcolorbox** package

Manual for version 3.94 (2016/07/14)

Thomas F. Sturm¹

<http://www.ctan.org/pkg/tcolorbox>

<https://github.com/T-F-S/tcolorbox>

Abstract

tcolorbox provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part. The package **tcolorbox** can be used for the setting of L^AT_EX examples where one part of the box displays the source code and the other part shows the output. Another common use case is the setting of theorems. The package supports saving and reuse of source code and text parts.

Contents

1	Introduction	8
1.1	Installation	8
1.2	Loading the Package	8
1.3	Libraries	9
2	Quick Reference	11
3	Macros for Box Creation	12
4	Option Keys	18
4.1	Title	18
4.2	Subtitle	21
4.3	Upper Part	22
4.4	Lower Part	24
4.5	Colors and Fonts	27
4.6	Text Alignment	30
4.7	Geometry	34
4.7.1	Width	34
4.7.2	Rules	35
4.7.3	Arcs	36
4.7.4	Spacing	38
4.7.5	Size Shortcuts	43
4.8	Corners	47
4.9	Transparency	50
4.10	Height Control	52
4.11	Box Content Additions	62
4.12	Overlays	69
4.13	Floating Objects	74

¹Prof. Dr. Dr. Thomas F. Sturm, Institut für Mathematik und Informatik, Universität der Bundeswehr München, D-85577 Neubiberg, Germany; email: thomas.sturm@unibw.de

4.14	Embedding into the Surroundings	76
4.15	Bounding Box	80
4.16	Layered Boxes and Every Box Settings	87
4.17	Capture Mode	90
4.18	Text Characteristics	91
4.19	Files	92
4.20	\tcbbox Specials	92
4.21	Counters, Labels, and References	94
4.22	Even and Odd Pages	96
4.23	Externalization	99
4.24	Miscellaneous	99
5	Initialization Option Keys	101
5.1	Numbered Boxes	101
5.2	Lists of \colorboxes	108
6	Side by Side	109
6.1	Basic Settings	109
6.2	Advanced Settings from the <code>xparse</code> Library	115
7	Saving and Loading of Verbatim Texts	119
8	Recording	120
8.1	Makros	120
8.2	Options	120
8.3	Example: Exercises	121
8.4	Example: Solutions	124
9	Technical Overview and Customization	126
9.1	Skins and Drawing Engines	126
9.2	Code Option Keys	130
9.3	Subskins	133
9.4	Drawing Scheme	134
9.5	Useful Properties	138
10	Library skins	140
10.1	Style Option Keys	140
10.2	Boxed Title Option Keys	147
10.2.1	Boxed Title Placement	147
10.2.2	Options for the Boxed Title Placement	149
10.2.3	Options for the Boxed Title Box	150
10.3	Watermark Option Keys	157
10.4	Clip Environments	164
10.5	Border Line Option Keys	169
10.6	Shadow Option Keys	174
10.6.1	Common Shadows and Halos	174
10.6.2	Lifted Shadows	179
10.6.3	Generic Shadows	180
10.6.4	TikZ Shadows	183
10.7	TikZ Picture Option Keys	184
10.8	Underlay Option Keys	187
10.9	Finish Option Keys	189

10.10 Jigsaw Skin Variants	191
10.11 Draft Mode	193
10.12 Skin Family 'standard'	194
10.13 Skin Family 'enhanced'	196
10.14 Skin Family 'bicolor'	209
10.15 Skin Family 'tile'	214
10.16 Skin Family 'beamer'	218
10.17 Skin Family 'widget'	223
10.18 Skin Family 'empty'	227
10.19 Skin 'spartan'	237
10.20 Skin 'draft'	238
10.21 Skin Family 'freelance'	240
11 Inclusion of Boxed Image Files	241
11.1 Macros	241
11.2 Option Keys	244
12 TikZ Image and Picture Fill Extensions; Auxiliary Macros	245
12.1 Fill Plain	245
12.2 Fill Stretch	246
12.3 Fill Overzoom	247
12.4 Fill Zoom	248
12.5 Fill Shrink	249
12.6 Fill Tile	250
12.7 Filling Options	251
12.8 Straightening of the Arcs	252
12.9 Extracting Node Dimensions	253
13 Library <code>vignette</code>	254
13.1 Vignette Drawing	254
13.2 Generic Geometry Settings	255
13.3 Generic Color and Style Settings	257
13.4 Generic Fading Settings	259
13.5 Vignette as Underlay	261
13.6 Vignette as Finish	263
14 Library <code>raster</code>	266
14.1 Concept of Rasters	266
14.2 Macros of the Library	268
14.3 Option Keys of the Library	272
14.4 Adding Styles for Specific Boxes	277
14.5 Combining Columns or Rows	279
14.6 Rasters inside Rasters	282
14.6.1 Raster Setup	282
14.6.2 Placing Spaces	283
15 Libraries <code>listings</code>, <code>listingsutf8</code>, and <code>minted</code>	287
15.1 Loading the Libraries	287
15.1.1 Loading <code>listings</code>	287
15.1.2 Loading <code>listingsutf8</code>	287
15.1.3 Loading <code>minted</code>	288
15.2 Common Macros of the Libraries	288

15.3	Option Keys of the <code>listings</code> Library	294
15.4	Option Keys of the <code>listingsutf8</code> Library	296
15.5	Option Keys of the <code>minted</code> Library	297
15.6	Common Option Keys of all Libraries	299
15.7	Option Keys for Processing and Full Document Examples	308
15.8	Creation of L ^A T _E X Tutorials	315
15.9	Creation of L ^A T _E X Exercises	322
15.10	List of Exercises	325
15.11	Solutions for the given L ^A T _E X Exercises	326
16	Library <code>theorems</code>	328
16.1	Macros of the Library	328
16.2	Option Keys of the Library	332
16.3	Examples for Definitions and Theorems	345
16.4	Using other theorem environments with <code>tcolorbox</code>	350
17	Library <code>breakable</code>	351
17.1	Technical Overview	351
17.2	Limitations and Known Bugs	352
17.3	Main Option Keys	353
17.4	Option Keys for the Break Appearance	357
17.5	Extra Options for Partial Boxes	359
17.6	Breakable boxes and the <code>multicol</code> package	362
17.7	Break Sequence for the Skins	365
17.8	Break by Hand (Faked Break)	374
18	Library <code>magazine</code>	375
18.1	Creation and Resetting of Box Arrays	375
18.2	Storing Content	376
18.3	Retrieving Content	378
18.4	Box Dimensions	381
19	Library <code>fitting</code>	383
19.1	Macros of the Library	383
19.2	Option Keys of the Library	385
20	Library <code>hooks</code>	394
20.1	Concept of Hooks	394
20.2	Box Content Additions	395
20.3	Embedding into the Surroundings	396
20.4	Overlays	397
20.5	Watermarks	399
20.6	Underlays	401
20.7	Finishes	402
20.8	Skin Code	402
20.9	Extras	404
21	Library <code>xparse</code>	405
21.1	Option Keys	405
21.2	Producing <code>tcolorbox</code> Environments and Commands	407
21.3	Producing <code>tcbox</code> Commands	410
21.4	Producing <code>tcblisting</code> Environments	413

21.5	Producing <code>tcbinputlisting</code> Commands	415
21.6	Producing <code>tboxfit</code> Commands	416
22	Library <small>LIB</small> <code>external</code>	418
22.1	Preparation of a Document for Externalization	419
22.2	Marking Externalization Snippets	420
22.3	Customization	425
22.4	Troubleshooting and FAQ	429
23	Library <small>LIB</small> <code>documentation</code>	430
23.1	Macros of the Library	430
23.2	Option Keys of the Library	440
23.3	Predefined Colors of the Library	447
A	Picture Credits	448
References		449
Index		450

1 Introduction

The package originates from the first edition of my book «*LATEX – Einführung in das Textsatzsystem*» [19] in about 2006. For the LATEX examples and tutorials given there, I wanted to have accentuated and colored boxes to display source code and compiled text in combination. Since, in my opinion, this type of boxes is also quite useful to highlight definitions and theorems, I applied them for my lecture notes in mathematics [16–18] as well. With this package, you are invited to apply these boxes for similar projects.

Starting with version 2.00, for all internal calculations ε -TEX [2] expressions are used in replacement of the package `calc`. The breaking news for version 2.00 is the support for breakable boxes. This new feature allows new applications of the package without affecting the core package too much if you do not need boxes to break automatically. With version 2.20, the often requested ‘side by side’ mode for listings has been added. With version 3.00, boxed titles are introduced together with improved customization options for overlays, underlays, finishes, and own code extensions.

Since the first public release in 2011, I received a lot of feedback from all over the world. I want to thank all who wrote me for supporting this package by sending bug reports and ideas for new or better features.

1.1 Installation

Typically, `tcolorbox` will be installed as part of a major LATEX distribution and there is nothing special to do for a user.

If you intend to make a local installation *by hand*, see the `README` file of the `tcolorbox` package for some hints. The short story is: you have to install not only `tcolorbox.sty`, but also all `*.code.tex` files in the local `texmf` tree.

1.2 Loading the Package

The base package `tcolorbox` loads the packages `pgf` [20], `verbatim` [15], `etoolbox` [7], and `environ` [14]. `tcolorbox` itself is loaded in the usual manner in the preamble:

```
\usepackage{tcolorbox}
```

The package takes option keys in the key-value syntax. Alternatively, you may use these keys later in the preamble with `\tcbselibrary`^{P.9} (see there). For example, the key to typeset listings is:

```
\usepackage[listing]{tcolorbox}
```

1.3 Libraries

The base package `tcolorbox` is extendable by program libraries. This is done by using option keys while loading the package or inside the preamble by applying the following macro with the same set of keys.

`\tcbuselibrary{<key list>}`

Loads the libraries given by the `<key list>`.

`\tcbuselibrary{listings, theorems}`

The following keys are used inside `\tcbuselibrary` respectively `\usepackage` without the key tree path `/tcb/library/`.

`/tcb/library/skins`

(LIB skins)

Loads the package `tikz` [20] and provides additional styles (skins) for the appearance of the colored boxes; see Section 10 from page 140.

`/tcb/library/vignette`

(LIB vignette)

Provides code for more ornamental; see Section 13 from page 254.

`/tcb/library/raster`

(LIB raster)

Provides additional macros and options for typesetting multiple boxes arranged in a kind of raster; see Section 14 from page 266.

`/tcb/library/listings`

(LIB listings)

Loads the package `listings` [6] and provides additional macros for typesetting listings which are described in Section 15 from page 287.

`/tcb/library/listingsutf8`

(LIB listingsutf8)

Loads the packages `listings` [6] and `listingsutf8` [10] for UTF-8 support. This is a variant of the library `listings` and is described in Section 15 from page 287.

`/tcb/library/minted`

(LIB minted)

Loads the package `minted` [11] to typeset listings with the `Pggments` [13] tool, also see Section 15 on page 287.

`/tcb/library/theorems`

(LIB theorems)

Provides additional macros for typesetting theorems which are described in Section 16 from page 328.

`/tcb/library/breakable`

(LIB breakable)

Provides support for automatic box breaking from one page to another; see Section 17 on page 351.

`/tcb/library/magazine`

(LIB magazine)

Provides support for storing broken box parts to be used later or in interchanged order, Section 18 on page 375.

`/tcb/library/fitting`

(LIB fitting)

Provides support for font size adaption of the box content to the box dimensions; see Section 19 from page 383.

`/tcb/library/hooks`

(LIB hooks)

Extends several option keys to 'hookable' keys; see Section 20 from page 394.

/tcb/library/xparse

(LIB xparse)

Provides document command production with `xparse` for `tcolorbox`; see Section 21 from page 405.

/tcb/library/external

(LIB external)

Provides externalization support for stand-alone document snippets, see Section 22 on page 418.

/tcb/library/documentation

(LIB documentation)

Provides additional macros for typesetting L^AT_EX documentations which are described in Section 23 from page 430.

/tcb/library/many

(style, no value)

Loads the libraries LIB skins, LIB breakable, LIB raster, LIB hooks, LIB theorems, LIB fitting, and LIB xparse. Use this shortcut, if you want to use all features of `tcolorbox` with exception of typesetting listings and using the specialized LIB documentation library.

/tcb/library/most

(style, no value)

Loads all libraries except LIB minted and LIB documentation. Use this shortcut, if you want to use all features of `tcolorbox` with exception of using the `minted` package and using the specialized LIB documentation library.

/tcb/library/all

(style, no value)

Loads all libraries. Use this shortcut only, if you intend to use the LIB documentation library.

Package tcolorbox

Basic Features

Base package

Advanced Features

LIB skins
LIB vignette
LIB raster
LIB breakable
LIB magazine
LIB theorems
LIB fitting
LIB hooks
LIB external
LIB xparse



Advanced Listings

LIB listings
LIB listingsutf8
LIB minted

Documentation

LIB documentation

2 Quick Reference



3 Macros for Box Creation

```
\begin{tcolorbox}[\langle options\rangle]  
  <environment content>  
\end{tcolorbox}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts. The appearance of this box is controlled by numerous options. In the most simple case the source code

```
\begin{tcolorbox}  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

creates the following compiled text box:

This is a **tcolorbox**.

The text content of the box can be divided in an upper and a lower part by the command `\tcblower`. Visually, both parts are separated by a line. For example:

```
\begin{tcolorbox}  
This is another \textbf{tcolorbox}.  
\tcblower  
Here, you see the lower part of the box.  
\end{tcolorbox}
```

This code gives the following box:

This is another **tcolorbox**.

Here, you see the lower part of the box.

The `\langle options\rangle` control the appearance and several functions of the boxes, see Section 4 on page 18 for the complete list. A quick example is given here:

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,title=My nice heading]  
This is another \textbf{tcolorbox}.  
\tcblower  
Here, you see the lower part of the box.  
\end{tcolorbox}
```

My nice heading

This is another **tcolorbox**.

Here, you see the lower part of the box.

\tcblower

Used inside `tcolorbox` to separate the upper box part from the optional lower box part. The upper and the lower part are treated as separate functional units. If you only want to draw a line, see `\tcbline`^{→ P. 199}.

\tcbset{\langle options \rangle}

Sets options for every following `tcolorbox`^{→ P. 12} inside the current TeX group. By default, this does not apply to nested boxes, see Section 4.16 on page 87. For example, the colors of the boxes may be defined for the whole document by this:

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

\tcbsetforeverylayer{\langle options \rangle}

Sets options for every following `tcolorbox`^{→ P. 12} inside the current TeX group. In contrast to `\tcbset`, this does also apply to nested boxes, see Section 4.16 on page 87. Technically, the `\langle options \rangle` are appended to the default values for every `tcolorbox` which are applied by `/tcb/reset`^{→ P. 99}.

You should not use this macro, if you are not completely sure that you want to have the `\langle options \rangle` also for boxes in boxes (in boxes in boxes ...).

```
\tcbset{colback=green!10!white}
\tcbsetforeverylayer{colframe=red!75!black}

\begin{tcolorbox}[title=All options for this box]
This is a tcolorbox.\par\medskip
\begin{tcolorbox}[title=Nested box]
Note that this nested box has a red frame but no green background.
\end{tcolorbox}
\end{tcolorbox}
\bigskip

\begin{tcolorbox}[reset]
Options given with |\tcbsetforeverylayer| survive a |reset|.
\end{tcolorbox}
```

All options for this box

This is a tcolorbox.

Nested box

Note that this nested box has a red frame but no green background.

Options given with `\tcbsetforeverylayer` survive a `reset`.

\tcbbox[*options*]{*box content*}


Creates a colored box which is fitted to the width of the given *box content*. In principle, most *options* for a `tcolorbox`^{P.12} can be used for `\tcbbox` with some restrictions. A `\tcbbox` cannot have a lower part and cannot be broken.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,nobeforeafter,center title}

Text \tcbbox[tcbbox raise base]{Hello World}\hfill
%
\tcbbox[left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=0mm,
        toptitle=0.5mm,bottomtitle=0.5mm,title=My table]{%
    \arrayrulecolor{blue!50!black}\renewcommand{\arraystretch}{1.2}%
    \begin{tabular}{r|c|l}
        One & Two & Three \\ \hline
        Men & Mice & Lions \\ \hline
        Upper & Middle & Lower \\
    \end{tabular}\hfill
%
\tcbbox[colback=blue!85!black,
        left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=1mm,arc=0mm,boxrule=0.5pt,
        title=My picture]{%
    \includegraphics[width=5cm]{Basilica_5.png}}
```

Text Hello World

My table		
One	Two	Three
Men	Mice	Lions
Upper	Middle	Lower



```
% \usepackage{tikz}
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,center title}

% Fixed width box
\begin{tcolorbox}Hello\World!\end{tcolorbox}

% Fitted width box (like hbox or makebox)
\tcbbox{Hello\World!}

% Fitted width box (using a \tikzname\ node)
\tcbbox[tikznode]{Hello\World!}
```

Hello
World!

HelloWorld!

Hello
World!

! See Section 21.2 on page 407 and Section 21.3 on page 410 for more elaborate methods to create new environments and commands.

\newtcolorbox[*init options*]{*name*} [*number*] [*default*] {*options*}

Creates a new environment *name* based on `tcolorbox`^{P.12}. Basically, `\newtcolorbox` operates like `\newenvironment`. This means, the new environment *name* optionally takes *number* arguments, where *default* is the default value for the optional first argument. The *options* are given to the underlying `tcolorbox`. Note that `/tcb/savedelimiter`^{P.26} is set to the given *name* automatically. The *init options* allow setting up automatic numbering, see Section 5 from page 101.

```
\newtcolorbox{mybox}{colback=red!5!white,
colframe=red!75!black}

\begin{mybox}
This is my own box.
\end{mybox}
```

This is my own box.

```
\newtcolorbox{mybox}[1]{colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
title=#1}

\begin{mybox}{Hello there}
This is my own box with a mandatory title.
\end{mybox}
```

Hello there

This is my own box with a mandatory title.

```
\newtcolorbox{mybox}[2]{colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
colbacktitle=red!85!black,enhanced,
attach boxed title to top center={yshift=-2mm},
title=#2,#1}

\begin{mybox}[colback=yellow]{Hello there}
This is my own box with a mandatory title
and options.
\end{mybox}
```

Hello there

This is my own box with a mandatory title and options.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2]{%
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
title=Examp.\thetcbcounter: #2,#1}
```

```
\begin{pabox}[colback=yellow]{Hello there}
This is my own box with a mandatory
numbered title and options.
\end{pabox}
```

Examp. 3.1: Hello there

This is my own box with a mandatory numbered title and options.

\renewtcolorbox[*init options*]{*name*} [*number*] [*default*] {*options*}

Operates like `\newtcolorbox`, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

```
\newtcbox[<init options>]{\<name>}{<number>} [<default>]{<options>}
```

Creates a new macro `\<name>` based on `\tcbbox`^{P.14}. Basically, `\newtcbox` operates like `\newcommand`. The new macro `\<name>` optionally takes `<number>+1` arguments, where `<default>` is the default value for the optional first argument. The `<options>` are given to the underlying `tcbbox`. The `<init options>` allow setting up automatic numbering, see Section 5 from page 101.

```
\newtcbox{\mybox}{colback=red!5!white,  
colframe=red!75!black}  
  
\mybox{This is my own box.}
```

This is my own box.

```
\newtcbox{\mybox}[1]{colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries,  
title=#1}  
  
\mybox>Hello there{This is my own box.}
```

Hello there

This is my own box.

```
\newtcbox{\mybox}[2][] {colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries,  
title=#2,#1}  
  
\mybox[colback=yellow]{Hello there}%  
{This is my own box.}
```

Hello there

This is my own box.

Definition in the preamble:

```
% counter from previous example  
\newtcbox[use counter from=pabox]{\pbbox}[2][] {  
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,  
title=(\thetcbcounter) #2,#1}
```

```
\pbbox[colback=yellow]{Hello there}%  
{This is my own box.}
```

(3.2) Hello there

This is my own box.

```
\newtcbox{\mybox}[1][red]{on line,  
arc=0pt,outer arc=0pt,colback=#1!10!white,colframe=#1!50!black,  
boxsep=0pt,left=1pt,right=1pt,top=2pt,bottom=2pt,  
boxrule=0pt,bottomrule=1pt,toprule=1pt}  
\newtcbox{\xmybox}[1][red]{on line,  
arc=7pt,colback=#1!10!white,colframe=#1!50!black,  
before upper={\rule[-3pt]{0pt}{10pt}},boxrule=1pt,  
boxsep=0pt,left=6pt,right=6pt,top=2pt,bottom=2pt}
```

The `\mybox[green]{quick}` brown `\mybox{fox}` `\mybox[blue]{jumps}` over the
`\mybox[green]{lazy}` `\mybox{dog}`. `\par`
The `\xmybox[green]{quick}` brown `\xmybox{fox}` `\xmybox[blue]{jumps}` over the
`\xmybox[green]{lazy}` `\xmybox{dog}`.

The quick brown fox jumps over the lazy dog.

The quick brown fox jumps over the lazy dog.

```
\renewtcbox[<init options>]{\<name>}{<number>} [<default>]{<options>}
```

Operates like `\newtcbox`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

\tcolorboxenvironment{<name>}{<options>}

An existing environment *<name>* is redefined to be boxed inside a `tcolorbox` with the given *<options>*.

```
% tcbuselibrary{skins}
\newenvironment{myitemize}{%
  \begin{itemize}}{\end{itemize}}

\tcolorboxenvironment{myitemize}[blanker,
  before skip=6pt,after skip=6pt,
  borderline west={3mm}{0pt}{red}]

Some text.
\begin{myitemize}
\item Alpha
\item Beta
\item Gamma
\end{myitemize}
More text.
```

Some text.


- Alpha
- Beta
- Gamma

More text.

See further examples in Section 16.4 on page 350.

4 Option Keys

For the `<options>` in `tcolorbox`^{→ P. 12} respectively `\tcbset`^{→ P. 13} the following pgf keys can be applied. The key tree path `/tcb/` is not to be used inside these macros. It is easy to add your own style keys using the syntax for pgf keys, see [19, 20] or the examples starting from page 315.

4.1 Title

`/tcb/title=<text>` (no default, initially empty)

Creates a heading line with `<text>` as content.

```
\begin{tcolorbox}[title=My heading line]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My heading line

This is a tcolorbox.

`/tcb/notitle` (no value, initially set)

Removes the title line if set before.

`/tcb/adjusted title=<text>` (style, no default, initially unset)

Creates a heading line with `<text>` as content. The minimal height of this line is adjusted to fit the text given by `/tcb/adjust text`. This option makes sense for single line headings if boxes are set side by side with equal height. Note that it is very easy to trick this adjustment.

```
\tcbset{colback=White,arc=0mm,width=(\linewidth-4pt)/4,
equal height group=AT,before=,after=\hfill,fonttitle=\bfseries}

The following titles are not adjusted:\\
\foreach \n in {xxx,ggg,AAA,\\"Agypten}
{\begin{tcolorbox}[title=\n,colframe=red!75!black]
Some content.\end{tcolorbox}}
Now, we try again with adjusted titles:\\
\foreach \n in {xxx,ggg,AAA,\\"Agypten}
{\begin{tcolorbox}[adjusted title=\n,colframe=blue!75!black]
Some content.\end{tcolorbox}}
```

The following titles are not adjusted:

xxx	ggg	AAA	\\"Agypten
Some content.	Some content.	Some content.	Some content.

Now, we try again with adjusted titles:

xxx	ggg	AAA	\\"Agypten
Some content.	Some content.	Some content.	Some content.

`/tcb/adjust text=<text>` (no default, initially Äpgjy)

This sets the reference text for `/tcb/adjusted title`. If your texts never exceed 'Äpgjy' in depth and height you don't need to care about this option.

N 2014-11-24

/tcb/squeezed title=<text> (style, no default, initially unset)

Creates a single heading line with <text> as content. If the <text> is longer than the available space, the text is squeezed to fit into the available space.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title={Short title}]
  First box
\tcbitem[squeezed title={This is a very very long title}]
  Second box
\tcbitem[squeezed title={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```

Short title This is a very very long title This title is clearly to long for this application

First box

Second box

Third box

N 2014-11-24

/tcb/squeezed title*=<text> (style, no default, initially unset)

This is a combination of /tcb/adjusted title^{P.18} and /tcb/squeezed title.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title*={Short title}]
  First box
\tcbitem[squeezed title*={This is a very very long title}]
  Second box
\tcbitem[squeezed title*={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```

Short title

This is a very very long title

This title is clearly to long for this application

First box

Second box


Third box

/tcb/detach title

(no value)

Detaches the title from its normal position. The text of the title is stored into `\tcbtittletext` and the formatted title is available by `\tcbttitle`. The main application is to move the title from its usual place to another one.

```
\newtcolorbox{mybox}[2][]{colbacktitle=red!10!white,  
colback=blue!10!white,coltitle=red!70!black,  
title={#2},fonttitle=\bfseries,#1}  
  
\begin{mybox}{My title}  
    This is a \textbf{tcolorbox}.  
\end{mybox}  
\begin{mybox}[detach title,before upper={\tcbtittle\quad}]{My title}  
    This is a \textbf{tcolorbox}.  
\end{mybox}  
\begin{mybox}[detach title,after upper={\par\hfill\tcbtittle}]{My title}  
    This is a \textbf{tcolorbox}.  
\end{mybox}
```



/tcb/attach title

(no value)

Attaches the title to its normal position. This option is used to reverse `/tcb/detach title`.

U 2015-07-08

/tcb/attach title to upper=<text>

(style, default empty, initially unset)

Attaches the title to the begin of the upper part of the box content. The optional `<text>` is set between the formatted title and the box content.

```
\newtcolorbox{mybox}[2][]{colbacktitle=red!10!white,  
colback=blue!10!white,coltitle=red!70!black,  
title={#2},fonttitle=\bfseries,#1}  
  
\begin{mybox}[attach title to upper={\ ---\ }]{My title}  
    This is a \textbf{tcolorbox}.  
\end{mybox}  
\begin{mybox}[attach title to upper,after title={:\ }]{My title}  
    This is a \textbf{tcolorbox}.  
\end{mybox}
```



More title options are documented in Section 4.11 on page 62 and Section 10.2 on page 147.

4.2 Subtitle

Inside the box content, one or more subtitles can be added. In general, a subtitle is a further `tcolorbox`^{P. 12} which inherits some color and geometry options from the enclosing box. It may be customized just like any other `tcolorbox`^{P. 12}.

N 2014-10-10

`\tcbsubtitle[<options>]{<text>}`

Used inside a `tcolorbox`^{P. 12} to add a subtitle box with the given `<text>`. This is an independent `tcolorbox`^{P. 12} which is formatted by several inherited properties of the enclosing box, by further settings from `/tcb/subtitle style`, and by the given `<options>`.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[before skip=\baselineskip]%
  {My subtitle}
  Further text.
\end{tcolorbox}
```

My title
This is a tcolorbox.
My subtitle
Further text.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  colbacktitle=yellow!50!red,
  coltitle=red!25!black,
  fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[before skip=\baselineskip]%
  {My subtitle}
  Further text.
\end{tcolorbox}
```

My title
This is a tcolorbox.
My subtitle
Further text.

N 2014-10-10

`/tcb/subtitle style=<options>`

(no default, initially empty)

Adds `tcolorbox <options>` to the settings for `\tcbsubtitle`.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  colbacktitle=yellow!50!red,
  coltitle=red!25!black,
  fonttitle=\bfseries,
  subtitle style={boxrule=0.4pt,
    colback=yellow!50!red!25!white} ]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[My subtitle]
  Further text.
\tcbsubtitle[Second subtitle]
  Further text.
\end{tcolorbox}
```

My title
This is a tcolorbox.
My subtitle
Further text.
Second subtitle
Further text.

4.3 Upper Part

The text content of a `tcolorbox`^{P. 12} may be parted into a mandatory *upper part* and an optional *lower part*. These parts are separated by `\tcblower`^{P. 12}. If there is no `\tcblower`^{P. 12} present, there is no *lower part* and the *upper part* forms the complete text content.

N 2015-01-06

`/tcb/upperbox=<mode>` (no default, initially **visible**)

Controls the treatment of the upper part of the box. If there is no lower part, this is the complete text content. Feasible values for `<mode>` are:

- **visible**: usual type setting of the upper part,
- **invisible**: empty space instead of the upper part contents.

```
\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}
```

`\bigskip`

```
\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\tcblower
This is the lower part.
\end{tcolorbox}
```



This is the lower part.

N 2015-01-06

`/tcb/visible` (style, no value)

Shortcut for setting `/tcb/upperbox` and `/tcb/lowerbox`^{P. 24} to be **visible**.

N 2015-01-06

`/tcb/invisible` (style, no value)

Shortcut for setting `/tcb/upperbox` and `/tcb/lowerbox`^{P. 24} to be **invisible**.

```
\begin{tcolorbox}[invisibility]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}
```



Saves the content of the box into a file for an optional later usage. This is the counterpart of `/tcb/savelowerto→ P. 24`, but it saves not only the upper part but the whole content. If a lower part is present, it is also saved including `\tcblower→ P. 12`.



This option cannot be combined with `/tcb/savelowerto→ P. 24`.

```
\begin{tcolorbox}[invisible,saveto=\jobname_mysave1.tex,colback=white]
This is a \textbf{tcolorbox} which seems to be empty.
The content is saved for later usage.
\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_mysave1.tex}
```

Now, we load the saved text:
 This is a **tcolorbox** which seems to be empty. The content is saved for later usage.

```
\begin{tcolorbox}[saveto=\jobname_mysave2.tex]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}

Now, we load the saved text:
\begin{tcolorbox}[colframe=red,colback=red!10,
  coltitle=black,colbacktitle=red!20,sidebyside,
  title=Here we see the saved content including the lower part]
\input{\jobname_mysave2.tex}
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

Now, we load the saved text:

Here we see the saved content including the lower part

This is a **tcolorbox**.

This is the lower part.

4.4 Lower Part

`/tcb/lowerbox=<mode>` (no default, initially **visible**)

Controls the treatment of the lower part of the box. Feasible values for `<mode>` are:

- **visible**: usual type setting of the lower part,
- **invisible**: empty space instead of the lower part contents,
- **ignored**: the lower part is not used (here).

The last two values are usually applied in connection with `savelowerto`.

```
\begin{tcolorbox}[lowerbox=invisible,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but invisible).
\end{tcolorbox}

\begin{tcolorbox}[lowerbox=ignored,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but ignored).
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

U 2014-11-28

`/tcb/savelowerto=<file name>` (no default, initially empty)

Saves the content of the lower part into a file for an optional later usage.

```
\begin{tcolorbox}[lowerbox=invisible,savelowerto=\jobname_bspsave.tex,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part which may be quite complex:
\$displaystyle f(x)=\frac{1+x^2}{1-x^2}\$.
\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_bspsave.tex}
```

This is a **tcolorbox**.

Now, we load the saved text:

This is the lower part which may be quite complex: $f(x) = \frac{1+x^2}{1-x^2}$.

`/tcb/lower separated=true|false` (default `true`, initially `true`)

If set to `true`, the lower part is visually separated from the upper part. It depends on the chosen skin how the visualization of the separation is done.

```
% \tcbuselibrary{skins,raster}
\begin{tcbraster}[colback=red!5!white,colframe=red!75!black,
    fonttitle=\bfseries,fontlower=\itshape]
%
\begin{tcolorbox}[title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
```

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

`/tcb/savedelimiter=<name>` (no default, initially `tcolorbox`)

Used in connection with new environment definitions which extend `tcolorbox` and use or allow the option `savelowerto`. To catch the end of the new box environment `<name>` has to be the name of this environment. Additionally, the environment definition has to use `\tcolorbox` instead of `\begin{tcolorbox}` and `\endtcolorbox` instead of `\end{tcolorbox}`.

```
\newenvironment{mybox}[1]{%
  \tcolorbox[savedelimiter=mybox,
  savelowerto=\jobname_bpsave2.tex,lowerbox=ignored,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=#1]%
}{\endtcolorbox}

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bpsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

The `savedelimiter` is used implicitly with `\newtcolorbox→ P.15` which allows a more convenient usage:

```
\newtcolorbox{mybox}[1]{%
  savelowerto=\jobname_bpsave2.tex,lowerbox=ignored,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=#1}%

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bpsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

4.5 Colors and Fonts

`/tcb/colframe=<color>` (no default, initially `black!75!white`)

Sets the frame `<color>` of the box.

```
\begin{tcolorbox}[colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/colback=<color>` (no default, initially `black!5!white`)

Sets the background `<color>` of the box.


```
\begin{tcolorbox}[colback=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/title filled=true|false` (default `true`, initially `false`)

Switches the drawing of the title background according to the given value. This option is set to `true` automatically by `/tcb/colbacktitle`, `/tcb/opacitybacktitle`^{P.50}, and `/tcb/title style`^{P.143}, and `/tcb/title code`^{P.132}.


```
\begin{tcolorbox}[title=My title,title filled]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[title=My title,
  title filled=false]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/colbacktitle=<color>` (no default, initially `black!50!white`)

Sets the background `<color>` of the title area of the box.

```
\begin{tcolorbox}[colbacktitle=red!50!white,
  title=My title,coltitle=black,
  fonttitle=\bfseries]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



/tcb/colupper=<color> (no default, initially black)

Sets the text <color> of the upper part.

```
\begin{tcolorbox}[colupper=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a tcolorbox.

This is the lower part.

/tcb/collower=<color> (no default, initially black)

Sets the text <color> of the lower part.

```
\begin{tcolorbox}[collower=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a tcolorbox.

This is the lower part.

/tcb/coltext=<color> (style, no default, initially black)

Sets the text <color> of the box. This is an abbreviation for setting colupper and collower to the same value.

```
\begin{tcolorbox}[coltext=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a tcolorbox.

This is the lower part.

/tcb/coltitle=<color> (no default, initially white)

Sets the title text <color> of the box.

```
\begin{tcolorbox}[coltitle=red!75!black,
colbacktitle=black!10!white,title=Test]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Test

This is a tcolorbox.

/tcb/fontupper=*<text>* (no default, initially empty)

Sets *<text>* before the content of the upper part (e.g. font settings).

```
\begin{tcolorbox}[fontupper=Hello!~\sffamily]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello! This is a **tcolorbox**.

/tcb/fontlower=*<text>* (no default, initially empty)

Sets *<text>* before the content of the lower part (e.g. font settings).

```
\begin{tcolorbox}[fontlower=\sffamily\bfseries]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/fonttitle=*<text>* (no default, initially empty)

Sets *<text>* before the content of the title text (e.g. font settings).

```
\begin{tcolorbox}[fonttitle=\sffamily\bfseries\large,title=Hello]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello

This is a **tcolorbox**.



More color options are provided by using skins documented in Section 10 from page 140.

4.6 Text Alignment

N 2015-05-07

`/tcb/halign=<alignment>` (no default, initially `justify`)

If there is no lower part, `halign` determines the horizontal `<alignment>` of the text content. Otherwise, `halign` determines the horizontal `<alignment>` of the upper part of the box only. The feasible values for `<alignment>` are more or less identical to the corresponding `/tikz/align` settings, even if the implementation differs.

- `justify`: usual left and right justified type setting.
- `left`: left border justification in analogy to plain TeX.
- `flush left`: left border justification with `\raggedright` of LATEX.
- `right`: right border justification in analogy to plain TeX.
- `flush right`: right border justification with `\raggedleft` of LATEX.
- `center`: centering in analogy to plain TeX.
- `flush center`: centering with `\centering` of LATEX.

The differences between the flush and non-flush version are explained in detail in the TikZ manual [20]. The short story is that the non-flush versions will often look more balanced but with more hyphenations.

```
\tcbset{colback=red!5!white,colframe=red!75!black,size=small,
fonttitle=\bfseries,width=3.5cm,box align=top,
nobeforeafter}

\begin{tcolorbox}[adjusted title=flush center,halign=flush center]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush left,halign=flush left]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush right,halign=flush right]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=center,halign=center]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=left,halign=left]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=right,halign upper=right]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
```

flush center

This is a demonstration text for showing how line breaking works.

flush left

This is a demonstration text for showing how line breaking works.

flush right

This is a demonstration text for showing how line breaking works.

center

This is a demonstration text for showing how line breaking works.

left

This is a demonstration text for showing how line breaking works.

right

This is a demonstration text for showing how line breaking works.

N 2015-05-07

`/tcb/halign upper=<alignment>` (no default, initially `justify`)


Alias for `/tcb/halign`.

`halign lower` determines the horizontal `<alignment>` of the lower part of the box. The feasible values for `<alignment>` are the same as for `/tcb/halign`^{→ P.30.}

```
\begin{tcbraster}[raster columns=3,fonttitle=\bfseries,
colback=red!5!white,colframe=red!75!black]

\begin{tcolorbox}[adjusted title=flush center,halign lower=flush center]
Upper part. \tcblower Lower part.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush left,halign lower=flush left]
Upper part. \tcblower Lower part.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush right,halign lower=flush right]
Upper part. \tcblower Lower part.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=center,halign lower=center]
Upper part. \tcblower Lower part.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=left,halign lower=left]
Upper part. \tcblower Lower part.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=right,halign lower=right]
Upper part. \tcblower Lower part.
\end{tcolorbox}

\end{tcbraster}
```



N 2015-05-07	/tcb/halign title=<alignment>	(no default, initially justify)												
	halign lower determines the horizontal $\langle alignment \rangle$ of the title of the box. The feasible values for $\langle alignment \rangle$ are the same as for $/tcb/halign \rightarrow P.30$.													
<pre>\begin{tcbraster}[raster columns=3,fonttitle=\bfseries, colback=red!5!white,colframe=red!75!black] \begin{tcolorbox}[adjusted title=flush center,halign title=flush center] This is a \textbf{tcolorbox}. \end{tcolorbox} \begin{tcolorbox}[adjusted title=flush left,halign title=flush left] This is a \textbf{tcolorbox}. \end{tcolorbox} \begin{tcolorbox}[adjusted title=flush right,halign title=flush right] This is a \textbf{tcolorbox}. \end{tcolorbox} \begin{tcolorbox}[adjusted title=center,halign title=center] This is a \textbf{tcolorbox}. \end{tcolorbox} \begin{tcolorbox}[adjusted title=left,halign title=left] This is a \textbf{tcolorbox}. \end{tcolorbox} \begin{tcolorbox}[adjusted title=right,halign title=right] This is a \textbf{tcolorbox}. \end{tcolorbox} \end{tcbraster}</pre>														
<table border="1"> <thead> <tr> <th>flush center</th> <th>flush left</th> <th>flush right</th> </tr> </thead> <tbody> <tr> <td>This is a tcolorbox.</td> <td>This is a tcolorbox.</td> <td>This is a tcolorbox.</td> </tr> <tr> <td>center</td> <td>left</td> <td>right</td> </tr> <tr> <td>This is a tcolorbox.</td> <td>This is a tcolorbox.</td> <td>This is a tcolorbox.</td> </tr> </tbody> </table>			flush center	flush left	flush right	This is a tcolorbox .	This is a tcolorbox .	This is a tcolorbox .	center	left	right	This is a tcolorbox .	This is a tcolorbox .	This is a tcolorbox .
flush center	flush left	flush right												
This is a tcolorbox .	This is a tcolorbox .	This is a tcolorbox .												
center	left	right												
This is a tcolorbox .	This is a tcolorbox .	This is a tcolorbox .												
U 2015-05-07 /tcb/flushleft upper (style, no value) Shortcut for setting $/tcb/halign \rightarrow P.30$ to flush left .														
U 2015-05-07 /tcb/center upper (style, no value) Shortcut for setting $/tcb/halign \rightarrow P.30$ to flush center .														
U 2015-05-07 /tcb/flushright upper (style, no value) Shortcut for setting $/tcb/halign \rightarrow P.30$ to flush right .														
U 2015-05-07 /tcb/flushleft lower (style, no value) Shortcut for setting $/tcb/halign lower \rightarrow P.31$ to flush left .														
U 2015-05-07 /tcb/center lower (style, no value) Shortcut for setting $/tcb/halign lower \rightarrow P.31$ to flush center .														
U 2015-05-07 /tcb/flushright lower (style, no value) Shortcut for setting $/tcb/halign lower \rightarrow P.31$ to flush right .														
U 2015-05-07 /tcb/flushleft title (style, no value) Shortcut for setting $/tcb/halign title$ to flush left .														
U 2015-05-07 /tcb/center title (style, no value) Shortcut for setting $/tcb/halign title$ to flush center .														
U 2015-05-07 /tcb/flushright title (style, no value) Shortcut for setting $/tcb/halign title$ to flush right .														

! The vertical alignment settings are only relevant for boxes which are larger than their natural height, see Section 4.10 on page 52.

U 2015-07-16

/tcb/valign=⟨alignment⟩ (no default, initially top)

If the height of a **tcolorbox** is not the natural height, **valign** determines the vertical ⟨alignment⟩ of the upper part. Feasible values are

- **top**: Anchor text at top.
- **center**: Anchor text at center.
- **bottom**: Anchor text at bottom.
- **scale**: Scale text vertically to fit into the available space. This is brutal and may not look very good. Consider Section 19 on page 383 alternatively.
- **scale***: Like **scale**, but scaling is bounded by **/tcb/valign scale limit**.

For a box with natural height, these settings are meaningless.

```
\tcbset{width=(\linewidth-2mm)/4,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=2cm}

\foreach \myalign in {top,center,bottom,scale}
{\begin{tcolorbox}[valign=\myalign]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2015-05-07

/tcb/valign upper=⟨alignment⟩ (no default, initially top)

Alias for **/tcb/valign**.

/tcb/valign lower=⟨alignment⟩ (no default, initially top)

This key has the same meaning for the lower part as **valign** for the upper part, i.e., it determines the vertical ⟨alignment⟩ of the lower part with feasible values **top**, **center**, **bottom**, **scale**, and **scale***.

N 2015-07-16

/tcb/valign scale limit=⟨real number⟩ (no default, initially 1.1)

Sets an upper scale limit for the **scale*** setting in **/tcb/valign** and **/tcb/valign lower**. Note that this value is not reset by **/tcb/reset**^{→ P. 99}. So, changes also apply to embedded boxes.

Also see **/tcb/sidebyside align**^{→ P. 110} for alignment settings when upper part and lower part are set side-by-side.

4.7 Geometry

4.7.1 Width

`/tcb/width=<length>` (no default, initially `\ linewidth`)

Sets the total width of the colored box to `<length>`. See also `/tcb/height`^{P.52}.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=\ linewidth/2]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-31

`/tcb/text width=<length>` (style, no default)

Sets the text width of the upper part to `<length>`. See also `/tcb/text height`^{P.53}.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text width=4cm]
This is a \textbf{tcolorbox} where the text has a width of 4cm.
\end{tcolorbox}
```

This is a **tcolorbox** where
the text has a width of 4cm.

N 2014-11-07

`/tcb/add to width=<length>` (style, no default)

Adds `<length>` to the current total width of the colored box.

```
\tcbset{width=4cm,colback=red!5!white,
colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[add to width=1cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

See Section 4.10 on page 52 for setting fixed height values.

4.7.2 Rules

/tcb/toprule=*<length>* (no default, initially 0.5mm)

Sets the line width of the top rule to *<length>*.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toprule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/bottomrule=*<length>* (no default, initially 0.5mm)

Sets the line width of the bottom rule to *<length>*.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/leftrule=*<length>* (no default, initially 0.5mm)

Sets the line width of the left rule to *<length>*.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/rightrule=*<length>* (no default, initially 0.5mm)

Sets the line width of the right rule to *<length>*.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[rightrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/titlerule=<length>` (no default, initially 0.5mm)

Sets the line width of the rule below the title to `<length>`.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,  
colbacktitle=red!90!black}  
  
\begin{tcolorbox}[titlerule=3mm,title=This is the title]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is the title

This is a **tcolorbox**.

`/tcb/boxrule=<length>` (style, no default, initially 0.5mm)

Sets all rules of the frame to `<length>`, i.e. `/tcb/toprule`^{P. 35}, `/tcb/bottomrule`^{P. 35}, `/tcb/leftrule`^{P. 35}, `/tcb/rightrule`^{P. 35}, and `/tcb/titlerule`.

```
\tcbset{colback=red!5!white,colframe=red!75!black}  
  
\begin{tcolorbox}[boxrule=3mm]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.



More options for drawing a `/tcb/borderline`^{P. 169} are provided by using skins documented in Section 10 from page 140.

4.7.3 Arcs

`/tcb/arc=<length>` (no default, initially 1mm)

Sets the inner radius of the four frame arcs to `<length>`.

```
\tcbset{colback=red!5!white,colframe=red!75!black}  
  
\begin{tcolorbox}[arc=0mm]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}  
\begin{tcolorbox}[arc=3mm]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2015-05-05

/tcb/circular arc

(style, no value)

Sets `/tcb/arc`^{→ P. 36} to match the half of the inner width of the colored box. If width and height of the box are identical, this gives a circle.



If the height of the box is smaller than the width, the result will look quite ugly.

```
\begin{tcolorbox}[width=3cm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center, valign=center,
  square, circular arc]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a
tcolorbox.

N 2015-05-05

/tcb/bean arc

(style, no value)

Sets `/tcb/arc`^{→ P. 36} to match the smaller value of the half of the inner width and of the inner height of the colored box.



This only works for a fixed `/tcb/height`^{→ P. 52}. Also, `/tcb/bean arc` must be used after width and height are set by option keys.

```
\tcbsize{fbox, boxrule=0.5mm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center, valign=center}

\begin{tcolorbox}[width=3cm, height=2cm,
  bean arc]
Box A
\end{tcolorbox}

\begin{tcolorbox}[width=2cm, height=3cm,
  bean arc]
Box B
\end{tcolorbox}
```

Box A

Box B

N 2015-05-05

/tcb/octagon arc

(style, no value)

Sets `/tcb/arc`^{→ P. 36} to match $\frac{1}{2+\sqrt{2}}$ of the inner width of the colored box. If width and height of the box are identical, the interior is a regular octagon.

```
\begin{tcolorbox}[enhanced,
  size=minimal, auto outer arc,
  width=2.1cm, octagon arc,
  colback=red, colframe=white, colupper=white,
  fontupper=\fontsize{7mm}{7mm}\selectfont\bfseries\sffamily,
  halign=center, valign=center,
  square, arc is angular,
  borderline={0.2mm}{-1mm}{red} ]
STOP
\end{tcolorbox}
```



N 2015-05-05

/tcb/arc is angular

(no value, initially unset)

Using this options applies a patch which straightens the corners arcs of the boxes. The little arcs are replaced by little straight lines.

! This patch is considered as an experimental feature. It changes some of the original TikZ code. This change may break with future updates of TikZ.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
arc=3mm}

\begin{tcolorbox}[arc is angular]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[arc is curved]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

N 2015-05-05

/tcb/arc is curved

(no value, initially set)

This option resets the patch from /tcb/arc is angular. The original TikZ code is activated.

/tcb/outer arc=<length>

(no default, initially unset)

Sets the outer radius of the four frame arcs to <length>.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=4mm,outer arc=1mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/auto outer arc

(no value, initially set)

Sets the outer radius of the four frame arcs automatically in dependency of the inner radius given by /tcb/arc^{P. 36}.

4.7.4 Spacing

/tcb/boxsep=<length>

(no default, initially 1mm)

Sets a common padding of <length> between the text content and the frame of the box. This value is added to the key values of `left`, `right`, `top`, `bottom`, and `middle` at the appropriate places.

```
\tcbset{colback=red!5!white,colframe=red!75!black,width=(\linewidth-4mm)/2,
before=,after=\hfill}

\begin{tcolorbox}[boxsep=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[boxsep=5mm,draft]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

frame: w=195.33255pt, h=48.97505pt

This is a tcolorbox.

upper: w=115.2724pt, h=6.296pt

interior: w=192.4873pt, h=46.1298pt

`/tcb/left=<length>` (style, no default, initially 4mm)

Sets the left space between all text parts and frame (additional to `boxsep`). This is an abbreviation for setting `lefttitle`, `leftupper`, and `leftlower` to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[left=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/lefttitle=<length>` (no default, initially 4mm)

Sets the left space between title text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[lefttitle=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

`/tcb/leftupper=<length>` (no default, initially 4mm)

Sets the left space between upper text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftupper=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

`/tcb/leftlower=<length>` (no default, initially 4mm)

Sets the left space between lower text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftlower=3cm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/right=<length> (style, no default, initially 4mm)

Sets the right space between all text parts and frame (additional to `boxsep`). This is an abbreviation for setting `righttitle`, `rightupper`, and `rightlower` to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,right=2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcol-
orbox**.

/tcb/righttitle=<length> (no default, initially 4mm)

Sets the right space between title text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,righttitle=2cm,title=My very long title text]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\end{tcolorbox}
```

My very long ti-
tle text

This is a **tcolorbox** with
standard upper box dimen-
sions.

/tcb/rightupper=<length> (no default, initially 4mm)

Sets the right space between upper text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightupper=2cm,title=My very long title text]
This is a \textbf{tcolorbox} with compressed upper box dimensions.
\end{tcolorbox}
```

My very long title text

This is a **tcol-
orbox** with
compressed
upper box
dimensions.

/tcb/rightlower=<length> (no default, initially 4mm)

Sets the right space between lower text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightlower=2cm]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\tcblower
This is the lower part with large space at right.
\end{tcolorbox}
```

This is a **tcolorbox** with standard upper box dimensions.

This is the lower part with large space at right.

/tcb/top=<length> (no default, initially 2mm)

Sets the top space between text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[top=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/toptitle=<length> (no default, initially 0mm)

Sets the top space between title and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toptitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/bottom=*(length)* (no default, initially 2mm)

Sets the bottom space between text and frame (additional to **boxsep**).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottom=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/bottomtitle=*(length)* (no default, initially 0mm)

Sets the bottom space between title and frame (additional to **boxsep**).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomtitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/middle=*(length)* (no default, initially 2mm)

Sets the space between upper and lower text to the separation line (additional to **boxsep**).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[middle=0mm,boxsep=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.
This is the lower part.

4.7.5 Size Shortcuts

`/tcb/size=(name)` (no default, initially `normal`)

Sets all geometry keys with exception of `/tcb/width`^{→ P. 34} to predefined length values. For `(name)`, the following values are feasible:


- `normal`: normal sized boxes e.g. of width `\ linewidth`.
- `title`: title line sized boxes.
- `small`: small boxes e.g. for keyword highlighting.
- `fbox`: identical to the standard `\fbox`.
- `tight`: no padding space at all.
- `minimal`: no padding space, no box rules.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\foreach \s in {minimal,tight,fbox,small,title,normal} {
  \tcbbox[size=\s,on line]{\s} }

\foreach \s in {minimal,tight,fbox,small,title,normal} {
  \tcbbox[size=\s,on line,title=Test]{\s} }

\foreach \s in {minimal,tight,fbox,small,title,normal} {
  \begin{tcolorbox}[size=\s,on line,title=Test,width=2.2cm]
    \s \tcblower lower\end{tcolorbox} }
```



Predefined values

	normal	title	small	fbox	tight	minimal
boxrule	0.5mm	0.4mm	0.3mm	0.4pt	0.4pt	0.0pt
boxsep	1.0mm	1.0mm	1.0mm	3.0pt	0.0pt	0.0pt
left	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
right	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
top	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
bottom	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
toptitle	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
bottomtitle	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
middle	2.0mm	0.75mm	0.5mm	1.0pt	0.2pt	0.0pt
arc	1.0mm	0.75mm	0.5mm	1.0pt	0.0pt	0.0pt
outer arc	auto	auto	auto	auto	0.0pt	0.0pt

/tcb/oversize=<length>

(style, default 0pt)

Sets the text width of the upper part to the current line width plus an optional *<length>*. This is achieved by changing the keys /tcb/width^{→ P. 34} /tcb/enlarge left by^{→ P. 81}, and /tcb/enlarge right by^{→ P. 81} appropriately. The resulting box is overlapping into the left and right margin of the page. Note that this style option has to be given *after* all other geometry keys!

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\textrit{Normal text for comparison:} \\
\lipsum[2]

\begin{tcolorbox}[oversize,title=Oversized box]
\lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[title=Normal box]
\lipsum[2]
\end{tcolorbox}
```

Normal text for comparison:

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Oversized box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Normal box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

According to the `<toggle preset>`, the left and the right settings of the `tcolorbox` are switched or not. Feasible values are:

- `none`: no switching.
- `forced`: the values of the left and right rules and spaces are switched.
- `evenpage`: if the page is an even page, the values of the left and right rules and spaces are switched. This value also sets `/tcb/check odd page`^{→ P. 96} to `true`.

! Horizontal bounding box enlargements are not toggled by this option. They can be toggled independently by `/tcb/toggle enlargement`^{→ P. 84}. For example, `/tcb/oversize`^{→ P. 44} changes the bounding box.

```
% \usepackage{lipsum}
% \usetikzlibrary{patterns}
% \tcbuselibrary{skins,breakable}
\begin{tcolorbox}[skin=enhancedmiddle,breakable,
  toggle left and right,
  boxrule=0mm,top=0mm,bottom=0mm,left=1mm,right=1mm,
  rightrule=1cm,colupper=blue!25!black,
  interior style={fill overzoom image=lichtspiel.jpg,fill image opacity=0.25},
  frame style={pattern=crosshatch dots light steel blue},
  overlay={%
    \tcbifoddpage{\coordinate (X) at ([xshift=-5mm]frame.east);}
    {\coordinate (X) at ([xshift=5mm]frame.west);}
    \fill[shading=ball,ball color=blue!50!white,opacity=0.5] (X) circle (4mm);}
\lipsum[1-6]
\end{tcolorbox}
```

This example switches a 1cm thick rule from the left to the right side depending on the page number. Thereby, the rule is always on the outer side of the double-sided paper. Additionally, a ball is drawn on the outer side with help of an overlay.

Lore ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellen-tesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit

ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

4.8 Corners

The four corners of any `tcolorbox` can be set individually as `/tcb/sharp corners` or as `/tcb/rounded corners`^{→ P. 48}. These settings are also reflected in the behavior of `/tcb/borderline`^{→ P. 169} and `/tcb/shadow`^{→ P. 180} as one would expect.

By default, all four corners are *rounded*. So, only the `/tcb/sharp corners` option will be necessary for most use cases. The `/tcb/rounded corners`^{→ P. 48} option can be used to revert a `/tcb/sharp corners` setting.

`/tcb/sharp corners=<position>` (default `all`, initially unset)

The `<position>` denotes one or more of the four box corners to be set as *sharp* corners. The not assigned corners will retain their mode. Feasible values for `<position>` are:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,  
colframe=red!75!black,  
sharp corners=northwest ]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a `tcolorbox`.

```
\begin{tcolorbox}[colback=red!5!white,  
colframe=red!75!black,  
sharp corners ]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a `tcolorbox`.

`/tcb/rounded corners=<position>` (default `all`, initially `all`)

The `/tcb/rounded corners` can be used to revert a `/tcb/sharp corners`^{P.47} setting. The `<position>` denotes one or more of the four box corners to be set as *rounded* corners. The not assigned corners will retain their mode. Feasible values for `<position>` are²:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,  
colframe=red!75!black,sharp corners,  
rounded corners=northwest ]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/sharpish corners`

(style, no value)

Shortcut for setting `/tcb/arc`^{P.36} and `/tcb/outer arc`^{P.38} to `0pt`. With this setting, rounded corners will appear as quasi-sharp, but e. g. the shadow will be somewhat rounder than the shadow of really sharp corners.

! Corners are still of type *rounded* with this option, but appear *sharp*. To switch back to rounded corners, one has to adapt `/tcb/arc`^{P.36} and `/tcb/outer arc`^{P.38}.

```
\begin{tcolorbox}[colback=red!5!white,  
colframe=red!75!black,  
sharpish corners ]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.


²The graphical examples assume that the boxes were set to have sharp corners before.

The following examples will show the differences between `/tcb/rounded corners`^{→ P. 48}, `/tcb/sharpish corners`^{→ P. 48}, and `/tcb/sharp corners`^{→ P. 47}. The later two give the same core box, but `/tcb/borderline`^{→ P. 169} and `/tcb/shadow`^{→ P. 180} settings are slightly different. The following examples use `/tcb/drop fuzzy shadow`^{→ P. 174}.

My title

This is a **tcolorbox**.


rounded corners



My title

This is a **tcolorbox**.


sharpish corners



My title

This is a **tcolorbox**.

sharp corners



4.9 Transparency

! Transparency effects are likely to be used in conjunction with *jigsaw* skin variants, see Section 10.10 on page 191.

/tcb/opacityframe=⟨fraction⟩ (no default, initially 1.0)
Sets the frame opacity of the box to the given ⟨fraction⟩.

```
\begin{tcolorbox}[opacityframe=0.25,  
colframe=red]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/opacityback=⟨fraction⟩ (no default, initially 1.0)
Sets the background opacity of the box to the given ⟨fraction⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,  
opacityframe=0.5, opacityback=0.5]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/opacitybacktitle=⟨fraction⟩ (no default, initially 1.0)
Sets the title background opacity of the box to the given ⟨fraction⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,  
opacityframe=0.5, opacitybacktitle=0.5,  
title filled, title=This is a title]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a title

This is a tcolorbox.

/tcb/opacityfill=⟨fraction⟩ (style, no default, initially 1.0)
Sets the fill opacity for frame, interior and optionally the title background to the given ⟨fraction⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,  
opacityfill=0.7, title=This is a title]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a title

This is a tcolorbox.

`/tcb-opacityupper=<fraction>` (no default, initially 1.0)

Sets the text opacity of the upper box part to the given `<fraction>`.

```
\begin{tcolorbox}[enhanced,opacityupper=0.5,
    interior style={pattern=checkerboard light }
    &gray]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb-opacitylower=<fraction>` (no default, initially 1.0)

Sets the text opacity of the lower box part to the given `<fraction>`.

```
\begin{tcolorbox}[enhanced,opacitylower=0.5,
    interior style={pattern=checkerboard light }
    &gray]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a tcolorbox.

This is the lower part.

`/tcb-opacitytext=<fraction>` (no default, initially 1.0)

Sets the text opacity of the upper and the lower box part to the given `<fraction>`.

```
\begin{tcolorbox}[enhanced,opacitytext=0.5,
    interior style={pattern=checkerboard light }
    &gray]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a tcolorbox.

This is the lower part.

`/tcb-opacitytitle=<fraction>` (no default, initially 1.0)

Sets the text opacity of the box title to the given `<fraction>`.

```
\begin{tcolorbox}[enhanced,opacitytitle=0.7,
    coltitle=black,
    fonttitle=\bfseries,title=This is a title,
    title style={pattern=checkerboard light }
    &gray]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a tcolorbox.

```
\begin{tcolorbox}[enhanced jigsaw,fonttitle=\bfseries,title=This is a title,
    opacityframe=0.5,opacityback=0.25,opacitybacktitle=0.25,opacitytext=0.8,
    colback=red!5!white,colframe=red!75!black,colbacktitle=yellow!20!red]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a tcolorbox.

4.10 Height Control

In a typical usage scenario, the height of a `tcolorbox` is computed automatically to fit the content. Nevertheless, the height can be set to a fixed value or to fit commonly for several boxes, e.g. if boxes are set side by side.

! The height control keys are only applicable to unbreakable boxes. If a box is set to be `/tcb/breakable`^{→ P. 353}, the height is always computed according to the *natural height*.

/tcb/natural height (no value, initially set)

Sets the total height of the colored box to its natural height depending on the box content.

/tcb/height=⟨length⟩ (no default)

Sets the total height of the colored box to `⟨length⟩` independent of the box content. `⟨length⟩` is the minimum height of the box, if `/tcb/height plus` is larger than zero.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white}

\begin{tcolorbox}[height=1cm,valign=center]
This box has a height of 1cm.
\end{tcolorbox}
\begin{tcolorbox}[height=2cm,valign=center]
This box has a height of 2cm.
\end{tcolorbox}
\begin{tcolorbox}[height=3cm,split=0.5,valign=center,valign lower=center]
This box has a height of 3cm.
\tcblower
Lower part.
\end{tcolorbox}
```

This box has a height of 1cm.

This box has a height of 2cm.

This box has a height of 3cm.

Lower part.

/tcb/height plus=⟨length⟩ (no default, initially 0pt)

The box may extend a given fixed `/tcb/height` up to the given `⟨length⟩`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,width=3cm,nobeforeafter}

\begin{tcolorbox}[height=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox.
This is a tcolorbox.
This is a tcolorbox.

`/tcb/height from=<min> to <max>`

(style, no default)

Sets the box height to a dimension between `<min>` and `<max>`.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}[1]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
bottom=1mm,right=1mm,boxsep=0mm,width=4.5cm,nobeforeafter,
height from=2cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatiibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

N 2014-10-31 `/tcb/text height=<length>`

(style, no default)

Sets the text height to `<length>`. This is the length from the top of the upper part to the bottom of the optional lower part. See also `/tcb/text width`^{P.34}.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text height=2cm]
This is a \textbf{tcolorbox} where the text area has a height of 2cm.
\end{tcolorbox}
```

This is a tcolorbox where the text area has a height of 2cm.

N 2014-11-07

/tcb/add to height=⟨length⟩ (style, no default)

Adds ⟨length⟩ to the current height of the colored box. **/tcb/height**^{→ P.52} has to be set before this key is used! If this option is used several times, then the **/tcb/height**^{→ P.52} is also increased several times.

```
\tcbset{height=1cm,  
  valign=center,width=(\linewidth-2mm)/2,  
  before=,after=\hfill,colframe=blue!75!black,colback=white}  
  
\begin{tcolorbox}  
  This box has a height of 1cm.  
\end{tcolorbox}  
\begin{tcolorbox}[add to height=1cm]  
  This box has a height of 2cm.  
\end{tcolorbox}
```

This box has a height of 1cm.

This box has a height of 2cm.

N 2016-02-16

/tcb/add to natural height=⟨length⟩ (style, no default)

The application of this option generates a box with natural height plus the given ⟨length⟩. If this option is used several times, then the last setting of ⟨length⟩ wins. The resulting box is not considered a fixed height box and the implementation is quite different to **/tcb/add to height**.

```
\tcbset{valign=center,width=(\linewidth-2mm)/2,  
  before=,after=\hfill,colframe=blue!75!black,colback=white}  
  
\begin{tcolorbox}  
  This box has natural height.  
\end{tcolorbox}  
\begin{tcolorbox}[add to natural height=1cm]  
  This box has natural height plus 1 cm.  
\end{tcolorbox}
```

This box has natural height.

This box has natural height plus 1 cm.

/tcb/height fill=true|false|maximum (default true, initially false)

If set to **true**, the height of the **tcolorbox** is set to the rest of the available vertical space of the current page. If set to **maximum**, the page is compressed as much as possible. Note that the **tcolorbox** is always set as its own paragraph using this option. Also see /tcb/text fill^{→ P. 65}.



Note that the library `\usepackage[breakable]` has to be loaded to use this key!

This height control key is only applicable to unbreakable boxes but it uses code from the library `\usepackage[breakable]`. The counterpart for breakable boxes is /tcb/height fixed for^{→ P. 358}.

This option can and should not be used for boxes in boxes, but it can be used for boxes inside a **tcbraster**^{→ P. 268}.

```
% \usepackage{lipsum}
% \tcbuselibrary{breakable}
\begin{tcolorbox}[height fill,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Box which fills the rest of the page]
\lipsum[1]
\end{tcolorbox}
```

Box which fills the rest of the page

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/square

(style, no value)

Sets `/tcb/height`^{→ P.52} to match the width of the colored box.

```
\begin{tcolorbox}[width=3cm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center, valign=center,
  square]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a
tcolorbox.

/tcb/space=<fraction>

(no default, initially 0)

If the height of a **tcolorbox** is not the natural height, the space difference between the forced and the natural size is distributed between the upper and the lower part of the box. This space could also be negative. `<fraction>` with a value between 0 and 1 is the amount of space which is added to the upper part, the rest is added to the lower part. If there is no lower part, then all of the space is added to the upper part always.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \f in {0.2,0.4,0.7}
{\begin{tcolorbox}[space=\f]
  This is the upper part.
  \tcblower
  This is the lower part.
\end{tcolorbox}}
```

This is the upper part.

This is the lower part.

This is the upper part.

This is the lower part.

This is the upper part.

This is the lower part.

/tcb/space to upper

(style)

This is an abbreviation for `space=1`, i.e. all extra space is added to the upper part.

/tcb/space to lower

(style, initially set)


This is an abbreviation for `space=0`, i.e. all extra space is added to the lower part (if there is any).

/tcb/space to both

(style)

This is an abbreviation for `space=0.5`, i.e. the extra space equally distributed between the upper and the lower part.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,  
colframe=blue!75!black,colback=white,height=3cm}  
  
\foreach \myspace in {space to upper,space to both,space to lower}  
{\begin{tcolorbox}[\myspace]  
    This is the upper part.  
    \tcblower  
    This is the lower part.  
\end{tcolorbox}}
```



N 2015-02-15

/tcb/space to=<macro>

(no default, initially unset)

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is saved into the given local `<macro>`. This `<macro>` can and should be used inside the box content to add content which is vertically sized to match `<macro>`.



- The actual length saved into `<macro>` is adapted dynamically during several compilations – at least two, but maybe more.
- Due to the adaption algorithm, objects can be sized with `<macro>` plus any offset length.
- Never ever use `<macro>` multiplied with a factor. The only exception to this rule is that the space can be split into parts which sum to `<macro>`.
- Never use this in combination with `/tcb/fit`^{P. 385}.

```
\begin{tcolorbox}[colframe=blue!75!black,colback=white,height=3cm,  
space to=\myspace]  
  
This is my box of height 3cm. The space is filled with a picture:\\[2mm]  
\includegraphics[width=\linewidth,height=\myspace]{goldshade.png}\\[1mm]  
This is some other text.  
\end{tcolorbox}
```

This is my box of height 3cm. The space is filled with a picture:



This is some other text.

```
\begin{tcolorbox}[colframe=blue!75!black,colback=white,height=3cm,
  space to=\myspace]
\includegraphics[width=\linewidth,
  height=0.33\dimexpr\myspace]{blueshade.png}\vspace{1mm}
This is my box of height 3cm.\vspace{2mm}
\includegraphics[width=\linewidth,
  height=0.67\dimexpr\myspace]{goldshade.png}
\end{tcolorbox}
```



/tcb/*split*=⟨fraction⟩

(no default)

If the height of a `tcolorbox` is not the natural height, the ⟨fraction⟩ with a value between 0 and 1 determines the positioning of the segmentation between the upper and the lower part. Here, 0 stands for top and 1 for bottom. Note that the box is split regardless of the actual dimensions of the text parts!

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,height=3cm,
colback=white,colframe=blue!75!black,valign=center,valign lower=center}

\foreach \f in {0.1,0.5,0.8}
{\begin{tcolorbox}[split=\f]
This is the upper part.
\tcblower
This is the lower part with a lot of text in several lines.
\end{tcolorbox}}
```

This is the upper part.

This is the upper part.

This is the upper part.

This is the lower part
with a lot of text in sev-
eral lines.

This is the lower part
with a lot of text in sev-
eral lines.

This is the lower part
with a lot of text in sev-
eral lines.

Boxes which are members of an `equal height group` will all get the same height, i.e. the maximum of all their natural heights. The `<id>` serves to distinguish between different height groups. Note that you have to compile twice to see changes and that height groups are global definitions.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,arc=0mm,
colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[equal height group=A,adjusted title={One}]
My smallest box.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Two}]
This box is also small.
\tcblower
But with a lower part.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Three}]
This box contains a lot of text just to fill the space
with word flowing and flowing and flowing until the box
is filled with all of it.
\end{tcolorbox}\linebreak
%
\tcbset{width=(\linewidth-1mm)/2,before=,after=\hfill,arc=0mm,
colframe=red!75!black,colback=white}
%
\begin{tcolorbox}[equal height group=B]
Now, we use another equal height group.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=B,after=]
\begin{equation*}
\int\limits_0^1 x^2 = \frac{1}{3}.
\end{equation*}
\end{tcolorbox}
```

One	Two	Three
My smallest box.	This box is also small. But with a lower part.	This box contains a lot of text just to fill the space with word flowing and flowing and flowing until the box is filled with all of it.
Now, we use another equal height group.		$\int_0^1 x^2 = \frac{1}{3}.$



See Section 14 on page 266 for more equal height options.

`/tcb/minimum for equal height group=<id>:<length>` (no default, initially unset)

Plants a `<length>` into the equal height group with the given `<id>`. This ensures that the height will not drop below `<length>`. Note that you cannot reduce a computed height value by using this key with a small value. The difference to applying `/tcb/height` → P. 52 directly is that the boxes are never too small for their content.

```
\tcbsset{colframe=blue!75!black,colback=white,arc=0mm,
  before=,after=\hfill,fonttitle=\bfseries,left=2mm,right=2mm,
  width=3.5cm,
  equal height group=C,
  minimum for equal height group=C:3.5cm}

\begin{tcolorbox}
My first box. All boxes will get 3.5cm times 3.5cm
if the content height is not too large.
\end{tcolorbox}%
\begin{tcolorbox}
My second box.
\tcblower
This is the lower part.
\end{tcolorbox}%
\begin{tcblisting}{}%
\textbf{Mixed}
with a listing.
\end{tcblisting}%
\begin{tcolorbox}[title={Fourth box}]
My final box.
\end{tcolorbox}%
```

My first box. All boxes will get 3.5cm times 3.5cm if the content height is not too large.

My second box.

This is the lower part.

`\textbf{Mixed}`
with a listing.

Mixed with a listing.

Fourth box

My final box.

N 2016-03-24

`/tcb/minimum for current equal height group=<length>` (no default, initially unset)

Sets `/tcb/minimum for equal height group` for the current equal height group. Apparently, this only works for an already known equal height group, i.e. `/tcb/equal height group` → P. 59 has to be set *before* this option is used. This option is likely to be used in combination with `/tcb/raster equal height` → P. 276

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster equal height,colframe=blue!75!black,colback=white,
  raster every box/.style={minimum for current equal height group=2cm}]
\tcbitem A
\tcbitem B
\end{tcbitemize}
```

A

B

N 2015-11-27
U 2016-02-22

/tcb/use height from group=<id>

(style, default current group)

Sets the current box to a fixed /tcb/height^{→ P. 52} which is copied from an equal height group with the given <id>. If this height is not available during the current compilation, no fixed height setting is used. If <id> is omitted, the current equal height group is used which has to be set before by /tcb/equal height group^{→ P. 59}.

Note that the natural height of the current box is not considered for computation of the group height. The main application for /tcb/use height from group is that the height can be adapted further by /tcb/add to height^{→ P. 54}.

```
\begin{tcolorbox}[use height from group=C,add to height=-2cm,  
colframe=blue!75!black,colback=white]  
Height from group 'C' of the previous example, but reduced by 2cm.  
\end{tcolorbox}%
```

Height from group 'C' of the previous example, but reduced by 2cm.

```
% \tcbuselibrary{raster}  
Every line is inside an equal height group:  
\begin{tcbraster}[raster equal height=rows,  
title=Box \thetcbrasternum,  
enhanced,size=small,colframe=red!50!black,colback=red!10!white]  
\begin{tcolorbox}First line\\second line\\  
The height of this box rules.\end{tcolorbox}  
\begin{tcolorbox}[use height from group]Test\end{tcolorbox}  
\begin{tcolorbox}[use height from group]  
First line\\second line\end{tcolorbox}  
\begin{tcolorbox}The height of this box rules.\end{tcolorbox}  
\end{tcbraster}
```

Every line is inside an equal height group:

Box 1

First line
second line
The height of this box rules.

Box 2

Test

Box 3

First line
second line

Box 4

The height of this box rules.

N 2015-11-27

\tcbheightfromgroup{<macro>}{<id>}

Saves the height from an equal height group with the given <id> to a <macro>. If this height is not available during the current compilation, <macro> is set to Opt.

4.11 Box Content Additions

The following options introduce some arbitrary `<code>` to the content of a `tcolorbox`. These additions can be given at the beginning or at the ending of the title, the upper part, or the lower part.

`/tcb/before title=<code>` (no default, initially unset)

The given `<code>` is placed *after* the color and font settings and *before* the content of the title.

```
\tcbset{before title={\textcolor{yellow}{\large Important:}{}~},  
       colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=My title]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

Important: My title

This is a `tcolorbox`.

`/tcb/after title=<code>` (no default, initially unset)

The given `<code>` is placed *after* the content of the title.

```
\tcbset{after title={\hfill\colorbox{Navy}{approved}},  
       colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=My title]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

My title

approved

This is a `tcolorbox`.

/tcb/before upper=⟨code⟩ (no default, initially unset)

The given ⟨code⟩ is placed *after* the color and font settings and *before* the content of the upper part.

```
\tcbset{before upper={\textit{The story:}}\par,
        colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

The story:
This is a **tcolorbox**.

U 2015-11-27

/tcb/after upper=⟨code⟩ (no default, initially unset)

The given ⟨code⟩ is placed *after* the content of the upper part.

```
\tcbset{after upper={\par\hfill\textit{Read more next week}},
        colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

Read more next week

N 2015-11-27

/tcb/after upper*=⟨code⟩ (no default, initially unset)

An \unskip and the given ⟨code⟩ is placed *after* the content of the upper part.

```
\begin{tcolorbox}[before upper=\flqq,after upper*=\frqq,
        colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

«This is a **tcolorbox**.»



Prior to version 3.80, `/tcb/after upper` had the functionality of `/tcb/after upper*`.

/tcb/before lower=<code> (no default, initially unset)

The given `<code>` is placed *after* the color and font settings and *before* the content of the lower part.

```
\tcbset{before lower=\textit{Behold:~},colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

Behold: This is the lower part.

U 2015-11-27

/tcb/after lower=<code> (no default, initially unset)

The given `<code>` is placed *after* the content of the lower part.

```
\begin{tcolorbox}[before lower=$,after lower=$,
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
\sin^2(x)+\cos^2(x)=1.
\end{tcolorbox}
```

This is a **tcolorbox**.

$\sin^2(x) + \cos^2(x) = 1$.

N 2015-11-27

/tcb/after lower*=<code> (no default, initially unset)

An `\unskip` and the given `<code>` is placed *after* the content of the lower part.

```
\begin{tcolorbox}[after lower*=\textit{This is the end.},
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part. *This is the end.*



Prior to version 3.80, `/tcb/after lower` had the functionality of `/tcb/after lower*`.

! If `/tcb/text fill` is used, one cannot have a lower part and the box is unbreakable.

N 2015-07-15

`/tcb/text fill`

(style, no value)

This style sets `/tcb/before upper`^{→ P. 63} and `/tcb/after upper`^{→ P. 63} to embedd the upper part with a minipage. If a fixed height was applied e.g. by `/tcb/height`^{→ P. 52} or `/tcb/height fill`^{→ P. 55}, this minipage gets a matching height. This allows to use vertical glue macros like `\vfill` to act like expected. If the box has no fixed height, setting `/tcb/text fill` has no other effect as making the box unbreakable.

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  height=8cm,text fill,
  title=My filled box]
This is a \textbf{tcolorbox}.
\par\vfill
\begin{center}
  My middle text.
\end{center}
\par\vfill
This is the end of my box.
\end{tcolorbox}
```

My filled box

This is a **tcolorbox**.

My middle text.

This is the end of my box.

! If `/tcb/tabularx` or `/tcb/tabularx*` are used, one cannot have a lower part.

`/tcb/tabularx=<preamble>` (style)

This style sets `/tcb/before upper`^{→ P. 63} and `/tcb/after upper`^{→ P. 63} and several geometry keys to support a `tabularx` with the given `<preamble>`. The packages `tabularx` [4], `array`, and `colortbl` have to be loaded separately.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
coltitle=black,center title}

\begin{tcolorbox}[tabularx={X||Y|Y|Y||Y},title=My table]
Group & One & Two & Three & Four & Sum\\ \hline
Red & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\ \hline
Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\ \hline
Blue & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\ \hline
Sum & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

`/tcb/tabularx*=<code>{<preamble>}` (style)

This is a variant of `/tcb/tabularx` which adds some `<code>` before the table starts.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
coltitle=black,center title}

\begin{tcolorbox}[tabularx*={\arrayrulewidth0.5mm}{X|X|X},title=My table]
One & Two & Three \\ \hline
1000.00 & 2000.00 & 3000.00\\ \hline
2000.00 & 3000.00 & 4000.00
\end{tcolorbox}
```

My table

One	Two	Three
1000.00	2000.00	3000.00
2000.00	3000.00	4000.00

`/tcb/tikz upper=⟨options⟩` (style)

This style adds a centered `tikzpicture` environment to the start and end of the upper part. The `⟨options⟩` may be given as TikZ picture options.

```
% \usepackage{tikz}

\begin{tcolorbox}[tikz upper,fonttitle=\bfseries,colback=white,colframe=black,
    title=\tikzname\ drawing]
\path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tcolorbox}
```

TikZ drawing



`/tcb/tikz lower=⟨options⟩` (style)

This style adds a centered `tikzpicture` environment to the start and end of the lower part. The `⟨options⟩` may be given as TikZ picture options.

```
% \usepackage{tikz}
% \tcbselibrary{skins, listings}
\tcbsset{tikz lower,listing side text,fonttitle=\bfseries,
    bicolor,colback=LightBlue!50!white,colbacklower=white,colframe=black,
    righthand width=3cm}

\begin{tcblisting}{title=\tikzname\ drawing}
\path[fill=yellow,draw=yellow!75!red]
(0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red]
(215:5mm) arc (215:325:5mm);
\end{tcblisting}
```

TikZ drawing

```
\path[fill=yellow,draw=yellow!75!red]
(0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red]
(215:5mm) arc (215:325:5mm);
```



/tcb/tikznode upper=⟨options⟩ (style)

This style places the upper part content into a centered TikZ node. The ⟨options⟩ may be given as TikZ node options. This style is especially useful for boxes with multiline texts which are fitted to the text width.

```
% \usepackage{tikz}
\newtcbx{\headline}[1][][enhanced,before=\begin{center},after=\end{center},
  ignore nobreak,fontupper=\Large\bfseries,
  colframe=red!50!black,colback=red!10!white,
  drop fuzzy shadow=yellow,tikznode upper,#1}

\headline{Important\\Headline}
```

Important
Headline

/tcb/tikznode lower=⟨options⟩ (style)

This style places the lower part content into a centered TikZ node. The ⟨options⟩ may be given as TikZ node options.

```
% \usepackage{tikz}
\begin{tcolorbox}[bicolor,colback=LightBlue!50!white,colbacklower=white,
  colframe=black,tikznode lower={inner sep=2pt,draw=red,fill=yellow}]
Upper part.
\tcblower
Lower part.
\end{tcolorbox}
```

Upper part.

Lower part.

/tcb/tikznode=⟨options⟩ (style)

Shortcut for setting /tcb/tikznode upper and /tcb/tikznode lower the same time.

/tcb/varwidth upper=⟨length⟩ (style, default /tcb/width^{→ P. 34})

This style places the upper part content into a varwidth environment. This style needs the varwidth package [1] to be loaded manually. The resulting box has a maximal width of ⟨length⟩. This option is only senseful for a \tcbbox^{→ P. 14}.

```
% \usepackage{varwidth}
\newtcbx{\varbox}[1][colframe=red!50!black,
  colback=red!10!white,varwidth upper}

\varbox{Short text.}
\varbox{This box contains is a longer text
  which is broken.}
```

Short text.

This box contains is a longer
text which is broken.

4.12 Overlays

With an overlay, arbitrary $\langle\text{graphical code}\rangle$ can be added to a `tcolorbox`. This code is executed *after* the frame and interior are drawn and *before* the text content is drawn. Therefore, you can decorate the `tcolorbox` with your own extensions. Common special cases are *watermarks* which are implemented using overlays. See Subsection 10.3 from page 157 if you want to add *watermarks*.


! If you use the core package only, the $\langle\text{graphical code}\rangle$ has to be `pgf` code and there is not much assistance for positioning. Therefore, the usage of the `/tcb/enhanced`^{→ P. 196} mode from the library skins is recommended which allows `tikz` code and gives access to `/tcb/geometry nodes`^{→ P. 129} for positioning.

`/tcb/overlay=<graphical code>` (no default, initially unset)

Adds $\langle\text{graphical code}\rangle$ to the box drawing process. This $\langle\text{graphical code}\rangle$ is drawn *after* the frame and interior and *before* the text content.

```
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
enlarge top by=5.5mm,
overlay={\foreach \x in {2cm,3.5cm} {
\begin{scope}[shift={[xshift=\x]frame.north west}]}
\path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
\path[fill=black] (-0.2,0) arc (0:180:1mm);
\end{scope}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins}      % preamble
\tcbset{ribbonbox/.style={enhanced,colback=red!5!white,colframe=red!75!black,
fonttitle=\bfseries,
overlay={\path[fill=blue!75!white,draw=blue,double=white!85!blue,
preaction={opacity=0.6,fill=blue!75!white},
line width=0.1mm,double distance=0.2mm,
pattern=fivepointed stars,pattern color=white!75!blue]
([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
-- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[ribbonbox,title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/no overlay` (style, no default, initially set)

Removes the overlay if set before.

`/tcb/overlay broken=<graphical code>` (no default, initially unset)

If the box is set to be `/tcb/breakable`^{P.353} and is broken actually, then the `<graphical code>` is added to the box drawing process. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay unbroken=<graphical code>` (no default, initially unset)

If the box is set to be `/tcb/breakable`^{P.353} but is not broken actually or if the box is set to be `/tcb/unbreakable`^{P.354}, then the `<graphical code>` is added to the box drawing process. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay first=<graphical code>` (no default, initially unset)

If the box is set to be `/tcb/breakable`^{P.353} and is broken actually, then the `<graphical code>` is added to the box drawing process for the `first` part of the break sequence. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay middle=<graphical code>` (no default, initially unset)

If the box is set to be `/tcb/breakable`^{P.353} and is broken actually, then the `<graphical code>` is added to the box drawing process for the `middle` parts (if any) of the break sequence. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay last=<graphical code>` (no default, initially unset)

If the box is set to be `/tcb/breakable`^{P.353} and is broken actually, then the `<graphical code>` is added to the box drawing process for the `last` part of the break sequence. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay unbroken and first=<graphical code>` (no default, initially unset)

This is an optimized abbreviation for setting `/tcb/overlay unbroken` and `/tcb/overlay first` together. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay middle and last=<graphical code>` (no default, initially unset)

This is an optimized abbreviation for setting `/tcb/overlay middle` and `/tcb/overlay last` together. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay unbroken and last=<graphical code>` (no default, initially unset)

This is an optimized abbreviation for setting `/tcb/overlay unbroken` and `/tcb/overlay last` together. `/tcb/overlay`^{P.69} overwrites this key.

`/tcb/overlay first and middle=<graphical code>` (no default, initially unset)

This is an optimized abbreviation for setting `/tcb/overlay first` and `/tcb/overlay middle` together. `/tcb/overlay`^{P.69} overwrites this key.

This example demonstrates the application of break sequence specific overlay options. Here, we define an environment `myexample` based on `tcolorbox` where the visible drawing is done totally by overlay keys.

Here, the first application of `myexample` produces an unbroken `tcolorbox`. The frame is drawn by the code given with `/tcb/overlay unbroken`.

The second application of `myexample` is broken into several parts which are drawn by the codes given with `/tcb/overlay first`, `/tcb/overlay middle`, and `/tcb/overlay last`.

```
% Preamble:  
%\usepackage{tikz, lipsum}  
%\tcbuselibrary{skins,breakable}  
%\newcounter{example}  
\colorlet{colexam}{red!75!black}  
\newtcolorbox[use counter=example]{myexample}{%
```

```

empty,title={Example \thetcbcounter},attach boxed title to top left,
boxed title style={empty,size=minimal,toprule=2pt,top=4pt,
  overlay={\draw [colexam, line width=2pt]
    ([yshift=-1pt]frame.north west)--([yshift=-1pt]frame.north east);}},
  coltitle=colexam,fonttitle=\Large\bfseries,
  before=\par\medskip\noindent,parbox=false,boxsep=0pt,left=0pt,right=3mm,top=4pt,
  breakable,pad at break*=0mm,vfill before first,
  overlay unbroken={\draw [colexam, line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west); },
  overlay first={\draw [colexam, line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east); },
  overlay middle={\draw [colexam, line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east); },
  overlay last={\draw [colexam, line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west);},%
}
}

\begin{myexample}
\lipsum[1]
\end{myexample}

\begin{myexample}
\lipsum[2-11]
\end{myexample}

\lipsum[12] % following text

```

Example 1

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Example 2

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent

euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdier, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdier sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in,

sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

Floating box from `floatplacement`

This floating box is placed at the top of a page.

4.13 Floating Objects

`/tcb/floatplacement=<values>` (no default, initially `htb`)

Sets `<values>` as default values for the usage of `/tcb/float` and `/tcb/float*`. Feasible are the usual parameters for floating objects.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,  
watermark color=red!15!white}  
  
\begin{tcolorbox}[floatplacement=t,float,  
title=Floating box from |floatplacement|,  
watermark text={I am floating}]  
This floating box is placed at the top of a page.  
\end{tcolorbox}
```

`/tcb/float=<values>` (default from `floatplacement`)

Turns the box to a floating object where `<values>` are the usual parameters for such floating objects. If they are not used, the placement uses the default values given by `floatplacement`.

```
\begin{tcolorbox}[float, title=Floating box from |float|,  
enhanced,watermark text={I'm also floating}]  
This box floats to a feasible place automatically. You do not have to  
use a numbering for this floating object.  
\end{tcolorbox}
```

Floating box from `float`

This box floats to a feasible place automatically. You do not have to use a numbering for this floating object.

`/tcb/float*=<values>` (default from `floatplacement`)

Identical to `/tcb/float`, but for wide boxes spanning the whole page width of two column documents or in conjunction with the packages `multicol` or `paracol`. Note that you have to set `width=\textwidth` additionally, if the box should span the whole page width in these cases!

```
\begin{tcolorbox}[float*=b, title=Floating box from |float*|,width=\textwidth,  
enhanced,watermark text={I'm also floating}]  
In this single column document, you will see no difference to |float|.   
\end{tcolorbox}
```

`/tcb/nofloat` (style, initially set)

Turns the floating behavior off.

Floating box from `float*`

In this single column document, you will see no difference to `float`.


N 2014-09-19

/tcb/every float=<code>

(no default, initially empty)

For floating objects, the /tcb/before^{→ P. 76} and /tcb/after^{→ P. 76} settings are ignored. Instead, the given <code> is inserted before a floating box. If the box is /tcb/breakable^{→ P. 353}, the given <code> is inserted before every part of the break sequence. The most common use case is every float=\centering.

```
\tcbbox[float=htb,title={Floating box},every float=\centering,  
colback=blue!50!black,colframe=blue!50!white,colbacktitle=blue!10!white,  
coltitle=black,center title]  
{\includegraphics[height=6cm]{lichtspiel.jpg}}
```



4.14 Embedding into the Surroundings

Typically, but not necessarily, a `tcolorbox` is put inside a separate paragraph and has some vertical space before and after it. This behavior is controlled by the keys `before` and `after`.

`/tcb/before=<code>` (no default, initially see `/tcb/autoparskip`)

Sets the `<code>` which is executed before the colored box. It is not used for floating boxes. Also, it is not used, if the box follows a heading immediately and `/tcb/ignore nobreak`^{P. 79} is set to `false`.

`/tcb/after=<code>` (no default, initially see `/tcb/autoparskip`)

Sets the `<code>` which is executed after the colored box. It is not used for floating boxes.

`/tcb/parskip` (style, no value)

Sets the keys `before` and `after` to values which are recommended, if the package `parskip` is used and there is no better idea for `before` and `after`. This is similar to:

```
\tcbset{parskip/.style={before={\par\pagebreak[0]\parindent=0pt},  
after={\par}}}
```

`/tcb/noparskip` (style, no value)

Sets the keys `before` and `after` to values which are recommended, if the package `parskip` is *not* used and there is no better idea for `before` and `after`. This is similar to:

```
\tcbset{noparskip/.style={before={\par\pagebreak[0]\smallskip\parindent=0pt},  
after={\par\smallskip}}}
```

`/tcb/autoparskip` (style, no value, initially set)

Tries to detect the usage of the package `parskip` and sets the keys `before` and `after` accordingly. Actually, the following is done:

- If the length of `\parskip` is greater than `0pt` at the beginning of the document, `/tcb/parskip` is executed. Here, the usage of package `parskip` is *assumed*.
- Otherwise, if the length of `\parskip` is not greater than `0pt` at the beginning of the document, `/tcb/noparskip` is executed. Here, the absence of package `parskip` is *assumed*.

`autoparskip` is the default for the package `tcolorbox`, if `before` or `after` are not changed otherwise.

`/tcb/nobeforeafter` (style, no value)

Abbreviation for clearing the keys `before` and `after`. The colored box is not put into a paragraph and there is no space before or after the box.

```
\tcbset{myone/.style={colback=LightGreen,colframe=DarkGreen,  
equal height group=nobefaf,width=\linewidth/4,nobeforeafter}}  
\begin{tcolorbox}[myone,title=Box 1]Box 1\end{tcolorbox} %  
\begin{tcolorbox}[myone,title=Box 2]Box 2\end{tcolorbox} %  
\begin{tcolorbox}[myone,title=Box 3]Box 3\end{tcolorbox} %  
\begin{tcolorbox}[myone,title=Box 4]Box 4\end{tcolorbox}
```

Box 1	Box 2	Box 3	Box 4
Box 1	Box 2	Box 3	Box 4

`/tcb/forces nobeforeafter` (style, no value)

Forces the setting of `/tcb/nobeforeafter` even if `/tcb/before` and `/tcb/after` are set to other values later. Do not use this option globally unless you *really* know what you do. Note that embedded boxes do not inherit this forced clearance.

`/tcb/baseline=<length>`

(no default, initially `0pt`)

Used to set the `\pgfsetbaseline` value of the resulting `tcolorbox`.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[baseline=3mm]
One line.
\end{tcolorbox}
\begin{tcolorbox}[baseline=3mm]
First line.\Second line.
\end{tcolorbox}
```

Some text

One line.

First line.
Second line.

N 2014-10-10

`/tcb/box align=<alignment>`

(style, no default, initially `bottom`)

Used to set the `/tcb/baseline` value of the resulting `tcolorbox`. Feasible values for `<alignment>` are:

- `bottom`: alignment with the box bottom,
- `top`: alignment with the box top,
- `center`: alignment with the box center,
- `base`: alignment with the box content base. This option is not applicable for a `tcolorbox`^{P.12} but for a `\tcbox`^{P.14} only. It is an alias for `/tcb/tcbox raise base`^{P.92}.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=bottom]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=bottom]
First line.\Second line.
\end{tcolorbox}
```

Some text

One line.

First line.
Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=top]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=top]
First line.\Second line.
\end{tcolorbox}
```

Some text

One line.

First line.
Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=center]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=center]
First line.\Second line.
\end{tcolorbox}
```

Some text

One line.

First line.
Second line.

```
\tcbset{colframe=red!50!white,nobeforeafter}
Some text\dotfill
\tcbox[nobeforeafter,box align=base]{One line}
\tcbox[nobeforeafter,box align=base,size=fbox]{Another line}
```

Some text

One line

Another line

N 2014-10-10
U 2015-03-16

/tcb/before skip=<glue> (style, no default)

Inserts some vertical space of the given <glue> before the colored box. This style sets /tcb/before^{→ P. 76}.

```
Some text.
\begin{tcolorbox}[before skip=1cm,
    colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Some text.

This is a tcolorbox.

N 2014-10-10
U 2015-03-16

/tcb/after skip=<glue> (style, no default)

Inserts some vertical space of the given <glue> after the colored box. This style sets /tcb/after^{→ P. 76}.

```
\begin{tcolorbox}[after skip=1cm,
    colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

Some text.

Some text.

N 2014-10-10

/tcb/beforeafter skip=<glue> (style, no default)

Inserts some vertical space of the given <glue> before and after the colored box. This style sets /tcb/before^{→ P. 76} and /tcb/after^{→ P. 76}.

```
\tcbset{beforeafter skip=0pt,
    colframe=red!50!white}
\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}
Second box.
\end{tcolorbox}
```

This is a tcolorbox.

Second box.

N 2014-11-07 **/tcb/left skip=***<length>* (style, no default, initially 0mm)

Inserts some horizontal space of the given *<length>* before the colored box. This style sets */tcb/grow to left by* ^{→ P. 83} with the negated *<length>*, i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[left skip=1cm,
    colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-11-07 **/tcb/right skip=***<length>* (style, no default, initially 0mm)

Inserts some horizontal space of the given *<length>* after the colored box. This style sets */tcb/grow to right by* ^{→ P. 83} with the negated *<length>*, i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[right skip=1cm,
    colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-10 **/tcb/leftright skip=***<length>* (style, no default)

Inserts some horizontal space of the given *<length>* before and after the colored box. This style changes the bounding box and the box width.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[leftright skip=1cm,
    colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-12-11 **/tcb/ignore nobreak=true|false** (default **true**, initially **false**)

After a heading, L^AT_EX tries to avoid a break by setting a *nobreak* boolean value. Starting from version 3.33, the */tcb/before* ^{→ P. 76} respectively */tcb/before skip* ^{→ P. 78} settings are not used after a heading if */tcb/ignore nobreak* is set to **false**. For an unbreakable box, */tcb/before nobreak* is used instead. Further, a */tcb/breakable* ^{→ P. 353} box will also try to avoid a break between a heading and a directly following first part of a break sequence. Set */tcb/ignore nobreak* to **true**, if *nobreak* should be ignored as prior to version 3.33. Also, such a setting may be used locally to enforce the */tcb/before* ^{→ P. 76} setting.

N 2014-12-16 **/tcb/before nobreak=***<code>* (no default, initially **\noindent**)

Sets the *<code>* which is executed before the colored box if it is unbreakable, if */tcb/ignore nobreak* is not set, and if the box follows a heading.

4.15 Bounding Box

Normally, every `tcolorbox` has a bounding box which fits exactly to the dimensions of the outer frame. Therefore, L^AT_EX reserves exactly the space needed for the box. This behavior can be changed by enlarging (or shrinking) the bounding box. If the bounding box is enlarged, the `tcolorbox` will get some clearance around it. If the bounding box is shrunk, i. e. enlarged with negative values, the `tcolorbox` will overlap to other parts of the page. For example, the `tcolorbox` could be stretched into the page margin.



The following examples use `/tcb/show bounding box`^{→ P. 171} to display the actual bounding box. For this, the library `\usepackage{skins}` has to be included and `/tcb/enhanced`^{→ P. 196} has to be set.

`/tcb/enlarge top initially by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by `<length>`. If the box is *breakable*, only the first box of the break sequence gets enlarged. `/tcb/enlarge top by`^{→ P. 81} overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge top initially by=-5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge top initially by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a `tcolorbox`.

This is a `tcolorbox`.

`/tcb/enlarge bottom finally by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the bottom of the box by `<length>`. If the box is *breakable*, only the last box of the break sequence gets enlarged. `/tcb/enlarge bottom by`^{→ P. 81} overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge bottom finally by=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge bottom finally by=-5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a `tcolorbox`.

This is a `tcolorbox`.

`/tcb/enlarge top at break by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by `<length>`, if the box is `/tcb/breakable`^{→ P.353}. In this case, it is applied to *middle* and *last* parts in a break sequence. `/tcb/enlarge top by` overwrites this key.

`/tcb/enlarge bottom at break by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the bottom of the box by `<length>`, if the box is `/tcb/breakable`^{→ P.353}. In this case, it is applied to *first* and *middle* parts in a break sequence. `/tcb/enlarge bottom by` overwrites this key.

`/tcb/enlarge top by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by `<length>`. `/tcb/enlarge top initially by`^{→ P.80} and `/tcb/enlarge top at break by` are set to `<length>`.

`/tcb/enlarge bottom by=<length>` (no default, initially 0mm)


Enlarges the bounding box distance to the bottom of the box by `<length>`. `/tcb/enlarge bottom finally by`^{→ P.80} and `/tcb/enlarge bottom at break by` are set to `<length>`.

`/tcb/enlarge left by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the left side of the box by `<length>`.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge left by=2cm,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge left by=-2cm,width=\ linewidth+2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




This is a **tcolorbox**.

`/tcb/enlarge right by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the right side of the box by `<length>`.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge right by=-2cm,width=\ linewidth+2cm,
    enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge right by=2cm,width=\ linewidth-2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



This is a **tcolorbox**.

/tcb/enlarge by=<length> (no default, initially 0mm)

Enlarges the bounding box distance to all sides of the box by <length>.

```
\tcbset{colframe=blue!75!black,colback=white,width=5cm,nobeforeafter}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

N 2015-11-20

/tcb/flush left (style, no value)

Enlarges the bounding box to the right side to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[flush left,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

N 2015-11-20

/tcb/flush right (style, no value)

Enlarges the bounding box to the left side to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[flush right,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

N 2015-11-20

/tcb/center (style, no value)

Enlarges the bounding box equally to both sides to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[center,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/grow to left by=<length>` (no default, initially 0mm)

Enlarges the current box width by $\langle length \rangle$ and enlarges (shrinks) the bounding box distance to the left side of the box by $-\langle length \rangle$. Also see `/tcb/left skip`^{P. 79}.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[width=5cm,grow to left by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox} with a width of 7cm.
\end{tcolorbox}
```

This is a **tcolorbox** with a width of 7cm.

`/tcb/grow to right by=<length>` (no default, initially 0mm)

Enlarges the current box width by $\langle length \rangle$ and enlarges (shrinks) the bounding box distance to the right side of the box by $-\langle length \rangle$. Also see `/tcb/right skip`^{P. 79}.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[grow to right by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\bigskip

\begin{tcolorbox}[grow to right by=2cm,grow to left by=1cm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

Floating box from `toggle enlargement`

This page is an even page. Therefore, the left and right enlargements are toggled. This box stretches to the right margin on odd pages and to the left margin on even pages. The current document is one-sided – this feature makes sense for two-sided documents only.

U 2015-11-13

`/tcb/toggle enlargement=<toggle preset>` (default `evenpage`, initially `none`)

According to the `<toggle preset>`, the left and the right enlargements of the bounding box are switched or not. Feasible values are:

- `none`: no switching.
- `forced`: the values of the left and right enlargement are switched.
- `evenpage`: if the page is an even page, the values of the left and right enlargement are switched. This value also sets `/tcb/check odd page`^{P. 96} to true.



See `/tcb/toggle left and right`^{P. 45} to toggle geometry settings.

```
\tcbset{colframe=blue!75!black,colback=white,  
grow to left by=20mm,grow to right by=-5mm}  
  
\begin{tcolorbox}[toggle enlargement=none,enhanced,show bounding box]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}  
\begin{tcolorbox}[toggle enlargement=forced]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}  
\begin{tcolorbox}[toggle enlargement=evenpage]  
This page is an \tcbifoddpage{odd}{even} page.  
Therefore, the left and right enlargements  
\tcbifoddpage{are not}{are} toggled.  
\end{tcolorbox}
```

This is a `tcolorbox`.

This is a `tcolorbox`.

This page is an even page. Therefore, the left and right enlargements are toggled.

```
\begin{tcolorbox}[colframe=red!60!black,colback=red!15!white,  
fonttitle=\bfseries,title=Floating box from \texttt{toggle enlargement},  
width=\textwidth,grow to right by=2cm,toggle enlargement,float=t]  
This page is an \tcbifoddpage{odd}{even} page.  
Therefore, the left and right enlargements \tcbifoddpage{are not}{are} toggled.  
This box stretches to the right margin on odd pages and to the left  
margin on even pages. The current document is one-sided -- this feature makes  
sense for two-sided documents only.  
\end{tcolorbox}
```

! The following keys should not be used with breakable boxes or boxes with a lower part.

/tcb/shrink tight (style, no value, initially unset)

The total colored box is shrunk to the dimensions of the upper part. There should be no lower part and no title. This style sets the **/tcb/boxsep** ^{P.38} to 0pt and other geometry keys to fitting values. This option is likely to be used with the following extrusion keys.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,boxrule=0.4pt,
nobeforeafter,tcbox raise base,shrink tight}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

 Lorem **\tcbbox**{ipsum} dolor sit amet, consectetur adipiscing elit.

This is a **tcolorbox**.

 Lorem ipsum dolor sit amet, consectetur adipiscing elit.

U 2014-09-19

/tcb/extrude left by=<length> (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given **<length>** to the left side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
frame style={opacity=0.25},interior style={opacity=0.5},
nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbbox[extrude left by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat
ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget,
consectetur id, vulputate a, magna.
```

U 2014-09-19

/tcb/extrude right by=<length> (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given **<length>** to the right side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
frame style={opacity=0.25},interior style={opacity=0.5},
nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbbox[extrude right by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat
ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget,
consectetur id, vulputate a, magna.
```

/tcb/extrude top by=<length> (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to the top side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,  
frame style={opacity=0.25},interior style={opacity=0.5},  
nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}
```

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
 \tcbox[extrude top by=1cm]{Curabitur} dictum gravida mauris.
 Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat
ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget,
consectetur id, vulputate a, magna.

/tcb/extrude bottom by=<length> (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to the bottom side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,  
frame style={opacity=0.25},interior style={opacity=0.5},  
nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}
```

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
 \tcbox[extrude bottom by=1cm]{Curabitur} dictum gravida mauris.
 Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat
ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget,
consectetur id, vulputate a, magna.

/tcb/extrude by=<length> (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to all sides. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,  
frame style={opacity=0.25},interior style={opacity=0.5},  
nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}
```

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis. \tcbox[Curabitur] dictum
gravida mauris. \tcbox[colframe=Green,interior style={opacity=0.0}]{Nam}
arcu libero, nonummy eget, consectetur id, \tcbox[vulputate] a, magna. Donec
vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus
et malesuada fames ac turpis egestas. \tcbox[Mauris ut leo.]

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat
ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget,
consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi
tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo.

4.16 Layered Boxes and Every Box Settings

A `tcolorbox` may contain another `tcolorbox` and so on. The package takes track of the nesting level using a counter `tcblayer`. Counter values may be used for doing some fancy things, but you should never change the counter value yourself.

The package takes special care for the first four layers or nesting levels, called managed layers. Here, footnote texts are administrated to find their intended place and specific layer dependent options may be set by changing `/tcb/every box on layer n→ P.88`. If needed, the number of managed layers can be increased by setting `\tcbsetmanagedlayer→ P.88` to a higher value than 4.

The following styles have a considerable influence on how layered boxes are processed. Note especially that nested boxes are getting a `/tcb/reset→ P.99` by default. You can change this, but be prepared for surprises if you do.

If the defaults are *not changed*, a `tcolorbox` gets its options in the following order. Following options overwrite preceding options.

1. On package load, all options are set to default values.
2. Every `\tcbset→ P.13` command adds or changes options for the following boxes inside the current T_EX group.
3. While entering a `tcolorbox`, a `/tcb/every box on layer n→ P.88` or `/tcb/every box on higher layers→ P.88` option list is applied. With default settings this means:
 - For layer 1 (lowest layer), the `/tcb/every box` option list is applied. Not overwritten options given by a preceding `\tcbset→ P.13` survive.
 - For layer 2 and above (nested boxes), a `/tcb/reset→ P.99` followed by `/tcb/every box` option list is applied. Every resettable options given by a preceding `\tcbset→ P.13` and by the surrounding box(es) are reset.
4. The `<options>` given to the `tcolorbox` are applied. Or, if the box was generated by `\newtcolorbox→ P.15` or friends, the `<options>` given there are applied.
5. If the box was generated by `\newtcolorbox→ P.15` or friends, some automated options are applied.

`/tcb/every box` (style)

By default, this style is empty.

```
% default setting:  
\tcbset{every box/.style={}}
```

It may be changed by redefining this style.

```
% setting all boxes to be enhanced:  
\tcbset{every box/.style={enhanced}}
```

The alternative for setting something for every box (on every layer) is `\tcbsetforeverylayer→ P.13`:

```
% setting all boxes to be enhanced:  
\tcbsetforeverylayer{enhanced}
```



/tcb/every box on layer n (style)

Here, n has to be replaced by a number ranging from 1 to the highest managed layer number (4 by default).

```
% default settings:  
\tcbset{  
    every box on layer 1/.style={every box},  
    every box on layer 2/.style={reset,every box},  
    every box on layer 3/.style={reset,every box},  
    every box on layer 4/.style={reset,every box},  
}
```

/tcb/every box on higher layers (style)

Higher layers are layers above the highest managed layer number (4 by default).

```
\tcbset{every box on higher layers/.style={reset,every box}}
```

\tcbsetmanagedlayer{<number>}

Replaces the highest managed layer number by <number> where 4 is the default. This macro can only be used inside the preamble. Using a <number> lower than 4 typically makes no sense, but is not forbidden.

```
% \usepackage{lipsum}  
% \tcbuselibrary{skins,breakable}  
\tcbset{colframe=red!75!black,fonttitle=\bfseries,  
colback=red!5!white,  
every box/.style={enhanced,watermark text=\thetcblayer,  
before=\par\smallskip,after=\par\smallskip},  
every box on layer 2/.style={reset,every box,colback=yellow!10!white,  
drop fuzzy shadow}}  
\begin{tcolorbox}[enhanced,jigsaw,breakable,title=Layer 1 Box]  
Here comes a footnote\footnote{Footnote from layer 1 box}.  
\lipsum[2]  
\begin{tcolorbox}[title=Layer 2 Box]  
abc\footnote{The footnote of abc}  
\end{tcolorbox}  
\begin{tcolorbox}[title=Another Box,ams equation]  
\tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} = \infty.  
\end{tcolorbox}  
Some text\footnote{Footnote from some text}.  
\begin{tcolorbox}[title=Yet Another Box]  
\tcbboxfit[height=2cm]{\lipsum[1]}  
My text.  
\begin{tcolorbox}  
Another lipsum text\footnote{A lipsum text}. \lipsum[3]  
\begin{tcolorbox}[title=Layer 4,colframe=blue,colback=white]  
Layer 4\footnote{Layer 4 footnote}  
\end{tcolorbox}  
The End\footnote{Last footnote}.  
\end{tcolorbox}  
\end{tcolorbox}  
\end{tcolorbox}
```

Layer 1 Box

Here comes a footnote^a. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras

nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Layer 2 Box

abc^a

^aThe footnote of abc

2

Another Box

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

(1)

Some text^b.

Yet Another Box

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My text.

Another ipsum text^a. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Layer 4

Layer 4^a

^aLayer 4 footnote

4

The End^b.

^aA ipsum text

^bLast footnote

^aFootnote from layer 1 box

^bFootnote from some text

4.17 Capture Mode

`/tcb/capture=<mode>` (no default, initially `minipage`)

The capture `<mode>` defines how the box content is processed.

Feasible values for `<mode>` are:

- `minipage`:

This is the default `<mode>` for `tcolorbox`^{P. 12}. The content may have an upper and a lower part. Optionally, the box can be `/tcb/breakable`^{P. 353}. The box content is put into a minipage or into something similar to a minipage.

- `hbox`:

This is the default `<mode>` for `\tcbox`^{P. 14}. The content cannot have a lower part and cannot be broken. The colored box is sized according to the dimensions of the content. A shortcut to set this mode is `/tcb/hbox`.

- `fitbox`: (needs the  fitting library)

This is the default `<mode>` for `\tcboxfit`^{P. 383}. The content cannot have a lower part and cannot be broken. The content is sized according to the dimensions of the colored box. A shortcut to set this mode is `/tcb/fit`^{P. 385}.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[capture=minipage]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=hbox]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=fitbox,height=9mm] % needs the 'fitting' library
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox.

`/tcb/hbox`

(style, no default)

Shortcut for `capture=hbox`.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[hbox]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/minipage`

(style, no default)

Shortcut for `capture=minipage`.

4.18 Text Characteristics

U 2015-10-14

/tcb/parbox=true|false (default true, initially true)

The text inside a `tcolorbox` is formatted using a L^AT_EX `minipage` if the box is unbreakable. If breakable, the box tries a mimicry of a `minipage`. In a `minipage` or `parbox`, paragraphs are formatted slightly different as the main text. If the key value is set to `false`, the normal main text behavior is restored. In some situations, this has some unwanted side effects. It is recommended that you use this experimental setting only where you really want to have this feature.

```
% \usepackage{lipsum} % preamble
\tcbset{width=(\linewidth-2mm)/2,nobeforeafter,arc=1mm,
colframe=blue!75!black,colback=white,fonttitle=\bfseries,fontupper=\small,
left=2mm,right=2mm,top=1mm,bottom=1mm,equal height group=parbox}

\begin{tcolorbox}[parbox,adjusted title={parbox=true (normal)}]
\lipsum[1-2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[parbox=false,adjusted title={parbox=false}]
\lipsum[1-2]
\end{tcolorbox}%
```

parbox=true (normal)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

parbox=false

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/hyphenationfix=true|false (default true, initially false)

Long words at the beginning of paragraphs in very narrow boxes will not be hyphenated using pdflatex. This problem is circumvented by applying the `hyphenationfix` option.

```
\tcbset{colframe=blue!75!black,  
fontupper=\normalsize,  
colback=blue!5!white,width=4cm}  
  
\begin{tcolorbox}  
Rechnungsadjunktentochter.\par  
Statthaltereikonzipist.  
\end{tcolorbox}  
  
\begin{tcolorbox}[hyphenationfix]  
Rechnungsadjunktentochter.\par  
Statthaltereikonzipist.  
\end{tcolorbox}
```

Rechnungsadjunktentochter.
Statthaltereikonzipist.

Rechnungsad-
junktentochter.
Statthal-
tereikonzipist.

! `parbox=false` and `hyphenationfix` should not be used together. They are targeting different box types and they do not blend very well.

4.19 Files

/tcb/tempfile=<file name> (no default, initially `\jobname.tcbtemp`)

Sets `<file name>` as name for the temporary file which is used inside `tcbwritetemp`^{P.119} and `\tcbusetemp`^{P.119} implicitly.

4.20 \tcbbox Specials

The following options are applicable for `\tcbbox`^{P.14} and `\tcbboxmath`^{P.330} only.

/tcb/tcbox raise=<length> (no default, initially Opt)

Raises the `\tcbbox`^{P.14} by the given `<length>`.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,  
fonttitle=\bfseries,nobeforeafter,center title}  
  
Test\dotfill  
\tcbbox[tcbox raise base]{Hello World 1}\dotfill  
\tcbbox{Hello World 2}\dotfill  
\tcbbox[tcbox raise=5mm]{Hello World 3}
```

Test

Hello World 1

Hello World 2

Hello World 3

/tcb/tcbox raise base (style, no value, initially unset)

Raises the `\tcbbox`^{P.14} such that the base of its content matches the base of the environmental line; see example above.

/tcb/on line (style, no value, initially unset)

Combines `/tcb/tcbox raise base` with `/tcb/nobeforeafter`^{P.76}. The resulting box behaves analogue to `\fbox`.


`/tcb/tcbox width=<mode>` (no default, initially `auto`)

Controls how `\tcbox`^{→ P. 14} respects a `/tcb/width`^{→ P. 34} setting. Feasible values for `<mode>` are:

- `auto` (initial setting): ignore `/tcb/width`^{→ P. 34} and set box width according to its content.
- `auto limited`: Set box width according to its content, if it is smaller than `/tcb/width`^{→ P. 34}. Otherwise, the content is set like in a `tcolorbox`^{→ P. 12} with line breaks.
- `forced center`: Set box width according to `/tcb/width`^{→ P. 34}. The content is centered and may overlap the box borders.
- `forced left`: Set box width according to `/tcb/width`^{→ P. 34}. The content is left aligned and may overlap the box borders.
- `forced right`: Set box width according to `/tcb/width`^{→ P. 34}. The content is right aligned and may overlap the box borders.
- `minimum center`: Set box width according to `/tcb/width`^{→ P. 34}, if the content fits into. The content is centered and the box width may grow beyond `/tcb/width`^{→ P. 34}.
- `minimum left`: Set box width according to `/tcb/width`^{→ P. 34}, if the content fits into. The content is left aligned and the box width may grow beyond `/tcb/width`^{→ P. 34}.
- `minimum right`: Set box width according to `/tcb/width`^{→ P. 34}, if the content fits into. The content is right aligned and the box width may grow beyond `/tcb/width`^{→ P. 34}.

```
\tcbset{size=small,on line,before upper=\strut,
colframe=blue!75!black,colback=blue!5!white,
fontupper=\normalsize,width=4cm}

\tcbox[tcbbox width=auto]{auto}\qquad
\tcbox[tcbbox width=auto limited]{auto limited}\qquad
\tcbox[tcbbox width=auto limited]{auto limited with long text} \\
\tcbox[tcbbox width=forced center]{forced center}\qquad
\tcbox[tcbbox width=forced center]{forced center with long text} \\
\tcbox[tcbbox width=forced left]{forced left}\qquad
\tcbox[tcbbox width=forced left]{forced left with long text} \\
\tcbox[tcbbox width=forced right]{forced right}\qquad
\tcbox[tcbbox width=forced right]{forced right with long text} \\
\tcbox[tcbbox width=minimum center]{minimum center}\qquad
\tcbox[tcbbox width=minimum center]{minimum center with long text} \\
\tcbox[tcbbox width=minimum left]{minimum left}\qquad
\tcbox[tcbbox width=minimum left]{minimum left with long text} \\
\tcbox[tcbbox width=minimum right]{minimum right}\qquad
\tcbox[tcbbox width=minimum right]{minimum right with long text}
```



4.21 Counters, Labels, and References

/tcb/phantom=⟨code⟩ (no default, initially unset)

The ⟨code⟩ is put in a box at the upper left corner of the `tcolorbox`. If the `tcolorbox` is breakable, the ⟨code⟩ is executed for the first box of the break sequence only. If there already was some phantom code given, the new ⟨code⟩ is appended.

The ⟨code⟩ is intended to be used for counter stepping, labelling, and related operations which do not produce visible text.

- The ⟨code⟩ is executed before the title and box content, i. e. counter values are ensured to be increased before usage.
- Labels are ensured to reference the correct page number.
- The ⟨code⟩ is executed only once even during fitting operations for title and box content.
- In combination with the `hyperref` package, the hyper anchor is set to the upper left corner of the `tcolorbox`, i. e. links inside the pdf document will jump to the box pleasantly.
- Since the ⟨code⟩ is executed inside a `TEX` group, only global operations can survive this group.

Examples for the `phantom` usage are given in Section 15.9 from page 322, e. g. Example 15.1 on page 323.

/tcb/nophantom (no value, initially set)

Removes the phantom code if set before.

/tcb/label=⟨marker⟩ (no default, initially unset)

The ⟨marker⟩ is set as label text for a reference with the `\ref` macro. Typically, this option is used for numbered boxes, see Subsection 5.1 from page 101, e. g. `/tcb/new/auto counter`^{→ P. 101}.

N 2014-11-28 /tcb/phantomlabel=⟨marker⟩ (no default, initially unset)

Equivalent to `/tcb/label` for an *unnumbered* box. A `\phantomsection` from the package `hyperref` is used to set a correct hyperlink target. This is not needed for a numbered box.

/tcb/label type=⟨type⟩ (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. ⟨type⟩ has to be a cross-reference type *known* to `cleveref` like `theorem`, `algorithm`, `result`, etc. References made with `cleveref` will use this type. Note that using `label type` will result in compilation errors, if `cleveref` is not loaded. For an example, see Theorem 16.3.5 on page 347.

/tcb/no label type (no value, initially set)

Removes a `/tcb/label type`, if set before.

/tcb/step=⟨counter⟩ (no default, initially unset)

Shortcut for `phantom={\refstepcounter{#1}}`. The given ⟨counter⟩ is increased and ready for labelling. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 101.

/tcb/step and label=⟨counter⟩{⟨marker⟩} (no default, initially unset)

Shortcut for using `/tcb/step` and `/tcb/label`. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 101.

`/tcb/list entry=<text>` (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 108 is used, this key describes the `<text>` for an entry into the generated list, e.g.

```
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 15.9 from page 322 for a complete example.

N 2014-09-19 `/tcb/list text=<text>` (style, no default)

This is a shortcut for setting `/tcb/list entry` to `\protect\numberline{\thetcbcounter}<text>`. So, the following settings are identical:

```
list text={My beautiful Example},  
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 15.9 from page 322 for a complete example.

`/tcb/add to list={<list>}{<type>}` (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 108 is used, list entries are generated automatically. With this key, you can enforce an entry to the given `<list>` with the given `<type>`. This issues:

```
\addcontentsline{<list>}{<type>}{<entry text>}
```

N 2016-06-22 `/tcb/nameref=<text>` (no default, initially unset)

If the `nameref` package is loaded, the given `<text>` is used for corresponding `\nameref` makros. Typically, the `<text>` will be chosen to be identical or nearly identical to the one for `/tcb/title` → P. 18.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%  
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,  
    title=Examp.\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={mynameLabel},nameref={Title or anything else}]{Title text}  
This is a tcolorbox.
```

```
\end{pabox}
```

```
This box is automatically numbered with \ref{mynameLabel} on page  
\pageref{mynameLabel}.
```

```
The box is titled '\nameref{mynameLabel}'.
```

Examp. 4.1: Title text

This is a tcolorbox.

This box is automatically numbered with 4.1 on page 95.

The box is titled 'Title or anything else'.

4.22 Even and Odd Pages

! Also see `/tcb/toggle left and right`^{→ P. 45} and `/tcb/toggle enlargement`^{→ P. 84} for further even/odd options.

U 2015-11-13

`/tcb/check odd page=true|false` (default `true`, initially `false`)

If set to `true`, a precise even/odd page testing for the current box is applied. This is done by using labels. If a box moves to another page, the document has to be compiled twice for the correct settings. If set to `false`, even/odd page tests may give wrong results for the first box of a page.

`/tcb/toggle left and right`^{→ P. 45}, `/tcb/toggle enlargement`^{→ P. 84}, and `/tcb/if odd page` automatically set `check odd page`, but for `\tcbifoddpage`^{→ P. 97} this option has to be set explicitly.

N 2015-11-13

`/tcb/if odd page={⟨odd options⟩}{⟨even options⟩}` (style, no default)

If the current box is on an odd page, the `⟨odd options⟩` are applied. On an even page, the `⟨even options⟩` are applied. `/tcb/check odd page` is automatically set for precise even/odd page testing.

```
\begin{tcolorbox}[if odd page={colback=yellow!50}{colback=red!50}]
This box is colored in yellow on an odd page
and is colored in red on an even page.
\end{tcolorbox}
```

This box is colored in yellow on an odd page and is colored in red on an even page.

! If a box is `/tcb/breakable`^{→ P. 353}, using `/tcb/if odd page` only acts upon the *first* box. If the setting should be repeated for every partial box of the break sequence, the option should be packed into `/tcb/extras`^{→ P. 359}. In this case, `/tcb/check odd page` has to be set explicitly! Also see `/tcb/if odd page*`^{→ P. 97}.



This option needs the `\tcb[breakable]` library, see Section 17 on page 351.

For breakable boxes, if the current partial box is on an odd page, the `⟨odd options⟩` are applied. On an even page, the `⟨even options⟩` are applied. `/tcb/check odd page`^{→P.96} is automatically set for precise even/odd page testing.

In contrast to `/tcb/if odd page`^{→P.96}, `/tcb/if odd page*` is used on *every* partial box of a break sequences and not only on the *first* box. Another difference is that `/tcb/if odd page*` is applied quite *late* during option processing, while `/tcb/if odd page`^{→P.96} is applied immediately.

`/tcb/if odd page*` is implemented as `/tcb/if odd page`^{→P.96} packed into `/tcb/extras`^{→P.359}.

```
% \tcbuselibrary{breakable}
\begin{tcolorbox}[breakable,if odd page*={colback=yellow!50}{colback=red!50}]
This breakable box is colored in yellow on an odd page
and is colored in red on an even page. For every partial box, the
test is repeated, i.e. this would give a yellow, red, yellow, red, \ldots\
sequence for a long content.
\end{tcolorbox}
```

This breakable box is colored in yellow on an odd page and is colored in red on an even page. For every partial box, the test is repeated, i.e. this would give a yellow, red, yellow, red, ... sequence for a long content.

If the current box is on an odd page, the `⟨odd code⟩` is executed. On an even page, the `⟨even code⟩` is executed. For precise even/odd page testing, the `/tcb/check odd page`^{→P.96} has to be set manually inside the box options.

The macro `\tcbifoddpage` can be used inside underlay, overlay, or watermark code to test if the box is on an odd page. This will work also for boxes in a break sequence.

The macro can also be used inside the box **content text**. For unbreakable boxes, the correct page test is applied. But for `/tcb/breakable`^{→P.353} boxes, `\tcbifoddpage` will always give the result for the page of the *first* box inside the box **content text**. If needed, the methods from the packages `changepage` or `ifoddpage` could be used here.

```
\tcbset{colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,check odd page,
title={Example for a box on an \tcbifoddpage{odd}{even} page},
watermark text={\tcbifoddpage{Odd}{Even} page!}]
\lipsum[1]
\end{tcolorbox}
```

Example for a box on an odd page

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

N 2015-11-13

\thetcolorboxnumber

This is a unique identifier (arabic number) for a tcolorbox. It is locally defined inside boxes and has no meaning outside. It is used for precise even/odd page testing, but may also be valuable for elaborate user code.

```
\begin{tcolorbox}[colback=yellow!5,title=Box \thetcolorboxnumber]
This box is \thetcolorboxnumber.
\tcbox[on line,size=fbox]{This box is \thetcolorboxnumber} and
\tcbox[on line,size=fbox]{this box is \thetcolorboxnumber}.
This box is \thetcolorboxnumber.
\end{tcolorbox}
```

Box 888

This box is 888. This box is 889 and this box is 890. This box is 888.

N 2015-11-13

\thetcolorboxpage

This macro contains the expanded arabic page number of the current tcolorbox. It is locally defined inside boxes and has no meaning outside. It is precise only, if `/tcb/check odd page`^{→ P. 96} was set.

```
\begin{tcolorbox}[colback=yellow!5,check odd page,
title=Box on page-\thetcolorboxpage]
This box is located on page-\thetcolorboxpage.
\end{tcolorbox}
```

Box on page 98

This box is located on page 98.

4.23 Externalization



See Section 22 on page 418 for the `\usepackage[external]{tikz}` library of `tcolorbox`.

If the `externalization` library of the `tikz` package is used and `/tcb/graphical environment→ P. 126` is set to `tikzpicture`, a `tcolorbox` could trigger the externalization process which will arise a compilation error.

To avoid this, there are two possible strategies:

- Ensure, that `\tikzexternalisable` is set before a `tcolorbox` is used. If you typically use the pattern `\tikzexternalenable some picture \tikzexternalisable`, there is nothing to care about.
- If `externalization` is enabled globally, use `/tcb/shield externalize` to shield any `tcolorbox`. The preamble code could look like this:

```
\usetikzlibrary{external}
\tikzexternalize
\tcbset{shield externalize}
```

`/tcb/shield externalize=true|false` (default `true`, initially `false`)

If set to `true`, the drawing part of the `tcolorbox` is not being externalized which is a good thing at the current state of art. Nevertheless, if the `tcolorbox` contains a `tikzpicture`, this picture is still externalized. Pictures drawn with help of `/tcb/tikz upper→ P. 67` or alike are *not* externalized.



If a `tcolorbox` is used inside a node of an encircling `tikzpicture` which is externalized, do *not* use `\tikzexternalisable` in front of the `tcolorbox`. `/tcb/shield externalize` is deactivated automatically inside a `tikzpicture`.

`/tcb/external=<file name>` (no default, initially unset)

Convenience option which calls `\tikzsetnextfilename{<file name>}`. Typically, it may be used inside the option list of a `tcolorbox` to set the externalization `<file name>` for the first `tikzpicture` which is discovered *inside* the box content. The package `tikz` [20] or the library `\usepackage[skins]{tikz}` has to be loaded to use this option. Additionally, `\usetikzlibrary{external}` has to be used.

`/tcb/remake=true|false` (default `true`, initially `false`)

Convenience option which calls `/tikz/external/remake next`. Typically, it may be used inside the option list of a `tcolorbox` to force the remake of the first `tikzpicture` which is discovered *inside* the box content. The package `tikz` [20] or the library `\usepackage[skins]{tikz}` has to be loaded to use this option. Additionally, `\usetikzlibrary{external}` has to be used.

4.24 Miscellaneous

`/tcb/reset` (no value, initially set)

Sets (nearly) all `tcolorbox` settings (including loaded libraries) back to their default values *plus* any settings given by `\tcbsetforeverylayer→ P. 13`. `/tcb/savedelimiter→ P. 26` and `/tcb/capture→ P. 90` keep their values. Also, all raster values (see Section 14 on page 266) are not resetted.

This option is useful for boxes in boxes where the inner box should not inherit the settings of the outer box. Note that for boxes inside boxes the `reset` is done automatically, if the standard settings of the package are used (v2.40 and above), see Section 4.16 from page 87.

/tcb/only=<overlay specification>>{<options>} (style, no default, initially unset)

Sets the given `tcolorbox` `<options>` in dependency of a `beamer` `<overlay specification>`. Note that this needs the `beamer` class. The `<options>` will only be used on the specified `beamer` frames.

```
\documentclass{beamer}
\usepackage[many]{tcolorbox}
\begin{document}

\begin{frame}
\begin{tcolorbox}[title=My title,fonttitle=\bfseries,
enhanced,colframe=red!50!black,colback=red!10,colbacktitle=red,
sidebyside,righthand width=3cm,
lowerbox=invisible,lower separated=false,
drop lifted shadow,
only=<1>{colbacktitle=yellow,coltitle=red!50!black,colframe=red},
only=<3>{colback=yellow!50,watermark text={Attention!}},
only=<3->{lowerbox=visible} ]
This is a test.
\begin{itemize}[<+->]
\item One
\item Two
\item \alert{Three}
\item Four
\end{itemize}
\tcblower
\begin{equation*}
\int\limits_{\{1\}}^x \frac{1}{t} dt = \ln(x).
\end{equation*}
\end{tcolorbox}
\end{frame}

\end{document}
```

/tcb/code=<code> (no default, initially unset)

The given `<code>` is executed immediately. This option is useful to place some arbitrary code into an option list.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
code={Useless at this spot but functional.},
fonttitle=\bfseries}

\begin{tcolorbox}[code={\newcommand{\mycommand}{\textit{working}}}, 
title=My \mycommand title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Useless at this spot but functional.

My *working* title

This is a `tcolorbox`.

5 Initialization Option Keys

The *initialization* options are only applicable for the generation of new environments and commands based on `tcolorbox` and friends. Particularly, they can be used for

- `\newtcolorbox`^{→ P. 15},
- `\newtcbox`^{→ P. 16},
- `\newtcblisting`^{→ P. 291},
- `\newtcbinputlisting`^{→ P. 293},
- `\new tcbtheorem`^{→ P. 328}, and
- `\new tcboxfit`^{→ P. 384}.



Typically, these options may generate counters and alike. It is **strongly** recommended that you use initialization options inside the preamble only. Otherwise, you may get trouble when using L^AT_EX's `\include` features.

5.1 Numbered Boxes

Counters assigned using the initialization options are administrated automatically. Especially, they are increased for each new box. Independent from the real counter name, the counter value can be referenced by `\thetcbcounter`, e.g. inside the title of the box. The real counter name is stored inside `\tcbcounter`.

`/tcb/new/auto counter` (no value, initially unset)

Creates a new counter automatically. With `/tcb/new/number format`^{→ P. 103} and `/tcb/new/number within`^{→ P. 103}, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=Examp.\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={myautocounter}]{Title with number}
This box is automatically numbered with \ref{myautocounter} on page
\pageref{myautocounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{pabox}
```

Examp. 5.1: Title with number

This box is automatically numbered with 5.1 on page 101. Inside the box, the 5.1 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pobox`.

`/tcb/new/use counter from=<tcolorbox>` (no default, initially unset)

Here, a counter from another `<tcolorbox>` is reused. Note that the settings for `/tcb/new/number format`^{P. 103} and `/tcb/new/number within`^{P. 103} are inherited and cannot be changed. The counter value is referenced by `\thetcbcounter`.

```
\newtcolorbox[use counter from=pabox]{mybox}[2][]{%
    colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
    title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounterfrom}]{Title with continued number}
This box is automatically numbered with \ref{myusecounterfrom} on page
\pageref{myusecounterfrom}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

Some Box 5.2: Title with continued number

This box is automatically numbered with 5.2 on page 102. Inside the box, the 5.2 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

`/tcb/new/use counter=<counter>` (no default, initially unset)

Here, an ordinary existing L^AT_EX `<counter>` is used for numbering. With `/tcb/new/number format`^{P. 103} and `/tcb/new/number within`^{P. 103}, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

```
% \newcounter{myexample}% preamble
\newtcolorbox[use counter=myexample,number format=\Alpha]{mybox}[2][]{%
    colback=green!5!white,colframe=green!55!black,fonttitle=\bfseries,
    title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounter}]{Title with \LaTeX\ number}
This box is automatically numbered with \ref{myusecounter} on page
\pageref{myusecounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

Some Box A: Title with L^AT_EX number

This box is automatically numbered with A on page 102. Inside the box, the A can also be referenced by `\thetcbcounter`. The real counter name is `myexample`.

N 2014-09-19 `/tcb/new/use counter*=<counter>` (no default, initially unset)

An existing L^AT_EX `<counter>` is used for numbering. In contrast to `/tcb/new/use counter`, the options `/tcb/new/number format`^{P. 103} and `/tcb/new/number within`^{P. 103} are ignored. Use this for counters which are already configured outside the `tcolorbox` package, e.g. the standard `figure` counter.

`/tcb/new/no counter` (no value, initially set)

The created boxes are not numbered. This is the default. The option may be used to overrule a previous option.

`/tcb/new/number within=<counter>` (no default, initially unset)

The automatic counter is set to zero, if `<counter>` is increased. Additionally, during output, the value of `<counter>` is prepended to the value of the automatic counter.

To prepend the automatic counter with the chapter number and to reset it with every new chapter, use:

```
number within=chapter
```

See `/tcb/new/use counter` ^{→ P. 102} for a complete example.

`/tcb/new/number format=<format macro>` (no default, initially `\arabic`)

Declares the format of the automatic counter. The `<format macro>` can be any valid L^AT_EX number formatting macro like `\arabic`, `\roman`, etc.

To display the counter value in large roman numbers, use:

```
number format=\Roman
```

See `/tcb/new/auto counter` ^{→ P. 101} for a complete example.

`/tcb/new/number freestyle=<code>` (no default, initially unset)

Allows advanced control over the complete number format. This option overrules the format given by `/tcb/new/number within` and `/tcb/new/number format`. Nevertheless, you can combine it with `/tcb/new/number within` to get the desired reset property.

The `<code>` is some formatting code which should contain `\tcbcounter` to reference the automated counter. Since this `<code>` is expanded, you have to secure each macro with `\noexpand` with exception of `\tcbcounter`.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section,
  number freestyle={(Q/\noexpand\thesection/\noexpand\Alph{\tcbcounter})},
  ]{phbox}[2][]{%
  colback=yellow!15!white,colframe=blue!75!black,fonttitle=\bfseries,
  title=Question~\thetcbcounter: #2,#1}
```

```
\begin{phbox}[label={myfreestyle}]{Title with freestyle number}
This box is automatically numbered with \ref{myfreestyle} on page
\pageref{myfreestyle}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{phbox}
```

Question (Q/5/A): Title with freestyle number

This box is automatically numbered with (Q/5/A) on page 103. Inside the box, the (Q/5/A) can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@phbox`.

! The following options `/tcb/new/crefname` and `/tcb/new/Crefname` need to be set inside the preamble.

U 2014-12-01

`/tcb/new/crefname={⟨singular⟩}{⟨plural⟩}` (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the lowercase `⟨singular⟩` and `⟨plural⟩` forms of the cross-reference are given. This type is the environment or macro name and `/tcb/label type`^{→ P. 94} is set automatically. See `/tcb/label type`^{→ P. 94} and [5] for more information.

U 2014-12-01

`/tcb/new/Crefname={⟨singular⟩}{⟨plural⟩}` (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the uppercase `⟨singular⟩` and `⟨plural⟩` forms of the cross-reference are given. This type is the environment or macro name and `/tcb/label type`^{→ P. 94} is set automatically. See `/tcb/label type`^{→ P. 94} and [5] for more information.

Definition in the preamble:

```
% \usepackage{cleveref}
\newtcolorbox[auto counter,number within=section,
            crefname={bluebox}{blueboxes}]{%
  {mybluebox}[2][][colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
              title=Bluebox \thetcbcounter: #2,#1]}
```

```
% \usepackage{varioref}
% \usepackage{cleveref}
\begin{mybluebox}[label={myreference}]{My title}
This is an example.
\end{mybluebox}

\cref{myreference}, \cref{myreference}.\\
\cpageref{myreference}, \cpageref{myreference}.\\
\namecref{myreference}, \namecref{myreference}.\\
\labelcref{myreference}, \labelcpageref{myreference}.\\
With \texttt{varioref}:\\
\Vref{myreference}, \vref{myreference}.\\
\Vref*{myreference}, \vref*{myreference}.
```

Bluebox 5.1: My title

This is an example.

Bluebox 5.1, bluebox 5.1.

Page 104, page 104.

Bluebox, bluebox.

5.1, 104.

With `varioref`:

Bluebox 5.1, bluebox 5.1.

Bluebox 5.1, bluebox 5.1.

Used to comfortably blend into an existing schema of naming and numbering for some selected cases. For example, a `tcolorbox` can be used to display and entitle an image pretending to be a standard `figure` environment. Here, `/tcb/titleP.18` is used instead of the standard `\caption` and `/tcb/list textP.95` can be used instead of the optional parameter of the standard `\caption`.

Feasible values for `<name>` are:

- `figures`: blend into the standard `figure` environment.
- `tables`: blend into the standard `table` environment.
- `listings`: blend into the standard `lstlisting` environment of the package `listings` [6].

! Note that `blend into=listings` can only be used in the document content or, preferably, inside a `\AtBeginDocument` clause! Using it without `\AtBeginDocument` inside the preamble does not work since the `listings` packages initializes its counter also inside `\AtBeginDocument`.

```
\begin{figure}[htb]
  \centering\includegraphics[height=4cm]{lichtspiel.jpg}
  \caption{A standard figure}
\end{figure}

\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure}
  \includegraphics[height=4cm]{lichtspiel.jpg}
\end{myfigure}
```



Figure 1: A standard figure

Figure 2: A tcolorbox figure



/tcb/blend before title=⟨value⟩(no default, initially **colon**)

This option formats the title output of `/tcb/new/blend into`^{→ P. 105}. Note that this is a common `tcolorbox` option which should be set globally or in the normal option part of `\newtcolorbox`^{→ P. 15}.

Feasible values for ⟨value⟩ are:

- **colon**: use name/number plus colon.
- **dash**: use name/number plus dash.
- **colon hang**: use name/number plus colon with hanging indent.
- **dash hang**: use name/number plus dash with hanging indent.

```
\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
blend before title=dash hang,title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure with quite a long title}
  \includegraphics[height=5cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 3 – A tcolorbox figure with quite a long title



/tcb/blend before title code=<code> (no default)

This option formats the title output of /tcb/new/blend into^{→ P. 105}. The <code> takes one parameter, the name/number. Use this, if /tcb/blend before title^{→ P. 106} is not flexible enough.

```
\newtcolorbox[blend into=figures]{myfigure}[2]{float=htb,capture=hbox,  
blend before title code={\fbox{\#1}\ },title={#2},every float=\centering,#1}  
  
\begin{myfigure}{A tcolorbox figure}  
    \includegraphics[height=6cm]{lichtspiel.jpg}  
\end{myfigure}
```

Figure 4 | A tcolorbox figure



5.2 Lists of `tcolorbox`s

For figures and tables, L^AT_EX provides the `\listoffigures` and `\listoftables` commands to create lists of these numbered entities. Also, a `tcolorbox` can be part of such a kind of list.

1. Assign a list `<name>` by the *initialization* option `/tcb/new/list inside`.
2. Optionally, a new `<type>` for list entries may be assigned by the *initialization* option `/tcb/new/list type`.
3. List entries are generated automatically within each new `tcolorbox` using the above initialization.
 - If `/tcb/list entry`^{→ P. 95} is set, the entry is generated with it.
 - Otherwise, if `/tcb/title`^{→ P. 18} is set, the entry is generated with it.
 - Otherwise, the entry is generated with the current number and the environment name.
4. The generated list is displayed by `\tcblistof`.

`/tcb/new/list inside=<name>` (no default, initially unset)

Assigns a list or contents file to the generated `tcolorbox`s. Entries to this list are saved to a file which gets the `<name>` as file name extension. The list is referenced by this name in `\tcblistof`. For example:

```
list inside=exam
```

See Section 15.9 from page 322 for a complete example.

`/tcb/new/list type=<type>` (no default, initially `tcolorbox`)

Optionally, some `<type>` can be assigned to the list entries. For a new `<type>`, a macro `\l@<type>` has to exist which controls the format of the list entry. The default type is defined by

```
\newcommand*\l@tcolorbox{\@dottedtocline{1}{1.5em}{2.3em}}
```

This is identical to the `\l@section` setting of L^AT_EX. `\l@tcolorbox` can be redefined or a new `<type>` can be assigned.

`\tcblistof[<macro>]{<name>}{<title text>}`

Displays the generated list of `tcolorbox`s with the given `<name>`. The heading is generated by `<macro>{<title text>}` where `\section` is the default setting for `<macro>`.

To display the list inside a subsection, use for example:

```
\tcblistof[\subsection]{exam}{List of Exercises}
```

The result of the example is found as Subsection 15.10 on page 325.

! The core of the list is generated by `\@starttoc{<name>}` which can be wrapped into an own macro.

6 Side by Side

A *side by side* box is a special `tcolorbox`^{→ P. 12} where the upper and lower part of the box are set side by side. All boxes of this kind are unbreakable.



Further side by side options for code examples are `/tcb/listing side text`^{→ P. 304}, `/tcb/text side listing`^{→ P. 304}, `/tcb/listing outside text`^{→ P. 304}, and `/tcb/text outside listing`^{→ P. 304}.

6.1 Basic Settings

`/tcb/sidebyside=true|false` (default `true`, initially `false`)

Normally, the upper part and the lower part of the box have their positions as their names suggest. If `sidebyside` is set to `true`, the upper part is drawn *left-handed* and the lower part is drawn *right-handed*. Both parts are drawn together with the geometry settings of the upper part but the space is divided horizontally according to the following options. Colors, fonts, and box content additions are used individually. The resulting box is unbreakable.

```
\tcbsset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside]
  This is the upper (\textit{left-handed}) part.
  \tcblower
  This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\begin{tcolorbox}[bicolor,sidebyside,righthand width=3cm,
  sharp corners,boxrule=.4pt,colback=green!5,colbacklower=green!50!black!50]
  \lipsum[2]
  \tcblower
  \includegraphics[width=\ linewidth]{goldshade}%
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



Sets the vertical *<alignment>* for the left-handed and right-handed part.

Feasible values for *<alignment>* are:

- **center**: identical to `minipage` option `c`.
- **top**: identical to `minipage` option `t` (aligns the top lines of the left-handed and right-handed side according to their baselines).
- **bottom**: identical to `minipage` option `b` (aligns the bottom lines of the left-handed and right-handed side according to their baselines).
- **center seam**: aligns the center of the left-handed and right-handed side.
- **top seam**: aligns the very top seam of the left-handed and right-handed side.
- **bottom seam**: aligns the very bottom seam of the left-handed and right-handed side.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,
left=2mm,right=2mm,sidebyside,sidebyside gap=6mm,width=(\linewidth-2mm)/3}

\begin{tcolorbox}[adjusted title=center,sidebyside align=center]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=top,sidebyside align=top]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=bottom,sidebyside align=bottom]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```

center

This is a text which is too long for one line. This is a short text.

top

This is a text which is too long for one line. This is a short text.

bottom

This is a text which is too long for one line. This is a short text.

center, **top**, and **bottom** are identical to the known corresponding `minipage` options. While this is the preferred approach for text content, the result for boxed content like tables or images may not be as expected.

For such content, one may use **center seam**, **top seam**, and **bottom seam**. For example, **top seam** aligns the very top seam of the left-handed and right-handed side.

```

\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
size=small,righthand width=4cm,sidebyside,sidebyside gap=6mm,lower separated=false}

\begin{tcolorbox}[adjusted title=center seam,sidebyside align=center seam]
This is my description text for the pictures displayed on the right-handed side.
\tcblower
\includegraphics[width=\linewidth/2]{goldshade}%
\includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}


\begin{tcolorbox}[adjusted title=top seam,sidebyside align=top seam]
This is my description text for the pictures displayed on the right-handed side.
\tcblower
\includegraphics[width=\linewidth/2]{goldshade}%
\includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=bottom seam,sidebyside align=bottom seam]
This is my description text for the pictures displayed on the right-handed side.
\tcblower
\includegraphics[width=\linewidth/2]{goldshade}%
\includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}

```

center seam

This is my description text for the pictures displayed on the right-handed side.



top seam

This is my description text for the pictures displayed on the right-handed side.



bottom seam

This is my description text for the pictures displayed on the right-handed side.



`/tcb/sidebarbysside gap=<length>` (no default, initially 10mm)

Sets the horizontal distance between the left-handed and right-handed part to `<length>`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,  
sidebyside,width=(\linewidth-2mm)/2}  
  
\begin{tcolorbox}[adjusted title=Wide gap,sidebyside gap=30mm]  
This is a text which is too long for one line.  
\tcblower  
This is a short text.  
\end{tcolorbox}\hfill  
\begin{tcolorbox}[adjusted title=Narrow gap,sidebyside gap=1mm]  
This is a text which is too long for one line.  
\tcblower  
This is a short text.  
\end{tcolorbox}
```

Wide gap

This is a text which is too long for one line.

This is a short text.

Narrow gap

This is a text which is too long for one line.

(no default, initially unset)

Sets the width of the left-handed part to the given `<length>`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=My title,sidebyside,lefthand width=3cm]  
This is the upper (\textit{left-handed}) part.  
\tcblower  
This is the lower (\textit{right-handed}) part.  
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

(no default, initially unset)

Sets the width of the right-handed part to the given `<length>`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=My title,sidebyside,righthand width=3cm]  
This is the upper (\textit{left-handed}) part.  
\tcblower  
This is the lower (\textit{right-handed}) part.  
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/left hand ratio=⟨fraction⟩ (no default, initially 0.5)

Sets the width of the left-handed part to the given ⟨fraction⟩ of the available space. ⟨fraction⟩ is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper
(*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/right hand ratio=⟨fraction⟩ (no default, initially 0.5)

Sets the width of the right-handed part to the given ⟨fraction⟩ of the available space. ⟨fraction⟩ is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.


This is the lower
(*right-handed*) part.

If one side of a side-by-side box should be adapted to the width of its content, this width has to be computed beforehand. The following example uses a savebox `\mysavebox` to store the picture to determine its width. A more convenient way to handle this task is to use the methods from Section 6.2 on page 115.

```
% tcbuselibrary{skins,xparse}
% \usepackage{lipsum}
% \newsavebox\mysavebox % preamble
\DeclareTotalTColorBox{\mysidebox}{ O{} +m +m }{
    bicolor,colback=white,colbacklower=yellow!10,
    fonttitle=\bfseries,center title,
    sidebyside,
    code={\sbox{\mysavebox}{#2}},
    lefthand width=\wd\mysavebox,
    drop lifted shadow,
    #1
}
{\usebox{\mysavebox}\tcblower#3}

\mysidebox[title=The Triangle]{%
\begin{tikzpicture}
\path[fill=red!20,draw=red!50!black]
(0,0) node[below]{A} -- (3,1) node[right]{B}
-- (1,4) node[above]{C} -- cycle;
\end{tikzpicture}%
}%
\lipsum[1]
}
```

The Triangle



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

6.2 Advanced Settings from the **xparse** Library


! All following macros and options need the  **xparse** library to be loaded, see Section 21 on page 405.

N 2015-11-20

\tcbsidebyside[*options*] {*left-handed content*} {*right-handed content*}

Creates a colored box using more or less arbitrary *options* for a **tcolorbox**^{→ P. 12}. The */tcb/sidebyside*^{→ P. 109} option is set to **true** and the *<left-handed content>* and *<right-handed content>* is filled into the box appropriately. The resulting box is unbreakable. **\tcbsidebyside** is not only a shortcut for using a normal **tcolorbox**^{→ P. 12} with */tcb/sidebyside*^{→ P. 109}, but allows setting further options like */tcb/sidebyside adapt*^{→ P. 116} and */tcb/sidebyside switch*^{→ P. 118}.

```
% \tcbselibrary{skins,xparse}
% \usepackage{lipsum}
\tcbsidebyside[title=The Triangle,
  sidebyside adapt=left,
  bicolor,colback=white,colbacklower=yellow!10,
  fonttitle=\bfseries,center title,drop lifted shadow,
]{%
  \begin{tikzpicture}
    \path[fill=red!20,draw=red!50!black]
      (0,0) node[below]{A} -- (3,1) node[right]{B}
      -- (1,4) node[above]{C} -- cycle;
  \end{tikzpicture}%
}{%
  \lipsum[1]
}
```



The Triangle

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/sidebyside adapt=<side(s)> (no default, initially `none`)

The option allows the left-handed and/or right-handed side to determine the dimensions of the box. This option is only valid inside `\tcbsidebyside`^{P.115}.

Feasible values for `<side(s)>` are:

- **none**: no measurement of left-handed and right-handed side.
- **left**: the actual width of the left-handed content is used to set `/tcb/leftwidth`^{P.112}.
- **right**: the actual width of the right-handed content is used to set `/tcb/rightwidth`^{P.112}.
- **both**: the actual width of the left-handed and right-handed content is used to set `/tcb/leftwidth`^{P.112}, `/tcb/rightwidth`^{P.112}, and the overall `/tcb/width`^{P.34}.

```
% \tcbsuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=left,
    title=Very important table,
    beamer,colframe=blue!50!black,colback=blue!10,
    lower separated=false,sidebyside gap=5mm
]{%
\begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
\end{tabular}
}%
This table contains the most important figures for
all future actions. You may notice that B follows A,
C follows B, and so on.
}
```

Very important table

left	center	right
A	B	C
D	E	F

This table contains the most important figures for all future actions. You may notice that B follows A, C follows B, and so on.

```
% \tcbsuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=right,
    blanker,sidebyside gap=5mm
]{%
\lipsum[2]
}%
\begin{tikzpicture}
\path [fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
\fill [red] (45:5mm) circle (1mm);
\fill [red] (135:5mm) circle (1mm);
\draw [line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tikzpicture}
}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=both,
enhanced,center,
title=Both sides adapted,
attach boxed title to top center={yshift=-2mm},
coltitle=black,boxed title style={colback=red!25},
segmentation style=solid,colback=red!5,colframe=red!50
]{%
\begin{tabular}{|l|c|r|}\hline
left & center & right\\\hline
A & B & C\\\hline
D & E & F\\\hline
\end{tabular}
}{%
\begin{tikzpicture}
\path [fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
\fill [red] (45:5mm) circle (1mm);
\fill [red] (135:5mm) circle (1mm);
\draw [line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tikzpicture}
}
```

Both sides adapted

left	center	right
A	B	C
D	E	F



`/tcb/sidebyside switch=true|false` (default true, initially false)

If set to true, the *<left-handed content>* and *<right-handed content>* of `\tcbsidebyside`^{P. 115} are switched. Obviously, this option is only valid inside `\tcbsidebyside`^{P. 115}.

The side switching can be made even/odd page sensitive, if used inside `/tcb/if odd page`^{P. 96}.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside{Left}{Right}

\tcbsidebyside[sidebyside switch]{Left}{Right}

\tcbsidebyside[title=Very important table,
  if odd page={sidebyside switch,sidebyside adapt=right,flushright title}%
    {sidebyside adapt=left},
  beamer,colframe=blue!50!black,colback=blue!10,
  lower separated=false,sidebyside gap=5mm
]{%
\begin{tabular}{|l|c|r|}\hline
  left & center & right\\\hline
  A & B & C\\\hline
  D & E & F\\\hline
\end{tabular}
}%
This table contains the most important figures for
all future actions. You may notice that B follows A,
C follows B, and so on.
}
```

Left	Right									
Right	Left									
Very important table										
<table border="1"> <thead> <tr> <th>left</th><th>center</th><th>right</th></tr> </thead> <tbody> <tr> <td>A</td><td>B</td><td>C</td></tr> <tr> <td>D</td><td>E</td><td>F</td></tr> </tbody> </table>		left	center	right	A	B	C	D	E	F
left	center	right								
A	B	C								
D	E	F								

This table contains the most important figures for all future actions. You may notice that B follows A, C follows B, and so on.

7 Saving and Loading of Verbatim Texts

The following macros are slightly modified versions of the original macros from the known packages `moreverb` and `verbatim`. They are used implicitly inside of a `tcolorbox` environment, but they can be used outside also.

```
\begin{tcbverbatimwrite}{\langle file name\rangle}
  \langle environment content\rangle
\end{tcbverbatimwrite}
```

Saves the `\langle environment content\rangle` to a file named by `\langle file name\rangle`. TeX macros inside the environment are not expanded.

```
\begin{tcbverbatimwrite}{\jobname_verbexp.tex}
  This text is saved \textit{as is}.
\end{tcbverbatimwrite}

Now, we are using the file:\par
\input{\jobname_verbexp.tex}
```

Now, we are using the file:
This text is saved *as is*.

This environment may be used inside an own environment. Note, that inside the environment definition `\tcbverbatimwrite` has to be used instead of `\begin{tcbverbatimwrite}` and `\endtcbverbatimwrite` instead of `\end{tcbverbatimwrite}`.

```
\newenvironment{myverbatim}{%
  \begingroup\tcbverbatimwrite{\jobname_myverb.tex}%
  \endtcbverbatimwrite\endgroup}

\begin{myverbatim}
  This is the text which is saved by my own environment.
\end{myverbatim}

Now, we are using the file:\par
\input{\jobname_myverb.tex}
```

Now, we are using the file:
This is the text which is saved by my own environment.

```
\begin{tcbwritetemp}
  \langle environment content\rangle
\end{tcbwritetemp}
```

Has the same function as `tcbverbatimwrite`, but uses the key value of `tempfile` for the file name.

```
\begin{tcbwritetemp}
  This text is saved \textit{as is}.
\end{tcbwritetemp}

Now, we are using the file:\par
\tcbusetemp
```

Now, we are using the file:
This text is saved *as is*.

`\tcbusetemp`

Loads the current temporary file which was saved by `tcbwritetemp`.

8 Recording

The package provides some macros and options to take *records* during compilation. This is done by L^AT_EX file operations to save some data to a file for later usage. The main application scenario is depicted in Section 8.3 on the next page where information about example solutions is recorded and read again in Section 8.4 on page 124.

8.1 Makros

N 2014-11-28

\tcbstartrecording [*file name*]

Opens a file denoted by *file name* for writing the records. The default file name is `\jobname.records`. See Section 8.3 on the next page for an example application.

N 2014-11-28

\tcbrecord {*content*}

Records any *content* to the record file. `\tcbrecord` is implemented as `\immediate\write`. `\tcbstartrecording` has to be called before; otherwise, `\tcbrecord` is silently ignored.

```
\tcbrecord{\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28

\tcbstoprecording

Closes the current record file which was opened by `\tcbstartrecording` before.

N 2014-11-28

\tcbinputrecords [*file name*]

Opens a file denoted by *file name* for reading the records via `\input`. The default file name is the name of the last used record file for saving. `\tcbstoprecording` has to be called before.

8.2 Options

N 2014-11-28

/tcb/record=*content*

(style, no default)

Records any *content* to the record file, see `\tcbrecord`. This key can be used several times to write several lines.

```
record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28

/tcb/no recording

Disables `\tcbrecord` and `/tcb/record` inside the current group.

8.3 Example: Exercises

The following application example creates exercises and their corresponding solutions. Each pair is generated inside a single `tcolorbox` where the solution is given below `\tcblower`^{P. 12}. For every example, the solution part is saved by `/tcb/savelowerto`^{P. 24} to a file. The saving is recorded using `/tcb/record`^{P. 120}. To enlighten the possibilities, the second exercise has no solution. Finally, the solutions are input in Section 8.4 on page 124.

Definition in the preamble:

```
% \tcbuselibrary{skins,xparse}

\NewTColorBox[auto counter,number within=section]{exercise}{+0{}}
{
    enhanced,colframe=green!20!black,colback=yellow!10!white,coltitle=green!40!black,
    fonttitle=\bfseries,
    underlay={\begin{tcbclipinterior}
        \shade[inner color=green!80!yellow,outer color=yellow!10!white]
            (interior.north west) circle (2cm);
        \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
            (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
    title={Exercise~\thetcbcounter},
    label={exercise@\thetcbcounter},
    attach title to upper=\quad,
    after upper={\par\hfill\textcolor{green!40!black}{%
        \itshape Solution on page~\pageref{solution@\thetcbcounter}}},%
    lowerbox=ignored,
    savelowerto=solutions/exercise-\thetcbcounter.tex,
    record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}},%
    #1
}

\NewTotalTColorBox{\solution}{mm}
{
    enhanced,colframe=red!20!black,colback=yellow!10!white,coltitle=red!40!black,
    fonttitle=\bfseries,
    underlay={\begin{tcbclipinterior}
        \shade[inner color=red!50!yellow,outer color=yellow!10!white]
            (interior.north west) circle (2cm);
        \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
            (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
    title={Solution of Exercise~\ref{exercise#1} on page~\pageref{exercise#1}:},
    phantomlabel={solution@#1},
    attach title to upper=\par,
} {\input{#2} }

\tcbset{no solution/.style={no recording,after upper=}}

```

```
\tcbstartrecording

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x)=\sin((\sin x)^2)
\end{equation*}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( \sin((\sin x)^2) \right)' \\
&= \cos((\sin x)^2) 2\sin x \cos x.
\end{align*}

```

```

\end{exercise}

\begin{exercise}[no solution]
It holds:
\begin{equation*}
\frac{d}{dx} \left( \ln|x| \right) = \frac{1}{x}.
\end{equation*}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x) = (\sin(\sin x))^2
\end{equation*}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( (\sin(\sin x))^2 \right)' \\
&= 2\sin(\sin x)\cos(\sin x)\cos x.
\end{align*}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x) = \sqrt{x^3 - 6x^2 + 2x}
\end{equation*}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( \sqrt{x^3 - 6x^2 + 2x} \right)' \\
&= \frac{3x^2 - 12x + 2}{2\sqrt{x^3 - 6x^2 + 2x}}.
\end{align*}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x) = \left( \frac{2+3x}{1-2x} \right)^3
\end{equation*}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( \frac{2+3x}{1-2x} \right)^3' \\
&= 3 \left( \frac{2+3x}{1-2x} \right)^2 \frac{(1-2x)3-(2+3x)(-2)}{(1-2x)^2} \\
&= \frac{21(2+3x)^2}{(1-2x)^4}.
\end{align*}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x) = \frac{\cos x}{(\tan 2x)^2}
\end{equation*}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( \frac{\cos x}{(\tan 2x)^2} \right)' \\
&= \frac{1}{(\tan 2x)^2} \left( \frac{(-\sin x)(\cos 2x)^2 + (\cos x)4\cos 2x(-\sin 2x)}{(\cos 2x)^2} \right) \\
&\quad - \frac{4\cos x(\cos 2x)^2 \sin 2x \cos 2x}{(\cos 2x)^3} \\
&= -\frac{\cos(2x)[\sin x \sin 2x \cos 2x + 4\cos x(\sin 2x)^2]}{(\sin 2x)^3} \\
&\quad + 4 \frac{\cos x(\cos 2x)^2}{(\sin 2x)^3}
\end{align*}

```

```

&= -\frac{\cos(2x)}{[\sin x \sin 2x \cos 2x + 4\cos x]} \cdot (\sin 2x)^3.

\end{aligned}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x) = \cos((2x^2+3)^3)
\end{equation*}
\end{exercise}
\tcblower
The derivative is:
\begin{aligned}
f'(x) &= \left( \cos((2x^2+3)^3) \right)' \\
&= -\sin((2x^2+3)^3) \cdot 3(2x^2+3)^2 \cdot 2 \cdot 2x \\
&= -12x(2x^2+3)^2 \sin((2x^2+3)^3).
\end{aligned}
\end{aligned}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x) = (x^2+1)\sqrt{x^4+1}
\end{equation*}
\end{exercise}
\tcblower
The derivative is:
\begin{aligned}
f'(x) &= \left( (x^2+1)\sqrt{x^4+1} \right)' \\
&= 2x\sqrt{x^4+1} + \frac{2x^3(x^2+1)}{\sqrt{x^4+1}}.
\end{aligned}
\end{aligned}
\end{exercise}

\tcbstoprecording

```

Exercise 8.1: Compute the derivative of the following function:

$$f(x) = \sin((\sin x)^2)$$

Solution on page 124

Exercise 8.2: It holds:

$$\frac{d}{dx}(\ln x) = \frac{1}{x}.$$

Exercise 8.3: Compute the derivative of the following function:

$$f(x) = (\sin(\sin x))^2$$

Solution on page 124

Exercise 8.4: Compute the derivative of the following function:

$$f(x) = \sqrt{x^3 - 6x^2 + 2x}$$

Solution on page 124

Exercise 8.5: Compute the derivative of the following function:

$$f(x) = \left(\frac{2+3x}{1-2x} \right)^3$$

Solution on page 125

Exercise 8.6: Compute the derivative of the following function:

$$f(x) = \frac{\cos x}{(\tan 2x)^2}$$

Solution on page 125

Exercise 8.7: Compute the derivative of the following function:

$$f(x) = \cos((2x^2 + 3)^3)$$

Solution on page 125

Exercise 8.8: Compute the derivative of the following function:

$$f(x) = (x^2 + 1)\sqrt{x^4 + 1}$$

Solution on page 125

8.4 Example: Solutions

This concludes the example given in Section 8.3 on page 121. Now, the saved and recorded solutions are included.

\tcbinputrecords

Solution of Exercise 8.1 on page 123:

The derivative is:

$$f'(x) = \left(\sin((\sin x)^2) \right)' = \cos((\sin x)^2)2 \sin x \cos x.$$

Solution of Exercise 8.3 on page 123:

The derivative is:

$$f'(x) = \left((\sin(\sin x))^2 \right)' = 2 \sin(\sin x) \cos(\sin x) \cos x.$$

Solution of Exercise 8.4 on page 123:

The derivative is:

$$f'(x) = \left(\sqrt{x^3 - 6x^2 + 2x} \right)' = \frac{3x^2 - 12x + 2}{2\sqrt{x^3 - 6x^2 + 2x}}.$$

Solution of Exercise 8.5 on page 124:

The derivative is:

$$f'(x) = \left(\left(\frac{2+3x}{1-2x} \right)^3 \right)' = 3 \left(\frac{2+3x}{1-2x} \right)^2 \frac{(1-2x)3 - (2+3x)(-2)}{(1-2x)^2} = \frac{21(2+3x)^2}{(1-2x)^4}.$$

Solution of Exercise 8.6 on page 124:

The derivative is:

$$\begin{aligned} f'(x) &= \left(\frac{\cos x}{(\tan 2x)^2} \right)' = \left(\frac{\cos x (\cos 2x)^2}{(\sin 2x)^2} \right)' \\ &= \frac{(\sin 2x)^2 [(-\sin x)(\cos 2x)^2 + (\cos x)4 \cos 2x (-\sin 2x)] - \cos x (\cos 2x)^2 4 \sin 2x \cos 2x}{(\sin 2x)^4} \\ &= -\frac{\cos(2x)[\sin x \sin 2x \cos 2x + 4 \cos x (\sin 2x)^2 + 4 \cos x (\cos 2x)^2]}{(\sin 2x)^3} \\ &= -\frac{\cos(2x)[\sin x \sin 2x \cos 2x + 4 \cos x]}{(\sin 2x)^3}. \end{aligned}$$

Solution of Exercise 8.7 on page 124:

The derivative is:

$$\begin{aligned} f'(x) &= \left(\cos((2x^2 + 3)^3) \right)' = -\sin((2x^2 + 3)^3) 3(2x^2 + 3)^2 2 \cdot 2x \\ &= -12x(2x^2 + 3)^2 \sin((2x^2 + 3)^3). \end{aligned}$$

Solution of Exercise 8.8 on page 124:

The derivative is:

$$f'(x) = \left((x^2 + 1) \sqrt{x^4 + 1} \right)' = 2x \sqrt{x^4 + 1} + \frac{2x^3(x^2 + 1)}{\sqrt{x^4 + 1}}.$$

9 Technical Overview and Customization

This section provides a technical overview of the skin concept of `tcolorbox`. For most applications of `tcolorbox`, one will not need to know the bells and whistles described herein. You may proceed to Section 10 on page 140 where the customization options for most users are documented.

The following explanations also cover options and settings from the `LIB skins` library, see Section 10 on page 140.

9.1 Skins and Drawing Engines

From a technical point of view, a *skin* is a style definition for the appearance of a `tcolorbox`. The core package provides some additional option keys for skins but only two skins called `standard`^{→ P. 194} and `standard jigsaw`^{→ P. 195}. The `LIB skins` library adds several more skins. To change to a skin, only one option from the core package has to be set.

`/tcb/skin=<name>` (style, no default, initially `standard`)

Sets the current skin to `<name>`. This is a style definition which sets all the following keys, i.e. for many use cases there is nothing more to do.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,  
width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=ske}  
  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[skin=beamer,beamer,adjusted title=My title]  
This is my content.  
\end{tcolorbox}
```



`/tcb/skin first=<name>` (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`^{→ P. 353} and is broken actually, then the skin for the *first* part of the break sequence is set to `<name>`, see Subsection 17.7 on page 365. Typically, this key is set by a `/tcb/skin`.

`/tcb/skin middle=<name>` (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`^{→ P. 353} and is broken actually, then the skin for the *middle* parts (if any) of the break sequence is set to `<name>`, see Subsection 17.7 on page 365. Typically, this key is set by a `/tcb/skin`.

`/tcb/skin last=<name>` (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`^{→ P. 353} and is broken actually, then the skin for the *last* part of the break sequence is set to `<name>`, see Subsection 17.7 on page 365. Typically, this key is set by a `/tcb/skin`.

`/tcb/graphical environment=<name>` (no default, initially `pgfpicture`)

Sets the graphical environment for the `tcolorbox` to `<name>`. Feasible values are `pgfpicture` and `tikzpicture` or environments which inherit from one of these two. This key is set by a `/tcb/skin` and may seldom be used directly.

The skin of a `tcolorbox` is drawn by up to four *engines*. Afterwards, the text content is drawn which is not part of a skin. The four steps are:

1. The *frame* of the box, drawn by `/tcb/frame engine`.
2. The *interior* of the box. The interior of a box with title is drawn differently from a box without title. `/tcb/interior titled engine` or `/tcb/interior engine`^{→ P. 128} is used to draw the interior.
3. The *segmentation* (line) of the box, if there is a lower part; drawn by `/tcb/segmentation engine`^{→ P. 128}.
4. The *title area* of the box, if there is a title and `/tcb/title filled`^{→ P. 27} is set to `true`; drawn by `/tcb/title engine`^{→ P. 128}.

`/tcb/frame engine=<name>` (no default, initially `standard`)

Sets the *frame* drawing engine for a box to `<name>`. Typically, this key is set by a `/tcb/skin`^{→ P. 126}. Feasible values for `<name>` are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathfirst`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathfirstjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathmiddlejigsaw`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathlast`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `pathlastjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`^{→ P. 140},
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior titled engine=<name>` (no default, initially `standard`)

Sets the *interior* drawing engine for a titled box to `<name>`. Typically, this key is set by a `/tcb/skin`^{→ P. 126}. Feasible values for `<name>` are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/interior style`^{→ P. 141},
- `pathfirst`: a `tikz` path which is controlled by `/tcb/interior style`^{→ P. 141},
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/interior style`^{→ P. 141},
- `pathlast`: a `tikz` path which is controlled by `/tcb/interior style`^{→ P. 141},
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

/tcb/interior engine=*<name>* (no default, initially **standard**)

Sets the *interior* drawing engine for an untitled box to *<name>*. Typically, this key is set by a */tcb/skin*^{→ P. 126}. Feasible values for *<name>* are:

- **standard**: the original code from the core package,
- **path**: a **tikz** path which is controlled by */tcb/interior style*^{→ P. 141},
- **pathfirst**: a **tikz** path which is controlled by */tcb/interior style*^{→ P. 141},
- **pathmiddle**: a **tikz** path which is controlled by */tcb/interior style*^{→ P. 141},
- **pathlast**: a **tikz** path which is controlled by */tcb/interior style*^{→ P. 141},
- **freelance**: deprecated.
- **spartan**: a quite spartan code.
- **empty**: draw nothing.

/tcb/segmentation engine=*<name>* (no default, initially **standard**)

Sets the *segmentation* (line) drawing engine for a box to *<name>*. Typically, this key is set by a */tcb/skin*^{→ P. 126}. Feasible values for *<name>* are:

- **standard**: the original code from the core package,
- **path**: a **tikz** path which is controlled by */tcb/segmentation style*^{→ P. 143},
- **freelance**: deprecated.
- **spartan**: a quite spartan code.
- **empty**: draw nothing.

/tcb/title engine=*<name>* (no default, initially **standard**)

Sets the *title area* drawing engine for a titled box to *<name>*. Typically, this key is set by a */tcb/skin*^{→ P. 126}. Feasible values for *<name>* are:

- **standard**: the original code from the core package,
- **path**: a **tikz** path which is controlled by */tcb/title style*^{→ P. 143},
- **pathfirst**: a **tikz** path which is controlled by */tcb/title style*^{→ P. 143},
- **pathmiddle**: a **tikz** path which is controlled by */tcb/title style*^{→ P. 143},
- **pathlast**: a **tikz** path which is controlled by */tcb/title style*^{→ P. 143},
- **freelance**: deprecated.
- **spartan**: a quite spartan code.
- **empty**: draw nothing.


! After an engine is set to an initializing value, the resulting graphical code can be changed using code option keys, see Section 9.2 on page 130.

`/tcb/geometry nodes=true|false` (default true, initially false)

If set to `true`, up to four `tikz` nodes are defined for a `tcolorbox` which are named `frame`, `interior`, `segmentation`, and `title`. These nodes describe the boundaries of the equally named parts of a `tcolorbox`. They are used by most engines based on TikZ. Typically, this key is set automatically by a `/tcb/skin`^{P.126}.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
        width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=geon}

\begin{tcolorbox}[adjusted title=The title]
    The upper part.\tcblower The lower part.
\end{tcolorbox}
\begin{tcolorbox}[enhanced,adjusted title=The title,
    frame code={\path[draw=red,fill=red!25]
        (frame.south west) rectangle (frame.north east);},
    interior titled code={\path[draw=blue,fill=blue!25]
        (interior.south west) rectangle (interior.north east);},
    segmentation code={\path[draw=green,fill=green!25]
        (segmentation.south west) rectangle (segmentation.north east);},
    title code={\path[draw=black,fill=brown!75!black]
        (title.south west) rectangle (title.north east);}]
    The upper part.\tcblower The lower part.
\end{tcolorbox}
```



9.2 Code Option Keys

The following code options are applicable for all skins. The used *<graphical code>* can be any pgf code. For all skins with exception of `standard`^{P. 194} and `standard jigsaw`^{P. 195}, the *<graphical code>* can also be any TikZ code.

`/tcb/frame code=<graphical code>` (code, default from `standard`)

The given *<graphical code>* is used for drawing the *frame* of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,frame code={
  \foreach \n in {north east,north west,south east,south west}
    {\path [fill=red!75!black] (interior.\n) circle (3mm); }]
  This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a `tcolorbox`.

This is the lower part.

`/tcb/frame empty` (style, no value)

This is a shortcut for setting `/tcb/frame code` to empty. This option removes the drawing of the frame. Alternatively, use `/tcb/frame hidden`^{P. 141}.

`/tcb/interior titled code=<graphical code>` (code, default from `standard`)

The given *<graphical code>* is used for drawing the *interior* of the box, if the box comes with a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,interior titled code={
  \path [draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}
  This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a `tcolorbox`.

This is the lower part.

`/tcb/interior titled empty` (style, no value)

This is a shortcut for setting `/tcb/interior titled code` to empty. This option removes the drawing of the untitled interior. Alternatively, use `/tcb/interior hidden`^{P. 142}.

/tcb/*interior code*=⟨graphical code⟩ (code, default from standard)

The given ⟨graphical code⟩ is used for drawing the *interior* of the box, if the box is without a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,interior code={
  \path[draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/*interior empty* (style, no value)

This is a shortcut for setting /tcb/*interior code* to empty. This option removes the drawing of the interior. Alternatively, use /tcb/*interior hidden*^{→ P.142}.

/tcb/*segmentation code*=⟨graphical code⟩ (code, default from standard)

The given ⟨graphical code⟩ is used for drawing the *segmentation* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,segmentation code={
  \path[top color=red!5!white,bottom color=red!5!white,middle color=blue]
    (segmentation.south west) rectangle (segmentation.north east);}
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/*segmentation empty* (style, no value)


This is a shortcut for setting /tcb/*segmentation code* to empty. This option removes the drawing of the segmentation line. Alternatively, use /tcb/*segmentation hidden*^{→ P.143}.

/tcb/title code=<graphical code> (code, default from standard)

The given <graphical code> is used for drawing the *title* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,title code={
\path[draw=yellow,solid,decorate,line width=2mm,
decoration={coil,aspect=0,segment length=10.1mm}]
([xshift=1mm]title.west) -- ([xshift=-1mm]title.east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/title empty (style, no value)

This is a shortcut for setting /tcb/title code to empty. This option removes the drawing of the title area. Alternatively, use /tcb/title hidden^{→ P. 144}.

9.3 Subskins

A subskin is a new `/tcb/skin`^{→ P. 126} based on an existing skin which is extended or changed.

! Never use geometry settings or bounding box options inside a subskin definition! If one skin is replaced by another skin, the overall bounding box should stay constant. Especially, if a skin is used for a breakable box, unpredictable and unpleasant results could arise otherwise. If you want to change the geometry also, use an additional style. See the skin `beamer`^{→ P. 218} and the style `/tcb/beamer`^{→ P. 218} as pattern.

`\tcbsubskin{<name>}{<base skin>}{<options>}`

Creates a new skin `<name>` which inherits all properties of an existing `<base skin>` plus the given `<options>`. The new skin `<name>` can be used as value for the keys `/tcb/skin`^{→ P. 126}, `/tcb/skin first`^{→ P. 126}, `/tcb/skin middle`^{→ P. 126}, and `/tcb/skin last`^{→ P. 126}. As `<base skin>`, one can take `standard`^{→ P. 194}, `empty`^{→ P. 227}, `enhanced`^{→ P. 196}, or any skin from the LIB skins library, see Section 10 on page 140.

```
% \tcbuselibrary{skins}
\tcbsubskin{mycross}{empty}{frame code=%
  \draw[red, line width=5pt] (frame.south west)--(frame.north east);
  \draw[red, line width=5pt] (frame.north west)--(frame.south east);},
skin first=mycross,skin middle=mycross,skin last=mycross }

\begin{tcolorbox}[skin=mycross]
This is my content.
\end{tcolorbox}
```

This is my content.

`/tcb/skin first is subskin of=<base skin>{<options>}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing `<base skin>` plus the given `<options>`. This skin is set as `/tcb/skin first`^{→ P. 126}.

See a detailed example on page 233.

`/tcb/skin middle is subskin of=<base skin>{<options>}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing `<base skin>` plus the given `<options>`. This skin is set as `/tcb/skin middle`^{→ P. 126}.

See a detailed example on page 233.

`/tcb/skin last is subskin of=<base skin>{<options>}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing `<base skin>` plus the given `<options>`. This skin is set as `/tcb/skin last`^{→ P. 126}.

See a detailed example on page 233.

9.4 Drawing Scheme

Depending on the complexity of a `tcolorbox` definition, the resulting box is drawn in a more or less complex series of steps.

To document and demonstrate these drawing steps, we consider the following box definition:


```
\newtcolorbox{testbox}[1][][enhanced,title=Test Box,  
boxrule=1mm,titlerule=0.5mm,colframe=blue!50!black,  
interior style={top color=blue!20!green!50!white,bottom color=blue!20!yellow!50!white},  
colbacktitle=blue!50!green!90!white,segmentation style={solid},  
fonttitle=\bfseries,drop fuzzy shadow,borderline={0.3mm}{0.35mm}{yellow!50!white},  
underlay={\path[fill image opacity=0.15,fill image scale=0.9,  
fill stretch picture={\draw[blue,line width=2mm] circle (1);}  
(interior.south west) rectangle (interior.north east);},  
watermark text={Watermark},watermark color={green!20!white},  
finish={\begin{tcbclipframe}  
 \path[bottom color=black,top color=black!50!white,opacity=0.1]  
 (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;  
 \path[top color=white,bottom color=black!50!white,opacity=0.1]  
 (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;  
 \end{tcbclipframe}},#1}
```

For this definition, we get the maximal number of drawing steps:



1. shadow

- Section 10.6 on page 174.



2. frame

- `/tcb/colframe`^{→ P. 27}, `/tcb/opacityframe`^{→ P. 50}
- `/tcb/frame code`^{→ P. 130}
- `/tcb/frame style`^{→ P. 140}

3. interior


- `/tcb/colback`^{→ P. 27}, `/tcb-opacityback`^{→ P. 50}
- `/tcb/interior code`^{→ P. 131}, `/tcb/interior titled code`^{→ P. 130}
- `/tcb/interior style`^{→ P. 141}

4. title area

- `/tcb/colbacktitle`^{→ P. 27}, `/tcb-opacitybacktitle`^{→ P. 50}
- `/tcb/title code`^{→ P. 132}
- `/tcb/title style`^{→ P. 143}


5. segmentation

- `/tcb/lower separated`^{→ P. 25}
- `/tcb/segmentation code`^{→ P. 131}
- `/tcb/segmentation style`^{→ P. 143}




6. border line

- Section 10.5 on page 169



7. underlay

- Section 10.2 on page 147
- Section 10.8 on page 187



8. overlay

Watermark

- Section 4.12 on page 69
- Section 10.3 on page 157

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. 9. text content Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lower part

- `/tcb/colupper→ P. 28`, `/tcb/collower→ P. 28`, `/tcb/coltitle→ P. 28`
- `/tcb/fontupper→ P. 29`, `/tcb/fontlower→ P. 29`, `/tcb/fonttitle→ P. 29`
- `/tcb-opacityupper→ P. 51`, `/tcb-opacitylower→ P. 51`, `/tcb-opacitytitle→ P. 51`

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. 10. finish Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lower part

- Section 10.9 on page 189

All together, the box is drawn:

```
% \usepackage{lipsum}
\begin{testbox}
\lipsum[2]
\tcblower
Lower part
\end{testbox}
```

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lower part

9.5 Useful Properties

The following macros describe certain *properties* which may be used for the drawing scheme, see Section 9.4 on page 134. Sometimes, they are even available inside the box content. All of them are considered to be *read-only* and should never be redefined by the user.

N 2016-02-16

\tcbheightspace

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is held by `\tcbheightspace`. This macro is not usable inside the box content, but for skins or inside `/tcb/underlay`^{P. 187}, `/tcb/overlay`^{P. 69}, etc. If such a space information is needed inside the box content, see `/tcb/space to`^{P. 57} instead.

```
% \tcbselibrary{skins}
\newtcolorbox{testbox}[2][]{enhanced,size=fbox,
  colframe=blue!75!black,colback=white,height=#2,
  underlay={\node[above,inner sep=3pt] at (interior.south){%
    \includegraphics[width=\tcbtextwidth,height=\tcbheightspace-3pt]{goldshade.png}};
  },
  #1}
\begin{testbox}{3cm}
  This is my box. The space is filled with a picture.
\end{testbox}
\begin{testbox}{2cm}
  This is my box. The space is filled with a picture.
\end{testbox}
```

This is my box. The space is filled with a picture.



This is my box. The space is filled with a picture.



N 2016-02-16

\tcbtextwidth

This property describes the box content width.

- If there also is a lower part, it describes the width of the upper part.
- For `/tcb/sidebyside`^{P. 109} boxes, it describes the combined text width plus segmentation.
- This property can be used inside the box content text with exception of `/tcb/fit`^{P. 385} boxes.
- `\tcbtextwidth` can be used for all box types for skins or inside `/tcb/underlay`^{P. 187}, `/tcb/overlay`^{P. 69}, etc.

```
\begin{tcolorbox}[colframe=blue!75!black]
  Inside a box: \tcbtextwidth\ (=\\the\\linewidth).
\end{tcolorbox}
```

Inside a box: 370.74823pt (=370.74823pt).

\tcbtextheight

This property describes the designated box content height. If the box is larger than the natural height, the actual content will be smaller than \tcbtextheight.

- For boxes with a fixed /tcb/height^{P. 52}, this property can be used inside the box content text. For other boxes, it denotes 0pt inside the box content.
- \tcbtextheight can be used for all box types for skins or inside /tcb/underlay^{P. 187}, /tcb/overlay^{P. 69}, etc.

```
% \tcbuselibrary{skins}
\begin{tcolorbox}[enhanced,colframe=blue!75!black,
underlay={\node[left,red] at (frame.east) {Here: \tcbtextheight};}]
Inside a box with natural height: \tcbtextheight.
\end{tcolorbox}
\begin{tcolorbox}[enhanced,colframe=blue!75!black,height=1cm,
underlay={\node[left,red] at (frame.east) {Here: \tcbtextheight};}]
Inside a box with fixed height: \tcbtextheight.
\end{tcolorbox}
```

Inside a box with natural height: 0pt.

Here: 7.95pt

Inside a box with fixed height: 8.5359pt.

Here: 8.5359pt

10 Library skins

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

This also loads the package `tikz` [20]. Typically but not necessarily, the following skins use `tikz` instead of `pgf`.

10.1 Style Option Keys

The following style options are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced`^{→ P. 196} supports *all* of them and `standard`^{→ P. 194} `none`.


`/tcb/frame style=<tikz keys>` (style, no default)

The `<tikz keys>` are used inside the `tikz` path command for drawing the *frame* of the box.

This option is available if the `/tcb/frame engine`^{→ P. 127} is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style={left color=red!75!black,
    right color=blue!75!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/frame style image=<file name>` (no default, initially unset)

Fills the frame with an external image referenced by `<file name>`. For advanced features like blending of a picture with the background, use `/tcb/frame style` together with `/tikz/fill stretch image`^{→ P. 246}.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}


\begin{tcolorbox}[enhanced,title=My title,
  frame style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/frame style tile={⟨graphics options⟩}{⟨file name⟩}` (no default, initially unset)

Fills the frame with a tile pattern based on an external image referenced by `⟨file name⟩`. The `⟨graphics options⟩` are given to the underlying `\includegraphics` command. For advanced features like blending of a picture with the background, use `/tcb/frame style`^{→ P. 140} together with `/tikz/fill tile image`^{→ P. 250}.


```
\tcbset{colback=red!5!white,coltitle=red!30!black,  
       opacityback=0.75,fonttitle=\bfseries}  
  
\begin{tcolorbox}[enhanced,title=My title,  
                 frame style tile={width=1cm}{pink_marble.png}]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```



`/tcb/frame hidden` (style, no value)

This is a shortcut for `frame style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the frame. Alternatively, use `/tcb/frame empty`^{→ P. 130}.

```
\tcbset{colback=red!5!white,colframe=red!75!black,  
       fonttitle=\bfseries,coltitle=black}  
  
\begin{tcolorbox}[enhanced,title=My title,  
                 frame hidden]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```




`/tcb/interior style=⟨tikz keys⟩` (style, no default)

The `⟨tikz keys⟩` are used inside the `tikz` path command for drawing the *interior* of the box. They are used for the titled and for the untitled version as well.

This option is available if the `/tcb/interior titled engine`^{→ P. 127} or `/tcb/interior engine`^{→ P. 128} is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[enhanced,title=My title,  
                interior style={left color=red!20!white,  
                               right color=yellow!50!white}]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```



/tcb/interior style image=<file name> (no default, initially unset)

Fills the interior with an external image referenced by <file name>. For advanced features like blending of a picture with the background, use **/tcb/interior style**^{→ P. 141} together with **/tikz/fill stretch image**^{→ P. 246}.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
    interior style image=goldshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/interior style tile={<graphics options>} {<file name>} (no default, initially unset)

Fills the interior with a tile pattern based on an external image referenced by <file name>. The <graphics options> are given to the underlying **\includegraphics** command. For advanced features like blending of a picture with the background, use **/tcb/interior style**^{→ P. 141} together with **/tikz/fill tile image**^{→ P. 250}.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
    interior style tile={width=2cm}{crinklepaper.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/interior hidden (style, no value)

This is a shortcut for **interior style={draw=none,fill=none}**. Depending on the skin, this option switches off the drawing of the interior. Alternatively, use **/tcb/interior empty**^{→ P. 131} and/or **/tcb/interior titled empty**^{→ P. 130}.

```
\tcbset{frame style={top color=red!20!white,
    bottom color=red!20!white!75!black},
    fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
    interior hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

`/tcb/segmentation style=<tikz keys>` (style, no default)

The `<tikz keys>` are used inside the `tikz` path command for drawing the *segmentation* line of the box.

This option is available if the `/tcb/segmentation engine`^{→ P. 128} is set to `path`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,  
fonttitle=\bfseries}  
  
\begin{tcolorbox}[enhanced,title=My title,  
segmentation style={double=white,draw=blue,  
double distance=1pt,solid}]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

`/tcb/segmentation hidden` (style, no value)

This is a shortcut for `segmentation style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the segmentation line. See also `/tcb/lower separated`^{→ P. 25} which has the same effect for most skins. Alternatively, use `/tcb/segmentation empty`^{→ P. 131}.

```
\tcbset{colback=red!5!white,colframe=red!75!black,  
fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=My title,  
enhanced,segmentation hidden]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

`/tcb/title style=<tikz keys>` (style, no default)

The `<tikz keys>` are used inside the `tikz` path command for drawing the *title area* of the box.

This option is available if the `/tcb/title engine`^{→ P. 128} is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,  
coltitle=blue!50!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[enhanced,title=My title,  
title style={left color=blue!15!yellow,  
right color=red!85!black}]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/title style image=*<file name>* (no default, initially unset)

Fills the title area with an external image referenced by *<file name>*. For advanced features like blending of a picture with the background, use **/tcb/title style** → P. 143 together with **/tikz/fill stretch image** → P. 246.

```
\tcbset{colback=blue!5!white,colframe=blue!75!black,  
fonttitle=\bfseries}  
  
\begin{tcolorbox}[enhanced,title=My title,  
title style image=blueshade.png]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/title style tile={<graphics options>}{<file name>} (no default, initially unset)

Fills the title area with a tile pattern based on an external image referenced by *<file name>*. The *<graphics options>* are given to the underlying **\includegraphics** command. For advanced features like blending of a picture with the background, use **/tcb/title style** → P. 143 together with **/tikz/fill tile image** → P. 250.

```
\tcbset{colback=red!5!white,colframe=red!75!black,  
coltitle=blue!50!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[enhanced,title=My title,  
title style tile={width=1cm}{pink_marble.png}]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/title hidden (style, no value)

This is a shortcut for **title style={draw=none,fill=none}**. Depending on the skin, this option switches off the drawing of the title background. See also **/tcb/title filled** → P. 27 for a similar effect. Alternatively, use **/tcb/title empty** → P. 132.

```
\tcbset{colback=red!5!white,colframe=red!75!black,  
fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=My title,  
enhanced,title hidden]  
This is a \textbf{tcolorbox}.  
\tcblower  
This is the lower part.  
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

The `<tikz keys>` are used to draw a title rule, i.e. a rule below the optional title. The width of the rule is controlled by `/tcb/titlerule→ P. 36`. It may be set directly to a smaller width to create mixed effects with the standard rule. This option is implemented as an `/tcb/underlay→ P. 187`. Thus, it is not available for `standard→ P. 194` and `standard jigsaw→ P. 195`, but for all other skins, e.g. `enhanced→ P. 196`. As an underlay, this option can be used multiple times and is removed by `/tcb/no underlay→ P. 187`.

```
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  title=My title,
  titlerule=1mm,
  titlerule style=yellow ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  title=My title,
  titlerule=1mm,
  titlerule style={yellow,line width=0.5mm} ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,
  colback=red!10!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  frame hidden,
  title=My title,
  boxrule=0pt,titlerule=1mm,
  titlerule style=red!50!black ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
%\usetikzlibrary{arrows.meta}
\begin{tcolorbox}[empty,
  coltitle=red!75!black,fonttitle=\bfseries,
  borderline horizontal={0.5mm}{0pt}{red!50!white},
  title=My title,
  titlerule style={red,
    arrows = {Hooks[arc=270]-Hooks[arc=270]}} ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

The combined TikZ style applied to frame, interior, and title background can be used by authors in customizing code.


/tikz/tcb fill frame

(style, no value)

This is a TikZ style which is finally applied to the *frame* of the box.

```
% tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
       colframe=red!75!black,fonttitle=\bfseries,
       frame code app={\path[tcb fill frame]
                     ([yshift=-2mm]frame.north)
                     circle (8mm); } }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




/tikz/tcb fill interior

(style, no value)

This is a TikZ style which is finally applied to the *interior* of the box.

```
% tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
       colframe=red!75!black,fonttitle=\bfseries,
       interior titled code app={\path[tcb fill interior]
                     ([yshift=-0.1pt]interior.north east)
                     --([yshift=3pt]interior.north)
                     --([yshift=-0.1pt]interior.north west)
                     --cycle; } }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




/tikz/tcb fill title

(style, no value)

This is a TikZ style which is finally applied to the *title area* of the box.

```
% tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
       colframe=red!75!black,fonttitle=\bfseries,
       colbacktitle=blue!75!black,
       title code app={\path[tcb fill title]
                     (title) circle (5mm); } }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



10.2 Boxed Title Option Keys

10.2.1 Boxed Title Placement

The following options place the title text into an own $\text{\tcbbox}^{\rightarrow \text{P.14}}$. This boxed title can be customized independently from the main box using $/\text{tcb}/\text{boxed title style}^{\rightarrow \text{P.151}}$. The placement can be influenced by $\langle\text{boxtitle options}\rangle$.

$/\text{tcb}/\text{attach boxed title to top left}=\{\langle\text{boxtitle options}\rangle\}$ (style, default empty)

The title is boxed with a $\text{\tcbbox}^{\rightarrow \text{P.14}}$ and attached to the top left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,  
attach boxed title to top left]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

A diagram illustrating the placement of a boxed title. On the left, the LaTeX code for a `tcolorbox` environment is shown. On the right, the resulting output is displayed. It consists of a large rectangular box containing the text "This is a tcolorbox.". In the top-left corner of this box, there is a smaller rounded rectangle containing the text "My title".

$/\text{tcb}/\text{attach boxed title to top center}=\{\langle\text{boxtitle options}\rangle\}$ (style, default empty)

The title is boxed with a $\text{\tcbbox}^{\rightarrow \text{P.14}}$ and attached to the top center of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,  
attach boxed title to top center]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

A diagram illustrating the placement of a boxed title. On the left, the LaTeX code for a `tcolorbox` environment is shown. On the right, the resulting output is displayed. It consists of a large rectangular box containing the text "This is a tcolorbox.". In the top center of this box, there is a smaller rounded rectangle containing the text "My title".

$/\text{tcb}/\text{attach boxed title to top right}=\{\langle\text{boxtitle options}\rangle\}$ (style, default empty)

The title is boxed with a $\text{\tcbbox}^{\rightarrow \text{P.14}}$ and attached to the top right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,  
attach boxed title to top right]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

A diagram illustrating the placement of a boxed title. On the left, the LaTeX code for a `tcolorbox` environment is shown. On the right, the resulting output is displayed. It consists of a large rectangular box containing the text "This is a tcolorbox.". In the top right corner of this box, there is a smaller rounded rectangle containing the text "My title".

$/\text{tcb}/\text{attach boxed title to bottom left}=\{\langle\text{boxtitle options}\rangle\}$ (style, default empty)

The title is boxed with a $\text{\tcbbox}^{\rightarrow \text{P.14}}$ and attached to the bottom left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,  
attach boxed title to bottom left]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

A diagram illustrating the placement of a boxed title. On the left, the LaTeX code for a `tcolorbox` environment is shown. On the right, the resulting output is displayed. It consists of a large rectangular box containing the text "My title". In the bottom-left corner of this box, there is a smaller rounded rectangle containing the text "This is a tcolorbox.". The text "My title" is positioned below "This is a tcolorbox.".

$/\text{tcb}/\text{attach boxed title to bottom center}=\{\langle\text{boxtitle options}\rangle\}$ (style, default empty)

The title is boxed with a $\text{\tcbbox}^{\rightarrow \text{P.14}}$ and attached to the bottom center of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,  
attach boxed title to bottom center]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

A diagram illustrating the placement of a boxed title. On the left, the LaTeX code for a `tcolorbox` environment is shown. On the right, the resulting output is displayed. It consists of a large rectangular box containing the text "This is a tcolorbox.". In the bottom center of this box, there is a smaller rounded rectangle containing the text "My title".

$/\text{tcb}/\text{attach boxed title to bottom right}=\{\langle\text{boxtitle options}\rangle\}$ (style, default empty)

The title is boxed with a $\text{\tcbbox}^{\rightarrow \text{P.14}}$ and attached to the bottom right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,  
attach boxed title to bottom right]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

A diagram illustrating the placement of a boxed title. On the left, the LaTeX code for a `tcolorbox` environment is shown. On the right, the resulting output is displayed. It consists of a large rectangular box containing the text "My title". In the bottom-right corner of this box, there is a smaller rounded rectangle containing the text "This is a tcolorbox.". The text "My title" is positioned below "This is a tcolorbox.".

N 2016-02-26

/tcb/attach boxed title to top={⟨boxtitle options⟩} (style, default empty)

This is a convenient style to mimic a standard title. It uses `/tcb/attach boxed title to top center→ P. 147`, `/tcb/minipage boxed title→ P. 155`, and sizes the boxed title to match the base box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

N 2016-02-26

/tcb/attach boxed title to top*={⟨boxtitle options⟩} (style, default empty)

In contrast to `/tcb/attach boxed title to top`, this style uses smaller left and right rules to avoid previewer glitches. Typically, one would not use different colors for the frame as in the example below.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top*,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

N 2016-02-26

/tcb/attach boxed title to bottom={⟨boxtitle options⟩} (style, default empty)

This is a convenient style to produce a standard-like title at the bottom of the box. It uses `/tcb/attach boxed title to bottom center→ P. 147`, `/tcb/minipage boxed title→ P. 155`, and sizes the boxed title to match the base box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

N 2016-02-26

/tcb/attach boxed title to bottom*={⟨boxtitle options⟩} (style, default empty)

In contrast to `/tcb/attach boxed title to bottom`, this style uses smaller left and right rules to avoid previewer glitches.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom*]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

N 2016-02-26

/tcb/flip title={⟨options⟩} (style, default empty)

This style combines `/tcb/attach boxed title to bottom*` with `/tcb/boxed title style→ P. 151`. The `⟨options⟩` are given to `/tcb/boxed title style→ P. 151`.

```
\begin{tcolorbox}[tile,flip title={sharp corners},
  title=My title,colback=red!10,
  colbacktitle=red!75!black]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

10.2.2 Options for the Boxed Title Placement

The `<boxtitle options>` of the keys described above are shift values. The dimensions of the boxed title are stored into two macros `\tcboxedtitleheight` and `\tcboxedtitlewidth`. These macros can be used inside the following `<boxtitle options>`:

`/tcb/boxtitle/xshift=<length>` (no default, initially 0pt)

The boxed title is shifted by `<length>` in the horizontal direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left={xshift=-2mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/boxtitle/yshift=<length>` (no default, initially 0pt)

The boxed title is shifted by `<length>` in the vertical direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-\tcboxedtitleheight/2},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/boxtitle/yshifttext=<length>` (no default, initially 0pt)

The text inside the main box by `<length>` to give room for e.g. a sunken title.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/boxtitle/yshift*=<length>` (no default, initially 0pt)

Sets `/tcb/boxtitle/yshift` and `/tcb/boxtitle/yshifttext` the same time.

`/tcb/boxtitle/yshifttext` is only set if necessary.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center={yshift*=-3mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.



The bounding box of the resulting total `tcolorbox` is adapted automatically to the *vertical* dimensions of the boxed title. Possible horizontal enlargements are *not* automatically computed.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left=
    {xshift=-2mm,yshift=-2mm},
  boxed title style={size=small,colback=blue},
  show bounding box]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

10.2.3 Options for the Boxed Title Box

! The boxed title options are implemented as an underlay, see Section 10.8 on page 187. Therefore, a boxed title is not drawn, if a skin does not support underlays like `standard`^{P.194}. Still, the room for the boxed titles gets reserved in these cases.

! A TikZ node `title` is produced by a boxed title which can be used inside `/tcb/frame code`^{P.130}, `/tcb/interior code`^{P.131}, underlays, overlays, and finishes.

! A boxed title is almost always the first underlay. The only exceptions are underlays defined by `/tcb/underlay boxed title`^{P.188} which are drawn before. Additionally, underlays defined by `/tcb/underlay boxed title`^{P.188} are only drawn, if a boxed title is actually set. They are ignored, if there is no boxed title.

N 2016-02-26

`/tcb/boxed title size=<size>` (no default, initially `title`)

This setting defines the basic size for the title box. Further settings can be applied using `/tcb/boxed title style`^{P.151}. Feasible values for `<size>` are:

- `title`: Sets the size according to `/tcb/size`^{P.43}=`title`.
- `standard`: No size setting. Typically, this is identical to `/tcb/size`^{P.43}=`normal`.
- `copy`: The size values for a title of the base box are copied for the title box.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,enhanced,boxrule=0.4pt,
    title=My title,attach boxed title to top center]
\begin{tcolorbox}[boxed title size=title]
    This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[boxed title size=standard]
    This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[boxed title size=copy]
    This is a \textbf{tcolorbox}.
\end{tcolorbox}
\end{tcbraster}
```



/tcb/boxed title style=<options> (style, initially empty)

By default, a boxed title is dimensioned with `/tcb/size→ P. 43=title` and inherits the `/tcb/skin→ P. 126` and `/tcb/colframe→ P. 27` of the main box. Also, the `/tcb/colback→ P. 27` is inherited from the main `/tcb/colbacktitle→ P. 27`. Font and color of the title text are set as usual. All other `<options>` are set by the `/tcb/boxed title style` key. Since a boxed title is set by `\tcbbox→ P. 14`, all `tcolorbox` options are applicable here. If `/tcb/boxed title style` is used several times, the `<options>` are appended.

```
\begin{tcolorbox}[enhanced,title=My title,
  fonttitle=\bfseries,coltitle=green!25!black,
  attach boxed title to top center=
  {yshift=-2mm,yshifttext=-1mm},
  boxed title style={colframe=green!75!black,
    colback=yellow!50!green}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a `tcolorbox`.

```
\begin{tcolorbox}[enhanced,title=My title,
  colframe=red!50!black,colback=red!10!white,
  arc=1mm,colbacktitle=red!10!white,
  fonttitle=\bfseries,coltitle=red!50!black,
  attach boxed title to top left=
  {xshift=3.2mm,yshift=-0.50mm},
  boxed title style={skin=enhancedfirst jigsaw,
    size=small,arc=1mm,bottom=-1mm,
    interior style={fill=None,
      top color=red!30!white,
      bottom color=red!20!white}}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a `tcolorbox`.

```
\begin{tcolorbox}[enhanced,title=My title,
  colframe=blue!50!black,colback=blue!10!white,colbacktitle=blue!5!yellow!10!white,
  fonttitle=\bfseries,coltitle=black,attach boxed title to top center=
  {yshift=-0.25mm-\tcbboxedtitleheight/2,yshifttext=2mm-\tcbboxedtitleheight/2},
  boxed title style={boxrule=0.5mm,
    frame code={ \path[tcb fill frame] ([xshift=-4mm]frame.west)
    -- (frame.north west) -- (frame.north east) -- ([xshift=4mm]frame.east)
    -- (frame.south east) -- (frame.south west) -- cycle; },
    interior code={ \path[tcb fill interior] ([xshift=-2mm]interior.west)
    -- (interior.north west) -- (interior.north east)
    -- ([xshift=2mm]interior.east) -- (interior.south east) -- (interior.south west)
    -- cycle; } }]
\lipsum[2]
\end{tcolorbox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newcolorbox{mybox}[2][] {enhanced,skin=enhancedlast jigsaw,
attach boxed title to top left={xshift=-4mm,yshift=-0.5mm},
fonttitle=\bfseries\sffamily,varwidth boxed title=0.7\linewidth,
colbacktitle=blue!45!white,colframe=red!50!black,
interior style={top color=blue!10!white,bottom color=red!10!white},
boxed title style={empty,arc=0pt,outer arc=0pt,boxrule=0pt},
underlay boxed title={

\fill[blue!45!white] (title.north west) -- (title.north east)
-- +(\tcbboxedtitleheight-1mm,-\tcbboxedtitleheight+1mm)
-- ([xshift=4mm,yshift=0.5mm]frame.north east) -- +(0mm,-1mm)
-- (title.south west) -- cycle;
\fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north west)
-- +(-0.4,0) -- +(0,-0.3) -- cycle;
\fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north east)
-- +(0,-0.3) -- +(0.4,0) -- cycle; },
title={#2},#1}

\begin{mybox}{My title}
\lipsum[2]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newcolorbox{mybox}[2][] {enhanced,
attach boxed title to top left={xshift=1cm,yshift=-2mm},
fonttitle=\bfseries,\varwidth boxed title=0.7\linewidth,
colbacktitle=green!45!white,coltitle=green!10!black,colframe=green!50!black,
interior style={top color=yellow!10!white,bottom color=green!10!white},
boxed title style={boxrule=0.75mm,colframe=white,
borderline={0.1mm}{0mm}{green!50!black},
borderline={0.1mm}{0.75mm}{green!50!black},
interior style={top color=green!10!white,bottom color=green!10!white,
middle color=green!50!white},
drop fuzzy shadow},
title={#2},#1}

\begin{mybox}{My title}
\lipsum[2]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{flipbox}[2][]{%
    enhanced,colframe=blue!50!black,colback=yellow!5,fonttitle=\bfseries,
    flip title={interior hidden},title={#2},#1}

\begin{flipbox}{My title}
\lipsum[2]
\end{flipbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{skin=enhancedlast jigsaw,interior hidden,
boxsep=0pt,top=0pt,colframe=red,coltitle=red!50!black,
fonttitle=\bfseries\sffamily,
attach boxed title to bottom center,
boxed title style={empty,boxrule=0.5mm},
varwidth boxed title=0.5\linewidth,
underlay boxed title={%
    \draw[white,line width=0.5mm]
        ([xshift=0.3mm-\tcboxedtitleheight*2,yshift=0.3mm]title.north west)
        --([xshift=-0.3mm+\tcboxedtitleheight*2,yshift=0.3mm]title.north east);
    \path[draw=red,top color=white,bottom color=red!50!white,line width=0.5mm]
        ([xshift=0.25mm-\tcboxedtitleheight*2,yshift=0.25mm]title.north west)
        cos +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
        sin +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
        -- ([xshift=0.25mm,yshift=0.25mm]title.south west)
        -- ([yshift=0.25mm]title.south east)
        cos +(\tcboxedtitleheight,\tcboxedtitleheight/2)
        sin +(\tcboxedtitleheight,\tcboxedtitleheight/2); },
title={#2},#1}

\begin{mybox}{My title}
\lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

```
% \usepackage{varwidth}
\newcolorbox{mybox}[2][][enhanced,
  before skip=2mm, after skip=2mm,
  colback=black!5,colframe=black!50,boxrule=0.2mm,
  attach boxed title to top left={xshift=1cm,yshift*=1mm-\tcbboxedtitleheight},
  varwidth boxed title*=-3cm,
  boxed title style={frame code={
    \path[fill=tcbcol@back!30!black]
      ([yshift=-1mm,xshift=-1mm]frame.north west)
      arc[start angle=0,end angle=180,radius=1mm]
      ([yshift=-1mm,xshift=1mm]frame.north east)
      arc[start angle=180,end angle=0,radius=1mm];
    \path[left color=tcbcol@back!60!black,right color=tcbcol@back!60!black,
      middle color=tcbcol@back!80!black]
      ([xshift=-2mm]frame.north west) -- ([xshift=2mm]frame.north east)
      [rounded corners=1mm]-- ([xshift=1mm,yshift=-1mm]frame.north east)
      -- (frame.south east) -- (frame.south west)
      -- ([xshift=-1mm,yshift=-1mm]frame.north west)
      [sharp corners]-- cycle;
    },interior engine=empty,
  },
  fonttitle=\bfseries,
  title={#2},#1}

\begin{mybox}[colbacktitle=green]{My title}
\lipsum[2]
\end{mybox}
\begin{mybox}[colbacktitle=red]{My title}
\lipsum[3]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

2016-02-26

/tcb/no boxed title style

(style, initially set)

Removes all options which were set by **/tcb/boxed title style**^{P.151}.

/tcb/hbox boxed title

(no value, initially set)

The title text content is captured with a horizontal box. Especially, there are no linebreak possible.

```
\newtcolorbox{mybox}[1]{hbox boxed title,  
enhanced,attach boxed title to top center=  
{yshift=-3mm,yshifttext=-1mm},  
boxed title style={size=small,colback=red},  
title={#1}}  
  
\begin{mybox}{Short title}  
This is a \textbf{tcolorbox}.  
\end{mybox}\bigskip  
  
\begin{mybox}{This title is not really very short}  
This is a \textbf{tcolorbox}.  
\end{mybox}
```

Short title

This is a **tcolorbox**.

This title is not really very short

This is a **tcolorbox**.

/tcb/minipage boxed title=<length>

(initially unset)

The title text content is captured with a minipage with a width of *<length>*. By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title,  
enhanced,attach boxed title to top center=  
{yshift=-3mm,yshifttext=-1mm},  
boxed title style={size=small,colback=red},  
center title,title={#1}}  
  
\begin{mybox}{Short title}  
This is a \textbf{tcolorbox}.  
\end{mybox}\bigskip  
  
\begin{mybox}{This title is not really very short}  
This is a \textbf{tcolorbox}.  
\end{mybox}
```

Short title

This is a **tcolorbox**.

This title is not really
very short

This is a **tcolorbox**.

/tcb/minipage boxed title*=<length>

(initially unset)

The title text content is captured with a minipage with a width of main box width plus *<length>*. By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title*=-2cm,  
enhanced,attach boxed title to top center=  
{yshift=-3mm,yshifttext=-1mm},  
boxed title style={size=small,colback=red},  
center title,title={#1}}  
  
\begin{mybox}{Short title}  
This is a \textbf{tcolorbox}.  
\end{mybox}\bigskip  
  
\begin{mybox}{This title is not really very short}  
This is a \textbf{tcolorbox}.  
\end{mybox}
```

Short title

This is a **tcolorbox**.

This title is not
really very short

This is a **tcolorbox**.

/tcb/tikznode boxed title=<options> (initially unset)

The title text content is captured with a TikZ node with given TikZ <options>. The text is centered by default

```
\newtcolorbox{mybox}[1]{tikznode boxed title,
enhanced,attach boxed title to top center=
{yshift=-3mm,yshifttext=-1mm},
boxed title style={size=small,colback=red},
title={#1}]

\begin{mybox}{Short title}
This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title\is not really\very short}
This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title
is not really
very short
This is a **tcolorbox**.

/tcb/varwidth boxed title=<length> (initially unset)

The title text content is captured with a varwidth environment with a width of <length>. This style needs the varwidth package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title,
enhanced,attach boxed title to top center=
{yshift=-3mm,yshifttext=-1mm},
boxed title style={size=small,colback=red},
center title,title={#1}]

\begin{mybox}{Short title}
This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not really
very short
This is a **tcolorbox**.

/tcb/varwidth boxed title*=<length> (initially unset)

The title text content is captured with a varwidth environment with a width of main box width plus <length>. This style needs the varwidth package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title*=-2cm,
enhanced,attach boxed title to top center=
{yshift=-3mm,yshifttext=-1mm},
boxed title style={size=small,colback=red},
center title,title={#1}]

\begin{mybox}{Short title}
This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not
really very short
This is a **tcolorbox**.

10.3 Watermark Option Keys

The following watermark options are applicable for all skins which use `tikzpicture` as `/tcb/graphical environment`^{→ P. 126}. Therefore, the skin `standard`^{→ P. 194} does not support these watermarks, but all other skins, e.g. `enhanced`^{→ P. 196}.


! The watermark options rely on the more general overlay options described in Section 4.12 from page 69. Therefore, `watermarks` and `overlays` cannot be used mixed. But a mixture is possible with the `LIB hooks` library, see Section 20.

`/tcb/watermark text=<text>` (no default, initially unset)

Writes some `<text>` in the center of the interior region of a `tcolorbox`. This `<text>` is written *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom`^{→ P. 160} or `/tcb/watermark stretch`^{→ P. 162}.

```
\tcbsset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```



`/tcb/watermark text on=<part> is <text>` (no default, initially unset)

This option writes some `<text>` in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark text`. But this is done only for boxes named `<part>` of a break sequence, see `/tcb/breakable`^{→ P. 353}.

Feasible values for `<part>` are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.
- `first and middle`: first and middle parts of a break sequence.

/tcb/watermark graphics=⟨file name⟩ (no default, initially unset)

Draws an external picture referenced by ⟨file name⟩ in the center of the interior region of a **tcolorbox**. The picture is drawn *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of /tcb/watermark **zoom**^{→ P. 160} or /tcb/watermark **stretch**^{→ P. 162}.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.15]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from
http://commons.wikimedia.org/wiki/File:Basilica_5.png

/tcb/watermark graphics on=⟨part⟩ is ⟨file name⟩ (no default, initially unset)

This option draws a picture referenced by ⟨file name⟩ in the center of the interior region of a **tcolorbox** as described for /tcb/watermark **graphics**. But this is done only for boxes named ⟨part⟩ of a break sequence, see /tcb/breakable^{→ P. 353}.

Feasible values for ⟨part⟩ are:

- **broken**: all broken box parts,
- **unbroken**: unbroken boxes only,
- **first**: first parts of a break sequence,
- **middle**: middle parts of a break sequence,
- **last**: last parts of a break sequence,
- **unbroken and first**: unbroken boxes and first parts of a break sequence,
- **middle and last**: middle and last parts of a break sequence.

/tcb/watermark tikz=*<graphical code>* (no default, initially unset)

Draws the given *tikz <graphical code>* in the center of the interior region of a **tcolorbox**. The code is executed *after* the frame and interior are drawn and *before* the text content is drawn. The result is zoomed or stretched according the values of **/tcb/watermark zoom**^{→ P. 160} or **/tcb/watermark stretch**^{→ P. 162}.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
watermark tikz={\draw [line width=2mm] circle (1cm)
node{\fontfamily{ptm}\fontseries{b}\fontsize{20mm}{20mm}\selectfont ?};}]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark tikz on=*<part>* **is** *<graphical code>* (no default, initially unset)

This option draws the given *tikz <graphical code>* in the center of the interior region of a **tcolorbox** as described for **/tcb/watermark tikz**. But this is done only for boxes named *<part>* of a break sequence, see **/tcb/breakable**^{→ P. 353}.

Feasible values for *<part>* are:

- **broken**: all broken box parts,
- **unbroken**: unbroken boxes only,
- **first**: first parts of a break sequence,
- **middle**: middle parts of a break sequence,
- **last**: last parts of a break sequence,
- **unbroken and first**: unbroken boxes and first parts of a break sequence,
- **middle and last**: middle and last parts of a break sequence.

/tcb/no watermark (style, no default, initially set)

Removes the watermark if set before. This is an alias for **/tcb/no overlay**^{→ P. 70}.

/tcb/watermark opacity=⟨fraction⟩

(no default, initially 1.00)

Sets the opacity value $\in [0, 1]$ for a watermark.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Opacity 1.00,watermark opacity=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Opacity 0.50,watermark opacity=0.50]
\lipsum[2]
\end{tcolorbox}%
```

Opacity 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, telus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Opacity 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, telus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark zoom=⟨fraction⟩

(no default, initially 0.75)

Sets the zoom value for a watermark. The zoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches the frame.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Zoom 0.5,watermark zoom=0.5]
\lipsum[2]
\end{tcolorbox}%
```

Zoom 1.0

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, telus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Zoom 0.5

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, telus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark shrink=<fraction> (no default, initially unset)

Identically to **/tcb/watermark zoom**^{→ P. 160}, but the watermark never gets enlarged. Thus, the watermark keeps its original size or is shrunk.

/tcb/watermark overzoom=<fraction> (no default, initially unset)

Sets the overzoom value for a watermark. The overzoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches all four sides of the frame.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
watermark opacity=0.5,
watermark graphics=lichtspiel.jpg,nobeforeafter,width=(\linewidth-2mm)/2}
```

```
\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[1]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Overzoom 1.0,watermark overzoom=1.0]
\lipsum[1]
\end{tcolorbox}%
```

Zoom 1.0

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Overzoom 1.0

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



If a **/tcb/watermark overzoom** value of 1.0 is used in connection with invisible top and bottom rules which still have a thickness greater than 0pt, the space of these invisible rules may not be covered by the watermark. For example, this situation may occur during the breaking of **/tcb/enhanced**^{→ P. 196} boxes. To avoid this optical glitch, just set **/tcb/pad at break**^{→ P. 357} to any desired value.

/tcb/watermark stretch=<fraction> (no default, initially unset)

Sets the stretch value for a watermark. The stretch value is applied to width and height in relation to the box dimensions. It does not respect the aspect ratio. The value 1.0 means to fill the whole box.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
watermark graphics=lichtspiel.jpg,watermark opacity=0.5,
nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Stretch 1.00,watermark stretch=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Stretch 0.50,watermark stretch=0.50]
\lipsum[2]
\end{tcolorbox}%
```

Stretch 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, telus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Stretch 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, telus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark color=<color> (no default, initially mixed background and frame color)

Sets the color for the watermark.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark,
watermark color=yellow!50!red]
\lipsum[1]
\end{tcolorbox}
```

My title

My Watermark

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Sets the watermark to be clipped to the interior area.

```
\tcbset{enhanced,colback=white,colframe=blue!50!white,fonttitle=\bfseries,
watermark opacity=0.5,watermark stretch=1.00,arc=3mm,
watermark graphics=lichtspiel.jpg}

\begin{tcolorbox}[title=Clip (default),clip watermark]
\lipsum[1]
\end{tcolorbox}

\begin{tcolorbox}[title=No clip,clip watermark=false]
\lipsum[1]
\end{tcolorbox}%
```

Clip (default)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

No clip

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

10.4 Clip Environments

The following clip environments are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced`^{→ P. 196} supports *all* of them and `standard`^{→ P. 194} `none`. The typical area of application is inside overlay code, see Section 4.12 from page 69.

```
\begin{tcbclipframe}
  <environment content>
\end{tcbclipframe}
```

Defines a `Tikz` scope which clips to the frame area path.

```
\makeatletter
\newcolorbox{picturebox}[2][]{%
  enhanced,frame hidden,interior hidden,fonttitle=\bfseries,
  overlay={\begin{tcbclipframe}\node at (frame)
    {\includegraphics[width=\tcbb@width,height=\tcbb@height]{#2}};\end{tcbclipframe}%
    \begin{tcbclipinterior}\fill[white,opacity=0.75]
      (frame.south west) rectangle (frame.north east);\end{tcbclipinterior},#1}
\makeatother

\begin{picturebox}[title=My Picture Box]{lichtspiel.jpg}
\lipsum[1]
\end{picturebox}
```

My Picture Box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.


```
\begin{tcbinvclipframe}
<environment content>
\end{tcbinvclipframe}
```

Defines a `Tikz` scope which clips to the *outside* of the frame area path.

```
\tcbset{enhanced jigsaw,fonttitle=\bfseries,opacityback=0.35,colback=blue!5!white,
frame style={left color=red!75!black,right color=red!10!yellow}]

\begin{tikzpicture} % draw two balls
\path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
\shadedraw [shading=ball] (0,0) circle (1cm);
\shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}


\begin{tcolorbox}[title=A translucent box,
overlay={\begin{tcbinvclipframe}
\draw[red,line width=1cm] ([xshift=-2mm,yshift=2mm]frame.north west)
--([xshift=2mm,yshift=-2mm]frame.south east);
\draw[red,line width=1cm] ([xshift=-2mm,yshift=-2mm]frame.south west)
--([xshift=2mm,yshift=2mm]frame.north east);
\end{tcbinvclipframe}}]
\lipsum[2]
\end{tcolorbox}
```



```
\begin{tcbclipinterior}
<environment content>
\end{tcbclipinterior}
```

Defines a `Tikz` scope which clips to the interior area path.


```
\begin{tcolorbox}[enhanced,title=My Title,
overlay={\begin{tcbclipinterior}
\draw[red,line width=1cm] (interior.north west)--(interior.south east);
\draw[red,line width=1cm] (interior.south west)--(interior.north east);
\end{tcbclipinterior}}]
\lipsum[1]
\end{tcolorbox}
```



```
\begin{tcbcliptitle}
<environment content>
\end{tcbcliptitle}
```

Defines a `Tikz` scope which clips to the title area path.

```
\begin{tcolorbox}[enhanced,title=My Title,colframe=blue,colback=yellow!10!white,
overlay={\begin{tcbcliptitle}\node at (title)
{\includegraphics[width=\linewidth]{lichtspiel.jpg}};\end{tcbcliptitle}}]
\lipsum[1]
\end{tcolorbox}
```



/tcb/clip title=true|false


(default true, initially false)

Sets the title to be clipped to the title area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!white,coltitle=black,
colbacktitle=yellow!50!white}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long}]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long},
clip title]
This is a tcolorbox.
\end{tcolorbox}
```



This is a title which is unbreakable and far too long

This is a tcolorbox.

This is a title which is unbreak

This is a tcolorbox.


/tcb/clip upper=true|false

(default true, initially false)

Sets the upper part to be clipped to the interior area.


```
\newcommand{\mygraphics}[2][]{%
\tcbox[enhanced,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
right=0pt,boxrule=0.4pt,drop fuzzy shadow,clip upper,
colback=black!75!white,toptitle=2pt,bottomtitle=2pt,nobeforeafter,
center title,fonttitle=\small\sffamily,title=\detokenize{#2}]
{\includegraphics[width=\the\dimexpr(\linewidth-4mm)/2\relax]{#2}}}

\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```



The example for `/tcb/clip upper`^{→ P. 167} sizes the box according to the dimensions of the picture. To do it the other way around, the watermark options provide an easy solution.

```
\newcommand{\mygraphics}[2][]{%
\tcbox[enhanced,capture=minipage,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
right=0pt,boxrule=0.4pt,drop fuzzy shadow,nobeforeafter,
colback=black!75!white,toptitle=2pt,bottomtitle=2pt,
center title,fonttitle=\small\sffamily,title=\detokenize{#2},
width=(\linewidth-4mm)/2,height=6cm,colbacktitle={black},
watermark zoom=1.0,watermark graphics={#2}]{}
\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```



`/tcb/clip lower=true|false`


(default true, initially false)

Sets the lower part to be clipped to the interior area.

```
\tcbsset{enhanced,width=5cm,colframe=red!50!black,text and listing}

\begin{tcblisting}{}%
Donaudampfschiffahrtskapitänsmützenfransen
\end{tcblisting}

\begin{tcblisting}{clip lower}%
Donaudampfschiffahrtskapitänsmützenfransen
\end{tcblisting}
```



10.5 Border Line Option Keys

The following borderline options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment`^{→ P. 126}. Therefore, the skin `standard`^{→ P. 194} does not support these border lines, but most other skins, e.g. `enhanced`^{→ P. 196}.

The borderlines are independent from the normal `tcolorbox` rules. They may be used with or without the `/tcb/segmentation engine`^{→ P. 128}.

The borderlines are stackable, i.e. several different border lines can be used on the same `tcolorbox`. They are drawn *after* the box frame and box interior and *before* overlays or watermarks.

! Technically, the normal `tcolorbox` rules result from a TikZ *filling* process. The border lines are created by a TikZ *drawing* process. This can be used to apply different effects.

`/tcb/borderline={⟨width⟩}{⟨offset⟩}{⟨options⟩}` (no default, initially unset)

Adds a new borderline to the stack of border lines. This borderline is drawn with the given `⟨width⟩` and gets an `⟨offset⟩` computed from the frame outline. A positive `⟨offset⟩` value moves the borderline inside the `tcolorbox` and a negative `⟨offset⟩` value moves it outside without changing the bounding box.

The borderline is drawn along a TikZ path with the given TikZ `⟨options⟩`. Note that the TikZ `line width` option should not be used here.

The borderline lines adapt to the rounded corners of the `tcolorbox`. An inside borderline will switch to sharp corners if necessary, an outside borderline will always be rounded except for `/tcb/sharp corners`^{→ P. 47}.

```
\begin{tcolorbox}[enhanced,title=Rounded corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
\bigskip
\begin{tcolorbox}[enhanced,title=Sharp corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,sharp corners=downhill,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
```

Rounded corners

This is a tcolorbox.

Sharp corners

This is a tcolorbox.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,boxsep=1.5mm,
colback=yellow!20!white,
colframe=blue,
borderline={1mm}{1mm}{white},
borderline={1mm}{2mm}{red} ]
\lipsum[1]
\end{tcolorbox}
```

Lore ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,
frame hidden,colback=blue!10!white,
borderline={1mm}{0mm}{blue,dotted} ]
\lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,skin=enhancedmiddle,
frame hidden,interior hidden,top=0mm,bottom=0mm,boxsep=0mm,
borderline={0.75mm}{0mm}{red},
borderline={0.75mm}{0.75mm}{red!50!yellow},
borderline={0.75mm}{1.5mm}{yellow}, ]
\lipsum[3]
\end{tcolorbox}
```

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

```
% \usepackage{lipsum}
\newcolorbox{mygreenbox}[2][]{%
  enhanced, width=\linewidth-6pt,
  enlarge top by=3pt, enlarge bottom by=3pt,
  enlarge left by=3pt, enlarge right by=3pt,
  title={#2}, frame hidden, boxrule=0pt, top=1mm, bottom=1mm,
  colframe=green!30!black, colbacktitle=green!50!yellow,
  coltitle=black, colback=green!25!white,
  borderline={0.5pt}{-0.5pt}{green!75!blue},
  borderline={1pt}{-3pt}{green!50!blue}, #1}

\begin{mygreenbox}{My title}
  \lipsum[4]
\end{mygreenbox}
```

My title

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

/tcb/no borderline

(no default, initially set)

Removes all borderlines if set before.

/tcb/show bounding box=<color>

(default red, initially unset)

Displays the bounding box borderline of a `tcolorbox`. Its intended use is debugging and fine tuning. It should not be part of a final document. The optional `<color>` is the base color for the bounding box borderline.

```
\tcbset{enhanced,nobeforeafter,width=4cm,fonttitle=\bfseries}

\begin{tcolorbox}[show bounding box,title=Normal]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=blue,title=Shadow,drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=green,title=Enlarged,drop fuzzy shadow,
  enlarge by=2mm]
This is a tcolorbox.
\end{tcolorbox}
```

Normal	Shadow	Enlarged
This is a tcolorbox.	This is a tcolorbox.	This is a tcolorbox.



The following *partial* borderlines act slightly different from the complete borderlines described before. They ignore rounded corner settings, their length is not modified by their $\langle offset \rangle$, they ignore skin settings but adapt to breakable boxes.

N 2014-10-20

/tcb/borderline north={⟨width⟩}{⟨offset⟩}{⟨options⟩} (no default, initially unset)

Adds a new borderline with the given $\langle width \rangle$ to the north of the **tcolorbox**. A positive $\langle offset \rangle$ value moves the borderline inside the **tcolorbox** and a negative $\langle offset \rangle$ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,  
borderline north={2pt}{-2pt}{red}]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20

/tcb/borderline south={⟨width⟩}{⟨offset⟩}{⟨options⟩} (no default, initially unset)

Adds a new borderline with the given $\langle width \rangle$ to the south of the **tcolorbox**. A positive $\langle offset \rangle$ value moves the borderline inside the **tcolorbox** and a negative $\langle offset \rangle$ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,  
borderline south={2pt}{-2pt}{red}]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20

/tcb/borderline east={⟨width⟩}{⟨offset⟩}{⟨options⟩} (no default, initially unset)

Adds a new borderline with the given $\langle width \rangle$ to the east of the **tcolorbox**. A positive $\langle offset \rangle$ value moves the borderline inside the **tcolorbox** and a negative $\langle offset \rangle$ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,  
borderline east={2pt}{-2pt}{red}]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20

/tcb/borderline west={⟨width⟩}{⟨offset⟩}{⟨options⟩} (no default, initially unset)

Adds a new borderline with the given $\langle width \rangle$ to the west of the **tcolorbox**. A positive $\langle offset \rangle$ value moves the borderline inside the **tcolorbox** and a negative $\langle offset \rangle$ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,  
borderline west={2pt}{-2pt}{red}]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20

/tcb/borderline horizontal={⟨width⟩}{⟨offset⟩}{⟨options⟩} (no default, initially unset)

Adds a new borderline with the given ⟨width⟩ to the north and south of the **tcolorbox**. A positive ⟨offset⟩ value moves the borderlines inside the **tcolorbox** and a negative ⟨offset⟩ value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,top=3mm,bottom=3mm,  
borderline horizontal={2pt}{0pt}{red}]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20

/tcb/borderline vertical={⟨width⟩}{⟨offset⟩}{⟨options⟩} (no default, initially unset)

Adds a new borderline with the given ⟨width⟩ to the east and west of the **tcolorbox**. A positive ⟨offset⟩ value moves the borderlines inside the **tcolorbox** and a negative ⟨offset⟩ value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,left=3mm,right=3mm,  
borderline vertical={2pt}{0pt}{red}]  
This is a \textbf{tcolorbox}.\\  
My second line.  
\end{tcolorbox}
```

This is a **tcolorbox**.

My second line.

```
\begin{tcolorbox}[enhanced,colback=yellow!10!white,boxrule=0pt,frame hidden,  
borderline north={1mm}{-2mm}{red},  
borderline south={1mm}{-2mm}{blue},  
borderline west={1mm}{-2mm}{green},  
borderline east={1mm}{-2mm}{yellow}]  
\lipsum[1]  
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

10.6 Shadow Option Keys

The following shadow options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment`^{→ P. 126}. Therefore, the skin `standard`^{→ P. 194} does not support these shadows, but most other skins, e.g. `enhanced`^{→ P. 196}.

The shadows are stackable, i.e. several different shadows can be used on the same `tcolorbox`. They are drawn *before* the box frame is drawn.

/tcb/no shadow (no default)
Removes all shadows if set before.

10.6.1 Common Shadows and Halos

/tcb/drop shadow=(color) (style, default `black!50!white`)
Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the `(color)` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[drop shadow]  
This is a tcolorbox.  
\end{tcolorbox}\par\bigskip  
\begin{tcolorbox}[title=Another shadow,  
drop shadow=blue]  
This is a tcolorbox.  
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/drop fuzzy shadow=(color) (style, default `black!50!white`)
Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the `(color)` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[drop fuzzy shadow]  
This is a tcolorbox.  
\end{tcolorbox}\par\bigskip  
\begin{tcolorbox}[title=Another shadow,  
drop fuzzy shadow=blue]  
This is a tcolorbox.  
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/drop midday shadow=(color) (style, default `black!50!white`)
Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the `(color)` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[drop midday shadow]  
This is a tcolorbox.  
\end{tcolorbox}\par\bigskip  
\begin{tcolorbox}[title=Another shadow,  
drop midday shadow=blue]  
This is a tcolorbox.  
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/drop fuzzy midday shadow=⟨color⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the ⟨color⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
    drop fuzzy midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/halo=⟨size⟩ with ⟨color⟩ (style, default `0.9mm with yellow`)

Adds a new halo shadow with the given ⟨color⟩ which overlaps the colorbox an all sides by ⟨size⟩.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,halo]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
    halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```

My own halo

This is a tcolorbox.

Another halo

This is a tcolorbox.

/tcb/fuzzy halo=⟨size⟩ with ⟨color⟩ (style, default `0.9mm with yellow`)

Adds a new fuzzy halo shadow with the given ⟨color⟩ which overlaps the colorbox an all sides by ⟨size⟩ plus `0.48mm`.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,fuzzy halo]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
    fuzzy halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```

My own halo

This is a tcolorbox.

Another halo

This is a tcolorbox.

```
\begin{tcolorbox}[blank,enhanced jigsaw,boxsep=2pt,arc=2pt,
    fuzzy halo=2mm with red!50!white,
    fuzzy halo=1mm with white]
\lipsum[1]
\end{tcolorbox}
```

Lore ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

For all following shadows, the optionally given `<color>` for the shadow can be changed equivalent to the preceding examples.

`/tcb/drop shadow southeast=<color>` (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop shadow`^{P.174}.

```
\begin{tcolorbox}[drop shadow southeast,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow south=<color>` (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop midday shadow`^{P.174}.

```
\begin{tcolorbox}[drop shadow south,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow southwest=<color>` (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow southwest,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow west=<color>` (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow west,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow northwest=<color>` (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northwest,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow north=<color>` (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow north,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow northeast=⟨color⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northeast,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow east=⟨color⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow east,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow southeast=⟨color⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to [/tcb/drop fuzzy shadow](#)^{P. 174}.

```
\begin{tcolorbox}[drop fuzzy shadow southeast,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow south=⟨color⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to [/tcb/drop fuzzy midday shadow](#)^{P. 175}.

```
\begin{tcolorbox}[drop fuzzy shadow south,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow southwest=⟨color⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow southwest,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow west=⟨color⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow west,
enhanced,colback=red!5!white,colframe=red!75!black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow northwest=<color> (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow north=<color> (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow northeast=<color> (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow east=<color> (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

10.6.2 Lifted Shadows

`/tcb/drop lifted shadow=<color>` (style, default `black!50!white`)

Adds a new lifted shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
boxrule=0.4pt,sharp corners,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
drop lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop small lifted shadow=<color>` (style, default `black!50!white`)

Adds a new small lifted shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
boxrule=0.4pt,sharp corners,
colframe=red!75!black,fonttitle=\bfseries}

\tcbox[drop small lifted shadow,size=fbox]
{This is a tcolorbox.}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
drop small lifted shadow=black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop large lifted shadow=<color>` (style, default `black!50!white`)

Adds a new large lifted shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop large lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
drop large lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

10.6.3 Generic Shadows

`/tcb/shadow={<xshift>}{<yshift>}{{<offset>}}{<options>}` (no default)

Adds a new shadow to the stack of shadows. This shadow follows the outline of the `tcolorbox` but is shifted by `<xshift>` and `<yshift>`. The `<offset>` value is a distance value from the frame outline. A positive `<offset>` value shrinks the shadow and a negative `<offset>` value enlarges the shadow. The shadow is filled along a TikZ path with the given TikZ `<options>`.

The shadows adapt to the rounded corners of the `tcolorbox`. An shrinked shadow will switch to sharp corners if necessary, an enlarged shadow may become more rounded depending on several factors. But `/tcb/sharp corners`^{→ P. 47} have sharp shadows.

! Shadows are not considered for the bounding box computation by default. Large shadows may be overlaped by the following content. But, the bounding box can be adapted if necessary.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
    shadow={2mm}{-1mm}{0mm}{black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
    shadow={-1mm}{-2mm}{0mm}{fill=blue,
        opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
    shadow={-1.5mm}{-1.5mm}{0mm}{fill=blue,
        opacity=0.25},
    shadow={1.5mm}{-1.5mm}{0mm}{fill=red,
        opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
    shadow={5.5mm}{-3.5mm}{2mm}{fill=black,
        opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Halo shadow,
    shadow={0mm}{0mm}{-1.5mm}%
        {fill=yellow!75!red,opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
```

My own shadow

This is a tcolorbox.

Another shadow

This is a tcolorbox.

Double shadow

This is a tcolorbox.

Far shadow

This is a tcolorbox.

Halo shadow

This is a tcolorbox.

`/tcb/fuzzy shadow={⟨xshift⟩}{⟨yshift⟩}{⟨offset⟩}{⟨step⟩}{⟨options⟩}` (no default)

Adds a new fuzzy shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This fuzzy shadow follows the outline of the tcolorbox but is shifted by `⟨xshift⟩` and `⟨yshift⟩`. The `⟨offset⟩` value is a distance value from the frame outline. A positive `⟨offset⟩` value shrinks the shadow and a negative `⟨offset⟩` value enlarges the shadow. The `{⟨step⟩}` value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a TikZ path with the given TikZ `⟨options⟩` but any `opacity` value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
    fuzzy shadow={2mm}{-1mm}{0mm}{0.1mm}%
    {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
    fuzzy shadow={-1mm}{-2mm}{0mm}{0.2mm}%
    {fill=blue}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
    fuzzy shadow={-1.5mm}{-1.5mm}{0mm}{0.1mm}%
    {blue},
    fuzzy shadow={1.5mm}{-1.5mm}{0mm}{0.1mm}%
    {red}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
    fuzzy shadow={5.5mm}{-3.5mm}{0mm}{0.3mm}%
    {black}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Glow shadow,
    fuzzy shadow={0mm}{0mm}{-1.5mm}{0.15mm}%
    {yellow!75!red}]
This is a tcolorbox.
\end{tcolorbox}
```

My own shadow

This is a tcolorbox.

Another shadow

This is a tcolorbox.

Double shadow

This is a tcolorbox.

Far shadow

This is a tcolorbox.

Glow shadow

This is a tcolorbox.

```
\newtcolorbox{mybox}[1][][enhanced,
    fuzzy shadow={1.0mm}{-1.0mm}{0.12mm}{0mm}{blue!50!white},
    fuzzy shadow={-1.0mm}{-1.0mm}{0.12mm}{0mm}{red!50!white},
    fuzzy shadow={-1.0mm}{1.0mm}{0.12mm}{0mm}{green!50!white},
    fuzzy shadow={1.0mm}{1.0mm}{0.12mm}{0mm}{yellow!50!white},#1
]

\begin{mybox}[title=A multi shadow box]
This is a tcolorbox.
\end{mybox}
```

A multi shadow box

This is a tcolorbox.





/tcb/smart shadow arc=true|false

(default true, initially true)

If set to **true**, the shadow drawing algorithm tries to do a somewhat smart calculation of the arc for the shadow. The result is pleasing for typical boxes with rounded corners, but gives strange results for circular boxes.

```
\tcbset{enhanced,nobeforeafter,colback=red!5!white,
       colframe=red!75!black,width=3cm,square,halign=center,valign=center
     }

\begin{tcolorbox}[drop shadow]
Smart shadow arc (arguably better than normal)
\end{tcolorbox}
\hfill
\begin{tcolorbox}[smart shadow arc=false, drop shadow]
Normal shadow arc
\end{tcolorbox}
\hfill
\begin{tcolorbox}[circular arc, drop shadow]
Smart shadow arc (worse than normal)
\end{tcolorbox}
\hfill
\begin{tcolorbox}[circular arc, smart shadow arc=false, drop shadow]
Normal shadow arc
\end{tcolorbox}
```

**/tcb/lifted shadow={⟨xshift⟩}{⟨yshift⟩}{⟨bend⟩}{⟨step⟩}{⟨options⟩}**

(no default)

Adds a new lifted shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This lifted shadow follows the outline of the **tcolorbox** but is shifted by **⟨xshift⟩** and **⟨yshift⟩** on the lower left corner and by $-⟨xshift⟩$ and **⟨yshift⟩** on the lower right corner. Additionally, there is a **⟨bend⟩** in the middle. The **⟨step⟩** value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a TikZ path with the given TikZ **⟨options⟩** but any **opacity** value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
       boxrule=0.1pt,
       colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
               lifted shadow={1mm}{-2mm}{3mm}{0.1mm}%
                           {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
```

My own shadow

This is a tcolorbox.

10.6.4 TikZ Shadows

Alternativ to the package shadow options described before, shadows from the «Shadows Library» of TikZ can be used. Such shadows can be added directly to the frame path using `/tcb/frame style`^{→ P. 140}.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  frame style={drop shadow} ]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,height=3cm,
  colback=red!5!white,colframe=red!75!black,
  halign=center,valign=center,
  frame style={circular drop shadow} ]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,width=2.5cm,
  square,circular arc,
  halign=center,valign=center,
  colback=red!5!white,colframe=red!75!black,
  frame style={circular glow={fill=red}} ]
tcolorbox
\end{tcolorbox}
```

tcolorbox

10.7 Ti_kZ Picture Option Keys

The following general options are applicable for skins which use `tikzpicture` as `/tcb/graphical environment`^{→ P. 126}. Therefore, the skin `standard`^{→ P. 194} does not support these options, but most other skins, e.g. `enhanced`^{→ P. 196}.

/tcb/tikz=*(tikz option list)* (no default, initially empty)

Adds the given *(tikz option list)* to the main `tikzpicture` environment used to draw the color box, see [20]. If this option is applied a second time, the new *(tikz option list)* is appended to the current option list.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Transparent box,
    tikz={opacity=0.5,transparency group}]
This is a tcolorbox.
\end{tcolorbox}
```

Transparent box

This is a tcolorbox.

```
\tcbset{enhanced,colback=red!5!white,
        colframe=red!75!black,fonttitle=\bfseries,
        fontupper=\bfseries\Huge,
        halign title=center,halign=center}

\begin{tcolorbox}[title=Rotated box,
    tikz={rotate=30}]
Sold!
\end{tcolorbox}
```

Rotated box

Sold!

/tcb/tikz reset (initially set)

Removes all options given by `/tcb/tikz`.

/tcb/at begin tikz=*(tikz code)* (no default, initially empty)

The given *(tikz code)* is executed at the beginning of the `tikzpicture` environment after the TikZ option `execute at begin picture` was applied. If this option is applied a second time, the new *(tikz code)* is appended to the current code.

/tcb/at begin tikz reset (initially set)

Removes all code given by `/tcb/at begin tikz`.

/tcb/at end tikz=*(tikz code)* (no default, initially empty)

The given *(tikz code)* is executed at the ending of the `tikzpicture` environment before the TikZ option `execute at end picture` was applied. If this option is applied a second time, the new *(tikz code)* is appended to the current code.

/tcb/at end tikz reset (initially set)

Removes all code given by `/tcb/at end tikz`.

/tcb/rotate=<angle>

(no default, initially unset)

Rotates the **tcolorbox** by the given *<angle>*. Note that this is a TikZ coordinate transformation i.e. not all graphical elements like shadings will really be rotated.

```
\tcbset{enhanced,colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=Rotated box,rotate=30]  
This is a tcolorbox.  
\end{tcolorbox}
```



/tcb/scale=<fraction>

(no default, initially unset)

Scales the **tcolorbox** by the given *<fraction>*. Note that this is a TikZ coordinate transformation i.e. not all graphical elements like line widths will really be scaled.

```
\tcbset{enhanced,colback=red!5!white,  
colframe=red!75!black,fonttitle=\bfseries}  
  
\begin{tcolorbox}[title=Scaled box,scale=0.5]  
This is a tcolorbox.  
\end{tcolorbox}  
\begin{tcolorbox}[title=Scaled box,scale=1.25]  
This is a tcolorbox.  
\end{tcolorbox}
```



/tcb/remember

(style, initially unset)

Shortcut for `tikz={remember picture}`. This allows one to reference nodes in other TikZ pictures.

```
\begin{tcolorbox}[enhanced,remember,colback=red!5!white,colframe=red!75!black,  
fonttitle=\bfseries,title=The four corners of a paper,  
overlay={\draw[red!50!white,line width=1mm,opacity=0.5,shorten >=3mm]  
(frame.north west) edge[->] (current page.north west)  
(frame.north east) edge[->] (current page.north east)  
(frame.south west) edge[->] (current page.south west)  
(frame.south east) edge[->] (current page.south east);}]  
This is a tcolorbox.  
\end{tcolorbox}
```

The four corners of a paper

This is a tcolorbox.

`/tcb/remember as=<name>` (style, no default, initially unset)

The `frame` node will be remembered by the given `<name>` to be referenced in other TikZ pictures.


```
% \usepackage{lipsum}
\newcolorbox{mybox}[1] [] {enhanced,colframe=blue!75!black,colback=blue!10!white,
fonttitle=\bfseries,#1}

\begin{mybox}[title=First Box,nobeforeafter,width=\ linewidth/4,remember as=one]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Second Box,nobeforeafter,width=\ linewidth/4,remember as=two]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Third Box,nobeforeafter,width=\ linewidth/4,remember as=three]
This is a test.
\end{mybox}

\lipsum[2]

\begin{mybox}[title=Fourth Box,remember as=four]
This is a test.
\end{mybox}

\begin{tikzpicture}[overlay,remember picture,line width=1mm,draw=red!75!black]
\draw[->] (one.east) to[bend right] node[above] {A} (two.west);
\draw[->] (two.east) to[bend left] node[above] {B} (three.west);
\draw[->] (three.east) to[bend left=90] node[right] {C} (four.east);
\draw[->] (four.west) to[bend left=90] node[left] {D} (one.west);
\end{tikzpicture}
```



10.8 Underlay Option Keys

Underlays are quite similar to overlays described in Section 4.12 on page 69. Underlays are drawn *after* the frame and interior are drawn and *before* overlays and the text content is drawn; see Section 9.4 on page 134 for the general drawing scheme.

The differences between underlays and overlays are:

- Underlays are not applicable for the skins `standard`^{P. 194} and `standard jigsaw`^{P. 195}, whereas overlays are applicable also for these skins. The skin `spartan`^{P. 237} supports underlays but no overlays.



If an underlay is used with the `standard`^{P. 194} skin, it is silently ignored.

- Underlays are stackable, i.e. several different underlays can be used on the same `tcolorbox`. Overlays are not stackable by default (but with some help of the library `LB hooks`).
- Boxed titles are implemented with underlays (Section 10.2 on page 147), watermarks are implemented with overlays (Section 10.3 on page 157).

`/tcb/underlay=<graphical code>` (no default, initially unset)

Adds `<graphical code>` to the box drawing process. This `<graphical code>` is drawn *after* the frame and interior and *before* the text content.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,
  colframe=red!75!black,fonttitle=\bfseries,watermark color=yellow!50!white,
  underlay={\begin{tcbclipinterior}
    \draw[red!40!white,line width=1cm] (interior.south west)--(interior.north east);
  \end{tcbclipinterior}},
  attach boxed title to top center={yshift=-2mm},#1}

\begin{mybox}[title=My box,watermark text=My Watermark]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/no underlay`

(style, no default, initially set)

Removes the underlay if set before.

<code>/tcb/underlay broken=<graphical code></code>	(no default, initially unset) If the box is set to be <code>/tcb/breakable</code> ^{P. 353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/underlay unbroken=<graphical code></code>	(no default, initially unset) If the box is set to be <code>/tcb/breakable</code> ^{P. 353} but is not broken actually or if the box is set to be <code>/tcb/unbreakable</code> ^{P. 354} , then the <code><graphical code></code> is added to the box drawing process. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/no underlay unbroken</code>	(style, no default, initially set) Removes the unbroken underlay if set before.
<code>/tcb/underlay first=<graphical code></code>	(no default, initially unset) If the box is set to be <code>/tcb/breakable</code> ^{P. 353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process for the <i>first</i> part of the break sequence. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/no underlay first</code>	(style, no default, initially set) Removes the first underlay if set before.
<code>/tcb/underlay middle=<graphical code></code>	(no default, initially unset) If the box is set to be <code>/tcb/breakable</code> ^{P. 353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process for the <i>middle</i> parts (if any) of the break sequence. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/no underlay middle</code>	(style, no default, initially set) Removes the middle underlay if set before.
<code>/tcb/underlay last=<graphical code></code>	(no default, initially unset) If the box is set to be <code>/tcb/breakable</code> ^{P. 353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process for the <i>last</i> part of the break sequence. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/no underlay last</code>	(style, no default, initially set) Removes the last underlay if set before.
<code>/tcb/underlay boxed title=<graphical code></code>	(no default, initially unset) If the box has a <i>boxed title</i> , see Section 10.2 on page 147, then the <code><graphical code></code> is added to the box drawing process <i>before</i> the boxed title is drawn.
<code>/tcb/no underlay boxed title</code>	(style, no default, initially set) Removes the boxed title underlay if set before.
<code>/tcb/underlay unbroken and first=<graphical code></code>	(no default, initially unset) This is an abbreviation for setting <code>/tcb/underlay unbroken</code> and <code>/tcb/underlay first</code> together. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/underlay middle and last=<graphical code></code>	(no default, initially unset) This is an abbreviation for setting <code>/tcb/underlay middle</code> and <code>/tcb/underlay last</code> together. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/underlay unbroken and last=<graphical code></code>	(no default, initially unset) This is an abbreviation for setting <code>/tcb/underlay unbroken</code> and <code>/tcb/underlay last</code> together. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.
<code>/tcb/underlay first and middle=<graphical code></code>	(no default, initially unset) This is an abbreviation for setting <code>/tcb/underlay first</code> and <code>/tcb/underlay middle</code> together. <code>/tcb/underlay</code> ^{P. 187} overwrites this key.

10.9 Finish Option Keys

Finishes are quite similar to underlays described in Section 10.8 on page 187 and overlays described in Section 4.12 on page 69. Finishes are drawn *after* the text content is drawn; see Section 9.4 on page 134 for the general drawing scheme. Therefore, a finish will reduce the readability of the text content.

Finishes are intended for special effects like highlights or glosses or text over text.

- Finishes are only applicable for the skins `enhanced`^{→ P. 196}, `empty`^{→ P. 227}, `freelance`^{→ P. 240}, `bicolor`^{→ P. 209}, `beamer`^{→ P. 218}, and `widget`^{→ P. 223}.



If a finish is used with the `standard`^{→ P. 194} skin, it is silently ignored.

- Finishes are stackable, i. e. several different finishes can be used on the same `tcolorbox`.

/tcb/finish=*<graphical code>* (no default, initially unset)

Adds *<graphical code>* to the box drawing process. This *<graphical code>* is drawn *after* the text content.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
  finish={\begin{tcbclipframe}
    \path[bottom color=black,top color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
    \path[top color=white,bottom color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
  \end{tcbclipframe}},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
  finish={\node[draw,fill=white,fill opacity=0.85,inner sep=5mm,
    rounded corners] at (frame.center) {\Huge\bfseries Finish!};},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Finish!

<code>/tcb/no finish</code>	(style, no default, initially set)
Removes the finish if set before.	
<code>/tcb/finish broken=<graphical code></code>	(no default, initially unset)
If the box is set to be <code>/tcb/breakable</code> ^{P.353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/finish unbroken=<graphical code></code>	(no default, initially unset)
If the box is set to be <code>/tcb/breakable</code> ^{P.353} but is not broken actually or if the box is set to be <code>/tcb/unbreakable</code> ^{P.354} , then the <code><graphical code></code> is added to the box drawing process. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/no finish unbroken</code>	(style, no default, initially set)
Removes the unbroken finish if set before.	
<code>/tcb/finish first=<graphical code></code>	(no default, initially unset)
If the box is set to be <code>/tcb/breakable</code> ^{P.353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process for the <i>first</i> part of the break sequence. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/no finish first</code>	(style, no default, initially set)
Removes the first finish if set before.	
<code>/tcb/finish middle=<graphical code></code>	(no default, initially unset)
If the box is set to be <code>/tcb/breakable</code> ^{P.353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process for the <i>middle</i> parts (if any) of the break sequence. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/no finish middle</code>	(style, no default, initially set)
Removes the middle finish if set before.	
<code>/tcb/finish last=<graphical code></code>	(no default, initially unset)
If the box is set to be <code>/tcb/breakable</code> ^{P.353} and is broken actually, then the <code><graphical code></code> is added to the box drawing process for the <i>last</i> part of the break sequence. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/no finish last</code>	(style, no default, initially set)
Removes the last finish if set before.	
<code>/tcb/finish unbroken and first=<graphical code></code>	(no default, initially unset)
This is an abbreviation for setting <code>/tcb/finish unbroken</code> and <code>/tcb/finish first</code> together. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/finish middle and last=<graphical code></code>	(no default, initially unset)
This is an abbreviation for setting <code>/tcb/finish middle</code> and <code>/tcb/finish last</code> together. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/finish unbroken and last=<graphical code></code>	(no default, initially unset)
This is an abbreviation for setting <code>/tcb/finish unbroken</code> and <code>/tcb/finish last</code> together. <code>/tcb/finish</code> ^{P.189} overwrites this key.	
<code>/tcb/finish first and middle=<graphical code></code>	(no default, initially unset)
This is an abbreviation for setting <code>/tcb/finish first</code> and <code>/tcb/finish middle</code> together. <code>/tcb/finish</code> ^{P.189} overwrites this key.	

N 2014-09-19

10.10 Jigsaw Skin Variants

As described in Section 9.1 on page 126, a `tcolorbox` is drawn by up to four *engines*. Typically, the `frame` engine fills the complete box area with color and the other engines fill certain areas with other colors. Finally, only the area which you see as *frame* of the box will display the frame color. For most applications, this is a good approach.

For certain boxes, a more delicate procedure is needed. E.g., if the box should be translucent, an already painted area cannot be made unpainted. Therefore, more elaborate frame engines saw holes into the frame where the interior area and optionally the title area will be painted. The resulting skins are called *jigsaw* skins. For `standard`^{→ P. 194} and `enhanced`^{→ P. 196}, there are variants called `standard jigsaw`^{→ P. 195} and `enhanced jigsaw`^{→ P. 203}.

```
\newcommand{\ballexample}{\begin{tikzpicture}
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}

\tcbset{enhanced,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries }

\ballexample

\begin{tcolorbox}[title=A normal box]
  \lipsum[2]
\end{tcolorbox}

\ballexample

\begin{tcolorbox}[title=A translucent jigsaw box,
  enhanced jigsaw,opacityback=0.35]
  \lipsum[2]
\end{tcolorbox}
```

A normal box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

A translucent jigsaw box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\tcbset{enhanced,colback=red!10!white,coltitle=black,
frame style={left color=red!75!black,right color=red!10!yellow},
fonttitle=\bfseries,interior hidden,title hidden}

\begin{tcolorbox}[title=A normal box with hidden interior and title]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[enhanced jigsaw,
title=A jigsaw box with hidden interior and title]
This is a tcolorbox.
\end{tcolorbox}
```

A normal box with hidden interior and title

This is a tcolorbox.

A jigsaw box with hidden interior and title

This is a tcolorbox.

```
\newtcolorbox{mybox}{skin=enhancedmiddle jigsaw,leftrule=5mm,rightrule=5mm,
boxsep=0mm,top=0mm,bottom=0mm,
frame style={top color=blue,bottom color=red},interior hidden}

\begin{mybox}
\lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10.11 Draft Mode

To reduce the compilation time while drafting a document, the *draft mode* can be applied. Basically, it changes all skins to `spartan`^{P. 237} and sets the `/tcb/fit algorithm`^{P. 391} to `squeeze`. Especially, when fuzzy shadows are used, the speedup will be considerable high.

! It is strongly recommended that the draft mode is *not* used for the final document. Use `spartan`^{P. 237} directly, if you want to stay with it. The draft mode implementation may change in future.

! Normally, switching to the draft mode should not alter the geometry of your document. Since overlays are deactivated, any code placed there (e.g. counter changes) is not executed anymore! Also, `/tcb/remember as`^{P. 186} will not have any effect. You may exclude critical code with `\tcbinterruptdraftmode` / `\tcbcontinuedraftmode` from converting to draft mode.

`\tcbstartdraftmode`

Any following `tcolorbox` code is put into *draft mode*. All skin settings are overruled with `spartan`^{P. 237}. Overlays, watermarks, shadows, borderlines, and rounded corners are deactivated for all `tcolorbox` layers.

`\tcbstopdraftmode`

The *draft mode* is deactivated for the following code.

`\tcbinterruptdraftmode`

If the compilation is in *draft mode*, the *draft mode* is deactivated until a following `\tcbcontinuedraftmode` is detected.

If the compilation is not in *draft mode*, nothing happens and a following `\tcbcontinuedraftmode` will not start the *draft mode*.

! The pair `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` cannot be used nested.

`\tcbcontinuedraftmode`

Continues the *draft mode* which was suspended by a preceding `\tcbinterruptdraftmode`. Nothing happens, if there was no draft mode before `\tcbinterruptdraftmode`.

! Code, which is place between `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` is shielded from *draft mode*.

`/tcb/draftmode=true|false` (default true, initially false)

If set to `true`, the *draft mode* is started. If set to `false`, the *draft mode* is stopped.

```
\newtcolorbox{mybeamer}[2][]{beamer,colback=Salmon!50!white,
colframe=FireBrick!75!black,adjusted title={#2},#1}

\begin{mybeamer}{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}\par\medskip
\begin{mybeamer}[draftmode]{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}
```

Beamer box

This box looks like a box provided by the `beamer` class.

Beamer box

This box looks like a box provided by the `beamer` class.

10.12 Skin Family 'standard'

! Note that the option keys `/tcb/frame style`^{→ P. 140}, `/tcb/interior style`^{→ P. 141}, `/tcb/segmentation style`^{→ P. 143}, and `/tcb/title style`^{→ P. 143} are not applicable to the standard skin. Also, watermarks (see Subsection 10.3) are not usable with the standard skin.

/tcb/skin=standard (skin)

This is the standard skin from the core package. All drawing engines are set to type `standard`. The drawing is based on pgf commands and does not need the `tikz` package.

Environment and engines for the skin 'standard'

```
/tcb/graphical environment→ P. 126: pgfpicture  
/tcb/frame engine→ P. 127: standard  
/tcb/interior titled engine→ P. 127: standard  
/tcb/interior engine→ P. 128: standard  
/tcb/segmentation engine→ P. 128: standard  
/tcb/title engine→ P. 128: standard
```

/tcb/standard (style, no value)

This is an abbreviation for setting `skin=standard`.

```
\begin{tcbraster}[standard,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=standard jigsaw

(skin)

This is the standard jigsaw skin from the core package. It differs from the skin `standard`^{P. 194} by its frame engine, see Section 10.10 on page 191.

Environment and engines for the skin 'standard jigsaw'

```
/tcb/graphical environmentP. 126: pgfpicture
/tcb/frame engineP. 127: standardjigsaw
/tcb/interior titled engineP. 127: standard
/tcb/interior engineP. 128: standard
/tcb/segmentation engineP. 128: standard
/tcb/title engineP. 128: standard
```

/tcb/standard jigsaw

(style, no value)

This is an abbreviation for setting `skin=standard jigsaw`.

```
\begin{tcbraster}[standard jigsaw,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.13 Skin Family 'enhanced'

! If you like the standard appearance of a `tcolorbox` but you want to have some 'enhanced' features, the `enhanced` skin is what you are looking for.

`/tcb/skin=enhanced` (skin)

This skin translates the drawing commands of the core package into `tikz` path commands. Therefore, it allows all `tikz` high level options for these paths and has more flexibility compared to the `standard`^{P. 194} skin. You pay for this with some prolonged compilation time. The `tikz` path options can be given with the option keys `/tcb/frame style`^{P. 140}, `/tcb/interior style`^{P. 141}, `/tcb/segmentation style`^{P. 143}, and `/tcb/title style`^{P. 143}.

Environment and engines for the skin 'enhanced'

```
/tcb/graphical environmentP. 126: tikzpicture  
/tcb/frame engineP. 127: path  
/tcb/interior titled engineP. 127: path  
/tcb/interior engineP. 128: path  
/tcb/segmentation engineP. 128: path  
/tcb/title engineP. 128: path
```

`/tcb/enhanced` (style, no value)

This is an abbreviation for setting `skin=enhanced`.

```
\begin{tcbraster}[enhanced,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
% \usetikzlibrary{shadings}           % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,
frame style={upper left=blue,upper right=red,lower left=yellow,lower right=green},
interior style={white,opacity=0.5},
segmentation style={black,solid,opacity=0.2,line width=1pt}}


\begin{tcolorbox}[title=Nice box in rainbow colors]
With the 'enhanced' skin, it is quite easy to produce fancy looking effects.
\tcblower
Note that this is still a \texttt{\tcolorbox}.
\end{tcolorbox}
```

Nice box in rainbow colors

With the 'enhanced' skin, it is quite easy to produce fancy looking effects.

Note that this is still a `tcolorbox`.

```
% \usetikzlibrary{decorations.pathmorphing} % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,boxrule=1mm,
frame style={draw=FireBrick,fill=Salmon},drop fuzzy shadow,
interior style={draw=FireBrick,top color=Salmon!10,bottom color=Salmon!20},
segmentation style={draw=FireBrick,solid,decorate,
decoration={coil,aspect=0,segment length=10.1mm}}}

\begin{tcblisting}[title=A listing box with shadow and some specials]
Of course, skins can be used for listings also.
\begin{equation}
\int\limits_1^2 \frac{1}{x} dx = \ln(2).
\end{equation}
\end{tcblisting}
```

A listing box with shadow and some specials

Of course, skins can be used for listings also.

```
\begin{equation}
\int\limits_1^2 \frac{1}{x} dx = \ln(2).
\end{equation}
```

Of course, skins can be used for listings also.

$$\int_1^2 \frac{1}{x} dx = \ln(2). \quad (2)$$

/tcb/enhanced standard

(style, no value)

For unbreakable boxes, this is identical to using [/tcb/enhanced](#)^{→ P. 196}. But, for breakable boxes, the *break sequence* is identical to the [standard](#)^{→ P. 194} skin, see Section 17.7 from page 365.

/tcb/blank

(style, initially unset)

This style relies on the skin [enhanced](#)^{→ P. 196}. All drawing operations are hidden and all margins are set to 0pt. See [/tcb/blanker](#)^{→ P. 228} for switching off the drawing engines.

```
\begin{tcolorbox}[blank,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

\tcbline

Sometimes, a line is only a line. With `\tcblower→ P. 12` you separate the box content into two functional units. `\tcbline` draws only a line which looks like the segmentation line between upper and lower part. Furthermore, you can use `\tcbline` more than just once. `\tcbline` always uses the `path` drawing engine. Therefore, the `/tcb/segmentation style→ P. 143` can be applied.

```
\tcbset{enhanced,colframe=blue!50!black,colback=white}

\begin{tcolorbox}[colupper=red!50!black,collower=green!50!black]
\lipsum[1]
\tcbline
\lipsum[2]
\tcblower
\lipsum[3]
\tcbline
\lipsum[4]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

\tcbline*

Equivalent to `\tcbline`, but in a breakable box, `\tcbline*` is removed if at a page/box break. Also, it is removed at the end of a box.

/tcb/skin=enhancedfirst

(skin)

This is a flavor of `enhanced`^{→ P. 196} which is used as a *first* part in a break sequence for `enhanced`^{→ P. 196}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'enhancedfirst'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathfirst
/tcb/interior titled engine→ P. 127: pathfirst
/tcb/interior engine→ P. 128: pathfirst
/tcb/segmentation engine→ P. 128: path
/tcb/title engine→ P. 128: pathfirst
```

```
\begin{tcbraster}[skin=enhancedfirst,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedmiddle

(skin)

This is a flavor of `enhanced`^{→ P. 196} which is used as a *middle* part in a break sequence for `enhanced`^{→ P. 196}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'enhancedmiddle'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathmiddle
/tcb/interior titled engine→ P. 127: pathmiddle
/tcb/interior engine→ P. 128: pathmiddle
/tcb/segmentation engine→ P. 128: path
/tcb/title engine→ P. 128: pathmiddle
```

```
\begin{tcbraster}[skin=enhancedmiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedlast

(skin)

This is a flavor of `enhanced`^{→ P. 196} which is used as a *last* part in a break sequence for `enhanced`^{→ P. 196}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'enhancedlast'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathlast
/tcb/interior titled engine→ P. 127: pathlast
/tcb/interior engine→ P. 128: pathlast
/tcb/segmentation engine→ P. 128: path
/tcb/title engine→ P. 128: pathlast
```

```
\begin{tcbraster}[skin=enhancedlast,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhanced jigsaw

(skin)

This is the jigsaw variant of skin enhanced^{→ P. 196}. It differs by its frame engine, see Section 10.10 on page 191.

Environment and engines for the skin 'enhanced jigsaw'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathjigsaw
/tcb/interior titled engine→ P. 127: path
/tcb/interior engine→ P. 128: path
/tcb/segmentation engine→ P. 128: path
/tcb/title engine→ P. 128: path
```

/tcb/enhanced jigsaw

(style, no value)

This is an abbreviation for setting skin=enhanced jigsaw.

```
\begin{tcbraster}[enhanced jigsaw,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\textbf{\tcblower}
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\textbf{\tcblower}
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedfirst jigsaw

(skin)

This is the jigsaw variant of skin enhancedfirst^{→ P. 200}. It differs by its frame engine, see Section 10.10 on page 191.

Environment and engines for the skin 'enhancedfirst jigsaw'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: pathfirstjigsaw  
/tcb/interior titled engine→ P. 127: pathfirst  
/tcb/interior engine→ P. 128: pathfirst  
/tcb/segmentation engine→ P. 128: path  
/tcb/title engine→ P. 128: pathfirst
```

```
\begin{tcbraster}[skin=enhancedfirst jigsaw,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,  
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedmiddle jigsaw

(skin)

This is the jigsaw variant of skin `enhancedmiddle`^{→ P. 201}. It differs by its frame engine, see Section 10.10 on page 191.

Environment and engines for the skin 'enhancedmiddle jigsaw'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathmiddlejigsaw
/tcb/interior titled engine→ P. 127: pathmiddle
/tcb/interior engine→ P. 128: pathmiddle
/tcb/segmentation engine→ P. 128: path
/tcb/title engine→ P. 128: pathmiddle
```

```
\begin{tcbraster}[skin=enhancedmiddle jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/marker

(style, no value)

This styles relies on the skin `enhancedmiddle jigsaw`. It is intended to be used as an optical marker like a highlighter pen.

```
\begin{tcolorbox}[marker]
\lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This examples demonstrates the creation of several *text marker* environments based on [enhancedmiddle](#) → P. 201.

```
\tcbset{textmarker/.style={%
    skin=enhancedmiddle jigsaw,breakable,parbox=false,
    boxrule=0mm,leftrule=5mm,rightrule=5mm,boxsep=0mm,arc=0mm,outer arc=0mm,
    left=3mm,right=3mm,top=1mm,bottom=1mm,toptitle=1mm,bottomtitle=1mm,oversize}%

\newtcolorbox[yellow]{textmarker,colback=yellow!5!white,colframe=yellow}
\newtcolorbox[orange]{textmarker,colback=DarkOrange!5!white,
                     colframe=DarkOrange!75!yellow}
\newtcolorbox[red]{textmarker,colback=red!5!white,colframe=red}
\newtcolorbox[blue]{textmarker,colback=DeepSkyBlue!5!white,colframe=DeepSkyBlue}
\newtcolorbox[green]{textmarker,colback=Chartreuse!5!white,colframe=Chartreuse}
\newtcolorbox[rainbow]{textmarker,interior hidden,
                      frame style={top color=blue,bottom color=red,middle color=green}%

\begin{yellow}
    \lipsum[1-3]
\end{yellow}

\begin{orange}
    \lipsum[4]
\end{orange}

\begin{red}
    \lipsum[5]
\end{red}

\begin{green}
    \lipsum[6]
\end{green}

\begin{blue}
    \lipsum[7]
\end{blue}

\begin{rainbow}
    \lipsum[8]
\end{rainbow}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique,

libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipisciing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipisciing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipisciing quis, ultrices a, dui.

/tcb/skin=enhancedlast jigsaw (skin)

This is the jigsaw variant of skin enhancedlast^{→ P. 202}. It differs by its frame engine, see Section 10.10 on page 191.

Environment and engines for the skin 'enhancedlast'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: pathlastjigsaw  
/tcb/interior titled engine→ P. 127: pathlast  
/tcb/interior engine→ P. 128: pathlast  
/tcb/segmentation engine→ P. 128: path  
/tcb/title engine→ P. 128: pathlast
```

```
\begin{tcbraster}[skin=enhancedlast jigsaw,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,  
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.14 Skin Family 'bicolor'

/tcb/skin=bicolor

(skin)

This skin is quite similar to the standard^{→ P. 194} and enhanced^{→ P. 196} skin. But instead of a segmentation line, the optional lower part of the box is filled with a different color or drawn with a different style.

Environment and engines for the skin 'bicolor'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: path  
/tcb/interior titled engine→ P. 127: special  
/tcb/interior engine→ P. 128: special  
/tcb/segmentation engine→ P. 128: special  
/tcb/title engine→ P. 128: path
```

- The most basic usage of this skin is to set the background color of the lower part by /tcb/colbacklower^{→ P. 210} and all other options like for the standard^{→ P. 194} skin.

```
\begin{tcolorbox}[skin=bicolor,title=The title,  
    colframe=FireBrick!75!black,colback=Salmon!50!white,colbacklower=Salmon]  
The upper part.  
\tcblower  
The lower part.  
\end{tcolorbox}
```

The title

The upper part.

The lower part.

- The more advanced usage of this skin is to apply the /tcb/frame style^{→ P. 140} and the /tcb/interior style^{→ P. 141} like for the enhanced^{→ P. 196} skin. Also, the /tcb/segmentation style^{→ P. 143} can be used, but it is applied to the whole lower part.

```
\begin{tcolorbox}[skin=bicolor,title=The title,  
    frame style={top color=FireBrick,  
        bottom color=FireBrick!15!white,draw=black},  
    interior style={left color=Salmon,right color=Salmon!50!white},  
    segmentation style={right color=Salmon,left color=Salmon!50!white}]  
The upper part.  
\tcblower  
The lower part.  
\end{tcolorbox}
```

The title

The upper part.


The lower part.

/tcb/bicolor

(style, no value)

This is an abbreviation for setting skin=bicolor.

```
\begin{tcbraster}[bicolor,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
  colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\end{tcbraster}
```



`/tcb/colbacklower=(color)` (no default, initially `black!15!white`)

Sets the background `(color)` of the lower part. It depends on the skin, if this value is used.

```
\tcbset{gitexample/.style={listing and comment,comment={#1},
skin=bicolor,boxrule=1mm,fonttitle=\bfseries,coltitle=black,
frame style={draw=black,left color=Gold,right color=Goldenrod!50!Gold},
colback=black,colbacklower=Goldenrod!75!Gold,
colupper=white,collower=black,
listing options={language={bash},aboveskip=0pt,belowskip=0pt,nolol,
basicstyle=\ttfamily\bfseries,extendedchars=true}}}

\begin{tcblisting}{title={Snapshot of the staging area},
gitexample={The option '-a' automatically stages all tracked and modified
files before the commit.\par
This can be combined with the message option '-m'
as seen in the third line.}}
git commit
git commit -a
git commit -am 'changes to my example'
\end{tcblisting}
```

Snapshot of the staging area

```
git commit
git commit -a
git commit -am 'changes to my example'
```

The option '-a' automatically stages all tracked and modified files before the commit.
This can be combined with the message option '-m' as seen in the third line.

/tcb/skin=bicolorfirst

(skin)

This is a flavor of `bicolor`^{→ P. 209} which is used as a *first* part in a break sequence for `bicolor`^{→ P. 209}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'bicolorfirst'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: pathfirst  
/tcb/interior titled engine→ P. 127: special  
/tcb/interior engine→ P. 128: special  
/tcb/segmentation engine→ P. 128: special  
/tcb/title engine→ P. 128: pathfirst
```

```
\begin{tcbraster}[skin=bicolorfirst,raster equal height,raster columns=4,  
 colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,  
 colbacktitle=LimeGreen!75!DarkGreen,  
 left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
 This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
 This is my content.  
\tcblower  
 More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
 This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
 This is my content.  
\tcblower  
 More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=bicolormiddle

(skin)

This is a flavor of `bicolor`^{→ P. 209} which is used as a *middle* part in a break sequence for `bicolor`^{→ P. 209}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'bicolormiddle'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathmiddle
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: pathmiddle
```

```
\begin{tcbraster}[skin=bicolormiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=bicolorlast

(skin)

This is a flavor of `bicolor`^{→ P. 209} which is used as a *last* part in a break sequence for `bicolor`^{→ P. 209}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'bicolorlast'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathlast
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: pathlast
```

```
\begin{tcbraster}[skin=bicolorlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.15 Skin Family 'tile'

N 2016-02-25

/tcb/skin=tile

(skin)

This skin is a variant of skin `bicolor`^{→ P. 209}. Especially, the optional lower part of the box is colored by `/tcb/colbacklower`^{→ P. 210}. The main difference to `bicolor`^{→ P. 209} is that `tile` has no frame.

Environment and engines for the skin 'tile'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: path
```

N 2016-02-25

/tcb/tile

(style, no value)

This is an abbreviation for setting `skin=tile`.



It also changes the geometry and some style options.

```
\begin{tcbraster}[tile,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
  colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
\textcolor{red}{\tcblower}
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\textcolor{red}{\tcblower}
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

This is a flavor of `tile`^{→ P. 214} which is used as a *first* part in a break sequence for `tile`^{→ P. 214}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'tilefirst'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: pathfirst
```

```
\begin{tcbraster}[skin=tilefirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

This is a flavor of `tile`^{→ P. 214} which is used as a *middle* part in a break sequence for `tile`^{→ P. 214}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'tilemiddle'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: pathmiddle
```

```
\begin{tcbraster}[skin=tilemiddle,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
  colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=tilelast

(skin)

This is a flavor of `tile`^{→ P. 214} which is used as a *last* part in a break sequence for `tile`^{→ P. 214}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'tilelast'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: pathlast
```

```
\begin{tcbraster}[skin=tilelast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\textcolor{red}{\tcblower}
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.16 Skin Family 'beamer'

/tcb/skin=beamer (skin)

This skin resembles boxes known from the `beamer` class and therefore is called 'beamer'. It uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

The appearance of the skin can be controlled by `/tcb/frame style`^{→ P. 140} and `/tcb/interior style`^{→ P. 141}, if needed. Here, the *segmentation* cannot be controlled by a style.

Environment and engines for the skin 'beamer'

<code>/tcb/graphical environment</code> ^{→ P. 126} :	<code>tikzpicture</code>
<code>/tcb/frame engine</code> ^{→ P. 127} :	<code>path</code>
<code>/tcb/interior titled engine</code> ^{→ P. 127} :	<code>special</code>
<code>/tcb/interior engine</code> ^{→ P. 128} :	<code>special</code>
<code>/tcb/segmentation engine</code> ^{→ P. 128} :	<code>special</code>
<code>/tcb/title engine</code> ^{→ P. 128} :	<code>path</code>

/tcb/beamer (style, no value)

This is an abbreviation for setting `skin=beamer`.

! It also changes the geometry and some style options.

```
\begin{tcbraster}[beamer,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
\textcolor{red}{\tcblower}
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\textcolor{red}{\tcblower}
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
\begin{tcolorbox}[beamer,colback=Salmon!50!white,colframe=FireBrick!75!black,
adjusted title=A colored box with the 'beamer' skin]
This box looks like a box provided by the \texttt{beamer} class.
\end{tcolorbox}
```

A colored box with the 'beamer' skin

This box looks like a box provided by the `beamer` class.

```
\begin{tcolorbox}[beamer,colframe=blue,colback=black,
watermark graphics=lichtspiel.jpg,
coltext=white,watermark opacity=0.75,watermark stretch=1.0,
title=Beamer Box with background picture]
\lipsum[1]
\end{tcolorbox}
```

Beamer Box with background picture

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\newtcolorbox{myblock}[2][]{%
beamer,breakable,colback=LightBlue,colframe=DarkBlue,#1,title=#2}%

\begin{myblock}{Beamerish \texttt{block}: \texttt{myblock}}
\lipsum[1]
\end{myblock}
```

Beamerish block: myblock

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/skin=beamerfirst

(skin)

This is a flavor of `beamer`^{→ P. 218} which is used as a *first* part in a break sequence for `beamer`^{→ P. 218}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'beamerfirst'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: pathfirst  
/tcb/interior titled engine→ P. 127: special  
/tcb/interior engine→ P. 128: special  
/tcb/segmentation engine→ P. 128: special  
/tcb/title engine→ P. 128: pathfirst
```

```
\begin{tcbraster}[beamer,skin=beamerfirst,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

/tcb/skin=beamermiddle

(skin)

This is a flavor of `beamer`^{→ P. 218} which is used as a *middle* part in a break sequence for `beamer`^{→ P. 218}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'beamermiddle'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathmiddle
/tcb/interior titled engine→ P. 127: special
/tcb/interior engine→ P. 128: special
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: pathmiddle
```

```
\begin{tcbraster}[beamer,skin=beamermiddle,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

/tcb/skin=beamerlast

(skin)

This is a flavor of `beamer`^{→ P. 218} which is used as a *last* part in a break sequence for `beamer`^{→ P. 218}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'beamerlast'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: pathlast  
/tcb/interior titled engine→ P. 127: special  
/tcb/interior engine→ P. 128: special  
/tcb/segmentation engine→ P. 128: special  
/tcb/title engine→ P. 128: pathlast
```

```
\begin{tcbraster}[beamer,skin=beamerlast,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

10.17 Skin Family 'widget'

/tcb/skin=widget

(skin)

This skin uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

The appearance of the skin can be controlled by `/tcb/frame style`^{→ P. 140}, `/tcb/interior style`^{→ P. 141}, and `/tcb/segmentation style`^{→ P. 143}, if needed.

Environment and engines for the skin 'widget'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: path  
/tcb/interior titled engine→ P. 127: path  
/tcb/interior engine→ P. 128: path  
/tcb/segmentation engine→ P. 128: special  
/tcb/title engine→ P. 128: special
```

/tcb/widget

(style, no value)

This is an abbreviation for setting `skin=widget`.

! It also changes the geometry and some style options.

```
\begin{tcbraster}[widget,raster equal height,raster columns=4,  
 colback=LightGreen,colframe=DarkGreen,  
 left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
 This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
 This is my content.  
\tcblower  
 More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
 This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
 This is my content.  
\tcblower  
 More content.  
\end{tcolorbox}  
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
\begin{tcolorbox}[widget,colback=Salmon!50!white,colframe=FireBrick!75!black,
adjusted title=A colored box with the 'widget' skin]
This is my content.
\end{tcolorbox}
```

A colored box with the 'widget' skin

This is my content.

/tcb/skin=widgetfirst

(skin)

This is a flavor of `widget→ P. 223` which is used as a *first* part in a break sequence for `widget→ P. 223`. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'widgetfirst'

/tcb/graphical environment ^{→ P. 126} :	tikzpicture
/tcb/frame engine ^{→ P. 127} :	pathfirst
/tcb/interior titled engine ^{→ P. 127} :	pathfirst
/tcb/interior engine ^{→ P. 128} :	pathfirst
/tcb/segmentation engine ^{→ P. 128} :	special
/tcb/title engine ^{→ P. 128} :	special

```
\begin{tcbraster}[widget,skin=widgetfirst,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=widgetmiddle

(skin)

This is a flavor of `widget`^{→ P. 223} which is used as a *middle* part in a break sequence for `widget`^{→ P. 223}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'widgetmiddle'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathmiddle
/tcb/interior titled engine→ P. 127: pathmiddle
/tcb/interior engine→ P. 128: pathmiddle
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: special
```

```
\begin{tcbraster}[widget,skin=widgetmiddle,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=widgetlast

(skin)

This is a flavor of `widget`^{→ P. 223} which is used as a *last* part in a break sequence for `widget`^{→ P. 223}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'widgetlast'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: pathlast
/tcb/interior titled engine→ P. 127: pathlast
/tcb/interior engine→ P. 128: pathlast
/tcb/segmentation engine→ P. 128: special
/tcb/title engine→ P. 128: special
```

```
\begin{tcbraster}[widget,skin=widgetlast,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.18 Skin Family 'empty'

/tcb/skin=empty (skin)

This skin sets all engines to `empty`, i.e. nothing is drawn at all. Therefore, this skin is a good starting point to create a complete new style by yourself.

Environment and engines for the skin 'empty'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: empty
/tcb/interior engine→ P. 128: empty
/tcb/segmentation engine→ P. 128: empty
/tcb/title engine→ P. 128: empty
```

/tcb/empty (style, no value)

This is an abbreviation for setting `skin=empty`.

```
\begin{tcbraster}[empty,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/blanker

(style, initially unset)

This style relies on the skin `empty`^{P. 227}. All engines are set to empty and all margins are set to `Opt`. In contrast to `/tcb/blank`^{P. 198}, the graphical paths are not constructed with exception of the geometry nodes.

```
\begin{tcolorbox}[blanker,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \tcbselibrary{fitting}
\newtcbboxfit{\mybox}{1}{blanker,width=4cm,height=7cm,top=4pt,
watermark text=#1}

\begin{tabular}{|c|c|c|}\hline
A & B & C\\\hline
\mybox{A}{\lipsum[1]} & \mybox{B}{\lipsum[2]} & \mybox{C}{\lipsum[3]}\\\hline
\end{tabular}
```

A	B	C
<p> Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.</p>	<p> Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.</p>	<p> Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.</p>

/tcb/blankest

(style, initially unset)

This style extends /tcb/blanker^{→ P. 228}. All engines are set to empty and all margins are set to Opt. In contrast to /tcb/blanker^{→ P. 228}, also title, shadow, underlay, overlay, finish and borderline are removed.

```
% \tcbuselibrary[raster]
\begin{tcbraster}[raster columns=3,raster equal height,
title=Box \thetcbrasternum,
enhanced,size=small,colframe=red!50!black,colback=red!10!white,
coltitle=yellow!85!black,
drop fuzzy shadow,watermark text={Box \thetcbrasternum},
borderline={.25mm}{-0.5mm}{green!40!black},
finish=\begin{tcbclipframe}\draw[blue,opacity=0.1,line width=1cm]
(frame.south west) -- (frame.north east);\end{tcbclipframe},
]
\begin{tcolorbox}\lipsum[4]\end{tcolorbox}
\begin{tcolorbox}[blanker]\lipsum[4]\end{tcolorbox}
\begin{tcolorbox}[blankest]\lipsum[4]\end{tcolorbox}
\end{tcbraster}
```

Box 1

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Box 2

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

/tcb/skin=emptyfirst

(skin)

This is a flavor of `empty`^{→ P. 227} which is used as a *first* part in a break sequence for `empty`^{→ P. 227}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'emptyfirst'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: empty
/tcb/interior engine→ P. 128: empty
/tcb/segmentation engine→ P. 128: empty
/tcb/title engine→ P. 128: empty
```

```
\begin{tcbraster}[empty,skin=emptyfirst,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=emptymiddle

(skin)

This is a flavor of `empty`^{→ P. 227} which is used as a *middle* part in a break sequence for `empty`^{→ P. 227}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'emptymiddle'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: empty
/tcb/interior engine→ P. 128: empty
/tcb/segmentation engine→ P. 128: empty
/tcb/title engine→ P. 128: empty
```

```
\begin{tcbraster}[empty,skin=emptymiddle,raster equal height,raster columns=4,
 coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
 left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=emptylast

(skin)

This is a flavor of `empty`^{→ P. 227} which is used as a *last* part in a break sequence for `empty`^{→ P. 227}. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'emptylast'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: empty
/tcb/interior titled engine→ P. 127: empty
/tcb/interior engine→ P. 128: empty
/tcb/segmentation engine→ P. 128: empty
/tcb/title engine→ P. 128: empty
```

```
\begin{tcbraster}[empty,skin=emptylast,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

This example demonstrates a breakable customized box. Here, we define an environment `freebox`. The first application of `freebox` produces an unbroken `tcolorbox`. The box is drawn by the code given by `/tcb/frame code`^{→ P. 130} and `/tcb/interior code`^{→ P. 131}. The second application of `freebox` is broken into several parts which are drawn by the codes given by `/tcb/skin first is subskin of`^{→ P. 133}, `/tcb/skin middle is subskin of`^{→ P. 133}, and `/tcb/skin last is subskin of`^{→ P. 133}.

```
% Preamble:
%\usepackage{tikz,lipsum}
%\tcbuselibrary{skins,breakable}
\tikzset{coltria/.style={fill=red!15!white}}


\newtcolorbox{freebox}[1][][empty,breakable,leftrule=5mm,left=2mm,
frame style={fill,top color=red!75!black,bottom color=red!75!black,middle color=red},
colback=yellow!50!white,
watermark color=red!50!yellow!75!white,
watermark text on=unbroken is unbroken box,
watermark text on=first is first part,
watermark text on=middle is middle part,
watermark text on=last is last part,
% code for unbroken boxes:
frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
--([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
--([yshift=5mm]frame.south east)--([xshift=-5mm]frame.south east)--cycle; },
interior code={\path[tcb fill interior] (interior.south west)--(interior.north west)
--([xshift=-4.8mm]interior.north east)--([yshift=-4.8mm]interior.north east)
--([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
--cycle; },
% code for the first part of a break sequence:
skin first is subskin of={emptyfirst}{%
frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
--([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
--(frame.south east)--cycle;
\path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
-- +(60:2mm)-- cycle; },
interior code={\path[tcb fill interior] (interior.south west|-frame.south)
--(interior.north west)--([xshift=-4.8mm]interior.north east)
--([yshift=-4.8mm]interior.north east)--(interior.south east|-frame.south)
--cycle; },
},%
% code for the middle part of a break sequence:
skin middle is subskin of={emptymiddle}{%
frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
--(frame.north east)--(frame.south east)--cycle;
\path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
-- +(300:2mm) -- cycle;
\path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
-- +(60:2mm) -- cycle;
},
interior code={\path[tcb fill interior] (interior.south west|-frame.south)
--(interior.north west|-frame.north)--(interior.north east|-frame.north)
--(interior.south east|-frame.south)--cycle; },
},
% code for the last part of a break sequence:
skin last is subskin of={emptylast}{%
frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
--(frame.north east)--([yshift=5mm]frame.south east)
--([xshift=-5mm]frame.south east)--cycle;
\path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
-- +(300:2mm) -- cycle;
},
interior code={\path[tcb fill interior] (interior.south west)
```

```

--(interior.north west|-frame.north)--(interior.north east|-frame.north)
--([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
--cycle; },
},
#1}

\begin{freebox}
\lipsum[1]
\end{freebox}

\begin{freebox}
\lipsum[1-12]
\end{freebox}

```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim.

Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacinia tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacinia commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacinia. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacinia vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacinia.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultricies a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacinia. Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et,

lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdierunt lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascentur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdierunt justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdierunt. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

10.19 Skin 'spartan'

/tcb/skin=spartan

(skin)

This skin is quite ... spartan. It supports no rounded corners, no overlays, no shadows, no borderlines, and no finishes. The only exception are underlays. One cannot do very fancy things with this skin, but it compiles very fast. Therefore, the `spartan` skin is used for the draft mode, see Section 10.11 on page 193. Nevertheless, it can be used as a normal skin.

Environment and engines for the skin 'spartan'

```
/tcb/graphical environment→ P. 126: tikzpicture
/tcb/frame engine→ P. 127: spartan
/tcb/interior titled engine→ P. 127: spartan
/tcb/interior engine→ P. 128: spartan
/tcb/segmentation engine→ P. 128: spartan
/tcb/title engine→ P. 128: spartan
```

/tcb/spartan

(style, no value)

This is an abbreviation for setting `skin=spartan`.

```
\begin{tcbraster}[spartan,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
\textcolor{red}{\tcblower}
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\textcolor{red}{\tcblower}
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

10.20 Skin 'draft'

/tcb/skin=draft

(skin)

This skin is intended to be used while drafting new geometric settings for a **tcolorbox**.

Environment and engines for the skin 'draft'

```
/tcb/graphical environment→ P. 126: tikzpicture  
/tcb/frame engine→ P. 127: special  
/tcb/interior titled engine→ P. 127: special  
/tcb/interior engine→ P. 128: special  
/tcb/segmentation engine→ P. 128: path  
/tcb/title engine→ P. 128: path
```

/tcb/draft

(style, no value)

This is an abbreviation for setting **skin=draft**.

```
\begin{tcbraster}[draft,raster equal height,raster columns=4,  
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,  
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]  
\begin{tcolorbox}  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\end{tcolorbox}  
\begin{tcolorbox}[adjusted title=My title]  
This is my content.  
\tcblower  
More content.  
\end{tcolorbox}  
\end{tcbraster}
```

frame: w=101.71864pt, h=56frh1006pt=101.71864pt, h=56frh1006pt=101.71864pt, h=56.11296pt
upper: w=87.49236pt, h=7.95pt
upperF: w=87.49236pt, h=7.95pt
lower: w=87.49236pt, h=22.55310pt
lowerF: w=87.49236pt, h=22.55310pt
interior: w=98.8734pt, h=53.2667pt
interiorF: w=98.8734pt, h=53.2667pt
frameF: w=87.49236pt, h=9.2425pt
frameL: w=87.49236pt, h=9.2425pt
frameR: w=87.49236pt, h=9.2425pt
frameB: w=87.49236pt, h=6.798pt

```
\vspace*{3mm}
\begin{tcolorbox}[draft,title=A colored box with the 'draft' skin]
\lipsum[1-3]
\tcblower
\lipsum[4-6]
\end{tcolorbox}
```

frame: w=423.94617pt, h=506.20157pt

A colored box with the 'draft' skin title: w=392.64822pt, h=6.2pt

Lo<rem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquip**upper w=392.64822pt, h=249.95pt**tus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in **lower w=392.64822pt, h=205.95pt**sagittis du, et vehicula libero dui cursus du. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur. Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas du, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

interior: w=421.10092pt, h=490.04318pt

10.21 Skin Family 'freelance'

! This skin family 'freelance' is deprecated with `tcolorbox` 3.00. It is not longer needed, because `/tcb/frame code`^{→ P. 130}, `/tcb/interior code`^{→ P. 131}, `/tcb/interior titled code`^{→ P. 130}, and `/tcb/title code`^{→ P. 132} can be applied to every skin now. In this sense, everything has become *freelance* now.

For users of `/tcb/freelance`: Old code should continue to work. There may be exceptions for breakable freelance boxes under certain circumstances. For new code, use `/tcb/empty`^{→ P. 227} or `/tcb/enhanced`^{→ P. 196} where you would have used `/tcb/freelance` before.

`/tcb/skin=freelance` (skin)

This skin gives full freedom for the appearance of the `tcolorbox`. All drawing engines are set to type `freelance`; they use the `tikz` package and compute the `/tcb/geometry nodes`^{→ P. 129}.

Environment and engines for the skin 'freelance'

<code>/tcb/graphical environment</code> ^{→ P. 126} :	<code>tikzpicture</code>
<code>/tcb/frame engine</code> ^{→ P. 127} :	<code>freelance</code>
<code>/tcb/interior titled engine</code> ^{→ P. 127} :	<code>freelance</code>
<code>/tcb/interior engine</code> ^{→ P. 128} :	<code>freelance</code>
<code>/tcb/segmentation engine</code> ^{→ P. 128} :	<code>freelance</code>
<code>/tcb/title engine</code> ^{→ P. 128} :	<code>freelance</code>

`/tcb/freelance` (style, no value)

This is an abbreviation for setting `skin=freelance`.

`/tcb/skin=freelancefirst` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 17.7 on page 365.

`/tcb/skin=freelancemiddle` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 17.7 on page 365.

`/tcb/skin=freelancelast` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 17.7 on page 365.

`/tcb/extend freelance=⟨options⟩` (no default, initially empty)

The `⟨options⟩` are added to the skin definition of `freelance`.

`/tcb/extend freelancefirst=⟨options⟩` (no default, initially empty)

The `⟨options⟩` are added to the skin definition of `freelancefirst` which is used as first part of the break sequence of `freelance`. See `/tcb/skin first is subskin of`^{→ P. 133} for a substitute of this key.

`/tcb/extend freelancemiddle=⟨options⟩` (no default, initially empty)

The `⟨options⟩` are added to the skin definition of `freelancemiddle` which is used as middle part of the break sequence of `freelance`. See `/tcb/skin middle is subskin of`^{→ P. 133} for a substitute of this key.

`/tcb/extend freelancelast=⟨options⟩` (no default, initially empty)

The `⟨options⟩` are added to the skin definition of `freelancelast` which is used as last part of the break sequence of `freelance`. See `/tcb/skin last is subskin of`^{→ P. 133} for a substitute of this key.

11 Inclusion of Boxed Image Files

The `\tcbuselibrary{skins}` library adds some commands to conveniently include boxed image files. For the following macros and options, the `\tcbuselibrary{skins}` library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 10 on page 140 for the documentation of all other options of the `\tcbuselibrary{skins}` library.

11.1 Macros

N 2014-11-14
U 2016-07-13

`\tcbincludegraphics[<options>]{<file name>}`

In principle, this macro includes an image file denoted by `<file name>` using the standard `\includegraphics` and puts it into a `tcolorbox`^{P. 12}. The `<options>` are `tcolorbox` keys to set up the colored box. Use `/tcb/graphic options`^{P. 244} to specify options for the underlying `\includegraphics`. Some `tcolorbox` option keys are automatically set, namely `/tcb/enhanced`^{P. 196} and options to center the image inside the box.

The sizing of the included image is done depending on the following:


- If a `/tcb/width`^{P. 34} is specified, but no fixed `/tcb/height`^{P. 52}, the image is sized to fill the inner width of the box. The height of the box adapts to the image.
- If a fixed `/tcb/height`^{P. 52} is specified, the image is sized to fill the fixed inner area of the box.
- If the `/tcb/capture`^{P. 90} mode `/tcb/hbox`^{P. 90} is specified, the image is sized according to given `\includegraphics` options only. The box adapts to the image.

```
% \tcbuselibrary[raster]
\begin{tcbraster}[raster columns=3,raster force size=false,size=fbox,
    colframe=red!50!black,colback=red!20!black,
    fonttitle=\bfseries,center title,drop fuzzy shadow]
\tcbincludegraphics[title=Normal]{goldshade.png}
\tcbincludegraphics[title=Fixed height,height=3cm]{goldshade.png}
\tcbincludegraphics[title=hbox mode,hbox,graphics options={width=3cm}]
    {goldshade.png}
\end{tcbraster}
```



The auxiliary macro `\imagename` may be used inside `\tcbincludegraphics`^{P. 241} to display the name of the file. `\imagename` is already partially detokenized and is allowed to contain special characters like the underscore. Note that an appropriate font is required to display such characters.

```
% \tcbselibrary{raster}
\begin{tcbraster}[size=fbox,
  colframe=red!50!black,colback=red!20!black,
  fonttitle=\bfseries\ttfamily,center title,drop fuzzy shadow]
\tcbincludegraphics[title=\imagename]{goldshade.png}
\tcbincludegraphics[finish={
  \node[fill=white,fill opacity=0.5,text opacity=1]
  at (frame.center) {\bfseries\ttfamily\imagename};}]{blueshade.png}
\end{tcbraster}
```




\tcbincludepdf[*options*]{*file name*}

This is a generalized version of `\tcbincludegraphics`^{→ P. 241} which allows to include a complete PDF file denoted by *file name*. Every page is boxed into an own `tcolorbox`^{→ P. 12} customized by the given *options*. It is reasonable to put such a series of boxes inside a `tcbraster`^{→ P. 268} for alignment.


Use `/tcb/graphics pages`^{→ P. 244} to use a selection of pages instead of using the whole file. The auxiliary macro `\imagepage` may be used inside `\tcbincludepdf` to display the current page number.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,colframe=blue,colback=white,
colbacktitle=blue!50!white,fonttitle=\small\bfseries\ttfamily,
left=0pt,right=0pt,top=0pt,bottom=0pt,boxsep=0pt,boxrule=0.6pt,
toptitle=1mm,bottomtitle=1mm,drop lifted shadow,center title,
graphics pages={1,...,6},title={\imagine{image}{\imagepage}}]
\tcbincludepdf{tcolorbox-example.pdf}
\end{tcbraster}
```


tcolorbox-example.pdf [1]



tcolorbox-example.pdf [2]



tcolorbox-example.pdf [3]



11.2 Option Keys

N 2014-11-14

/tcb/*graphics options*=⟨options⟩

(no default, initially empty)

Used for `\tcbincludegraphics`^{P. 241} and `\tcbincludepdf`^{P. 243} to specify `\includegraphics ⟨options⟩`.

```
% \tcbuselibrary{raster}
\begin{tcbbraster}[raster columns=3,size=fbox,raster equal height,
  colframe=red!50!black,colback=red!20!black,drop fuzzy shadow]
\tcbincludegraphics{goldshade.png}
\tcbincludegraphics[graphics options={angle=20}]{goldshade.png}
\tcbincludegraphics[graphics options={viewport=0cm 0cm 8cm 4cm,clip}]
{goldshade.png}
\end{tcbbraster}
```



N 2014-11-14

/tcb/*graphics directory*=⟨directory⟩

(no default, initially empty)

Used for `\tcbincludegraphics`^{P. 241} and `\tcbincludepdf`^{P. 243} to specify a file system ⟨directory⟩ where the image files are located.

```
\tcbset{
  graphics directory={.},
  graphics directory={examples},
  graphics directory={../../pictures},
}
```



The `\graphicspath` macro from the `graphics` package is superior to this option.
`\tcbgraphics directory` may be used especially for `\tcbincludepdf`^{P. 243}.

N 2014-11-14

/tcb/*graphics pages*=⟨selection⟩

(no default, initially 1, ..., `\pdfpages`)

Used for `\tcbincludepdf`^{P. 243} to specify a ⟨selection⟩ of pages to be included. The largest page number is accessible by `\pdfpages`. The ⟨selection⟩ has to be given using the `\foreach` syntax of TikZ.

```
\tcbset{
  graphics pages={1,3,7},
  graphics pages={1,...,10},
  graphics pages={1,3,...,18},
  graphics pages={100,...,\pdfpages},
}
```

12 TikZ Image and Picture Fill Extensions; Auxiliary Macros

The `\tcbuselibrary{skins}` library adds some image and picture fill options to the vast option set of TikZ [20]. These options can be used in any `tikzpicture`. For the following options, the `\tcbuselibrary{skins}` library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```


See Section 10 on page 140 for the documentation of all other options of the `\tcbuselibrary{skins}` library.

12.1 Fill Plain

`/tikz/fill plain image=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is put in the center of the path, but it is not resized to fit into the path area.


```
\begin{tikzpicture}
\path[draw,fill plain image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill plain image*=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is put in the center of the path, but it is not resized to fit into the path area. The `<graphics options>` are given to the underlying `\includegraphics` command.


```
\begin{tikzpicture}
\path[draw,fill plain ]
  {image*={width=2.5cm}{goldshade.png}}
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill plain picture=<graphical code>` (no default, initially unset)

Fills the current path with the given `<graphical code>`. The result is put in the center of the path, but it is not resized to fit into the path area. Note that this is almost identical to the standard `path picture` option.

```
\begin{tikzpicture}
\path[draw,fill plain picture=%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




12.2 Fill Stretch

`/tikz/fill stretch image=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is stretched to fill the path area.

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill stretch image*={<graphics options>}<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command. The image is stretched to fill the path area.


```
\begin{tikzpicture}
\path[fill stretch image*=
{angle=90,origin=c}{goldshade.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill stretch picture=<graphical code>` (no default, initially unset)

Fills the current path with the given `<graphical code>`. The result is stretched to fill the path area.

```
\begin{tikzpicture}
\path[draw,fill stretch picture=%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




12.3 Fill Overzoom

`/tikz/fill overzoom image=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is zoomed such that the path area fills the image.


```
\begin{tikzpicture}
\path[fill overzoom image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill overzoom image*={<graphics options>}<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command. The image is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[fill overzoom image*=
{angle=90,origin=c}{goldshade.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill overzoom picture=<graphical code>` (no default, initially unset)

Fills the current path with the given `<graphical code>`. The result is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[draw,fill overzoom picture=%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




12.4 Fill Zoom

`/tikz/fill zoom image=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.


```
\begin{tikzpicture}
\path [draw,fill zoom image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill zoom image*={<graphics options>} {<file name>}` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path [draw,fill zoom image*=
{angle=90,origin=c}{goldshade.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




`/tikz/fill zoom picture=<graphical code>`

(no default, initially unset)

Fills the current path with the given `<graphical code>`. The result is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path [draw,fill zoom picture=%
\draw [red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw [red,line width=5mm] (-1,-1) -- (1,1);
\draw [red,line width=5mm] (-1,1) -- (1,-1);
]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




12.5 Fill Shrink

`/tikz/fill shrink image=<file name>`

(no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




`/tikz/fill shrink image*=<file name>`

(no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink ]
  [image*={width=1.5cm}{goldshade.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




`/tikz/fill shrink picture=<graphical code>`

(no default, initially unset)

Fills the current path with the given `<graphical code>`. The result is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink picture=%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.6 Fill Tile

`/tikz/fill tile image=<file name>` (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by `<file name>`.


```
\begin{tikzpicture}
\path[fill tile image=pink_marble.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill tile image*={<graphics options>}{<file name>}` (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command.


```
\begin{tikzpicture}
\path[fill tile image*={width=1cm}{pink_marble.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill tile picture=<graphical code>` (no default, initially unset)

Fills the current path with a tile pattern using the given `<graphical code>`.


```
\begin{tikzpicture}
\path[draw,fill tile picture=%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill tile picture*={<fraction>}{<graphical code>}` (no default, initially unset)

Fills the current path with a tile pattern using the given `<graphical code>`. The graphic is resized by `<fraction>`.

```
\begin{tikzpicture}
\path[draw,fill tile picture*={0.25}{%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




12.7 Filling Options

`/tikz/fill image opacity=<fraction>` (no default, initially 1.0)

Sets the fill opacity for the image or picture fill options to the given `<fraction>`.

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png] (0,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.75]
(2,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.5]
(4,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.25]
(6,0) circle (1cm);
\path[fill=red] (8,0) circle (1cm);
\end{tikzpicture}
```



`/tikz/fill image scale=<fraction>` (no default, initially 1.0)

Stretches, zooms, overzooms or shrinks the image or picture to the given `<fraction>` of the width and height of the current path.

```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
(0,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=0.75]
(3,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=1.5]
(6,0) rectangle +(2,2);
\end{tikzpicture}
```



`/tikz/fill image options=<graphics options>` (no default, initially empty)

The `<graphics options>` are given to the underlying `\includegraphics` command for the image fill options. This can be just together with `/tikz/fill stretch image`^{P. 246}, `/tikz/fill overzoom image`^{P. 247}, `/tikz/fill zoom image`^{P. 248}, and `/tikz/fill tile image`^{P. 250}.

```
\begin{tikzpicture}
\path[fill image options={width=1cm},
      fill tile image=pink_marble.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,\dots,315}
  { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```





Image blending example

```
\begin{tikzpicture}[every node/.style={circle,minimum width=2cm}]
\node[fill stretch image=blueshade.png]
(A) at (120:3cm) {A};
\node[fill stretch image=goldshade.png]
(B) at (60:3cm) {B};
\node[
  preaction={fill stretch image=blueshade.png},
  fill stretch image=goldshade.png,
  fill image opacity=0.5] (C) {C};
\path (A) -- node{\$+\$} (B);
\draw[->,very thick] (A)--(C);
\draw[->,very thick] (B)--(C);
\end{tikzpicture}
```



12.8 Straightening of the Arcs




This patch is considered as an experimental feature. It changes some of the original TikZ code. This change may break with future updates of TikZ.

N 2014-05-05

\tcbpatcharcangular

The TikZ package provides a nice `rounded corners` option to replace all corners by little arcs. `\tcbpatcharcangular` is a patch which straightens the arcs. To say it more prosaic, the little arcs are replaced by little straight lines.

```
\begin{tikzpicture}
\draw[thick,rounded corners=8pt]
(0,0) -- (0,2) -- (1,3.25) -- (2,2) -- (2,0)
-- (0,2) -- (2,2) -- (0,0) -- (2,0);
\tcbpatcharcangular
\draw[thick,rounded corners=8pt,xshift=2.5cm]
(0,0) -- (0,2) -- (1,3.25) -- (2,2) -- (2,0)
-- (0,2) -- (2,2) -- (0,0) -- (2,0);
\end{tikzpicture}
```



N 2014-05-05

\tcbpatcharcround

This macro reverts `\tcbpatcharcangular`, i.e., the patch from `\tcbpatcharcangular` is replaced by the original code.

12.9 Extracting Node Dimensions

The following auxiliary macros are defined by the `\tikz` skins library. They allow to determine the width and height of an arbitrary TikZ node. To be more specific, they determine the east-to-west and the north-to-south dimensions which may be not the maximal dimensions for a non-rectangular node. Note that the following dimensions are measured exactly including the line width of the border line. If a new rectangle or node with the same dimensions and a border is to be drawn, this border width has to be subtracted.

N 2014-09-19 `\tcbsettowidthofnode{\langle register \rangle}{\langle node \rangle}`

Sets the east-to-west dimension of the given `\langle node \rangle` to the TeX `\langle register \rangle`.

N 2014-09-19 `\tcbsetmacrotowidthofnode{\langle macro \rangle}{\langle node \rangle}`

Defines `\langle macro \rangle` as the east-to-west dimension of the given `\langle node \rangle`.

N 2014-09-19 `\tcbsettoheightofnode{\langle register \rangle}{\langle node \rangle}`

Sets the north-to-south dimension of the given `\langle node \rangle` to the TeX `\langle register \rangle`.

N 2014-09-19 `\tcbsetmacrotoheightofnode{\langle macro \rangle}{\langle node \rangle}`

Defines `\langle macro \rangle` as the north-to-south dimension of the given `\langle node \rangle`.

```
\begin{tikzpicture}
\node[align=center,draw=red,fill=yellow] (A) {This is my\\example node};
\tcbsetmacrotowidthofnode\mywidth{A}
\tcbsetmacrotoheightofnode\myheight{A}
\path[fill=blue!25!white]           % rectangle widthout border
 ([xshift=2mm]A.south east)
 rectangle node{Copy} +(\mywidth,\myheight);
\node[draw=blue,fill=blue!25!white, % standard border width 0.4pt
      minimum width=\mywidth-0.4pt,    % minus width of border
      minimum height=\myheight-0.4pt   % minus height of border
      ]
      at ([xshift=5cm]A) {Copy 2};
\end{tikzpicture}
```

This is my
example node

Copy

Copy 2

13 Library vignette

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{vignette}
```

This also loads the  skins library, see Section 10 on page 140, and the `fadings` library of tikz [20].

13.1 Vignette Drawing

N 2016-04-22

```
\tcbvignette{\langle options\rangle}
```

In this context, a *vignette* is a four part rectangular frame. It is constructed as several TikZ paths and, therefore, can only be used inside a `tikzpicture` environment or inside `tcolorbox`^{→ P. 12} options.

The `\langle options\rangle` control position, size and style settings of the vignette. Theses options have the common key path `/tcb/vig/` and are described in the following.

The next examples show direct `\tcbvignette` usage without a `tcolorbox`^{→ P. 12}.

```
\begin{tikzpicture}
  \tcbvignette{}
\end{tikzpicture}
```



```
\begin{tikzpicture}
  \node[draw,fill=blue!15!white] (A) {Test};
  \tcbvignette{outside node=A,raised color=blue}
\end{tikzpicture}
```



```
\begin{tikzpicture}
  \node[draw,fill=blue!15!white] (A) {Another Test};
  \tcbvignette{size=3mm,outside node=A,
    north style=red,east style=yellow,
    south style=blue,west style=green}
\end{tikzpicture}
```



```
\begin{tikzpicture}
  \node[inner sep=3mm,fill=red!75] (A) {Test};
  \tcbvignette{over node=A,fade in}
\end{tikzpicture}
```




`\tcbvignette` can be used directly inside appropriate options keys for `tcolorbox`^{→ P. 12}. Note that options like `/tcb/underlay`^{→ P. 187} need `/tcb/enhanced`^{→ P. 196} or similar settings.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=1mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay={\tcbvignette{size=1mm,inside node=frame,
    raised color=green!50!black}}]
  This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

Mostly, convenient short cuts like `/tcb/underlay vignette`^{→ P. 261} can be used to add a *vignette* to a `tcolorbox`^{→ P. 12}. Here, `\tcbvignette` is used internally.


```
\begin{tcolorbox}[enhanced, size=small, sharp corners,
  colback=green!10, colframe=green!50!black,
  boxrule=1mm, titlerule=0mm,
  title=My title, center title, fonttitle=\bfseries,
  underlay vignette]
  This is a tcolorbox.
\end{tcolorbox}
```



13.2 Generic Geometry Settings


N 2016-04-22	<code>/tcb/vig/xmin=<length></code>	(no default, initially 0pt)
	Sets the lower horizontal limit of a <code>\tcbvignette</code> ^{→ P. 254} .	
N 2016-04-22	<code>/tcb/vig/xmax=<length></code>	(no default, initially 1cm)
	Sets the upper horizontal limit of a <code>\tcbvignette</code> ^{→ P. 254} .	
N 2016-04-22	<code>/tcb/vig/ymin=<length></code>	(no default, initially 0pt)
	Sets the lower vertical limit of a <code>\tcbvignette</code> ^{→ P. 254} .	
N 2016-04-22	<code>/tcb/vig/ymax=<length></code>	(no default, initially 1cm)
	Sets the upper vertical limit of a <code>\tcbvignette</code> ^{→ P. 254} .	

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (3,2);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (3,2);
  \tcbvignette{xmin=1cm,xmax=2.5cm,ymin=0.5cm,ymax=1.75cm}
\end{tikzpicture}
```



N 2016-04-22	<code>/tcb/vig/lower left corner=<coordinates></code>	(style, initially 0,0)
	Sets the lower left corner of a <code>\tcbvignette</code> ^{→ P. 254} . This style sets <code>/tcb/vig/xmin</code> and <code>/tcb/vig/ymin</code> .	
N 2016-04-22	<code>/tcb/vig/upper right corner=<coordinates></code>	(style, initially 1,1)
	Sets the upper right corner of a <code>\tcbvignette</code> ^{→ P. 254} . This style sets <code>/tcb/vig/xmax</code> and <code>/tcb/vig/ymax</code> .	

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (3,2);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (3,2);
  \tcbvignette{lower left corner={1,0.5},
    upper right corner={2.5,1.75}}
\end{tikzpicture}
```



N 2016-04-22	<code>/tcb/vig/inside node=<name></code>	(style, initially unset)
	Places the <code>\tcbvignette</code> ^{→ P. 254} inside the node with the given <code><name></code> . The outer limits of the <i>vignette</i> are adapted to the node geometry.	


```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{inside node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/outside node=<name>** (style, initially unset)

Places the `\tcbvignette`^{→ P. 254} outside the node with the given `<name>`. The inner limits of the *vignette* are adapted to the node geometry.


```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{outside node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/over node=<name>** (style, initially unset)

Places the `\tcbvignette`^{→ P. 254} over the node with the given `<name>`. The outer limits of the *vignette* are adapted to the node geometry, but are shifted to the outside by `/tcb/vig/over node offset`.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{over node offset=1mm,over node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/over node offset=<length>** (no default, initially 0.1mm)

Determines the shift value for `/tcb/vig/over node`. Note that `/tcb/vig/over node offset` has to be set *before* `/tcb/vig/over node` is used.

N 2016-04-22 **/tcb/vig/north size=<length>** (no default, initially 2mm)

Sets the thickness of the north *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{north size=4mm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/south size=<length>** (no default, initially 2mm)

Sets the thickness of the south *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{south size=4mm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/east size=<length>** (no default, initially 2mm)

Sets the thickness of the east *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{east size=4mm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/west size=<length>** (no default, initially 2mm)

Sets the thickness of the west *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{west size=4mm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/vertical size=<length>** (style, initially 2mm)
Sets /tcb/vig/north size^{→ P. 256} and /tcb/vig/south size^{→ P. 256}, to the given <length>.

```
\begin{tikzpicture}
  \tcbvignette{vertical size=4mm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig.horizontal size=<length>** (style, initially 2mm)
Sets /tcb/vig/east size^{→ P. 256} and /tcb/vig/west size^{→ P. 256}, to the given <length>.

```
\begin{tikzpicture}
  \tcbvignette{horizontal size=4mm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/size=<length>** (style, initially 2mm)
Sets /tcb/vig/north size^{→ P. 256}, /tcb/vig/south size^{→ P. 256}, /tcb/vig/east size^{→ P. 256}, and /tcb/vig/west size^{→ P. 256} to the given <length>.

```
\begin{tikzpicture}
  \tcbvignette{size=4mm}
\end{tikzpicture}
```



! /tcb/vig/north size^{→ P. 256}, /tcb/vig/south size^{→ P. 256}, etc. have to be set *before* /tcb/vig/outside node^{→ P. 256} is used.

13.3 Generic Color and Style Settings

N 2016-04-22 **/tcb/vig/north style={<style>}** (no default, initially red!50!white)
Sets TikZ <style> options for the north vignette part.

```
\begin{tikzpicture}
  \tcbvignette{north style=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/south style={<style>}** (no default, initially red!50!black)
Sets TikZ <style> options for the south vignette part.

```
\begin{tikzpicture}
  \tcbvignette{south style={draw=blue,fill=yellow}}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/east style={<style>}** (no default, initially red!75!black)
Sets TikZ <style> options for the east vignette part.

```
\begin{tikzpicture}
  \tcbvignette{east style={left color=yellow!75!black,
    right color=blue!75!black}}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/west style={<style>}** (no default, initially red!75!white)
Sets TikZ *<style>* options for the west *vignette* part.

```
\begin{tikzpicture}
\tcbvignette{west style={preaction={fill=black!20},
pattern=checkerboard,
pattern color=black!30}}
\end{tikzpicture}
```



N 2016-05-24 **/tcb/vig/scope={<style>}** (no default, initially empty)
The four *vignette* parts are drawn inside a TikZ **scope** environment which takes the given *<style>* as option.

```
\begin{tikzpicture}
\tcbvignette{scope={transparency group,opacity=0.25}}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/raised color=<color>** (no default)
Creates a raised frame impression by setting the four style options */tcb/vig/north style*^{→ P. 257}, */tcb/vig/south style*^{→ P. 257}, */tcb/vig/east style*^{→ P. 257}, and */tcb/vig/west style* to darkened and lightened variations of the given *<color>*.

```
\begin{tikzpicture}
\tcbvignette{raised color=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/lowered color=<color>** (no default)
Creates a lowered frame impression by setting the four style options */tcb/vig/north style*^{→ P. 257}, */tcb/vig/south style*^{→ P. 257}, */tcb/vig/east style*^{→ P. 257}, and */tcb/vig/west style* to darkened and lightened variations of the given *<color>*.

```
\begin{tikzpicture}
\tcbvignette{lowered color=green!75!black}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/color from=<inner> to <outer>** (no default)
Sets the four style options */tcb/vig/north style*^{→ P. 257}, */tcb/vig/south style*^{→ P. 257}, */tcb/vig/east style*^{→ P. 257}, and */tcb/vig/west style* such that the color shades from the *<inner>* color to the *<outer>* color.

```
\begin{tikzpicture}
\tcbvignette{color from=red to blue!50}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/base color=<color>** (no default)
Sets the base color for */tcb/vig/raised color*, */tcb/vig/lowered color*, */tcb/finish fading vignette*^{→ P. 264}. Typically, this value has not to be set directly.

/tcb/vig/draw method=direct|clipped (no default, initially direct)

Especially, if shadings or fadings are used, the drawn *vignette* graphs are displayed sometimes not as perfect as expected. Glitches and imperfections are very dependent on the previewer software. The /tcb/vig/draw method intends to give a choice of alternative drawing methods.

- **direct**: The *vignette* parts are drawn/filled by using a single TikZ graph. This is the preferred (and default) method for solid color graphs.
- **clipped**: The *vignette* parts are drawn somewhat oversized and are clipped to the intended region. In combination with shadings and fadings this seems to give a better/different optical result (depends on the previewer).

```
\begin{tikzpicture}
  \tcbvignette{color from=red to yellow}
\end{tikzpicture}
```



```
\begin{tikzpicture}
  \tcbvignette{color from=red to yellow,draw method=clipped}
\end{tikzpicture}
```



This option is a stopgap and may be changed or preferably removed in future.

13.4 Generic Fading Settings

The **fadings** library of **tikz** [20] is loaded automatically by the **vignette** library. Amongst others, the fadings **west**, **east**, **north**, and **south** are defined inside the **fadings** library.

The **vignette** library adds some more fadings called **semi west**, **semi east**, **semi north**, and **semi south**. These fadings are much *weaker* than the normal fadings.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (1,1);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (1,1);
  \fill [path fading=semi west,blue] (0,0) rectangle (1,1);
\end{tikzpicture}
```



Comparison of the Fadings

west



east



north



south



semi west



semi east



semi north




semi south



N 2016-04-22 **/tcb/vig/fade in={⟨style⟩}** (style, default white)

Sets the four style options `/tcb/vig/north style`^{→ P. 257}, `/tcb/vig/south style`^{→ P. 257}, `/tcb/vig/east style`^{→ P. 257}, and `/tcb/vig/west style`^{→ P. 258} such that the paths fade from outside to inside.


```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{fade in=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/fade out={⟨style⟩}** (style, default white)

Sets the four style options `/tcb/vig/north style`^{→ P. 257}, `/tcb/vig/south style`^{→ P. 257}, `/tcb/vig/east style`^{→ P. 257}, and `/tcb/vig/west style`^{→ P. 258} such that the paths fade from inside to outside.


```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{fade out=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/semi fade in={⟨style⟩}** (style, default white)

Sets the four style options `/tcb/vig/north style`^{→ P. 257}, `/tcb/vig/south style`^{→ P. 257}, `/tcb/vig/east style`^{→ P. 257}, and `/tcb/vig/west style`^{→ P. 258} such that the paths fade weak from outside to inside.


```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{semi fade in=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/semi fade out={⟨style⟩}** (style, default white)

Sets the four style options `/tcb/vig/north style`^{→ P. 257}, `/tcb/vig/south style`^{→ P. 257}, `/tcb/vig/east style`^{→ P. 257}, and `/tcb/vig/west style`^{→ P. 258} such that the paths fade weak from inside to outside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{semi fade out=blue}
\end{tikzpicture}
```



13.5 Vignette as Underlay

N 2016-04-22

`/tcb/underlay vignette={⟨options⟩}` (style, no default)

This puts a `\tcbvignette`^{→ P. 254} with the given `⟨options⟩` as `/tcb/underlay`^{→ P. 187} to a `tcolorbox`^{→ P. 12}. The dimensions of the *vignette* are matched to the dimensions of the `tcolorbox`^{→ P. 12}. For example, `/tcb/leftrule`^{→ P. 35} is used as `/tcb/vig/west size`^{→ P. 256}. Also, `/tcb/colframe`^{→ P. 27} is used as `/tcb/vig/raised color`^{→ P. 258}.

For a `/tcb/breakable`^{→ P. 353} `tcolorbox`, the *vignette* is also been broken. Alternatively, `\tcbvignette`^{→ P. 254} could be used directly inside an `/tcb/underlay`^{→ P. 187} with appropriate settings.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
colback=green!10,colframe=green!50!black,
boxrule=2mm,titlerule=0mm,
title=My title,center title,fonttitle=\bfseries,
underlay vignette]
This is a tcolorbox.
\end{tcolorbox}
```

My title

This is a tcolorbox.

```
\begin{tcolorbox}[enhanced,size=small,arc=0pt,
colback=blue!10,colframe=blue,boxrule=2mm,
underlay vignette={size=1.5mm}]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
colframe=red,interior hidden,boxrule=2mm,
colupper=white,center upper,fontupper=\bfseries,
underlay vignette]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
colback=red!50!yellow,frame hidden,boxrule=2mm,
underlay vignette={color from=red!50!yellow to white,
draw method=clipped,size=2.1mm}]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
\tcbbox[enhanced,sharp corners,colback=red!10,colframe=red]
{Test}

\tcbbox[enhanced,sharp corners,colback=red!10,colframe=red,
underlay vignette]{Test}
```

Test

Test

N 2016-04-22

/tcb/underlay raised shading vignette={⟨options⟩} (style, no default)

This is a special style derived from /tcb/underlay vignette^{→ P. 261}, where the frame color is shaded to create a soft raised frame impression.

```
\begin{tcolorbox}[enhanced,sharp corners,  
colback=green!10,  
colframe=green!50!black,  
size=small,boxrule=2mm,titlerule=0mm,  
title=My title,center title,fonttitle=\bfseries,  
underlay raised shading vignette]  
This is a tcolorbox.  
\end{tcolorbox}
```

My title

This is a tcolorbox.

N 2016-04-22

/tcb/underlay raised fading vignette={⟨options⟩} (style, no default)

This style gives a similar effect as /tcb/underlay raised shading vignette, but a path fading is used here. Different optical impression are very previewer-dependent.

```
\begin{tcolorbox}[enhanced,sharp corners,  
colback=green!10,  
colframe=green!50!black,  
size=small,boxrule=2mm,titlerule=0mm,  
title=My title,center title,fonttitle=\bfseries,  
underlay raised fading vignette]  
This is a tcolorbox.  
\end{tcolorbox}
```

My title

This is a tcolorbox.

N 2016-04-22

/tcb/underlay shade in vignette={⟨options⟩} (style, no default)

This is a special style derived from /tcb/underlay vignette^{→ P. 261}, where the frame color is shaded into the interior color.

```
\begin{tcolorbox}[enhanced,sharp corners,frame hidden,  
colback=green!10,  
colframe=green!50!black,  
size=small,boxrule=2mm,titlerule=0mm,  
underlay shade in vignette]  
This is a tcolorbox.  
\end{tcolorbox}
```

This is a tcolorbox.

13.6 Vignette as Finish

N 2016-04-22

`/tcb/finish vignette={⟨options⟩}` (style, no default)

This puts a `\tcbvignette`^{→ P. 254} with the given `⟨options⟩` as `/tcb/finish`^{→ P. 189} to a `tcolorbox`^{→ P. 12}. The default style settings create a raised frame impression by drawing black and white color parts with reduced opacity.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish vignette={size=1mm}]
  This is a tcolorbox.
\end{tcolorbox}
```

My title

This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish vignette={size=3mm}]{pink_marble.png}
```



N 2016-04-22

`/tcb/finish raised fading vignette={⟨options⟩}` (style, no default)

This puts a `\tcbvignette`^{→ P. 254} with the given `⟨options⟩` as `/tcb/finish`^{→ P. 189} to a `tcolorbox`^{→ P. 12}. The default style settings create a soft raised frame impression by drawing fading black and white color parts.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish raised fading vignette={size=1mm}]
  This is a tcolorbox.
\end{tcolorbox}
```

My title

This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish raised fading vignette={size=3mm}]{pink_marble.png}
```



/tcb/finish fading vignette={⟨options⟩}

(style, no default)

This puts a `\tcbvignette`^{→ P. 254} with the given `⟨options⟩` as `/tcb/finish`^{→ P. 189} to a `tcolorbox`^{→ P. 12}. The default style settings fade the box into white from inside to outside. Note that `/tcb/vig/over node`^{→ P. 256} is used here. `/tcb/vig/over node offset`^{→ P. 256} can be adapted to overlap the box more or less. The fade color can be set using `/tcb/vig/base color`^{→ P. 258}.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish fading vignette={size=2mm}]
  This is a tcolorbox.
\end{tcolorbox}
```

My title

This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish fading vignette={size=3mm}]{pink_marble.png}
```



```
\begin{tcolorbox}[colback=blue!50!black,size=small,
  title=Example]
\tcbincludegraphics[blankest,
  finish fading vignette={base color=blue!50!black,size=3mm,
  over node offset=0.2mm}]{pink_marble.png}
\end{tcolorbox}
```


Example



```

\begin{tcbitemize}[raster columns=3,bicolor,
raster equal height,sharp corners,boxrule=2mm,
colframe=red,colback=yellow!5,colbacklower=yellow!25!red!20]
\tcbitem A
\tcbitem[underlay vignette] B
\tcbitem[underlay={\tcbvignette{inside node=interior,
lowered color=red,size=1mm}}] C
\tcbitem[underlay vignette,
underlay={\tcbvignette{inside node=interior,
lowered color=red,size=1mm}}] D
\tcbitem[boxrule=3mm,underlay vignette={size=2mm},
underlay={\tcbvignette{inside node=interior,
lowered color=red,size=1mm}}] E
\tcbitem[underlay raised shading vignette] F
\tcbitem[underlay raised shading vignette,
underlay={\tcbvignette{inside node=interior,
lowered color=red,size=1mm}}] G
\tcbitem[title=H1,underlay={\tcbvignette{inside node=interior,
lowered color=red,size=1mm}},finish vignette] H2
\tcbitem[boxrule=0.25mm,colback=red!30,finish vignette] I1 \tcblower I2
\tcbitem[title,colback=red!30,finish raised fading vignette] J1 \tcblower J2
\tcbitem[boxrule=1mm,underlay={\tcbvignette{inside node=interior,
raised color=red,size=1mm}}] K
\tcbitem[boxrule=1mm,title=L1,underlay={\tcbvignette{inside node=title,
lowered color=red,size=0.5mm}}] L2
\end{tcbitemize}

```



14 Library raster


The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{raster}
```

14.1 Concept of Rasters

A *raster* is used to align several colored boxes in a regular way. It can be seen as a far related counterpart to the `matrix` construct of TikZ, but it differs in many aspects.

In principle, `tcolorbox`s are arranged in rows and columns when put inside a `tcb raster`^{P. 268} environment. The boxes are fluently added to the raster like adding text to a paragraph. Especially, line/row breaks are done automatically and one cannot end a line/row ahead of schedule. Further, a *raster* is not restricted to a single page but may break into an arbitrary series of pages.



```

\begin{tcbraster}[raster columns=3,raster rows=3,raster height=\linewidth,
enhanced,size=small,sharp corners,arc=8mm,colframe=red!50!black,
colback=yellow!10!white,watermark overzoom=1.0,fit algorithm=hybrid* ]
\begin{tcolorbox}[rounded corners=northwest,boxrule=0pt,
watermark graphics=lichtspiel.jpg]\end{tcolorbox}
\tcboxif{\lipsum[1]}
\begin{tcolorbox}[rounded corners=northeast,boxrule=0pt,
watermark graphics=goldshade.png]\end{tcolorbox}
\tcboxif{\lipsum[2]}
\begin{tcolorbox}[valign=center,halign=center]Nine Boxes.\end{tcolorbox}
\tcboxif{\lipsum[3]}
\begin{tcolorbox}[rounded corners=southwest,boxrule=0pt,
watermark graphics=goldshade.png]\end{tcolorbox}
\tcboxif{\lipsum[4]}
\begin{tcolorbox}[rounded corners=southeast,boxrule=0pt,
watermark graphics=lichtspiel.jpg]\end{tcolorbox}
\end{tcbraster}

```



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nine Boxes.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellenesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellenesque felis eu massa.



Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.



14.2 Macros of the Library


N 2014-11-10

```
\begin{tcbraster}[\langle options \rangle]
  <environment content>
\end{tcbraster}
```


A raster arranges enclosed boxes in a regular way, mainly into rows and columns. The *<options>* are used to control the raster parameters and to set the properties for the enclosed boxes.

- The *raster* is only allowed to contain a series of `tcolorbox`^{P. 12} environments or derived constructs. With some small restrictions, boxes created with `\tcbxboxfit`^{P. 383} can also be added. Boxes created with `\tcbx`^{P. 14} are not reasonable here, but may be used to a certain degree.
- Do not add anything else between the boxes inside the raster with exception of white-space. Especially, do not use `\backslash` or `\par` to end a row; row breaks are done automatically.
- The boxes inside a raster are numbered automatically. `\thetcbasternum` may be used inside a box to access this number.

```
\begin{tcbraster}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbasternum}]
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbraster}
```



```
\begin{tcbraster}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbasternum}]
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbraster}
```




```
\begin{tcbitemize}[\langle options \rangle]
  <environment content>
\end{tcbitemize}
```

This is a special case of a `tcbraster`^{→ P. 268} with the given `\langle options \rangle`.

- Here, the enclosed boxes are created using `\tcbitem`.
- There has to be at least one `\tcbitem`.
- One cannot use anything else than `\tcbitem` to add something to the *raster*.

This leads to a very compact syntax.

```
\begin{tcbitemize}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbasternum}]
  \tcbitem First box
  \tcbitem Second box
  \tcbitem This is a box\\with a second line
  \tcbitem[colback=yellow,colbacktitle=yellow!50!black] Another box
  \tcbitem A box again
\end{tcbitemize}
```



`tcbitemize` has more restrictions than `tcbraster`^{→ P. 268}. Especially, the `/tcb/capture`^{→ P. 90} mode has to be `minipage`. For example, `/tcb/fit`^{→ P. 385} cannot be used safely. If `/tcb/fit`^{→ P. 385} should be used, turn over to `tcbraster`^{→ P. 268}.

```
\tcbitem[\langle options \rangle]
```

Used inside `tcbitemize` to create a new `tcolorbox`^{→ P. 12} with the given `\langle options \rangle`.


```
\begin{tcboxedraster}[\textit{raster options}] {\textit{box options}}
  \textit{environment content}
\end{tcboxedraster}
```

This is a convenience environment which combines a `tcolorbox`^{→ P. 12} with an embedded `tcbraster`^{→ P. 268}. The `\textit{box options}` are given to the outer `tcolorbox`^{→ P. 12}, while the `\textit{raster options}` are given to the embedded `tcbraster`^{→ P. 268}. This environment is especially useful for rasters inside rasters.

```
\begin{tcboxedraster}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  {colback=yellow!10,fonttitle=\bfseries,title=Boxed Raster}
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcboxedraster}
```




```
% \tcbuselibrary{skins}
\begin{tcbraster}[raster columns=2, raster equal height,
  raster every box/.style={size=small,colframe=red!50!black,colback=red!10!white,
  valign=center,halign=center}]
  \begin{tcolorbox}One\end{tcolorbox}
  \begin{tcolorbox}Two\end{tcolorbox}
  \begin{tcboxedraster}{blankest}
    \begin{tcolorbox}Three\end{tcolorbox}
    \begin{tcolorbox}Four\end{tcolorbox}
    \begin{tcolorbox}Five\end{tcolorbox}
    \begin{tcolorbox}Six\end{tcolorbox}
  \end{tcboxedraster}
  \begin{tcolorbox}Seven\end{tcolorbox}
\end{tcbraster}
```



```
\begin{tcbboxeditemize}[\langle raster options\rangle]{\langle box options\rangle}
  \langle environment content\rangle
\end{tcbboxeditemize}
```

This is a convenience environment which combines a `tcolorbox`^{→ P. 12} with an embedded `tcbitemize`^{→ P. 269}. The `\langle box options\rangle` are given to the outer `tcolorbox`^{→ P. 12}, while the `\langle raster options\rangle` are given to the embedded `tcbitemize`^{→ P. 269}. This environment is especially useful for rasters inside rasters.

```
\begin{tcbboxeditemize}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbasternum}]
  {\colback=yellow!10,fonttitle=\bfseries,title=Boxed Itemize}
    \tcbitem First box
    \tcbitem Second box
    \tcbitem This is a box\with a second line
    \tcbitem Another box
    \tcbitem A box again
\end{tcbboxeditemize}
```



14.3 Option Keys of the Library


N 2014-11-10

/tcb/raster columns=<number>

(no default, initially 2)

Sets the <number> of columns for a *raster*.

```
\begin{tcbitemize}[raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
\begin{tcbitemize}[raster columns=4,
  size=small,colframe=blue!50!black,colback=blue!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10

/tcb/raster rows=<number>

(no default, initially 2)

Sets the <number> of rows for a *raster*. Note that this is only relevant in connection with setting /tcb/raster height^{→ P. 273} to a value greater than 0pt. Then, it defines the number of rows *per* given height.

N 2014-11-10

/tcb/raster width=<length>

(no default, initially \linewidth)

Sets the total raster width to the given <length>. /tcb/raster left skip^{→ P. 274} and /tcb/raster right skip^{→ P. 274} are part of the total width.

```
\begin{tcbitemize}[raster width=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```




N 2014-11-10

/tcb/raster height=<length> (no default, initially 0pt)

Sets the raster height *per /tcb/raster rows*^{→P. 272} to the given <length>. This forces an appropriate height for the enclosed boxes. */tcb/raster before skip* and */tcb/raster after skip* are not part of this calculation. If the <length> is set to 0pt, this feature is deactivated.

```
\begin{tcbitemize}[raster height=4cm, raster rows=2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem[enhanced,
    finish={\draw[blue,very thick,<->] (frame.south)
      -- node[right,pos=.75]{4cm} +(0,4); }]
  Three
  \tcbitem Four
  \tcbitem Five
\end{tcbitemize}
```



N 2014-11-10

/tcb/raster before skip=<glue> (no default, initially 2mm)

Space of the given <glue> is inserted vertically before the *raster*. This space is discardable.

U 2014-12-16

/tcb/raster after skip=<glue> (no default, initially 2mm)

Space of the given <glue> is inserted vertically after the *raster*. This space is discardable.

N 2015-01-08

/tcb/raster equal skip=<length> (style, no default)

Shortcut to set */tcb/raster before skip*, */tcb/raster after skip*, */tcb/raster column skip*^{→P. 274}, and */tcb/raster row skip*^{→P. 274} to the same <length> value.

```
\begin{tcbitemize}[raster equal skip=4mm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10

/tcb/raster left skip=<length>

(no default, initially 0pt)

Space of the given <length> is inserted horizontally left of the *raster*.

```
\begin{tcbitemize}[raster left skip=2cm,  
size=small,colframe=red!50!black,colback=red!10!white]  
  \tcbitem One  
  \tcbitem Two  
  \tcbitem Three  
  \tcbitem Four  
\end{tcbitemize}
```

One

Two

Three

Four

N 2014-11-10

/tcb/raster right skip=<length>

(no default, initially 0pt)

Space of the given <length> is inserted horizontally right of the *raster*.

```
\begin{tcbitemize}[raster right skip=2cm,  
size=small,colframe=red!50!black,colback=red!10!white]  
  \tcbitem One  
  \tcbitem Two  
  \tcbitem Three  
  \tcbitem Four  
\end{tcbitemize}
```

One

Two

Three

Four

N 2014-11-10

/tcb/raster column skip=<length>

(no default, initially 2mm)

Space of the given <length> is inserted horizontally between the columns.

```
\begin{tcbitemize}[raster column skip=2cm,  
size=small,colframe=red!50!black,colback=red!10!white]  
  \tcbitem One  
  \tcbitem Two  
  \tcbitem Three  
  \tcbitem Four  
\end{tcbitemize}
```

One

Two

Three

Four

N 2014-11-10

/tcb/raster row skip=<length>

(no default, initially 2mm)

Space of the given <length> is inserted vertically between the rows.

```
\begin{tcbitemize}[raster row skip=0pt,  
size=small,colframe=red!50!black,colback=red!10!white]  
  \tcbitem One  
  \tcbitem Two  
  \tcbitem Three  
  \tcbitem Four  
\end{tcbitemize}
```

One

Two

Three

Four

N 2014-11-10

/tcb/raster halign=(*alignment*)

(no default, initially **left**)

Defines the horizontal alignment for the boxes of the rows of a *raster*, if these rows are not completely filled (mainly: the last one).

Feasible values for *<alignment>* are:

- **left**: align to the left side,
- **center**: align to the center,
- **right**: align to the right side.

```
\begin{tcbitemize}[raster halign=center,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
\end{tcbitemize}
```

One

Two

Three

N 2014-11-10

/tcb/raster valign=(*alignment*)

(no default, initially **center**)

Defines the vertical alignment for the boxes of a row, if the boxes do not have equal height.

This sets the /tcb/box align^{→ P. 77} option.

Feasible values for *<alignment>* are:

- **top**: align to the top side,
- **center**: align to the center,
- **bottom**: align to the bottom side.

```
\begin{tcbitemize}[raster valign=top, raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=center, raster columns=3,
  size=small,colframe=blue!50!black,colback=blue!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=bottom, raster columns=3,
  size=small,colframe=green!50!black,colback=green!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
```

One

Two

Three

One

Two

Three

One

Two

Three

N 2014-11-10

/tcb/raster equal height=<type>

(default **all**, initially **none**)

Puts the enclosed boxes into a common /tcb/equal height group^{→ P.59}. The <id> of the equal height group is chosen automatically, but it may be set manually by /tcb/raster equal height group. Also see /tcb/minimum for current equal height group^{→ P.60}. Feasible values for <type> are:

- **none**: no equal height setting,
- **rows**: all boxes in a row are set to equal height,
- **all**: all boxes in the raster are set to equal height.

Note that you have to compile twice to see changes.

```
\begin{tcbitemize}[raster equal height=rows,  
size=small,colframe=red!50!black,colback=red!10!white]  
  \tcbitem One  
  \tcbitem \Huge Two  
  \tcbitem Three  
  \tcbitem Four  
\end{tcbitemize}
```

One

TWO

Three

Four

```
\begin{tcbitemize}[raster equal height,  
size=small,colframe=red!50!black,colback=red!10!white]  
  \tcbitem One  
  \tcbitem \Huge Two  
  \tcbitem Three  
  \tcbitem Four  
\end{tcbitemize}
```

One

TWO

Three

Four

N 2014-11-10

/tcb/raster equal height group=<id>

(no default)

Overwrites the automatically chosen id with the given <id>. If this is used to share a common height between the *raster* and another raster or box, the /tcb/raster equal height option should be set to **all**.

```
\tcbset{size=small,colframe=red!50!black,colback=red!10!white}  
\begin{tcolorbox}[equal height group=raster-manual-id]  
  A single box  
\end{tcolorbox}  
\begin{tcbitemize}[raster equal height,raster equal height group=raster-manual-id]  
  \tcbitem One  
  \tcbitem \Huge Two  
\end{tcbitemize}
```

A single box

One


TWO

N 2014-11-10

/tcb/raster force size=true|false (default true, initially true)

Enforces the raster size computations onto the enclosed boxes. If set to **false**, individual settings can be used (for the better or worse).

```
\begin{tcbitemize}[raster force size=false, raster halign=center,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem[add to width=-3cm] Three
\tcbitem[add to width=-3cm] Four
\tcbitem[add to width=-3cm] Five
\tcbitem[add to width=3cm] Six
\end{tcbitemize}
```



N 2014-11-10

/tcb/raster reset (no value)

Sets all raster settings back to their default values. Note that **/tcb/reset**^{P.99} does not execute this option. Style settings like **/tcb/raster odd column** etc. are not touched by **/tcb/raster reset**.

14.4 Adding Styles for Specific Boxes

The following styles can be defined to address certain boxes inside a *raster*. Note that such style definitions are not removed by **/tcb/reset**^{P.99} or **/tcb/raster reset**. The style definitions are used in the order given below.

N 2014-11-24

/tcb/raster every box (style)


This style is used for every box.

N 2014-11-10

/tcb/raster odd column (style)

This style is used for every box in an odd column.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster odd column/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```



N 2014-11-10

/tcb/raster even column (style)

This style is used for every box in an even column.

N 2014-11-10

/tcb/raster column n (style)

This style is used for every box in the **n**-th column. **n** has to be replaced by a number.

N 2014-11-10

/tcb/raster odd row (style)

This style is used for every box in an odd row.

N 2014-11-10 **/tcb/raster even row** (style)

This style is used for every box in an even row.

N 2014-11-10 **/tcb/raster row m** (style)

This style is used for every box in the m-th row. m has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster row 2/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One	Two
Three	Four

N 2014-11-10 **/tcb/raster odd number** (style)

This style is used for every box with an odd number.

N 2014-11-10 **/tcb/raster even number** (style)

This style is used for every box with an even number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster columns=3,
raster even number/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\tcbitem Five
\tcbitem Six
\end{tcbitemize}
```

One	Two	Three
Four	Five	Six

N 2014-11-10 **/tcb/raster row m column n** (style)

This style is used for the box in the m-th row and n-th column. m and n have to be replaced by numbers.

N 2014-11-10 **/tcb/raster number n** (style)

This style is used for the box with number n. n has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster number 4/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One	Two
Three	Four


14.5 Combining Columns or Rows

N 2016-02-19

/tcb/raster multicolumn=<number> (no default, initially unset)

This option has to be set inside the option list of a `tcolorbox`^{→ P. 12} inside a `tcbraster`^{→ P. 268} or inside `\tcbitem`^{→ P. 269} inside `tcbitemize`^{→ P. 269}. It merges the given `<number>` of boxes into one single box on the same line. The resulting box gets the `\thetcbasternum` of the first box. If there are not enough boxes available on the current line, this option is ignored and a warning is given.


```
\begin{tcbitemize}[raster equal height=rows,raster columns=3,
    title=\thetcbasternum,colframe=red!50!black,colback=red!10!white]
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=1]
    multicolumn=1
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=2]
    multicolumn=2
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=3]
    multicolumn=3
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=2]
    multicolumn=2
\end{tcbitemize}
```



This option has to be set inside the option list of a `tcolorbox`^{→ P. 12} inside a `tcbraster`^{→ P. 268} or inside `\tcbitem`^{→ P. 269} inside `tcbitemize`^{→ P. 269}. This option not really merges boxes, but simply sizes the current box to fit the space of ⟨number⟩ rows.

! /tcb/raster multirow needs /tcb/raster height^{→ P. 273} to be set. How to achieve a similar result for boxes without fixed /tcb/raster height^{→ P. 273} is shown afterwards.


```
\begin{tcbitemize}[raster rows=3,raster columns=3,raster height=6cm,
raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multirow=2]
multirow=2
\tcbitem[raster multicolumn=2,raster multirow=2,blankest]
\begin{tcbitemize}[raster rows=2,raster columns=2,raster height=\tcboxtextheight]
\tcbitem
\tcbitem
\tcbitem
\tcbitem
\end{tcbitemize}
\end{tcbitemize}
```



For rasters without fixed `/tcb/raster height`^{→ P. 273}, `/tcb/raster multirow`^{→ P. 280} cannot be used. Note that `\tcbtextheight`^{→ P. 139} also cannot be used like in the previous example.

But, with combination of `/tcb/raster equal height`^{→ P. 276} and `/tcb/space to`^{→ P. 57}, a similar effect can be created:

```
\begin{tcbitemize}[raster columns=3,raster equal height=rows,
raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white]
\lipsum[2]
\tcbitem[raster multicolumn=2,blankest,space to=\myspace]
\begin{tcbitemize}[raster columns=2]
\tcbitem This is a box of the inner raster.
\tcbitem
\tcbitem[height=\myspace]
\tcbitem[height=\myspace]
\end{tcbitemize}
\end{tcbitemize}
```



14.6 Rasters inside Rasters

A *raster* inside a *raster* cannot be used directly, because a *raster* can only contain a *tcolorbox* or something derived from a *tcolorbox*. So, a *raster* can be put inside a *tcolorbox* inside a *raster*.

Some examples for such constructions can be found at `tcboxedraster`^{→ P. 270}, `/tcb/raster multicolumn`^{→ P. 279}, `/tcb/raster multirow`^{→ P. 280}.

14.6.1 Raster Setup

The intermediatelying `tcolorbox`^{→ P. 12} can be made invisible by using `/tcb/blankest`^{→ P. 229}.

```
\begin{tcbraster}[raster equal height=rows,  
raster every box/.style={colframe=red!50!black,colback=red!10!white}]  
  \begin{tcolorbox}[blankest]  
    \begin{tcbraster}[raster columns=1]  
      \begin{tcolorbox}One\end{tcolorbox}  
      \begin{tcolorbox}Two\end{tcolorbox}  
    \end{tcbraster}  
  \end{tcolorbox}  
  \begin{tcolorbox}raster+tcolorbox+raster\end{tcolorbox}  
\end{tcbraster}
```

One

Two

raster+tcolorbox+raster

```
\begin{tcbraster}[raster equal height=rows,  
raster every box/.style={colframe=red!50!black,colback=red!10!white}]  
  \begin{tcboxedraster}[raster columns=1]{blankest}  
    \begin{tcolorbox}One\end{tcolorbox}  
    \begin{tcolorbox}Two\end{tcolorbox}  
  \end{tcboxedraster}  
  \begin{tcolorbox}raster+tcboxedraster\end{tcolorbox}  
\end{tcbraster}
```

One

Two

raster+tcboxedraster

```
\begin{tcbitemize}[raster equal height=rows,  
raster every box/.style={colframe=red!50!black,colback=red!10!white}]  
  \tcbitem[blankest]  
    \begin{tcbitemize}[raster columns=1]  
      \tcbitem One  
      \tcbitem Two  
    \end{tcbitemize}  
  \tcbitem tcbitemize+tcitem+tcitemize  
\end{tcbitemize}
```

One

Two

tcbitemize+tcitem+tcitemize

14.6.2 Placing Spaces

If the heights of boxes inside staggered rasters should be matched, the space has to be distributed accordingly.

- For fixed height boxes/rasters using `/tcb/raster height→ P. 273`, the height of boxes is available by `\tcboxtextheight→ P. 139`. This can be used to size deeper layered boxes/rasters.
- For boxes/rasters layed out using `/tcb/raster equal height→ P. 276`, space can be distributed by `/tcb/space to→ P. 57`. It can take several compilations until all spaces are distributed correctly.

```
\begin{tcblayer}[raster rows=2,raster height=6cm,
raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\begin{tcbitemize}[blankest]
\begin{tcblayer}[raster columns=1,raster rows=2,raster height=\tcboxtextheight]
\tcbitem One
\tcbitem Two
\end{tcblayer}
\tcbitem This is a fixed height box.
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
\end{tcblayer}
```

One

This is a fixed height box.

Two


Three

Four

```

\begin{tcbitemize}[raster columns=4,raster rows=4,raster height=0.8\linewidth,
raster every box/.style={size=small,beamer,
colframe=blue!75!yellow,colback=red!75!yellow!20,
center title,title=Box}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\tcbitem[raster multirow=2,blankest]
\begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
\tcbitem Twelve
\tcbitem Eleven
\end{tcbitemize}
\tcbitem[raster multirow=2,raster multicolumn=2,
colframe=red!75!yellow,colback=blue!75!yellow!20]
This is an example with fixed height boxes.
\tcbitem[raster multirow=2,blankest]
\begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
\tcbitem Five
\tcbitem Six
\end{tcbitemize}
\tcbitem Ten
\tcbitem Nine
\tcbitem Eight
\tcbitem Seven
\end{tcbitemize}

```



```

\begin{tcbitemize}[raster equal height=rows,
raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem[blankest,space to=\myspace]
\begin{tcbitemize}[raster columns=1]
\tcbitem One
\tcbitem[add to natural height=\myspace]
This box will adapt its height.
\end{tcbitemize}
\tcbitem This is a flexible height box.
\tcbitem \lipsum[4]
\tcbitem[blankest,space to=\myspace]
\begin{tcbitemize}[raster columns=1]
\tcbitem One
\tcbitem[add to natural height=\myspace]
This box will adapt its height.
\end{tcbitemize}
\end{tcbitemize}

```

One

This is a flexible height box.

This box will adapt its height.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

One

This box will adapt its height.

```

\begin{tcbitemize}[raster equal height=rows,
raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem[blankest,space to=\myspace]
\begin{tcbitemize}[raster columns=1]
\tcbitem One
\tcbitem[add to natural height=\myspace]
This box will adapt its height.
\tcbitem \lipsum[4]
\end{tcbitemize}
\tcbitem[blankest,space to=\myspace]
\begin{tcbitemize}[raster columns=1]
\tcbitem[blankest]\includegraphics[width=\linewidth]{goldshade.png}
\tcbitem[add to natural height=\myspace]
This box will adapt its height.
\end{tcbitemize}
\end{tcbitemize}

```

One

This box will adapt its height.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.



This box will adapt its height.

15 Libraries `listings`, `listingsutf8`, and `minted`

15.1 Loading the Libraries

In contrast to other `tcolorbox` libraries, the libraries `listings`, `listingsutf8`, and `minted` are concurrent in the sense that they all do the same thing, i. e. displaying listings with or without typesetting the listing in L^AT_EX parallel. The difference is the underlying L^AT_EX package which does the core job for displaying a listing. So, typically, you need just *one* of these libraries. If you do not have a clue, which one of them you should use, you should take `listingsutf8`.

! The order in which the libraries are included influences the default settings and the `/tcb/reset`^{→ P. 99} behavior. The settings of a later loaded library overwrite the settings of a previous loaded library. A library is never loaded twice.

15.1.1 Loading `listings`

This library uses the package `listings` [6] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{listings}
```

This also loads the package `listings` [6].

The `/tcb/listing engine`^{→ P. 299} is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

15.1.2 Loading `listingsutf8`

To extend `listings` for UTF-8 encoded sources, you can use the support from the package `listingsutf8` [10] by loading the library variant `listingsutf8`.

```
\tcbuselibrary{listingsutf8}
\tcbset{listing utf8=latin1}% optional; 'latin1' is the default.
```

This also loads the library `listings` and the packages `listings` [6] and `listingsutf8` [10].

The `/tcb/listing engine`^{→ P. 299} is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

15.1.3 Loading

This library uses the package `minted` [11] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{minted}
```

This also loads the package `minted` [11].

! The `minted` package uses the external tool `Pygments` [13] to apply syntax highlighting. It has to be installed and set up, before the library can be used, see [11] and [13]. The `tcolorbox` library  does not work, if the package `minted` [11] does not work.

The `/tcb/listing engine`^{→ P. 299} is set to `minted` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=minted}
```

15.2 Common Macros of the Libraries

```
\begin{tcblisting}{\langle options \rangle}
  \langle environment content \rangle
\end{tcblisting}
```

Creates a colored box based on a `tcolorbox`^{→ P. 12}. Controlled by the given `\langle options \rangle`, the environment content is typeset normally and/or as a listing. Furthermore, the `\langle options \rangle` control appearance and functions of the `tcolorbox`. By default, the listing is interpreted as a L^AT_EX listing.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black]
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

This is a \LaTeX\ example which displays the text as source code
and in compiled form.

This is a L^AT_EX example which displays the text as source code and in compiled form.

```
% \tcbuselibrary{listings} /or/ \tcbuselibrary{listingsutf8}
\begin{tcblisting}[colback=yellow!5,colframe=yellow!50!black,listing only,
    title=This is source code in another language (XML), fonttitle=\bfseries,
    listing options={language=XML,columns=fullflexible,keywordstyle=\color{red}}]
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
    <description>
        Apache Ant build file (http://ant.apache.org/)
    </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
    <description>
        Apache Ant build file (http://ant.apache.org/)
    </description>
</project>
```

```
% \tcbuselibrary{minted}
\begin{tcblisting}[colback=yellow!5,colframe=yellow!50!black,listing only,
    title=This is source code in another language (XML), fonttitle=\bfseries,
    listing engine=minted,minted language=xml]
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
    <description>
        Apache Ant build file (http://ant.apache.org/)
    </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
    <description>
        Apache Ant build file (http://ant.apache.org/)
    </description>
</project>
```

```
% This box is as wide as needed (listing only !)
% \tcbuselibrary{skins}
\begin{tcblisting}[colback=green!5!white,colframe=green!50!black,listing only,
    hbox,enhanced,drop fuzzy shadow,before=\begin{center},after=\end{center}]
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

```
\begin{tcboutputlisting}
  <environment content>
\end{tcboutputlisting}
```

Saves the environment content to a file which is named by the key value of `listing file`. Later, this file can be loaded by `\tcbinputlisting` or `\tcbuselistingtext` or `\tcbuselistinglisting`.

```
\begin{tcboutputlisting}
  This \textbf{text} is written to a standardized file for later usage.
\end{tcboutputlisting}
```

`\tcbinputlisting{<options>}`

Creates a colored boxed based on a `tcolorbox`. The text content is read from a file named by the key value of `listing file`. Apart from that, the function is equal to that of `tcblisting`^{P. 288}.

```
\tcbinputlisting{colback=red!5!white,colframe=red!75!black,text only}
\tcbinputlisting{colback=green!5,colframe=green!75!black,listing only}
```



```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

`\tcbuselistingtext`

Loads text from a file named by the key value of `listing file`.

```
\tcbuselistingtext
```



`\tcbuselistinglisting`

Typesets text as listing from a file named by the key value of `listing file`.

```
\tcbuselistinglisting
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

`\tcbusetemplisting`

Typesets text as listing from a temporary file which was written by `tcbwritetemp`^{P. 119}.

! See Section 21.4 on page 413 and Section 21.5 on page 415 for more elaborate methods to create new environments and commands.

! If a new sort of `tcblisting` environments should be created with one optional argument only, one is highly recommended to use `\DeclareTCBListing→ P. 413` or `\NewTCBListing→ P. 413` instead of `\newtcblisting` to avoid content scanning problems.

`\newtcblisting[<init options>]{<name>}[<number>][<default>]{<options>}`

Creates a new environment `<name>` based on `tcblisting→ P. 288`. Basically, `\newtcblisting` operates like `\newenvironment`. This means, the new environment `<name>` optionally takes `<number>` arguments, where `<default>` is the default value for the optional first argument. The `<options>` are given to the underlying `tcblisting`. Note that `/tcb/savedelimiter→ P. 26` is set to the given `<name>` automatically. The `<init options>` allow setting up automatic numbering, see Section 5 from page 101.

```
\newtcblisting{mybox}{%
    colback=red!5!white,
    colframe=red!75!black}

\begin{mybox}
This is my \LaTeX\ box.
\end{mybox}
```

This is my \LaTeX\ box.

This is my LATEX box.

```
\newtcblisting{mybox}[1]{%
    colback=red!5!white,
    colframe=red!75!black,
    fonttitle=\bfseries,
    title=#1}

\begin{mybox}{Listing Box}
This is my \LaTeX\ box.
\end{mybox}
```

This is my \LaTeX\ box.

This is my LATEX box.

```
\newtcblisting{mybox}[2][]{%
    colback=red!5!white,
    colframe=red!75!black,
    fonttitle=\bfseries,
    title=#2,#1}

\begin{mybox}[listing only]
{Listing Box}
This is my \LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}[listing side text]
{Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
```

This is my \LaTeX\ box.

This is my \LaTeX\ box.

This is my LATEX box.

Definition in the preamble:

```
\newtcblisting[auto counter]{mycbox}[1]{%
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=Listing \thetcbcounter: #1}
```

```
\begin{mycbox}{Listing Box}
This is my \LaTeX\ box.
\end{mycbox}
```

Listing 1: Listing Box

This is my \LaTeX\ box.

This is my L^AT_EX box.

\renewtcblisting [*init options*] {*name*} [*number*] [*default*] {*options*}

Operates like `\newtcblisting`^{P. 291}, but based on `\ renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

```
\newtcbinputlisting[<init options>]{\<name>}[\<number>][<default>]{<options>}
```

Creates a new macro `\<name>` based on `\tcbinputlisting`^{P. 290}. Basically, `\newtcbinputlisting` operates like `\newcommand`. The new macro `\<name>` optionally takes `<number>` arguments, where `<default>` is the default value for the optional first argument. The `<options>` are given to the underlying `tcbinputlisting`. The `<init options>` allow setting up automatic numbering, see Section 5 from page 101.

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
    listing file={#2},
    title=Listing (\thetcbcounter) of \texttt{#2},
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
{\jobname.tcbtemp}
```

Listing (2) of tcolorbox tcbtemp

This is the included file content:

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
    listing file={#2},
    title=Listing (\thetcbcounter) of \texttt{#2},
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
{\jobname.tcbtemp}
```

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
    listing engine=minted,minted language=latex,minted style=colorful,
    listing file={#2},
    title=Listing (\thetcbcounter) of \texttt{#2},
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    listing only,breakable,#1}
```

```
\mylisting[before upper=\textit{This is the included file content:}]
{\jobname.tcbtemp}
```

Listing (3) of tcolorbox tcbtemp

This is the included file content:

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
    listing engine=minted,minted language=latex,minted style=colorful,
    listing file={#2},
    title=Listing (\thetcbcounter) of \texttt{#2},
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
{\jobname.tcbtemp}
```

```
\renewtcbinputlisting[<init options>]{\<name>}[\<number>][<default>]{<options>}
```

Operates like `\newtcbinputlisting`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

15.3 Option Keys of the `listings` Library

`/tcb/listing options=<key list>` (no default, initially `style=tcblatex`)

Sets the options from the package `listings` [6] which are used during typesetting of the listing. For L^AT_EX listings, there is a predefined `listings` style named `tcblatex` which can be used.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!25,left=6mm,
listing options={style=tcblatex,numbers=left,numberstyle=\tiny\color{red!75!black}}]
This is a \LaTeX\ example which displays the text as source code
and in compiled form. Additionally, we use line numbers here.
\end{tcblisting}
```

1 This is a \LaTeX\ example which displays the text as source code
2 and in compiled form. Additionally, we use line numbers here.

This is a L^AT_EX example which displays the text as source code and in compiled form.
Additionally, we use line numbers here.

`/tcb/no listing options` (no value, initially unset)

Abbreviation for `listing options={}`. This removes all options for the `listings` package. This includes the `tcblisting` standard style `tcblatex` and the encoding presets. Use this option, if you want to set the `listings` options outside of `tcblisting`, e.g. globally in the preamble.

```
\begin{tcblisting}[no listing options]
All \textit{listings} options removed.
\end{tcblisting}
```

All `\textit{listings}` options removed.

All `listings` options removed.

`/tcb/listing style=<style>` (no default, initially `tcblatex`)

Abbreviation for `listing options={style=...}`. This key sets a `<style>` for the `listings` package, see [6]. For L^AT_EX, there is a predefined style named `tcblatex`.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,
listing style=tcblatex]
Here, we use the predefined style.
\end{tcblisting}
```

Here, we use the predefined style.

Here, we use the predefined style.

/tcb/listing inputencoding=<encoding> (no default, initially \inputencodingname)

Sets the input encoding value for the predefined listing style `tcblatex` and `tcbdocumentation` from the library [UB documentation](#). The initial value is derived from the package `inputenc` if used.

/tcb/listing remove caption=true|false (default true, initially true)

If set to `true`, some part of the caption building code of the `listings` package is silenced to prevent some unwanted interaction with the `hyperref` package resulting in additional vertical space. If set to `false`, the `listings` package code is kept unchanged. Note that listings outside `tcblisting`^{P. 288} and `\tcbinputlisting`^{P. 290} are always processed normally. Typically, a user is not expected to use this key at all.

/tcb/every listing line=<text> (no default, initially unset/empty)

Inserts some `<text>` to the begin of every line of a listing. Note that this is a hack of the `listings` package code. This may become unusable or superfluous in the future.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
listing only,listing options={style=tcblatex,language=sh},
every listing line={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}}
```

```
\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

/tcb/every listing line*=<text> (no default, initially unset/empty)

Identical to `/tcb/every listing line` plus additional enlargement of `/tcb/rightupper`^{P. 40} by the width of `<text>`. Therefore, this option has to be used after the geometry settings are done. This option is intended to be used in conjunction with `/tcb/hbox`^{P. 90}.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
listing only,listing options={style=tcblatex,language=sh},hbox,
every listing line*={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}}
```

```
\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

See further options in Section 15.6 on page 299.

! For an combined example of using `\lstinline` inside a `tcolorbox`, see `\DeclareTotalTCBox`^{P. 411}.

15.4 Option Keys of the `LIB listingsutf8` Library

The `LIB listingsutf8` library is an extension of the `LIB listings` library, so all options from Section 15.3 on page 294 are applicable.

`/tcb/listing utf8=<one-byte-encoding>` (style, no default, initially `latin1`)

Abbreviation for using `/tcb/listing inputencoding`^{→ P. 295} together with UTF-8 support from the package `listingsutf8` [10]. This option is available only for the library variant `LIB listingsutf8`. The `<one-byte-encoding>` is one of the applicable encodings from [10], e.g. `latin1`.

See further options in Section 15.6 on page 299.

15.5 Option Keys of the minted Library

`/tcb/minted language=<programming language>` (no default, initially `latex`)
Sets a `<programming language>` known to Pygments [13].

```
\begin{tcblisting}[listing engine=minted,minted style=trac,
    minted language=java,
    colback=red!5!white,colframe=red!75!black,listing only]
public class HelloWorld {
    // A 'Hello World' in Java
    public static void main(String[] args) {
        System.out.println("Hello World!");
    }
}\end{tcblisting}
```

```
public class HelloWorld {
    // A 'Hello World' in Java
    public static void main(String[] args) {
        System.out.println("Hello World!");
    }
}
```

`/tcb/minted options=<key list>` (no default, initially `tabsize=2,fontsize=\small`)
Sets the options from the package `minted` [11] which are used during typesetting of the listing.

```
% \tcbuselibrary{skins}
\newtcblisting{myjava}{listing engine=minted,minted style=colorful,
    minted language=java,minted options={fontsize=\small,linenos,numbersep=3mm},
    colback=blue!5!white,colframe=blue!75!black,listing only,
    left=5mm,enhanced,
    overlay={\begin{tcbclipinterior}\fill[red!20!blue!20!white] (frame.south west)
        rectangle ([xshift=5mm]frame.north west);\end{tcbclipinterior}}}

\begin{myjava}
public class HelloWorld {
    // A 'Hello World' in Java
    public static void main(String[] args) {
        System.out.println("Hello World!");
    }
}\end{myjava}
```

```
1  public class HelloWorld {
2      // A 'Hello World' in Java
3      public static void main(String[] args) {
4          System.out.println("Hello World!");
5      }
6  }
```

/tcb/minted style=<style> (no default, initially unset)

Sets a `<style>` known to Pygments [13]. This is independent from `/tcb/minted options`^{→ P. 297}. Note that styles are always applied globally; all following examples will be set in the given `<style>` until a new style is set. Also note that setting `\usemintedstyle{<style>}` only once per document is more economic, if all styles in a document are the same. For examples of different styles, see `/tcb/minted language`^{→ P. 297} and `/tcb/minted options`^{→ P. 297}.

See further options in Section 15.6 on the following page.

15.6 Common Option Keys of all Libraries

For the *<options>* in `\tcblisting`^{→ P. 288} respectively `\tcbinputlisting`^{→ P. 290} the following pgf keys can be applied. The key tree path `/tcb/` is not to be used inside these macros.

/tcb/listing engine=*<engine>* (no default)

Sets the *<engine>* which typesets the listings. Feasible values are

- `listings`, if library `\usepackage{listings}` or `\usepackage{listingsutf8}` is loaded.
- `minted`, if library `\usepackage{minted}` is loaded.

/tcb/listing file=*<file name>* (no default, initially `\jobname.listing`)

Sets the *<file name>* of the file which is used to save listings.

/tcb/listing and text (no value, initially set)

Typesets the environment content as listing in the upper part and as compiled text in the lower part.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing and text]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L^AT_EX example.

/tcb/text and listing (no value)

Typesets the environment content as compiled text in the upper part and as listing in the lower part.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,text and listing]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L^AT_EX example.

This is a \LaTeX\ example.

/tcb/listing only (no value)

Typesets the environment content as listing.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing only]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/text only

(no value)

Typesets the environment content as compiled text.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black, text only]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L^AT_EX example.

/tcb/comment=<text>

(no default, initially empty)

Records a comment with <text> as content. The comment is displayed e.g. in conjunction with /tcb/listing and comment^{→ P. 303} and /tcb/comment and listing^{→ P. 303}.

```
\begin{tcblisting}[comment={This comment is really only a comment},
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a \textbf{tcolorbox}.

This is a tcolorbox.

N 2014-11-17 /tcb/comment only

(no value)

Typesets the environment content with the comment text.

```
\begin{tcblisting}[comment only,
  comment={This is a comment.},
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a comment.

/tcb/image comment={<options>}{<filename>}

(style, no default, initially unset)

Uses an image denoted by <filename> as comment for the listing. The image is included by the standard \includegraphics macro with given <options>.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing side comment,
  image comment={width=2.5cm}{example-image-a.pdf},center lower]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



N 2014-11-14

/tcb/tcbimage comment=⟨filename⟩ (style, no default, initially unset)


Uses an image denoted by ⟨filename⟩ as *comment* for the listing. The image is included by the `\tcbincludegraphics`^{→ P. 241} macro. The inclusion can be customized by **/tcb/comment style**^{→ P. 303}.



The library `tib skins` is needed to apply this option.

```
% \tcbselibrary{skins}
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing side comment,
righthand width=3cm,lower separated=false,
tcbimage comment={example-image-a.pdf},
comment style={size=fbox,colframe=blue,colback=blue!50,sharp corners,
drop fuzzy shadow}]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



N 2014-11-14

/tcb/pdf comment=⟨filename⟩ (style, default listing file, initially unset)

Uses a PDF file denoted by ⟨filename⟩ as *comment* for the listing. The image is included by `\tcbincludepdf`^{→ P. 243} inside a `tcbraster`^{→ P. 268}. The inclusion can be customized by **/tcb/comment style**^{→ P. 303}.



The libraries `tib skins` and `tib raster` are needed to apply this option.

```
% \tcbuselibrary{skins,raster}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
righthand width=3cm,lower separated=false,middle=1mm,
pdf comment={tcolorbox-example.pdf},
comment style={raster columns=3,graphics pages={1,2,3},
colframe=blue,drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

1 Colored boxes

```
My box.
My box with my title
My box with my title
Upper part of my box.
Lower part of my box.

My box.
I can do this also with a title.
Lower part of my box.

Now we play box and rock. Where is the lower part?
Here I am.
For instance with you find me.

Please settings.

My box.
This box is filled with an external image.
Title and subtitle are made just to demonstrate to show the image.

This box uses a boxed title. The box of the title can be formatted independently from the main box.
```

2 IPyX-Examples

```
This is a LaTeX example:
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
righthand width=3cm,lower separated=false,middle=1mm,
pdf comment={tcolorbox-example.pdf},
comment style={raster columns=3,graphics pages={1,2,3},
colframe=blue,drop fuzzy shadow}}
This is a IPyX example:

$$\sum_{n=1}^{\infty} x^n = \frac{ax+b}{c} \quad (1)$$


```

3 Boxes

```
This is a LaTeX example:
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
righthand width=3cm,lower separated=false,middle=1mm,
pdf comment={tcolorbox-example.pdf},
comment style={raster columns=3,graphics pages={1,2,3},
colframe=blue,drop fuzzy shadow}}
This is a IPyX example:

$$\sum_{n=1}^{\infty} x^n = \frac{ax+b}{c} \quad (2)$$


```

3 Theorems

```
\textbf{Theorem 3.1} (Summation of Numbers)
For all natural numbers  $n \geq 1$  holds:

$$\sum_{k=1}^n k = \frac{n(n+1)}{2} \quad (3)$$


```

We have given Theorem 77 on page 77.

4.2 Theorem (Summation of Numbers). For all natural numbers $n \geq 1$ holds:

$$\sum_{k=1}^n k = \frac{n(n+1)}{2} \quad (4)$$

4 Watermarks

```
Box with a watermark picture:
Here you see my nice logo which is a watermark. The picture is a watermark because it is not scaled and it is not printed, neither for web or print or whatever graphical code. See the documentation for more options.
```

5 Boxes in boxes

```
Box inside box:
Box inside box inside box:
And now for some completely different stuff:
The [ ] [ ] section [ ] now.
```

6 Breakable Boxes

```
Box with a break:
Lorum ipsum dolor sit amet, consectetur adipicing elit. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa. Donec ut odio, condimentum id, pulvinar eu, tincidunt at, erat. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa. Donec ut odio, condimentum id, pulvinar eu, tincidunt at, erat. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa. Donec ut odio, condimentum id, pulvinar eu, tincidunt at, erat. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Donec ut odio, condimentum id, pulvinar eu, tincidunt at, erat. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa. Donec ut odio, condimentum id, pulvinar eu, tincidunt at, erat. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Donec ut odio, condimentum id, pulvinar eu, tincidunt at, erat. Ut purus etiam, tempor nunc. Sed arcu libero, semper eget, consectetur et, varius sit amet, massa.
```

N 2014-11-14

/tcb/pdf extension=*(extension)* (no default, initially pdf)

Sets the PDF file name extension for **/tcb/pdf comment**^{→ P. 301} to *(extension)*. Note that *(extension)* always overwrites any actual extension given inside **/tcb/pdf comment**^{→ P. 301}.

N 2014-11-14

/tcb/comment style=*(options)* (no default, initially empty)

Sets the *(options)* for **/tcb/tcbimage comment**^{→ P. 301} and **/tcb/pdf comment**^{→ P. 301}. These are **tcolorbox** options to customize the colored box drawn around the image(s), also image options encapsulated by **/tcb/graphics options**^{→ P. 244}, and **tcbraster**^{→ P. 268} options for **/tcb/pdf comment**^{→ P. 301}.

/tcb/listing and comment (no value)

Typesets the environment content as listing in the upper part and a given comment in the lower part.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing and comment,
comment={This is my comment. It may contain line breaks.\par
It can even use the environment content
\flqq\ignorespaces\tcbuselistingtext\unskip\frqq}]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is my comment. It may contain line breaks.
It can even use the environment content «This is a \LaTeX\ example.»

/tcb/comment and listing (no value)

Typesets a given comment in the upper part and the environment content as listing in the lower part.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,comment and listing,
comment={This is my comment.}]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is my comment.

This is a \LaTeX\ example.

/tcb/listing side text (no value)

Typesets the environment content side by side as listing in the left (upper) part and as compiled text in the right (lower) part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L^AT_EX example.

/tcb/text side listing (no value)

Typesets the environment content side by side as compiled text in the left (upper) part and as listing in the right (lower) part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text side listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L^AT_EX example.

This is a \LaTeX\ example.

/tcb/listing outside text (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and as compiled text outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 109.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L^AT_EX example.

/tcb/text outside listing (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and as compiled text outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 109.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text outside listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L^AT_EX example.

This is a \LaTeX\ example.

/tcb/listing side comment

(no value)

Typesets the environment content side by side as listing in the left (upper) part and a given comment in the right (lower) part.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



/tcb/comment side listing

(no value)

Typesets the environment content side by side with a given comment in the left (upper) part and as listing in the right (lower) part.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,comment side listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}]
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a \LaTeX\ example.

/tcb/listing outside comment

(no value)

Typesets the environment content side by side as listing in a `tcolorbox` and a given comment outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 109.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing outside comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



/tcb/comment outside listing

(no value)

Typesets the environment content side by side as listing in a `tcolorbox` and a given comment outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 109.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,comment outside listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}]
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a \LaTeX\ example.

/tcb/listing above text

(no value)

Typesets the environment content as listing in a **tcolorbox** and as compiled text outside and below the box. The outside text is treated as *lower* part of the **tcolorbox** and can be formatted with all lower part options. The distance between box and text is controlled by /tcb/middle^{→ P. 42}.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing above text]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L^AT_EX example.

N 2014-11-07 /tcb/listing above* text

(no value)

Widely equal to /tcb/listing above text, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by /tcb/after^{→ P. 76}.

/tcb/text above listing

(no value)

Typesets the environment content as listing in a **tcolorbox** and as compiled text outside and above the box. The outside text is treated as *lower* part of the **tcolorbox** and can be formatted with all lower part options. The distance between box and text is controlled by /tcb/middle^{→ P. 42}.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,text above listing]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L^AT_EX example.

This is a \LaTeX\ example.

N 2014-11-07 /tcb/text above* listing

(no value)

Widely equal to /tcb/text above listing, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by /tcb/before^{→ P. 76}.


/tcb/listing above comment

(no value)

Typesets the environment content as listing in a `tcolorbox` and a given comment outside and below the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and comment is controlled by `/tcb/middle`^{→ P. 42}.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,listing above comment,
  center lower,image comment={width=3cm}{example-image-a.pdf}]
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a `\LaTeX\ example.`



N 2014-11-07

/tcb/listing above* comment

(no value)


Widely equal to `/tcb/listing above comment`, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by `/tcb/after`^{→ P. 76}.

/tcb/comment above listing

(no value)

Typesets the environment content as listing in a `tcolorbox` and a given comment outside and above the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and comment is controlled by `/tcb/middle`^{→ P. 42}.

```
\begin{tcblisting}[colback=red!5!white,colframe=red!75!black,comment above listing,
  center lower,image comment={width=3cm}{example-image-a.pdf}]
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a `\LaTeX\ example.`

N 2014-11-07

/tcb/comment above* listing

(no value)

Widely equal to `/tcb/comment above listing`, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by `/tcb/before`^{→ P. 76}.

15.7 Option Keys for Processing and Full Document Examples

A complete L^AT_EX document including `\documentclass`, `\begin{document}` and `\end{document}` cannot be processed directly by `tcolorbox`. It always has to be compiled separately. There are two methods supported by the package to process and display such a full document example:

- Prepare and compile the example document independent from your main document. The source file and the resulting PDF file can be included into the main document afterwards. This is the most economic way since the example document can be left untouched after the example is complete.
- The other possibility is to compile the example on the fly while the main document is compiled. This way has some charm, because the example can be edited inside the main document. But be aware that the compilation of the example is issued on every run of the main document. Also, there are fewer degrees of freedom how the example is compiled.

For both methods, the resulting example PDF file can be included as a `/tcb/pdf` comment^{→ P. 301}.

The following example shows how to apply the first method. There already is a file `tcolorbox-example.tex` and a PDF file `tcolorbox-example.pdf`. Both of them are input partly by the following:

```
% \tcbuselibrary{breakable,skins,raster}
\tcbinputlisting{
  enhanced jigsaw,breakable,pad at break*=2mm,height fixed for=first and middle,
  lower separated=false,
  leftlower=0pt,rightlower=0pt,middle=0pt,
  colframe=red!50!black,colback=yellow!10!white,
  listing and comment,
  listing file={tcolorbox-example},
  listing options=
    {style=tcb latex,txc style=*\color{red!70!black},firstline=20,lastline=85},
  after upper={\par\bigskip\textrtt{\ldots}\par},
  pdf comment,
  comment style={drop lifted shadow,graphics pages={1,\dots,4}}},
}
```

```
\documentclass[article]
\usepackage{tikz,lipsum,lmodern}
\usepackage[most]{tcolorbox}

\begin{document}

%-----
\section{Colored boxes}

\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black]
  My box.
\end{tcolorbox}

\begin{tcolorbox}[colback=blue!5!white,colframe=blue!75!black,title=My title]
  My box with my title.
\end{tcolorbox}

\begin{tcolorbox}[colback=green!5!white,colframe=green!75!black]
  Upper part of my box.
\end{tcolorbox}
```

```

Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!5!white,colframe=yellow!50!black,
colbacktitle=yellow!75!black,title=My title]
I can do this also with a title.
\tcblower
Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,lowerbox=invisible,
savelowerto=\jobname_ex.tex]
Now, we play hide and seek. Where is the lower part?
\tcblower
I'm invisible until you find me.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,title=Here I am]
\input{\jobname_ex.tex}
\end{tcolorbox}

\begin{tcolorbox}[enhanced,sharp corners=uphill,
colback=blue!50!white,colframe=blue!25!black,coltext=yellow,
fontupper=\Large\bfseries,arc=6mm,boxrule=2mm,boxsep=5mm,
borderline={0.3mm}{0.3mm}{white}]
Funny settings.
\end{tcolorbox}

\begin{tcolorbox}[enhanced,frame style image=blueshade.png,
opacityback=0.75,opacitybacktitle=0.25,
colback=blue!5!white,colframe=blue!75!black,
title=My title]
This box is filled with an external image.\par
Title and interior are made partly transparent to show the image.
\end{tcolorbox}

\begin{tcolorbox}[enhanced,attach boxed title to top
center={yshift=-3mm,yshifttext=-1mm},
colback=blue!5!white,colframe=blue!75!black,colbacktitle=red!80!black,
title=My title,fonttitle=\bfseries,
boxed title style={size=small,colframe=red!50!black} ]
This box uses a \textit{boxed title}. The box of the title can
be formatted independently from the main box.
\end{tcolorbox}

```

...

1 Colored boxes

My box.

My title
My box with my title.

Upper part of my box.
Lower part of my box.

My title
I can do this also with a title.
Lower part of my box.

Now, we play hide and seek. Where is the lower part?

Here I am
I'm invisible until you find me.

Funny settings

My title
This box is filled with an external image.
Title and interior are made partly transparent to show the image.

My title
This box uses a *boxed* title. The box of the title can be formatted independently from the main box.

2 L^AT_EX-Examples

```
This is a LATEX example:  
\begin{equation}  
\sum\limits_{i=1}^n i = \frac{n(n+1)}{2}.  
\end{equation}
```

This is a L^AT_EX example:

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}. \quad (1)$$

Side by side

<pre>This is a L^AT_EX example: \begin{equation} \sum\limits_{i=1}^n i = \frac{n(n+1)}{2}. \end{equation></pre>	<pre>This is a L^AT_EX example: $\sum_{i=1}^n i = \frac{n(n+1)}{2}. \quad (2)$</pre>
--	--

3 Theorems

Theorem 3.1: Summation of Numbers
For all natural number n it holds:

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}. \quad (3)$$

We have given Theorem ?? on page ??.

3.2 Theorem (Summation of Numbers): For all natural number n it holds:

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}. \quad (4)$$

4 Watermarks

Box with a watermark picture

Here, you see my nice box with a picture as a watermark. This picture is automatically resized to fit the dimensions of my box. Instead of a picture, some text could be used or arbitrary graphical code. See the documentation for `\imposture`.

ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hemerobius. Curabitur malesuada ut massa. Cras euismod. Pellentesque in nulla. Cum sociis natus est, magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus hucus matri. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Sed mollis ultricies semper elit. Proin fermentum, nunc vel sem, euismod enim. Sed dictum turpis. Ut viverra nisi, id molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt tristique libero. Vivamus viverra fermentum felis. Maecenas eget quam ac purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis velit vitae risus.

Praesent euismod enim vel sem, euismod enim vel sem. Sed blandulum nulla a faucibus semper. Leo velit ultricies tellus. Aenean venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacinia quam, in hendrerit risus eros egit felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed blandulum eu lacus. Etiam semper ligula, euismod enim vel sem. Sed blandulum nulla a faucibus semper. Leo velit ultricies tellus. Aenean venenatis arcu wisi vel nisl. Matris tempor ligula sed lacinia. Duis cursus enim vel augue. Cras ac magna. Cras nulla. Nulla egistas. Curabitur a leo. Quisque egistas wisi eget nunc. Nam feugiat lacinia vel est. Curabitur consectetur. Suspendisse vel felis. Etiam lobortis enim, imperdiet etiam vel sem, lauctor etiam vel sem. Aenean faucibus etiam vel sem. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egistas dui, et convallis et, erat sed nisl. Curabitur etiam vel sem. Curabitur etiam vel sem. Aliquam dolor odio, condimentum ultricies, sem, pharetra et, velit. Integer arcu est, nonummy vel, fermentum faucibus, sapiens wisi, odio. Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit.

1

2

4 Watermarks

Box with a watermark picture

Here, you see my nice box with a picture as a watermark. This picture is automatically resized to fit the dimensions of my box. Instead of a picture, some text could be used or arbitrary graphical code. See the documentation for `\imposture`.

5 Boxes in boxes

Box



6 Breakable Boxes

Breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit. Vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras metus. Aenean rhoncus sem. Nulla et lectus vestibulum fringilla ultrices. Phasellus et tellus. Etiam nonummy vel, gravida placerat. Integer sapien est, iaculis in, purus quis, viverra ac, nunc. Praesent eget sem vel leo ultricies bibendum. Aenean faucibus, Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue enim, aliquam vel, eleifend sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae,

3

4

N 2014-11-14

/tcb/no process

(no default)

Removes all processing commands if set before.

N 2014-11-14

/tcb/process code=(code)

(no default, initially empty)

Adds `<code>` which is executed during `\tcbinputlisting→ P. 290` and `tcblisting→ P. 288`. At the time of executing the given `<code>`, the listing is already written to `/tcb/listing file→ P. 299`, but the colored box is not constructed yet. Its intended use is to process the listing somehow before displaying. The processing result can be used inside a `/tcb/comment→ P. 300`. Several `/tcb/process code` options can be given which are processed in the given order. Typically, `<code>` is added by using the following styles `/tcb/run system command`, `/tcb/run pdflatex`, etc.



To use the further options, the compiler has to be called with the `-shell-escape` permission to authorize potentially dangerous system calls. Be warned that this is a security risk. Anyway, it's more economic to compile examples independent from the main document and to include them as shown in the previous pages.

N 2014-11-14

/tcb/run system command=(system command)

(style, no default, initially unset)

Runs a `<system command>`, if the document is compiled with the `-shell-escape` permission. The current listing file can be accessed as `\filename@area\filename@base\filename@ext`. This `<system command>` is added to `/tcb/process code`.

N 2014-11-14

/tcb/compilable listing

(style, no default)

Sets `/tcb/listing file→ P. 299` to `\jobname-listing-(counter)`.



The default `/tcb/listing file→ P. 299` setting cannot be used to compile a listing, since the base name equals the `\jobname` and the included PDF files should be unique. Therefore, to use `/tcb/run pdflatex` etc., the `/tcb/listing file→ P. 299` has to be set to a unique value. One may use `/tcb/compilable listing` for this purpose.

N 2014-11-14

/tcb/run pdflatex=(arguments)

(style, no default, initially unset)

Issues a `pdflatex` compilation of the listing with the given `<arguments>`.

- The main document has to be compiled with the `-shell-escape` permission.
- The `/tcb/listing file→ P. 299` has to be unique for the listing.
- If the listing has to be compiled twice, add `run pdflatex` two times to the option list.

```
\begin{tcblisting}[enhanced jigsaw,lower separated=false,
leftlower=0pt,rightlower=0pt,
colframe=red!50!black,colback=yellow!10!white,
listing options={style=tcb latex,txcstyle=\color{red!70!black}},
listing and comment,
pdf comment,freeze pdf,
compilable listing,
run pdflatex
]
\documentclass{beamer}
\usepackage{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
\begin{block}{Hello World}
\begin{itemize}[<+->]
\item One
\item Two
\end{itemize}
\end{block}
\begin{alertblock}{Integral}
\begin{equation}

```

```

\visible<3->{\int\limits_1^x \frac{1}{t}dt}
\visible<4->{ = \ln(x).}

\end{equation}
\end{alertblock}
\end{frame}
\end{document}
\end{tcblisting}

```

```

\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
\begin{block}{Hello World}
\begin{itemize}[<+->]
\item One
\item Two
\end{itemize}
\end{block}

\begin{alertblock}{Integral}
\begin{equation}
\visible<3->{\int\limits_1^x \frac{1}{t}dt}
\visible<4->{ = \ln(x).}
\end{equation}
\end{alertblock}
\end{frame}
\end{document}

```

Beamer example

The screenshot shows a Beamer slide with a dark blue header bar containing the title 'Beamer example'. Below the header, there are two main content blocks. The first block, titled 'Hello World', contains a bulleted list with 'One' highlighted in blue. The second block, titled 'Integral', contains a mathematical equation $\int_1^x \frac{1}{t} dt$. The slide has a light gray background and a black footer bar with navigation icons.

Beamer example

This screenshot shows the same Beamer slide after the next frame has been rendered. The 'Hello World' block now shows both 'One' and 'Two' in the list. The 'Integral' block remains the same, displaying the equation $\int_1^x \frac{1}{t} dt$. The slide structure and footer are identical to the previous screenshot.

Beamer example

This screenshot shows the Beamer slide after the final frame has been rendered. Both the 'Hello World' and 'Integral' blocks remain the same as in the previous screenshots. The slide's layout and footer are consistent throughout.

Beamer example


This screenshot shows the Beamer slide after the final frame has been rendered. Both the 'Hello World' and 'Integral' blocks remain the same as in the previous screenshots. The slide's layout and footer are consistent throughout.

- N 2014-11-14 `/tcb/run xelatex=<arguments>` (style, no default, initially unset)
Issues a `xelatex` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run lualatex=<arguments>` (style, no default, initially unset)
Issues a `lualatex` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run makeindex=<arguments>` (style, no default, initially unset)
Issues a `makeindex` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run bibtex=<arguments>` (style, no default, initially unset)
Issues a `bibtex` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run biber=<arguments>` (style, no default, initially unset)
Issues a `biber` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run arara=<arguments>` (style, no default, initially unset)
Issues an `arara` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run latex=<arguments>` (style, no default, initially unset)
Issues a `latex` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run dvips=<arguments>` (style, no default, initially unset)
Issues a `dvips` compilation of the listing with the given `<arguments>`.
- N 2014-11-14 `/tcb/run ps2pdf=<arguments>` (style, no default, initially unset)
Issues a `ps2pdf` compilation of the listing with the given `<arguments>`.

```
\begin{tcblisting}{enhanced jigsaw,
    title={PSTricks with pdflatex}, fonttitle=\bfseries,
    colframe=red!50!black, colback=yellow!10!white,
    listing options={style=tcbblatex, texcsstyle=*\color{red!70!black}\color{black}},
    lower separated=false, middle=0pt,
    listing side comment, righthand width=4cm,
    compilable listing,
    run latex, run dvips, run ps2pdf,
    pdf comment, freeze pdf,
    comment style={raster columns=1,
        graphics options={viewport=0.5in 7.7in 3.5in 10.5in, clip}},
}
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01, linecolor=MyColor]{\nHue}}
\end{document}
\end{tcblisting}
```

PSTricks with pdflatex

```
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01, linecolor=MyColor]{\nHue}}
\end{document}
```



! For most applications, you will like to add `/tcb/freeze pdf` as option, since the included `pdf` file is only refreshed, if the source for this file has changed.

N 2016-07-14 `/tcb/freeze file=<file>` (no default, initially unset)

Observes some `<file>`, usually the final file produced by `/tcb/process code`^{→ P. 311}, `/tcb/run system command`^{→ P. 311}, `/tcb/run pdflatex`^{→ P. 311}, etc. If the MD5 checksum of the current `/tcb/listing file`^{→ P. 299} is unchanged and `<file>` exists, the processing is skipped and the `<file>` is kept (frozen). Typically, the style `/tcb/freeze pdf` can be used for convenience.

N 2016-07-14 `/tcb/freeze none` (no default, initially set)

Freeze no file and always execute the given process commands.

N 2016-07-14 `/tcb/freeze extension=<text>` (style, no default)

Calls `/tcb/freeze file` with the current `/tcb/listing file`^{→ P. 299} stripped with its extension plus `<text>` as new extension.

```
...
listing file=myfile.tex,
freeze extension=-modified.pdf,    % -> myfile-modified.pdf is observed
...
```

N 2016-07-14 `/tcb/freeze pdf` (no value)

Calls `/tcb/freeze file` with the current `/tcb/listing file`^{→ P. 299} stripped with its extension plus `.pdf` as new extension.

N 2016-07-14 `/tcb/freeze png` (no value)

Calls `/tcb/freeze file` with the current `/tcb/listing file`^{→ P. 299} stripped with its extension plus `.png` as new extension. See the examples for `/tcb/run pdflatex`^{→ P. 311} and `/tcb/run ps2pdf`^{→ P. 313}.

N 2016-07-14 `/tcb/freeze jpg` (no value)

Calls `/tcb/freeze file` with the current `/tcb/listing file`^{→ P. 299} stripped with its extension plus `.jpg` as new extension.

15.8 Creation of L^AT_EX Tutorials

The following source code gives a guideline for the creation of L^AT_EX tutorials. In the next section, a framework for L^AT_EX exercises is described. All examples shall be numbered optionally.

Firstly, some additional tcb keys are defined for the appearance. For the examples, three environments `texexp`, `texexptitled`, and `texexptitledspec` are defined with automatic numbering.

- `texexp` is used for untitled examples,
- `texexptitled` is used for titled examples,
- `texexptitledspec` is used for titled examples with special treatment.

Definition in the preamble:

```
\tcbset{
    texexp/.style={colframe=red!50!yellow!50!black, colback=red!50!yellow!5!white,
                   coltitle=red!50!yellow!3!white,
                   fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small},
    example/.style 2 args={texexp,
                           title={Example \thetcbcounter: #1},label={#2}},
}

\newtcblisting[texexp][1]{texexp,#1}
\newtcblisting[auto counter,number within=section]{texexptitled}[3][]{%
    example={#2}{#3},#1}
\newcolorbox[use counter from=texexptitled]{texexptitledspec}[3][]{%
    example={#2}{#3},#1}
```

```
\begin{tcblisting}[texexp]
This is a \LaTeX example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

This is a \LaTeX example which displays the text as source code
and in compiled form.

This is a L^AT_EX example which displays the text as source code and in compiled form.

```
\begin{texexptitled}{First example with a title line}{firstExample}
Here, we use Example \ref{firstExample} with a title line.
\end{texexptitled}
```

Example 15.1: First example with a title line

Here, we use Example \ref{firstExample} with a title line.

Here, we use Example 15.1 with a title line.

```
\begin{texexp}{}  
This is a \LaTeX\ example which displays the text as source code  
and in compiled form.  
\end{texexp}
```

This is a \LaTeX\ example which displays the text as source code
and in compiled form.

This is a LATEX example which displays the text as source code and in compiled form.

```
\begin{texexp}{text and listing}  
This is a \LaTeX\ example which displays the text as source code  
and in compiled form.  
\end{texexp}
```

This is a LATEX example which displays the text as source code and in compiled form.

This is a \LaTeX\ example which displays the text as source code
and in compiled form.

```
\begin{texexp}{listing only}  
This is a \LaTeX\ example which displays the text as source code only.  
\end{texexp}
```

This is a \LaTeX\ example which displays the text as source code only.

```
\begin{texexp}{text only}  
This is a \LaTeX\ example which displays the text in compiled form only.  
\end{texexp}
```

This is a LATEX example which displays the text in compiled form only.

```
\begin{texexptitled}{An Example with a Heading}{heading1}  
This is a \LaTeX\ example with a numbered heading line  
which can be referred to.  
\end{texexptitled}  
Here, we see Example \ref{heading1}.
```

Example 15.2: An Example with a Heading

This is a \LaTeX\ example with a numbered heading line
which can be referred to.

This is a LATEX example with a numbered heading line which can be referred to.

Here, we see Example 15.2.

```
\begin{texexptitled}[listing only]{Another Example with a Heading}{heading2}
The keys can be used in combination. Here, an example with a heading line
and source code only is given.
\end{texexptitled}
Here, we see Example \ref{heading2}.
```

Example 15.3: Another Example with a Heading

The keys can be used in combination. Here, an example with a heading line and source code only is given.

Here, we see Example 15.3.

```
\begin{texexptitled}[float]{A floating Example with a Heading}{heading3}
This is another \LaTeX\ example with numbered heading line.
But now, the box is a floating object.
\end{texexptitled}
```

Example 15.4: A floating Example with a Heading

This is another \LaTeX\ example with numbered heading line.
But now, the box is a floating object.

This is another \LaTeX\ example with numbered heading line. But now, the box is a floating object.

The floating box of the last example is seen as Example \ref{heading3} on page \pageref{heading3}.

The floating box of the last example is seen as Example 15.4 on page 317.

```
\begin{texexptitledspec}{Special application}{texexpbox1}
\begin{lstlisting}[style=tcblatex]
Some \LaTeX\ source code.
\end{lstlisting}
\tcblower
For special cases, the environment |texexptitledspec| with style
|example| can be used directly. As one can see, the upper and the lower
part of the box can be used uncoupled also.
\end{texexptitledspec}
```

Example 15.5: Special application

Some \LaTeX\ source code.


For special cases, the environment `texexptitledspec` with style `example` can be used directly. As one can see, the upper and the lower part of the box can be used uncoupled also.

The following series of examples demonstrate the application of `tcolorbox`^{P.12} options for diversification.

```
\begin{texexptitled}{How to use options (1)}{\par The basic example}{options1}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

**Example 15.6: How to use options (1):
The basic example**


```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,enhanced,segmentation hidden,middle=0mm]{How to use options (2)}{\par The text output is centered and the  
segmentation line has vanished.}{options2}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

**Example 15.7: How to use options (2):
The text output is centered and the segmentation line has vanished.**

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```




```
\begin{texexptitled}[tikz lower,bicolor,colbacklower=white]
{How to use options (3):\par Here, the |tikzpicture| is totally hidden.
The |bicolor| skin highlights the output.}{options3}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{texexptitled}
```

Example 15.8: How to use options (3):

Here, the `tikzpicture` is totally hidden. The `bicolor` skin highlights the output.

```
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
```




```
\begin{texexptitled}[center lower,listing side text,righthand width=3.5cm,
bicolor,colbacklower=white]
{How to use options (4):\par The |bicolor| skin also works with side
by side mode}{options4}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 15.9: How to use options (4):

The `bicolor` skin also works with side by side mode


```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}
```




```
\begin{tikzpicture}[center lower,listing outside text,righthand width=3.5cm]
{How to use options (5):\par Putting our picture outside is just
 a matter of one word.}{options5}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
 (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{tikzpicture}
```

**Example 15.10: How to use options (5):
Putting our picture outside is just a matter of one word.**

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
 (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{tikzpicture}[center lower,text above listing]
{How to use options (6):\par The picture may also be put above
 the listing box.}{options6}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
 (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{tikzpicture}
```




**Example 15.11: How to use options (6):
The picture may also be put above the listing box.**

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
 (\w:1cm) circle (7mm);}
\end{tikzpicture}
```

```
\begin{texexptitled}[beamer,center lower,text outside listing,lefthand width=3.5cm]
{How to use options (7):\par Our style is easily transformed into
a beamerish one.}{options7}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 15.12: How to use options (7):
Our style is easily transformed into a beamerish one.



```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}
```

15.9 Creation of L^AT_EX Exercises

In the following, a guideline is given for the creation of L^AT_EX exercises with solutions. These solutions are saved to disk for application at a place of choice. Therefore, all used exercises are logged to a file `\jobname.records` for automatic processing. The solution contents themselves are saved to a subdirectory named `solutions`. Also see Section 8 on page 120.

- Before the first exercise is given, `\tcbstartrecording`^{P. 120} has to be called to start recording.
- The solution is given as content of a `tcboutputlisting`^{P. 290} environment. Note, that you can use this content also inside the exercise with `\tcbuselistingtext`^{P. 290} in compiled form.
- After the last exercise is given (and before using the solutions), `\tcbstoprecording`^{P. 120} has to be called to stop recording.
- The solutions are loaded by `\tcbinputrecords`^{P. 120}.

Inside the exercise text, there may be text parts which are needed as L^AT_EX source code and as compiled text as well. These parts can be saved by `tcbwritetemp`^{P. 119} and used in compiled form by `\tcbusetemp`^{P. 119} or as source code by `\tcbusetemplisting`^{P. 290}.

At first, we generate some a common style for the exercises and the solutions. Further, since exercises and solutions should be numbered, we force to use a label `<marker>`. Automatically, the label `exe:<marker>` is used to mark the exercise and the label `sol:<marker>` is used to mark the solution.

```
\tcbset{texercise/.style={arc=0.5mm, colframe=blue!25!yellow!90!white,
  colback=blue!25!yellow!5!white, coltitle=blue!25!yellow!40!black,
  fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small,
  listing options={style=tcbflatex,texcsstyle=*\color{red!40!black}}},
  }
```

With these preparations, the kernel environment `texercise` for our exercises is created quickly:

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section,list inside=exam]{texercise}[2][]{%
  texercisestyle,
  listing file={solutions/texercise\thetcbcounter.tex},
  label={exe:#2},
  record={\string\processsol{solutions/texercise\thetcbcounter.tex}{#2}},
  title={Exercise \thetcbcounter\hfill\mdseries Solution on page \pageref{sol:#2}},
  list text={Exercise with solution on page \pageref{sol:#2}},#1}
```

The following examples demonstrate the application.

```
\tcbstartrecording
```

```
\begin{texercise}{tabular_example}
\textit{Create the following table:}\par\smallskip%
\begin{tcboutputlisting}
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries \itshape Das alte Italien}\\\hline
\multicolumn{2}{|c|}{\bfseries \itshape Antike} &
\multicolumn{2}{|c|}{\bfseries \itshape Mittelalter}\\\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{|c|}{\itshape Kaiserreich}&
\multicolumn{1}{|c|}{\itshape Franken}&
\multicolumn{1}{|c|}{\itshape Teilstaaten}\\\hline
In den Zeiten der römischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das römische Kaiserreich wurde von einem Alleinherrschер, dem Kaiser,
regiert.
& In der Völkerwanderungszeit übernahmen die Goten und später die
Franken die Vorherrschaft.
& Im späteren Mittelalter regierten Fürsten einen Fleckenteppich
von Einzelstaaten.\\\hline
\end{tabular}
\end{tcboutputlisting}
\tcbuselistingtext%
\end{texercise}
```

Exercise 15.1

Solution on page 326

Create the following table:

Das alte Italien			
Antike		Mittelalter	
Republik	Kaiserreich	Franken	Teilstaaten
In den Zeiten der römischen Republik standen dem Staat jeweils zwei Konsuln vor, deren Machtbefugnisse identisch waren.	Das römische Kaiserreich wurde von einem Alleinherrschер, dem Kaiser, regiert.	In der Völkerwanderungszeit übernahmen die Goten und später die Franken die Vorherrschaft.	Im späteren Mittelalter regierten Fürsten einen Fleckenteppich von Einzelstaaten.

```

\begin{texercise}{macro_oneparam}
\begin{tcboutputlisting}
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%


Create a new macro \verb+\headingline+ which produces the
following output:\par\smallskip
\begin{tcbwritetemp}
\headingline{Very important heading}
\end{tcbwritetemp}
\tcbusetemp\listing\tcbusetemp%
\end{texercise}

```

Exercise 15.2

Solution on page 326

Create a new macro `\headingline` which produces the following output:

```
\headingline{Very important heading}
```

Very important heading

```

\begin{texercise}{macro_twoparam}
\begin{tcboutputlisting}
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
    \multicolumn{1}{c}{\bfseries#1}\hline%
    #2\hline%
  \end{tabular}\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%


Create a new macro \verb+\minitable+ which produces the
following output:\par\smallskip
\begin{tcbwritetemp}
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
\end{tcbwritetemp}
\tcbusetemp\listing\par\smallskip\tcbusetemp%
\end{texercise}

```

Exercise 15.3

Solution on page 326

Create a new macro `\minitable` which produces the following output:

```
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
```

My heading

In this tiny tabular, there is only a heading and some text below
which has a width of ten centimeters.

```

\begin{texercise}{macro_threeparam}
\begin{tcboutputlisting}
\newcommand{\synop}[3]{%
\begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
\multicolumn{2}{c}{\bfseries #1}\hline
\multicolumn{1}{c|}{\itshape English}&
\multicolumn{1}{c}{\itshape German}\hline
#2 & #3
\end{tabular}}
\end{tcboutputlisting}
\tcbuselistingtext%
Create a new macro \verb+\synop+ which typesets a synoptic text according
to the following example. Base your macro on a tabular which takes the
total line width.\par\smallskip
\begin{tcbwritetemp}
\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"ur einen Mann,
ein riesiger Sprung f\"ur die Menschheit.}%
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbwritetemp%
\end{texercise}

```

Exercise 15.4

Solution on page 327

Create a new macro `\synop` which typesets a synoptic text according to the following example. Base your macro on a tabular which takes the total line width.

```

\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"ur einen Mann,
ein riesiger Sprung f\"ur die Menschheit.}

```

Neil Armstrong

<i>English</i>	<i>German</i>
That's one small step for a man, one giant leap for mankind.	Das ist ein kleiner Schritt für einen Mann, ein riesiger Sprung für die Menschheit.

\tcbstoprecording

Now, we give a list of all exercises with:

```

\tcblistof[\subsection]{exam}{List of Exercises%
\label{listofexercises}}

```

15.10 List of Exercises

15.1 Exercise with solution on page 326	323
15.2 Exercise with solution on page 326	324
15.3 Exercise with solution on page 326	324
15.4 Exercise with solution on page 327	325

15.11 Solutions for the given L^AT_EX Exercises

For all solutions, a macro `\processsol` was written to the file `\jobname.records`. Now, we need a definition for this macro to use the solutions.

```
% \usepackage{hyperref} % for phantomlabel
\newtcbinputlisting{\processsol}[2]{%
texercise,
listing only,
listing file={#1},
phantomlabel={sol:#2},%
title={Solution for Exercise \ref{exe:#2} on page \pageref{exe:#2}},%
}
```

The loading of all solutions is done by:

```
\tcbinputrecords
```

With this, we get:

Solution for Exercise 15.1 on page 323

```
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\hline
\multicolumn{2}{|c|}{\bfseries Antike} &
\multicolumn{2}{|c|}{\bfseries Mittelalter}\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{|c|}{\itshape Kaiserreich}&
\multicolumn{1}{|c|}{\itshape Franken}&
\multicolumn{1}{|c|}{\itshape Teilstaaten}\hline
In den Zeiten der r\"omischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das r\"omische Kaiserreich wurde von einem Alleinherrschter, dem Kaiser,
regiert.
& In der V\"okerwanderungszeit \"ubernahmen die Goten und sp\"ater die
Franken die Vorherrschaft.
& Im sp\"ateren Mittelalter regierten F\"ursten einen Fleckenteppich
von Einzelstaaten.\hline
\end{tabular}
```

Solution for Exercise 15.2 on page 324

```
\newcommand{\headingline}[1]{%
\begin{center}\Large\bfseries #1\end{center}}
```

Solution for Exercise 15.3 on page 324

```
\newcommand{\minitable}[2]{%
\begin{center}\begin{tabular}{p{10cm}}\hline%
\multicolumn{1}{c}{\bfseries#1}\hline%
#2\hline%
\end{tabular}\end{center}}
```

Solution for Exercise 15.4 on page 325

```
\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
  \multicolumn{2}{c}{\bfseries #1}\hline
  \multicolumn{1}{c|}{\itshape English}&
  \multicolumn{1}{c}{\itshape German}\hline
  #2 & #3
  \end{tabular}}
```

16 Library LIB theorems

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{theorems}
```

This also loads the package `amsmath`.

16.1 Macros of the Library

U 2016-06-22

```
\newtcbtheorem[<init options>]{<name>}{<display name>}{<options>}{<prefix>}
```

Creates new environments `<name>` and `<name>*` based on `tcolorbox` to frame a (mathematical) theorem. The `<display name>` is used in the title line with a number, e.g. «Theorem 5.1». The `<options>` are given to the underlying `tcolorbox` to control the appearance. The `<init options>` allow setting up automatic numbering, see Section 5 on page 101. The new environment `<name>` takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and is also set as `/tcb/nameref`^{P.95} identifier. The second mandatory parameter is a `<marker>`. The theorem is automatically labeled with `<prefix><separator><marker>` where `<separator>` is predefined as `:`, see `/tcb/label separator`^{P.335}.

The new environment `<name>*` takes one optional and one mandatory parameter and represents an unnumbered variant of the environment `<name>`. This variant is not labeled and not listed in lists of theorems.

Definition in the preamble:

```
\newtcbtheorem[number within=section]{mytheo}{My Theorem}%
  {colback=green!5,colframe=green!35!black,fonttitle=\bfseries}{th}
```

```
\begin{mytheo}{This is my title}{theoexample}
  This is the text of the theorem. The counter is automatically assigned and,
  in this example, prefixed with the section number. This theorem is numbered with
  \ref{th:theoexample} and is given on page \pageref{th:theoexample}.
\end{mytheo}
```

My Theorem 16.1: This is my title

This is the text of the theorem. The counter is automatically assigned and, in this example, prefixed with the section number. This theorem is numbered with 16.1 and is given on page 328.

```
\begin{mytheo}[label=myownlabel]{This is my title}{}%
  The label parameter can be left empty without \LaTeX\ error.
  Or you may use an own label to reference Theorem \ref{myownlabel}.
\end{mytheo}
```

My Theorem 16.2: This is my title

The label parameter can be left empty without L^AT_EX error. Or you may use an own label to reference Theorem 16.2.

```
\begin{mytheo}{}{}  
The title can also be left empty without problem. Note that the ':'  
vanished magically.  
\end{mytheo}
```

My Theorem 16.3

The title can also be left empty without problem. Note that the ':' vanished magically.

```
\begin{mytheo*}[Unnumbered Theorem]  
This theorem is not numbered.  
\end{mytheo*}
```

My Theorem: Unnumbered Theorem

This theorem is not numbered.

```
\begin{mytheo*}[]  
This theorem has no number and no title.  
\end{mytheo*}
```

My Theorem

This theorem has no number and no title.

\renewtcbtheorem [*init options*] {*(name)*} {*(display name)*} {*(options)*} {*(prefix)*}

Operates like **\newtcbtheorem**^{→ P. 328}, but based on **\renewenvironment** instead of **\newenvironment**. An existing environment is redefined.

\tcbsmaketheorem {*(name)*} {*(display name)*} {*(options)*} {*(counter)*} {*(prefix)*}

! **\newtcbtheorem**^{→ P. 328} supersedes this macro.

Creates a new environment *(name)* based on **tcolorbox** to frame a (mathematical) theorem. The *(display name)* is used in the title line with a number, e.g. «Theorem 5.1». The *(options)* are given to the underlying **tcolorbox** to control the appearance. The *(counter)* is used for automatic numbering. The new environment *(name)* takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and the second mandatory parameter is a *(marker)*. The theorem is automatically labeled with *(prefix)**(separator)**(marker)* where *(separator)* is predefined as ':', see **/tcb/label separator**^{→ P. 335}.

\tcbboxmath[*options*]{*mathematical box content*}

Creates a `tcolorbox`^{P.12} which is fitted to the width of the given *mathematical box content*. This box is intended to be applied as part of a larger formula and may be used as replacement for the `\boxed` macro of `amsmath`.

```
\begin{equation}
\tcbset{fonttitle=\scriptsize}
\tcbboxmath[colback=LightBlue!25!white,colframe=blue]{ a^2 = 16 }
\quad \Rightarrow \quad
\tcbboxmath[colback=Salmon!25!white,colframe=red,title=Implication]%
{ a = 4 \vee a=-4. }
\end{equation}
```

$$a^2 = 16 \quad \Rightarrow \quad \text{Implication} \quad a = 4 \vee a = -4. \quad (3)$$

\tcbhighmath[*options*]{*mathematical box content*}

This is a special case of the `\tcbboxmath` macro which uses the style `/tcb/highlight math`^{P.337}. It is intended to provide context sensitive highlighting of formula parts. The color settings via `/tcb/highlight math style`^{P.337} may be different inside theorems or other colored areas and outside.

```
\tcbset{myformula/.style={colback=yellow!10!white,colframe=red!50!black,
every box/.style={highlight math style={colback=LightBlue!50!white,colframe=Navy}}}

\begin{align}
\tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty. \\
\int x^2 dx &= \frac{1}{3}x^3 + c.}
\end{align}

\begin{tcolorbox}[ams align,myformula]
\tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty. \\
\int x^2 dx &= \frac{1}{3}x^3 + c.}
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (4)$$

$$\int x^2 dx = \frac{1}{3}x^3 + c. \quad (5)$$

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (6)$$

$$\int x^2 dx = \frac{1}{3}x^3 + c. \quad (7)$$

`\tcbhighmath`^{P. 330} can be used in symbiosis with the `empheq` package which allows to specify own boxing commands to mark multiline formulas.

```
% \usepackage{empheq}
\begin{empheq}[box=\tcbhighmath]{align}
a &= \sin(z) \\
E &= mc^2 + \int_a^b x \, dx
\end{empheq}

\tcbset{highlight math style={enhanced,
    colframe=red!60!black, colback=yellow!50!white, arc=4pt, boxrule=1pt,
    drop fuzzy shadow}}


\begin{empheq}[box=\tcbhighmath]{align}
a &= \sin(z) \\
E &= mc^2 + \int_a^b x \, dx
\end{empheq}
```

$$a = \sin(z) \tag{8}$$

$$E = mc^2 + \int_a^b x \, dx \tag{9}$$

$$a = \sin(z) \tag{10}$$

$$E = mc^2 + \int_a^b x \, dx \tag{11}$$

Besides `\tcbhighmath`^{P. 330}, one can easily define an independent new box based on `\tcbbox`^{P. 14} which acts like `\tcbhighmath`^{P. 330}:

```
% \usepackage{empheq}
\newtcbox{\otherbox}[1][]{nobeforeafter,math upper,tcbox raise base,
    enhanced,frame hidden,boxrule=0pt,interior style={top color=green!10!white,
    bottom color=green!10!white,middle color=green!50!yellow},
    fuzzy halo=1pt with green,#1}

\begin{empheq}[box=\otherbox]{align}
a &= \sin(z) \\
E &= mc^2 + \int_a^b x \, dx
\end{empheq}

\begin{equation}
\tcbhighmath{E} = \otherbox{mc^2}
\end{equation}
```

$$a = \sin(z) \tag{12}$$

$$E = mc^2 + \int_a^b x \, dx \tag{13}$$

$$\boxed{E} = \boxed{mc^2} \tag{14}$$

16.2 Option Keys of the Library

/tcb/separator sign=*sign*

(no default, initially :)

The given *sign* is used inside the title text of a theorem as separator between display name combined with number and the specific title text. It is omitted, if there is no specific title text.

```
% \usepackage{amssymb}
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign={\ $\blacktriangleright$}}{theo}
\begin{sometheorem}{My example}{}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.4 ▶ My example

My theorem text.

/tcb/separator sign colon

(style, no value, initially set)

Sets /tcb/separator sign to the default colon : sign.

/tcb/separator sign dash

(style, no value)

Sets /tcb/separator sign to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign dash}{theo}
\begin{sometheorem}{My example}{}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.5 – My example

My theorem text.

/tcb/separator sign none

(style, no value)

Sets /tcb/separator sign to empty.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign none}{theo}
\begin{sometheorem}{My example}{}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.6 My example

My theorem text.

/tcb/description delimiters={⟨left⟩}{⟨right⟩} (no default, initially empty)

The given ⟨left⟩ and ⟨right⟩ delimiter signs are used to frame the descriptive title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 description delimiters={\flqq}{\frqq}{theo}}
\begin{sometheorem}{My example}{}\\
My theorem text.
\end{sometheorem}
```

Theorem 16.7: «My example»

My theorem text.

/tcb/description delimiters parenthesis (style, no value)

Sets /tcb/description delimiters to (and).

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 description delimiters parenthesis}{theo}
\begin{sometheorem}{My example}{}\\
My theorem text.
\end{sometheorem}
```

Theorem 16.8: (My example)

My theorem text.

/tcb/description delimiters none (style, no value, initially set)

Sets /tcb/description delimiters to the default empty texts.

/tcb/description color=⟨color⟩ (default empty, initially empty)

Sets the ⟨color⟩ of the descriptive title text deviating from /tcb/colttitle^{→ P. 28}. The color is reset to /tcb/colttitle^{→ P. 28}, if description color is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 description color=red!25!yellow}{theo}
\begin{sometheorem}{My example}{}\\
My theorem text.
\end{sometheorem}
```

Theorem 16.9: My example

My theorem text.

/tcb/description font=*(text)* (default empty, initially empty)

Sets *(text)* (e.g. font settings) before the descriptive title text deviating from **/tcb/fonttitle**^{→ P. 29}. The *(text)* is removed, if **description font** is used without value.

```
\new tcbtheorem [use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 description delimiters={\glqq}{\grqq},
 description font=\mdseries\itshape}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.10: „*My example*“

My theorem text.

/tcb/description formatter=*(macro)* (default empty, initially empty)

Sets *(macro)* as formatter for the descriptive title text. The *(macro)* has to take one mandatory argument (the description text).

Note that **/tcb/description delimiters**^{→ P. 333}, **/tcb/description color**^{→ P. 333}, and **/tcb/description font** are ignored, if this option is used.

If **description formatter** is used without value, the formatter is reset to its standard behavior.

```
\newtcbbox{\formbox}{enhanced,frame empty,size=minimal,boxsep=2pt,arc=1pt,
on line,interior style image=goldshade.png}

\new tcbtheorem [use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 description formatter=\formbox}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.11: **My example**

My theorem text.

/tcb/terminator sign=*(sign)* (no default, initially empty)

The given *(sign)* is used as terminator at the end of the title text of a theorem.

```
\new tcbtheorem [use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 terminator sign={.}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.12: **My example.**

My theorem text.

/tcb/terminator sign colon

(style, no value, initially set)

Sets /tcb/terminator sign^{→ P. 334} to the colon : sign.

```
\new tcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign dash,terminator sign colon}{theo}
\begin{sometheorem}{My example}{}%
My theorem text.
\end{sometheorem}
```

Theorem 16.13 – My example:

My theorem text.

/tcb/terminator sign dash

(style, no value)

Sets /tcb/terminator sign^{→ P. 334} to an en-dash sign.

```
\new tcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 terminator sign dash}{theo}
\begin{sometheorem}{My example}{}%
My theorem text.
\end{sometheorem}
```

Theorem 16.14: My example –

My theorem text.

/tcb/terminator sign none

(style, no value)

Sets /tcb/terminator sign^{→ P. 334} to the default empty text.**/tcb/label separator=<separator>**

(no default, initially :)

The given <separator> is used for labels created with environments which are defined themselves by \new tcbtheorem^{→ P. 328}. This <separator> is put between <prefix> (defined by \new tcbtheorem^{→ P. 328}) and <marker> (defined by an actual theorem environment).

```
\new tcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 label separator=--}{theo}
\begin{sometheorem}{My example}{myex}%
My theorem text.
\end{sometheorem}
See Example~\ref{theo*myex}.
```

Theorem 16.15: My example

My theorem text.

See Example 16.15.

/tcb/theorem name and number (style, no value, initially set)

Prints theorem name followed by theorem number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 theorem name and number}{theo}
\begin{sometheorem}{My example}{}%
My theorem text.
\end{sometheorem}
```

Theorem 16.16: My example

My theorem text.

/tcb/theorem number and name (style, no value)

Prints theorem number followed by theorem name inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 theorem number and name}{theo}
\begin{sometheorem}{My example}{}%
My theorem text.
\end{sometheorem}
```

16.17 Theorem: My example

My theorem text.

/tcb/theorem name (style, no value)

Prints theorem name without number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 theorem name,enhanced,watermark text=\thetcbcounter}{theo}
\begin{sometheorem}{My example}{}%
My theorem text.
\end{sometheorem}
```

Theorem: My example

My theorem text.

16.18

/tcb/theorem={⟨display name⟩}{⟨counter⟩}{⟨title⟩}{⟨marker⟩} (no default)

This key is internally used by `\tcbmaketheorem`^{→ P. 329}, but can be used directly in a `tcolorbox` for a more flexible approach. The ⟨display name⟩ is used together with the increased ⟨counter⟩ value and the ⟨title⟩ for the title line of the box. Additionally, a `\label` with the given ⟨marker⟩ is created.

```
% \newcounter{texercise}% preamble
\begin{tcolorbox}[colback=green!10,colframe=green!50!black,arc=4mm,
    theorem={Test}{texercise}{Direct usage}{myMarker}]
Here, we see the test \ref{myMarker}.
\end{tcolorbox}
```

Test 1: Direct usage

Here, we see the test 1.

For a common appearance inside the document, the key `theorem` should not be used directly as in the example above, but as part of a new environment created by hand or using `\tcbmaketheorem`^{→ P. 329} or using its successor `\newtcbtheorem`^{→ P. 328}.

/tcb/highlight math (style, no value)

Predefined style which is used for `\tcbhighmath`^{→ P. 330}. It can be changed comfortable with `/tcb/highlight math style`.

/tcb/highlight math style=⟨style definition⟩ (style, no default)

Changes the definition for `/tcb/highlight math` to the given ⟨style definition⟩. See `\tcbhighmath`^{→ P. 330} for another example.

```
% \tcbuselibrary{skins}
\tcbset{highlight math style={enhanced,%<-- needed for the 'remember' options
    colframe=red,colback=red!10!white,boxsep=0pt}}
\begin{align*}
\tcbhighmath[remember as=fx]{f(x)}
&= \int_1^x \frac{1}{t^2} dt = \left[ -\frac{1}{t} \right]_1^x \\
&= -\frac{1}{x} + \frac{1}{1} \\
&= 1 - \frac{1}{x}.
\end{align*}
```

$$\begin{aligned} f(x) &= \int_1^x \frac{1}{t^2} dt = \left[-\frac{1}{t} \right]_1^x \\ &= -\frac{1}{x} + \frac{1}{1} \\ &= 1 - \frac{1}{x}. \end{aligned}$$

/tcb/math upper (style, no value)

Sets the upper part to mathematical mode with font `\displaystyle`.

/tcb/math lower (style, no value)

Sets the lower part to mathematical mode with font `\displaystyle`.

/tcb/math (style, no value)

Sets the upper part *and* lower part to mathematical mode with font `\displaystyle`.

```
\begin{tcolorbox}[math,colback=yellow!10!white,colframe=red!50!black]
 \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$



The following styles are only tested to work with the original `amsmath` environments. If e.g. the `equation` environment is redefined as `gather`, then `/tcb/ams equation` should / could not be used. Obviously, you are encouraged to use `/tcb/ams gather` → P. 340 in this case.

U 2014-10-30 /tcb/ams equation upper (style, no value)

Adds an `amsmath equation` environment to the start and end of the upper part.

U 2014-10-30 /tcb/ams equation lower (style, no value)

Adds an `amsmath equation` environment to the start and end of the lower part.

U 2014-10-30 /tcb/ams equation (style, no value)

Adds an `amsmath equation` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation,colback=yellow!10!white,colframe=red!50!black]
 \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{15}$$

U 2014-10-30 /tcb/ams equation* upper (style, no value)

Adds an `amsmath equation*` environment to the start and end of the upper part.

U 2014-10-30 /tcb/ams equation* lower (style, no value)

Adds an `amsmath equation*` environment to the start and end of the lower part.

U 2014-10-30 /tcb/ams equation* (style, no value)

Adds an `amsmath equation*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation*,colback=yellow!10!white,colframe=red!50!black]
 \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

/tcb/ams align upper (style, no value)

Adds an `\begin{aligned}` environment to the start and end of the upper part.

/tcb/ams align lower (style, no value)

Adds an `\end{aligned}` environment to the start and end of the lower part.

/tcb/ams align (style, no value)

Adds an `\begin{aligned}` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty. \\
  \int x^2 \, dx &= \frac{1}{3}x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (16)$$

$$\int x^2 \, dx = \frac{1}{3}x^3 + c. \quad (17)$$

/tcb/ams align* upper (style, no value)

Adds an `\begin{aligned*}` environment to the start and end of the upper part.

/tcb/ams align* lower (style, no value)

Adds an `\end{aligned*}` environment to the start and end of the lower part.

/tcb/ams align* (style, no value)

Adds an `\begin{aligned*}` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty. \\
  \int x^2 \, dx &= \frac{1}{3}x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \, dx = \frac{1}{3}x^3 + c.$$

/tcb/ams gather upper (style, no value)

Adds an `amsmath` `gather` environment to the start and end of the upper part.

/tcb/ams gather lower (style, no value)

Adds an `amsmath` `gather` environment to the start and end of the lower part.

/tcb/ams gather (style, no value)

Adds an `amsmath` `gather` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams_gather,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty. \\
  \int x^2 \, dx = \frac{1}{3}x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (18)$$

$$\int x^2 \, dx = \frac{1}{3}x^3 + c. \quad (19)$$

/tcb/ams gather* upper (style, no value)

Adds an `amsmath` `gather*` environment to the start and end of the upper part.

/tcb/ams gather* lower (style, no value)

Adds an `amsmath` `gather*` environment to the start and end of the lower part.

/tcb/ams gather* (style, no value)

Adds an `amsmath` `gather*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams_gather*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty. \\
  \int x^2 \, dx = \frac{1}{3}x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \, dx = \frac{1}{3}x^3 + c.$$

`/tcb/ams nodisplayskip upper` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part. Note that the text content has to start with such a formula.

`/tcb/ams nodisplayskip lower` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the lower part. Note that the text content has to start with such a formula.

`/tcb/ams nodisplayskip` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part *and* lower part. Note that the text content has to start with such a formula.

```
\begin{tcolorbox}[ams nodisplayskip,colback=yellow!10!white,colframe=red!50!black]
\begin{gather}
\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \\
\int x^2 \, dx = \frac{1}{3}x^3 + c.
\end{gather}
And now for something completely different.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (20)$$

$$\int x^2 \, dx = \frac{1}{3}x^3 + c. \quad (21)$$

And now for something completely different.

New colored mathematical environments are easily created using `\newtcolorbox`^{→ P. 15}:

```
\newtcolorbox{mymath}{ams gather*,colback=yellow!10!white,colframe=red!50!black}

\begin{mymath}
\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \\
\int x^2 \, dx = \frac{1}{3}x^3 + c.
\end{mymath}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$
$$\int x^2 \, dx = \frac{1}{3}x^3 + c.$$

All described options like `/tcb/ams gather upper`^{→ P. 340}, `/tcb/ams gather lower`^{→ P. 340}, `/tcb/ams gather`^{→ P. 340} are (partially) setting (overwriting) the keys `/tcb/before upper`^{→ P. 63}, `/tcb/after upper`^{→ P. 63}, `/tcb/before lower`^{→ P. 64}, `/tcb/after lower`^{→ P. 64}.

! Therefore, e.g. `\tcbset{ams gather,before upper={\text{Pythagoras:}}}` produces an invalid result. For this case, you are invited to use `\tcbset{ams gather,before upper app={\text{Pythagoras:}}}`, see `/tcb/before upper app`^{→ P. 395}.

`/tcb/theorem style=<name>` (no default, initially `standard`)

Applies a predefined style `<name>` to the theorem environment. Some of the feasible `<name>` values resemble style names from the packages `theorem` and `ntheorem` to give convenient access to known patterns.

! The styles alter `/tcb/separator sign`^{P.332}, `/tcb/description delimiters`^{P.333}, `/tcb/terminator sign`^{P.334}, and more. Therefore, one should apply such keys *after* a theorem style.

For the following examples, we use:

Definition in the preamble:

```
\newtcbtheorem[use counter from=mytheo]{theorem}{Theorem}{%
    fonttitle=\bfseries\upshape,fontupper=\itshape,
    colframe=green!50!black,colback=green!10!white,
    colbacktitle=green!20!white,coltitle=blue!75!black}{theo}
```

The predefined styles are:

- `standard`: This is the initial value.

```
\begin{theorem}[theorem style=standard]{standard}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

Theorem 16.19: standard

This is my theorem.

$$a^2 + b^2 = c^2.$$

- `change standard`

```
\begin{theorem}[theorem style=change standard]{change standard}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.20 Theorem: change standard

This is my theorem.

$$a^2 + b^2 = c^2.$$

- `plain`

```
\begin{theorem}[theorem style=plain]{plain}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

Theorem 16.21 (plain): This is my theorem.

$$a^2 + b^2 = c^2.$$

- **break**

```
\begin{theorem}[theorem style=break]{break}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

Theorem 16.22 (break):

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **plain apart**

```
\begin{theorem}[theorem style=plain apart]{plain apart}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

Theorem 16.23 (plain apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **change**

```
\begin{theorem}[theorem style=change]{change}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.24 Theorem (change): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **change break**

```
\begin{theorem}[theorem style=change break]{change break}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.25 Theorem (change break):

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **change apart**

```
\begin{theorem}[theorem style=change apart]{change apart}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.26 Theorem (change apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **margin**

```
\begin{theorem}[theorem style=margin, left=10mm]{margin}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}  
\begin{theorem}[theorem style=margin, left=10mm, oversize]{margin}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.27 Theorem (margin): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

16.28 Theorem (margin): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **margin break**

```
\begin{theorem}[theorem style=margin break, left=10mm]{margin break}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}  
\begin{theorem}[theorem style=margin break, left=10mm, oversize]{margin break}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.29 Theorem (margin break):

This is my theorem.

$$a^2 + b^2 = c^2.$$

16.30 Theorem (margin break):

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **margin apart**

```
\begin{theorem}[theorem style=margin apart, left=10mm]{margin apart}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}  
\begin{theorem}[theorem style=margin apart, left=10mm, oversize]{margin apart}{}  
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}  
\end{theorem}
```

16.31 Theorem (margin apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

16.32 Theorem (margin apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

16.3 Examples for Definitions and Theorems

In the following, the application of `\tcbmaketheoremP. 329` to highlight mathematical definitions, theorems, or the like is demonstrated.

At first, additional tcb keys are created for the appearance of the colored boxes. It is assumed that theorems and corollaries should be identically colored. All following environments are numbered with a common counter, but this can be changed easily. Here, the counter output is supplemented by the subsection number. Further, the `cleverref` package [5] is used for clever references.

Definition in the preamble:

```
% \usepackage{cleverref}
\tcbset{
    defstyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
                    arc=0mm, colback=blue!5!white,colframe=blue!75!black},
    theostyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
                     colback=red!10!white,colframe=red!75!black},
}
\newtcbbtheorem[number within=subsection,crefname={definition}{definitions}]%
  {Definition}{Definition}{defstyle}{def}
\newtcbbtheorem[use counter from=Definition,crefname={theorem}{theorems}]%
  {Theorem}{Theorem}{theostyle}{theo}
\newtcbbtheorem[use counter from=Definition,crefname={corollary}{corollaries}]%
  {Corollary}{Corollary}{theostyle}{cor}
```

By `\newtcbbtheoremP. 328`, commonly numbered theorem environments are created now. `defstyle` and `theostyle` are used for the appearance.

Now, everything is prepared for the following examples.

The following theorem is numbered as `\Cref{theo:diffbarstetig}` and referenced with the marker `\texttt{theo:diffbarstetig}.\bigskip`

```
\begin{Theorem}{Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung zu Testzwecken ungewöhnlich lang ist}{diffbarstetig}
Eine Funktion $f:I\rightarrow\mathbb{R}$ ist in $x_0\in I$ stetig, wenn $f$ in $x_0$ differenzierbar ist.
\end{Theorem}
```

The following theorem is numbered as Theorem 16.3.1 and referenced with the marker `theo:diffbarstetig`.

Theorem 16.3.1: Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung zu Testzwecken ungewöhnlich lang ist

Eine Funktion \$f:I\rightarrow\mathbb{R}\$ ist in \$x_0\in I\$ stetig, wenn \$f\$ in \$x_0\$ differenzierbar ist.

The following definition is numbered as \Cref{def:diffbarkeit} and referenced with the marker \texttt{\def:diffbarkeit}.\bigskip

```
\begin{Definition}{Differenzierbarkeit}{diffbarkeit}
Eine Funktion  $f: I \rightarrow \mathbb{R}$  auf einem Intervall  $I$  heißt  $x_0 \in I$  differenzierbar oder linear approximierbar, wenn der Grenzwert
\begin{equation*}
\lim_{x \rightarrow x_0} \frac{f(x) - f(x_0)}{x - x_0} = \lim_{h \rightarrow 0} \frac{f(x_0 + h) - f(x_0)}{h}
\end{equation*}
existiert. Bei Existenz heißt dieser Grenzwert Ableitung oder Differentialquotient von  $f$  in  $x_0$  und man schreibt  $f'(x_0)$  oder ihn
\begin{equation*}
f'(x_0) \quad \text{oder} \quad \frac{df}{dx}(x_0).
\end{equation*}
\end{Definition}
```

The following definition is numbered as Definition 16.3.2 and referenced with the marker `def:diffbarkeit`.

Definition 16.3.2: Differenzierbarkeit

Eine Funktion $f : I \rightarrow \mathbb{R}$ auf einem Intervall I heißt in $x_0 \in I$ differenzierbar oder linear approximierbar, wenn der Grenzwert

$$\lim_{x \rightarrow x_0} \frac{f(x) - f(x_0)}{x - x_0} = \lim_{h \rightarrow 0} \frac{f(x_0 + h) - f(x_0)}{h}$$

existiert. Bei Existenz heißt dieser Grenzwert Ableitung oder Differentialquotient von f in x_0 und man schreibt für ihn

$$f'(x_0) \quad \text{oder} \quad \frac{df}{dx}(x_0).$$

The following corollary is numbered as \Cref{cor:nullstellen} and referenced with the marker \texttt{\cor:nullstellen}.\bigskip

```
\begin{Corollary}{Nullstellenexistenz}{nullstellen}
Ist  $f: [a, b] \rightarrow \mathbb{R}$  stetig und haben  $f(a)$  und  $f(b)$  entgegengesetzte Vorzeichen, also  $f(a)f(b) < 0$ , so besitzt  $f$  eine Nullstelle  $x_0 \in ]a, b[$ , also  $f(x_0) = 0$ .
\end{Corollary}
```

The following corollary is numbered as Corollary 16.3.3 and referenced with the marker `cor:nullstellen`.

Corollary 16.3.3: Nullstellenexistenz

Ist $f : [a, b] \rightarrow \mathbb{R}$ stetig und haben $f(a)$ und $f(b)$ entgegengesetzte Vorzeichen, also $f(a)f(b) < 0$, so besitzt f eine Nullstelle $x_0 \in]a, b[$, also $f(x_0) = 0$.

```
\begin{Theorem}[boxrule=2mm,toptitle=-1.5mm,bottomtitle=-1.5mm]{%
    Hinreichende Bedingung f\"ur Wendepunkte}{wendehinreichend}%
$f$ sei eine auf einem Intervall $]a,b[$ dreimal stetig differenzierbare Funktion.  

Ist $f''(x_0)=0$ in $x_0 \in ]a,b[$ und $f'''(x_0) \neq 0$, so ist  

$(x_0, f(x_0))$ ein Wendepunkt von $f$.
\end{Theorem}
```

Theorem 16.3.4: Hinreichende Bedingung für Wendepunkte

f sei eine auf einem Intervall \$]a,b[\$ dreimal stetig differenzierbare Funktion. Ist \$f''(x_0) = 0\$ in \$x_0 \in]a,b[\$ und \$f'''(x_0) \neq 0\$, so ist \$(x_0, f(x_0))\$ ein Wendepunkt von f.

```
% \usepackage{variorref}
% \usepackage{cleveref}
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}{%
    theorem style=plain apart,label type=theorem,enhanced,frame hidden,
    boxrule=2mm,titlerule=0mm,toptitle=1mm,bottomtitle=1mm,
    fonttitle=\bfseries\large,fontupper=\normalsize,
    coltitle=green!35!black,colbacktitle=green!15!white,
    colback=green!50!yellow!15!white,borderline={1pt}{Opt}{green!25!blue},
}{theo}

\begin{YetAnotherTheorem}[Mittelwertsatz f\"ur $n$ Variable]{meanvaluethm}%
Es sei $n \in \mathbb{N}$, $D \subset \mathbb{R}^n$ eine offene Menge und  

$f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke  

$[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt  

\begin{equation*}
f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)
\end{equation*}
\end{YetAnotherTheorem}

\medskip
Here, |cleveref| support is used to reference \Cref{theo:meanvaluethm}  

on \Cpageref{theo:meanvaluethm}. This \namecref{theo:meanvaluethm}  

can also be referenced by |\Vref| resulting in \Vref{theo:meanvaluethm}.
```

Theorem 16.3.5 (Mittelwertsatz für n Variable)

Es sei \$n \in \mathbb{N}\$, \$D \subseteq \mathbb{R}^n\$ eine offene Menge und \$f \in C^1(D, \mathbb{R})\$. Dann gibt es auf jeder Strecke \$[x_0, x] \subset D\$ einen Punkt \$\xi \in [x_0, x]\$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)$$

Here, |cleveref| support is used to reference Theorem 16.3.5 on Page 347. This theorem can also be referenced by |\Vref| resulting in Theorem 16.3.5.

! Note that |tcb|/label type^{P.94} was used in the example above to feed |cleveref| [5] with the needed name information.

Here, using `\Vref` resulting in `\Vref{theo:meanvaluethm}` is more interesting \ldots

Here, using `\Vref` resulting in Theorem 16.3.5 on page 347 is more interesting...

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{theorem style=change apart,enhanced,arc=0mm,outer arc=0mm,
boxrule=0mm,toprule=1mm,bottomrule=1mm,left=1mm,right=1mm,
titlerule=0mm,toptitle=0mm,bottomtitle=1mm,top=0mm,
colframe=red!50!black,colback=red!5!white,coltitle=red!50!black,
title style={top color=yellow!50!white,bottom color=red!5!white,
middle color=yellow!50!white},
fonttitle=\bfseries\sffamily\normalsize,fontupper=\normalsize\itshape,
}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"ur  $n$  Variable}{mittelwertsatz_n2}%
Es sei  $n \in \mathbb{N}$ ,  $D \subseteq \mathbb{R}^n$  eine offene Menge und  $f \in C^1(D, \mathbb{R})$ . Dann gibt es auf jeder Strecke  $[x_0, x] \subset D$  einen Punkt  $\xi \in [x_0, x]$ , so dass gilt
\begin{equation*}
f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)
\end{equation*}
\end{YetAnotherTheorem}
```

16.3.6 Theorem (Mittelwertsatz für n Variable)

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)$$

```
% \usepackage{varwidth} \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{enhanced,frame empty,interior empty,colframe=ForestGreen!50!white,
coltitle=ForestGreen!50!black,fonttitle=\bfseries,colbacktitle=ForestGreen!15!white,
borderline={0.5mm}{0mm}{ForestGreen!15!white},
borderline={0.5mm}{0mm}{ForestGreen!50!white,dashed},
attach boxed title to top center={yshift=-2mm},
boxed title style={boxrule=0.4pt},varwidth boxed title}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"ur  $n$  Variable}{mittelwertsatz_n3}%
Es sei  $n \in \mathbb{N}$ ,  $D \subseteq \mathbb{R}^n$  eine offene Menge und  $f \in C^1(D, \mathbb{R})$ . Dann gibt es auf jeder Strecke  $[x_0, x] \subset D$  einen Punkt  $\xi \in [x_0, x]$ , so dass gilt
\begin{equation*}
f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)
\end{equation*}
\end{YetAnotherTheorem}
```

Theorem 16.3.7: Mittelwertsatz für n Variable

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)$$

You need more attention for your theorems? Here, you are ...

```
% tcbuselibrary{skins} % preamble
\begin{Theorem}[enhanced,
    fuzzy halo=3mm with yellow,
    fuzzy halo=2mm with red,
    fuzzy halo=1mm with yellow,
    watermark color=red!35!white,
    watermark text={Overacting\\Fundamental Theorem}]%
{Fundamental Theorem of Theorems}{fundamental}%
\lipsum[1-2]
\end{Theorem}
```

Theorem 16.3.8: Fundamental Theorem of Theorems

Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Let's try a more conservative approach:

```
% tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{theorem style=plain, enhanced, colframe=blue!50!black, colback=yellow!20!white,
 coltitle=red!50!black, fonttitle=\upshape\bfseries, fontupper=\itshape,
 drop fuzzy shadow=blue!50!black!50!white, boxrule=0.4pt}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"ur $n$ Variable}{mittelwertsatz_n4}%
Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und
$f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke
$[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt
\begin{equation*}
f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)
\end{equation*}
\end{YetAnotherTheorem}
```

Theorem 16.3.9 (Mittelwertsatz für n Variable): Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^T (x - x_0)$$

16.4 Using other theorem environments with `tcolorbox`

Instead of creating theorem environments with the methods described before, environments from other packages can be boxed with a `tcolorbox`.

Environments may be created e.g. by methods from the `theorem` package or the `amsthm` package. `\tcolorboxenvironment→ P. 17` can be used to put a box around these environments.

Definition in the preamble:

```
\usepackage{amsthm}

\theoremstyle{plain}%
\newtheorem{lem}{Lemma}%

\tcolorboxenvironment{lem}{
    enhanced jigsaw,colframe=cyan,interior hidden,
    breakable,before skip=10pt,after skip=10pt }

\tcolorboxenvironment{proof}{%
    blanker,breakable,left=5mm,
    before skip=10pt,after skip=10pt,
    borderline west={1mm}{0pt}{red}}
```

```
\begin{lem}
    \lipsum[2]
\end{lem}

\lipsum[3]

\begin{proof}
    \lipsum*[4]
\end{proof}
```

Lemma 1. *Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.*

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Proof. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. □

17 Library breakable

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{breakable}
```

17.1 Technical Overview

The library  `breakable` supports the automatic breaking of a `tcolorbox`. This feature is enabled by `/tcb/breakable`^{→ P. 353} and disabled by `/tcb/unbreakable`^{→ P. 354}.

If a `tcolorbox` is set to be `/tcb/breakable`^{→ P. 353}, then the following algorithm is executed:

1. The box content is read to a box register similar but not identical to the unbreakable case.
2. If the total box fits into the current page, it is shipped out visibly unbroken and the algorithm stops.

Unbroken Box

The box.

unbroken

3. Otherwise, it is checked if at least `/tcb/lines before break`^{→ P. 354} of the upper box can be placed on the current page. If not, a page break is inserted and the algorithm goes back to Step 2.
4. Now, the *break sequence* starts. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *first part* of the *break sequence* and shipped out.

Broken Box

The box.

first

5. If the remaining content of the total box fits into the current page, the algorithm continues with Step 7, else with Step 6.
6. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *middle part* of the *break sequence* and shipped out. Then, the algorithm goes back to Step 5.

The box.

middle

7. The remaining part is named *last part* of the *break sequence* and shipped out. The algorithm stops.

The box.

last

The algorithm takes care that the optional segmentation line never appears at the end of a box. The optional lower box part is also checked to have at least `/tcb/lines before break`^{→ P. 354}.

In principle, all boxes of the *break sequence* share the same geometric parameters. The differences are:

- The given `/tcb/before`^{P. 76} and `/tcb/after`^{P. 76} values are used only before the *first* and after the *last* part of the *break sequence*.
- A special behavior between the parts of the *break sequence* can be given by `/tcb/toprule at break`^{P. 357}, `/tcb/bottomrule at break`^{P. 357}, `/tcb/enlarge top at break by`^{P. 81}, and `/tcb/enlarge bottom at break by`^{P. 81}.
- The `/tcb/skin`^{P. 126} decides *how* the *first*, *middle*, and *last* part look like. Actually, every part type has its own skin given by the options `/tcb/skin first`^{P. 126}, `/tcb/skin middle`^{P. 126}, and `/tcb/skin last`^{P. 126}. Typically, these options are set automatically by the main skin, see Subsection 17.7 from page 365.

17.2 Limitations and Known Bugs

- The maximal total height of the upper and of the lower part of normal breakable `tcolorboxes` is about 65536pt (ca. 2300cm) apiece. If such a part gets longer, the output will get buggy without warning. For very oversized boxes which are longer than 65536pt, use the `unlimited` value for `/tcb/breakable`^{P. 353}. With the `unlimited` setting, the applied algorithm has (virtually) no height limit for boxes, but very likely the compiler memory will have to be increased for boxes longer than 300 pages (depending on compiler settings and box content). But it is recommended to use `unlimited` for critical large boxes only.
- You can nest an unbreakable `tcolorbox` inside another `tcolorbox`, even inside a breakable one. But you cannot not nest a breakable box inside a breakable box. The `/tcb/breakable`^{P. 353} key for a nested box is ignored automatically³, i.e. inner boxes are always unbreakable.

After all, in the unlikely case you really want to have the nested box to be breakable, use `/tcb/enforce breakable`^{P. 354} for the nested box⁴. **But, a breakable box inside a breakable box will usually give a mess.**

- If your text content contains some text color changing commands, your color will not survive the break to the next box. But, with the `fntspec` package and `xelatex` or `lualatex`, you can use `\addfontfeatures{Color=mycolor}` to add a font color which survives the break.

- N 2014-10-30
- The `perpage` option of the `footmisc` package is deliberately deactivated inside a breakable box since all footnotes are placed at the end of the box (possibly far away from the reference point).

- N 2016-02-15
- Making a box `/tcb/breakable`^{P. 353} which actually is not broken creates a box which acts *almost* like an unbreakable box. Visual differences are kept as indiscernible as possible, but can appear with certain `/tcb/before`^{P. 76} and `/tcb/after`^{P. 76} settings, especially, if there is an automatic page break before the box.

- N 2016-05-25
- LuaTeX version 0.95 changes the behaviour of the basic `\vsplit` (a bug?!) resulting in badly broken boxes. Thanks to Jeremy Engel, the `breakable` library contains a patch for this which also loads the the `ifluatex` package.

³Until `tcolorbox` 3.04, the `/tcb/breakable`^{P. 353} key was not ignored for nested boxes.

⁴`/tcb/enforce breakable`^{P. 354} acts like `/tcb/breakable`^{P. 353} until `tcolorbox` 3.04.

17.3 Main Option Keys

`/tcb/breakable=true|false|unlimited` (default `true`, initially `false`)

Allows the `tcolorbox` to be breakable. If the box is larger than the available space at the current page, the box is automatically broken and continued to the next next page. All sorts of `tcolorbox` can be made breakable. It depends on the skin how the breaking looks like. If you do not know better, use `/tcb/enhanced`^{→ P. 196} for breaking a box. The parts of the *break sequence* are numbered by the counter `tcbbreakpart`.

- `false`: Sets the `tcolorbox` to be unbreakable.
- `true`: Breaks the `tcolorbox` from one page to another. The maximal total height of the upper and of the lower part is about 65536pt (ca. 2300cm or ca. 90 pages) apiece.
- `unlimited`: Experimental code for unlimited total height of breakable boxes. For boxes longer than 300 pages (or even shorter ones) the compiler memory will have to be increased.

```
% \usepackage{lipsum} % preamble
\tcbset{enhanced jigsaw,colback=red!5!white,colframe=red!75!black,
watermark color=yellow!25!white,watermark text=\arabic{tcbbreakpart},
fonttitle=\bfseries}

\begin{tcolorbox}[breakable,title=My breakable box]
\lipsum[1-6]
\end{tcolorbox}
```

My breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea

dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

/tcb/unbreakable (no value, initially set)

Sets the `tcolorbox` to be unbreakable.

/tcb/enforce breakable (no value)

A `tcolorbox` inside a `tcolorbox` is automatically set to be unbreakable. Using `/tcb/breakable`^{→ P.353} on such an inner box has no effect. If one *really* wants the inner box to be breakable, use `/tcb/enforce breakable`. **This will usually give a mess of shattered boxes. You are advised to not use this option.**

Note that `/tcb/enforce breakable` has the functionality that `/tcb/breakable`^{→ P.353} had until package version 3.04 and exists for backward compatibility.

/tcb/title after break=*<text>* (no default, initially empty)

The `/tcb/title`^{→ P.18} is used only for the *first* part of a *break sequence*. Use `title after break` to create a heading line with *<text>* as content for all following parts.

/tcb/notitle after break (no value, initially set)

Removes the title line or following parts in a *break sequence* if set before.

/tcb/adjusted title after break=*<text>* (style, no default, initially unset)

Works like `/tcb/adjusted title`^{→ P.18} but applied to `/tcb/title after break`.

/tcb/lines before break=*<number>* (no default, initially 2)

Assures that the given *<number>* of lines of the upper box part or the lower box part are placed before a break happens.

/tcb/break at=⟨length⟩/⟨length⟩/…/⟨length⟩ (no default, initially 0pt)

Defines break points at the given ⟨length⟩ values. The first ⟨length⟩ defines the (maximal) height of the first partial box, the second ⟨length⟩ defines the (maximal) height of the second partial box, and so on. The last ⟨length⟩ value is applied to all following partial boxes if any. Setting a length to 0pt means that the naturally available space is used for breaking.

```
% \usepackage{multicol,lipsum}
\begin{multicols}{3}\footnotesize
Breakable boxes inside a |multicols| environment need special attendance.
They are broken by default at |\textheight|.
The |break at| option can be used to insert better break points by hand.
\begin{tcolorbox}[enhanced,jigsaw,size=small,vfill before first,
colframe=red,colback=yellow!10!white,before title=\raggedright,
title={Broken box inside a |multicols| environment},fonttitle=\bfseries,
enforce breakable,% use only breakable in the real world!
pad at break=1mm,break at=3cm/6.3cm ]
\lipsum[1]
\end{tcolorbox}
\refKey{/tcb/height fixed for} may also be considered for |multicols| environments.
\end{multicols}
```

Breakable boxes inside a `multicols` environment need special attendance. They are broken by default at `\textheight`. The `break at` option can be used to insert better break points by hand.

Broken box inside a `multicols` environment

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dic-

tum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis,

viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/height fixed for^{P.358} may also be considered for `multicols` environments.

/tcb/enlargepage=⟨length⟩/⟨length⟩/…/⟨length⟩ (no default, initially 0pt)

Inserts a `\enlargethispage{⟨length⟩}` to the pages of the break sequence, i. e. allows one to enlarge (or shrink) partial boxes. The first ⟨length⟩ is applied to the first partial box, the second ⟨length⟩ is applied to the second partial box, and so on. The last ⟨length⟩ value is applied to all following partial boxes if any. Note that floating boxes will not be enlarged.

```
\begin{tcolorbox}[breakable,enlargepage=0mm/\baselineskip/2\baselineskip/0mm,...]
```

The example code enlarged the second partial box by one line, the third partial box by two lines, and all following parts are not enlarged.

! If an automated page break occurs before the first partial box, the page enlargement is applied to the page before the first partial box *and* again to the page of the first partial box. Insert a manual break to prevent this.
In general, `enlargepage` should be used at the final stage of a document for fine-tuning only.

`/tcb/enlargepage flexible=<length>` (no default, initially 0pt)

This allows an automated page enlargement for up to $\langle length \rangle$. The algorithm can use this to avoid breaking a box, if there is enough room after enlargement. Also, the *last* partial box of a break sequence may be enlarged to avoid further breaking.

Note that this potential enlargement is *additive* to settings of `/tcb/enlargepage`^{→ P. 355}. But `/tcb/enlargepage flexible` overwrites settings of `/tcb/pad before break*`^{→ P. 357} or `/tcb/pad at break*`^{→ P. 357}.

```
% The following setting hinders orphan lines for the last partial box
\tcbset{enlargepage flexible=\baselineskip}
```

N 2014-12-15

`/tcb/compress page=<option>` (default `all`, initially `baselineskip`)

This option controls the space management on the page which contains the unbroken box or the first part of a *break sequence*. Feasible $\langle option \rangle$ values are:

- `all` (default value): All shrinkable glue on the page is potentially used for the unbroken box or the first part of a *break sequence*. Thus, all vertical spaces on the page will potentially be reduced to their minimal values.
- `baselineskip` (initial value): Shrinkable glue up to one `\baselineskip` on the page is potentially used for the unbroken box or the first part of a *break sequence*.
- `none`: The break algorithm respects the target size of the given glue values on the page. This was the initial value before version 3.34.



Note that the box *content* is not influenced by this option.

`/tcb/shrink break goal=<length>` (no default, initially 0pt)

This is an emergency parameter if the break algorithm produces unpleasant breaks. It shrinks the goal height of the current box part by $\langle length \rangle$ which may result in smaller boxes. Never use negative values. *Usually, this option will never be needed at all.*

17.4 Option Keys for the Break Appearance

/tcb/toprule at break=⟨length⟩ (no default, initially 0.5mm)

Sets the line width of the top rule to ⟨length⟩ if the box is /tcb/breakable^{→ P. 353}. In this case, it is applied to *middle* and *last* parts in a break sequence. Note that /tcb/toprule^{→ P. 35} overwrites this value if used afterwards.

/tcb/bottomrule at break=⟨length⟩ (no default, initially 0.5mm)

Sets the line width of the bottom rule to ⟨length⟩ if the box is /tcb/breakable^{→ P. 353}. In this case, it is applied to *first* and *middle* parts in a break sequence. Note that /tcb/bottomrule^{→ P. 35} overwrites this value if used afterwards.

/tcb/topsep at break=⟨length⟩ (no default, initially 0mm)

Additional vertical space of ⟨length⟩ which is added at the top of *middle* and *last* parts in a break sequence. In general, it is not advisable to change this value if these parts start with a rule or a title.

/tcb/bottomsep at break=⟨length⟩ (no default, initially 0mm)

Additional vertical space of ⟨length⟩ which is added at the bottom of *first* and *middle* parts in a break sequence. In general, it is not advisable to change this value if these parts end with a rule.

/tcb/pad before break=⟨length⟩ (style, no default, initially 3.5mm)

Sets the total amount of vertical space after the text content and before the break point to ⟨length⟩. This style sets /tcb/toprule at break to 0pt and changes /tcb/topsep at break as required. In general, it is not advisable to change this value if the *middle* and *last* parts in a break sequence start with a rule or a title.

/tcb/pad before break*=⟨length⟩ (style, no default)

Sets /tcb/pad before break to ⟨length⟩ and /tcb/enlargepage flexible^{→ P. 356} to an appropriate value such that empty closing frames are avoided.

/tcb/pad after break=⟨length⟩ (style, no default, initially 3.5mm)

Sets the total amount of vertical space after the break point and before the text content to ⟨length⟩. This style sets /tcb/bottomrule at break to 0pt and changes /tcb/bottomsep at break as required. In general, it is not advisable to change this value if the *first* and *middle* parts in a break sequence end with a rule.

/tcb/pad at break=⟨length⟩ (style, no default, initially 3.5mm)

Abbreviation for setting ⟨length⟩ to /tcb/pad before break and /tcb/pad after break.

/tcb/pad at break*=⟨length⟩ (style, no default)

Sets /tcb/pad at break to ⟨length⟩ and /tcb/enlargepage flexible^{→ P. 356} to an appropriate value such that empty closing frames are avoided.

```
% \usepackage{lipsum} % preamble
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced jigsaw,breakable,pad at break*=0mm,
title={For this box, the pad space at the break point is set to 0mm}]
\lipsum[1-2]
\end{tcolorbox}
```

For this box, the pad space at the break point is set to 0mm

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

! `/tcb/pad at break→ P. 357` or `/tcb/pad at break*→ P. 357` should be used as very last option in an option list, because they adapt other settings.

! Also see `/tcb/enlarge top at break by→ P. 81` and `/tcb/enlarge bottom at break by→ P. 81`.

`/tcb/height fixed for=<part>` (no default, initially `none`)

When certain amount of space is available for a partial box of a break sequence, the partial box typically is smaller than this space (depending on the box content). For given `<part>`(s), the height can be set to all available space.

- **none**: Every partial `tcolorbox` is set with its natural height.
- **first**: The *first* partial box is set to a height which matches the available space.
- **middle**: All *middle* partial boxes are set to a height which matches the available space.
- **last**: The *last* partial box is set to a height which matches the available space.
- **first and middle**: The *first* and all *middle* partial boxes are set to a height which matches the available space.
- **middle and last**: All *middle* partial boxes and the *last* partial box are set to a height which matches the available space.
- **all**: All partial boxes are set to a height which matches the available space.

! If the box keeps unbroken, this option is not applied. See `/tcb/height→ P. 52` for setting a fixed height for unbroken boxes. See `/tcb/height fill→ P. 55` for giving unbroken boxes maximum height.

`/tcb/vfill before first=true|false` (default `true`, initially `false`)

Inserts a `\vfill` at the begin of the *first* partial box to move this partial box to the end of the current page. This may be used as an alternative to `/tcb/height fixed for=first` to get justified columns or pages. The `\vfill` is not inserted, if the box gets not actually broken.

17.5 Extra Options for Partial Boxes

N 2015-07-16	<code>/tcb/extras={⟨options⟩}</code>	(no default, initially unset)
	Adds <code>tcolorbox ⟨options⟩</code> to every box of a <i>break sequence</i> after skin settings are done. This is quite late in box processing. Geometry and break settings should <i>not be used</i> here, because they will either be ignored or have unexpected negative results. But it is possible to change most colors, skin effects, shadows, borders, frame code, etc. Note that using <code>/tcb/extras</code> for every box is very seldom an advantage over setting the options directly. Usually, <code>/tcb/extras first</code> , <code>/tcb/extras middle</code> , etc. are sensible to apply.	
N 2015-07-16	<code>/tcb/no extras</code>	(style, no default, initially set)
	Removes all extras if set before.	
N 2015-07-16	<code>/tcb/extras broken={⟨options⟩}</code>	(no default, initially unset)
	If the box is set to be <code>/tcb/breakable</code> ^{→ P. 353} and <i>is</i> broken actually, then the <code>⟨options⟩</code> are added to every box of the <i>break sequence</i> . <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/extras unbroken={⟨options⟩}</code>	(no default, initially unset)
	If the box is set to be <code>/tcb/breakable</code> ^{→ P. 353} but <i>is not</i> broken actually or if the box is set to be <code>/tcb/unbreakable</code> ^{→ P. 354} , then the <code>⟨options⟩</code> are added to the box. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/no extras unbroken</code>	(style, no default, initially set)
	Removes the unbroken extras if set before.	
N 2015-07-16	<code>/tcb/extras first={⟨options⟩}</code>	(no default, initially unset)
	If the box is set to be <code>/tcb/breakable</code> ^{→ P. 353} and <i>is</i> broken actually, then the <code>⟨options⟩</code> are added to the <i>first</i> box of the break sequence. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/no extras first</code>	(style, no default, initially set)
	Removes the first extras if set before.	
N 2015-07-16	<code>/tcb/extras middle={⟨options⟩}</code>	(no default, initially unset)
	If the box is set to be <code>/tcb/breakable</code> ^{→ P. 353} and <i>is</i> broken actually, then the <code>⟨options⟩</code> are added to every <i>middle</i> box (if any) of the break sequence. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/no extras middle</code>	(style, no default, initially set)
	Removes the middle extras if set before.	
N 2015-07-16	<code>/tcb/extras last={⟨options⟩}</code>	(no default, initially unset)
	If the box is set to be <code>/tcb/breakable</code> ^{→ P. 353} and <i>is</i> broken actually, then the <code>⟨options⟩</code> are added to the <i>last</i> box of the break sequence. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/no extras last</code>	(style, no default, initially set)
	Removes the last extras if set before.	
N 2015-07-16	<code>/tcb/extras unbroken and first={⟨options⟩}</code>	(no default, initially unset)
	This is an abbreviation for setting <code>/tcb/extras unbroken</code> and <code>/tcb/extras first</code> together. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/extras middle and last={⟨options⟩}</code>	(no default, initially unset)
	This is an abbreviation for setting <code>/tcb/extras middle</code> and <code>/tcb/extras last</code> together. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/extras unbroken and last={⟨options⟩}</code>	(no default, initially unset)
	This is an abbreviation for setting <code>/tcb/extras unbroken</code> and <code>/tcb/extras last</code> together. <code>/tcb/extras</code> overwrites this key.	
N 2015-07-16	<code>/tcb/extras first and middle={⟨options⟩}</code>	(no default, initially unset)
	This is an abbreviation for setting <code>/tcb/extras first</code> and <code>/tcb/extras middle</code> together. <code>/tcb/extras</code> overwrites this key.	

```
% \usepackage{lipsum,multicol}
% \usetikzlibrary{decorations.pathmorphing}
% \tcbuselibrary{skins}
\newtcolorbox{mybox}[1][]{%
    tile,
    colback=green!7,coltitle=blue!50!black,colbacktitle=blue!5,
    center title,
    toprule=1.25mm,bottomrule=1.25mm,
    extras unbroken and first={%
        borderline north={0.25mm}{0.5mm}{blue},decoration={zigzag,amplitude=0.5mm},decorate},
    extras unbroken and last={%
        borderline south={0.25mm}{0.5mm}{blue},decoration={zigzag,amplitude=0.5mm},decorate},
    #1
}

\begin{mybox}[title=My unbroken box]
\lipsum[1]
\end{mybox}

\begin{multicols}{3}
\begin{mybox}[title=My broken box,
    enforce breakable,% use only breakable in the real world!
    break at=4.2cm,pad at break=2mm,
    height fixed for=first and middle, ]
\lipsum[2]
\end{mybox}
\end{multicols}
\end{mybox}
```

My unbroken box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My broken box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan biben-

dum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus

mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus maoris.

17.6 Breakable boxes and the `multicol` package

Unbreakable `tcolorboxes` can be used without special care inside a `multicols` environment from the `multicol` package [9].

Since version 3.10, a breakable `tcolorbox` detects, if it is used inside a `multicols` environment. But choosing break points for a

breakable box cannot be done by the balancing routine of `multicols`. By default, boxes will break at `\textheight`. To get pleasant results, use the `/tcb/break at→ P.355` and `/tcb/height fixed for→ P.358` options.

```
% \usepackage{lipsum,multicol} % preamble
\small
\begin{multicols}{2}
  \lipsum[1]
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=title,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=1mm, break at=7.5cm/0pt ]
    \lipsum[2-4]
  \end{tcolorbox}
  \lipsum[4]
\end{multicols}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis.

Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

This example is already set inside a `multicols` environment. This time, a `middle` part has full `\textheight`. `/tcb/height fixed forP.358` is used to spread this box part over the full height to align with neighboring columns.

```
% \usepackage{lipsum,multicol}
\lipsum[1]
\begin{tcolorbox}[enhanced ,
  jigsaw,breakable,
  size=title,
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=My breakable box,
  pad at break=2mm,
  break at=8.2cm/0pt,
  height fixed for=middle ]
\lipsum[2-7]
\end{tcolorbox}
\lipsum[8]
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus

adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellenesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi

quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec

odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

The following example has a `\tcolorbox` which fills the `\multicols` environment completely. Here, `/tcb/height fixed for→ P. 358` is used to give all three columns the full height. Note that the appropriate `/tcb/break at→ P. 355` value is not computed automatically but set manually.

```
% \usepackage{lipsum,multicol} % preamble
\small
\begin{multicols}{3}
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=2mm,drop fuzzy shadow,
    height fixed for=all, break at=11.4cm ]
    \lipsum[1-3]
  \end{tcolorbox}
\end{multicols}
```

My breakable box


Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur


auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.


Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

17.7 Break Sequence for the Skins

The following diagrams document the *break sequence* for different skins. Depending on the main skin of a `tcolorbox`, the actual skins of the *break sequence* parts are displayed.







skin=empty

unbroken



skin=emptyfirst

middle
last

skin=emptyfirst

unbroken



skin=emptyfirst

middle
last

skin=emptymiddle

unbroken



skin=emptymiddle

middle
last


skin=emptylast


unbroken








skin=emptylast


middle
last











17.8 Break by Hand (Faked Break)



See Section 17.6 on page 362 for *real* column breaks.

Since the appearance of broken boxes is done by skins, it is quite easy to 'fake a break'. For this, you actually don't need the `\tikz` `breakable` library at all.

```
\tcbset{enhanced,equal height group=fakedbreak,
        colback=LightGreen,colframe=DarkGreen,
        width=(\linewidth-6mm)/3,nobeforeafter,
        left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm}
%
\begin{tcolorbox}[title=My broken box,skin=enhancedfirst]
This is a box which breaks from one column to another
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedmiddle]
column. I am sorry to say that this is a trick.
Nevertheless, you may use this trick for your
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedlast]
own purposes.
\end{tcolorbox}
```

My broken box

This is a box which breaks
from one column to another

column. I am sorry to say that
this is a trick. Nevertheless,
you may use this trick for your

own purposes.

18 Library magazine

The main purpose of this library is to store a `tcolorbox` into an array of box registers for later usage.

If the `tcolorbox` is not breakable, there is not much add-on compared to usual TeX/LaTeX box storage and usage (and you do not really need this library for that use case). For a breakable `tcolorbox`, this library allows to capture all partial boxes into a sequence of registers. The partial boxes can be used anywhere in arbitrary order.

Example Article

This is an example for an article which starts right here and is continued to the following pages. The body text for the article is written inside a single `tcolorbox`. This box is split into parts using the tools from this section,
— *continued on page 378* —

The name of this library indicates *magazine* in the sense of storage, but also in the sense of a journal where an article often is *continued on page x*. An example for this kind of application is given throughout this section starting on the right hand side. The creation of this library was motivated by Ulrike Fischer and Steven B. Segletes.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{magazine}
```

This also loads the library  `breakable`, see Section 17 on page 351.



The box register operations of this library are global. TeX grouping will not clear the registers when leaving the current group. Also be aware that extensive use of large box arrays may eat up TeX's available memory and registers.

18.1 Creation and Resetting of Box Arrays

N 2015-07-13

`\newboxarray{<name>}`

This creates a new box array called `<name>`. There already is a box array available with name `default` which can be used directly. Note that the creation is a global operation.

```
\newboxarray{myarray}
```

N 2015-07-13

`\boxarrayreset[<name>]`

Resets the size counter of a box array `<name>` to zero. If `<name>` is not provided, `default` is used as name. Use this or `/tcb/reset box array`^{→ P.375} before you apply `/tcb/store to box array`^{→ P.376}. Otherwise, all boxes would be appended to the already existing boxes. This command does not clear box registers.

```
\boxarrayreset          % resets 'default'  
\boxarrayreset{myarray} % resets 'myarray'
```

N 2015-07-13

`/tcb/reset box array=<name>`

(default `default`, initially unset)

Resets the size counter of a box array `<name>` to zero. Use this or `\boxarrayreset`^{→ P.375} (which does the same) before you apply `/tcb/store to box array`^{→ P.376}.

```
\tcbset{  
    reset box array,           % resets 'default'  
    reset box array=myarray, % resets 'myarray'  
}
```

\boxarrayclear[<name>]

Works like `\boxarrayreset` to reset the size counter of a box array `<name>` to zero. Additionally, all allocated box registers of the box array are cleared of their content. Note that the allocated box registers stay allocated. So, this may be useful to clear memory, but not to free registers for other applications. If `\consumeboxarray`^{→ P. 379} or `\consumetboxarray`^{→ P. 379} was used to apply the stored boxes, there is no advantage in using `\boxarrayclear`^{→ P. 376}.

```
\boxarrayclear           % clears 'default'
\boxarrayclear{myarray} % clears 'myarray'
```

18.2 Storing Content

/tcb/store to box array=<name>


(default `default`, initially unset)

Stores a `tcolorbox` or all parts of a break sequence of a `tcolorbox` into a box array `<name>`. If no `<name>` is given, the already existing `default` box array is used. Otherwise, the box array has to be created beforehand with `\newboxarray`. Note that the box has to be `/tcb/breakable`^{→ P. 353}, if the box shall break into several parts. Typically, manual break points are additionally defined by `/tcb/break at`^{→ P. 355}. Otherwise, the box parts will have a length of about `\textheight`. For most use cases, a `/tcb/reset box array` should be applied to reset the box array counter.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced jigsaw, size=fbox, width=4cm,
  colback=yellow!10, colframe=yellow!10!black,
  enforce breakable, % use only breakable in the real world!
  break at=7cm/4cm,
  height fixed for=all,
  watermark text=\arabic{tcbbreakpart},
  reset box array,
  store to box array
]
\lipsum[1]
\end{tcolorbox}

\useboxarray{1}\hfill
\begin{tabular}{b}{cc}
\multicolumn{2}{c}{\includegraphics[width=7cm]{Basilica_5.png}}\\
\useboxarray{2} & \useboxarray{3}
\end{tabular}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhon-



cus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi do-

lor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

If the first box part should fill the rest of the available space of the current page, you can use `\pagegoal-\pagetotal` minus some distance for the first element of `/tcb/break at→ P. 355`. You may want to have some additional distance to the preceding text.


```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,breakable,
  reset box array,
  store to box array,
  break at=\pagegoal-\pagetotal-5mm/0pt,
  height fixed for=first and middle]
\lipsum[1-15]
\end{tcolorbox}%
%
\consumetcbarray{1}{blanker, before=\par\vfill\noindent}
```

```
\begin{tcolorbox}[blanker, width=4cm,
  fontupper=\footnotesize,
  enforce breakable,% use only breakable in the real world!
  break at=4cm,
  height fixed for=all,
  watermark text=\arabic{tcbbreakpart},
  reset box array,
  store to box array
]
\includegraphics[width=\linewidth]{Basilica_5.png}\par
\lipsum[1-2]
\end{tcolorbox}

\begin{tcbitemize}[raster columns=3,raster equal height,
  size=small,halign=center,sharp corners,colback=blue!5]
\tcbitem\consumeboxarray{5}
\tcbitem\consumeboxarray{6}
\tcbitem\consumeboxarray{1}
\tcbitem\consumeboxarray{2}
\tcbitem\consumeboxarray{3}
\tcbitem\consumeboxarray{4}
\end{tcbitemize}
```

lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec

ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam

arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus

vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at,

mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor

N 2015-07-13 `/tcb/reset and store to box array=<name>` (style, default `default`, initially unset)
Combination of `/tcb/reset box array→ P. 375` and `/tcb/store to box array→ P. 376`.

N 2015-07-13 `/tcb/do not store to box array` (style, no default, initially set)
Disables the `/tcb/store to box array→ P. 376` option, if set before.

N 2015-07-13 `\begin{boxarraystore}{<name>}`
`<environment content>`
`\end{boxarraystore}`

Stores the environment content into a box array `<name>`. This corresponds to the standard L^AT_EX environment `lrbox`, but the storage operation is global. As long as `\boxarrayreset→ P. 375` is not used, every new `boxarraystore→ P. 378` adds a further box to the array.

```
\boxarrayreset
\begin{boxarraystore}{default}\fbox{Mary}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Had}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{a}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Little}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Lamb}\end{boxarraystore}
\useboxarray{5}\useboxarray{4}\useboxarray{3}\useboxarray{2}\useboxarray{1}\hfill
\useboxarray{1}\useboxarray{5}
```

Mary Lamb Little a Had

Mary Lamb

18.3 Retrieving Content

N 2015-07-13 `\boxarraygetsize [<name>] {<macro>}`

Stores the current size of a box array `<name>` into a given `<macro>`. If no `<name>` is given, the already existing `default` box array is used.

```
\boxarraygetsize{\mysize}
Current size of the default box array:
\mysize.
```

Current size of the default box array: 5.

— continued from page 375 —
namely `/tcb/reset and store to box array→ P. 378` with a new box array `myarticle` which was created by `\newboxarray{myarticle}`.

The resulting parts are distributed throughout this Section 18 on page 375 using `\consumetcboxarray→ P. 379` at

— continued on page 379 —

N 2015-07-13 `\useboxarray [<name>] {<index>}`

Typesets the box with the given `<index>` number from the box array `<name>`. If no `<name>` is given, the already existing `default` box array is used. It is considered an error, if a not existing box array `<name>` is used. It is silently ignored, if the `<index>` is out of range. Note that `\useboxarray→ P. 378` corresponds to the standard `\usebox` macro, respectively, `\copy`.

```
\boxarraygetsize{\mysize}
\foreach \n in {1,...,\mysize} { \useboxarray{\n} }
```


Mary Had a Little Lamb

N 2015-07-13

\useboxarray[<name>]{<index>}{<options>}

Typesets the box with the given $\langle index \rangle$ number from the box array $\langle name \rangle$ using `\useboxarray` as content of a $\text{\tcb}^{\rightarrow P.14}$. If no $\langle name \rangle$ is given, the already existing **default** box array is used. It is considered an error, if a not existing box array $\langle name \rangle$ is used. It is silently ignored, if the $\langle index \rangle$ is out of range. The $\text{\tcb}^{\rightarrow P.14}$ can be customized by `tcolorbox <options>`.

```
\boxarraygetsize{\mysize}
\foreach \n in {1,...,\mysize} { \useboxarray{\n}{on line,colframe=yellow,
colback=yellow!10} }
```



N 2015-07-13

\consumeboxarray[<name>]{<index>}

Typesets the box with the given $\langle index \rangle$ number from the box array $\langle name \rangle$. If no $\langle name \rangle$ is given, the already existing **default** box array is used. It is considered an error, if a not existing box array $\langle name \rangle$ is used. It is silently ignored, if the $\langle index \rangle$ is out of range. In contrast to `\useboxarray`, `\consumeboxarray^{\rightarrow P.379}` corresponds to the standard `\box` macro, i.e. after typesetting the box register is cleared and cannot be used again.

```
\boxarraygetsize{\mysize}
First run: \foreach \n in {1,...,\mysize} { \consumeboxarray{\n} }
\par
Second run: \foreach \n in {1,...,\mysize} { \consumeboxarray{\n} }
```

First run:

Second run:

N 2015-07-13

\consumetboxarray[<name>]{<index>}{<options>}

Typesets the box with the given $\langle index \rangle$ number from the box array $\langle name \rangle$ using `\consumeboxarray^{\rightarrow P.379}` as content of a $\text{\tcb}^{\rightarrow P.14}$. If no $\langle name \rangle$ is given, the already existing **default** box array is used. It is considered an error, if a not existing box array $\langle name \rangle$ is used. It is silently ignored, if the $\langle index \rangle$ is out of range. The $\text{\tcb}^{\rightarrow P.14}$ can be customized by `tcolorbox <options>`. After typesetting the box register is cleared and cannot be used again.

— continued from page 378 —
the appropriate places you see. The linking texts like *continued on page x* are created by `/tcb/finish^{\rightarrow P.189}` commands for the embedding $\text{\tcb}^{\rightarrow P.14}$. To label the box parts, `/tcb/phantomlabel^{\rightarrow P.94}` is used.
These quite small partial boxes are

— continued on page 382 —

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced jigsaw, size=fbox, width=6cm,
  colback=yellow!10, colframe=yellow!10!black,
  enforce breakable, % use only breakable in the real world!
  break at=5cm,
  watermark text=\arabic{tcbbreakpart},
  reset and store to box array
]
\lipsum[1]
\end{tcolorbox}

\consumeboxarray{2} \hfill \consumeboxarray{1} \hfill \consumeboxarray{1}
```

lus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tel-

N 2015-07-13

\boxarraygetbox[*name*]{*macro*}{*index*}

Assigns the box with the given *index* number from the box array *name* to a *macro*. If no *name* is given, the already existing **default** box array is used. It is considered an error, if a not existing box array *name* is used. If the *index* is out of range, the *macro* will be undefined.

```
\tcbx[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\boxarraygetsize{\mysize} Array size: \mysize

\boxarraygetbox{\mybox}{1}
Box width: \the\wd\mybox
\quad\usebox{\mybox}
```

Array size: 1
 Box width: 30.35799pt

18.4 Box Dimensions

N 2015-07-13

\boxarraygetwidth[⟨name⟩]{⟨macro⟩}{⟨index⟩}

Assigns the width of the box with the given ⟨index⟩ number from the box array ⟨name⟩ to a ⟨macro⟩. If no ⟨name⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨name⟩ is used. If the ⟨index⟩ is out of range, the ⟨macro⟩ will be set to `Opt`.

```
\tcbbox[size=small,colframe=blue!20,colback=yellow!5,on line,  
       reset and store to box array]{Test}  
  
\begin{tabular}{ll}  
  \useboxarray{1} & width of box 1: \boxarraygetwidth{\mylen}{1} \mylen\\  
  \useboxarray{2} & width of box 2: \boxarraygetwidth{\mylen}{2} \mylen  
\end{tabular}
```

Test width of box 1: 30.35799pt
 width of box 2: 0pt

N 2015-07-13

\boxarraygetheight[⟨name⟩]{⟨macro⟩}{⟨index⟩}

Assigns the height of the box with the given ⟨index⟩ number from the box array ⟨name⟩ to a ⟨macro⟩. If no ⟨name⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨name⟩ is used. If the ⟨index⟩ is out of range, the ⟨macro⟩ will be set to `Opt`.

```
\tcbbox[size=small,colframe=blue!20,colback=yellow!5,on line,  
       reset and store to box array]{Test}  
  
\begin{tabular}{ll}  
  \useboxarray{1} & height of box 1: \boxarraygetheight{\mylen}{1} \mylen\\  
  \useboxarray{2} & height of box 2: \boxarraygetheight{\mylen}{2} \mylen  
\end{tabular}
```

Test height of box 1: 9.89883pt
 height of box 2: 0pt

N 2015-07-13

\boxarraygetdepth[⟨name⟩]{⟨macro⟩}{⟨index⟩}

Assigns the depth of the box with the given ⟨index⟩ number from the box array ⟨name⟩ to a ⟨macro⟩. If no ⟨name⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨name⟩ is used. If the ⟨index⟩ is out of range, the ⟨macro⟩ will be set to `Opt`.

```
\tcbbox[size=small,colframe=blue!20,colback=yellow!5,on line,  
       reset and store to box array]{Test}  
  
\begin{tabular}{ll}  
  \useboxarray{1} & depth of box 1: \boxarraygetdepth{\mylen}{1} \mylen\\  
  \useboxarray{2} & depth of box 2: \boxarraygetdepth{\mylen}{2} \mylen  
\end{tabular}
```

Test depth of box 1: 3.69884pt
 depth of box 2: 0pt

\boxarraygettotalheight [*<name>*] {*<macro>*} {*<index>*}

Assigns the total height of the box with the given *<index>* number from the box array *<name>* to a *<macro>*. If no *<name>* is given, the already existing **default** box array is used. It is considered an error, if a not existing box array *<name>* is used. If the *<index>* is out of range, the *<macro>* will be set to **Opt**.

— *continued from page 379* —

for demonstration purposes. With the tools of this section, a magazine type document could be created, but this still needs a lot of manual control.

```
\boxarrayreset
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
      store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & total height of box 1: \boxarraygettotalheight{\mylen}{1} \mylen \\
\useboxarray{2} & total height of box 2: \boxarraygettotalheight{\mylen}{2} \mylen
\end{tabular}
```

Test	total height of box 1: 13.59767pt total height of box 2: 0pt
------	---

19 Library fitting

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{fitting}
```

19.1 Macros of the Library

\tcbboxfit [*options*] {*box content*}

Creates a colored box where the given *box content* is fitted to the width and height of the box. A `tcbboxfit` has to have a fixed height. If no fixed height is given, a square box is constructed. In principle, most *options* for a `tcolorbox`^{P.12} can be used for `\tcbboxfit` with some restrictions. A `\tcbboxfit` cannot have a lower part and cannot be broken.

```
% \usepackage{lipsum} \tcbuselibrary{raster}
\tcbset{colframe=blue!50!black,colback=red!10!white,
        boxsep=0pt,top=1mm,bottom=1mm,left=1mm,right=1mm,
        fit algorithm=hybrid*,raster equal skip=1mm}
\begin{tcbraster}[raster columns=3,raster valign=bottom]
    \tcbboxfit[height=8cm]{\lipsum[1]}
    \tcbboxfit[height=4cm]{\lipsum[1]}
    \tcbboxfit[height=2cm]{\lipsum[1]}
\end{tcbraster}
\begin{tcbraster}[colback=green!10!white,boxsep=1mm]
    \tcbboxfit[height=4cm]{\lipsum[2]}
    \tcbboxfit[height=4cm,title=With a title]{\lipsum[2]}
\end{tcbraster}
```

Lore ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placaret. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lore ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placaret. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

With a title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

! See Section 21.6 on page 416 for more elaborate methods to create new commands.

\newtcboxfit [*init options*] {*name*} [*number*] [*default*] {*options*}

Creates a new macro *name* based on \tcboxfit. Basically, \newtcboxfit operates like \newcommand. The new macro *name* optionally takes *number*+1 arguments, where *default* is the default value for the optional first argument. The *options* are given to the underlying tcboxfit. The *init options* allow setting up automatic numbering, see Section 5 from page 101.

```
\newtcboxfit{\mybox}{colback=red!5!white,
colframe=red!75!black, width=4cm,
height=1.5cm, halign=center}

\mybox{This is my own box.}\par
\mybox{This is my own box with more text
to be written.}
```

This is my
own box.

This is my own
box with more
text to be written.

```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2]{colback=red!5!white,
colframe=red!75!black, fonttitle=\bfseries,
boxsep=1mm, left=0mm, right=0mm, top=0mm,
bottom=0mm, halign=center, valign=center,
nobeforeafter, width=#1, height=#2}

\mybox[2.5cm]{1cm}{First box}%
\mybox[2.5cm]{1cm}{Second box with more text} \\
\mybox[5cm]{2cm}{Third box with text} \\
\mybox[5cm]{3cm}{\lipsum[1]}
```

First box Second box
with more text

Third box with text

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, pharetra ac, adipiscing viverra felis. Curabitur dictum, viverra id, sem. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, lacinia ac, nunc. Praesent eget sem vel leo ultricies bibendum, id ullamcorper risus. Maecenas dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2]{colback=red!5!white,
colframe=red!75!black,
width=#2, height=#2/3*2, #1}

\mybox[colback=yellow]{5cm}%
{\lipsum[2]}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellius. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio, metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque et nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt uta. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

\renewtcboxfit [*init options*] {*name*} [*number*] [*default*] {*options*}

Operates like \newtcboxfit^{→ P. 384}, but based on \renewcommand instead of \newcommand. An existing macro is redefined.

\tcbfontsize{*factor*}

Selects a font size inside a tcolorbox which is scaled with the given *factor* relative to \tcbfitdim.

```
\tcbset{colback=red!5!white, colframe=red!75!black}
\begin{tcolorbox}[fit basedim=10pt]
\tcbfontsize{0.25} Very tiny, \\
\tcbfontsize{0.5} Small, \\
\tcbfontsize{1} Normal, \\
\tcbfontsize{2} Large, \\
\tcbfontsize{4} Huge. \\
\end{tcolorbox}
```

Very tiny,
Small,
Normal,
Large,
Huge.

19.2 Option Keys of the Library

The font size for the content of a box with fixed width and fixed height can be adjusted automatically. This is called the *fitbox capture mode*. Note that the fit control algorithm constructs a series of versions for the box and selects the 'best'. Therefore, the compilation time is quite longer than for a normal box. The algorithm will fail, if a different selected font size does not change the overall size of the box content. The `\tcbboxfit`^{→ P. 383} macro uses this algorithm by default.

! The fit control keys are only applicable to unbreakable boxes without a lower part. The box content should not change counters.

/tcb/fit (style, initially unset)

Sets the `/tcb/capture`^{→ P. 90} mode to **fitbox**, i. e. enables the font size adjustment algorithm. Thereby, a `tcolorbox`^{→ P. 12} acts like `\tcbboxfit`^{→ P. 383} where the given `<box content>` is fitted to the width and height of the box. Therefore, the box has to have a fixed height. If no fixed height is given, a square box is constructed. The font dimension `\tcboxfitdim` can also be used to adjust the margins of the box since a box with a tiny font may not need large margins. The number of constructed boxes is saved to the macro `\tcboxfitsteps` for analysis.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\newtcolorbox{fitting}[2][]{fit,height=#2,boxsep=1pt,valign=center,opacityupper=0.5,
top=0.4\tcboxfitdim,bottom=0.4\tcboxfitdim,left=0.75\tcboxfitdim,right=0.75\tcboxfitdim,
enhanced,watermark text={\tcboxfitsteps},colframe=blue!75!black,colback=white,#1}

\begin{fitting}{4cm}
\lipsum[1]
\end{fitting}

\begin{fitting}{2cm}
\lipsum[2]
\end{fitting}

\begin{fitting}{1cm}
\lipsum[3]
\end{fitting}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

/tcb/fit to=<width> and <height> (style, initially unset)

Shortcut for using `/tcb/fit` and setting the `<width>` and `<height>` values separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=3cm and 2cm]
This box content is fitted to the given
dimensions.
\end{tcolorbox}
```

This box content is fitted to the given dimensions.

/tcb/fit to height=<height> (style, initially unset)

Shortcut for using `/tcb/fit` and setting the `<height>` value separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to height=2cm]
This box content is fitted to the given
height.
\end{tcolorbox}
```

This box content is fitted to the given height.

/tcb/fit basedim=<length> (no default, initially 10pt)

Sets the starting font dimension for the font size adjustment algorithm to `<length>`. The algorithm never enlarges this dimension.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=4cm and 2cm]
Too few words for
the box.
\end{tcolorbox}

\begin{tcolorbox}[fit to=4cm and 2cm,
fit basedim=50pt]
Enough words for the box.
\end{tcolorbox}
```

Too few words for the box.

Enough words for the box.

/tcb/fit skip=<real value> (no default, initially 1.2)

Sets the skip value of the selected font to `<real value>` times `\tcbfitdim`.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
colframe=red!75!black, left=1mm,
right=1mm, boxsep=0mm}

\begin{tcolorbox}[fit to=5cm and 4cm,
fit skip=1.0 ]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/fit fontsize macros

(style, initially unset)

Redefines the standard L^AT_EX font size macros `\tiny`, `\scriptsize`, `\footnotesize`, `\small`, `\normalsize`, `\large`, `\Large`, `\LARGE`, `\huge`, and `\Huge`, to set font sizes relative to the current `\tcbfitdim`. Note that the display skip values for mathematical formulas are respected by the redefined macros.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
colframe=red!75!black, left=1mm,
right=1mm, boxsep=0mm}

\begin{tcolorbox}[fit to height=4cm]
{\Large\bfseries This text is
not adapted:\par}
\lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[fit to height=4cm,
fit fontsize macros ]
{\Large\bfseries This text is adapted:\par}
\lipsum[2]
\end{tcolorbox}
```

This text is not adapted:

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This text is adapted:

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\tcbset{colback=red!5!white,
colframe=red!75!black, left=1mm,
right=1mm, boxsep=0mm}

\let\realHuge=\Huge

\begin{tcolorbox}[fit basedim=7pt,
fontupper=\normalsize,
fit fontsize macros]
The relative relative font size macros
are also usable without the
\textit{fit} algorithm.\par
{\Huge Adapted Huge} ---
{\realHuge Original Huge}
\end{tcolorbox}
```

The relative relative font size macros are also usable without the `fit` algorithm.

Adapted Huge –
Original Huge

```
\tcbset{size=fbox,colback=red!5!white,
colframe=red!75!black}

\tcboxfit[height=5cm,
fit fontsize macros,
fonttitle=\normalsize\bfseries,
title=Adapted title]
{\lipsum[2]}
```

Adapted title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit height plus=(dimension)` (no default, initially 0pt)

The box is allowed to enlarge the fixed height up to the given `(dimension)`, before a font size fit is applied. An optional `/tcb/fit width plus`^{→ P.388} is tried after the height adaption.

```
% \usepackage{lipsum}
\tcset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
\lipsum[2]
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit width plus=(dimension)` (no default, initially 0pt)

The box is allowed to enlarge the fixed width up to the given `(dimension)`, before a font size fit is applied. An optional `/tcb/fit height plus`^{→ P.388} is tried before the width adaption.

```
% \usepackage{lipsum}
\tcset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
\lipsum[2]
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



Typically but not necessarily, the optional title of a `tcolorbox` is not part of the fit operation. If a `/tcb/fit width plus→ P.388` is applied, the title is also adapted to the new width. If counters are increased inside the title text, they may be increased more than one time. To avoid this, you are encouraged to use `/tcb/phantom→ P.94` or `/tcb/step and label→ P.94` to set counters or use automatic numbering, see Subsection 5.1 from page 101.

`/tcb/fit width from=<min> to <max>` (style, no default)

Sets the box width to `<min>` and allows the width to grow up to `<max>`.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,height=4cm}

\begin{tcolorbox}[fit,width=\linewidth/2]
\lipsum[2]
\end{tcolorbox}\par
\begin{tcolorbox}[fit width from=\linewidth/2 to \linewidth]
\lipsum[2]
\end{tcolorbox}\par
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit height from=<min> to <max>` (style, no default)

Sets the box height to $\langle min \rangle$ and allows the height to grow up to $\langle max \rangle$.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
bottom=1mm,right=1mm,boxsep=0mm,width=4cm,nobeforeafter,
fit height from=1cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit algorithm=(name)` (no default, initially `fontsize`)

Sets the algorithm for the fitting process *after* optionally width and height are adapted.
Feasible values for `<name>` are:

- **fontsize** (initial): The algorithm is a bisection method that adapts the font size until certain stop conditions are fulfilled. This is the most time-consuming method but it is robust and gives pleasant results.

! The used font has to be freely scalable for this method! Other content than text is not scaled down. The aspect ratio is fully guaranteed.

- **N 2014-10-29**: First, the `fontsize` algorithm is applied. If the font was scaled down and the resulting height is too small, the box is squeezed to fit the area.

! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully guaranteed.

- **areaset**: The algorithm calculates the area size for the text without scaling the font. The text box is shaped for the needed aspect ratio in one or two steps. Finally, it is scaled down with a standard `\resizebox` macro.

! The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully guaranteed.

- **N 2014-10-29**: The `areaset` algorithm is applied, but if the content was scaled down and the resulting height is too small, the box is squeezed to fit the area.

! The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully guaranteed.

- **hybrid**: First, this algorithm estimates the needed font size in one or two steps. Then an `areaset` fitting as above is applied.

! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully guaranteed.

- **N 2014-10-29**: First, this algorithm estimates the needed font size in one or two steps. Then an `areaset*` fitting as above is applied.

! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully guaranteed.

- **squeeze**: The text box is brutally scaled down to fit.

! The aspect ratio is very likely to be horrible. You should not use this method for final documents.

```
% \usepackage{lipsum}
\newtcbboxfit{mybox}[1]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
bottom=1mm,right=1mm,boxsep=0mm,width=3.5cm,height=7cm,nobeforeafter,
before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
enhanced,watermark text={\textcolor{red}{\tcbfitsteps}},
fonttitle=\bfseries,adjusted title=#1,fit algorithm=#1}

\mybox{fontsize}{\lipsum[2]}\hfill
\mybox{hybrid}{\lipsum[2]}\hfill
\mybox{areaseize}{\lipsum[2]}\hfill
\mybox{squeeze}{\lipsum[2]}
```

Quality `\dotfill` versus `\dotfill` Speed

fontsize

 Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

hybrid

 Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

areaseize

 Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

squeeze

 Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Quality versus Speed

```
% \usepackage{lipsum}
\newtcbboxfit{mybox}[2]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
size=tight,width=7.2cm,height=5cm,nobeforeafter,
before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
enhanced,fonttitle=\bfseries,adjusted title=#2,fit algorithm=#1}

\mybox{hybrid}{hybrid (possible gap at end)}{\lipsum[1]}\hfill
\mybox{hybrid*}{hybrid* (no gap but possibly squeezed)}{\lipsum[1]}
```

hybrid (possible gap at end)

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

hybrid* (no gap but possibly squeezed)

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



The following options set control parameters for the fit algorithm. Mainly, they apply to the `fontsize` variant, see [/tcb/fit algorithm](#)^{P.391}. The options should be seen as experimental and are likely to change in future versions, if necessary.

/tcb/fit maxstep=⟨number⟩ (no default, initially 20)

Sets the maximal step size for the font size adjustment algorithm. In normal situations, the algorithm stops before reaching the initial value of 20 steps. If the box content does not shrink, this value prevents an endless loop.

/tcb/fit maxfontdiff=⟨dimension⟩ (no default, initially 0.1pt)

The algorithm stops, if the font size is determined within a deviation of ⟨dimension⟩.

/tcb/fit maxfontdiffgap=⟨dimension⟩ (no default, initially 1pt)

The algorithm stops, if the number of lines is determined and the font size is determined within a deviation of ⟨dimension⟩.

/tcb/fit maxwidthdiff=⟨dimension⟩ (no default, initially 1pt)

The algorithm stops, if the (optionally) flexible box width is determined within a deviation of ⟨dimension⟩.

/tcb/fit maxwidthdiffgap=⟨dimension⟩ (no default, initially 10pt)

The algorithm stops, if the number of lines is determined and the (optionally) flexible box width is determined within a deviation of ⟨dimension⟩.

/tcb/fit warning=⟨value⟩ (no default, initially off)

Typically, the fit control algorithm constructs several auxiliary boxes to determine the optimal one. If not switched off, the construction of the auxiliary boxes may produce many `hbox` warnings. This option key changes the `\hbadness` value.

- **off**: Most of 'Underfull \hbox' and 'Overfull \hbox' warnings are switched off (including the ones for the finally used box).
- **on**: All warnings for all auxiliary boxes are displayed.
- **final**: Only warnings for the finally used box are displayed. Note that an additional box has to be constructed for these messages.

20 Library hooks

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{hooks}
```

For the skin related options, the library  skins has to be loaded separately.

20.1 Concept of Hooks

A hook is a placeholder in some L^AT_EX code where additional code can be added. For example, the L^AT_EX macro `\AtBeginDocument` adds code to a hook which is placed at the beginning of every document.

Several option keys of `tcolorbox` allow providing some code which is added to specific places of a colored box. For example, `/tcb/before upper`^{P. 63} places code before the content of the upper part. A following usage of this key overwrites any prior settings.

The library  hooks extends `/tcb/before upper`^{P. 63} and several more existing keys to 'hookable' versions, e.g. `/tcb/before upper app`^{P. 395} and `/tcb/before upper pre`^{P. 395}. The 'hookable' keys don't overwrite prior settings but either *append* or *prepend* the newly given code to the existing code.

The general naming convention (with some small exceptions) is:

- `<option key> app`: works like `<option key>` but *appends* its code to the existing code.
- `<option key> pre`: works like `<option key>` but *prepends* its code to the existing code.

If the original `<option key>` is used (again), all code will be overwritten. Therefore, the order of the option key usage is crucial.

```
% \usepackage{array,tabularx}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X} % see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
        colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
        coltitle=black,center title,
        tabularx={X||Y|Y|Y||Y},% this sets 'before upper' and 'after upper'
        before upper app={Group & One & Two & Three & Four & Sum\\\hline\hline} }
```

```
\begin{tcolorbox}[title=My table]
Red  & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\\hline
Blue  & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

20.2 Box Content Additions

The following option keys extend the options given in Subsection 4.11 from page 62.

/tcb/before title app=⟨code⟩ (no default)

Appends the given ⟨code⟩ to /tcb/before title^{→ P.62} after the color and font settings and before the content of the title.

/tcb/before title pre=⟨code⟩ (no default)

Prepends the given ⟨code⟩ to /tcb/before title^{→ P.62} after the color and font settings and before the content of the title.

/tcb/after title app=⟨code⟩ (no default)

Appends the given ⟨code⟩ to /tcb/after title^{→ P.62} after the content of the title.

/tcb/after title pre=⟨code⟩ (no default)

Prepends the given ⟨code⟩ to /tcb/after title^{→ P.62} after the content of the title.

/tcb/before upper app=⟨code⟩ (no default)

Appends the given ⟨code⟩ to /tcb/before upper^{→ P.63} after the color and font settings and before the content of the upper part.

/tcb/before upper pre=⟨code⟩ (no default)

Prepends the given ⟨code⟩ to /tcb/before upper^{→ P.63} after the color and font settings and before the content of the upper part.

/tcb/after upper app=⟨code⟩ (no default)

Appends the given ⟨code⟩ to /tcb/after upper^{→ P.63} after the content of the upper part.

/tcb/after upper pre=⟨code⟩ (no default)

Prepends the given ⟨code⟩ to /tcb/after upper^{→ P.63} after the content of the upper part.

```
% \tcbuselibrary{theorems}
\tcbset{ams align,%
  colback=yellow!10!white,colframe=red!50!black,
  before upper app={\frac{2}{\sqrt{2}}\sqrt{2}.\\},
  after upper pre={\sin\left(\frac{\pi}{2}\right)=1.},
}

\begin{tcolorbox}
\sum_{n=1}^{\infty} \frac{1}{n} = \infty.
\int x^2 dx = \frac{1}{3}x^3 + c.
\end{tcolorbox}
```

$$\frac{2}{\sqrt{2}} = \sqrt{2}. \quad (22)$$

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (23)$$

$$\int x^2 dx = \frac{1}{3}x^3 + c. \quad (24)$$

$$\sin\left(\frac{\pi}{2}\right) = 1. \quad (25)$$

`/tcb/before lower app=<code>` (no default)

Appends the given `<code>` to `/tcb/before lower`^{→ P. 64} after the color and font settings and before the content of the lower part.

`/tcb/before lower pre=<code>` (no default)

Prepends the given `<code>` to `/tcb/before lower`^{→ P. 64} after the color and font settings and before the content of the lower part.

`/tcb/after lower app=<code>` (no default)

Appends the given `<code>` to `/tcb/after lower`^{→ P. 64} after the content of the lower part.

`/tcb/after lower pre=<code>` (no default)

Prepends the given `<code>` to `/tcb/after lower`^{→ P. 64} after the content of the lower part.

20.3 Embedding into the Surroundings

The following option keys extend the options given in Subsection 4.14 from page 76.



The 'hookable' versions are usable inside the document. In the preamble, they can only be used after explicit setting of `/tcb/before`^{→ P. 76} and `/tcb/after`^{→ P. 76} or by e.g. `/tcb/parskip`^{→ P. 76}.

`/tcb/before app=<code>` (no default)

Appends the given `<code>` to `/tcb/before`^{→ P. 76} before the colored box.

`/tcb/before pre=<code>` (no default)

Prepends the given `<code>` to `/tcb/before`^{→ P. 76} before the colored box.

`/tcb/after app=<code>` (no default)

Appends the given `<code>` to `/tcb/after`^{→ P. 76} after the colored box.

`/tcb/after pre=<code>` (no default)

Prepends the given `<code>` to `/tcb/after`^{→ P. 76} after the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,before app={The box follows:\\[4pt]}, 
  after app={This is the end.}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

The box follows:

My title

This is a **tcolorbox**.

This is the end.

20.4 Overlays

The following option keys extend the options given in Subsection 4.12 from page 69.

/tcb/overlay app=⟨graphical code⟩ (no default)
Appends the given ⟨graphical code⟩ to /tcb/overlay^{→ P. 69.}

```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
enlarge top by=5.5mm,
overlay={\foreach \x in {2cm,3.5cm} {
\begin{scope}[shift={[xshift=\x]frame.north west}]}
\path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
\path[fill=black] (-0.2,0) arc (0:180:1mm);
\end{scope}}}}
\tcbset{ribbon/.style={overlay app={%
\path[fill=blue!75!white,draw=blue,double=white!85!blue,
preaction={opacity=0.6,fill=blue!75!white},
line width=0.1mm,double distance=0.2mm,
pattern=fivepointed stars,pattern color=white!75!blue]
([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
-- ++(-1,1) -- ++(-0.5,0) -- +(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[frogbox,ribbon,title=My title]
This is a \textbf{tcolorbox}. \par
Here, we apply a second overlay.
\end{tcolorbox}
```



/tcb/overlay pre=⟨graphical code⟩ (no default)
Prepends the given ⟨graphical code⟩ to /tcb/overlay^{→ P. 69.}.

/tcb/overlay unbroken app=⟨graphical code⟩ (no default)
Appends the given ⟨graphical code⟩ to /tcb/overlay unbroken^{→ P. 70.}.

/tcb/overlay unbroken pre=⟨graphical code⟩ (no default)
Prepends the given ⟨graphical code⟩ to /tcb/overlay unbroken^{→ P. 70.}.

/tcb/overlay first app=⟨graphical code⟩ (no default)
Appends the given ⟨graphical code⟩ to /tcb/overlay first^{→ P. 70.}.

/tcb/overlay first pre=⟨graphical code⟩ (no default)
Prepends the given ⟨graphical code⟩ to /tcb/overlay first^{→ P. 70.}.

<code>/tcb/overlay middle app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay middle</code> ^{→ P.70.}	
<code>/tcb/overlay middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay middle</code> ^{→ P.70.}	
<code>/tcb/overlay last app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay last</code> ^{→ P.70.}	
<code>/tcb/overlay last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay last</code> ^{→ P.70.}	
<code>/tcb/overlay broken app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay broken</code> ^{→ P.70.}	
<code>/tcb/overlay broken pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay broken</code> ^{→ P.70.}	
<code>/tcb/overlay unbroken and first app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay unbroken and first</code> ^{→ P.70.}	
<code>/tcb/overlay unbroken and first pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay unbroken and first</code> ^{→ P.70.}	
<code>/tcb/overlay middle and last app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay middle and last</code> ^{→ P.70.}	
<code>/tcb/overlay middle and last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay middle and last</code> ^{→ P.70.}	
<code>/tcb/overlay unbroken and last app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay unbroken and last</code> ^{→ P.70.}	
<code>/tcb/overlay unbroken and last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay unbroken and last</code> ^{→ P.70.}	
<code>/tcb/overlay first and middle app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay first and middle</code> ^{→ P.70.}	
<code>/tcb/overlay first and middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay first and middle</code> ^{→ P.70.}	

N 2014-09-19

<code>/tcb/overlay first and middle app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/overlay first and middle</code> ^{→ P.70.}	
<code>/tcb/overlay first and middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/overlay first and middle</code> ^{→ P.70.}	

N 2014-09-19

20.5 Watermarks

The following option keys extend the options given in Subsection 10.3 from page 157.

! Watermarks are special overlays. The `LIB hooks` library allows the combination of several watermarks and overlays.

`/tcb/watermark text app=<text>` (no default)

Appends a `/tcb/watermark text`^{→ P. 157} to the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.25,
  watermark text app=Basilica,watermark color=Navy
]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from
http://commons.wikimedia.org/wiki/File:Basilica_5.png

`/tcb/watermark text pre=<text>` (no default)

Prepends a `/tcb/watermark text`^{→ P. 157} to the colored box.

`/tcb/watermark text app on=<part> is <text>` (no default)

Appends a `/tcb/watermark text on`^{→ P. 157} the named `<part>` of a break sequence.

`/tcb/watermark text pre on=<part> is <text>` (no default)

Prepends a `/tcb/watermark text on`^{→ P. 157} the named `<part>` of a break sequence.

/tcb/watermark graphics app=⟨file name⟩ (no default)

Appends a /tcb/watermark graphics^{→ P. 158} referenced by ⟨file name⟩ to the colored box.

/tcb/watermark graphics pre=⟨file name⟩ (no default)

Prepends a /tcb/watermark graphics^{→ P. 158} referenced by ⟨file name⟩ to the colored box.

/tcb/watermark graphics app on=⟨part⟩ is ⟨file name⟩ (no default)

Appends a /tcb/watermark graphics on^{→ P. 158} the named ⟨part⟩ of a break sequence.

The picture is referenced by ⟨file name⟩.

/tcb/watermark graphics pre on=⟨part⟩ is ⟨file name⟩ (no default)

Prepends a /tcb/watermark graphics on^{→ P. 158} the named ⟨part⟩ of a break sequence.

The picture is referenced by ⟨file name⟩.

/tcb/watermark tikz app=⟨graphical code⟩ (no default)

Appends a /tcb/watermark tikz^{→ P. 159} with the given tikz ⟨graphical code⟩ to the colored box.

/tcb/watermark tikz pre=⟨graphical code⟩ (no default)

Prepends a /tcb/watermark tikz^{→ P. 159} with the given tikz ⟨graphical code⟩ to the colored box.

```
% \usepackage{tikz}
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
watermark color=Navy,watermark opacity=0.25,
smiley/.style={watermark tikz pre={%
\path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);}}}

\begin{tcolorbox}[enhanced,title=My title, watermark text=Watermark,
smiley]
\lipsum[1-2]
\end{tcolorbox}
```

My title

Lore ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark tikz app on=⟨part⟩ is ⟨graphical code⟩ (no default)

Appends a /tcb/watermark tikz on^{→ P. 159} the named ⟨part⟩ of a break sequence.

/tcb/watermark tikz pre on=⟨part⟩ is ⟨graphical code⟩ (no default)

Prepends a /tcb/watermark tikz on^{→ P. 159} the named ⟨part⟩ of a break sequence.

20.6 Underlays

The following option keys extend the options given in Section 10.8 on page 187. There are no app type keys since underlays are stackable by default.

<code>/tcb/underlay pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay</code> ^{→ P. 187} .	
<code>/tcb/underlay unbroken pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay unbroken</code> ^{→ P. 188} .	
<code>/tcb/underlay first pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay first</code> ^{→ P. 188} .	
<code>/tcb/underlay middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay middle</code> ^{→ P. 188} .	
<code>/tcb/underlay last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay last</code> ^{→ P. 188} .	
<code>/tcb/underlay boxed title pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay boxed title</code> ^{→ P. 188} .	
<code>/tcb/underlay broken pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay broken</code> ^{→ P. 188} .	
<code>/tcb/underlay unbroken and first pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay unbroken and first</code> ^{→ P. 188} .	
<code>/tcb/underlay middle and last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay middle and last</code> ^{→ P. 188} .	
<code>/tcb/underlay unbroken and last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay unbroken and last</code> ^{→ P. 188} .	
<code>/tcb/underlay first and middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/underlay first and middle</code> ^{→ P. 188} .	

N 2014-09-19

20.7 Finishes

The following option keys extend the options given in Section 10.9 on page 189. There are no app type keys since finishes are stackable by default.

<code>/tcb/finish pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish</code> ^{→ P. 189} .	
<code>/tcb/finish unbroken pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish unbroken</code> ^{→ P. 190} .	
<code>/tcb/finish first pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish first</code> ^{→ P. 190} .	
<code>/tcb/finish middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish middle</code> ^{→ P. 190} .	
<code>/tcb/finish last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish last</code> ^{→ P. 190} .	
<code>/tcb/finish broken pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish broken</code> ^{→ P. 190} .	
<code>/tcb/finish unbroken and first pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish unbroken and first</code> ^{→ P. 190} .	
<code>/tcb/finish middle and last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish middle and last</code> ^{→ P. 190} .	
<code>/tcb/finish unbroken and last pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish unbroken and last</code> ^{→ P. 190} .	
<code>N 2014-09-19 /tcb/finish first and middle pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/finish first and middle</code> ^{→ P. 190} .	

20.8 Skin Code

The following option keys extend the options given in Subsection 9.2 from page 130.

<code>/tcb/frame code app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/frame code</code> ^{→ P. 130} .	
<code>/tcb/frame code pre=<graphical code></code>	(no default)
Prepends the given <code><graphical code></code> to <code>/tcb/frame code</code> ^{→ P. 130} .	
<code>/tcb/interior titled code app=<graphical code></code>	(no default)
Appends the given <code><graphical code></code> to <code>/tcb/interior titled code</code> ^{→ P. 130} .	

```
\begin{tcolorbox}[title=My title,enhanced,colframe=Navy,
  frame code app={\draw[yellow,line width=1cm] (
    frame.south west)--(frame.north east);},
  interior titled code app={\draw[red,line width=1cm]
  (frame.north west)--(frame.south east);},
]
\lipsum[1]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

- /tcb/interior titled code pre=<graphical code>** (no default)
Prepends the given <graphical code> to /tcb/interior titled code^{→ P. 130}.
- /tcb/interior code app=<graphical code>** (no default)
Appends the given <graphical code> to /tcb/interior code^{→ P. 131}.
- /tcb/interior code pre=<graphical code>** (no default)
Prepends the given <graphical code> to /tcb/interior code^{→ P. 131}.
- /tcb/segmentation code app=<graphical code>** (no default)
Appends the given <graphical code> to /tcb/segmentation code^{→ P. 131}.
- /tcb/segmentation code pre=<graphical code>** (no default)
Prepends the given <graphical code> to /tcb/segmentation code^{→ P. 131}.
- /tcb/title code app=<graphical code>** (no default)
Appends the given <graphical code> to /tcb/title code^{→ P. 132}.
- /tcb/title code pre=<graphical code>** (no default)
Prepends the given <graphical code> to /tcb/title code^{→ P. 132}.

20.9 Extras

The following option keys extend the options given in Section 17.5 on page 359. There are no app type keys since extras are stackable by default.

N 2015-07-16	<code>/tcb/extras pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras unbroken pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras unbroken ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras first pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras first ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras middle pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras middle ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras last pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras last ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras broken pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras broken ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras unbroken and first pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras unbroken and first ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras middle and last pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras middle and last ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras unbroken and last pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras unbroken and last ^{→ P. 359} .	
N 2015-07-16	<code>/tcb/extras first and middle pre={⟨options⟩}</code>	(no default)
	Prepends the given ⟨options⟩ to /tcb/extras first and middle ^{→ P. 360} .	

21 Library

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{xparse}
```

This also loads the package `xparse` [12].

The purpose of this library is to give comfortable access to the powerful document command production with `xparse` for `tcolorbox`. See the `xparse` package documentation [12] for details about the argument *(specification)* used in this section.

21.1 Option Keys

`/tcb/verbatim` (style, no value)

Sets options for a *verbatim* style `\tcbox`^{P. 14}. Since the indented boxes may contain only very few words, the dimensions are made smaller and `/tcb/nobeforeafter`^{P. 76} and `/tcb/tcbox raise base`^{P. 92} are set.

```
\DeclareTotalTCBox{\myverb}{ v }{verbatim,
  colframe=red!75!black,colupper=blue}{#1}
\myverb{\textbf} is a \myverb{\LaTeX} command.
```

`\textbf` is a `\LaTeX` command.

`/tcb/IfNoValueTF={⟨argument⟩}{⟨true options⟩}{⟨false options⟩}` (no default)

Wraps the `\IfNoValueTF` command of `xparse` for option setting. If the *⟨argument⟩* has no value, the *⟨true options⟩* are set. Otherwise, the *⟨false options⟩* are set.

```
\DeclareTCColorBox{mybox}{ o }{colframe=red!75!black,
  IfNoValueTF={#1}{colback=red!5!white}{enhanced,interior style image=#1}}
\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[goldshade.png]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

/tcb/IfValueTF={⟨argument⟩}{⟨true options⟩}{⟨false options⟩} (no default)

Wraps the \IfValueTF command of `xparse` for option setting. If the ⟨argument⟩ has a value, the ⟨true options⟩ are set. Otherwise, the ⟨false options⟩ are set.

```
\DeclareTCColorBox{mybox}{ o }{colframe=red!75!black,colback=red!5!white,
  IfValueTF={#1}{title={\flqq #1\frqq},fonttitle=\bfseries}{}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[My title]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

«My title»

This is a tcolorbox.

/tcb/IfBooleanTF={⟨argument⟩}{⟨true options⟩}{⟨false options⟩} (no default)

Wraps the \IfBooleanTF command of `xparse` for option setting. If the ⟨argument⟩ is \BooleanTrue, the ⟨true options⟩ are set. If the ⟨argument⟩ is \BooleanFalse, the ⟨false options⟩ are set.

```
\DeclareTCColorBox{mybox}{ s }{colframe=red!75!black,
  IfBooleanTF={#1}{colback=yellow!50!red}{colback=red!5!white}{}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}*
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

21.2 Producing `tcolorbox` Environments and Commands

```
\DeclareTCBox[<init options>]{<name>}{<specification>}{<options>}
```

Creates a new environment `<name>` based on `tcolorbox`^{P. 12}.

Basically, `\DeclareTCBox` operates like `\DeclareDocumentEnvironment`. This means, the new environment `<name>` is constructed with the given argument `<specification>`. The `<options>` are given to the underlying `tcolorbox`^{P. 12}.

Note that `/tcb/savedelimiter`^{P. 26} is set to the given `<name>` automatically.

The `<init options>` allow setting up automatic numbering, see Section 5 from page 101.

The new environment is always created, irrespective of an already existing environment with the same name.

```
% counter from previous example
\DeclareTCBox[use counter from=pabox]{mybox}{ O{red} m d"" 0{} }
  {enhanced,colframe=#1!75!black,colback=#1!5!white,
   fonttitle=\bfseries,title={\thetcbcounter-#2},
   IfValueTF={#3}{watermark text={#3}}{},#4}

\begin{mybox}{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[blue]{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[green]{My title}"My Watermark"
This is a tcolorbox.
\end{mybox}

\begin{mybox}[yellow]{My title}[colbacktitle=yellow!50!white,coltitle=black]
This is a tcolorbox.
\end{mybox}

\begin{mybox}[purple]{My title}"All together"[coltitle=yellow]
This is a tcolorbox.
\end{mybox}
```

21.1 My title

This is a tcolorbox.

21.2 My title

This is a tcolorbox.

21.3 My title

This is a tcolorbox.

My Watermark

21.4 My title

This is a tcolorbox.

21.5 My title

This is a tcolorbox.

All together

\NewTColorBox [*init options*] {*name*} {*specification*} {*options*}

Operates like **\DeclareTColorBox**, but based on **\NewDocumentEnvironment** instead of **\DeclareDocumentEnvironment**. An error is issued if *name* has already been defined.

\RenewTColorBox [*init options*] {*name*} {*specification*} {*options*}

Operates like **\DeclareTColorBox**, but based on **\RenewDocumentEnvironment** instead of **\DeclareDocumentEnvironment**. An existing environment is redefined.

\ProvideTColorBox [*init options*] {*name*} {*specification*} {*options*}

Operates like **\DeclareTColorBox**, but based on **\ProvideDocumentEnvironment** instead of **\DeclareDocumentEnvironment**. The environment *name* is only created if it is not already defined.

\DeclareTotalTColorBox[*init options*]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}

Creates a new command $\langle name \rangle$ based on $\text{tcolorbox}^{\rightarrow \text{P. 12}}$. In contrast to $\text{\\DeclareTColorBox}^{\rightarrow \text{P. 407}}$, also the $\langle content \rangle$ of the tcolorbox is specified. Basically, $\text{\\DeclareTotalTColorBox}$ operates like $\text{\\DeclareDocumentCommand}$. This means, the new command $\langle name \rangle$ is constructed with the given argument $\langle specification \rangle$. The $\langle options \rangle$ are given to the underlying $\text{tcolorbox}^{\rightarrow \text{P. 12}}$ which is filled with the specified $\langle content \rangle$.

Note that $/tcb/savedelimiter^{\rightarrow \text{P. 26}}$ is set to the given $\langle name \rangle$ automatically.

The $\langle init options \rangle$ allow setting up automatic numbering, see Section 5 from page 101.

The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTColorBox{\diabox}{ O{} v m }
  { bicolor,nobeforeafter,equal height group=diabox,width=5.7cm,
    fonttitle=\bfseries\ttfamily,adjusted title={#2},center title,
    colframe=blue!20!black,leftupper=0mm,rightupper=0mm,colback=black!75!white,#1}
  { \tikz\path[fill zoom image={#2}] (0,0) rectangle (\linewidth,4cm);%
    \tcblower#3}

\diabox{blueshade.png}{Created with |GIMP|.\url{http://www.gimp.org}}
\diabox{goldshade.png}{Created with |GIMP|.\url{http://www.gimp.org}}
```



\NewTotalTColorBox[*init options*]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}

Operates like $\text{\\DeclareTotalTColorBox}^{\rightarrow \text{P. 409}}$, but based on $\text{\\NewDocumentCommand}$ instead of $\text{\\DeclareDocumentCommand}$. An error is issued if $\langle name \rangle$ has already been defined.

\RenewTotalTColorBox[*init options*]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}

Operates like $\text{\\DeclareTotalTColorBox}^{\rightarrow \text{P. 409}}$, but based on $\text{\\RenewDocumentCommand}$ instead of $\text{\\DeclareDocumentCommand}$. An existing command is redefined.

\ProvideTotalTColorBox[*init options*]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}

Operates like $\text{\\DeclareTotalTColorBox}^{\rightarrow \text{P. 409}}$, but based on $\text{\\ProvideDocumentCommand}$ instead of $\text{\\DeclareDocumentCommand}$. The command $\langle name \rangle$ is only created if it is not already defined.

21.3 Producing tcbx Commands

\DeclareTCBox [*init options*] {*\name*} {*specification*} {*options*}

Creates a new command *\name* based on *\tcbbox*^{P. 14}. Basically, **\DeclareTCBox** operates like **\DeclareDocumentCommand**. This means, the new command *\name* is constructed with the given argument *specification*. The *options* are given to the underlying *\tcbbox*^{P. 14}.

Note that */tcb/savedelimiter*^{P. 26} is set to the given *name* automatically.

The *init options* allow setting up automatic numbering, see Section 5 from page 101.

The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBox[use counter from=pabox]{\mybox}{ s m s }
{ nobeforeafter,colback=red!5!white,colframe=red!75!black,
  title={#2 (Box \thetcbcounter)},fonttitle=\bfseries,
  IfBooleanTF={#1}{enhanced,drop shadow}{},
  IfBooleanTF={#3}{colbacktitle=red!50!white}{} }
```

```
\mybox{Bird}{This is my first box.}
\hfill
\mybox*{Tree}{This is my second box.}
\par\bigskip
\mybox{Bike}*{This is my third box.}
\hfill
\mybox*{City}*{This is my fourth box.}
```

Bird (Box 21.6)

This is my first box.

Tree (Box 21.7)

This is my second box.

Bike (Box 21.8)

This is my third box.

City (Box 21.9)

This is my fourth box.

\NewTCBox [*init options*] {*\name*} {*specification*} {*options*}

Operates like **\DeclareTCBox**^{P. 410}, but based on **\NewDocumentCommand** instead of **\DeclareDocumentCommand**. An error is issued if *\name* has already been defined.

\RenewTCBox [*init options*] {*\name*} {*specification*} {*options*}

Operates like **\DeclareTCBox**^{P. 410}, but based on **\RenewDocumentCommand** instead of **\DeclareDocumentCommand**. An existing command is redefined.

\ProvideTCBox [*init options*] {*\name*} {*specification*} {*options*}

Operates like **\DeclareTCBox**^{P. 410}, but based on **\ProvideDocumentCommand** instead of **\DeclareDocumentCommand**. The command *\name* is only created if it is not already defined.

\DeclareTotalTCBox[*init options*]{\<name>}{\<specification>}{\<options>}{\<content>}

Creates a new command `\<name>` based on `\tcbx`^{P.14}. In contrast to `\DeclareTCBox`, also the `\<content>` of the `tcb` is specified.

Basically, `\DeclareTotalTCBox` operates like `\DeclareDocumentCommand`. This means, the new command `\<name>` is constructed with the given argument `\<specification>`. The `\<options>` are given to the underlying `\tcbx`^{P.14} which is filled with the specified `\<content>`. Note that `/tcb/savedelimiter`^{P.26} is set to the given `\<name>` automatically.

The `\<init options>` allow setting up automatic numbering, see Section 5 from page 101.

The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTCBox{\myverb}{ O{red} v O{} }
{ fontupper=\ttfamily,nobeforeafter,tcbx raise base,arc=0pt,outer arc=0pt,
  top=0pt,bottom=0pt,left=0mm,right=0mm,
  lefrule=0pt,rightrule=0pt,toprule=0.3mm,bottomrule=0.3mm,boxsep=0.5mm,
  colback=#1!10!white,colframe=#1!50!black,#3}{#2}

To set a word \textbf{bold} in \myverb{\LaTeX}, use
\myverb[green]{\textbf{bold}}. Alternatively, write
\myverb[yellow]{\bfseries bold}.

In \myverb[blue]{\LaTeX}[enhanced,fuzzy halo], other font settings are
done in the same way, e.g. \myverb{\textit}, \myverb{\itshape}\\
or \myverb[brown]{\texttt}, \myverb[brown]{\ttfamily}.
```

To set a word **bold** in `\LaTeX`, use `\textbf{bold}`. Alternatively, write `\bfseries bold`. In `\LaTeX`, other font settings are done in the same way, e.g. `\textit`, `\itshape` or `\texttt`, `\ttfamily`.

The next example uses `\lstinline` from the `listings` package to typeset the verbatim content.

```
% \usepackage{listings} or \tcbuselibrary{listings}
\DeclareTotalTCBox{\commandbox}{ s v }
{verbatim,colupper=white,colback=black!75!white,colframe=black}
{\IfBooleanTF{#1}{\textcolor{red}{\ttfamily\bfseries > }}{}%}
\lstinline[language=command.com,keywordstyle=\color{blue!35!white}\bfseries]^#2^

\commandbox*{cd "My Documents"} changes to directory \commandbox{My Documents}.

\commandbox*{dir /A} lists the directory content.

\commandbox*{copy example.txt d:\target} copies \commandbox{example.txt} to
\commandbox{d:\target}.
```

> `cd "My Documents"` changes to directory `My Documents`.

> `dir /A` lists the directory content.

> `copy example.txt d:\target` copies `example.txt` to `d:\target`.

`\NewTotalTCBox[init options]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}`

Operates like `\DeclareTotalTCBox`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\langle name\rangle` has already been defined.

`\RenewTotalTCBox[init options]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}`

Operates like `\DeclareTotalTCBox`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTotalTCBox[init options]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}`

Operates like `\DeclareTotalTCBox`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\langle name\rangle` is only created if it is not already defined.

`\tcbxverb[options]{\langle verbatim box content\rangle}`

Creates a colored box based on `\tcbx`^{P.14} which is fitted to the width of the given `\langle verbatim box content\rangle`. The underlying `\tcbx`^{P.14} is styled with `/tcb/verbatim`^{P.405} plus the given `\langle options\rangle`. The difference to `\tcbx`^{P.14} is that the `\langle verbatim box content\rangle` is interpreted *verbatim*. Therefore, `\tcbxverb` acts similar to `\verb`.

```
\tcbxverb{\LaTeX}, \tcbxverb[colback=blue!10!white,colupper=blue]{\LaTeX},  
\tcbxverb[blank,fuzzy halo]{\LaTeX}, \tcbxverb[beamer]{\LaTeX},  
\tcbxverb[enhanced,skin=enhancedmiddle jigsaw,colframe=red]{\LaTeX}.
```

`\LaTeX`, `\LaTeX`, `\LaTeX`, `\LaTeX`, | `\LaTeX` |.

21.4 Producing `tcblisting` Environments



The following commands need the `listings` library to be included.

\DeclareTCBListing [*init options*] {*name*} {*specification*} {*options*}

Creates a new environment *name* based on `tcblisting`^{P.288}.

Basically, `\DeclareTCBListing` operates like `\DeclareDocumentEnvironment`. This means, the new environment *name* is constructed with the given argument *specification*.

The *options* are given to the underlying `tcblisting`^{P.288}.

Note that `/tcb/savedelimiter`^{P.26} is set to the given *name* automatically.

The *init options* allow setting up automatic numbering, see Section 5 from page 101.

The new environment is always created, irrespective of an already existing environment with the same name.

```
\DeclareTCBListing{mybox}{ s 0{} m }%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  IfBooleanTF={#1}
    {listing side text}
    {text side listing},
  title=#3,#2}

\begin{mybox}{Listing Box}
This is my
\TeX\ box.
\end{mybox}
\bigskip

\begin{mybox}{*{Listing Box}}
This is my
\TeX\ box.
\end{mybox}
\bigskip

\begin{mybox}[colback=yellow]
{Listing Box}
This is my
\TeX\ box.
\end{mybox}
```

Listing Box

This is my
\TeX\ box. This is my
\TeX\ box.

Listing Box

This is my
\TeX\ box. This is my
\TeX\ box.

Listing Box

This is my
\TeX\ box. This is my
\TeX\ box.

\NewTCBListing [*init options*] {*name*} {*specification*} {*options*}

Operates like `\DeclareTCBListing`^{P.413}, but based on `\NewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An error is issued if *name* has already been defined.

\RenewTCBListing [*init options*] {*name*} {*specification*} {*options*}

Operates like `\DeclareTCBListing`^{P.413}, but based on `\RenewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An existing environment is redefined.

\ProvideTCBListing [*init options*] {*name*} {*specification*} {*options*}

Operates like `\DeclareTCBListing`^{P.413}, but based on `\ProvideDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. The environment *name* is only created if it is not already defined.

Caveats of using an environment ending with an optional argument

```
\DeclareTCBListing{mybox}{ O{} }{listing only,#1}

\begin{mybox}[colframe=red]
\good
\end{mybox}

\begin{mybox}[colframe=red]\good\end{mybox}

\begin{mybox}
\good
\end{mybox}

\begin{mybox} \good\end{mybox}

\begin{mybox}\bad!\end{mybox}

\begin{mybox}
[\good]
\end{mybox}

\begin{mybox} [\good]\end{mybox}

\begin{mybox} [\bad!]\end{mybox}
```

21.5 Producing tcbinputlisting Commands



The following commands need the `\listings` library to be included.

\DeclareTCBInputListing [*init options*] {*\name*} {*specification*} {*options*}

Creates a new command *\name* based on *\tcbinputlisting*^{P. 290}. Basically, *\DeclareTCBInputListing* operates like *\DeclareDocumentCommand*. This means, the new command *\name* is constructed with the given argument *specification*. The *options* are given to the underlying *\tcbinputlisting*^{P. 290}.

The *init options* allow setting up automatic numbering, see Section 5 from page 101.

The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ 0{} 0{red} m }{%
    listing file={#3},title=Listing~\thetcbcounter,
    colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
    fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
[blue]{\jobname.tcbtemp}
```

Listing 21.10

This is the included file content:

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ 0{}%
    0{red} m }{%
    listing file={#3},title=Listing~\thetcbcounter,
    colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
    fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
[blue]{\jobname.tcbtemp}
```

\NewTCBInputListing [*init options*] {*\name*} {*specification*} {*options*}

Operates like *\DeclareTCBInputListing*^{P. 415}, but based on *\NewDocumentCommand* instead of *\DeclareDocumentCommand*. An error is issued if *\name* has already been defined.

\RenewTCBInputListing [*init options*] {*\name*} {*specification*} {*options*}

Operates like *\DeclareTCBInputListing*^{P. 415}, but based on *\RenewDocumentCommand* instead of *\DeclareDocumentCommand*. An existing command is redefined.

\ProvideTCBInputListing [*init options*] {*\name*} {*specification*} {*options*}

Operates like *\DeclareTCBInputListing*^{P. 415}, but based on *\ProvideDocumentCommand* instead of *\DeclareDocumentCommand*. The command *\name* is only created if it is not already defined.

21.6 Producing `tboxfit` Commands



The following commands need the `\tcbfitting` library to be included.

`\DeclareTCBoxFit` [*init options*] {*\name*} {*specification*} {*options*}

Creates a new command *\name* based on `\tcbxboxfit`^{P. 383}. Basically, `\DeclareTCBoxFit` operates like `\DeclareDocumentCommand`. This means, the new command *\name* is constructed with the given argument *specification*. The *options* are given to the underlying `\tcbxboxfit`^{P. 383}.

Note that `/tcb/savedelimiter`^{P. 26} is set to the given *name* automatically.

The *init options* allow setting up automatic numbering, see Section 5 from page 101.

The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTCBoxFit{\mybox}{ O{} m o }
  {colback=red!5!white,
   colframe=red!75!black,
   width=#2,height=#2/3*2,
   IfValueTF={#3}{height=#3}{},
   #1}

\mybox[colback=yellow]{5cm}%
  {\lipsum[2]}

\mybox[colback=yellow]{5cm}[4cm]{\lipsum[2]}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`\NewTCBoxFit` [*init options*] {*\name*} {*specification*} {*options*}

Operates like `\DeclareTCBoxFit`^{P. 416}, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if *\name* has already been defined.

`\RenewTCBoxFit` [*init options*] {*\name*} {*specification*} {*options*}

Operates like `\DeclareTCBoxFit`^{P. 416}, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTCBoxFit` [*init options*] {*\name*} {*specification*} {*options*}

Operates like `\DeclareTCBoxFit`^{P. 416}, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command *\name* is only created if it is not already defined.

```
\DeclareTotalTCBoxFit[<init options>]{<\name>}{<specification>}{<options>}{<content>}
```

Creates a new command `\<name>` based on `\tcboxfit`^{P.383}. In contrast to `\DeclareTCBoxFit`, also the `<content>` of the `tcboxfit` is specified.

Basically, `\DeclareTotalTCBoxFit` operates like `\DeclareDocumentCommand`. This means, the new command `\langle name \rangle` is constructed with the given argument `specification`. The `options` are given to the underlying `\tcbxofitP. 383` which is filled with the specified `content`.

Note that `/tcb/savedelimiter`^{P.26} is set to the given $\langle name \rangle$ automatically.

The `<init options>` allow setting up automatic numbering, see Section 5 from page 101.

The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTotalTCBoxFit{\multibox}{ O{} m O{10} m }
  {nobeforeafter,colback=red!5!white,colframe=red!75!black,width=#2,height=#2/3*2,
   valign=center,#1}
  { \foreach \n in {1,...,#3} { #4} }

\multibox{5cm}{I shall not repeat.}
\multibox[colframe=blue!75!white]{5cm}[20]{I shall not repeat.} \\
\multibox[colback=yellow,height=5cm]{14cm}[100]{I shall not repeat.}
```

```
\NewTotalTCBoxFit[<init options>]{\name}{\specification}{\options}{\content}
```

Operates like `\DeclareTotalTCBoxFit`^{P.417}, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\langle name\rangle` has already been defined.

```
\RenewTotalTCBoxFit[{\langle init options\rangle}]{\langle name\rangle}{\langle specification\rangle}{\langle options\rangle}{\langle content\rangle}
```

Operates like `\DeclareTotalTCBoxFit`^{P.417}, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

```
\ProvideTotalTCBoxFit[<init options>]{\<name>}{<specification>}{<options>}{<content>}
```

Operates like `\DeclareTotalTCBoxFit`^{P.417}, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\<name>` is only created if it is not already defined.

22 Library LIB `external`

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{external}
```

The purpose of this library is to support externalization of document snippets like graphics or boxes which can be compiled stand-alone. These snippets are written to external files, compiled and the resulting pdf files are included to the main document as images. The whole procedure saves compilation time, if such a snippet is costly to compile but needs to compile just once or very seldom.

There are very good alternatives to this library. One should consider the `standalone` package or the TikZ externalization library instead. The LIB `external` library is something in between and can be seen as poor man variant of the TikZ externalization library.

The main differences between TikZ externalization and LIB `external` are:

- TikZ `external` compiles the whole original document in a sophisticated way while LIB `external` uses only the preamble or a part of the preamble of the original document.
- TikZ `external` can automatically externalize all `tikzpicture` environments while LIB `external` externalizes marked snippets only.
- Code snippets to be externalized by LIB `external` are not restricted to `tikzpicture` environments. But these snippets have to be stand-alone without dependencies to the rest of the document.

Why should somebody use LIB `external` instead of the more powerful TikZ `external`? One reason could be compilation speed, but the main reason for creating the library at all was that TikZ `external` tends to choke on complicated documents where the sophisticated mechanism stumbles. Since LIB `external` does not use the original document body for compilation, this cannot happen.



Source snippets are compiled, if their `md5` checksum has changed. They are not compiled automatically, if option settings are changed or anything outside the snippet is changed. Use `/tcb/external/force remake`^{→ P. 419} to force compilation in this case or simply delete the externalized pdf oder md5 files.



To use the externalization options, the compiler has to be called with the `-shell-escape` permission to authorize potentially dangerous system calls. Be warned that this is a security risk.

22.1 Preparation of a Document for Externalization

The preamble of the main document has to contain the `\tcbEXTERNALIZE`^{P. 419} command. Without this command, no externalization operation will be executed.

N 2015-03-11

`\tcbEXTERNALIZE`

It is mandatory for externalization that this command is used once in the preamble of the main document. Every setting *before* `\tcbEXTERNALIZE`^{P. 419} will also be used for compiling an external snippet. Every setting *after* `\tcbEXTERNALIZE`^{P. 419} will be ignored for compiling an external snippet. Place this command right before `\begin{document}`, if you are not absolutely sure about another place.

The main document has to look like the following:

```
\documentclass[a4paper]{book}%
% for example
\usepackage{...}%
%
% ...
% Typically, all or the very most settings for the document.

\tcbEXTERNALIZE% Typically, just before \begin{document}

% Additional settings which are ABSOLUTELY irrelevant for the
% stand-alone snippets.
%
\begin{document}
% The document.
% This also contains the marked snippets for externalization.
\end{document}
```

During compilation, a `/tcb/external/runner`^{P. 419} file is dynamically created (several times). This is the actual main file for compiling an externalized snippet.

N 2015-03-11

`/tcb/external/runner=<file name>` (no default, initially `\jobname_run.tex`)

Sets the *<file name>* for dynamically created `runner` file. This is the actual main file for a document snippet. Typically, the initial setting is not needed to be changed.

```
\tcbset{external/runner=myrunner.tex}
```

N 2015-03-11 `/tcb/external/prefix=<text>` (no default, initially `external/`)

The *<text>* is prefixed to any `/tcb/external/name`^{P. 421} for an externalization snippet. The initial setting implies saving all snippets into an `external/` subdirectory. Depending on the operation system, the subdirectory may have to be created manually once.

```
% Use a 'real' prefix instead of writing into a subdirectory:
\tcbset{external/prefix=ext_}
```

N 2015-03-11

`/tcb/external/externalize=true|false` (default `true`, initially `true`)

If set to `true`, the marked snippets are compiled if necessary. If set to `false`, the marked snippets are not compiled but included as text. `/tcb/external/externalize`^{P. 419} can only be used after `\tcbEXTERNALIZE`^{P. 419}.

N 2015-03-11

`/tcb/external/force remake=true|false` (default `true`, initially `false`)

If set to `true`, the marked snippets are always compiled. If set to `true`, the marked snippets are compiled only if necessary. The necessity is given, if a compiled pdf file is missing or the `md5` checksum of the source snippet has changed.

N 2015-03-11

`/tcb/external/!` (style)

Shortcut for setting `/tcb/external/force remake`^{P. 419} to `true`.

N 2015-06-12

`/tcb/external/-` (style)

Shortcut for setting `/tcb/external/externalize`^{P. 419} to `false`.


22.2 Marking Externalization Snippets

N 2015-03-11

```
\begin{tcbexternal}[\langle options \rangle]{\langle name \rangle}  
  <environment content>  
\end{tcbexternal}
```

Marks the environment content as a snippet for externalization. Typically, the content is a `tikzpicture` or something similar. It is important to note that the snippet should not have any dependencies with the rest of the document, e.g. referencing counters or setting counters is not possible. The `\langle name \rangle` is automatically prefixed with `/tcb/external/prefix`^{P. 419}. In combination, this has to be a unique file name. It is advised to not use spaces or umlauts for the name. The `\langle options \rangle` are keys from the `/tcb/external/` key tree.

```
\begin{tcbexternal}{example_tikzpicture}  
  \begin{tikzpicture}  
    \path[fill=yellow!50!white] (0,0) circle (11mm);  
    \path[fill=white] (0,0) circle (9mm);  
    \foreach \w/\c in {90/red,210/green,330/blue}  
      {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}  
  \end{tikzpicture}  
\end{tcbexternal}
```



If a `tcolorbox`^{P. 12} is externalized, one should use `/tcb/nobeforeafter`^{P. 76} for the box. Indention and distances to the text before and after have to be given separately outside the `tcbexternal`^{P. 420} environment.

```
\noindent%  
\begin{tcbexternal}[minipage]{example_tcolorbox}  
  \begin{tcolorbox}[nobeforeafter,enhanced,  
    fonttitle=\bfseries,title=Externalized Box,  
    colframe=red!50!black,drop fuzzy shadow,  
    interior style={fill overzoom image=goldshade.png}]  
    This complete tcolorbox is externalized. One cannot use numbered  
    boxes here. Note the \texttt{minipage} option which tells the  
    current line width to the external snippet.  
  \end{tcolorbox}  
\end{tcbexternal}
```

Externalized Box

This complete tcolorbox is externalized. One cannot use numbered boxes here. Note the `minipage` option which tells the current line width to the external snippet.

```
\begin{tcolorbox}[nobeforeafter,enhanced,
  fonttitle=\bfseries,title=Externalized Box,
  colframe=blue!50!black,
  interior style={fill overzoom image=blueshade.png}]
\begin{tcbexternal}[minipage]{example_tcolorbox2}
\color{white}%
The interior of the tcolorbox is externalized.
One can use numbered boxes without problems.
Note that the text color has to be set for the text manually
since it is converted into an image.
\end{tcbexternal}
\end{tcolorbox}
```

Externalized Box

The interior of the tcolorbox is externalized. One can use numbered boxes without problems. Note that the text color has to be set for the text manually since it is converted into an image.

```
\begin{tcbexternal}[minipage]{example_tabularx}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}%
\begin{tabularx}{\linewidth}{|l|Y|Y|Y||Y|}\hline
Group & One & Two & Three & Four & Sum\\\hline
Red & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\\hline
Blue & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\\hline
Sum & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00\\\hline
\end{tabularx}
\end{tcbexternal}
```

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

N 2015-03-11

/tcb/external/name=<name>

(no default, initially unnamed)

The <name> is automatically prefixed with /tcb/external/prefix^{P.419}. In combination, this has to be a unique file name for externalization. Typically, this key is not used directly but is set indirectly as mandatory parameter, see tcbexternal.

```
\begin{extcolorbox}[(options)]{<name>}[(tcolorbox options)]
<environment content>
\end{extcolorbox}
```

This is an externalized version of `tcolorbox`^{→ P. 12} created using `\newtcexternalizetcolorbox`^{→ P. 427}:

```
\newtcexternalizetcolorbox{extcolorbox}{tcolorbox}{}{}
```

`<options>` and `<name>` are given to the underlying `tcbexternal`^{→ P. 420} environment, while `<tcolorbox options>` are given to `tcolorbox`^{→ P. 12}.

- ! Note that you should not redefine `/tcb/before`^{→ P. 76} and `/tcb/after`^{→ P. 76} inside the `<tcolorbox options>`, since the externalized version would not be identical to the non-externalized otherwise.

```
\begin{extcolorbox}[minipage]{example_extcolorbox}
[ enhanced,colframe=red!50!black,colback=yellow!10,
  fonttitle=\bfseries,drop fuzzy shadow,
  title=My external box ]
```

This box is completely externalized.

```
\begin{tcolorbox}[colframe=blue,colback=blue!5,before skip=6pt]
Inner box.
\end{tcolorbox}
\end{extcolorbox}
```

My external box

This box is completely externalized.

Inner box.

- ! • **Never** externalize numbered boxes.
- **Never** externalize boxes which contain references to other things, e.g. using `\ref` or `\cite`.
- **Never** externalize breakable boxes.


```
\begin{extikzpicture}[\langle options \rangle]{\langle name \rangle}[\langle tikz options \rangle]
  <environment content>
\end{extikzpicture}
```

This is an externalized version of `tikzpicture` created using
`\newtcbexternalizeenvironment`^{→ P. 427}:

```
\newtcbexternalizeenvironment{extikzpicture}{tikzpicture}{}{}{}
```

`\langle options \rangle` and `\langle name \rangle` are given to the underlying `tcbexternal`^{→ P. 420} environment, while `\langle tikz options \rangle` are given to `tikzpicture`.

```
\begin{center}
\begin{extikzpicture}[
  preamble={\usepackage{pgfplots}}, % add package for external graph
  input source on error=false, % do not load source on error
]{example_pgfplots}
\pgfplotsset{width=12cm}
\begin{axis}[3d box=background,grid=major,
  xlabel=$x$, ylabel=$y$, zlabel=$z$, view/h=40,
  mesh/interior colormap name=hot,
  colormap/blackwhite,
  z buffer=sort,domain=0:90,y domain=0:60,
  zmin=0,zmax=2,z post scale=1.2,
]
\addplot3[surf,mesh/interior colormap name=blackwhite,
  colormap/hot,] ( {cos(x)}, {sin(x)}, {2*sin(y)} );
\addplot3[surf] ( {2*cos(x)*cos(y)}, {2*sin(x)*cos(y)}, {2*sin(y)} );
\end{axis}
\end{extikzpicture}
\end{center}
```




N 2015-03-11

/tcb/externalize listing=<name> (style, no default)

The text content of a `tcblisting`^{→ P. 288} is externalized with the given `<name>`. Note that the listing part is not externalized.

```
\begin{tcblisting}{externalize listing=example_listing,
  bicolor,colback=yellow!10,colframe=yellow!50!black,
  colbacklower=white,center lower}
\begin{tikzpicture}
  \path [fill=yellow!50!white] (0,0) circle (11mm);
  \path [fill=white] (0,0) circle (9mm);
  \foreach \w/\c in {90/red,210/green,330/blue}
    {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
  \path [fill=yellow!50!white] (0,0) circle (11mm);
  \path [fill=white] (0,0) circle (9mm);
  \foreach \w/\c in {90/red,210/green,330/blue}
    {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



N 2015-03-11

/tcb/externalize listing!=<name> (style, no default)

Combination of /tcb/externalize listing^{→ P. 424} and /tcb/external/force remake^{→ P. 419}.

N 2015-03-11

/tcb/externalize example=<name> (style, no default)

The text content of a `dispExample*`^{→ P. 435} is externalized with the given `<name>`. Note that the listing part is not externalized.

```
\begin{dispExample*}{sidebyside,externalize example=example_example}
\tikz\path[shading=ball,
  ball color=red] circle (7mm);
\end{dispExample*}
```

```
\tikz\path[shading=ball,
  ball color=red] circle (7mm);
```



N 2015-03-11

/tcb/externalize example!=<name> (style, no default)

Combination of /tcb/externalize example^{→ P. 424} and /tcb/external/force remake^{→ P. 419}.

22.3 Customization

N 2015-03-11 **/tcb/external/safety=⟨length⟩** (no default, initially 2mm)

The snippet box is surrounded with a safety border with a thickness of ⟨length⟩. This border is automatically trimmed during picture inclusion. The reason for this mechanism is to catch box content which extrudes over the bounding box. For example, shadows of a `tcolorbox` are painted outside the bounding box and would be lost otherwise.

N 2015-03-11 **/tcb/external/environment=⟨env⟩** (no default, initially unset)

Surrounds the exported snippet text with an environment ⟨env⟩ without parameters. Note that this option is ignored for `/tcb/externalize listing`.

N 2015-05-05 **/tcb/external/environment with percent=true|false** (default true, initially true)

If set to `true`, the `\begin` and `\end` code of `/tcb/external/environment`^{→ P. 425} is appended with a percent sign. For verbatim environments, this option typically has to be set to `false`.

N 2015-03-11 **/tcb/external/minipage=⟨length⟩** (default `\ linewidth`, initially unset)

Surrounds the exported snippet text with a minipage. The optional ⟨length⟩ parameter sets the width of the minipage. Note that the default width is the current line width of the main document. See `tcbexternal`^{→ P. 420} for examples. Note that this option is ignored for `/tcb/externalize listing`.

N 2015-03-11 **/tcb/external/plain** (no value, initially set)

Removes any text which was set to surround the snippet. This removes the setting of `/tcb/external/minipage`^{→ P. 425}, but is independent of `/tcb/external/safety`^{→ P. 425}.

N 2015-03-11 **/tcb/external/compiler=⟨text⟩** (no default, initially pdflatex)

Sets the name of the compiler for the snippets. Note that this compiler has to support the `\pdfmdfivesum` primitive e.g. using the `pdftexcmds` package. This should work for `xelatex` and `lualatex`.

N 2015-03-11 **/tcb/external/runs=⟨number⟩** (no default, initially 1)

Sets the number of compiler runs for the snippet.

```
\begin{tcbexternal}[minipage,runs=2]{example_raster}
\begin{tcbitemize}[raster equal height,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem \Huge Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
\end{tcbexternal}
```

One

TWO

Three

Four

N 2015-03-11 **/tcb/external/input source on error=true|false** (default true, initially true)

If set to `true`, the source code of the snippet is loaded instead of the failed pdf picture. Typically, this will lead to an error stop at the faulty place of the source and such helps detecting the cause. If the source input compiles without error, the document setup may be incorrect, see Section 22.1 on page 419. Maybe, the `external/` subdirectory has to be created manually in this case, see `/tcb/external/prefix`^{→ P. 419}.

If the option is set to `false`, the compilation stops immediately on an error. The log file of the external snippet has to be consulted for error messages in this case.

N 2015-05-05	<code>/tcb/external/preclass=<code></code>	(no default, initially unset)
The given <code><code></code> is added before the snippet document. Typically, this means before <code>\documentclass</code> . This is not used for compilation of the main document.		
N 2015-05-05	<code>/tcb/external/PassOptionsToPackage={<options>}{{<package>}}</code>	(no default, initially unset)
The given <code><options></code> are passed to the given <code><package></code> for the snippet document. This is a shortcut for using <code>/tcb/external/preclass</code> ^{P. 426} with <code>\PassOptionsToPackage</code> . This not used for compilation of the main document.		
N 2015-05-05	<code>/tcb/external/PassOptionsToClass={<options>}{{<class>}}</code>	(no default, initially unset)
The given <code><options></code> are passed to the given <code><class></code> for the snippet document. This is a shortcut for using <code>/tcb/external/preclass</code> ^{P. 426} with <code>\PassOptionsToClass</code> . This not used for compilation of the main document.		
N 2015-05-05	<code>/tcb/external/clear preclass</code>	(no value)
Removes all additional <code>/tcb/external/preclass</code> ^{P. 426} settings.		
N 2015-03-11	<code>/tcb/external/preamble=<code></code>	(no default, initially unset)
The given <code><code></code> is added to the preamble of the snippet document. This is not used for compilation of the main document.		
N 2015-05-05	<code>/tcb/external/preamble tcbset=<options></code>	(no default, initially unset)
The given <code><options></code> are added as parameter for <code>\tcbset</code> ^{P. 13} to the preamble of the snippet document. This are not used for compilation of the main document.		
N 2015-03-16	<code>/tcb/external/clear preamble</code>	(no value)
Removes all additional <code>/tcb/external/preamble</code> ^{P. 426} settings.		
N 2015-03-11	<code>\tcbifexternal{<true>}{{<false>}}</code>	

```
\tcbifexternal{
  \usepackage{onlyforexternal}
}{%
  \usepackage{onlyformain}
}
```

N 2015-03-11

\newtcbexternalizeenvironment{<newenv>}{<env>}{<options>}{<begin>}{<end>}

Creates a new environment $\langle newenv \rangle$ which is based on $\text{tcbexternal}^{\rightarrow P. 420}$. This environment takes *at least* one optional parameter and one mandatory parameter. These two parameters are passed to $\text{tcbexternal}^{\rightarrow P. 420}$. Further, the given $\langle options \rangle$ are always added to the option list of $\text{tcbexternal}^{\rightarrow P. 420}$.

The environment content is externalized and the external snippet is surrounded by an environment $\langle env \rangle$. All further parameters of $\langle newenv \rangle$ are given to $\langle env \rangle$ as parameters. The included image is prepended by $\langle begin \rangle$ and appended by $\langle end \rangle$.

`extikzpicture` $\rightarrow P. 423$ is an example application for $\text{\\newtcbexternalizeenvironment}^{\rightarrow P. 427}$.

```
\newtcbexternalizeenvironment{extabular}{tabular}{}{\par\centering}{\par}
\begin{extabular}{example_tabular}{|l|p{6cm}|r|}\hline
A & B & C\\\hline
a & This table is externalized as snippet. Obviously,
    this only makes sense for highly complex tables.
& b\\\hline
\end{extabular}
```

A	B	C
a	This table is externalized as snippet. Obviously, this only makes sense for highly complex tables.	b

N 2015-03-11

\renewtcbexternalizeenvironment{<newenv>}{<env>}{<options>}{<begin>}{<end>}

Identical to $\text{\\newtcbexternalizeenvironment}^{\rightarrow P. 427}$, but the environment $\langle newenv \rangle$ is created by $\text{\\renewenvironment}$ instead of \\newenvironment .

N 2015-03-11

\newtcbexternalizetcolorbox{<newenv>}{<env>}{<options>}{<begin>}{<end>}{<options>}

Creates a new environment $\langle newenv \rangle$ which is based on $\text{tcbexternal}^{\rightarrow P. 420}$. This environment takes *at least* one optional parameter and one mandatory parameter. These two parameters are passed to $\text{tcbexternal}^{\rightarrow P. 420}$. Further, the given $\langle options \rangle$ are always added to the option list of $\text{tcbexternal}^{\rightarrow P. 420}$.

The environment content is externalized and the external snippet is surrounded by an environment $\langle env \rangle$. All further parameters of $\langle newenv \rangle$ are given to $\langle env \rangle$ as parameters.

In contrast to $\text{\\newtcbexternalizeenvironment}^{\rightarrow P. 427}$, the environment $\langle env \rangle$ is intended to be based on $\text{tcolorbox}^{\rightarrow P. 12}$ or $\text{tcblisting}^{\rightarrow P. 288}$.

The $\langle begin end options \rangle$ are options for settings the space before and after the included image using $/tcb/before^{\rightarrow P. 76}$, $/tcb/before skip^{\rightarrow P. 78}$, $/tcb/after^{\rightarrow P. 76}$, or $/tcb/after skip^{\rightarrow P. 78}$.

!

Use the exact identical values for $/tcb/before^{\rightarrow P. 76}$ and $/tcb/after^{\rightarrow P. 76}$ inside $\langle begin end options \rangle$ as they where used for definition of $\langle env \rangle$! Otherwise, externalized and non-externalized version will have different spacings.

`extcolorbox` $\rightarrow P. 422$ is an example application for $\text{\\newtcbexternalizetcolorbox}^{\rightarrow P. 427}$.

Definition in the preamble:

```
\newtcblisting{myownlisting}[2][]{%
    enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    colbacktitle=red!50!yellow,before skip=6pt,after skip=6pt,
    title={#2},#1}

\newtcbexternalizetcolorbox{exmyownlisting}{myownlisting}{minipage}%
{before skip=6pt,after skip=6pt}% same values as for mylisting
```

```
\begin{exmyownlisting}[example_mylisting] % <- name for the external file
  {My externalized example box}
  This is my \LaTeX\ box.
\end{exmyownlisting}
```

My externalized example box

This is my \LaTeX\ box.

This is my L^AT_EX box.

N 2015-03-11

\renewtcbexternalizetcolorbox{⟨newenv⟩}{⟨env⟩}{⟨options⟩}{⟨begin end options⟩}

Identical to **\newtcbexternalizetcolorbox**, but the environment ⟨newenv⟩ is created by **\renewenvironment** instead of **\newenvironment**.

N 2016-07-14

\tcbiffleprocess{⟨condition⟩}{⟨source⟩}{⟨md5-file⟩}{⟨target⟩}{⟨true⟩}{⟨false⟩}

This is a low-level macro which is internally used. The MD5 digest of a ⟨source⟩ file is compared with a stored MD5 digest from an auxiliary ⟨md5-file⟩. If they are not equal, the auxiliary ⟨md5-file⟩ is updated to store the current MD5 digest. Further,

- if ⟨condition⟩ equals 0, ⟨true⟩ is executed.
- if ⟨condition⟩ equals 1:
 - If the current and stored MD5 digests were different, ⟨true⟩ is executed.
 - Otherwise, if the ⟨target⟩ file is not existing, ⟨true⟩ is executed.
 - Otherwise, if the ⟨target⟩ file is older than the ⟨md5-file⟩, ⟨true⟩ is executed.
 - Otherwise, ⟨false⟩ is executed.
- if ⟨condition⟩ equals 2, ⟨false⟩ is executed.

The intended processing purpose of the ⟨true⟩ code is to produce a ⟨target⟩ file from the given ⟨source⟩ file.

22.4 Troubleshooting and FAQ

- I use the default settings, but the `external` subdirectory is not created.

Depending on operating system and compiler, an `external` subdirectory is automatically created or not. If not, create such a directory manually or add the following to your document⁵:

```
\ShellEscape{mkdir external}
```

or

```
\ShellEscape{mkdir -p external}
```

If the combination of `/tcb/external/prefix`^{→ P. 419} and chosen snippet name points to another subdirectory than `external`, this has to be adapted.

- I use the `minted` package and I get a cache directory for every externalized snippet.

To avoid this problem, there are several ways.

- If you do not need `minted` inside the snippet code, you may use `\usepackage{minted}` after `\tcbEXTERNALIZE`^{→ P. 419} or use `\tcbifexternal`^{→ P. 426} to switch `minted` off for the external code. If `minted` is already included by another package, add the following to your preamble:

```
\tcbset{external/PassOptionsToPackage={draft}{minted}}
```

- If `minted` is needed for the snippet code, caching can be switched off by adding the following to your preamble:

```
\tcbset{external/PassOptionsToPackage={cache=false}{minted}}
```

Alternatively, the `cachedir` option of `minted` may be used to redirect the cache.

⁵The `shellesc` package is loaded automatically by the library.

23 Library LIB documentation

This library has the single purpose to support LATEX package documentations like this one. Actually, the visual nature follows the approach from Till Tantau's pgf [20] documentation. Typically, this library is assumed to be used in conjunction with the class `ltxdoc` or alike.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{documentation}
```

This also loads the library LIB `listings`, see Section 15 on page 287, the library LIB `skins`, see Section 10 on page 140, the libraN 2014-09-19;e, see Section 21 on page 405, and a bunch of packages, namely `pifont`, `marvosym`, `makeidx`, `marginnote`, `refcount`, and `hyperref`.

! The package `makeidx` is loaded only, if `\printindex` is *not* already defined. Therefore, one can include an alternative to `makeidx` like `imakeidx` *before* the library `documentation` is used.

! The package `marginnote` is loaded only, if `\marginnote` is *not* already defined.

For UTF-8 support, load:

```
\tcbuselibrary{listingsutf8,documentation}
```

For `minted` [11] support, load:

```
\tcbuselibrary{documentation,minted}
\tcbset{listing engine=minted}
```

23.1 Macros of the Library

```
\begin{docCommand}[(options)]{<name>}{<parameters>}
  <command description>
\end{docCommand}
```

Documents a LATEX macro with given `<name>` where `<name>` is written without backslash. The given `<options>` are set with `\tcbsset`^{P.13}. This macro takes mandatory or optional `<parameters>`. It is automatically indexed and can be referenced with `\refCom`^{P.437}{`<name>`}.

```
\begin{docCommand}{foomakedocSubKey}{\marg[name]\marg[key path]}
  Creates a new environment \meta{name} based on \refEnv{docKey} for the
  documentation of keys with the given \meta{key path}.
\end{docCommand}
```

```
\foomakedocSubKey{<name>}{<key path>}
  Creates a new environment <name> based on docKeyP.432 for the documentation of keys with
  the given <key path>.
```

```
\begin{docCommand}[color definition=blue]{foomakedocSubKey*}%
  {\marg{name}\marg{key path}}
  Creates a new environment \meta{name} based on \refEnv{docKey} for the
  documentation of keys with the given \meta{key path}.
\end{docCommand}
```

```
\foomakedocSubKey*{\langle name\rangle}{\langle key path\rangle}
Creates a new environment \langle name\rangle based on \refEnv{docKey} for the documentation of keys with
the given \langle key path\rangle.
```

```
\begin{docCommand*}[\langle options\rangle]{\langle name\rangle}{\langle parameters\rangle}
  \langle command description\rangle
\end{docCommand*}
```

Identical to `docCommand`, but without index entry.

```
\begin{docEnvironment}[\langle options\rangle]{\langle name\rangle}{\langle parameters\rangle}
  \langle environment description\rangle
\end{docEnvironment}
```

Documents a L^AT_EX environment with given `\langle name\rangle`. The given `\langle options\rangle` are set with `\tcbset`^{P. 13}. This environment takes mandatory or optional `\langle parameters\rangle`. It is automatically indexed and can be referenced with `\refEnv`^{P. 437}{\langle name\rangle}.

```
\begin{docEnvironment}{foocolorbox}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

```
\begin{foocolorbox}[\langle options\rangle]
  \langle environment content\rangle
\end{foocolorbox}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

```
\begin{docEnvironment}%
  [doclang/environment content=My content text]%
  {foocolorbox*}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

```
\begin{foocolorbox*}[\langle options\rangle]
  \langle My content text\rangle
\end{foocolorbox*}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

```
\begin{docEnvironment*}[\langle options\rangle]{\langle name\rangle}{\langle parameters\rangle}
  \langle environment description\rangle
\end{docEnvironment*}
```

Identical to `docEnvironment`^{P. 431}, but without index entry.

U 2014-09-29

```
\begin{docKey}[(key path)][(options)]{<name>}{<parameters>}{<description>}
  <key description>
\end{docKey}
```

Documents a key with given *<name>* and an optional *<key path>*. The given *<options>* are set with $\text{\tcbset}^{\rightarrow \text{P.13}}$. This key takes mandatory or optional *<parameters>* as value with a short *<description>*. It is automatically indexed and can be referenced with $\text{\refKey}^{\rightarrow \text{P.438}}\{<\text{name}>\}$.

<pre>\begin{docKey}[foo]{footitle}{=\text{\meta{text}}}{no default, initially empty} Creates a heading line with \text{\meta{text}} as content. \end{docKey}</pre>
--

<pre>/foo/footitle=<text></pre>	(no default, initially empty)
---------------------------------------	-------------------------------

Creates a heading line with *<text>* as content.

U 2014-09-29

```
\begin{docKey*}[(key path)][(options)]{<name>}{<parameters>}{<description>}
  <key description>
\end{docKey*}
```

Identical to $\text{\docKey}^{\rightarrow \text{P.432}}$, but without index entry.

\docValue{<name>}

Documents a value with given *<name>*. Typically, this is a value for a key. This value is automatically indexed.

<pre>A feasible value for \text{\refKey}{/foo/footitle} is \text{\docValue{foovalue}}.</pre>
--

<pre>A feasible value for /foo/footitle^{\rightarrow \text{P.432}} is \text{\foovalue}.</pre>

\docValue*{<name>}

Identical to $\text{\docValue}^{\rightarrow \text{P.432}}$, but without index entry.

U 2014-10-09

\docAuxCommand{<name>}

Documents an auxiliary or minor L^AT_EX macro with given *<name>* where *<name>* is written without backslash. This macro is automatically indexed.

<pre>The macro \text{\docAuxCommand{fooaux}} holds some interesting data.</pre>

<pre>The macro \text{\fooaux} holds some interesting data.</pre>
--

U 2014-10-09

\docAuxCommand*{<name>}

Identical to $\text{\docAuxCommand}^{\rightarrow \text{P.432}}$, but without index entry.

\docAuxEnvironment{<name>}

Documents an auxiliary or minor L^AT_EX environment with given *<name>*. This macro is automatically indexed.

<pre>The environment \text{\docAuxEnvironment{fooauxenv}} holds some interesting data.</pre>
--

<pre>The environment \text{\fooauxenv} holds some interesting data.</pre>

\docAuxEnvironment*{<name>}

Identical to $\text{\docAuxEnvironment}^{\rightarrow \text{P.432}}$, but without index entry.

\docAuxKey [*key path*] {*name*}

Documents an auxiliary key with given *name* and an optional *key path*. It is automatically indexed.

The key `\docAuxKey[foo]{fooaux}` holds some interesting data.

The key `/foo/fooaux` holds some interesting data.

\docAuxKey* [*key path*] {*name*}

Identical to \docAuxKey^{→ P. 433}, but without index entry.

N 2015-01-08

\docCounter {*name*}

Documents a counter with given *name*. The counter is automatically indexed.

The counter `\docCounter{foocounter}` can be used for computation.

The counter `foocounter` can be used for computation.

N 2015-01-08

\docCounter* {*name*}

Identical to \docCounter^{→ P. 433}, but without index entry.

N 2015-01-08

\docLength {*name*}

Documents a counter with given *name*. The counter is automatically indexed.

The length `\docLength{foolength}` can be used for computation.

The length `foolength` can be used for computation.

N 2015-01-08

\docLength* {*name*}

Identical to \docLength^{→ P. 433}, but without index entry.

\docColor {*name*}

Documents a color with given *name*. The color is automatically indexed.

The color `\docColor{foocolor}` is available.

The color `foocolor` is available.

\docColor* {*name*}

Identical to \docColor^{→ P. 433}, but without index entry.

`\cs{\name}`

Macro from `ltxdoc` [3] to typeset a command word `\name` where the backslash is prefixed. The library overwrites the original macro.

This is a `\cs{foocommand}`.

This is a `\foocommand`.

`\meta{\text}`

Macro from `doc` [8] to typeset a meta `\text`. The library overwrites the original macro.

This is a `\meta{text}`.

This is a `\text`.

`\marg{\text}`

Macro from `ltxdoc` [3] to typeset a `\text` with curly brackets as a mandatory argument. The library overwrites the original macro.

This is a mandatory `\marg{argument}`.

This is a mandatory `\{argument\}`.

`\oarg{\text}`

Macro from `ltxdoc` [3] to typeset a `\text` with square brackets as an optional argument. The library overwrites the original macro.

This is an optional `\oarg{argument}`.

This is an optional `\{argument\}`.

`\brackets{\text}`

Sets the given `\text` with curly brackets.

Here we use `\brackets{some text}`.

Here we use `\{some text\}`.

U 2014-10-10

```
\begin{dispExample}
  <environment content>
\end{dispExample}
```

Creates a colored box based on a `tcolorbox`^{P. 12}. It displays the environment content as source code in the upper part and as compiled text in the lower part of the box. The appearance is controlled by `/tcb/documentation listing style`^{P. 440} and the style `/tcb/docexample`^{P. 440}. It may be changed by redefining this style.

```
\begin{dispExample}
This is a \LaTeX\ example.
\end{dispExample}
```

This is a `\LaTeX` example.

This is a L^AT_EX example.

U 2014-10-10

```
\begin{dispExample*}{<options>}
  <environment content>
\end{dispExample*}
```

The starred version of `dispExample`^{P. 435} takes `tcolorbox`^{P. 12} `<options>` as parameter. These `<options>` are executed after `/tcb/docexample`^{P. 440}.

```
\begin{dispExample*}{sidebyside}
This is a \LaTeX\ example.
\end{dispExample*}
```

This is a `\LaTeX` example.

This is a L^AT_EX example.

```
\begin{dispListing}
  <environment content>
\end{dispListing}
```

Creates a colored box based on a `tcolorbox`^{→ P. 12}. It displays the environment content as source code. The appearance is controlled by `/tcb/documentation listing style`^{→ P. 440} and the style `/tcb/doceexample`^{→ P. 440}. It may be changed by redefining this style.

```
\begin{dispListing}
This is a \LaTeX\ example.
\end{dispListing}
```

This is a `\LaTeX\ example.`

```
\begin{dispListing*}[\langle options \rangle]
  <environment content>
\end{dispListing*}
```

The starred version of `dispListing`^{→ P. 436} takes `tcolorbox`^{→ P. 12} `\langle options \rangle` as parameter. These `\langle options \rangle` are executed after `/tcb/doceexample`^{→ P. 440}.

```
\begin{dispListing*}[title=My listing]
This is a \LaTeX\ example.
\end{dispListing*}
```

My listing

This is a `\LaTeX\ example.`

```
\begin{absquote}
  <environment content>
\end{absquote}
```

Used to typeset an abstract as quoted and small text.

```
\begin{absquote}
|tcolorbox| provides an environment for colored and framed text boxes with a
heading line. Optionally, such a box can be split in an upper and a lower part.
\end{absquote}
```

`tcolorbox` provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part.

\tcbmakedocSubKey{\langle name\rangle}{\langle key path\rangle}

Creates a new environment $\langle name \rangle$ based on $\text{docKey}^{\rightarrow \text{P. 432}}$ for the documentation of keys with the given $\langle key path \rangle$ as default. The new environment $\langle name \rangle$ takes the same parameters as $\text{docKey}^{\rightarrow \text{P. 432}}$ itself. A second starred environment $\langle name \rangle$ is also created, which is identical to $\langle name \rangle$ but without index entry.

```
\tcbmakedocSubKey{docFooKey}{foo}

\begin{docFooKey}{foodummy}{=\meta{nothing}}{no default, initially empty}
Some key.
\end{docFooKey}

\begin{docFooKey*}{foo another dummy}{=\meta{nothing}}{no default, initially empty}
Some key (not indexed).
\end{docFooKey*}

/fooodummy=<nothing>                                (no default, initially empty)
Some key.

/foofoo another dummy=<nothing>                      (no default, initially empty)
Some key (not indexed).
```

\refCom{\langle name\rangle}

References a documented L^AT_EX macro with given $\langle name \rangle$ where $\langle name \rangle$ is written without backslash. The page reference is suppressed if it links to the same page.

We have created \refCom{foomakedocSubKey} as an example.

We have created \foomakedocSubKey^{→ P. 430} as an example.

\refCom*{\langle name\rangle}

References a documented L^AT_EX macro with given $\langle name \rangle$ where $\langle name \rangle$ is written without backslash. There is no page reference.

We have created \refCom*{foomakedocSubKey} as an example.

We have created \foomakedocSubKey as an example.

\refEnv{\langle name\rangle}

References a documented L^AT_EX environment with given $\langle name \rangle$. The page reference is suppressed if it links to the same page.

We have created \refEnv{foocolorbox} as an example.

We have created foocolorbox^{→ P. 431} as an example.

\refEnv*{\langle name\rangle}

References a documented L^AT_EX environment with given $\langle name \rangle$. There is no page reference.

We have created \refEnv*{foocolorbox} as an example.

We have created foocolorbox as an example.

\refKey{<name>}

References a documented key with given *<name>* where *<name>* is the full path name of the key. The page reference is suppressed if it links to the same page.

We have created \refKey{/foo/footitle} as an example.

We have created /foo/footitle^{→ P. 432} as an example.

\refKey*{<name>}

References a documented key with given *<name>* where *<name>* is the full path name of the key. There is no page reference.

We have created \refKey*{/foo/footitle} as an example.

We have created /foo/footitle as an example.

\refAux{<name>}

References some auxiliary environment, key, value, or color. The hyperlink color is used, but there is no real link.

Some pages back, one can see \refAux{/foo/footitle} as an example.

Some pages back, one can see /foo/footitle as an example.

\refAuxcs{<name>}

References some auxiliary macro *<name>* where *<name>* is written without backslash. The hyperlink color is used, but there is no real link.

Some pages back, one can see \refAuxcs{fooaux} as an example.

Some pages back, one can see \fooaux as an example.

\colDef{<text>}

Sets *<text>* with the command color, see /tcb/color command^{→ P. 442}.

This is my \colDef{text}.

This is my text.

\colOpt{<text>}

Sets *<text>* with the option color, see /tcb/color option^{→ P. 442}.

This is my \colOpt{text}.

This is my text.

N 2014-09-19

\tcbdocmarginnote[*options*]{*text*}

Creates a `tcolorbox` note with the given *text* inside the margin using the `marginnote` package. The style of the `tcolorbox` is predefined and can be altered by `/tcb/doc marginnoteP. 447` and the given *options*.

```
Some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
Alternatively to |\tcbdocmarginnote|, you can always use
|\marginnote| with a |tcolorbox| directly.\par
This is further text%
\tcbdocmarginnote[colframe=blue!50!white,colback=blue!5!white]{Note B}
with another note.
```

Note A:t which is commented by a note inside the margin. Alternatively to `\tcbdocmarginnote`, you can always use `\marginnote` with a `tcolorbox` directly.
This Note B:t with another note.

N 2014-09-19

\tcbdocnew{*date*}

Auxiliary macro which typesets the `/tcb/doclang/newP. 443` text with the given *date*. It may be redefined for customization.

```
\tcbdocnew{1981-10-29}.
% Next one is displayed in the margin:
\tcbdocmarginnote{\tcbdocnew{1978-02-09}}
```

New 1981-10-29 New:
1978-02-09

N 2014-09-19

\tcbdocupdated{*date*}

Auxiliary macro which typesets the `/tcb/doclang/updatedP. 443` text with the given *date*. It may be redefined for customization.

```
\tcbdocupdated{2014-09-19}.
```

Updated: 2014-09-19.

23.2 Option Keys of the Library

U 2015-03-16

/tcb/docexample (style, no value)

Sets the style for `dispExample`^{P. 435} and `dispListing`^{P. 436} with the colors `ExampleBack` and `ExampleFrame`. To change the appearance of the examples, this style can be redefined.

```
% Predefined style:  
\tcbset{  
    docexample/.style={colframe=ExampleFrame,colback=ExampleBack,  
        before skip=\medskipamount,after skip=\medskipamount,  
        fontlower=\footnotesize}  
}
```

/tcb/documentation listing options=<key list> (no default, initially `style=tcbdocumentation`)

Sets the options from the package `listings` [6]. They are used inside `dispExample`^{P. 435} and `dispListing`^{P. 436} to typeset the listings. Note that this is not identical to the key `/tcb/listing options`^{P. 294} which is used for 'normal' listings.

Used for `/tcb/listing engine`^{P. 299}=`listings` only.

/tcb/documentation listing style=<listing style> (no default, initially `tcbdocumentation`)

Abbreviation for `documentation listing options={style=...}`. This key sets a `<style>` for the `listings` package, see [6]. Note that this is not identical to the key `/tcb/listing style`^{P. 294} which is used for 'normal' listings.

Used for `/tcb/listing engine`^{P. 299}=`listings` only.

/tcb/documentation minted style=<key list> (no default, initially unset)

Sets a `<style>` known to Pygments [13] for the package `minted` [11], if used. Note that this is not identical to the key `/tcb/minted style`^{P. 298} which is used for 'normal' listings.

Used for `/tcb/listing engine`^{P. 299}=`minted` only.

/tcb/documentation minted options=<minted style> (no default, initially `tabsize=2,fontsize=\small`)

Sets the options from the package `minted` [11] which are used during typesetting of the listing, if used. Note that this is not identical to the key `/tcb/minted options`^{P. 297} which is used for 'normal' listings.

Used for `/tcb/listing engine`^{P. 299}=`minted` only.



The following two keys are deprecated and without function (v3.50 and above). Use `/tcb/before`^{P. 76} and `/tcb/after`^{P. 76} with appropriate values instead. Also see `/tcb/docexample`^{P. 440}.

/tcb/before example=<macros> (no default, initially empty)

Sets the `<macros>` which are executed before `dispExample`^{P. 435} and `dispListing`^{P. 436} additional to `/tcb/before`^{P. 76}.

/tcb/after example=<macros> (no default, initially empty)

Sets the `<macros>` which are executed after `dispExample`^{P. 435} and `dispListing`^{P. 436} additional to `/tcb/after`^{P. 76}.

N 2015-01-09

/tcb/index command=*<macro>* (no default, initially \index)

Replaces the internally used \index macro by the given *<macro>*. The *<macro>* has to take one mandatory argument like \index. This option is mutually exclusive with **/tcb/index command name**^{→ P. 441}.

```
\tcbset{index command=\myindexcommand}
```

N 2015-01-09

/tcb/index command name=*<name>* (no default, initially unset)

Replaces the internally used \index macro by \index[*<name>*], i.e. \index{...} is replaced by \index[*<name>*]{...}. This option is intended to be used with **imakeidx** and is mutually exclusive with **/tcb/index command**^{→ P. 441}.

```
\tcbset{index command name=mydoc}
```

/tcb/index format=*<format>* (no default, initially pgf)

Determines the basic *<format>* of the generated index. Feasible values are:

- **pgfsection**: The index is formatted like in the pgf documentation (as a section).
- **pgfchapter**: The index is formatted like in the pgf documentation (as a chapter).
- **pgf**: Alias for **pgfsection**.
- **doc**: The index is assumed to be formatted by **doc** or **ltxdoc**. The usage of **makeindex** with **-s gind.ist** is assumed. The package **hypdoc** has to be loaded *before* **tcolorbox**.
- **off**: The index is not formatted by **tcolorbox**. Use this, if the index is formatted by other package like **imakeidx**.

/tcb/index actual=*<character>* (no default, initially @)

Sets the character for 'actual' in automatic indexing.

/tcb/index quote=*<character>* (no default, initially ")

Sets the character for 'quote' in automatic indexing.

/tcb/index level=*<character>* (no default, initially !)

Sets the character for 'level' in automatic indexing.

/tcb/index default settings (style, no value)

Sets the **makeindex** default values for **/tcb/index actual**^{→ P. 441}, **/tcb/index quote**^{→ P. 441}, and **/tcb/index level**^{→ P. 441}.

/tcb/index german settings (style, no value)

Sets the **makeindex** values recommended for German language texts. This is identical to setting the following:

```
\tcbset{index actual={=},index quote={!},index level={>}}
```

<code>/tcb/index annotate=true false</code>	(default <code>true</code> , initially <code>true</code>)
If set to <code>true</code> , the index entries are annotated with short descriptions given by <code>/tcb/doclang/environment</code> ^{→ P. 443} , <code>/tcb/doclang/key</code> ^{→ P. 443} , and others.	
<code>/tcb/index colorize=true false</code>	(default <code>true</code> , initially <code>false</code>)
If set to <code>true</code> , the index entries colorized according to the color settings given by <code>/tcb/color environment</code> ^{→ P. 442} , <code>/tcb/color key</code> ^{→ P. 442} , and others.	
<code>/tcb/color command=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by macro definitions.	
<code>/tcb/color environment=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by environment definitions.	
<code>/tcb/color key=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by key definitions.	
<code>/tcb/color value=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by value definitions.	
N 2015-01-08 <code>/tcb/color counter=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by counter definitions.	
N 2015-01-08 <code>/tcb/color length=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by length definitions.	
<code>/tcb/color color=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color used by color definitions.	
<code>/tcb/color definition=<color></code>	(no default, initially <code>Definition</code>)
Sets the highlight color for <code>/tcb/color command</code> ^{→ P. 442} , <code>/tcb/color environment</code> ^{→ P. 442} , <code>/tcb/color key</code> ^{→ P. 442} , <code>/tcb/color value</code> ^{→ P. 442} , <code>/tcb/color counter</code> ^{→ P. 442} , <code>/tcb/color length</code> ^{→ P. 442} , and <code>/tcb/color color</code> ^{→ P. 442} .	
<code>/tcb/color option=<color></code>	(no default, initially <code>Option</code>)
Sets the color used for optional arguments.	
<code>/tcb/color hyperlink=<color></code>	(no default, initially <code>Hyperlink</code>)
Sets the color for all hyper-links, i. e. all internal and external links.	

The following keys are provided for language specific settings. The English language is predefined.

/tcb/english language (style, no value)

Sets all language specific settings to English.

/tcb/doclang/color=⟨text⟩ (no default, initially **color**)

Text used in the index for colors.

/tcb/doclang/colors=⟨text⟩ (no default, initially **Colors**)

Heading text in the index for colors.

N 2015-01-08 /tcb/doclang/counter=⟨text⟩ (no default, initially **counter**)

Text used in the index for counters.

N 2015-01-08 /tcb/doclang/counters=⟨text⟩ (no default, initially **Counters**)

Heading text in the index for counters.

/tcb/doclang/environment=⟨text⟩ (no default, initially **environment**)

Text used in the index for environments.

/tcb/doclang/environments=⟨text⟩ (no default, initially **Environments**)

Heading text in the index for environments.

/tcb/doclang/environment content=⟨text⟩ (no default, initially **environment content**)

Text used in docEnvironment^{→P.431}.

/tcb/doclang/index=⟨text⟩ (no default, initially **Index**)

Heading text for the index.

/tcb/doclang/key=⟨text⟩ (no default, initially **key**)

Text used in the index for keys.

/tcb/doclang/keys=⟨text⟩ (no default, initially **Keys**)

Heading text used in the index for keys.

N 2015-01-08 /tcb/doclang/length=⟨text⟩ (no default, initially **length**)

Text used in the index for lengths.

N 2015-01-08 /tcb/doclang/lengths=⟨text⟩ (no default, initially **Lengths**)

Heading text in the index for lengths.

N 2014-09-19 /tcb/doclang/new=⟨text⟩ (no default, initially **New**)

Announcement text for new content.

/tcb/doclang/pageshort=⟨text⟩ (no default, initially **P.**)

Short text for page references.

N 2014-09-19 /tcb/doclang/updated=⟨text⟩ (no default, initially **Updated**)

Announcement text for updated content.

/tcb/doclang/value=⟨text⟩ (no default, initially **value**)

Text used in the index for values.

/tcb/doclang/values=⟨text⟩ (no default, initially **Values**)

Heading text in the index for values.

/tcb/doc left=<length> (no default, initially 2em)

Sets the left hand offset of the documentation texts from `docCommand`^{P. 430}, `docEnvironment`^{P. 431}, `docKey`^{P. 432}, etc, to `<length>`.

```
\begin{docCommand*}[doc left=2cm,doc left indent=-2cm]{myCommandA}{\marg{argument}}
  This is the documentation of \refCom{myCommandA} which takes one \meta{argument}.
  \refCom{myCommandA} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandA{\argument}
  This is the documentation of \myCommandAP. 444 which takes one \argument.
  \myCommandAP. 444 does some funny things with its \argument.
```

/tcb/doc right=<length> (no default, initially 0em)

Sets the right hand offset of the documentation texts from `docCommand`^{P. 430}, `docEnvironment`^{P. 431}, `docKey`^{P. 432}, etc, to `<length>`.

```
\begin{docCommand*}[doc right=2cm]{myCommandB}{\marg{argument}}
  This is the documentation of \refCom{myCommandB} which takes one \meta{argument}.
  \refCom{myCommandB} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandB{\argument}
  This is the documentation of \myCommandBP. 444 which takes one \argument.
  \myCommandBP. 444 does some funny things with its \argument.
```

/tcb/doc left indent=<length> (no default, initially -2em)

Sets the left hand indent of documentation heads from `docCommand`^{P. 430}, `docEnvironment`^{P. 431}, `docKey`^{P. 432}, etc, to `<length>`.

```
\begin{docCommand*}[doc left indent=2cm]{myCommandC}{\marg{argument}}
  This is the documentation of \refCom{myCommandC} which takes one \meta{argument}.
  \refCom{myCommandC} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandC{\argument}
  This is the documentation of \myCommandCP. 444 which takes one \argument.
  \myCommandCP. 444 does some funny things with its \argument.
```

/tcb/doc right indent=<length> (no default, initially Opt)

Sets the right hand indent of documentation heads from `docCommand`^{P. 430}, `docEnvironment`^{P. 431}, `docKey`^{P. 432}, etc, to `<length>`.

```
\begin{docCommand*}[doc right indent=-10mm,doc right=10mm,
  doc description=test value]{myCommandD}{\marg{argument}}
  This is the documentation of \refCom{myCommandD} which takes one \meta{argument}.
  \refCom{myCommandD} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandD{\argument}
  This is the documentation of \myCommandDP. 444 which takes one \argument.
  \myCommandDP. 444 does some funny things with its \argument.
```

The head lines of the main documentation environments `docCommand`^{→ P. 430}, `docEnvironment`^{→ P. 431}, `docKey`^{→ P. 432}, etc, are set inside `tcolorboxes`. Options to these `tcolorboxes` can be given using the following keys.

/tcb/doc head command=⟨options⟩ (no default, initially empty)

Sets ⟨options⟩ for the head line of `docCommand`^{→ P. 430} and `docCommand*`^{→ P. 431}.

```
\tcbset{doc head command={interior style={fill, left color=red!20!white,
right color=blue!20!white}}}

\begin{docCommand*}{myCommandE}{\marg{argument}}
This is the documentation of \refCom{myCommandE} which takes one \meta{argument}.
\refCom{myCommandE} does some funny things with its \meta{argument}.
\end{docCommand*}
```

`\myCommandE{⟨argument⟩}`

This is the documentation of `\myCommandE`^{→ P. 445} which takes one ⟨argument⟩.
`\myCommandE`^{→ P. 445} does some funny things with its ⟨argument⟩.

/tcb/doc head environment=⟨options⟩ (no default, initially empty)

Sets ⟨options⟩ for the head line of `docEnvironment`^{→ P. 431} and `docEnvironment*`^{→ P. 431}.

```
\tcbset{doc head environment={beamer, boxsep=2pt, arc=2pt, colback=green!20!white,
after=\par\smallskip}>

\begin{docEnvironment*}{myEnvironment}{\marg{argument}}
This is the documentation of \refEnv{myEnvironment} which
takes one \meta{argument}.
\end{docEnvironment*}
```

```
\begin{myEnvironment}{⟨argument⟩}
⟨environment content⟩
\end{myEnvironment}
```

This is the documentation of `myEnvironment`^{→ P. 445} which takes one ⟨argument⟩.

/tcb/doc head key=⟨options⟩ (no default, initially empty)

Sets ⟨options⟩ for the head line of `docKey`^{→ P. 432} and `docKey*`^{→ P. 432}.

```
\tcbset{doc head key={boxsep=4pt, arc=4pt, boxrule=0.6pt,
frame style=fill, interior style=fill, colframe=green!50!black}>

\begin{docKey*}{/foo/myKey}{}{no value}
This is the documentation of \refKey{/foo/myKey}.
\end{docKey*}
```

`/foo/myKey`

(no value)

This is the documentation of `/foo/myKey`^{→ P. 445}.

/tcb/doc head=⟨options⟩ (no default, initially empty)

Shortcut for setting the same ⟨options⟩ for `/tcb/doc head command`^{→ P. 445}, `/tcb/doc head environment`^{→ P. 445}, and `/tcb/doc head key`^{→ P. 445}.

The description texts of the main documentation environments `docCommand`^{→ P. 430}, `docEnvironment`^{→ P. 431}, `docKey`^{→ P. 432}, etc, are set in a compact form without indentation and `parskip=0pt`. This settings can overruled by using the following keys to insert code before (or after) the description texts.

N 2015-10-09

/tcb/before doc body command=⟨code⟩ (no default, initially empty)

Executes ⟨code⟩ before the description texts of `docCommand`^{→ P. 430} and `docCommand*`^{→ P. 431}.

```
\tcbset{before doc body command={%
  \setlength{\parindent}{2.5em}%
  \setlength{\parskip}{1ex plus 0.75ex minus 0.25ex}%
}%

\begin{docCommand*}{myCommandG}{\marg{argument}}
  This is the documentation of \refCom{myCommandG} which takes one \meta{argument}.
  \refCom{myCommandG} does some funny things with its \meta{argument}.
\end{docCommand*}

\myCommandG{⟨argument⟩}
  This is the documentation of \myCommandG→ P. 446 which takes one ⟨argument⟩.
\myCommandG→ P. 446 does some funny things with its ⟨argument⟩.
```

N 2015-10-09

/tcb/after doc body command=⟨code⟩ (no default, initially empty)

Executes ⟨code⟩ after the description texts of `docCommand`^{→ P. 430} and `docCommand*`^{→ P. 431}.

```
\tcbset{after doc body command={%
  \hfill\nolinebreak[1]\hspace*{⟨fill⟩}\textcolor{red}{\$diamondsuit\$}%
}%

\begin{docCommand*}{myCommandH}{\marg{argument}}
  This is the documentation of \refCom{myCommandH} which takes one \meta{argument}.
  \refCom{myCommandH} does some funny things with its \meta{argument}.
\end{docCommand*}

\myCommandH{⟨argument⟩}
  This is the documentation of \myCommandH→ P. 446 which takes one ⟨argument⟩.
\myCommandH→ P. 446 does some funny things with its ⟨argument⟩. ◇
```

N 2015-10-09

/tcb/before doc body environment=⟨code⟩ (no default, initially empty)

Executes ⟨code⟩ before the description texts of `docEnvironment`^{→ P. 431} and `docEnvironment*`^{→ P. 431}.

N 2015-10-09

/tcb/after doc body environment=⟨code⟩ (no default, initially empty)

Executes ⟨code⟩ after the description texts of `docEnvironment`^{→ P. 431} and `docEnvironment*`^{→ P. 431}.

N 2015-10-09

/tcb/before doc body key=⟨code⟩ (no default, initially empty)

Executes ⟨code⟩ before the description texts of `docKey`^{→ P. 432} and `docKey*`^{→ P. 432}.

N 2015-10-09

/tcb/after doc body key=⟨code⟩ (no default, initially empty)

Executes ⟨code⟩ after the description texts of `docKey`^{→ P. 432} and `docKey*`^{→ P. 432}.

N 2015-10-09

/tcb/before doc body=⟨options⟩ (no default, initially empty)

Shortcut for setting the same ⟨options⟩ for `/tcb/before doc body command`^{→ P. 446}, `/tcb/before doc body environment`^{→ P. 446}, and `/tcb/before doc body key`^{→ P. 446}.

N 2015-10-09

/tcb/after doc body=⟨options⟩ (no default, initially empty)

Shortcut for setting the same ⟨options⟩ for `/tcb/after doc body command`^{→ P. 446}, `/tcb/after doc body environment`^{→ P. 446}, and `/tcb/after doc body key`^{→ P. 446}.

/tcb/doc description=*<text>* (no default, initially empty)

Sets a (short!) additional description *<text>* for **docCommand**^{→ P. 430} or **docEnvironment**^{→ P. 431}. Such a description is mandatory for **docKey**^{→ P. 432}.

```
\begin{docCommand*}[doc description=my description]{myCommandF}{\marg{argument}}
  This is the documentation of \refCom{myCommandF} which takes one \meta{argument}.
  \refCom{myCommandF} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandF{<argument>}
  This is the documentation of \myCommandF→ P. 447 which takes one <argument>.
  \myCommandF→ P. 447 does some funny things with its <argument>.
```

! Note that the description *<text>* may overlap with the text on the left hand side if too long. Linebreaks can be used inside the *<text>*.

/tcb/doc into index=*true|false* (default **true**, initially **true**)

If set to **false**, no index entries are written for the main documentation environments. The same effect is achieved by using e. g. **docCommand***^{→ P. 431} instead of **docCommand**^{→ P. 430}.

N 2014-09-19 **/tcb/doc marginnote**=*<options>* (no default, initially empty)

Sets style *<options>* for the displayed box of the **\tcbdocmarginnote**^{→ P. 439} command.

```
\tcbsset{doc marginnote={colframe=blue!50!white,colback=blue!5!white}}%
This is some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
```

This Note A is commented by a note inside the margin.

N 2014-09-19 **/tcb/doc new**=*<date>* (style, no default)

Adds a marginnote with a 'New: *<date>*' message at the beginning of the upper box part. The intended use is inside the option list of **docCommand**^{→ P. 430}, **docEnvironment**^{→ P. 431}, etc.

```
\begin{docCommand}[doc new=2000-01-01]{foosomething}{\marg{text}}
  Some command for something.
\end{docCommand}
```

New: **\foosomething**{<text>}
2000-01-01 Some command for something.

N 2014-09-19 **/tcb/doc updated**=*<date>* (style, no default)

Adds a marginnote with a 'Updated: *<date>*' message at the beginning of the upper box part. See **/tcb/doc new**^{→ P. 447}.

N 2014-09-19 **/tcb/doc new and updated**=*{<new date>}{<update date>}* (style, no default)

Adds a marginnote with 'New: *<new date>*' and 'Updated: *<update date>*' messages at the beginning of the upper box part. See **/tcb/doc new**^{→ P. 447}.



23.3 Predefined Colors of the Library

The following colors are predefined. They are used as default colors in some library commands.

Option **Option**  , **Definition**  , **ExampleFrame**  , **ExampleBack**  , **Hyperlink**  .

A Picture Credits

The following pictures were used inside this documentation.



References

- [1] Donald Arseneau. *The varwidth package*. Sept. 26, 2011.
<http://mirrors.ctan.org/macros/latex/contrib/varwidth/varwidth-doc.pdf>.
- [2] Peter Breitenlohner. *The ε -TEX manual*. Version 2. Feb. 1998.
http://mirrors.ctan.org/systems/doc/etex/etex_man.pdf.
- [3] David Carlisle. *The file ltxdoc.dtx for use with LATEX 2 ε* . Nov. 11, 2007.
<http://mirror.ctan.org/macros/latex/base/ltxdoc.dtx>.
- [4] David Carlisle. *The tabularx package*. Oct. 28, 2014.
<http://mirror.ctan.org/macros/latex/required/tools/tabularx.pdf>.
- [5] Toby Cubitt. *The cleveref Package*. Dec. 28, 2013.
<http://mirror.ctan.org/macros/latex/contrib/cleveref/cleveref.pdf>.
- [6] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*. Version 1.6. June 4, 2015.
<http://mirror.ctan.org/macros/latex/contrib/listings/listings.pdf>.
- [7] Philipp Lehman and Joseph Wright. *The etoolbox Package*. Aug. 2, 2015.
<http://mirror.ctan.org/macros/latex/contrib/etoolbox/etoolbox.pdf>.
- [8] Frank Mittelbach. *The doc and shortverb Packages*. June 30, 2011.
<http://mirror.ctan.org/macros/latex/base/doc.dtx>.
- [9] Frank Mittelbach. *An environment for multicolumn output*. Sept. 30, 2015.
<http://mirror.ctan.org/macros/latex/required/tools/multicol.pdf>.
- [10] Heiko Oberdiek. *The listingsutf8 package*. Nov. 10, 2011.
<http://mirror.ctan.org/macros/latex/contrib/oberdiek/listingsutf8.pdf>.
- [11] Geoffrey M. Poore and Konrad Rudolph. *The minted package. Highlighted source code in LATEX*. Sept. 9, 2015.
<http://mirror.ctan.org/macros/latex/contrib/minted/minted.pdf>.
- [12] The LATEX3 Project. *The xparse Package*. Oct. 14, 2015.
<http://mirror.ctan.org/macros/latex/contrib/l3packages/xparse.pdf>.
- [13] Pygments. *Python syntax highlighter*. 2013.
<http://pygments.org/>.
- [14] Will Robertson. *A couple of things involving environments*. May 4, 2014.
<http://mirror.ctan.org/macros/latex/contrib/environ/environ.pdf>.
- [15] Rainer Schöpf, Bernd Raichle, and Chris Rowley. *A New Implementation of LATEX's verbatim and verbatim* Environments*. Mar. 12, 2001.
<http://mirror.ctan.org/macros/latex/required/tools/verbatim.pdf>.
- [16] Thomas F. Sturm. *Mathematik 1 (B.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2007.
<http://www.unibw.de/bw/sturm>.
- [17] Thomas F. Sturm. *Mathematik 2 (B.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2008.
<http://www.unibw.de/bw/sturm>.
- [18] Thomas F. Sturm. *Höhere Mathematik: Fortgeschrittene mathematische Methoden (M.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2010.
<http://www.unibw.de/bw/sturm>.
- [19] Thomas F. Sturm. *LATEX – Einführung in das Textsatzsystem*. 10th edition. RRZN-Handbücher. Hannover: Regionales Rechenzentrum für Niedersachsen (RRZN), Mar. 2014.
<http://www.rrzn.uni-hannover.de/buch.html?&titel=latex>.
- [20] Till Tantau. *The TikZ and PGF Packages. Manual for version 3.0.1a*. Aug. 29, 2015.
<http://mirrors.ctan.org/graphics/pgf/base/doc/pgfmanual.pdf>.

Index

- key, 418
! key, 418

absquote environment, 435
add to height key, 54
add to list key, 95
add to natural height key, 54
add to width key, 34
adjust text key, 18
adjusted title key, 18
adjusted title after break key, 354
after key, 76
after app key, 395
after doc body key, 445
after doc body command key, 445
after doc body environment key, 445
after doc body key key, 445
after example key, 439
after lower key, 64
after lower app key, 395
after lower pre key, 395
after lower* key, 64
after pre key, 395
after skip key, 78
after title key, 62
after title app key, 394
after title pre key, 394
after upper key, 63
after upper app key, 394
after upper pre key, 394
after upper* key, 63
all key, 10
all value, 47, 48, 276, 356, 358
ams align key, 339
ams align lower key, 339
ams align upper key, 339
ams align* key, 339
ams align* lower key, 339
ams align* upper key, 339
ams equation key, 338
ams equation lower key, 338
ams equation upper key, 338
ams equation* key, 338
ams equation* lower key, 338
ams equation* upper key, 338
ams gather key, 340
ams gather lower key, 340
ams gather upper key, 340
ams gather* key, 340
ams gather* lower key, 340
ams gather* upper key, 340
ams nodisplayskip key, 341
ams nodisplayskip lower key, 341
ams nodisplayskip upper key, 341
arc key, 36
arc is angular key, 38
arc is curved key, 38
areasize value, 390
areasize* value, 390
at begin tikz key, 184
at begin tikz reset key, 184
at end tikz key, 184
at end tikz reset key, 184
attach boxed title to bottom key, 148
attach boxed title to bottom center key, 147
attach boxed title to bottom left key, 147
attach boxed title to bottom right key, 147
attach boxed title to bottom* key, 148
attach boxed title to top key, 148
attach boxed title to top center key, 147
attach boxed title to top left key, 147
attach boxed title to top right key, 147
attach boxed title to top* key, 148
attach title key, 20
attach title to upper key, 20
auto value, 93
auto counter key, 101
auto limited value, 93
auto outer arc key, 38
autoparskip key, 76
base value, 77
base color key, 258
baseline key, 77
baselineskip value, 356
beamer key, 218
beamer Skin, 218
beamerfirst Skin, 220
beameralast Skin, 222
beamermiddle Skin, 221
bean arc key, 37
before key, 76
before app key, 395
before doc body key, 445
before doc body command key, 445
before doc body environment key, 445
before doc body key key, 445
before example key, 439
before lower key, 64
before lower app key, 395
before lower pre key, 395
before nobreak key, 79
before pre key, 395
before skip key, 78
before title key, 62
before title app key, 394
before title pre key, 394
before upper key, 63
before upper app key, 394
before upper pre key, 394

beforeafter skip key, 78
bicolor key, 209
bicolor Skin, 209
bicolorfirst Skin, 211
bicolorlast Skin, 213
bicolormiddle Skin, 212
blank key, 198
blanker key, 228
blankest key, 229
blend before title key, 106
blend before title code key, 107
blend into key, 105
borderline key, 169
borderline east key, 172
borderline horizontal key, 173
borderline north key, 172
borderline south key, 172
borderline vertical key, 173
borderline west key, 172
both value, 116
bottom key, 42
bottom value, 33, 77, 110, 275
bottom seam value, 110
bottomrule key, 35
bottomrule at break key, 357
bottomsep at break key, 357
bottomtitle key, 42
box align key, 77
`\boxarrayclear`, 375
`\boxarraygetbox`, 379
`\boxarraygetdepth`, 380
`\boxarraygetheight`, 380
`\boxarraygetsize`, 377
`\boxarraygettatalheight`, 381
`\boxarraygetwidth`, 380
`\boxarrayreset`, 374
boxarraystore environment, 377
boxed title size key, 150
boxed title style key, 151
boxrule key, 36
boxsep key, 38
`\brackets`, 433
break value, 343
break at key, 355
breakable key, 9, 353
broken value, 157–159

capture key, 90
center key, 82
center value, 30, 33, 77, 110, 275
center lower key, 32
center seam value, 110
center title key, 32
center upper key, 32
change value, 343
change apart value, 343
change break value, 343
change standard value, 342
check odd page key, 96
circular arc key, 37

clear preamble key, 425
clear preclass key, 425
clip lower key, 168
clip title key, 167
clip upper key, 167
clip watermark key, 163
clipped value, 259
code key, 100
colback key, 27
colbacklower key, 210
colbacktitle key, 27
`\colDef`, 437
colframe key, 27
collower key, 28
colon value, 106
colon hang value, 106
`\colOpt`, 437
color key, 442
color color key, 441
color command key, 441
color counter key, 441
color definition key, 441
color environment key, 441
color from key, 258
color hyperlink key, 441
color key key, 441
color length key, 441
color option key, 441
color value key, 441
Colors
 Definition, 446
 ExampleBack, 446
 ExampleFrame, 446
 foocolor, 432
 Hyperlink, 446
 Option, 446
colors key, 442
coltext key, 28
coltitle key, 28
colupper key, 28
comment key, 300
 comment above listing key, 307
 comment above* listing key, 307
 comment and listing key, 303
 comment only key, 300
 comment outside listing key, 305
 comment side listing key, 305
 comment style key, 303
 compilable listing key, 311
 compiler key, 424
 compress page key, 356
`\consumeboxarray`, 378
`\consumetcboxarray`, 378
copy value, 150
counter key, 442
Counters
 foocounter, 432
counters key, 442
Crefname key, 104

crefname key, 104
\cs, 433
dash value, 106
dash hang value, 106
\DeclareTCBInputListing, 414
\DeclareTCBListing, 412
\DeclareTCBox, 409
\DeclareTCBoxFit, 415
\DeclareTColorBox, 406
\DeclareTotalTCBox, 410
\DeclareTotalTCBoxFit, 416
\DeclareTotalTColorBox, 408
Definition color, 446
description color key, 333
description delimiters key, 333
description delimiters none key, 333
description delimiters parenthesis key, 333
description font key, 334
description formatter key, 334
detach title key, 20
direct value, 259
dispExample environment, 434
dispExample* environment, 434
dispListing environment, 435
dispListing* environment, 435
do not store to box array key, 377
doc value, 440
doc description key, 446
doc head key, 444
doc head command key, 444
doc head environment key, 444
doc head key key, 444
doc into index key, 446
doc left key, 443
doc left indent key, 443
doc marginnote key, 446
doc new key, 446
doc new and updated key, 446
doc right key, 443
doc right indent key, 443
doc updated key, 446
\docAuxCommand, 431
\docAuxCommand*, 431
\docAuxEnvironment, 431
\docAuxEnvironment*, 431
\docAuxKey, 432
\docAuxKey*, 432
\docColor, 432
\docColor*, 432
docCommand environment, 429
docCommand* environment, 430
\docCounter, 432
\docCounter*, 432
docEnvironment environment, 430
docEnvironment* environment, 430
docexample key, 439
docKey environment, 431
docKey* environment, 431
\docLength, 432
\docLength*, 432
documentation key, 10
documentation listing options key, 439
documentation listing style key, 439
documentation minted options key, 439
documentation minted style key, 439
\docValue, 431
\docValue*, 431
downhill value, 47, 48
draft key, 238
draft Skin, 238
draftmode key, 193
draw method key, 259
drop fuzzy midday shadow key, 175
drop fuzzy shadow key, 174
drop fuzzy shadow east key, 178
drop fuzzy shadow north key, 178
drop fuzzy shadow northeast key, 178
drop fuzzy shadow northwest key, 178
drop fuzzy shadow south key, 177
drop fuzzy shadow southeast key, 177
drop fuzzy shadow southwest key, 177
drop fuzzy shadow west key, 177
drop large lifted shadow key, 179
drop lifted shadow key, 179
drop midday shadow key, 174
drop shadow key, 174
drop shadow east key, 177
drop shadow north key, 176
drop shadow northeast key, 177
drop shadow northwest key, 176
drop shadow south key, 176
drop shadow southeast key, 176
drop shadow southwest key, 176
drop shadow west key, 176
drop small lifted shadow key, 179
east fading, 259
east value, 47, 48
east size key, 256
east style key, 257
empty key, 227
empty Skin, 227
empty value, 127, 128
emptyfirst Skin, 230
emptylast Skin, 232
emptymiddle Skin, 231
enforce breakable key, 354
english language key, 442
enhanced key, 196
enhanced Skin, 196
enhanced jigsaw key, 203
enhanced jigsaw Skin, 203
enhanced standard key, 198
enhancedfirst Skin, 200
enhancedfirst jigsaw Skin, 204
enhancedlast Skin, 202
enhancedlast jigsaw Skin, 208
enhancedmiddle Skin, 201

enhancedmiddle jigsaw Skin, 205
enlarge bottom at break by key, 81
enlarge bottom by key, 81
enlarge bottom finally by key, 80
enlarge by key, 82
enlarge left by key, 81
enlarge right by key, 81
enlarge top at break by key, 81
enlarge top by key, 81
enlarge top initially by key, 80
enlargepage key, 355
enlargepage flexible key, 356
environment key, 424, 442
environment content key, 442
environment with percent key, 424
Environments
 absquote, 435
 boxarraystore, 377
 dispExample, 434
 dispExample*, 434
 dispListing, 435
 dispListing*, 435
 docCommand, 429
 docCommand*, 430
 docEnvironment, 430
 docEnvironment*, 430
 docKey, 431
 docKey*, 431
 extcolorbox, 421
 extikzpicture, 422
 fooauxenv, 431
 foocolorbox, 430
 foocolorbox*, 430
 tcbclipframe, 164
 tcbclipinterior, 166
 tcbcliptitle, 166
 tcbexternal, 419
 tcbinvclipframe, 165
 tcbitemize, 269
 tcblisting, 288
 tcboutputlisting, 290
 tcboxeditemize, 271
 tcboxedraster, 270
 tcraster, 268
 tcbverbatimwrite, 119
 tcbwritetemp, 119
 tcolorbox, 12
environments key, 442
equal height group key, 59
evenpage value, 45, 84
every box key, 87
every box on higher layers key, 88
every box on layer n key, 88
every float key, 75
every listing line key, 295
every listing line* key, 295
ExampleBack color, 446
ExampleFrame color, 446
extcolorbox environment, 421
extend freelance key, 240
extend freelancefirst key, 240
extend freelancelast key, 240
extend freelancemiddle key, 240
external key, 10, 99
externalize key, 418
externalize example key, 423
externalize example! key, 423
externalize listing key, 423
externalize listing! key, 423
extikzpicture environment, 422
extras key, 359
extras broken key, 359
extras broken pre key, 403
extras first key, 359
extras first and middle key, 359
extras first and middle pre key, 403
extras first pre key, 403
extras last key, 359
extras last pre key, 403
extras middle key, 359
extras middle and last key, 359
extras middle and last pre key, 403
extras middle pre key, 403
extras pre key, 403
extras unbroken key, 359
extras unbroken and first key, 359
extras unbroken and first pre key, 403
extras unbroken and last key, 359
extras unbroken and last pre key, 403
extras unbroken pre key, 403
extrude bottom by key, 86
extrude by key, 86
extrude left by key, 85
extrude right by key, 85
extrude top by key, 86

fade in key, 260
fade out key, 260
Fadings
 east, 259
 north, 259
 semi east, 259
 semi north, 259
 semi south, 259
 semi west, 259
 south, 259
 west, 259
false value, 76, 79, 277, 353
fbox value, 43
figures value, 105
fill image opacity key, 251
fill image options key, 251
fill image scale key, 251
fill overzoom image key, 247
fill overzoom image* key, 247
fill overzoom picture key, 247
fill plain image key, 245
fill plain image* key, 245
fill plain picture key, 245

fill shrink image key, 249
fill shrink image* key, 249
fill shrink picture key, 249
fill stretch image key, 246
fill stretch image* key, 246
fill stretch picture key, 246
fill tile image key, 250
fill tile image* key, 250
fill tile picture key, 250
fill tile picture* key, 250
fill zoom image key, 248
fill zoom image* key, 248
fill zoom picture key, 248
final value, 392
finish key, 189
finish broken key, 190
finish broken pre key, 401
finish fading vignette key, 264
finish first key, 190
finish first and middle key, 190
finish first and middle pre key, 401
finish first pre key, 401
finish last key, 190
finish last pre key, 401
finish middle key, 190
finish middle and last key, 190
finish middle and last pre key, 401
finish middle pre key, 401
finish pre key, 401
finish raised fading vignette key, 263
finish unbroken key, 190
finish unbroken and first key, 190
finish unbroken and first pre key, 401
finish unbroken and last key, 190
finish unbroken and last pre key, 401
finish unbroken pre key, 401
finish vignette key, 263
first value, 157–159, 358
first and middle value, 157, 358
fit key, 384
fit algorithm key, 390
fit basedim key, 385
fit fontsize macros key, 386
fit height from key, 389
fit height plus key, 387
fit maxfontdiff key, 392
fit maxfontdiffgap key, 392
fit maxstep key, 392
fit maxwidthdiff key, 392
fit maxwidthdiffgap key, 392
fit skip key, 385
fit to key, 385
fit to height key, 385
fit warning key, 392
fit width from key, 388
fit width plus key, 387
fitbox value, 90
fitting key, 9
flip title key, 148
float key, 74
float* key, 74
floatplacement key, 74
flush center value, 30, 32
flush left key, 82
flush left value, 30, 32
flush right key, 82
flush right value, 30, 32
flushleft lower key, 32
flushleft title key, 32
flushleft upper key, 32
flushright lower key, 32
flushright title key, 32
flushright upper key, 32
fontlower key, 29
fontsize value, 390
fontsize* value, 390
fonttitle key, 29
fontupper key, 29
`\fooaux`, 431
fooaux key, 432
fooauxenv environment, 431
foocolor color, 432
foocolorbox environment, 430
foocolorbox* environment, 430
foocounter counter, 432
foodummy key, 436
`\foolength` length, 432
`\foomakedocSubKey`, 429
`\foomakedocSubKey*`, 430
`\foosomething`, 446
footitle key, 431
foovalue value, 431
force remake key, 418
forced value, 45, 84
forced center value, 93
forced left value, 93
forced right value, 93
forces nobeforeafter key, 76
frame code key, 130
frame code app key, 401
frame code pre key, 401
frame empty key, 130
frame engine key, 127
frame hidden key, 141
frame style key, 140
frame style image key, 140
frame style tile key, 141
freelance key, 240
freelance Skin, 240
freelance value, 127, 128
freelancefirst Skin, 240
freelancelast Skin, 240
freelancemiddle Skin, 240
freeze extension key, 314
freeze file key, 314
freeze jpg key, 314
freeze none key, 314
freeze pdf key, 314

freeze png key, 314
fuzzy halo key, 175
fuzzy shadow key, 181

geometry nodes key, 129
graphical environment key, 126
graphics directory key, 244
graphics options key, 244
graphics pages key, 244
grow to left by key, 83
grow to right by key, 83

halign key, 30
halign lower key, 31
halign title key, 32
halign upper key, 30
halo key, 175
hbox key, 90
hbox value, 90
hbox boxed title key, 155
height key, 52
height fill key, 55
height fixed for key, 358
height from key, 53
height plus key, 52
highlight math key, 337
highlight math style key, 337
hooks key, 9
horizontal size key, 257
hybrid value, 390
hybrid* value, 390
Hyperlink color, 446
hyphenationfix key, 92

if odd page key, 96
if odd page* key, 97
IfBooleanTF key, 405
IfNoValueTF key, 404
IfValueTF key, 405
ignore nobreak key, 79
ignored value, 24
image comment key, 300
\imagename, 242
\imagepage, 243
index key, 442
index actual key, 440
index annotate key, 441
index colorize key, 441
index command key, 440
index command name key, 440
index default settings key, 440
index format key, 440
index german settings key, 440
index level key, 440
index quote key, 440
input source on error key, 424
inside node key, 255
interior code key, 131
interior code app key, 402
interior code pre key, 402

interior empty key, 131
interior engine key, 128
interior hidden key, 142
interior style key, 141
interior style image key, 142
interior style tile key, 142
interior titled code key, 130
interior titled code app key, 401
interior titled code pre key, 402
interior titled empty key, 130
interior titled engine key, 127
invisible key, 22
invisible value, 22, 24

justify value, 30

key key, 442
Keys
/foo/
 fooaux, 432
 foodummy, 436
 footitle, 431
/tcb/
 add to height, 54
 add to list, 95
 add to natural height, 54
 add to width, 34
 adjust text, 18
 adjusted title, 18
 adjusted title after break, 354
 after, 76
 after app, 395
 after doc body, 445
 after doc body command, 445
 after doc body environment, 445
 after doc body key, 445
 after example, 439
 after lower, 64
 after lower app, 395
 after lower pre, 395
 after lower*, 64
 after pre, 395
 after skip, 78
 after title, 62
 after title app, 394
 after title pre, 394
 after upper, 63
 after upper app, 394
 after upper pre, 394
 after upper*, 63
 ams align, 339
 ams align lower, 339
 ams align upper, 339
 ams align*, 339
 ams align* lower, 339
 ams align* upper, 339
 ams equation, 338
 ams equation lower, 338
 ams equation upper, 338
 ams equation*, 338

ams equation* lower, 338
 ams equation* upper, 338
 ams gather, 340
 ams gather lower, 340
 ams gather upper, 340
 ams gather*, 340
 ams gather* lower, 340
 ams gather* upper, 340
 ams nodisplayskip, 341
 ams nodisplayskip lower, 341
 ams nodisplayskip upper, 341
 arc, 36
 arc is angular, 38
 arc is curved, 38
 at begin tikz, 184
 at begin tikz reset, 184
 at end tikz, 184
 at end tikz reset, 184
 attach boxed title to bottom, 148
 attach boxed title to bottom center, 147
 attach boxed title to bottom left, 147
 attach boxed title to bottom right, 147
 attach boxed title to bottom*, 148
 attach boxed title to top, 148
 attach boxed title to top center, 147
 attach boxed title to top left, 147
 attach boxed title to top right, 147
 attach boxed title to top*, 148
 attach title, 20
 attach title to upper, 20
 auto outer arc, 38
 autoparskip, 76
 baseline, 77
 beamer, 218
 bean arc, 37
 before, 76
 before app, 395
 before doc body, 445
 before doc body command, 445
 before doc body environment, 445
 before doc body key, 445
 before example, 439
 before lower, 64
 before lower app, 395
 before lower pre, 395
 before nobreak, 79
 before pre, 395
 before skip, 78
 before title, 62
 before title app, 394
 before title pre, 394
 before upper, 63
 before upper app, 394
 before upper pre, 394
 beforeafter skip, 78
 bicolor, 209
 blank, 198
 blanker, 228
 blankest, 229
 blend before title, 106
 blend before title code, 107
 borderline, 169
 borderline east, 172
 borderline horizontal, 173
 borderline north, 172
 borderline south, 172
 borderline vertical, 173
 borderline west, 172
 bottom, 42
 bottomrule, 35
 bottomrule at break, 357
 bottomsep at break, 357
 bottomtitle, 42
 box align, 77
 boxed title size, 150
 boxed title style, 151
 boxrule, 36
 boxsep, 38
 break at, 355
 breakable, 353
 capture, 90
 center, 82
 center lower, 32
 center title, 32
 center upper, 32
 check odd page, 96
 circular arc, 37
 clip lower, 168
 clip title, 167
 clip upper, 167
 clip watermark, 163
 code, 100
 colback, 27
 colbacklower, 210
 colbacktitle, 27
 colframe, 27
 collower, 28
 color color, 441
 color command, 441
 color counter, 441
 color definition, 441
 color environment, 441
 color hyperlink, 441
 color key, 441
 color length, 441
 color option, 441
 color value, 441
 coltext, 28
 coltitle, 28
 colupper, 28
 comment, 300
 comment above listing, 307
 comment above* listing, 307

comment and listing, 303
comment only, 300
comment outside listing, 305
comment side listing, 305
comment style, 303
compilable listing, 311
compress page, 356
description color, 333
description delimiters, 333
description delimiters none, 333
description delimiters parenthesis, 333
description font, 334
description formatter, 334
detach title, 20
do not store to box array, 377
doc description, 446
doc head, 444
doc head command, 444
doc head environment, 444
doc head key, 444
doc into index, 446
doc left, 443
doc left indent, 443
doc marginnote, 446
doc new, 446
doc new and updated, 446
doc right, 443
doc right indent, 443
doc updated, 446
docexample, 439
documentation listing options, 439
documentation listing style, 439
documentation minted options, 439
documentation minted style, 439
draft, 238
draftmode, 193
drop fuzzy midday shadow, 175
drop fuzzy shadow, 174
drop fuzzy shadow east, 178
drop fuzzy shadow north, 178
drop fuzzy shadow northeast, 178
drop fuzzy shadow northwest, 178
drop fuzzy shadow south, 177
drop fuzzy shadow southeast, 177
drop fuzzy shadow southwest, 177
drop fuzzy shadow west, 177
drop large lifted shadow, 179
drop lifted shadow, 179
drop midday shadow, 174
drop shadow, 174
drop shadow east, 177
drop shadow north, 176
drop shadow northeast, 177
drop shadow northwest, 176
drop shadow south, 176
drop shadow southeast, 176
drop shadow southwest, 176
drop shadow west, 176
drop small lifted shadow, 179
empty, 227
enforce breakable, 354
english language, 442
enhanced, 196
enhanced jigsaw, 203
enhanced standard, 198
enlarge bottom at break by, 81
enlarge bottom by, 81
enlarge bottom finally by, 80
enlarge by, 82
enlarge left by, 81
enlarge right by, 81
enlarge top at break by, 81
enlarge top by, 81
enlarge top initially by, 80
enlargepage, 355
enlargepage flexible, 356
equal height group, 59
every box, 87
every box on higher layers, 88
every box on layer n, 88
every float, 75
every listing line, 295
every listing line*, 295
extend freelance, 240
extend freelancefirst, 240
extend freelancelast, 240
extend freelancemiddle, 240
external, 99
externalize example, 423
externalize example!, 423
externalize listing, 423
externalize listing!, 423
extras, 359
extras broken, 359
extras broken pre, 403
extras first, 359
extras first and middle, 359
extras first and middle pre, 403
extras first pre, 403
extras last, 359
extras last pre, 403
extras middle, 359
extras middle and last, 359
extras middle and last pre, 403
extras middle pre, 403
extras pre, 403
extras unbroken, 359
extras unbroken and first, 359
extras unbroken and first pre, 403
extras unbroken and last, 359
extras unbroken and last pre, 403
extras unbroken pre, 403
extrude bottom by, 86
extrude by, 86
extrude left by, 85
extrude right by, 85
extrude top by, 86

finish, 189
finish broken, 190
finish broken pre, 401
finish fading vignette, 264
finish first, 190
finish first and middle, 190
finish first and middle pre, 401
finish first pre, 401
finish last, 190
finish last pre, 401
finish middle, 190
finish middle and last, 190
finish middle and last pre, 401
finish middle pre, 401
finish pre, 401
finish raised fading vignette, 263
finish unbroken, 190
finish unbroken and first, 190
finish unbroken and first pre, 401
finish unbroken and last, 190
finish unbroken and last pre, 401
finish unbroken pre, 401
finish vignette, 263
fit, 384
fit algorithm, 390
fit basedim, 385
fit fontsize macros, 386
fit height from, 389
fit height plus, 387
fit maxfontdiff, 392
fit maxfontdiffgap, 392
fit maxstep, 392
fit maxwidthdiff, 392
fit maxwidthdiffgap, 392
fit skip, 385
fit to, 385
fit to height, 385
fit warning, 392
fit width from, 388
fit width plus, 387
flip title, 148
float, 74
float*, 74
floatplacement, 74
flush left, 82
flush right, 82
flushleft lower, 32
flushleft title, 32
flushleft upper, 32
flushright lower, 32
flushright title, 32
flushright upper, 32
fontlower, 29
fonttitle, 29
fontupper, 29
forces nobeforeafter, 76
frame code, 130
frame code app, 401
frame code pre, 401
frame empty, 130
frame engine, 127
frame hidden, 141
frame style, 140
frame style image, 140
frame style tile, 141
freelance, 240
freeze extension, 314
freeze file, 314
freeze jpg, 314
freeze none, 314
freeze pdf, 314
freeze png, 314
fuzzy halo, 175
fuzzy shadow, 181
geometry nodes, 129
graphical environment, 126
graphics directory, 244
graphics options, 244
graphics pages, 244
grow to left by, 83
grow to right by, 83
halign, 30
halign lower, 31
halign title, 32
halign upper, 30
halo, 175
hbox, 90
hbox boxed title, 155
height, 52
height fill, 55
height fixed for, 358
height from, 53
height plus, 52
highlight math, 337
highlight math style, 337
hyphenationfix, 92
if odd page, 96
if odd page*, 97
IfBooleanTF, 405
IfNoValueTF, 404
IfValueTF, 405
ignore nobreak, 79
image comment, 300
index actual, 440
index annotate, 441
index colorize, 441
index command, 440
index command name, 440
index default settings, 440
index format, 440
index german settings, 440
index level, 440
index quote, 440
interior code, 131
interior code app, 402
interior code pre, 402
interior empty, 131
interior engine, 128

`interior hidden`, 142
`interior style`, 141
`interior style image`, 142
`interior style tile`, 142
`interior titled code`, 130
`interior titled code app`, 401
`interior titled code pre`, 402
`interior titled empty`, 130
`interior titled engine`, 127
`invisible`, 22
`label`, 94
`label separator`, 335
`label type`, 94
`left`, 39
`left skip`, 79
`lefthand ratio`, 113
`lefthand width`, 112
`leftlower`, 39
`leftright skip`, 79
`leftrule`, 35
`lefttitle`, 39
`leftupper`, 39
`lifted shadow`, 182
`lines before break`, 354
`list entry`, 95
`list text`, 95
`listing above comment`, 307
`listing above text`, 306
`listing above* comment`, 307
`listing above* text`, 306
`listing and comment`, 303
`listing and text`, 299
`listing engine`, 299
`listing file`, 299
`listing inputencoding`, 295
`listing only`, 299
`listing options`, 294
`listing outside comment`, 305
`listing outside text`, 304
`listing remove caption`, 295
`listing side comment`, 305
`listing side text`, 304
`listing style`, 294
`listing utf8`, 296
`lower separated`, 25
`lowerbox`, 24
`marker`, 205
`math`, 338
`math lower`, 338
`math upper`, 338
`middle`, 42
`minimum for current equal height group`, 60
`minimum for equal height group`, 60
`minipage`, 90
`minipage boxed title`, 155
`minipage boxed title*`, 155
`minted language`, 297
`minted options`, 297
`minted style`, 298
`nameref`, 95
`natural height`, 52
`no borderline`, 171
`no boxed title style`, 154
`no extras`, 359
`no extras first`, 359
`no extras last`, 359
`no extras middle`, 359
`no extras unbroken`, 359
`no finish`, 190
`no finish first`, 190
`no finish last`, 190
`no finish middle`, 190
`no finish unbroken`, 190
`no label type`, 94
`no listing options`, 294
`no overlay`, 70
`no process`, 311
`no recording`, 120
`no shadow`, 174
`no underlay`, 187
`no underlay boxed title`, 188
`no underlay first`, 188
`no underlay last`, 188
`no underlay middle`, 188
`no underlay unbroken`, 188
`no watermark`, 159
`nobeforeafter`, 76
`nofloat`, 74
`noparskip`, 76
`nophantom`, 94
`notitle`, 18
`notitle after break`, 354
`octogon arc`, 37
`on line`, 92
`only`, 100
`opacityback`, 50
`opacitybacktitle`, 50
`opacityfill`, 50
`opacityframe`, 50
`opacitylower`, 51
`opacitytext`, 51
`opacitytitle`, 51
`opacityupper`, 51
`outer arc`, 38
`overlay`, 69
`overlay app`, 396
`overlay broken`, 70
`overlay broken app`, 397
`overlay broken pre`, 397
`overlay first`, 70
`overlay first and middle`, 70
`overlay first and middle app`, 397
`overlay first and middle pre`, 397
`overlay first app`, 396
`overlay first pre`, 396
`overlay last`, 70
`overlay last app`, 397

overlay last pre, 397
 overlay middle, 70
 overlay middle and last, 70
 overlay middle and last app, 397
 overlay middle and last pre, 397
 overlay middle app, 397
 overlay middle pre, 397
 overlay pre, 396
 overlay unbroken, 70
 overlay unbroken and first, 70
 overlay unbroken and first app, 397
 overlay unbroken and first pre, 397
 overlay unbroken and last, 70
 overlay unbroken and last app, 397
 overlay unbroken and last pre, 397
 overlay unbroken app, 396
 overlay unbroken pre, 396
 oversize, 44
 pad after break, 357
 pad at break, 357
 pad at break*, 357
 pad before break, 357
 pad before break*, 357
 parbox, 91
 parskip, 76
 pdf comment, 301
 pdf extension, 303
 phantom, 94
 phantomlabel, 94
 process code, 311
 raster after skip, 273
 raster before skip, 273
 raster column n, 277
 raster column skip, 274
 raster columns, 272
 raster equal height, 276
 raster equal height group, 276
 raster equal skip, 273
 raster even column, 277
 raster even number, 278
 raster even row, 278
 raster every box, 277
 raster force size, 277
 raster halign, 275
 raster height, 273
 raster left skip, 274
 raster multicolumn, 279
 raster multirow, 280
 raster number n, 278
 raster odd column, 277
 raster odd number, 278
 raster odd row, 277
 raster reset, 277
 raster right skip, 274
 raster row m, 278
 raster row m column n, 278
 raster row skip, 274
 raster rows, 272
 raster valign, 275
 raster width, 272
 record, 120
 remake, 99
 remember, 185
 remember as, 186
 reset, 99
 reset and store to box array, 377
 reset box array, 374
 right, 40
 right skip, 79
 righthand ratio, 113
 righthand width, 112
 rightlower, 41
 rightrule, 35
 righttitle, 40
 rightupper, 40
 rotate, 185
 rounded corners, 48
 run arara, 313
 run biber, 313
 run bibtex, 313
 run dvips, 313
 run latex, 313
 run lualatex, 313
 run makeindex, 313
 run pdflatex, 311
 run ps2pdf, 313
 run system command, 311
 run xelatex, 313
 savedelimiter, 26
 savelowerto, 24
 saveto, 23
 scale, 185
 segmentation code, 131
 segmentation code app, 402
 segmentation code pre, 402
 segmentation empty, 131
 segmentation engine, 128
 segmentation hidden, 143
 segmentation style, 143
 separator sign, 332
 separator sign colon, 332
 separator sign dash, 332
 separator sign none, 332
 shadow, 180
 sharp corners, 47
 sharpish corners, 48
 shield externalize, 99
 show bounding box, 171
 shrink break goal, 356
 shrink tight, 85
 sidebyside, 109
 sidebyside adapt, 116
 sidebyside align, 110
 sidebyside gap, 112
 sidebyside switch, 118
 size, 43
 skin, 126
 skin first, 126

skin first is subskin of, 133
 skin last, 126
 skin last is subskin of, 133
 skin middle, 126
 skin middle is subskin of, 133
 smart shadow arc, 182
 space, 56
 space to, 57
 space to both, 57
 space to lower, 56
 space to upper, 56
 spartan, 237
 split, 58
 square, 56
 squeezed title, 19
 squeezed title*, 19
 standard, 194
 standard jigsaw, 195
 step, 94
 step and label, 94
 store to box array, 375
 subtitle style, 21
 tabularx, 66
 tabularx*, 66
 tcbimage comment, 301
 tcbox raise, 92
 tcbox raise base, 92
 tcbox width, 93
 tempfile, 92
 terminator sign, 334
 terminator sign colon, 335
 terminator sign dash, 335
 terminator sign none, 335
 text above listing, 306
 text above* listing, 306
 text and listing, 299
 text fill, 65
 text height, 53
 text only, 300
 text outside listing, 304
 text side listing, 304
 text width, 34
 theorem, 337
 theorem name, 336
 theorem name and number, 336
 theorem number and name, 336
 theorem style, 342
 tikz, 184
 tikz lower, 67
 tikz reset, 184
 tikz upper, 67
 tikznode, 68
 tikznode boxed title, 156
 tikznode lower, 68
 tikznode upper, 68
 tile, 214
 title, 18
 title after break, 354
 title code, 132
 title code app, 402
 title code pre, 402
 title empty, 132
 title engine, 128
 title filled, 27
 title hidden, 144
 title style, 143
 title style image, 144
 title style tile, 144
 titlerule, 36
 titlerule style, 145
 toggle enlargement, 84
 toggle left and right, 45
 top, 41
 toprule, 35
 toprule at break, 357
 topsep at break, 357
 toptitle, 41
 unbreakable, 354
 underlay, 187
 underlay boxed title, 188
 underlay boxed title pre, 400
 underlay broken, 188
 underlay broken pre, 400
 underlay first, 188
 underlay first and middle, 188
 underlay first and middle pre, 400
 underlay first pre, 400
 underlay last, 188
 underlay last pre, 400
 underlay middle, 188
 underlay middle and last, 188
 underlay middle and last pre, 400
 underlay middle pre, 400
 underlay pre, 400
 underlay raised fading vignette, 262
 underlay raised shading vignette, 262
 underlay shade in vignette, 262
 underlay unbroken, 188
 underlay unbroken and first, 188
 underlay unbroken and first pre, 400
 underlay unbroken and last, 188
 underlay unbroken and last pre, 400
 underlay unbroken pre, 400
 underlay vignette, 261
 upperbox, 22
 use height from group, 61
 valign, 33
 valign lower, 33
 valign scale limit, 33
 valign upper, 33
 varwidth boxed title, 156
 varwidth boxed title*, 156
 varwidth upper, 68
 verbatim, 404
 vfill before first, 358

```

visible, 22
watermark color, 162
watermark graphics, 158
watermark graphics app, 399
watermark graphics app on, 399
watermark graphics on, 158
watermark graphics pre, 399
watermark graphics pre on, 399
watermark opacity, 160
watermark overzoom, 161
watermark shrink, 161
watermark stretch, 162
watermark text, 157
watermark text app, 398
watermark text app on, 398
watermark text on, 157
watermark text pre, 398
watermark text pre on, 398
watermark tikz, 159
watermark tikz app, 399
watermark tikz app on, 399
watermark tikz on, 159
watermark tikz pre, 399
watermark tikz pre on, 399
watermark zoom, 160
widget, 223
width, 34
/tcb/boxtitle/
xshift, 149
yshift, 149
yshift*, 149
yshifttext, 149
/tcb/doclang/
color, 442
colors, 442
counter, 442
counters, 442
environment, 442
environment content, 442
environments, 442
index, 442
key, 442
keys, 442
length, 442
lengths, 442
new, 442
pageshort, 442
updated, 442
value, 442
values, 442
/tcb/external/
 $-$ , 418
 $!$ , 418
clear preamble, 425
clear preclass, 425
compiler, 424
environment, 424
environment with percent, 424
externalize, 418
force remake, 418
input source on error, 424
minipage, 424
name, 420
PassOptionsToClass, 425
PassOptionsToPackage, 425
plain, 424
preamble, 425
preamble tcbset, 425
preclass, 425
prefix, 418
runner, 418
runs, 424
safety, 424
/tcb/library/
all, 10
breakable, 9
documentation, 10
external, 10
fitting, 9
hooks, 9
listings, 9
listingsutf8, 9
magazine, 9
many, 10
minted, 9
most, 10
raster, 9
skins, 9
theorems, 9
vignette, 9
xparse, 10
/tcb/new/
auto counter, 101
blend into, 105
Crefname, 104
crefname, 104
list inside, 108
list type, 108
no counter, 102
number format, 103
number freestyle, 103
number within, 103
use counter, 102
use counter from, 102
use counter*, 102
/tcb/vig/
base color, 258
color from, 258
draw method, 259
east size, 256
east style, 257
fade in, 260
fade out, 260
horizontal size, 257
inside node, 255
lower left corner, 255
lowered color, 258
north size, 256

```

```

north style, 257
outside node, 256
over node, 256
over node offset, 256
raised color, 258
scope, 258
semi fade in, 260
semi fade out, 260
size, 257
south size, 256
south style, 257
upper right corner, 255
vertical size, 257
west size, 256
west style, 258
xmax, 255
xmin, 255
ymax, 255
ymin, 255
/tikz/
  fill image opacity, 251
  fill image options, 251
  fill image scale, 251
  fill overzoom image, 247
  fill overzoom image*, 247
  fill overzoom picture, 247
  fill plain image, 245
  fill plain image*, 245
  fill plain picture, 245
  fill shrink image, 249
  fill shrink image*, 249
  fill shrink picture, 249
  fill stretch image, 246
  fill stretch image*, 246
  fill stretch picture, 246
  fill tile image, 250
  fill tile image*, 250
  fill tile picture, 250
  fill tile picture*, 250
  fill zoom image, 248
  fill zoom image*, 248
  fill zoom picture, 248
  tcb fill frame, 146
  tcb fill interior, 146
  tcb fill title, 146
keys key, 442
label key, 94
label separator key, 335
label type key, 94
last value, 157–159, 358
left key, 39
left value, 30, 116, 275
left skip key, 79
lefthand ratio key, 113
lefthand width key, 112
leftlower key, 39
leftright skip key, 79
leftrule key, 35
lefttitle key, 39
leftupper key, 39
length key, 442
Lengths
  \foolength, 432
lengths key, 442
lifted shadow key, 182
lines before break key, 354
list entry key, 95
list inside key, 108
list text key, 95
list type key, 108
listing above comment key, 307
listing above text key, 306
listing above* comment key, 307
listing above* text key, 306
listing and comment key, 303
listing and text key, 299
listing engine key, 299
listing file key, 299
listing inputencoding key, 295
listing only key, 299
listing options key, 294
listing outside comment key, 305
listing outside text key, 304
listing remove caption key, 295
listing side comment key, 305
listing side text key, 304
listing style key, 294
listing utf8 key, 296
listings key, 9
listings value, 105, 299
listingsutf8 key, 9
lower left corner key, 255
lower separated key, 25
lowerbox key, 24
lowered color key, 258
magazine key, 9
many key, 10
\marg, 433
margin value, 344
margin apart value, 344
margin break value, 344
marker key, 205
math key, 338
math lower key, 338
math upper key, 338
maximum value, 55
\meta, 433
middle key, 42
middle value, 157–159, 358
middle and last value, 157–159, 358
minimal value, 43
minimum center value, 93
minimum for current equal height group
  key, 60
minimum for equal height group key, 60
minimum left value, 93
minimum right value, 93
minipage key, 90, 424

```

minipage value, 90, 269
minipage boxed title key, 155
minipage boxed title* key, 155
minted key, 9
minted value, 299
minted language key, 297
minted options key, 297
minted style key, 298
most key, 10

name key, 420
nameref key, 95
natural height key, 52
new key, 442
`\newboxarray`, 374
`\newtcbexternalizeenvironment`, 426
`\newtcbexternalizetcolorbox`, 426
`\NewTCBInputListing`, 414
`\newtcbinputlisting`, 293
`\NewTCBListing`, 412
`\newtcblisting`, 291
`\NewTCBox`, 409
`\newtcbox`, 16
`\NewTCBoxFit`, 415
`\newtcboxfit`, 383
`\new tcbtheorem`, 328
`\NewTColorBox`, 407
`\newtcolorbox`, 15
`\NewTotalTCBox`, 411
`\NewTotalTCBoxFit`, 416
`\NewTotalTColorBox`, 408
no borderline key, 171
no boxed title style key, 154
no counter key, 102
no extras key, 359
no extras first key, 359
no extras last key, 359
no extras middle key, 359
no extras unbroken key, 359
no finish key, 190
no finish first key, 190
no finish last key, 190
no finish middle key, 190
no finish unbroken key, 190
no label type key, 94
no listing options key, 294
no overlay key, 70
no process key, 311
no recording key, 120
no shadow key, 174
no underlay key, 187
no underlay boxed title key, 188
no underlay first key, 188
no underlay last key, 188
no underlay middle key, 188
no underlay unbroken key, 188
no watermark key, 159
nobeforeafter key, 76
nofloat key, 74
none value, 45, 84, 116, 276, 356, 358

noparskip key, 76
nophantom key, 94
normal value, 43, 150
north fading, 259
north value, 47, 48
north size key, 256
north style key, 257
northeast value, 47, 48
northwest value, 47, 48
notitle key, 18
notitle after break key, 354
number format key, 103
number freestyle key, 103
number within key, 103

`\oarg`, 433
octagon arc key, 37
off value, 392, 440
on value, 392
on line key, 92
only key, 100
opacityback key, 50
opacitybacktitle key, 50
opacityfill key, 50
opacityframe key, 50
opacitylower key, 51
opacitytext key, 51
opacitytitle key, 51
opacityupper key, 51
Option color, 446
outer arc key, 38
outside node key, 256
over node key, 256
over node offset key, 256
overlay key, 69
overlay app key, 396
overlay broken key, 70
overlay broken app key, 397
overlay broken pre key, 397
overlay first key, 70
overlay first and middle key, 70
overlay first and middle app key, 397
overlay first and middle pre key, 397
overlay first app key, 396
overlay first pre key, 396
overlay last key, 70
overlay last app key, 397
overlay last pre key, 397
overlay middle key, 70
overlay middle and last key, 70
overlay middle and last app key, 397
overlay middle and last pre key, 397
overlay middle app key, 397
overlay middle pre key, 397
overlay pre key, 396
overlay unbroken key, 70
overlay unbroken and first key, 70
overlay unbroken and first app key, 397
overlay unbroken and first pre key, 397
overlay unbroken and last key, 70

overlay unbroken and last app key, 397
 overlay unbroken and last pre key, 397
 overlay unbroken app key, 396
 overlay unbroken pre key, 396
 oversize key, 44

 pad after break key, 357
 pad at break key, 357
 pad at break* key, 357
 pad before break key, 357
 pad before break* key, 357
 pageshort key, 442
 parbox key, 91
 parskip key, 76
 PassOptionsToClass key, 425
 PassOptionsToPackage key, 425
 path value, 127, 128
 pathfirst value, 127, 128
 pathfirstjigsaw value, 127
 pathjigsaw value, 127
 pathlast value, 127, 128
 pathlastjigsaw value, 127
 pathmiddle value, 127, 128
 pathmiddlejigsaw value, 127
 pdf comment key, 301
 pdf extension key, 303
 \pdfpages, 244
 pgf value, 440
 pgfchapter value, 440
 pgfsection value, 440
 phantom key, 94
 phantomlabel key, 94
 plain key, 424
 plain value, 342
 plain apart value, 343
 preamble key, 425
 preamble tcbset key, 425
 preclass key, 425
 prefix key, 418
 process code key, 311
 \ProvideTCBInputListing, 414
 \ProvideTCBListing, 412
 \ProvideTCBox, 409
 \ProvideTCBoxFit, 415
 \ProvideTColorBox, 407
 \ProvideTotalTCBox, 411
 \ProvideTotalTCBoxFit, 416
 \ProvideTotalTColorBox, 408

 raised color key, 258
 raster key, 9
 raster after skip key, 273
 raster before skip key, 273
 raster column n key, 277
 raster column skip key, 274
 raster columns key, 272
 raster equal height key, 276
 raster equal height group key, 276
 raster equal skip key, 273
 raster even column key, 277

 raster even number key, 278
 raster even row key, 278
 raster every box key, 277
 raster force size key, 277
 raster halign key, 275
 raster height key, 273
 raster left skip key, 274
 raster multicolumn key, 279
 raster multirow key, 280
 raster number n key, 278
 raster odd column key, 277
 raster odd number key, 278
 raster odd row key, 277
 raster reset key, 277
 raster right skip key, 274
 raster row m key, 278
 raster row m column n key, 278
 raster row skip key, 274
 raster rows key, 272
 raster valign key, 275
 raster width key, 272
 record key, 120
 \refAux, 437
 \refAuxcs, 437
 \refCom, 436
 \refCom*, 436
 \refEnv, 436
 \refEnv*, 436
 \refKey, 437
 \refKey*, 437
 remake key, 99
 remember key, 185
 remember as key, 186
 \renewtcbexternalizeenvironment, 426
 \renewtcbexternalizetcolorbox, 427
 \RenewTCBInputListing, 414
 \renewtcbinputlisting, 293
 \RenewTCBListing, 412
 \renewtcblisting, 292
 \RenewTCBox, 409
 \renewtcbox, 16
 \RenewTCBoxFit, 415
 \renewtcboxfit, 383
 \renewtcbtheorem, 329
 \RenewTColorBox, 407
 \renewtcolorbox, 15
 \RenewTotalTCBox, 411
 \RenewTotalTCBoxFit, 416
 \RenewTotalTColorBox, 408
 reset key, 99
 reset and store to box array key, 377
 reset box array key, 374
 right key, 40
 right value, 30, 116, 275
 right skip key, 79
 righthand ratio key, 113
 righthand width key, 112
 rightlower key, 41
 rightrule key, 35

righttitle key, 40
rightupper key, 40
rotate key, 185
rounded corners key, 48
rows value, 276
run arara key, 313
run biber key, 313
run bibtex key, 313
run dvips key, 313
run latex key, 313
run lualatex key, 313
run makeindex key, 313
run pdflatex key, 311
run ps2pdf key, 313
run system command key, 311
run xelatex key, 313
runner key, 418
runs key, 424

safety key, 424
savedelimiter key, 26
savelowersto key, 24
saveto key, 23
scale key, 185
scale value, 33
scale* value, 33
scope key, 258
segmentation code key, 131
segmentation code app key, 402
segmentation code pre key, 402
segmentation empty key, 131
segmentation engine key, 128
segmentation hidden key, 143
segmentation style key, 143
semi east fading, 259
semi fade in key, 260
semi fade out key, 260
semi north fading, 259
semi south fading, 259
semi west fading, 259
separator sign key, 332
separator sign colon key, 332
separator sign dash key, 332
separator sign none key, 332
shadow key, 180
sharp corners key, 47
sharpish corners key, 48
shield externalize key, 99
show bounding box key, 171
shrink break goal key, 356
shrink tight key, 85
sidebyside key, 109
sidebyside adapt key, 116
sidebyside align key, 110
sidebyside gap key, 112
sidebyside switch key, 118
size key, 43, 257
skin key, 126
skin first key, 126
skin first is subskin of key, 133

skin last key, 126
skin last is subskin of key, 133
skin middle key, 126
skin middle is subskin of key, 133
Skins
 beamer, 218
 beamercolor, 220
 beameralternate, 222
 beamermiddle, 221
 bicolor, 209
 bicolorfirst, 211
 bicolorlast, 213
 bicolormiddle, 212
 draft, 238
 empty, 227
 emptyfirst, 230
 emptylast, 232
 emptymiddle, 231
 enhanced, 196
 enhanced jigsaw, 203
 enhancedfirst, 200
 enhancedfirst jigsaw, 204
 enhancedlast, 202
 enhancedlast jigsaw, 208
 enhancedmiddle, 201
 enhancedmiddle jigsaw, 205
 freelance, 240
 freelancefirst, 240
 freelancelast, 240
 freelancemiddle, 240
 spartan, 237
 standard, 194
 standard jigsaw, 195
 tile, 214
 tilefirst, 215
 tilelast, 217
 timiddle, 216
 widget, 223
 widgetfirst, 224
 widgetlast, 226
 widgetmiddle, 225
skins key, 9
small value, 43
smart shadow arc key, 182
south fading, 259
south value, 47, 48
south size key, 256
south style key, 257
southeast value, 47, 48
southwest value, 47, 48
space key, 56
space to key, 57
space to both key, 57
space to lower key, 56
space to upper key, 56
spartan key, 237
spartan Skin, 237
spartan value, 127, 128
split key, 58

square key, 56
squeeze value, 390
squeezed title key, 19
squeezed title* key, 19
standard key, 194
standard Skin, 194
standard value, 127, 128, 150, 342
standard jigsaw key, 195
standard jigsaw Skin, 195
step key, 94
step and label key, 94
store to box array key, 375
subtitle style key, 21

tables value, 105
tabularx key, 66
tabularx* key, 66
tcb fill frame key, 146
tcb fill interior key, 146
tcb fill title key, 146
tcbclipframe environment, 164
tcbclipinterior environment, 166
tcbcliptitle environment, 166
\tcbcontinuedraftmode, 193
\tcbcounter, 101
\tcbboxmarginnote, 438
\tcbboxnew, 438
\tcbboxupdated, 438
tcbexternal environment, 419
\tcbEXTERNALIZE, 418
\tcbfitdim, 383–386
\tcbfitsteps, 384
\tcbfontsize, 383
\tcbheightfromgroup, 61
\tcbheightspace, 138
\tcbhighmath, 330
\tcbifexternal, 425
\tcbiffileprocess, 427
\tcbifoddpage, 97
tcbimage comment key, 301
\tcbboxincludegraphics, 241
\tcbboxincludepdf, 243
\tcbboxinputlisting, 290
\tcbboxinputrecords, 120
\tcbinterruptdraftmode, 193
tcbinvclipframe environment, 165
\tcbitem, 269
tcbitemize environment, 269
\tcbline, 199
\tcbline*, 199
tcblisting environment, 288
\tcblistof, 108
\tcblower, 12
\tcbmakelocSubKey, 436
\tcbmaketheorem, 329
tcboutputlisting environment, 290
\tcbbox, 14
tcbbox raise key, 92
tcbbox raise base key, 92
tcbbox width key, 93

tcboxeditemize environment, 271
tcboxedraster environment, 270
\tcbboxedtitleheight, 149
\tcbboxedtitlewidth, 149
\tcbboxfit, 382
\tcbboxmath, 330
\tcbboxverb, 411
\tcbpatcharcangular, 252
\tcbpatcharcround, 252
tcbraster environment, 268
\tcbrecord, 120
\tcbset, 13
\tcbsetforeverylayer, 13
\tcbsetmacrotoheightofnode, 253
\tcbsetmacrotowidthofnode, 253
\tcbsetmanagedlayer, 88
\tcbsettoheightofnode, 253
\tcbsettowidthofnode, 253
\tcbsetwidebyside, 115
\tcbstartdraftmode, 193
\tcbstartrecording, 120
\tcbstopdraftmode, 193
\tcbstoprecording, 120
\tcbsubskin, 133
\tcbsubtitle, 21
\tcbtextheight, 139
\tcbtextwidth, 138
\tcbtitle, 20
\tcbtitletext, 20
\tcbuselibrary, 9
\tcbuselistinglisting, 290
\tcbuselistingtext, 290
\tcbusetemp, 119
\tcbusetempling, 290
tcbverbatimwrite environment, 119
\tcbvignette, 254
\tcbwritetemp environment, 119
tcolorbox environment, 12
\tcolorboxenvironment, 17
tempfile key, 92
terminator sign key, 334
terminator sign colon key, 335
terminator sign dash key, 335
terminator sign none key, 335
text above listing key, 306
text above* listing key, 306
text and listing key, 299
text fill key, 65
text height key, 53
text only key, 300
text outside listing key, 304
text side listing key, 304
text width key, 34
theorem key, 337
theorem name key, 336
theorem name and number key, 336
theorem number and name key, 336
theorem style key, 342
theorems key, 9

\thetcbcounter, 101, 102
\thetcbrasternum, 268, 279
\thetcboxnumber, 98
\thetcboxpage, 98
tight value, 43
tikz key, 184
tikz lower key, 67
tikz reset key, 184
tikz upper key, 67
tikznode key, 68
tikznode boxed title key, 156
tikznode lower key, 68
tikznode upper key, 68
tile key, 214
tile Skin, 214
tilefirst Skin, 215
tilelast Skin, 217
tilemiddle Skin, 216
title key, 18
title value, 43, 150
title after break key, 354
title code key, 132
title code app key, 402
title code pre key, 402
title empty key, 132
title engine key, 128
title filled key, 27
title hidden key, 144
title style key, 143
title style image key, 144
title style tile key, 144
titlerule key, 36
titlerule style key, 145
toggle enlargement key, 84
toggle left and right key, 45
top key, 41
top value, 33, 77, 110, 275
top seam value, 110
toprule key, 35
toprule at break key, 357
topsep at break key, 357
toptitle key, 41
true value, 79, 353

unbreakable key, 354
unbroken value, 157–159
unbroken and first value, 157–159
underlay key, 187
underlay boxed title key, 188
underlay boxed title pre key, 400
underlay broken key, 188
underlay broken pre key, 400
underlay first key, 188
underlay first and middle key, 188
underlay first and middle pre key, 400
underlay first pre key, 400
underlay last key, 188
underlay last pre key, 400
underlay middle key, 188
underlay middle and last key, 188

underlay middle and last pre key, 400
underlay middle pre key, 400
underlay pre key, 400
underlay raised fading vignette key, 262
underlay raised shading vignette key, 262
underlay shade in vignette key, 262
underlay unbroken key, 188
underlay unbroken and first key, 188
underlay unbroken and first pre key, 400
underlay unbroken and last key, 188
underlay unbroken and last pre key, 400
underlay unbroken pre key, 400
underlay vignette key, 261
unlimited value, 352, 353
updated key, 442
uphill value, 47, 48
upper right corner key, 255
upperbox key, 22
use counter key, 102
use counter from key, 102
use counter* key, 102
use height from group key, 61
\useboxarray, 377
\usetcboxarray, 378

valign key, 33
valign lower key, 33
valign scale limit key, 33
valign upper key, 33
value key, 442
Values
all, 47, 48, 276, 356, 358
areasize, 390
areasize*, 390
auto, 93
auto limited, 93
base, 77
baselineskip, 356
both, 116
bottom, 33, 77, 110, 275
bottom seam, 110
break, 343
broken, 157–159
center, 30, 33, 77, 110, 275
center seam, 110
change, 343
change apart, 343
change break, 343
change standard, 342
clipped, 259
colon, 106
colon hang, 106
copy, 150
dash, 106
dash hang, 106
direct, 259
doc, 440
downhill, 47, 48
east, 47, 48
empty, 127, 128

evenpage, 45, 84
false, 76, 79, 277, 353
fbox, 43
figures, 105
final, 392
first, 157–159, 358
first and middle, 157, 358
fitbox, 90
flush center, 30, 32
flush left, 30, 32
flush right, 30, 32
fontsize, 390
fontsize*, 390
foovalue, 431
forced, 45, 84
forced center, 93
forced left, 93
forced right, 93
freelance, 127, 128
hbox, 90
hybrid, 390
hybrid*, 390
ignored, 24
invisible, 22, 24
justify, 30
last, 157–159, 358
left, 30, 116, 275
listings, 105, 299
margin, 344
margin apart, 344
margin break, 344
maximum, 55
middle, 157–159, 358
middle and last, 157–159, 358
minimal, 43
minimum center, 93
minimum left, 93
minimum right, 93
minipage, 90, 269
minted, 299
none, 45, 84, 116, 276, 356, 358
normal, 43, 150
north, 47, 48
northeast, 47, 48
northwest, 47, 48
off, 392, 440
on, 392
path, 127, 128
pathfirst, 127, 128
pathfirstjigsaw, 127
pathjigsaw, 127
pathlast, 127, 128
pathlastjigsaw, 127
pathmiddle, 127, 128
pathmiddlejigsaw, 127
pgf, 440
pgfchapter, 440
pgfsection, 440
plain, 342
plain apart, 343
right, 30, 116, 275
rows, 276
scale, 33
scale*, 33
small, 43
south, 47, 48
southeast, 47, 48
southwest, 47, 48
spartan, 127, 128
squeeze, 390
standard, 127, 128, 150, 342
tables, 105
tight, 43
title, 43, 150
top, 33, 77, 110, 275
top seam, 110
true, 79, 353
unbroken, 157–159
unbroken and first, 157–159
unlimited, 352, 353
uphill, 47, 48
visible, 22, 24
west, 47, 48
values key, 442
varwidth boxed title key, 156
varwidth boxed title* key, 156
varwidth upper key, 68
verbatim key, 404
vertical size key, 257
vfill before first key, 358
vignette key, 9
visible key, 22
visible value, 22, 24
watermark color key, 162
watermark graphics key, 158
watermark graphics app key, 399
watermark graphics app on key, 399
watermark graphics on key, 158
watermark graphics pre key, 399
watermark graphics pre on key, 399
watermark opacity key, 160
watermark overzoom key, 161
watermark shrink key, 161
watermark stretch key, 162
watermark text key, 157
watermark text app key, 398
watermark text app on key, 398
watermark text on key, 157
watermark text pre key, 398
watermark text pre on key, 398
watermark tikz key, 159
watermark tikz app key, 399
watermark tikz app on key, 399
watermark tikz on key, 159
watermark tikz pre key, 399
watermark tikz pre on key, 399
watermark zoom key, 160
west fading, 259

`west` value, 47, 48
`west size` key, 256
`west style` key, 258
`widget` key, 223
`widget Skin`, 223
`widgetfirst Skin`, 224
`widgetlast Skin`, 226
`widgetmiddle Skin`, 225
`width` key, 34

`xmax` key, 255
`xmin` key, 255
`xparse` key, 10
`xshift` key, 149

`ymax` key, 255
`ymin` key, 255
`yshift` key, 149
`yshift*` key, 149
`yshifttext` key, 149