sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ **COOKBOOKS ↗**

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos`, `add_wordmarks`, `add_headshots`, `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"`, and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos add_wordmarks add_headshots axis_logos add_images title_image team_tiers`. Extra `mpl`; seaborn routes here.

`height`: share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform`: a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)`: `"logo" "wordmark" "headshot"`.

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image`: a team (with `league`) or an image URL or path; `side="left" "right"`; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team`, optionally `tier_rank`. Also `tier_desc`, `presort`, `no_line_below_tier`, `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default" "dark"` or one from `marks()`
`id_system`	`"auto"`; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant`.

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x y team`, optional `season`
`geom_sdv_headshots`	`x y player_id`
`geom_from_path`	`x y path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league height=0.1 alpha variant id_system`.

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)`, so add it after `labs`. `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv`: `which`, `season`, `na_value="grey"`, `alpha`. The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin`, `theme`, `mode`; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above" "below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart`; `logo_layer` is the layer itself (`chart_height`, `x_type`, `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height`, else the figure `height`. Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup`, "sdvplot logos", for a `LayerControl`.

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)`: a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy`.

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")`; extra keywords go to `ColumnDefinition`. `plottable_sdv_theme(name, mode=)`: `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()`, with the four verbs in `__all__`, a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py`.

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`

```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES


```
gt_theme_sdv_team(gt, "KC", league="nfl")
```




sdv



sdv · dark



kenpom



savant



broadsheet



midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)  # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color · paper · stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)  # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W / L / T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build **reactable** columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with **sportypy**, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: Social game-day graphics ↗

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl` `cfb` `ufl` `usfl` `xfl` `aaf` `nba` `wnba` `nbagl` `mbb` `wbb` `mlb` `milb` `ncaa_baseball` `ncaa_softball` `nhl` `ahl` `echl` `ohl` `qmjhl` `whl` `ushl` `pwhl` `phf` `ncaa_mhockey` `ncaa_whockey` `soccer`. 32 without teams, among them `cfl` `fiba` `iihf` `fifa` `epl` `mls` `nwsl` `nfhs_*`, lacrosse `nll` `pll` `world_lacrosse`, tennis `atp` `wta` `itf`, volleyball `fivb`, curling `wcf` `curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: Surfaces and shot charts ↗

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1, -1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: NFL · CFB · NBA · WNBA · MLB · NHL · PWHL · Soccer · Cricket

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), @sportsdataverse/sdvplot (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ COOKBOOKS ↗

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos` , `add_wordmarks` , `add_headshots` , `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"` , and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos` `add_wordmarks` `add_headshots` `axis_logos` `add_images` `title_image` `team_tiers` . Extra `mpl` ; seaborn routes here.

`height` : share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform` : a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)` : `"logo"` `"wordmark"` `"headshot"` .

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image` : a team (with `league`) or an image URL or path; `side="left"` `"right"` ; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team` , optionally `tier_rank` . Also `tier_desc` , `presort` , `no_line_below_tier` , `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default"` `"dark"` or one from `marks()`
`id_system`	`"auto"` ; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant` .

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x` `y` `team` , optional `season`
`geom_sdv_headshots`	`x` `y` `player_id`
`geom_from_path`	`x` `y` `path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league` `height=0.1` `alpha` `variant` `id_system` .

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)` , so add it after `labs` . `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv` : `which` , `season` , `na_value="grey"` , `alpha` . The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin` , `theme` , `mode` ; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above"` `"below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart` ; `logo_layer` is the layer itself (`chart_height` , `x_type` , `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height` , else the figure `height` . Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup` , "sdvplot logos", for a `LayerControl` .

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)` : a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy` .

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")` ; extra keywords go to `ColumnDefinition` . `plottable_sdv_theme(name, mode=)` : `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()` , with the four verbs in `__all__` , a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py` .

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES

```
gt_theme_sdv_team(gt, "KC", league="nfl")
```



sdv · sdv · dark · kenpom · savant · broadsheet · midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)   # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color · paper · stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)   # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W/L/T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build **reactable** columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with **sportypy**, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: **Social game-day graphics ↗**

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl` `cfb` `ufl` `usfl` `xfl` `aaf` `nba` `wnba` `nbagl` `mbb` `wbb` `mlb` `milb` `ncaa_baseball` `ncaa_softball` `nhl` `ahl` `echl` `ohl` `qmjhl` `whl` `ushl` `pwhl` `phf` `ncaa_mhockey` `ncaa_whockey` `soccer`. 32 without teams, among them `cfl` `fiba` `iihf` `fifa` `epl` `mls` `nwsl` `nfhs_*`, lacrosse `nll` `pll` `world_lacrosse`, tennis `atp` `wta` `itf`, volleyball `fivb`, curling `wcf` `curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: **Surfaces and shot charts ↗**

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1`, `-1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: **NFL** · **CFB** · **NBA** · **WNBA** · **MLB** · **NHL** · **PWHL** · **Soccer** · **Cricket**

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), **@sportsdataverse/sdvplot** (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ **COOKBOOKS ↗**

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos`, `add_wordmarks`, `add_headshots`, `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"`, and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos add_wordmarks add_headshots axis_logos add_images title_image team_tiers`. Extra `mpl`; seaborn routes here.

`height`: share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform`: a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)`: `"logo" "wordmark" "headshot"`.

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image`: a team (with `league`) or an image URL or path; `side="left" "right"`; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team`, optionally `tier_rank`. Also `tier_desc`, `presort`, `no_line_below_tier`, `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default" "dark"` or one from `marks()`
`id_system`	`"auto"`; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant`.

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x y team`, optional `season`
`geom_sdv_headshots`	`x y player_id`
`geom_from_path`	`x y path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league height=0.1 alpha variant id_system`.

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)`, so add it after `labs`. `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv`: `which`, `season`, `na_value="grey"`, `alpha`. The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin`, `theme`, `mode`; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above" "below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart`; `logo_layer` is the layer itself (`chart_height`, `x_type`, `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height`, else the figure `height`. Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup`, "sdvplot logos", for a `LayerControl`.

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)`: a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy`.

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")`; extra keywords go to `ColumnDefinition`. `plottable_sdv_theme(name, mode=)`: `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()`, with the four verbs in `__all__`, a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py`.

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES

```
gt_theme_sdv_team(gt, "KC", league="nfl")
```



sdv · sdv · dark · kenpom

savant · broadsheet · midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)  # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color` · `paper` · `stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)  # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W / L / T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build **reactable** columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with **sportypy**, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`, …; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: Social game-day graphics ↗

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl` `cfb` `ufl` `usfl` `xfl` `aaf` `nba` `wnba` `nbagl` `mbb` `wbb` `mlb` `milb` `ncaa_baseball` `ncaa_softball` `nhl` `ahl` `echl` `ohl` `qmjhl` `whl` `ushl` `pwhl` `phf` `ncaa_mhockey` `ncaa_whockey` `soccer`. 32 without teams, among them `cfl` `fiba` `iihf` `fifa` `epl` `mls` `nwsl` `nfhs_*`, lacrosse `nll` `pll` `world_lacrosse`, tennis `atp` `wta` `itf`, volleyball `fivb`, curling `wcf` `curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: Surfaces and shot charts ↗

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1, -1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: NFL · CFB · NBA · WNBA · MLB · NHL · PWHL · Soccer · Cricket

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), **@sportsdataverse/sdvplot** (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ COOKBOOKS ↗

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos` , `add_wordmarks` , `add_headshots` , `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"` , and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos` `add_wordmarks` `add_headshots` `axis_logos` `add_images` `title_image` `team_tiers` . Extra `mpl` ; seaborn routes here.

`height` : share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform` : a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)` : `"logo"` `"wordmark"` `"headshot"` .

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image` : a team (with `league`) or an image URL or path; `side="left"` `"right"` ; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team` , optionally `tier_rank` . Also `tier_desc` , `presort` , `no_line_below_tier` , `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default"` `"dark"` or one from `marks()`
`id_system`	`"auto"` ; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant` .

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x` `y` `team` , optional `season`
`geom_sdv_headshots`	`x` `y` `player_id`
`geom_from_path`	`x` `y` `path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league` `height=0.1` `alpha` `variant` `id_system` .

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)` , so add it after `labs` . `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv` : `which` , `season` , `na_value="grey"` , `alpha` . The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin` , `theme` , `mode` ; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above"` `"below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart` ; `logo_layer` is the layer itself (`chart_height` , `x_type` , `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height` , else the figure `height` . Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup` , "sdvplot logos", for a `LayerControl` .

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)` : a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy` .

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")` ; extra keywords go to `ColumnDefinition` . `plottable_sdv_theme(name, mode=)` : `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()` , with the four verbs in `__all__` , a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py` .

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES

```
gt_theme_sdv_team(gt, "KC", league="nfl")
```



sdv · sdv · dark · kenpom · savant · broadsheet · midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)   # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color · paper · stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)   # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W/L/T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build reactable columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with sportypy, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: Social game-day graphics ↗

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl cfb ufl usfl xfl aaf nba wnba nbagl mbb wbb mlb milb ncaa_baseball ncaa_softball nhl ahl echl ohl qmjhl whl ushl pwhl phf ncaa_mhockey ncaa_whockey soccer`. 32 without teams, among them `cfl fiba iihf fifa epl mls nwsl nfhs_*`, lacrosse `nll pll world_lacrosse`, tennis `atp wta itf`, volleyball `fivb`, curling `wcf curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: Surfaces and shot charts ↗

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1`, `-1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: NFL · CFB · NBA · WNBA · MLB · NHL · PWHL · Soccer · Cricket

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), @sportsdataverse/sdvplot (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ **COOKBOOKS ↗**

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: **Getting started ↗**

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: **Matplotlib logos ↗**

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: **Colours and themes ↗**

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: **Team identity ↗**

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: **Interactive web ↗**

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: **Seasons and eras ↗**

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: **Cache ↗**

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: **Errors ↗**

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos`, `add_wordmarks`, `add_headshots`, `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"`, and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos add_wordmarks add_headshots axis_logos add_images title_image team_tiers`. Extra `mpl`; seaborn routes here.

`height`: share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform`: a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)`: `"logo" "wordmark" "headshot"`.

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image`: a team (with `league`) or an image URL or path; `side="left" "right"`; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team`, optionally `tier_rank`. Also `tier_desc`, `presort`, `no_line_below_tier`, `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default" "dark"` or one from `marks()`
`id_system`	`"auto"`; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant`.

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x y team`, optional `season`
`geom_sdv_headshots`	`x y player_id`
`geom_from_path`	`x y path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league height=0.1 alpha variant id_system`.

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)`, so add it after `labs`. `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv`: `which`, `season`, `na_value="grey"`, `alpha`. The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin`, `theme`, `mode`; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above" "below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart`; `logo_layer` is the layer itself (`chart_height`, `x_type`, `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height`, else the figure `height`. Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup`, "sdvplot logos", for a `LayerControl`.

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)`: a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy`.

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")`; extra keywords go to `ColumnDefinition`. `plottable_sdv_theme(name, mode=)`: `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()`, with the four verbs in `__all__`, a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py`.

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES

```
gt_theme_sdv_team(gt, "KC", league="nfl")
```



sdv · sdv · dark · kenpom · savant · broadsheet · midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)  # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color` · `paper` · `stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)  # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W / L / T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build **reactable** columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with **sportypy**, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

`sdvplot v0.2.0`

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: **Social game-day graphics ↗**

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl` `cfb` `ufl` `usfl` `xfl` `aaf` `nba` `wnba` `nbagl` `mbb` `wbb` `mlb` `milb` `ncaa_baseball` `ncaa_softball` `nhl` `ahl` `echl` `ohl` `qmjhl` `whl` `ushl` `pwhl` `phf` `ncaa_mhockey` `ncaa_whockey` `soccer`. 32 without teams, among them `cfl` `fiba` `iihf` `fifa` `epl` `mls` `nwsl` `nfhs_*`, lacrosse `nll` `pll` `world_lacrosse`, tennis `atp` `wta` `itf`, volleyball `fivb`, curling `wcf` `curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: **Surfaces and shot charts ↗**

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1, -1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: **NFL** · **CFB** · **NBA** · **WNBA** · **MLB** · **NHL** · **PWHL** · **Soccer** · **Cricket**

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), **@sportsdataverse/sdvplot** (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ COOKBOOKS ↗

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS


```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos` , `add_wordmarks` , `add_headshots` , `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"` , and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos` `add_wordmarks` `add_headshots` `axis_logos` `add_images` `title_image` `team_tiers` . Extra `mpl` ; seaborn routes here.

`height` : share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform` : a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)` : `"logo"` `"wordmark"` `"headshot"` .

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image` : a team (with `league`) or an image URL or path; `side="left"` `"right"` ; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team` , optionally `tier_rank` . Also `tier_desc` , `presort` , `no_line_below_tier` , `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default"` `"dark"` or one from `marks()`
`id_system`	`"auto"` ; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant` .

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x` `y` `team` , optional `season`
`geom_sdv_headshots`	`x` `y` `player_id`
`geom_from_path`	`x` `y` `path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league` `height=0.1` `alpha` `variant` `id_system` .

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)` , so add it after `labs` . `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv` : `which` , `season` , `na_value="grey"` , `alpha` . The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin` , `theme` , `mode` ; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above"` `"below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart` ; `logo_layer` is the layer itself (`chart_height` , `x_type` , `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height` , else the figure `height` . Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup` , "sdvplot logos", for a `LayerControl` .

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)` : a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy` .

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")` ; extra keywords go to `ColumnDefinition` . `plottable_sdv_theme(name, mode=)` : `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()` , with the four verbs in `__all__` , a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py` .

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES


```
gt_theme_sdv_team(gt, "KC", league="nfl")
```




sdv




sdv · dark



kenpom



savant



broadsheet



midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)   # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color · paper · stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)   # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W/L/T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build **reactable** columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with **sportypy**, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: Social game-day graphics ↗

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl` `cfb` `ufl` `usfl` `xfl` `aaf` `nba` `wnba` `nbagl` `mbb` `wbb` `mlb` `milb` `ncaa_baseball` `ncaa_softball` `nhl` `ahl` `echl` `ohl` `qmjhl` `whl` `ushl` `pwhl` `phf` `ncaa_mhockey` `ncaa_whockey` `soccer`. 32 without teams, among them `cfl` `fiba` `iihf` `fifa` `epl` `mls` `nwsl` `nfhs_*`, lacrosse `nll` `pll` `world_lacrosse`, tennis `atp` `wta` `itf`, volleyball `fivb`, curling `wcf` `curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: Surfaces and shot charts ↗

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1`, `-1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: NFL · CFB · NBA · WNBA · MLB · NHL · PWHL · Soccer · Cricket

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), **@sportsdataverse/sdvplot** (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ **COOKBOOKS ↗**

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos`, `add_wordmarks`, `add_headshots`, `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"`, and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos add_wordmarks add_headshots axis_logos add_images title_image team_tiers`. Extra `mpl`; seaborn routes here.

`height`: share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform`: a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)`: `"logo" "wordmark" "headshot"`.

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image`: a team (with `league`) or an image URL or path; `side="left" "right"`; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team`, optionally `tier_rank`. Also `tier_desc`, `presort`, `no_line_below_tier`, `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default" "dark"` or one from `marks()`
`id_system`	`"auto"`; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant`.

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x y team`, optional `season`
`geom_sdv_headshots`	`x y player_id`
`geom_from_path`	`x y path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league height=0.1 alpha variant id_system`.

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)`, so add it after `labs`. `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv`: `which`, `season`, `na_value="grey"`, `alpha`. The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin`, `theme`, `mode`; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above" "below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart`; `logo_layer` is the layer itself (`chart_height`, `x_type`, `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height`, else the figure `height`. Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup`, "sdvplot logos", for a `LayerControl`.

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)`: a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy`.

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")`; extra keywords go to `ColumnDefinition`. `plottable_sdv_theme(name, mode=)`: `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()`, with the four verbs in `__all__`, a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py`.

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES

```
gt_theme_sdv_team(gt, "KC", league="nfl")
```



sdv · sdv · dark · kenpom · savant · broadsheet · midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)   # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color` · `paper` · `stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)   # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W/L/T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build **reactable** columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with **sportypy**, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: Social game-day graphics ↗

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`. reactablefmtr ports, `reactable_sdv_*`: `data_bars color_tiles color_scales pill_buttons bubble_grid icon_sets icon_trend icon_assign highlight merge_column gauge sparkline sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl cfb ufl usfl xfl aaf nba wnba nbagl mbb wbb mlb milb ncaa_baseball ncaa_softball nhl ahl echl ohl qmjhl whl ushl pwhl phf ncaa_mhockey ncaa_whockey soccer`. 32 without teams, among them `cfl fiba iihf fifa epl mls nwsl nfhs_*`, lacrosse `nll pll world_lacrosse`, tennis `atp wta itf`, volleyball `fivb`, curling `wcf curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: Surfaces and shot charts ↗

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1, -1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout statsbomb uefa impect espn`; tracking `tracab skillcorner secondspectrum metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: NFL · CFB · NBA · WNBA · MLB · NHL · PWHL · Soccer · Cricket

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` & co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), **@sportsdataverse/sdvplot** (npm)

sdvplot :: CHEAT SHEET

Team logos, wordmarks, player headshots and team colours for Python, across **28 leagues** (pro, college, minor-league and junior). One front door, `add_logos()`, draws on **matplotlib** (and seaborn), **plotnine**, **plotly**, **altair**, **bokeh**, **holoviews**, **folium** and **pygal**. Resolves abbreviations, names and 19 provider id systems, and picks the right era's mark for a season. The Python counterpart to sdvplotR. Page 1: identity, colours, the front door. Page 2: every adapter, pydeck, Perspective. Page 3: great_tables and 122 table themes. Page 4: layout, export, reactable, 59 playing surfaces.

sdvplot v0.2.0

Python ≥ 3.10 · polars 1.24+ or 2 · extras per library

GALLERY ↗ COOKBOOKS ↗

FRONT DOOR · ANY LIBRARY

INSTALL & IMPORT

```
pip install sdvplot   # or: uv add sdvplot
pip install "sdvplot[mpl,tables]"
import sdvplot
```

Extras, one per library: `mpl plotnine plotly altair bokeh holoviews tables reactable folium pygal plottable itables pydeck perspective surfaces svg`, or `all`.

Every call takes `league`: `"nfl" "nba" "wnba" "mlb" "nhl" "cfb" "mbb" "wbb" "soccer"` and 19 more (Coverage, col 3).

Cookbook: Getting started ↗

LOGOS, WORDMARKS & HEADSHOTS

Function	Draws
`add_logos(target, x, y, teams)`	team logos at points
`add_wordmarks()`	wordmarks (NFL, MLB, MiLB, PHF)
`add_headshots(.., players)`	player photos
`axis_logos(target, "x")`	logos as tick labels

The front door picks the adapter from `target` (an Axes, a `ggplot`, a Plotly figure, …). Keywords: `league` (required), `height` (share of the axis), `alpha`, `season`, `variant`, `id_system`.

```
import matplotlib.pyplot as plt
seeds = ["KC", "BUF", "BAL", "HOU",
         "LAC", "PIT", "DEN"]
x = list(range(1, 8))
fig, ax = plt.subplots(figsize=(8, 1.6))
sdvplot.add_logos(ax, x, [0] * 7, seeds,
                  league="nfl", height=0.7)
ax.set(xlim=(0.5, 7.5), ylim=(-1, 1))
```

Cookbook: Matplotlib logos ↗

SAME CALL, OTHER LIBRARIES

```
import plotly.graph_objects as go
fig = go.Figure(go.Bar(x=seeds, y=x))
sdvplot.axis_logos(fig, "x", league="nfl")
```

plotnine, Altair and tables return a new object: keep it.

HEADSHOTS

```
sdvplot.headshot_url("3139477", "nfl")
```

`id_system="espn"` (default, every league), `"gsis"` (NFL, via nflverse) or `"league"` (NFL gsis, NBA / WNBA Stats, MLBAM, NHL ids). An unknown id gets the CDN's silhouette.

TEAM COLOURS

```
sdvplot.palette("nfl", teams=["LV", "KC"])
#> {'LV': '#000000', 'KC': '#e31837'}
sdvplot.team_colors("nba", df["team"],
                    which="secondary")
```

`palette()` is a `{team: colour}` dict any library takes (seaborn `palette=`); `team_colors()` returns one colour per value (a str, list or Series, like its input; None for a miss). Both take `which="primary" "secondary"`, `season`, `id_system`, `strict`. Without `teams`, `palette` covers the whole league.



Cookbook: Colours and themes ↗

TEAM IDENTITY & MARKS

Function	Returns
`resolve(values, league)`	team ids from abbrs, names, provider ids
`suggest(value, league, n=5)`	closest `(team_id, name)` matches
`teams(league=None)`	polars index: `abbr name conference color_primary color_source`, …
`logo_url()`	a mark's URL; `variant`, `mark_type="logo" "wordmark"`
`logo_image()`	a PIL image; `size`
`marks()`	every archived mark: `variant mark_type archive_url`
`headshot_url()`	player photo URL

```
sdvplot.resolve(
  ["LV", "OAK", "Las Vegas Raiders"], "nfl")
#> ['13', '13', '13']
sdvplot.suggest("Golden St", "nba")
#> [('9', 'Golden State Warriors')]
sdvplot.teams("nfl", include_conferences=True)
```

`include_conferences` adds college conferences and AFC / NFC / NFL rows. `teams()` with no league is every league.

Concepts: Team identity ↗

WHICH ADAPTER RUNS

The target's library picks it: a matplotlib Axes or seaborn, a plotnine `ggplot`, a great_tables `GT` (`add_logos(gt, "team", league=)` is `gt_sdv_logos`), a Plotly, Altair, Bokeh, HoloViews, folium or pygal object. Any other raises `UnsupportedTargetError`; a missing extra, `OptionalDependencyError`.

`axis_logos` needs axes: matplotlib, seaborn, plotnine, Plotly, Altair. Elsewhere it raises `TypeError`. Page 2 has every module.

Cookbook: Interactive web ↗

ID SYSTEMS

`id_system="auto"` (the default) tries `team_id espn espn_abbr nhl nflverse mlbstats nba_api hockeytech ncaa pff cricinfo cfbd bref sportsipy fangraphs sdvplotr name` in order; pass one to pin it, or `"nhl_id"` for NHL stats ids, which `"auto"` never tries.

`strict=True` (resolve, colours, URLs, tables) raises `UnresolvedTeamError` on a miss. A plot skips an unknown team with one `SdvplotWarning`.

SEASONS & VARIANTS

```
# the Oakland-era mark
sdvplot.logo_url("OAK", "nfl", season=2010)
sdvplot.logo_url("LV", "nfl", variant="dark")
sdvplot.marks("LV", "nfl")  # every variant
```

`season=` works everywhere and picks the mark in use that year (15 leagues are season-dated). `variant="default" "dark"` always work; the archive adds `scoreboard`, `grayscale`, `on_light`, … (the error lists a league's set).

Concepts: Seasons and eras ↗

COVERAGE

League	Teams
nfl nba wnba mlb nhl	32 / 30 / 15 / 30 / 32
cfb mbb wbb	687 / 366 / 364
soccer · cricket	2,631 · 111
ahl echl ohl qmjhl whl ushl pwhl phf	hockey minors & juniors
milb ncaa_baseball ncaa_softball	286 / 414 / 415
ncaa_mhockey ncaa_whockey nbagl ufl usfl xfl aaf	110 / 48 / 32 / 11 / 9 / 11 / 8

Wordmarks: NFL, MLB, MiLB, PHF. Headshots: ESPN ids in every league.

CACHE & VERSIONS

```
sdvplot.versions()
#> keys: sdvplot, index,
#>   manifest_last_modified
sdvplot.clear_cache()
```

The team index ships inside the package, so `resolve`, `palette` and `teams` never touch the network. Logos, the manifest and headshots download once and are cached. `SDVPLOT_CACHE_DIR` moves the cache; after `SDVPLOT_CACHE_TTL` days (default 7) the manifest is rechecked.

Concepts: Cache ↗

ERRORS & WARNINGS

Class	When
`SdvplotError`	base of every error below
`InputError`	a bad argument (a `ValueError`)
`UnresolvedTeamError`	a miss under `strict=True`
`OfflineError`	not cached, not downloadable
`DownloadError` · `IntegrityError`	CDN error status · sha256 mismatch
`OptionalDependencyError`	the extra is missing
`UnsupportedTargetError`	no adapter for the target
`UnsafeDownloadError`	over the byte cap, past the deadline, or off https
`UnsafeCachePathError`	a file would land outside the cache

Warnings: `SdvplotWarning`, `SdvplotDeprecationWarning`.

Reference: Errors ↗

TYPE HINTS

```
from sdvplot.typing import (
    IdSystem, HeadshotIdSystem, Which,
    MarkType, AxisMarkType)
```

`Literal`s for `id_system`, `which`, `mark_type`; ships `py.typed`.

COLOURS ANYWHERE

```
import seaborn as sns
sns.barplot(df, x="team", y="wins",
            hue="team",
            palette=sdvplot.palette("nfl"))
```

plotnine: `scale_color_sdv("nfl")`; pygal: `team_style()`; tables: `gt_theme_sdv_team`, `reactable_sdv_team_color_bg`; pydeck and Perspective: page 2.

sdvplot :: ADAPTERS

One module per plotting library, each with the same four verbs (`add_logos` , `add_wordmarks` , `add_headshots` , `axis_logos`) plus whatever that library needs. The front door on page 1 calls these for you; import a module directly for its extras or to skip the dispatch. Each needs its extra: `pip install "sdvplot[plotly]"` , and so on. Every web adapter takes `embed=True` to inline images as data URIs, for offline HTML and static export.

sdvplot v0.2.0

9 plot libraries · pydeck · Perspective

GALLERY ↗ COOKBOOKS ↗

ADAPTERS · ONE PER LIBRARY

SDVPLOT.MATPLOTLIB

`add_logos` `add_wordmarks` `add_headshots` `axis_logos` `add_images` `title_image` `team_tiers` . Extra `mpl` ; seaborn routes here.

`height` : share of the Axes height, in (0, 1], default 0.1. `zorder=3` draws above lines and markers. `transform` : a Cartopy CRS such as `ccrs.PlateCarree()` (required on a GeoAxes) or a matplotlib Transform.

```
from sdvplot.matplotlib import add_images
add_images(ax, [1, 2], [0, 0],
           ["a.png", "b.png"], height=0.2)
```

`add_images` takes local paths, `file://` URIs or https URLs (http is refused). `axis_logos(ax, "y", mark_type=)` : `"logo"` `"wordmark"` `"headshot"` .

Reference: sdvplot.matplotlib ↗

TITLES & TIERS

```
from sdvplot.matplotlib import (
    title_image, team_tiers)
title_image(ax, "KC", "Chiefs offense",
            league="nfl", height=28)
team_tiers(tiers, "nba", title="Tiers",
           theme="light")
```

`title_image` : a team (with `league`) or an image URL or path; `side="left"` `"right"` ; `height` in points.

`team_tiers` returns a Figure. `tiers` has `tier_no` (1 is top) and `team` , optionally `tier_rank` . Also `tier_desc` , `presort` , `no_line_below_tier` , `devel=True` (text, no downloads), `variant="auto"` (dark marks on the dark theme).

Recipe: College hoops tiers ↗

SHARED KEYWORDS

Keyword	Meaning
`league`	required, keyword only
`height=0.1`	share of the plot height
`alpha=1`	opacity, 0 to 1
`season`	the mark in use that year
`variant`	`"default"` `"dark"` or one from `marks()`
`id_system`	`"auto"` ; headshots `"espn"`
`embed=False`	web adapters: inline the images

`add_headshots` has no `season` or `variant` .

SDVPLOT.PLOTNINE

Layer	Aesthetics
`geom_sdv_logos` `geom_sdv_wordmarks`	`x` `y` `team` , optional `season`
`geom_sdv_headshots`	`x` `y` `player_id`
`geom_from_path`	`x` `y` `path` (any image)
`geom_mean_lines` `geom_median_lines`	`x0` and / or `y0`

Geom parameters: `league` `height=0.1` `alpha` `variant` `id_system` .

```
from plotnine import aes, ggplot
from sdvplot.plotnine import (
    geom_sdv_logos, geom_mean_lines)
(ggplot(df, aes("epa", "sr", team="team"))
 + geom_mean_lines(aes(x0="epa", y0="sr"))
 + geom_sdv_logos(league="nfl",
                  height=0.12))
```

`title_image("KC", "Chiefs", league="nfl")` is added with `+` and replaces `labs(title=)` , so add it after `labs` . `team_tiers(data, league)` returns a ggplot.

TEAM COLOUR SCALES

```
from plotnine import geom_point
from sdvplot.plotnine import scale_color_sdv
(ggplot(df, aes("epa", "sr", color="team"))
 + geom_point() + scale_color_sdv("nfl"))
```

`scale_color_sdv` (alias `scale_colour_sdv`), `scale_fill_sdv` : `which` , `season` , `na_value="grey"` , `alpha` . The plotnine module also has the four front-door verbs.

Cookbook: plotnine ↗

LOGOS ON AN AXIS

```
sdvplot.axis_logos(ax, "x", league="nfl")
sdvplot.axis_logos(ax, "y", league="nba",
                   mark_type="headshot")
```

The tick labels must be teams (player ids for `"headshot"`); labels that are not stay as text, with one warning.

SDVPLOT.PERSPECTIVE

```
from sdvplot.perspective import (
    perspective_sdv_config)
cfg = perspective_sdv_config(df,
    team_col="team", league="nfl")
PerspectiveWidget(data, **cfg)
```

Team-coloured cells or series; `plugin` , `theme` , `mode` ; `perspective_logo_column()` adds logos. Python ≥ 3.11. Cookbook ↗

SDVPLOT.PLOTLY

```
import sdvplot.plotly as sp
sp.add_logos(fig, x, y, teams,
             league="nfl", xref="x2",
             yref="y2", layer="below",
             embed=True)
```

Layout images: `xref` / `yref` pick a subplot's axes, `layer="above"` `"below"` the traces. sdvplot pins the axis ranges so each image is exactly `height` of the plot. `embed=True` also makes kaleido export work.

SDVPLOT.ALTAIR

```
import altair as alt
import sdvplot.altair as salt
pts = alt.Chart(df).mark_point().encode(
    x="epa", y="sr")
alt.layer(pts, salt.logo_layer(
    df["epa"], df["sr"], df["team"],
    league="nfl", height=0.12))
```

`add_logos(chart, …)` returns a new `LayerChart` ; `logo_layer` is the layer itself (`chart_height` , `x_type` , `y_type`). `embed=True` for vl-convert PNGs.

SDVPLOT.BOKEH

```
from bokeh.plotting import figure
p = figure(frame_width=400,
           frame_height=300)
sdvplot.add_logos(p, x, y, teams,
                  league="nfl", height=0.15)
```

One `image_url` glyph per call, sized in screen pixels (logos keep their size on zoom): `height` × `frame_height` , else the figure `height` . Factor and datetime axes work.

SDVPLOT.HOLOVIEWS

```
hv.extension("bokeh")
pts = sdvplot.add_logos(hv.Scatter(df),
    x, y, teams, league="nfl")
```

A Bokeh plot hook (Bokeh backend only); teams resolve, and warn, at the call.

SDVPLOT.PYDECK

```
import sdvplot.pydeck as sdeck
sdeck.deck(
  sdeck.surface_layer("hockey", "nhl"),
  sdeck.logo_icon_layer(shots, x="x",
    y="y", team="team", league="nhl"))
```

Layer props are dicts (`pydeck.Layer(**props)`); `pass_arc_layer` draws team-colour arcs; `surface_layer` all ten sportypy sports. Cookbook ↗

SDVPLOT.FOLIUM

```
import folium
m = folium.Map(location=[39, -95],
               zoom_start=4, height=600)
sdvplot.add_logos(m, [-94.48, -78.79],
    [39.05, 42.77], ["KC", "BUF"],
    league="nfl", height=0.06)
```

`x` is longitude, `y` latitude; `height` is a share of the map's pixel height. Markers go in one `FeatureGroup` , "sdvplot logos", for a `LayerControl` .

SDVPLOT.PYGAL

```
import pygal
import sdvplot.pygal as spg
chart = pygal.Bar(style=spg.team_style(
    ["KC", "BUF"], league="nfl"))
```

`team_style(teams, league=, which=)` : a pygal `Style` in the teams' colours, one per series. `add_*` draw on XY charts at render time; copy a chart with `copy.deepcopy` .

SDVPLOT.PLOTTABLE

```
from plottable import Table
from sdvplot.plottable import logo_column
Table(df, column_definitions=[
    logo_column("team", league="nfl",
                title="")])
```

Also `headshot_column(name, league=, id_system="espn")` ; extra keywords go to `ColumnDefinition` . `plottable_sdv_theme(name, mode=)` : `Table` keywords for any of 122 table themes.

WHAT ADD_* RETURNS

Returns	Libraries
the target, drawn on	matplotlib, Plotly, Bokeh, folium, pygal
a new object; the target is unchanged	plotnine (`ggplot`), Altair (`LayerChart`), HoloViews (a copy), great_tables (`GT`)

SDVPLOT.TESTING

`check_adapter_contract(adapter, make_target)` and `check_table_adapter_contract(adapter, make_table)` raise an `AssertionError` naming the broken rule.

A new adapter: a module named after the library, importing it inside `requires_extra()` , with the four verbs in `__all__` , a `_drawn_marks(target)` test hook, and one `register_adapter(…)` line in `_dispatch.py` .

Adapters: Add an adapter ↗ · contract ↗

sdvplot :: TABLES

sdvplot.great_tables ports sdvplotR's table toolkit (gtUtils, by Andrew Weatherman) to **great_tables**, under the same names: team images, 20 themes plus 122 source-named ones, legends, colouring, annotations, layouts and image export. Each helper takes a `GT` first and returns a new one, so they chain with `GT.pipe`. Needs `sdvplot[tables]`. Page 4: layout, saving images, reactable.

sdvplot v0.2.0

great_tables ≥ 1.0 · nokap to save

GALLERY ↗ COOKBOOKS ↗

GREAT_TABLES · IMAGES, THEMES

TEAM IMAGES IN CELLS

Function	Does · key arguments
`gt_sdv_logos(gt, columns, league=)`	team keys → logos; `height=30` (px), `include_name`, `season`, `locations`
`gt_sdv_wordmarks()`	keys → wordmarks; `height`, `season`
`gt_sdv_headshots()`	player ids → photos; `id_system="espn"`
`gt_sdv_cols_label()`	column *names* → images; `mark_type="logo" "wordmark" "headshot"`
`gt_merge_stack_team_color(gt, col1, col2, team_col)`	stack two columns, the lower in team colour; `font_size_top=14`, `font_size_bottom=12`


```
from great_tables import GT
from sdvplot.great_tables import (
    gt_sdv_logos, gt_theme_sdv)
(GT(df)
 .pipe(gt_sdv_logos, "team",
       league="nfl", height=28)
 .pipe(gt_theme_sdv))
```

Values resolve like `resolve()`; `strict=True` raises on a miss.

Cookbook: Tables ↗

THEMES

```
gt_theme_sdv_team(gt, "KC", league="nfl")
```



sdv · sdv · dark · kenpom · savant · broadsheet · midnight

SOURCE-NAMED THEMES

```
gt_theme_source(gt, "datagolf", mode="dark")
gt_theme_economist(gt)   # a shortcut
```

122 themes after sports, news and data sites (98 with dark): `sdv_table_themes()`; 20 have shortcuts. Also reactable, plottable, itables. Concepts ↗

THEME OPTIONS

Each is `gt_theme_<name>()`: `almanac athletic booktabs broadsheet brutalist drench gtutils kenpom midnight ncaa pl savant scoreboard sofa swiss terminal tier tufte`, plus `sdv` and `sdv_team`.

Argument	Themes
`density="comfortable" "compact" "social"`	all
`accent`	almanac booktabs broadsheet brutalist midnight scoreboard swiss terminal tufte
`style="light" "dark"`	sdv, sofa, tier
`color · paper · stripe`	drench · broadsheet · almanac

Extra keywords go to great_tables' `tab_options`.

Cookbook: Colours and themes ↗

PREVIEW & PALETTES

```
gt_theme_preview(df)   # {name: GT}
gt_theme_preview(df, ["kenpom", "pl"], n=8)
gt_color_ranks(gt, "wins",
               palette=pal_midnight)
```

`gt_theme_preview(data, themes=None, n=5)`: the first `n` rows in each theme. `pal_midnight`: a rank palette that reads on `midnight` / `terminal`.

COLOUR BY VALUE

Function	Does · key arguments
`gt_color_ranks()`	fill cells on a palette; `palette`, `domain`, `reverse`, `rows`
`gt_color_pills()`	value in a coloured pill; `digits`, `format_type`, `suffix`
`gt_percentile_bar()`	bar + marker; `domain=(0, 100)`, `decimals`
`gt_color_results()`	W/L/T rows; `result_column`, `win_color`, `loss_color`
`gt_row_accent(gt, column)`	bar on each row's edge; `palette`, `side="left"`
`gt_indicator_boxes()`	0/1 as boxes; `indicator_vals`, `color_yes`
`gt_tiers(gt, levels)`	colour a tier column; `colors`, `tier_column="tier"`

LEGENDS

```
(GT(df)
 .pipe(gt_color_ranks, "wins")
 .pipe(gt_legend_continuous,
       title="Wins", type="steps"))
```

Function	Does · key arguments
`gt_legend_continuous()`	colour bar; `type="continuous" "steps" "blocks"`, `n_bins=5`, `location="bottom"`
`gt_legend_discrete(gt, key_info)`	`{label: colour}` key (default: `gt_tiers`'s); `heading`, `shape`

The legend reads the columns, palette and domain the colouring step recorded.

HIGHLIGHT & FOCUS

Function	Does · key arguments
`gt_highlight_cells(gt, columns, condition)`	fill where `condition`, e.g. `lambda s: s > 0.7`; `fill`, `bold`
`gt_highlight_na()`	style missing values; `missing_text`, `na_strings`
`gt_outliers()`	`method="iqr" "sd" "bounds"`, `threshold`, `side`, `note`
`gt_spotlight(gt, rows)`	emphasise rows, dim the rest; `accent_color`
`gt_bold_rows(gt, rows)`	bold rows; `highlight_color`
`gt_group_stripes()`	band alternate row groups; `color`, `start=2`

```
(GT(df)
 .pipe(gt_highlight_cells, "wins",
       lambda s: s >= 12, bold=True)
 .pipe(gt_spotlight, [0, 1]))
```

`rows`: 0-based positions, a polars expression, or a function of the frame.

BORDERS & RULES

Function	Does · key arguments
`gt_border_grid()`	full grid; `color`, `weight=1`
`gt_border_bars_top(gt, colors)` / `_bottom`	colour bars; `bar_height=10`, `img`, `text`
`gt_cutline(gt, after)`	a line after row `after`; `label`, `style="dashed"`

FORMAT

Function	Does · key arguments
`gt_delta(gt, from_, to)`	a change column; `percent`, `arrows`, `after`
`gt_fmt_rank()`	1 → 1st; `superscript=True`
`gt_fmt_tally()`	W-L(-T) in one cell; `separator`, `share`
`gt_significance(gt, columns, p_columns)`	stars; `levels=(0.01, 0.05, 0.1)`, `hide_p`
`gt_scale_note()`	divide and say so; `divisor=1000`
`gt_wrap_labels()`	break labels; `width=12`
`gt_set_font(gt, font_family)`	`from_google_font=True`

```
(GT(df)
 .pipe(gt_fmt_tally, ["wins", "losses"])
 .pipe(gt_delta, "last_wins", "wins"))
```

HEADERS & ANNOTATIONS

Function	Does · key arguments
`gt_title_header(gt, title)`	`kicker`, `subtitle`, `date`, `*_style`
`gt_column_subheaders()`	`col={"heading": .., "subtitle": ..}`
`gt_538_caption()`	`top_caption`, `bottom_caption`
`gt_marginalia(gt, columns)`	a column as margin notes; `width=220`
`gt_social_tag(gt, accounts)`	handles with icons; `stack`, `caption`
`gt_watermark()`	`text` or `image`; `opacity=0.06`, `angle`

```
(GT(df)
 .pipe(gt_title_header, "NFC North",
       kicker="2025 SEASON",
       subtitle="Final standings")
 .pipe(gt_cutline, 1, label="Champion")
 .pipe(gt_social_tag,
       {"x": "@SportsDataverse"}))
```

Recipe: CFB conference table ↗

TIPS & FROM R

`columns` takes a name, a list or a polars selector. Apply a theme before cell fills.

From R: the same names and arguments; `from` is `from_`. `gt_theme_preview` returns a dict; paletteer names in `gt_legend_continuous` are not ported.

sdvplot :: LAYOUT, EXPORT & SURFACES

Put several great_tables side by side and save them as trimmed PNGs for social posts; build reactable columns of logos, headshots and team-coloured bars; and draw a league's field, court, rink or pitch in a team's colours with sportypy, then move provider shot and event coordinates onto it. Ends with sportsdataverse-py data, the sdvplotR name map and where to read more.

sdvplot v0.2.0

[tables] · [reactable] · [surfaces]: sportypy ≥ 1.2

GALLERY ↗ COOKBOOKS ↗

TABLES · LAYOUT & EXPORT

LAYOUT

Function	Does · key arguments
`gt_grid(tables)`	tables in a grid under one title; `ncol=2`, `labels`, `gap=24`
`gt_stack_tables(tables)`	one above another; `gap=16`, `align`
`gt_snake(gt)`	long table in side-by-side blocks; `n_cols=2`, `rows_per_col`
`gt_snake_align(x)`	reshape a parallel frame to match

```
gt_grid([afc, nfc], ncol=2,
        title="2025 standings")
gt_grid(gt_theme_preview(df), ncol=3)
GT(nba).pipe(gt_snake, n_cols=3)
```

`tables`: a list of `GT`, or a dict (its values, in order). Both also take `subtitle`, `caption`, `source_note` and `file=`: `None` returns the HTML, a path writes an image. Style with `title_style`, `subtitle_style`, `caption_style` dicts.

SAVE AS AN IMAGE

Function	Does · key arguments
`gt_save_crop(gt, file)`	PNG, trimmed, padded; `whitespace=50`, `bg`, `zoom=2`, `width`
`gt_social_crop(gt, file)`	pad to `aspect_ratio="1:1"`, `"4:5"`,…; `gravity`
`gt_save_batch(data, group, fn, file, dir=)`	one image per group, `match_width=True`

```
gt_save_crop(tbl, "table.png",
             whitespace=40)
gt_social_crop(tbl, "post.png",
               aspect_ratio="4:5")
gt_save_batch(nfl, "conference", build,
              "nfl-{group}.png", dir="out")
```

`build(df, value)` returns a `GT`; `{group}` becomes the slugged value; it returns the files written. Saving runs headless Chrome through `nokap`, trimmed with Pillow. `file=None` returns the PIL image.

Automation: Social game-day graphics ↗

REACTABLE COLUMNS

Function	Returns · key arguments
`reactable_sdv_logos(league=)`	a `Column`; `height=30`, `include_name`, `season`, `default_img`
`reactable_sdv_wordmarks(league=)`	a `Column`; as logos
`reactable_sdv_headshots(league=)`	a `Column`; `height=40`, `id_system="espn"`
`reactable_sdv_cols_label(data, league=)`	a *list* of Columns, marks as headers; `mark_type`
`reactable_sdv_team_color_bar(data, team_col, league=)`	a bar in team colour; `which`, `max_value`
`reactable_sdv_team_color_bg(data, team_col, league=)`	a team-colour cell fill; `alpha=0.15`

```
from reactable import Reactable
from sdvplot.reactable import (
    reactable_sdv_logos,
    reactable_sdv_team_color_bar)
Reactable(df, columns=[
  reactable_sdv_logos(league="nba",
                      id="team"),
  reactable_sdv_team_color_bar(df, "team",
    league="nba", id="wins")])
```

Other keywords (`id`, `name`, …) go to `reactable.Column`.

reactablefmtr ports, `reactable_sdv_*`: `data_bars` `color_tiles` `color_scales` `pill_buttons` `bubble_grid` `icon_sets` `icon_trend` `icon_assign` `highlight` `merge_column` `gauge` `sparkline` `sparkbar`, most in team colours (`team_col=`); `_frame()` adds title, legend, source; `_theme(name)` takes 27 reactablefmtr and 122 registry themes. Cookbook ↗

PLAYING SURFACES

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
sdvplot.surface("nba", "BOS", ax=ax,
                center_logo=True)
ax.scatter(shots["court_x"],
           shots["court_y"])
```

`surface(league, team=None, *, season, ax, center_logo)` draws sportypy's field, court, rink or pitch in a team's colours and returns the Axes. `center_logo=True` is 0.25 of the Axes height, or pass a fraction.

SURFACE LEAGUES & OPTIONS

```
sdvplot.surface("nhl", "BOS",
                center_logo=0.3)
sdvplot.surface("nfl", "KC", season=2010)
```

59 keys, ten sports. 27 team leagues (colours, `center_logo`): `nfl` `cfb` `ufl` `usfl` `xfl` `aaf` `nba` `wnba` `nbagl` `mbb` `wbb` `mlb` `milb` `ncaa_baseball` `ncaa_softball` `nhl` `ahl` `echl` `ohl` `qmjhl` `whl` `ushl` `pwhl` `phf` `ncaa_mhockey` `ncaa_whockey` `soccer`. 32 without teams, among them `cfl` `fiba` `iihf` `fifa` `epl` `mls` `nwsl` `nfhs_*`, lacrosse `nll` `pll` `world_lacrosse`, tennis `atp` `wta` `itf`, volleyball `fivb`, curling `wcf` `curling_canada`.

PWHL draws its own rink; on a diamond the logo sits in shallow centre field.

sportypy keywords pass through: `display_range`, `xlim`, `ylim`, `rotation` to `draw()`; `field_updates`, `color_updates`, `units`, … to the surface. `surface("nba", display_range="defense")` is a half court.

Cookbook: Surfaces and shot charts ↗

COURT COORDINATES

```
# stats.nba.com legacy frame -> feet
shots = sdvplot.court_coords(shots)
# Euroleague (cm) -> FIBA court (m)
pts = sdvplot.court_coords(pts,
    x="coord_x", y="coord_y",
    provider="euroleague")
```

Adds `court_x`, `court_y` (Float64) on sportypy's centre-court frame; returns the frame's own type (pandas or polars). Reads `x_legacy` / `y_legacy` (`LOC_X` / `LOC_Y`) by default. ESPN `coordinate_x` / `_y` are already in feet: don't convert them. Euroleague free throws (`-1`, `-1`) become null.

PITCH COORDINATES

```
# soccer events -> 105 x 68 m pitch
ev = sdvplot.pitch_coords(ev,
    provider="statsbomb")
fig, ax = plt.subplots()
sdvplot.surface("soccer", ax=ax)
ax.scatter(ev["pitch_x"], ev["pitch_y"])
```

Adds `pitch_x`, `pitch_y` in metres from the centre spot, attacking +x. Providers: `opta` (`statsperform`) `wyscout` `statsbomb` `uefa` `impect` `espn`; tracking `tracab` `skillcorner` `secondspectrum` `metrica` also need `pitch_length`, `pitch_width`. `flip`: True, or a boolean column, turns rows half a turn. ESPN reads `field_position_x` / `_y`, as sportsdataverse-py's `espn_soccer_game_plays` returns them; its `(0, 0)` becomes null.

WITH SPORTSDATAVERSE DATA

```
import polars as pl
import sportsdataverse.nba as nba
box = nba.load_nba_team_boxscore([2025])
off = box.group_by("team_abbreviation").agg(
    pl.col("assists", "team_score").mean())
fig, ax = plt.subplots()
sdvplot.add_logos(ax, off["assists"],
    off["team_score"],
    off["team_abbreviation"],
    league="nba", height=0.06)
```

Per league: NFL · CFB · NBA · WNBA · MLB · NHL · PWHL · Soccer · Cricket

FROM SDVPLOTR

sdvplotR	sdvplot
`sdv_teams()` · `sdv_resolve()` · `sdv_marks()`	`teams()` · `resolve()` · `marks()`
`sdv_logo_url()` · `sdv_headshot_url()`	`logo_url()` · `headshot_url()`
`sdv_color_palette()` · `sdv_team_colors()`	`palette()` · `team_colors()`
`sdv_surface()` · `sdv_court_coords()` · `sdv_pitch_coords()`	`surface()` · `court_coords()` · `pitch_coords()`
`geom_sdv_logos()` &co.	same names in `sdvplot.plotnine`; `add_logos()` anywhere
`element_sdv_logo()`, `scale_x_sdv_headshots()`	`axis_logos()`
`ggtitle_image()` · `sdv_team_tiers()`	`title_image()` · `team_tiers()`
`gt_*()` · `reactable_sdv_*()` · `sdv_table_themes()`	same names

Arguments match (`league`, `id_system`, `season`, `strict`, `variant = "default"`); only `from` → `from_`. Not ported: `sdv_team_factor()` (three lines over `resolve()`).

LEARN MORE

GALLERY ↗ every chart and table in one place

Start: Getting started · reference

Concepts: identity · colours · logos · seasons · cache · adapters

Recipes: NFL EPA · CFB table · head-to-head card · NHL shot map

Leaderboards: NFL weekly · NBA · **Siblings:** sdvplotR (R), @sportsdataverse/sdvplot (npm)