

Jenkins

- Jenkins
 - Continuous Delivery
 - Jenkins with Maven Build
 - Setup maven
 - Maven build phases
 - pom.xml definitions
 - pom.xml parameters
 - Jenkins Job
 - Artifacts Archive
 - Jenkins Build and Deploy
 - Setup Apache Tomcat on Amazon Linux:
 - Tomcat War file deployment Configs
 - Apache Tomcat Terminology
 - Jenkins Plugin installation
 - Jenkins Job to deploy war file
 - Jenkinsfile Deployment for Build and Deployment
 - Assignment
 - Execution of Java Build and Deployment using AWS CICD.
 - Java Database Connection
 - Using Mysql Database Server
 - Configure Mysql DB AWS RDS
 - Connecting to an RDS
 - Multiple Environment Configuration
 - SSM Parameter Store.

Continuous Delivery

Continuous Delivery (CD) is a DevOps practice that is used to deploy an application quickly while maintaining a high quality with an automated approach. It is about the way application package is deployed in the Web Server or in the Application Server in environment such as dev, test or staging. Deployment of an application can be done using shell script, batch file, or plugins available in Jenkins. Approach of automated deployment in case of Continuous Delivery and Continuous Deployment will be always same most of the time. In the case of Continuous Delivery, the application package is always production ready

Jenkins with Maven Build

Setup maven

- Go to **Jenkins Dashboard** -> **Manage Jenkins** -> **Global Tool Configuration** > **Maven** > Give a Name **Maven_Local** > Check **Install Automatically** > Install from Apache (specify a version) > **Save**
- You can give a logical name to identify the correct version while configuring a build job.

Maven build phases

- Maven itself requires Java installed on your machine.
- You can verify if Maven is installed on your machine by running **mvn -v** in your command line/terminal.
- Maven is based on the **Project Object Model (POM)** configuration, which is stored in the XML file called the same – **pom.xml**.
- It is a structured format that describes the project, it's dependencies, plugins, and goals.
- **pom.xml** file should be present in your project directory
- Below are the Maven Build Phases
 - **Validate** : Validate Project is correct & all necessary information is available.
 - **Compile** : Compile the Source Code
 - **Test** : Test the Compiled Source Code using suitable unit Testing Framework (like JUnit)
 - **package** : Take the compiled code and package it.
 - **Install** : Install package in Local Repo, for use as a dependency in other project locally.
 - **Deploy** : Copy the final package to the remote repository for sharing with other developers.
- The above are always sequential, if you specify **install**, all the phases before **install** are checked.

pom.xml definitions

- **<modelVersion>** : POM model version (always 4.0.0).
- **<groupId>** : Group or organization that the project belongs to. Often expressed as an inverted domain name.
- **<artifactId>** : Name to be given to the project's library artifact (for example, the name of its JAR or WAR file).
- **<version>** : Version of the project that is being built.
- **<packaging>** : How the project should be packaged. Defaults to **jar** for JAR file packaging. Use **war** for WAR file packaging.

pom.xml parameters

- In the **mvn** command, a parameter can be passed using **mvn clean install "-Dparameter1=value1" "-Dparameter2=value2"**
 - The above values passed in the command can be referenced in **pom.xml** definition with **\${parameter1}** and **\${parameter2}**.

Jenkins Job

- Click on **New Item** then enter an item name, select **Freestyle project**.
- Under **Source Code Management** tab, select Git and then set the Repository URL to point to your GitHub Repository. **https://github.com/YourUserName/repo-name.git**
- Under **Build Environment** > **Build Step** > Select **Invoke top-level Maven targets** from dropdown > select the Maven Version that we just created, specify **clean install**.

- Under Advanced tab, specify the `pom.xml` file relative path location from git repository.
- Click on **Save**

it will run command `mvn clean install -f pom.xml`

```
[test-jenkins-maven-build-freestyle-project] $
/var/lib/jenkins/tools/hudson.tasks.Maven_MavenInstallation/Maven_Local/bin/mvn -f
java-tomcat-sample/pom.xml clean install
```

- Click OK and Build a Job and you will see that a `war` file is created.

`clean` -> Deletes `/var/lib/jenkins/workspace/jenkins-maven-build/java-tomcat-sample/target`


Artifacts Archive

- Go to **Jenkins dashboard** -> **Jenkins project or build job** -> **Post-build Actions** -> **Add post-build action** -> **Archive the artifacts**:
- Enter details for options in **Archive the artifacts** section:
 - For **Files to archive** enter the Path of the `.war` file like : `java-tomcat-sample/target/*.war`
- **Save** the changes and **Build Now**.
- Check the directories as below to validate above information:

```
ls /var/lib/jenkins/jobs
ls /var/lib/jenkins/jobs/<JOB_NAME>
ls /var/lib/jenkins/jobs/<JOB_NAME>/builds/<BUILD_NUMBER>
ls /var/lib/jenkins/workspace/<JOB_NAME>
```

```
[ec2-user@ip-172-31-4-240 java-tomcat-sample]$ tree /var/lib/jenkins/jobs/test-jenkins-maven-build-freestyle-project/
/var/lib/jenkins/jobs/test-jenkins-maven-build-freestyle-project/
```

```
├── builds
│   ├── 1
│   │   ├── build.xml
│   │   ├── changelog.xml
│   │   └── log
│   ├── 2
│   │   ├── build.xml
│   │   ├── changelog.xml
│   │   └── log
│   └── 3
│       ├── archive
│       │   ├── java-tomcat-sample
│       │   │   └── target
│       │   │       └── java-tomcat-maven-example.war
```



- The Build Project Summary, shows the last successful Build Artifact Name.

Jenkins

Dashboard > test-jenkins-maven-build-freestyle-project >

Status

Changes

Workspace

Build Now

Configure

Delete Project

Rename

Build History

Filter builds...

67	Oct 9, 2022, 6:39 AM
66	Oct 9, 2022, 6:31 AM
65	Oct 9, 2022, 6:28 AM
64	Oct 9, 2022, 5:38 AM
63	Oct 9, 2022, 5:36 AM
62	Oct 9, 2022, 5:29 AM
61	Oct 9, 2022, 5:07 AM

Atom feed for all
Atom feed for failures

Project test-jenkins-maven-build-freestyle-project

Maven Build Job

Last Successful Artifacts

java-tomcat-maven-example.war
14.51 MB
view

Permalinks

- Last build (#7), 7 min 38 sec ago
- Last stable build (#7), 7 min 38 sec ago
- Last successful build (#7), 7 min 38 sec ago
- Last failed build (#5), 18 min ago
- Last unsuccessful build (#5), 18 min ago
- Last completed build (#7), 7 min 38 sec ago

Edit description

Disable Project

- If you check the directory structure, there will be **archive** directory present under the subsequent build number for which the job is executed with Post build action as **Archive the artifacts**

Jenkins Build and Deploy

- Below steps assume that, you have a Jenkins Server Up and Running on one of the EC2 instance.

Setup Apache Tomcat on Amazon Linux:

- Launch a new EC2 Instance for Webserver Configuration

```
sudo hostnamectl set-hostname tomcat.example.com
sudo yum install java-1.8.0 java-devel -y
cd /opt/
sudo wget https://archive.apache.org/dist/tomcat/tomcat-9/v9.0.35/bin/apache-
tomcat-9.0.35.tar.gz
sudo tar -zxvf apache-tomcat-9.0.35.tar.gz
-----
z - The file is a “gzipped” file
v - Verbose, print the file names as they are extracted one by one
x - Extract files
f - Use the following tar archive for the operation
-----
sudo ls -ltr /opt/apache-tomcat-9.0.35/bin
sudo cd /opt/apache-tomcat-9.0.35/bin
```

- To Start Apache Tomcat : Run the `./startup.sh` file in `/opt/apache-tomcat-9.0.35/bin`
- We can make the scripts executable and then create a symbolic link for this scripts.

```
sudo chmod +x /opt/apache-tomcat-9.0.35/bin/startup.sh
sudo chmod +x /opt/apache-tomcat-9.0.35/bin/shutdown.sh
```

- Create symbolic link to these file so that tomcat server start and stop can be executed from any directory.

```
echo $PATH
sudo ln -s /opt/apache-tomcat-9.0.35/bin/startup.sh /usr/bin/tomcatup
sudo ln -s /opt/apache-tomcat-9.0.35/bin/shutdown.sh /usr/bin/tomcatdown
tomcatup
netstat -nltp | grep 8080
```

If you want to run Apache Tomcat on same Machine where Jenkins is Installed, then change the port of Apache Tomcat in : `/opt/apache-tomcat-9.0.35/conf/server.xml` file to `8090` as below,

```
<Connector port="8090" protocol="HTTP/1.1"
           connectionTimeout="20000"
           redirectPort="8443" />
```

- If above changes are made, execute the command `tomcatdown` and `tomcatup`.
- Create an empty repo and clone it, add project files into the local git folder and commit -> push the local repo to remote github repo using Git Bash.
- Verify the files are available in your github repository

Tomcat War file deployment Configs

- To have access to the dashboard the admin user needs the manager-gui role. Later, we will need to deploy a WAR file using Maven, for this, we need the `manager-script` role too.
- In order for Tomcat to accept remote deployments, we have to add a user with the role `manager-script`. To do so, edit the file `../conf/tomcat-users.xml` and add the following lines:
- In this case : add below configuration in file `/opt/apache-tomcat-9.0.35/conf/tomcat-users.xml` under `tomcat-users`.

```
<role rolename="manager-gui"/>
<role rolename="manager-script"/>
<user username="admin" password="admin" roles="manager-gui, manager-script"/>
<user username="deployer" password="deployer" roles="manager-script" />
```

- Edit the RemoteAddrValve under this file `/opt/apache-tomcat-9.0.35/webapps/manager/META-INF/context.xml` to allow all.
- Before

```
<Valve className="org.apache.catalina.valves.RemoteAddrValve"
  allow="127\.\d+\.\d+\.\d+|::1|0:0:0:0:0:0:0:1" />
```

- After

```
<Valve className="org.apache.catalina.valves.RemoteAddrValve"
  allow=".*" />
```

- Restart the tomcat server using `tomcatdown` and `tomcatup`

Apache Tomcat Terminology

- **Document root** : This is the top-level directory of a web application where all the application resources are located, like JSP files, HTML pages, Java classes, and images.
- **Context path** : This refers to the location that's relative to the server's address and represents the name of the web application. For e.g, If the WAR File is kept under the `$CATALINA_HOME\webapps\myapp` directory, it'll be accessed by the URL `http://TOMCAT_IP:PORT/myapp`, and its context path will be `/myapp`.
- **WAR** – Web Archive. It's the extension of a file that packages a web application directory hierarchy in ZIP format.

Jenkins Plugin installation

- To install the Plugin `Deploy to container` navigate to `Manage Jenkins > Manage Plugins`, search `Deploy to container` under `Available` tab.

Jenkins Job to deploy war file

- Click on **New Item** then enter an item name, select **Freestyle project**.
- Select the GitHub project checkbox and set the Project URL to point to your GitHub Repository.
`https://github.com/YourUserName/`
- Under Source Code Management Section : Provide the Github Repository URL of the Maven Project, keep the branch as `master`.
- Go to Jenkins Project -> Configure -> Under Build Environment Build Step > Select `Invoke top-level Maven targets` from dropdown > select the `Maven Version` that is configured > Enter `clean install`
- Under `Post-build Actions`, from the `Add post-build action` dropdown button select the option `Deploy war/ear to a container`
- Enter details of the War file that will be created as:
 - For `WAR/EAR` files you can use wild cards, e.g. `**/*.war`.

- The **context path** is the context path part of the URL under which your application will be published in Tomcat.
- Select the appropriate Tomcat version from the Container dropdown box (note that you can also deploy to Glassfish or JBoss using this Jenkins plugin).
- Under the **Credentials**, Add username and password value that is entered in the **tomcat-users.xml** file. Specify the ID of the credentials as **tomcat_creds**. This will be used later in Pipeline Script.
- The Tomcat URL is the base URL through which your Tomcat instance can be reached (e.g **http://172.31.67.85:8080**)

Make Sure network is open on specific port by checking the Security Group attached to EC2 Instance.

- **Save** the changes and **Build Now**.
- Once Jenkins Job is build, if there is a Success for deploy, verify the deployment files on Tomcat Server under **/opt/apache-tomcat-9.0.35/webapps/** path.
- Access the Application in Browser with specific Home Page present in **src/webapp** i.e **<TOMCAT_SERVER_IP>:<TOMCAT_PORT>/<CONTEXT_PATH>/index.jsp**
- Make some changes in the code on the github configured branch in the Jenkins Job and build the Job again to verify the Artifact Deployment on Tomcat Path.

Jenkinsfile Deployment for Build and Deployment

- Execute the **Jenkinsfile_Maven_Build_Deploy** to run the same Build Steps from Freestyle Project using Jenkinsfile Pipeline Code.
- Modify the necessary Pipeline Code inside the Jenkinsfile.

Assignment

Execution of Java Build and Deployment using AWS CICD.

- Configure CodePipeline, CodeBuild, CodeDeploy to use the existing Java Code Files and create a .war file using maven and deploy the .war file on Tomcat Servers.

Jenkins:

- Integration with Github.
- Build Step for Maven Command Execution:
 - mvn clean install -f pom.xml
- Archiving the artifacts (.war file)
- Deploy to Container Plugin:
 - .war file path, tomcat url, context path.

AWS CICD:

Environment Pre-requisite : EC2 instance (codedeploy agent, tomcat installed)

CodePipeline Integration with Github.

- CodeBuild buildspec.yml command execution:
 - install maven inside buildspec.yml
 - mvn clean install -f pom.xml
 - artifacts: section , .war file to be copied on S3.
- CodeDeploy for .war deployment:

```
- appspec.yml
  src: path/to/java-tomcat.war
  dest: /opt/apache-tomcat/webapps/
```

Java Database Connection

- The Java Project Object Model file i.e `pom.xml` file contains `dependency` specified as below:

```
<dependency>
  <groupId>mysql</groupId>
  <artifactId>mysql-connector-java</artifactId>
  <version>8.0.24</version>
</dependency>
```

- During the Java Build, the above mentioned dependency packages i.e jar files are downloaded from Maven Website Portal and added inside the `lib` path inside the Artifact `.war` file.
- The `mysql-connector-java-8.0.24.jar` file can be found under `/opt/apache-tomcat-9.0.35/webapps/java-tomcat-sample-deploy/WEB-INF/lib/mysql-connector-java-8.0.24.jar`
- Jar files contain `.class` files already compiled and can be used as import packages in `.java` programs.
- To view the content of the Jar files use command as : `jar tf FILENAME.jar`
 - `jar tf /opt/apache-tomcat-9.0.35/webapps/java-tomcat-sample-deploy/WEB-INF/lib/mysql-connector-java-8.0.24.jar`
- This will display all the `.class` files present.
- The `mysql-connector-java-8.0.24.jar` file is used in the `java-tomcat-sample/src/main/java/dao/GetDao.java` file to import methods and use objects to make connection to mysql database.

Using Mysql Database Server

Configure Mysql DB AWS RDS

- Go to RDS service and click on create database, Chose standard create, Select Mysql.
- On templates select Free tier.
- Keep the username and password as desired.
- For DB instance size, let us keep the default value of db.t3.micro.
- For allocated storage we can keep the default 20 GB as storage.
- The RDS similar to EC2 is launched in the VPC.Under connectivity select the VPC and click on "additional connectivity configuration ".
- Select the subnet group by default.
- Always make sure the "Public Access" setting is always set to No. As we'd never want our database to be accessed by internet.
- Select the security group. Make sure EC2 instance IP is whitelisted on port 3306 on this security group.
- Keep other default configuration same.

Connecting to an RDS

- Since we have selected public access as no , this RDS can be only accessed from within a VPC.
- On one of the EC2 machine, install mysql client to connect to RDS.

```
#Install the mysql client on EC2
sudo yum install mysql -y
sudo yum install mysql-connector-java.noarch -y
```

- These commands will install the mysql client which helps us connect to any mysql database
- Now to connect to the RDS that we have created, navigate to the RDS console. Click on the RDS and copy the endpoint.

```
# command to connect to mysql
mysql -h rds-endpoint-name -P 3306 -u username -p
mysql -h database-1.cpjjcutwuaxy.us-east-1.rds.amazonaws.com -P 3306 -u admin -p
```

- Use below mysql commands to create database and tables.

```
mysql> show databases;
mysql> create database db;
mysql> use db;

# Create employees table
CREATE TABLE employees (
    emp_no      INT          NOT NULL,
    birth_date  DATE          NOT NULL,
    first_name  VARCHAR(14)   NOT NULL,
    last_name   VARCHAR(16)   NOT NULL,
    gender      ENUM ('M','F') NOT NULL,
    hire_date   DATE          NOT NULL,
    PRIMARY KEY (emp_no)
);

show tables;
desc employees;

INSERT INTO `employees` VALUES (10001,'1953-09-02','Georgi','Facello','M','1986-06-26'),
(10002,'1964-06-02','Bezalel','Simmel','F','1985-11-21'),
(10003,'1959-12-03','Parto','Bamford','M','1986-08-28'),
(10004,'1954-05-01','Chirstian','Koblick','M','1986-12-01'),
(10005,'1955-01-21','Kyoichi','Maliniak','M','1989-09-12'),
(10006,'1953-04-20','Anneke','Preusig','F','1989-06-02'),
(10007,'1957-05-23','Tzvetan','Zielinski','F','1989-02-10'),
(10008,'1958-02-19','Saniya','Kalloufi','M','1994-09-15'),
(10009,'1952-04-19','Sumant','Peac','F','1985-02-18'),
(10010,'1963-06-01','Duangkaew','Piveteau','F','1989-08-24'),
(10011,'1953-11-07','Mary','Sluis','F','1990-01-22'),
(10012,'1960-10-04','Patricio','Bridgland','M','1992-12-18'),
```

```
(10013,'1963-06-07','Eberhardt','Terkki','M','1985-10-20'),
(10014,'1956-02-12','Berni','Genin','M','1987-03-11'),
(10015,'1959-08-19','Guoxiang','Nooteboom','M','1987-07-02'),
(10016,'1961-05-02','Kazuhito','Cappelletti','M','1995-01-27'),
(10017,'1958-07-06','Cristinel','Bouloucos','F','1993-08-03'),
(10018,'1954-06-19','Kazuhide','Peha','F','1987-04-03'),
(10019,'1953-01-23','Lillian','Haddadi','M','1999-04-30'),
(10020,'1952-12-24','Mayuko','Warwick','M','1991-01-26');
```

Create Title Table

```
CREATE TABLE titles (
    emp_no      INT          NOT NULL,
    title       VARCHAR(50)  NOT NULL,
    from_date   DATE         NOT NULL,
    to_date     DATE,
    # FOREIGN KEY (emp_no) REFERENCES employees (emp_no) ON DELETE CASCADE,
    PRIMARY KEY (emp_no,title, from_date)
);
```

```
INSERT INTO `titles` VALUES (10001,'Senior Engineer','1986-06-26','9999-01-01'),
(10002,'Staff','1996-08-03','9999-01-01'),
(10003,'Senior Engineer','1995-12-03','9999-01-01'),
(10004,'Engineer','1986-12-01','1995-12-01'),
(10004,'Senior Engineer','1995-12-01','9999-01-01'),
(10005,'Senior Staff','1996-09-12','9999-01-01'),
(10005,'Staff','1989-09-12','1996-09-12'),
(10006,'Senior Engineer','1990-08-05','9999-01-01'),
(10007,'Senior Staff','1996-02-11','9999-01-01'),
(10007,'Staff','1989-02-10','1996-02-11'),
(10008,'Assistant Engineer','1998-03-11','2000-07-31'),
(10009,'Assistant Engineer','1985-02-18','1990-02-18'),
(10009,'Engineer','1990-02-18','1995-02-18'),
(10009,'Senior Engineer','1995-02-18','9999-01-01'),
(10010,'Engineer','1996-11-24','9999-01-01'),
(10011,'Staff','1990-01-22','1996-11-09'),
(10012,'Engineer','1992-12-18','2000-12-18'),
(10012,'Senior Engineer','2000-12-18','9999-01-01'),
(10013,'Senior Staff','1985-10-20','9999-01-01'),
(10014,'Engineer','1993-12-29','9999-01-01'),
(10015,'Senior Staff','1992-09-19','1993-08-22'),
(10016,'Staff','1998-02-11','9999-01-01'),
(10017,'Senior Staff','2000-08-03','9999-01-01'),
(10017,'Staff','1993-08-03','2000-08-03'),
(10018,'Engineer','1987-04-03','1995-04-03'),
(10018,'Senior Engineer','1995-04-03','9999-01-01'),
(10019,'Staff','1999-04-30','9999-01-01'),
(10020,'Engineer','1997-12-30','9999-01-01');
```

```
SELECT employees.emp_no,employees.first_name, employees.last_name,
employees.hire_date, titles.title, titles.from_date, titles.to_date FROM employees
left JOIN titles ON employees.emp_no=titles.emp_no;
```

- Once above DB and Tables are created, validate the details of the DB Hostname, Database, DB UserName, DB Password values in file `java-tomcat-sample/src/main/java/dao/GetDao.java`
- Modify the above DB Password that is set in the above file and build and deploy artifact WAR File again.
- Execute the Jenkins Job to build above artifact and deploy the same on the Webserver Context Path.
- A directory with name of the `.war` file is present on the `webapps` path.

```
[root@tomcat java-tomcat-sample-deploy]# pwd
/opt/apache-tomcat-9.0.35/webapps/java-tomcat-sample-deploy
[root@tomcat java-tomcat-sample-deploy]# tree .
.
├── index.jsp
├── META-INF
│   ├── MANIFEST.MF
│   ├── maven
│   │   └── com.example
│   │       └── java-tomcat-sample
│   │           ├── pom.properties
│   │           └── pom.xml
│   └── war-tracker
├── register_2.jsp
├── register_3.jsp
├── register_4.jsp
├── register.jsp
├── showUser.jsp
└── WEB-INF
    ├── classes
    │   ├── app_login.class
    │   ├── app_register.class
    │   ├── dao
    │   │   └── GetDao.class
    │   ├── GetController.class
    │   └── model
    │       └── Users.class
    ├── lib
    │   ├── mysql-connector-java-8.0.24.jar
    │   └── protobuf-java-3.11.4.jar
    └── web.xml

9 directories, 18 files
[root@tomcat java-tomcat-sample-deploy]#
```

- To view the content of `.war` file use : `jar tf java-tomcat-sample-deploy.war`

```
[root@tomcat webapps]# pwd
/opt/apache-tomcat-9.0.35/webapps
[root@tomcat webapps]# jar tf java-tomcat-sample-deploy.war
META-INF/
META-INF/MANIFEST.MF
WEB-INF/
WEB-INF/classes/
WEB-INF/classes/dao/
WEB-INF/classes/model/
WEB-INF/lib/
WEB-INF/web.xml
WEB-INF/classes/app_register.class
WEB-INF/classes/app_login.class
WEB-INF/classes/dao/GetDao.class
WEB-INF/classes/model/Users.class
WEB-INF/classes/GetController.class
WEB-INF/lib/mysql-connector-java-8.0.24.jar
WEB-INF/lib/protobuf-java-3.11.4.jar
register.jsp
register_2.jsp
register_3.jsp
register_4.jsp
index.jsp
showUser.jsp
META-INF/maven/
META-INF/maven/com.example/
META-INF/maven/com.example/java-tomcat-sample/
META-INF/maven/com.example/java-tomcat-sample/pom.xml
META-INF/maven/com.example/java-tomcat-sample/pom.properties
[root@tomcat webapps]#
```

- Also, validate the details returned in the WebPage from Database.

Multiple Environment Configuration

- In Application Code, the details that will change as per Environments (dev/qa/prod), those config changes, should not be hardcoded in the program code.

SSM Parameter Store.

- Create Parameter `qa_db_rds_password` as SecureString Type, store the DB Password.
- In Java, there is `aws-sdk`, add the dependency in your pom.xml file.
- Dynamically as per users input for specific deployment, `sh "sed -i /s/SDLC_ENV/${params.SDLC_ENV}/ java-tomcat-sample/src/main/java/dao/GetDao.java"` , during the build and packaging, the code is replaced with correct environment variables, so that, credentials are retrieved specifically for that environment.

