

```
In [1]: import pandas as pd
import matplotlib.pyplot as plt
import os

BASE_dir = os.getcwd()
DATA_PATH = os.path.abspath(BASE_dir + '\\..\\data\\smart_home_energy.csv')
FIG_PATH = os.path.abspath(BASE_dir + '/../reports/Milestone1/figures')

df_initial = pd.read_csv(DATA_PATH)
df_initial
```

Out [1]:

	home_id	timestamp	device_id	device_type	room	status	power_watt	user_present	activity	indoor_temp	outdoor_temp
0	1	2022-01-01 00:00:00	air_conditioner1	air_conditioner	bedroom	off	0.000000	1	sleeping	11.4	11.9
1	1	2022-01-01 00:00:00	light1	light	living_room	on	105.880000	1	sleeping	11.4	11.9
2	1	2022-01-01 00:00:00	tv1	tv	living_room	off	0.000000	1	sleeping	11.4	11.9
3	1	2022-01-01 00:00:00	fridge1	fridge	kitchen	on	223.460000	1	sleeping	11.4	11.9
4	1	2022-01-01 00:00:00	washer1	washer	laundry_room	off	0.000000	1	sleeping	11.4	11.9
...	...	...	...	...	...	...	...	...	...	...	...
1751995	10	2022-12-31 23:45:00	air_conditioner10	air_conditioner	bedroom	off	0.000000	1	sleeping	10.8	11.1
1751996	10	2022-12-31 23:45:00	light10	light	living_room	off	0.000000	1	sleeping	10.8	11.1
1751997	10	2022-12-31 23:45:00	tv10	tv	living_room	off	0.000000	1	sleeping	10.8	11.1
1751998	10	2022-12-31 23:45:00	fridge10	fridge	kitchen	on	261.350000	1	sleeping	10.8	11.1
1751999	10	2022-12-31 23:45:00	washer10	washer	laundry_room	on	1884.819597	1	sleeping	10.8	11.1

1752000 rows × 16 columns

```
In [2]: print(df_initial.columns)

Index(['home_id', 'timestamp', 'device_id', 'device_type', 'room', 'status',
       'power_watt', 'user_present', 'activity', 'indoor_temp', 'outdoor_temp',
       'humidity', 'light_level', 'day_of_week', 'hour_of_day', 'price_kwh'],
      dtype='object')
```

Checking the data types for all columns

```
In [3]: df_initial.info()

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1752000 entries, 0 to 1751999
Data columns (total 16 columns):
#   Column      Dtype
---  ---
0   home_id     int64
1   timestamp   object
2   device_id   object
3   device_type object
4   room        object
5   status      object
6   power_watt  float64
7   user_present int64
8   activity    object
9   indoor_temp float64
10  outdoor_temp float64
11  humidity    float64
12  light_level float64
13  day_of_week int64
14  hour_of_day int64
15  price_kwh   int64
dtypes: float64(5), int64(5), object(6)
memory usage: 213.9+ MB
```

Converting the timestamp column to appropriate type for further analysis

```
In [4]: df_initial['timestamp'] = pd.to_datetime(df_initial['timestamp'])
df_initial.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1752000 entries, 0 to 1751999
Data columns (total 16 columns):
#   Column          Dtype
---  -
0   home_id         int64
1   timestamp       datetime64[ns]
2   device_id       object
3   device_type     object
4   room            object
5   status          object
6   power_watt      float64
7   user_present    int64
8   activity        object
9   indoor_temp     float64
10  outdoor_temp    float64
11  humidity        float64
12  light_level     float64
13  day_of_week     int64
14  hour_of_day     int64
15  price_kWh       int64
dtypes: datetime64[ns](1), float64(5), int64(5), object(5)
memory usage: 213.9+ MB
```

## Checking for null values column-wise

```
In [5]: for attr in df_initial.columns:
        print(df_initial[attr].isnull().value_counts())
        print()
```

```
home_id
False    1752000
Name: count, dtype: int64
```

```
timestamp
False    1752000
Name: count, dtype: int64
```

```
device_id
False    1752000
Name: count, dtype: int64
```

```
device_type
False    1752000
Name: count, dtype: int64
```

```
room
False    1752000
Name: count, dtype: int64
```

```
status
False    1752000
Name: count, dtype: int64
```

```
power_watt
False    1752000
Name: count, dtype: int64
```

```
user_present
False    1752000
Name: count, dtype: int64
```

```
activity
False    1752000
Name: count, dtype: int64
```

```
indoor_temp
False    1752000
Name: count, dtype: int64
```

```
outdoor_temp
False    1752000
Name: count, dtype: int64
```

```
humidity
False    1752000
Name: count, dtype: int64
```

```
light_level
False    1752000
Name: count, dtype: int64
```

```
day_of_week
False    1752000
Name: count, dtype: int64
```

```
hour_of_day
False    1752000
Name: count, dtype: int64
```

```
price_kWh
False    1752000
Name: count, dtype: int64
```

**No null values found**

**Since all columns have valid repeated data, checking for duplicates isn't necessary**

## Type of appliances considered in dataset

```
In [6]: df_initial['device_type'].value_counts()
```

```
Out [6]: device_type
air_conditioner    350400
light              350400
tv                 350400
fridge             350400
washer             350400
Name: count, dtype: int64
```

## Finding the difference in intervals between timestamps

```
In [7]: df_unique_ts = df_initial.drop_duplicates(subset='timestamp')['timestamp']
df_unique_ts.diff().value_counts().head()
```

```
Out [7]: timestamp
0 days 00:15:00    35039
Name: count, dtype: int64
```

## Since there is 15 min difference between each timestamp, checking for any missing interval

```
In [8]: full_range = pd.date_range(start=df_unique_ts.min(), end=df_unique_ts.max(), freq='15min')
missing = full_range.difference(df_unique_ts)
print(f'missing timestamps: {missing}')
```

```
missing timestamps: DatetimeIndex([], dtype='datetime64[ns]', freq='15min')
```

no missing timestamp

## Computing Energy in kWh from power logs for each interval

```
In [9]: df_initial['energy_kWh'] = (df_initial['power_watt'] * 0.25) / 1000 # since power is energy consumed in unit
df_initial['energy_kWh']
```

```
Out [9]: 0          0.000000
1          0.026470
2          0.000000
3          0.055865
4          0.000000
...
1751995    0.000000
1751996    0.000000
1751997    0.000000
1751998    0.065338
1751999    0.471205
Name: energy_kWh, Length: 1752000, dtype: float64
```

## Checking for any invalid values of energy consumption (negative)


```
In [10]: (df_initial['energy_kWh'] < 0).value_counts() # as no device can consume negative energy
```

```
Out [10]: energy_kWh
False      1752000
Name: count, dtype: int64
```

## Outlier Detection using scatter plot in month-wise distribution

```
In [11]: plt.figure(figsize=(12,4))
plt.scatter(df_initial['timestamp'].dt.month, df_initial['energy_kWh'], s = 3)
plt.title("Outlier Detection using Scatter Plot")
plt.xlabel('Months')
plt.ylabel('Energy (kWh)')
plt.savefig(FIG_PATH+'\\Energy_Month_Wise.png')
plt.show()
```

Outlier Detection using Scatter Plot



no outlier observed


## distribution plots wrt different features

```
In [12]: df_subset1 = df_initial.pivot_table(index='device_type', values='energy_kWh', aggfunc='sum')
df_subset1.round(2)
```

```
Out [12]:
```

	energy_kWh
air_conditioner	13001.83
fridge	23248.45
light	3539.48
tv	7448.75
washer	5315.65

```
In [13]: df_subset1.plot(kind='bar')
plt.title('Energy Consumption per appliance in a year')
plt.xlabel('Device Type')
plt.ylabel('Energy in kWh')
plt.savefig(FIG_PATH+'\\Energy_Appliance_Wise.png')
plt.show()
```




Here it is clearly seen the order of energy consumption in appliance: fridge > air\_conditioner > tv > washer > light

```
In [14]: df_subset2 = df_initial.pivot_table(index='activity', columns='device_type', values='energy_kWh', aggfunc='sum')
df_subset2.round(2)
```

```
Out [14]:
```

device_type	air_conditioner	fridge	light	tv	washer
away	803.07	4821.68	153.43	350.79	700.70
cooking	3871.85	3937.49	1276.43	296.00	1084.80
idle	2470.21	2071.30	152.74	150.47	572.87
sleeping	1400.06	7989.06	231.36	559.09	1661.87
watching_tv	4456.64	4428.91	1725.52	6092.40	1295.40

```
In [15]: df_subset2.plot(kind='bar')
plt.title('Energy Consumption per appliance wrt activity in a year')
plt.xlabel('Activity')
plt.ylabel('Energy in kWh')
plt.savefig(FIG_PATH+'\\Energy_Per_Device_Activity_Wise.png')
plt.show()
```



from above plot we can infer which device is majorly used for a certain activity like an association rule


```
In [16]: df_subset3 = df_initial.pivot_table(index='user_present', columns='device_type', values='energy_kWh', aggfunc=
df_subset3.round(2)
```

```
Out [16]:
```

device_type	air_conditioner	fridge	light	tv	washer
user_present					
0	803.07	4821.68	153.43	350.79	700.70
1	12198.76	18426.76	3386.05	7097.96	4614.94

```
In [17]: df_subset3.plot(kind='bar')
plt.title('Energy Consumption per appliance wrt presence of user in a year')
plt.xlabel('user present')
plt.ylabel('Energy in kWh')
plt.savefig(FIG_PATH+'\\Energy_Per_Device_User_Presence_Wise.png')
plt.show()
```

Energy Consumption per appliance wrt presence of user in a year



the above plot shows that fridge is always in use irrespective of user presence

```
In [18]: df_subset4 = df_initial.pivot_table(index='status', columns='device_type', values='energy_kwh', aggfunc='sum')
df_subset4.round(2)
```

```
Out [18]:
```

device_type	air_conditioner	fridge	light	tv	washer
status					
off	0.00	NaN	0.00	0.00	0.00
on	13001.83	23248.45	3539.48	7448.75	5315.65

there is no device here that consumes energy when off


```
In [19]: df_subset5 = df_initial.pivot_table(index='hour_of_day', columns='device_type', values='energy_kwh', aggfunc='sum')
df_subset5.round(2)
```

```
Out [19]:
```

device_type	air_conditioner	fridge	light	tv	washer
hour_of_day					
0	158.53	1000.05	97.34	70.82	139.99
1	142.36	1002.17	30.89	69.48	141.92
2	153.64	1000.74	30.10	69.47	126.74
3	152.70	1005.37	28.04	71.74	139.75
4	144.41	996.14	29.27	71.70	142.34
5	138.14	999.31	68.53	69.61	145.22
6	141.96	1000.57	233.94	71.42	387.80
7	182.06	1001.42	168.40	74.26	387.77
8	275.64	994.88	30.90	156.07	246.50
9	383.66	985.69	28.23	287.43	140.34
10	524.43	967.43	29.19	322.85	136.31
11	662.08	946.19	30.85	317.42	134.69
12	748.38	933.28	28.89	314.42	211.03
13	789.10	912.90	29.57	320.85	213.12
14	827.75	906.99	29.59	315.22	136.45
15	826.02	908.66	31.62	317.78	135.28
16	1005.22	909.43	28.46	240.00	126.80
17	1328.95	921.83	193.86	108.98	134.52
18	1312.26	940.58	471.00	188.58	134.84
19	1113.84	956.73	559.65	818.14	386.61
20	831.58	974.24	561.28	1282.21	389.58
21	599.84	987.28	510.09	1206.63	392.10
22	356.28	994.07	245.03	576.26	393.78
23	203.01	1002.50	44.75	107.41	392.17

```
In [20]: df_subset5.plot(kind='line',)
plt.title('Energy Consumption per appliance wrt month in a year')
plt.xlabel('Month')
```

```
plt.ylabel('Energy in kWh')
plt.savefig(FIG_PATH+'\\Energy_Per_Device_Month_Wise.png')
plt.show()
```



the above plot shows the use/consumption of which device spikes up or drops down during a certain month of year

```
In [21]: df_subset5 = df_initial.pivot_table(index='room', columns='device_type', values='energy_kWh', aggfunc='sum')
df_subset5.round(2)
```

```
Out [21]:
```

	device_type	air_conditioner	fridge	light	tv	washer
<b>room</b>						
bedroom		13001.83	NaN	NaN	NaN	NaN
kitchen		NaN	23248.45	NaN	NaN	NaN
laundry_room		NaN	NaN	NaN	NaN	5315.65
living_room		NaN	NaN	3539.48	7448.75	NaN


from the above table it can be inferred that air\_conditioner is installed in bedrooms only, fridge in kitchen, washer in laundry room while both light and tv are in living room

```
In [22]: df_subset6 = df_initial.pivot_table(index='day_of_week', columns='device_type', values='energy_kWh', aggfunc='sum')
weekdays={
    0: 'Monday',
    1: 'Tuesday',
    2: 'Wednesday',
    3: 'Thursday',
    4: 'Friday',
    5: 'Saturday',
    6: 'Sunday'
}
df_subset6.index = df_subset6.index.map(weekdays)
df_subset6.round(2)
```

```
Out [22]:
```


	device_type	air_conditioner	fridge	light	tv	washer
<b>day_of_week</b>						
Monday		1471.41	3298.33	541.05	1072.53	738.38
Tuesday		1490.25	3313.36	521.87	1057.42	730.77
Wednesday		1524.76	3311.07	509.49	1064.57	726.06
Thursday		1571.67	3326.80	496.72	1058.90	724.06
Friday		1572.81	3310.20	498.31	1062.52	722.74
Saturday		2689.86	3384.52	492.65	1075.67	847.47
Sunday		2681.08	3304.16	479.40	1057.14	826.18

```
In [23]: df_subset6.plot(kind='line')
plt.title('Energy Consumption per appliance wrt week day in a year')
plt.xlabel('Day of the week')
plt.ylabel('Energy in kWh')
plt.savefig(FIG_PATH+'\\Energy_Per_Device_WeekDay_Wise.png')
plt.show()
```



this plot shows the spike in the use of air conditioner and slight spike in use of washer near the weekends, others are used steadily throughout the week

```
In [24]: df_subset7 = df_initial[df_initial['device_type'] == 'light']
df_subset7 = df_subset7.pivot_table(index='light_level', values='energy_kWh', aggfunc='mean')
df_subset7 = df_subset7.reset_index()
df_subset7.plot(kind='scatter', x='light_level', y='energy_kWh')
plt.title('Light Level vs Energy Consumption (Light Device)')
plt.xlabel('Light Level')
plt.ylabel('Consumption By Light')
plt.savefig(FIG_PATH+'\\Light_level_light_consumption.png')
plt.show()
```



from above plot it can be concluded that when light level is low naturally the consumption of electricity by light device is high.

## observing relation between values of 'price\_kWh' and other features

```
In [25]: df_initial['price_kWh'].describe()
```

```
Out [25]: count    1.752000e+06
mean      2.250000e+03
std       5.590172e+02
min       1.500000e+03
25%      1.500000e+03
50%      2.500000e+03
75%      2.500000e+03
max       3.000000e+03
Name: price_kWh, dtype: float64
```

```
In [26]: for attr in df_initial.columns:
if attr != 'energy_kWh' and (df_initial[attr].dtype != object):
print(df_initial[[attr, 'energy_kWh']].corr())
print()
```



```

home_id      home_id  energy_kWh
1.000000    -0.046145
energy_kWh   -0.046145    1.000000

timestamp    energy_kWh
1.000000    0.008793
energy_kWh   0.008793    1.000000

power_watt   energy_kWh
1.0          1.0
energy_kWh   1.0        1.0

user_present energy_kWh
1.000000    0.108452
energy_kWh   0.108452    1.000000

indoor_temp  energy_kWh
1.000000    0.136976
energy_kWh   0.136976    1.000000

outdoor_temp energy_kWh
1.000000    0.136327
energy_kWh   0.136327    1.000000

humidity     energy_kWh
1.000000    -0.044761
energy_kWh  -0.044761    1.000000

light_level  energy_kWh
1.000000    0.019396
energy_kWh   0.019396    1.000000

day_of_week  energy_kWh
1.000000    0.031299
energy_kWh   0.031299    1.000000

hour_of_day  energy_kWh
1.000000    0.145333
energy_kWh   0.145333    1.000000

price_kWh    energy_kWh
1.000000     0.130418
energy_kWh   0.130418    1.000000

```

```

In [27]: df_subset8 = df_initial.pivot_table(index='hour_of_day', values='price_kWh', aggfunc='sum')
df_subset8.round(2)

```

```


Out [27]:
           price_kWh
hour_of_day
0      109500000
1      109500000
2      109500000
3      109500000
4      109500000
5      109500000
6      182500000
7      182500000
8      182500000
9      182500000
10     182500000
11     182500000
12     182500000
13     182500000
14     182500000
15     182500000
16     182500000
17     219000000
18     219000000
19     219000000
20     219000000
21     182500000
22     109500000
23     109500000

```

```

In [28]: df_subset8.plot(kind='line')
plt.title('Price variation throught the day summed over year')
plt.xlabel('Hour of day')
plt.ylabel('Price in VND')
plt.savefig(FIG_PATH+'\\VND_price_Distribution.png')
plt.show()

```



```
In [29]: df_subset9 = df_initial.pivot_table(index='home_id', values='price_kWh', aggfunc='sum')
df_subset9
```

```
Out [29]:
```

	price_kWh
home_id	
1	394200000
2	394200000
3	394200000
4	394200000
5	394200000
6	394200000
7	394200000
8	394200000
9	394200000
10	394200000


While the 'price\_kWh' shows appropriate distribution and correlation eith other features, the original dataset follows VND currency so these values might make sense by that country standards but seems incomprehensible for indian (INR) standards.

Hence, dropping 'price\_kWh'

```
In [30]: df_initial.drop('price_kWh', axis=1, inplace=True)
```

```
In [31]: df_initial['device_id'].value_counts().plot(kind='bar', figsize=(8,8))
plt.title('Checking importance of device_id')
plt.xlabel('device_id values')
plt.ylabel('frequency')
```

```
Out [31]: Text(0, 0.5, 'frequency')
```



'device\_id' is dropped because it is just a unique identifier with no predictive meaning also the value represented by this is same as 'device\_type' since each home has equal no. of devices.

'home\_id' is retained because the dataset logs the same device\_type across multiple houses,

so keeping 'home\_id' is necessary to distinguish identical timestamps and devices from different homes.


```
In [32]: df_initial.drop('device_id', axis=1, inplace=True)
```

## Checking imbalance in record entries

since the timestamp-appliance follow a panel-logging system, there will be balanced entries for the columns: timestamp, home\_id, device\_id, device\_type, room, day\_of\_week and hour\_of\_day

### appliance-wise status imbalance

```
In [33]: pd.crosstab(df_initial['device_type'], df_initial['status']).plot(kind='bar', stacked=True)
plt.title('Device Type Count')
plt.xlabel('Device Type')
plt.ylabel('Frequency')
plt.show()
```




here it is observed that fridge is never off and so always consumes energy

```
In [34]: activity_count = df_initial['activity'].value_counts()
activity_count
```

```
Out [34]: activity
sleeping      582955
away          373780
watching_tv   335850
cooking       300395
idle          159020
Name: count, dtype: int64
```

```
In [35]: activity_count.plot(kind='bar')
plt.title('Count of activity records in dataset')
plt.xlabel('Activity')
plt.ylabel('Frequency')
plt.savefig(FIG_PATH+'\\Activity_Record_Value_Count.png')
plt.show()
```




From above, it can be concluded that sleeping is the most dominant activity in dataset

frequency order: sleeping > away > watching\_tv > cooking > idle

```
In [36]: df_initial['energy_kWh'].plot(kind='hist')
plt.title('Energy Consumption value distribution')
plt.xlabel('Energy in kWh')
```

```
plt.ylabel('Frequency')
plt.savefig(FIG_PATH+'Energy_Consumption_Distribution_Initial.png')
plt.show()
```



Most 15-minute intervals show very low energy use, while only a few intervals spike because of heavy appliances like ACs, washers, and fridges.

This kind of skewed pattern is normal in smart-home data and will be taken care of during normalization in later stages.

```
In [37]: df_initial['energy_kWh'].describe().round(2)
```

```
Out [37]: count    1752000.00
          mean       0.03
          std        0.06
          min        0.00
          25%        0.00
          50%        0.00
          75%        0.05
          max        0.87
          Name: energy_kWh, dtype: float64
```

## Balanced Dataset For Plot

Since the dataset follows panel-logging system the count of timestamps, home\_id, device\_id, device\_type, hour\_of\_day, and day\_of\_week values are equal

The room values might be unequal for living room has 2 devices while the others have 1

for other categorical values (status, user\_present, and activity) sample creation:

Identifying the minimum value count for equal-sized samples

```
In [38]: df_initial['status'].value_counts()
```

```
Out [38]: status
off      1151365
on        600635
          Name: count, dtype: int64
```

```
In [39]: df_initial['user_present'].value_counts()
```

```
Out [39]: user_present
1      1378220
0       373780
          Name: count, dtype: int64
```

```
In [40]: df_initial['activity'].value_counts()
```

```
Out [40]: activity
sleeping    582955
away        373780
watching_tv 335850
cooking     300395
idle        159020
          Name: count, dtype: int64
```

1,00,000 samples can be taken for each attribute value

```
In [41]: on_sample = df_initial[df_initial['status']=='on'].sample(100000)
         off_sample = df_initial[df_initial['status']=='off'].sample(100000)

         user_present_sample = df_initial[df_initial['user_present']==1].sample(100000)
         user_absent_sample = df_initial[df_initial['user_present']==0].sample(100000)
```

```

sleeping_sample = df_initial[df_initial['activity']=='sleeping'].sample(100000)
away_sample = df_initial[df_initial['activity']=='away'].sample(100000)
watching_tv_sample = df_initial[df_initial['activity']=='watching_tv'].sample(100000)
cooking_sample = df_initial[df_initial['activity']=='cooking'].sample(100000)
idle_sample = df_initial[df_initial['activity']=='idle'].sample(100000)

```

obtain balanced dataset by concatenating the equal sized samples:

```

In [42]: df_status_balanced = pd.concat([on_sample, off_sample])
df_user_balanced = pd.concat([user_present_sample, user_absent_sample])
df_activity_balanced = pd.concat([
    sleeping_sample, away_sample, watching_tv_sample, cooking_sample, idle_sample
])


```

#### 1. balanced status value count plot

```

In [43]: pivot_table1=df_status_balanced.pivot_table(index='status', columns='device_type', values='energy_kWh', aggfunc='sum')
pivot_table1.plot(kind='bar')
plt.title('plot with balanced status value count ')
plt.xlabel('status')
plt.ylabel('energy in kWh')
plt.savefig(FIG_PATH+'\\Balanced_wrt_status.png')

```




#### 2. balanced user presence value count plot

```


In [44]: pivot_table2=df_user_balanced.pivot_table(index='user_present', columns='device_type', values='energy_kWh', aggfunc='sum')
pivot_table2.plot(kind='bar')
plt.title('plot with balanced user_present value count ')
plt.xlabel('user_present')
plt.ylabel('energy in kWh')
plt.savefig(FIG_PATH+'\\Balanced_wrt_user_presence.png')

```



### 3. balanced activity value count plot

```
In [45]: pivot_table3=df_activity_balanced.pivot_table(index='activity', columns='device_type', values='energy_kwh', aggfunc='sum')
pivot_table3.plot(kind='bar')
plt.title('plot with balanced activity value count ')
plt.xlabel('activity')
plt.ylabel('energy in kWh')
plt.savefig(FIG_PATH+'\\Balanced_wrt_activity.png')
```



## Normalization and Standardization

```
In [46]: df_initial.columns
```

```
Out [46]: Index(['home_id', 'timestamp', 'device_type', 'room', 'status', 'power_watt', 'user_present', 'activity', 'indoor_temp', 'outdoor_temp', 'humidity', 'light_level', 'day_of_week', 'hour_of_day', 'energy_kwh'], dtype='object')
```

```
In [47]: num_cols = ['power_watt', 'indoor_temp', 'outdoor_temp', 'humidity', 'light_level']

for attr in num_cols:
    print(attr)
    print(df_initial[attr].describe())
    print()
```

```
power_watt
count    1.752000e+06
mean      1.199867e+02
std       2.252036e+02
min       0.000000e+00
25%       0.000000e+00
50%       0.000000e+00
75%       2.181600e+02
```

```
max      3.482295e+03
Name: power_watt, dtype: float64
```

```
indoor_temp
count      1.752000e+06
mean       2.119561e+01
std        8.014708e+00
min        2.200000e+00
25%        1.520000e+01
50%        2.030000e+01
75%        2.650000e+01
max        4.320000e+01
Name: indoor_temp, dtype: float64
```

```
outdoor_temp
count      1.752000e+06
mean       2.119547e+01
std        7.930646e+00
min        4.000000e+00
25%        1.520000e+01
50%        2.030000e+01
75%        2.650000e+01
max        4.120000e+01
Name: outdoor_temp, dtype: float64
```

```
humidity
count      1.752000e+06
mean       6.048777e+01
std        1.889061e+01
min        2.370000e+01
25%        4.510000e+01
50%        5.940000e+01
75%        7.170000e+01
max        1.000000e+02
Name: humidity, dtype: float64
```

```
light_level
count      1.752000e+06
mean       2.548263e+02
std        2.777288e+02
min        0.000000e+00
25%        4.710000e+01
50%        9.240000e+01
75%        4.238000e+02
max        1.000000e+03
Name: light_level, dtype: float64
```

**Descriptive statistics show that most numerical features (temperature, humidity, light level, energy) lie within naturally bounded ranges and exhibit skewness, especially due to zero-heavy power readings. Standardizing these variables (mean=0, std=1) would distort their physical interpretation, and create unnecessary negative values. Therefore, MinMaxScaler is more suitable as it preserves range relationships and scales all features proportionally between 0 and 1 without altering their real-world meaning.**

```
In [48]: non_num_cat = ['device_type', 'room', 'status', 'activity']
```

**OneHotEncoder is used for categorical features because they do not possess any inherent order, and encoding them as independent binary variables prevents the model from learning false numerical relationships.**

```
In [49]: other_cols = ['home_id', 'user_present', 'timestamp', 'day_of_week', 'hour_of_day', 'user_present']
```

**Above columns carry contextual or already-numeric info that doesn't need transformation, so they remain as-is.**

```
In [50]: df_initial['energy_kWh'].describe()
```

```
Out [50]: count      1.752000e+06
mean       2.999667e-02
std        5.630090e-02
min        0.000000e+00
25%        0.000000e+00
50%        0.000000e+00
75%        5.454000e-02
max        8.705738e-01
Name: energy_kWh, dtype: float64
```

```
In [51]: target_col = ['energy_kWh']
```

## Note: energy\_kWh is not scaled

The target variable is left unchanged because:

- Models can directly learn from its natural scale
- Scaling the target is only necessary for neural networks or extreme ranges
- Keeping it raw makes evaluation metrics (MAE, RMSE) easier to interpret

```
In [52]: from sklearn.preprocessing import MinMaxScaler, OneHotEncoder
from sklearn.model_selection import train_test_split
import joblib # to save scaler/encoder

# scaling numerical value columns:
scaler = MinMaxScaler()
X_num = pd.DataFrame(scaler.fit_transform(df_initial[num_cols]), columns=num_cols, index=df_initial.index)

joblib.dump(scaler, "../saved_objects/scaler_minmax.joblib")
```



```
# Encoding labeled data
encoder = OneHotEncoder(sparse_output=False, handle_unknown='ignore')
X_cat_array = encoder.fit_transform(df_initial[non_num_cat])
encoded_cols = encoder.get_feature_names_out(non_num_cat)
X_cat = pd.DataFrame(encoder.fit_transform(df_initial[non_num_cat]), columns=encoded_cols, index=df_initial.index)

joblib.dump(encoder, "../saved_objects/ohe_device_room_status_activity.joblib")

# Columns that do not need to undergo transformation
X_rem = df_initial[other_cols].copy()

# Concatenating all features after transformation
X = pd.concat([X_rem, X_num, X_cat], axis=1)

# Extracting the target variable for regression.
y = df_initial[target_col].copy()

print("Final feature shape:", X.shape)
print("Target shape:", y.shape)
```

Final feature shape: (1752000, 27)  
Target shape: (1752000, 1)

```
In [53]: X.head()
```

Out [53]:

	home_id	user_present	timestamp	day_of_week	hour_of_day	user_present	power_watt	indoor_temp	outdoor_temp	humidity	...	room_kitchen
0	1	1	2022-01-01	5	0	1	0.000000	0.22439	0.212366	0.281782	...	0.0
1	1	1	2022-01-01	5	0	1	0.030405	0.22439	0.212366	0.281782	...	0.0
2	1	1	2022-01-01	5	0	1	0.000000	0.22439	0.212366	0.281782	...	0.0
3	1	1	2022-01-01	5	0	1	0.064170	0.22439	0.212366	0.281782	...	1.0
4	1	1	2022-01-01	5	0	1	0.000000	0.22439	0.212366	0.281782	...	0.0

5 rows × 27 columns

```
In [54]: y.head()
```

Out [54]:

	energy_kWh
0	0.000000
1	0.026470
2	0.000000
3	0.055865
4	0.000000

### Data Split

```
In [55]: X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.3, random_state=10, shuffle=True
)

# Splitting the dataset so the model learns on 70% of data and is tested on the remaining 30%.
# 'random_state' ensures reproducibility, and 'shuffle=True' avoids any time-based ordering bias.
print("Train shape:", X_train.shape, y_train.shape)
print("Test shape:", X_test.shape, y_test.shape)
```

Train shape: (1226400, 27) (1226400, 1)  
Test shape: (525600, 27) (525600, 1)

**Note:** For hyperparameter tuning in later milestones, the current test set will be further split into validation and final test subsets.

```
In [ ]:
```