

Sprinter Signers

The MPC set is an integral part of running the Sprinter Stash credit system. It validates liquidity requests and generates signatures that allow solvers to use the requested liquidity.

MPC set is built out of multiple instances of Sprinter Signing:

<https://github.com/sprintertech/sprinter-signing>

This is a fork of Sygma Relay that is customized to process liquidity requests.

Sygma relay deployment guide: <https://github.com/sprintertech/sygma-relayer-deployment>

Difference from infra perspective when running Sprinter Signing instance, based on [template ecs file from guide](#)

- Point to new shared config URL (`--config-url` flag)
 - TBD (link to new shared config)
- Remove envs:
 - `SYG_RELAYER_MPCCONFIG_FROSTKEYSHAREPATH`
- Update these secrets based on values shared in 1pass:
 - `SYG_RELAYER_MPCCONFIG_KEY`
 - generate a new key
 - `SYG_RELAYER_MPCCONFIG_TOPOLOGYCONFIGURATION_ENCRYPTIONKEY`
 - `SYG_RELAYER_MPCCONFIG_TOPOLOGYCONFIGURATION_URL`
 - `SYG_CHAINS`
- Add new secret:
 - `SYG_RELAYER_COINMARKETCAPCONFIG_APIKEY`
- Expose additional port
 - Port `3000` of each signer should be exposed so it is accessible from outside. On this port, signers expose public API for starting the signing

process for liquidity request.

Additional requirements:

- **The signer should have a DNS entry, like the Sygma relayer, so it can be accessed by other signers during MPC communication.**
- **The signer should have a side cart, like the Sygma relayer, so it sends its logs to the grafana instance.**