ORACLE Academy



3-1

Logical Comparisons and Precedence Rules





Objectives

- This lesson covers the following objectives:
 - Evaluate logical comparisons to restrict the rows returned based on two or more conditions
 - Apply the rules of precedence to determine the order in which expressions are evaluated and calculated



DP 3-1 Logical Comparisons and Precedence Rules

Mary Million Sunx.

Purpose

- Not too many things in life depend on just one condition
- For instance, if you want to go to college, you probably need good grades and the tuition money to pay for it
- If you have extra money, you could either save it or spend it
- If you want to go to a movie, you may not want to go this weekend and you may not want to sit in the first 10 rows of the theater



DP 3-1 Logical Comparisons and Precedence Rules

Purpose

- In SQL, it is often desirable to be able to restrict the rows returned by a query based on two or more conditions
- As the manager of a fast food business, you may need to know the names of your staff who are either cooks or order takers
- You don't need or want the entire staff list, you just want a subset of it
- Conditional operators such as AND, NOT, and OR make these types of requests easy to do



DP 3-1 Logical Comparisons and Precedence Rules

Logical Conditions

- Logical conditions combine the result of two component conditions to produce a single result based on them
- For example, to attend a rock concert, you need to buy a ticket AND have transportation to get there
- If both conditions are met, you can go to the concert
- What if you can't get transportation, can you go?



DP 3-1 Logical Comparisons and Precedence Rules

Logical Conditions

- Another logical condition combines two component conditions with OR
- All employees will receive a raise either by having a perfect attendance record OR by meeting their monthly sales quota
- If an employee meets either of these two conditions, the employee gets a raise



DP 3-1 Logical Comparisons and Precedence Rules

Logical Operators

- A logical operator combines the results of two or more conditions to produce a single result
- A result is returned ONLY IF the overall result of the condition is true
- AND -- Returns TRUE if both conditions are true
- OR -- Returns TRUE if either condition is true
- NOT -- Returns TRUE if the condition is false



DP 3-1 Logical Comparisons and Precedence Rules

AND Operator

 In the query below, the results returned will be rows that satisfy BOTH conditions specified in the WHERE clause

SELECT last_name, department_id, salary
FROM employees

WHERE department id > 50 AND salary > 12000;

LAST_NAME	DEPARTMENT_ID	SALARY
King	90	24000
Kochhar	90	17000
De Haan	90	17000



DP 3-1 Logical Comparisons and Precedence Rules

Copyright $\ \ \, \mathbb{C}$ 2020, Oracle and/or its affiliates. All rights reserved.

AND Operator

Another example of using AND in the where clause

```
SELECT last_name, hire_date, job_id
FROM employees
WHERE hire_date > '01-Jan-1998' AND job_id LIKE 'SA%';
```

LAST_NAME	DATE STARTED	JOB_ID
Zlotkey	29-Jan-2000	SA_MAN
Taylor	24-Mar-1998	SA_REP
Grant	24-May-1999	SA_REP



DP 3-1 Logical Comparisons and Precedence Rules

Copyright $\hbox{@}$ 2020, Oracle and/or its affiliates. All rights reserved.

Reminder: dates must be entered in single quotes, and the default format is dd-Mon-yyyy

OR Operator

- If the WHERE clause uses the OR condition, the results returned from a query will be rows that satisfy either one of the OR conditions
- In other words, all rows returned have a location_id of 2500 OR they have a manager_id equal to 124

```
SELECT department_name, manager_id, location_id
FROM departments
WHERE location id = 2500 OR manager id=124;
```

DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
Shipping	124	1500
Sales	149	2500



DP 3-1 Logical Comparisons and Precedence Rules

NOT Operator

 The NOT operator will return rows that do NOT satisfy the condition in the WHERE clause

```
SELECT department_name, location_id
FROM departments
WHERE location id NOT IN (1700,1800);
```

DEPARTMENT_NAME	LOCATION_ID	
Shipping	1500	
IT	1400	
Sales	2500	



DP 3-1 Logical Comparisons and Precedence Rules

- Consider the following SELECT statement
- In what order are the expressions evaluated and calculated?

```
SELECT last_name||' '||salary*1.05 AS "Employee Raise"
FROM employees
WHERE department_id IN(50,80) AND first_name LIKE 'C%'
OR last_name LIKE '%s%';
```

 Luckily, when things get this complicated, SQL has a few basic rules that are easy to follow



DP 3-1 Logical Comparisons and Precedence Rules

- Notice that the AND operator is evaluated before the OR operator
- This means that for the example on the previous slide, if either of the conditions in the AND statement are not met, then the OR operator is used to select the rows
- This is an important concept to remember

ORDER	OPERATOR
1	Arithmetic + - * /
2	Concatenation
3	Comparison <, <=, >, >=, <>
4	IS (NOT) NULL, LIKE, (NOT) IN
5	(NOT) BETWEEN
6	NOT
7	AND
8	OR



DP 3-1 Logical Comparisons and Precedence Rules

- First, the AND condition is evaluated, so all employees working in dept 80 or 50, AND who have a first name starting with "C" are returned
- The OR clause is then evaluated and returns employees whose last name contains "s"

```
SELECT last_name||' '||salary*1.05

AS "Employee Raise", department_id,
first_name
FROM employees
WHERE department_id IN(50,80)

AND first_name LIKE 'C%'
OR last name LIKE '%s%';
```

Employee Raise	DEPARTMENT _ID	FIRST_ NAME
Higgins 12600	110	Shelley
Mourgos 6090	50	Kevin
Rajs 3675	50	Trenna
Davies 3255	50	Curtis
Matos 2730	50	Randall
Vargas 2625	50	Peter
Ernst 6300	60	Bruce
Hartstein 13650	20	Michael



Academy

DP 3-1 Logical Comparisons and Precedence Rules

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

15

Employee Curtis Davis is in department 50 and his first name starts with a "C", so is returned by the AND clause.

The OR then returns any employees whose last name contains the letter "s".

If either of the conditions in the AND statement are not met, then the OR condition would have to evaluate to true to return any rows.

 In this example, the order of the OR and AND have been reversed from the previous slide

```
SELECT last_name||' '||salary*1.05 AS "Employee Raise",
department_id,
   first_name
FROM employees
WHERE department_id IN(50,80)
   OR first_name LIKE 'C%'
   AND last_name LIKE '%s%';

first_name starts with a "C" AND assert the content of the
```

The order of operations is:
first_name starts with a "C" AND
last_name contains an "s". Both
these conditions must be met to be

Any instance of employees in department 50 and 80 will be returned.

returned.



DP 3-1 Logical Comparisons and Precedence Rules

 Adding parenthesis changes the way the Where clause is evaluated, and the rows returned

```
SELECT last_name||' '||salary*1.05 AS "Employee Raise",
department_id,
  first_name
FROM employees
WHERE (department_id IN(50,80) OR first_name LIKE 'C%')
AND last_name LIKE '%s%';
```

The order of operations is:

The values in the parentheses are selected.

All instances of the values in the parentheses that also contain the letter "s" in their last_name will be returned.



DP 3-1 Logical Comparisons and Precedence Rules

Copyright $\ensuremath{\mathbb{C}}$ 2020, Oracle and/or its affiliates. All rights reserved.

Terminology

- Key terms used in this lesson included:
 - -AND
 - -OR
 - -NOT
 - -Precedence Rules



DP 3-1 Logical Comparisons and Precedence Rules

Summary

- In this lesson, you should have learned how to:
 - Evaluate logical comparisons to restrict the rows returned based on two or more conditions
 - Apply the rules of precedence to determine the order in which expressions are evaluated and calculated



DP 3-1 Logical Comparisons and Precedence Rules

Copyright $\ensuremath{\mathbb{C}}$ 2020, Oracle and/or its affiliates. All rights reserved.

ORACLE Academy