

Functional Verification of Tezos Smart Contracts in Coq

Bruno Bernardo, *Raphaël Cauderlier*, Zhenlei Hu, Basile Pesin,
Julien Tesson

Nomadic Labs, Paris, France

FMBC, Porto
October 11, 2019

Nomadic Labs



- R&D company focused on distributed, decentralised and formally verified software.
- Involved in the development of the core software of the Tezos blockchain.
- Based in Paris, France.

Tezos

- Public blockchain
- Live since June 2018
- Implemented in OCaml
- Open source project (MIT License)
<https://gitlab.com/tezos/tezos>

Tezos

- Liquid Proof of Stake
 - Block production rights come from owned tokens
 - Rights can be delegated
 - Delegations are revocable
- On-chain governance
 - Ruleset can be amended through on-chain vote
Consensus, smart contract language, voting procedure
 - Voting right is the same as block production right
- Formal methods
 - Recognised as crucial since the Tezos whitepaper
 - Static analysis, model checking, and functional verification (in F^* and Coq)
 - Targeting both the OCaml implementation of the Tezos node and the smart-contract layer

Michelson: Tezos smart contract language

- stack-based Turing-complete language
 - low-level computation paradigm
 - high-level data structures
- designed with software verification in mind
 - static typing
 - language specification (syntax, typing, semantics)
 - failure is explicit
 - integers do not overflow
 - division returns an option
- implemented using an OCaml GADT
 - subject reduction for free

Michelson example: vote

```

storage (map string int);
parameter string;
code {
  # Check that at least 5tz have been sent
  AMOUNT;
  PUSH mutez 5000000; COMPARE; GT; IF { FAIL } {};

  # Pair and stack manipulation
  DUP; DIP { CDR; DUP }; CAR; DUP;

  DIP { # Get the number of votes for the chosen option
        GET; IF_NONE { FAIL } {};
        # Increment
        PUSH int 1; ADD; SOME };
  UPDATE;
  NIL operation; PAIR
}

```

Mi-Cho-Coq



- Deep embedding of the Michelson language in Coq
- Weakest-precondition calculus
- Free software (MIT License)
<https://gitlab.com/nomadic-labs/mi-cho-coq/>

Syntax of types

```
Inductive comparable_type : Set :=
| nat | int | string | bytes | bool
| mutez | address | key_hash | timestamp.

Inductive type : Set :=
| Comparable_type (_ : comparable_type)
| unit | option (_ : type) | lambda (_ _ : type)
| pair (_ _ : type) | or (_ _ : type)
(* Domain specific *)
| key | signature | operation | contract (_ : type)
(* Data structures *)
| list (_ : type) | set (_ : comparable_type)
| map (_ : comparable_type) (_ : type).

Coercion Comparable_type : comparable_type >-> type.

Definition stack_type := Datatypes.list type.
```


Syntax and typing of instructions

```
Inductive instruction
  : stack_type -> stack_type -> Set :=
| FAILWITH {A B a} : instruction (a :: A) B
| SEQ {A B C} : instruction A B -> instruction B C ->
    instruction A C
| IF {A B} : instruction A B -> instruction A B ->
    instruction (bool :: A) B
| LOOP {A} : instruction A (bool :: A) ->
    instruction (bool :: A) A
| COMPARE {a : comparable_type} {S} :
    instruction (a :: a :: S) (int :: S)
| DROP {a S} : instruction (a :: S) S
| DUP {a S} : instruction (a :: S) (a :: a :: S)
| SWAP {a b S} : instruction (a :: b :: S) (b :: a :: S)
| ...
```

Semantics

```

Fixpoint eval {A B : stack_type}
  (i : instruction A B) (input : stack A) : stack B :=
  match i, input with
  | FAILWITH, (x, _) =>
    ...
  | SEQ i1 i2, input =>
    eval i2 (eval i1 input)
  | IF bt bf, (b, st) =>
    if b then eval bt st else eval bf st
  | LOOP body, (b, st) =>
    if b then eval (SEQ body (LOOP body)) st
    else st
  ...

```

Semantics

```

Fixpoint eval {A B : stack_type}
  (i : instruction A B) (input : stack A) : M (stack B) :=
  match i, input with
  | FAILWITH, (x, _) =>
    Failed _ (Assertion_Failure _ x)
  | SEQ i1 i2, input =>
    bind (eval i2) (eval i1 input)
  | IF bt bf, (b, st) =>
    if b then eval bt st else eval bf st
  | LOOP body, (b, st) =>
    if b then eval (SEQ body (LOOP body)) st
    else Return _ st
  ...

```

Semantics

```
Fixpoint eval {A B : stack_type}
  (i : instruction A B) (input : strack A)
  (fuel : nat) {struct fuel} : M (stack B) :=
match fuel with
| 0 => Failed _ Out_of_fuel
| S n =>
  match i, input with
  | FAILWITH, (x, _) =>
    Failed _ (Assertion_Failure _ x)
  | SEQ i1 i2, input =>
    bind (eval i2 n) (eval i1 n input)
  | IF bt bf, (b, st) =>
    ...
  | LOOP body, (b, st) =>
    ...
```

Semantics of domain specific operations

- mutez and timestamp arithmetics are supported
- serialisation, cryptographic primitives, and access to the chain context are axiomatized

Verification

```
Definition correct_smart_contract {A B : stack_type}
  (i : instruction A B) min_fuel spec : Prop :=
forall (input : stack A) (output : stack B) fuel,
  fuel >= min_fuel input ->
  eval i fuel input = Return (stack B) output <->
  spec input output.
```

Verification

```
Definition correct_smart_contract {A B : stack_type}
  (i : instruction A B) min_fuel spec : Prop :=
  forall (input : stack A) (output : stack B) fuel,
    fuel >= min_fuel input ->
    eval i fuel input = Return (stack B) output <->
    spec input output.
```

Full functional verification: we characterize all successful runs of the contract.

Computing weakest precondition

```
Fixpoint wp {A B} (i : instruction A B) fuel
  (post : stack B -> Prop) : (stack A -> Prop) :=
  match fuel with
  | 0 => fun _ => False
  | S fuel =>
    match i, input with
    | FAILWITH, _ => False
    | SEQ B C, input => wp B fuel (wp C fuel post) input
    | IF bt bf, (b, input) =>
      if b then wp bt fuel post input
      else wp bf fuel post input
    | LOOP body, (b, input) =>
      if b then wp (SEQ body (LOOP body)) fuel post input
      else post input
    | ...
```


Correctness of wp

```
Lemma wp_correct {A B} (i : instruction A B)
  fuel (post : stack B -> Prop) (input : stack A) :
  wp i fuel psi input <->
    exists output,
      eval i fuel input = Return _ output /\ psi output.
Proof. ... Qed.
```

Proven smart contracts

- Vote example
- Default "manager" smart contract
- Multisig
 - n persons share the ownership of the contract.
 - they agree on a threshold t (an integer).
 - to do anything with the contract, at least t owners must agree.
 - possible actions:
 - transfer from the multisig contract to somewhere else
 - change the list of owners and the threshold

Conclusion

- The Michelson smart-contract language is formalized in Coq.
- This formalisation can be used to prove interesting Michelson smart-contracts.

Ongoing and Future Work

- certify compilers to Michelson
- formalize the Michelson cost model
- use code extraction to replace the current GADT-based implementation in OCaml
- formalize the contract life, mutual and recursive calls
- implement serialisation and cryptography

Thank you!

- Tezos
<https://gitlab.com/tezos/tezos>
- Mi-Cho-Coq
<https://gitlab.com/nomadic-labs/mi-cho-coq/>
- Multisig contract in Michelson
<https://github.com/murbard/smart-contracts/blob/master/multisig/michelson/multisig.tz>
- Multisig proof
https://gitlab.com/nomadic-labs/mi-cho-coq/blob/master/src/contracts_coq/multisig.v




La Pile qui Chante

Mutlisig Specification

```
Definition multisig_spec
  (counter : N)
  (action : data action_ty)
  (sigs : Datatypes.list (Datatypes.option (data sign)))
  (stored_counter : N)
  (threshold : N)
  (keys : Datatypes.list (data key))
  (new_stored_counter : N)
  (new_threshold : N)
  (new_keys : Datatypes.list (data key))
  (returned_operations : Datatypes.list (data operation)) :
let params : data parameter_ty := ((counter, action), sigs)
let storage : data storage_ty := (stored_counter, (threshold,
counter = stored_counter /\
exists first_sigs remaining_sigs,
  sigs = (first_sigs ++ remaining_sigs)%list /\
length first_sigs = length keys /\
```

Mutlisig Specification



```
check_all_signatures
  first_sigs keys
  (fun k sig =>
    check_signature
      env k sig
      (pack env pack_ty ((chain_id_ env, address_ env ST.self
                           (counter, action)))) /\
(count_signatures first_sigs >= threshold)%N /\
new_stored_counter = (1 + stored_counter)%N /\
```



La Pile qui Chante

Mutlisig Specification

```
match action with
| inl (amout, contr) =>
  new_threshold = threshold /\
  new_keys = keys /\
  returned_operations = (transfer_tokens env unit tt amout con
| inr (inl kh) =>
  new_threshold = threshold /\
  new_keys = keys /\
  returned_operations = (set_delegate env kh :: nil)%list
| inr (inr (nt, nks)) =>
  new_threshold = nt /\
  new_keys = nks /\
  returned_operations = nil
end.
```

La Pile qui Chante