Nama   : Septiandi Nugraha
NIM   : 21104060
Kelas   : S1SE 05 B
Mata Kuliah   : Basis Data

1. Nama database yaitu

```
CREATE DATABASE db_tokokaka;
      ▷ Execute
      DEFAULT CHARACTER SET = 'utf8mb4';
```

2. Tabel store_information

```
▷ Execute
CREATE TABLE Store_Information(
    Store_Name VARCHAR(30),
    Sales INT,
    Txn_Date VARCHAR(30)
);

▷ Execute
INSERT INTO Store_Information
VALUES ('Los Angeles', 1500, 'Jan-05-1999'),
       ('San Diego', 250, 'Jan-07-1999'),
       ('Los Angeles', 300, 'Jan-08-1999'),
       ('Boston', 700, 'Jan-08-1999');

▷ Execute
SELECT * FROM Store_Information;
```

Store_Information ×

SELECT * FROM Store_Information

Q Input to filter result

Cost: 61ms <   1   > Total 4

		Store_Name varchar(30)	Sales int	Txn_Date varchar(30)
	1	Los Angeles	1500	Jan-05-1999
	2	San Diego	250	Jan-07-1999
	3	Los Angeles	300	Jan-08-1999
	4	Boston	700	Jan-08-1999

3. Tabel geography

```
▷ Execute
CREATE TABLE Geography(
    Region_Name VARCHAR(15),
    Store_Name VARCHAR(15)
);

▷ Execute
INSERT INTO Geography
VALUES ('East', 'Boston'),
       ('East', 'New York'),
       ('West', 'Los Angeles'),
       ('West', 'San Diego');

▷ Execute
SELECT * FROM Geography;
```

Cost: 343ms < 1 > Total 4

	Region_Name varchar(15)	Store_Name varchar(15)
1	East	Boston
2	East	New York
3	West	Los Angeles
4	West	San Diego

4. SQL Join
   a. Query Multi Table

```
SELECT A1.Region_Name REGION,
SUM(A2.Sales) SALES
FROM Geography A1, Store_Information A2
WHERE A1.Store_Name = A2.Store_Name
GROUP BY A1.Region_Name
```

Cost: 120ms < 1 > Total 2

	REGION varchar	SALES newdecimal
1	East	700
2	West	2050

   b. SQL Join

```
SELECT A1.Region_Name REGION,
SUM(A2.Sales) SALES
FROM Geography A1
JOIN Store_Information A2
ON A1.Store_Name = A2.Store_Name
GROUP BY A1.Region_Name
```

Cost: 100ms < 1 > Total 2

		REGION varchar	SALES newdecimal
	1	East	700
	2	West	2050

c. Inner Join

```
SELECT A1.Store_Name STORE,
SUM(A2.Sales) SALES
FROM Geography A1
INNER JOIN Store_Information A2
ON A1.Store_Name = A2.Store_Name
GROUP BY A1.Store_Name
```

Cost: 65ms < 1 > Total 3

		STORE varchar	SALES newdecimal
	1	Boston	700
	2	Los Angeles	1800
	3	San Diego	250

5. Outer Join
   a. Left Outer Join

```
SELECT A1.Store_Name STORE,
SUM(A2.Sales) SALES
FROM Geography A1
LEFT OUTER JOIN Store_Information A2
ON A1.Store_Name = A2.Store_Name
GROUP BY A1.Store_Name
```

Cost: 83ms < 1 > Total 4

		STORE varchar	SALES newdecimal
	1	Boston	700
	2	Los Angeles	1800
	3	New York	(NULL)
	4	San Diego	250