

Swagger Petstore - OpenAPI 3.0

Version: 1.0.11

OpenAPI2LaTeX Generator

September 27, 2025

Contents

1	Information	1
1.1	Other Information	1
I	Endpoints	3
2	pet	4
2.1	Add a new pet to the store	4
2.1.1	Request Body	4
2.1.2	Responses	5
2.2	Update an existing pet	5
2.2.1	Request Body	5
2.2.2	Responses	6
2.3	Finds Pets by status	6
2.3.1	Parameters	6
2.3.2	Responses	6
2.4	Finds Pets by tags	7
2.4.1	Parameters	7
2.4.2	Responses	7
2.5	Updates a pet in the store with form data	8
2.5.1	Parameters	8
2.5.2	Responses	8
2.6	Find pet by ID	9
2.6.1	Parameters	9
2.6.2	Responses	9
2.7	Deletes a pet	9
2.7.1	Parameters	10
2.7.2	Responses	10
2.8	uploads an image	10
2.8.1	Parameters	11
2.8.2	Request Body	11
2.8.3	Responses	11
3	store	12
3.1	Returns pet inventories by status	12
3.1.1	Responses	12
3.2	Place an order for a pet	13

3.2.1	Request Body	13
3.2.2	Responses	13
3.3	Find purchase order by ID	13
3.3.1	Parameters	14
3.3.2	Responses	14
3.4	Delete purchase order by ID	14
3.4.1	Parameters	14
3.4.2	Responses	15
4	user	16
4.1	Create user	16
4.1.1	Request Body	16
4.1.2	Responses	17
4.2	Creates list of users with given input array	17
4.2.1	Request Body	17
4.2.2	Responses	17
4.3	Logs user into the system	18
4.3.1	Parameters	18
4.3.2	Responses	18
4.4	Logs out current logged in user session	19
4.4.1	Responses	19
4.5	Update user	19
4.5.1	Parameters	19
4.5.2	Request Body	19
4.5.3	Responses	20
4.6	Get user by user name	20
4.6.1	Parameters	20
4.6.2	Responses	20
4.7	Delete user	21
4.7.1	Parameters	21
4.7.2	Responses	21
II	Schemas	22
5	Address	23
5.1	city	23
5.2	state	23
5.3	street	23
5.4	zip	24
6	ApiResponse	25
6.1	code	25
6.2	message	25
6.3	type	25
7	Category	26

7.1	id	26
7.2	name	26
8	Order	27
8.1	complete	27
8.2	id	27
8.3	petId	27
8.4	quantity	28
8.5	shipDate	28
8.6	status	28
9	Pet	29
9.1	category	29
9.2	id	29
9.3	name	29
9.4	photoUrls	30
9.5	status	30
9.6	tags	30
10	Tag	31
10.1	id	31
10.2	name	31
11	User	32
11.1	email	32
11.2	firstName	32
11.3	id	32
11.4	lastName	33
11.5	password	33
11.6	phone	33
11.7	userStatus	33
11.8	username	34

Chapter 1

Information

This is a sample Pet Store Server based on the OpenAPI 3.0 specification. You can find out more about Swagger at <https://swagger.io>. In the third iteration of the pet store, we've switched to the design first approach! You can now help us improve the API whether it's by making changes to the definition itself or to the code. That way, with time, we can improve the API in general, and expose some of the new features in OAS3.

*If you're looking for the Swagger 2.0/OAS 2.0 version of Petstore, then click [here](#). Alternatively, you can load via the *Edit > Load Petstore OAS 2.0* menu option!*

Some useful links:

- [The Pet Store repository](#)
- [The source API definition for the Pet Store](#)

1.1 Other Information

Table 1.1: API Information

Terms Of Service	http://swagger.io/terms/
Version	1.0.11
License	Apache 2.0

Table 1.2: Server Information

	https://petstore3.swagger.io/api/v3
--	---

Table 1.3: Security Schemes

api_{key}	Type	apiKey
	Name	api_key
	In	header
	Type	oauth2

petstore_{auth}

Part I

Endpoints

Chapter 2

pet

Everything about your Pets

2.1 Add a new pet to the store

Resource Path	/pet
HTTP Method	POST
	https://petstore3.swagger.io/api/v3
Security	petstore_auth ^a

^aSee table 1.3 on page 2

Add a new pet to the store

2.1.1 Request Body

Create a new pet in the store

Table 2.1: Request body for addPet

Property	Value
Required	true
Content	application/json Pet. See chapter 9 on page 29. application/x-www-form-urlencoded Pet. See chapter 9 on page 29. application/xml Pet. See chapter 9 on page 29.

2.1.2 Responses

See table 2.2 for response codes and data.

Table 2.2: Responses for addPet

Code	Content Type	Notes
200	application/json	Pet. See chapter 9 on page 29 for schema.
200	application/xml	Pet. See chapter 9 on page 29 for schema.

2.2 Update an existing pet

Resource Path	/pet
HTTP Method	PUT
	https://petstore3.swagger.io/api/v3
Security	petstore_auth ^a

^aSee table 1.3 on page 2

Update an existing pet by Id

2.2.1 Request Body

Update an existent pet in the store

Table 2.3: Request body for updatePet

Property	Value
Required	true
Content	application/json Pet. See chapter 9 on page 29. application/x-www-form-urlencoded Pet. See chapter 9 on page 29. application/xml Pet. See chapter 9 on page 29.
continued on next page	

continued from previous page

2.2.2 Responses

See table 2.4 for response codes and data.

Table 2.4: Responses for updatePet

Code	Content Type	Notes
200	application/json	Pet. See chapter 9 on page 29 for schema.
200	application/xml	Pet. See chapter 9 on page 29 for schema.

2.3 Finds Pets by status

Resource Path	/pet/findByStatus
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	petstore_auth ^a

^aSee table 1.3 on page 2

Multiple status values can be provided with comma separated strings

2.3.1 Parameters

- **status** Status values that need to be considered for filter

in - query

required - false

explode - true

schema

type - string

default - available

2.3.2 Responses

See table 2.5 for response codes and data.

Table 2.5: Responses for findPetsByStatus

Code	Content Type	Notes
200	application/json	successful operation
200	application/xml	successful operation

2.4 Finds Pets by tags

Resource Path	/pet/findByTags
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	petstore_auth ^a

^aSee table 1.3 on page 2

Multiple tags can be provided with comma separated strings. Use tag1, tag2, tag3 for testing.

2.4.1 Parameters

- **tags** Tags to filter by

in - query

required - false

explode - true

schema

type - array

2.4.2 Responses

See table 2.6 for response codes and data.

Table 2.6: Responses for findPetsByTags

Code	Content Type	Notes
200	application/json	successful operation
200	application/xml	successful operation

2.5 Updates a pet in the store with form data

Resource Path	/pet/{petId}
HTTP Method	POST
	https://petstore3.swagger.io/api/v3
Security	petstore_auth ^a

^aSee table 1.3 on page 2

2.5.1 Parameters

- **petId** ID of pet that needs to be updated

in - path

required - true

schema

type - integer

format - int64

- **name** Name of pet that needs to be updated

in - query

required - false

schema

type - string

- **status** Status of pet that needs to be updated

in - query

required - false

schema

type - string

2.5.2 Responses

See table 2.7 for response codes and data.

Table 2.7: Responses for updatePetWithForm

Code	Content Type	Notes
------	--------------	-------

2.6 Find pet by ID

Resource Path	/pet/{petId}
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	api_key, petstore_auth ^a

^aSee table 1.3 on page 2

Returns a single pet

2.6.1 Parameters

- **petId** ID of pet to return

in - path

required - true

schema

type - integer

format - int64

2.6.2 Responses

See table 2.8 for response codes and data.

Table 2.8: Responses for getPetById

Code	Content Type	Notes
200	application/json	Pet. See chapter 9 on page 29 for schema.
200	application/xml	Pet. See chapter 9 on page 29 for schema.

2.7 Deletes a pet

Resource Path	/pet/{petId}
HTTP Method	DELETE
	https://petstore3.swagger.io/api/v3
Security	petstore_auth ^a

^aSee table 1.3 on page 2

delete a pet

2.7.1 Parameters

- **api_{key}**
 - *in* - header
 - *required* - false
 - *schema*
 - type* - string

petId Pet id to delete

in - path
required - true
schema
type - integer
format - int64

2.7.2 Responses

See table 2.9 for response codes and data.

Table 2.9: Responses for deletePet

Code	Content Type	Notes
------	--------------	-------

2.8 uploads an image

Resource Path	/pet/{petId}/uploadImage
HTTP Method	POST
Security	https://petstore3.swagger.io/api/v3 petstore_auth ^a

^aSee table 1.3 on page 2

2.8.1 Parameters

- **petId** ID of pet to update

in - path

required - true

schema

type - integer

format - int64

- **additionalMetadata** Additional Metadata

in - query

required - false

schema

type - string

2.8.2 Request Body

Table 2.10: Request body for uploadFile

Property	Value
Required	false
Content	application/octet-stream

2.8.3 Responses

See table 2.11 for response codes and data.

Table 2.11: Responses for uploadFile

Code	Content Type	Notes
200	application/json	ApiResponse . See chapter 6 on page 25 for schema.

Chapter 3

store

Access to Petstore orders

3.1 Returns pet inventories by status

Resource Path	/store/inventory
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	api_key ^a

^aSee table 1.3 on page 2

Returns a map of status codes to quantities

3.1.1 Responses

See table 3.1 for response codes and data.

Table 3.1: Responses for getInventory

Code	Content Type	Notes
200	application/json	successful operation

3.2 Place an order for a pet

Resource Path	/store/order
HTTP Method	POST
	https://petstore3.swagger.io/api/v3
Security	None

Place a new order in the store

3.2.1 Request Body

Table 3.2: Request body for placeOrder

Property	Value
Required	false
Content	application/json Order. See chapter 8 on page 27. application/x-www-form-urlencoded Order. See chapter 8 on page 27. application/xml Order. See chapter 8 on page 27.

3.2.2 Responses

See table 3.3 for response codes and data.

Table 3.3: Responses for placeOrder

Code	Content Type	Notes
200	application/json	Order. See chapter 8 on page 27 for schema.

3.3 Find purchase order by ID

Resource Path	/store/order/{orderId}
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	None

For valid response try integer IDs with value $j=5$ or $j=10$. Other values will generate exceptions.

3.3.1 Parameters

- **orderId** ID of order that needs to be fetched

in - path

required - true

schema

type - integer

format - int64

3.3.2 Responses

See table 3.4 for response codes and data.

Table 3.4: Responses for getOrderById

Code	Content Type	Notes
200	application/json	Order . See chapter 8 on page 27 for schema.
200	application/xml	Order . See chapter 8 on page 27 for schema.

3.4 Delete purchase order by ID

Resource Path	/store/order/{orderId}
HTTP Method	DELETE
	https://petstore3.swagger.io/api/v3
Security	None

For valid response try integer IDs with value ; 1000. Anything above 1000 or nonintegers will generate API errors

3.4.1 Parameters

- **orderId** ID of the order that needs to be deleted

in - path

required - true

schema

type - integer

format - int64

3.4.2 Responses

See table 3.5 for response codes and data.

Table 3.5: Responses for deleteOrder

Code	Content Type	Notes
------	--------------	-------

Chapter 4

user

Operations about user

4.1 Create user

Resource Path	/user
HTTP Method	POST
	https://petstore3.swagger.io/api/v3
Security	None

This can only be done by the logged in user.

4.1.1 Request Body

Created user object

Table 4.1: Request body for createUser

Property	Value
Required	false
Content	application/json User. See chapter 11 on page 32. application/x-www-form-urlencoded User. See chapter 11 on page 32. application/xml User. See chapter 11 on page 32.
continued on next page	

continued from previous page

4.1.2 Responses

See table 4.2 for response codes and data.

Table 4.2: Responses for createUser

Code	Content Type	Notes
default	application/json	User . See chapter 11 on page 32 for schema.
default	application/xml	User . See chapter 11 on page 32 for schema.

4.2 Creates list of users with given input array

Resource Path	/user/createWithList
HTTP Method	POST
	https://petstore3.swagger.io/api/v3
Security	None

Creates list of users with given input array

4.2.1 Request Body

Table 4.3: Request body for createUsersWithListInput

Property	Value
Required	false
Content	application/json

4.2.2 Responses

See table 4.4 for response codes and data.

Table 4.4: Responses for createUsersWithListInput

Code	Content Type	Notes
200	application/json	User . See chapter 11 on page 32 for schema.
200	application/xml	User . See chapter 11 on page 32 for schema.
continued on next page		

continued from previous page

4.3 Logs user into the system

Resource Path	/user/login
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	None

4.3.1 Parameters

- **username** The user name for login

in - query

required - false

schema

type - string

- **password** The password for login in clear text

in - query

required - false

schema

type - string

4.3.2 Responses

See table 4.5 for response codes and data.

Table 4.5: Responses for loginUser

Code	Content Type	Notes
200	application/json	successful operation
200	application/xml	successful operation

4.4 Logs out current logged in user session

Resource Path	/user/logout
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	None

4.4.1 Responses

See table 4.6 for response codes and data.

Table 4.6: Responses for logoutUser

Code	Content Type	Notes
------	--------------	-------

4.5 Update user

Resource Path	/user/{username}
HTTP Method	PUT
	https://petstore3.swagger.io/api/v3
Security	None

This can only be done by the logged in user.

4.5.1 Parameters

- **username** name that need to be deleted

in - path

required - true

schema

type - string

4.5.2 Request Body

Update an existent user in the store

Table 4.7: Request body for updateUser

Property	Value
Required	false
Content	application/json User. See chapter 11 on page 32. application/x-www-form-urlencoded User. See chapter 11 on page 32. application/xml User. See chapter 11 on page 32.

4.5.3 Responses

See table 4.8 for response codes and data.

Table 4.8: Responses for updateUser

Code	Content Type	Notes
------	--------------	-------

4.6 Get user by user name

Resource Path	/user/{username}
HTTP Method	GET
	https://petstore3.swagger.io/api/v3
Security	None

4.6.1 Parameters

- **username** The name that needs to be fetched. Use user1 for testing.

in - path

required - true

schema

type - string

4.6.2 Responses

See table 4.9 for response codes and data.

Table 4.9: Responses for getUserByName

Code	Content Type	Notes
200	application/json	User. See chapter 11 on page 32 for schema.
200	application/xml	User. See chapter 11 on page 32 for schema.

4.7 Delete user

Resource Path	/user/{username}
HTTP Method	DELETE
	https://petstore3.swagger.io/api/v3
Security	None

This can only be done by the logged in user.

4.7.1 Parameters

- **username** The name that needs to be deleted

in - path

required - true

schema

type - string

4.7.2 Responses

See table 4.10 for response codes and data.

Table 4.10: Responses for deleteUser

Code	Content Type	Notes
------	--------------	-------

Part II

Schemas

Chapter 5

Address

5.1 city

Table 5.1: Properties for Address::city

Property	Value
Type	string
Required	false
Example	Palo Alto.

5.2 state

Table 5.2: Properties for Address::state

Property	Value
Type	string
Required	false
Example	CA.

5.3 street

Table 5.3: Properties for Address::street

Property	Value
Type	string
Required	false
continued on next page	

continued from previous page	
Example	437 Lytton.

5.4 zip

Table 5.4: Properties for Address::zip

Property	Value
Type	string
Required	false
Example	94301.

Chapter 6

ApiResponse

6.1 code

Table 6.1: Properties for ApiResponse::code

Property	Value
Type	integer
Required	false
Format	int32.

6.2 message

Table 6.2: Properties for ApiResponse::message

Property	Value
Type	string
Required	false

6.3 type

Table 6.3: Properties for ApiResponse::type

Property	Value
Type	string
Required	false

Chapter 7

Category

7.1 id

Table 7.1: Properties for Category::id

Property	Value
Type	integer
Required	false
Format	int64.
Example	1.

7.2 name

Table 7.2: Properties for Category::name

Property	Value
Type	string
Required	false
Example	Dogs.

Chapter 8

Order

8.1 complete

Table 8.1: Properties for Order::complete

Property	Value
Type	<code>boolean</code>
Required	false

8.2 id

Table 8.2: Properties for Order::id

Property	Value
Type	<code>integer</code>
Required	false
Format	int64.
Example	10.

8.3 petId

Table 8.3: Properties for Order::petId

Property	Value
Type	<code>integer</code>
Required	false
continued on next page	

continued from previous page	
Format	int64.
Example	198772.

8.4 quantity

Table 8.4: Properties for Order::quantity

Property	Value
Type	integer
Required	false
Format	int32.
Example	7.

8.5 shipDate

Table 8.5: Properties for Order::shipDate

Property	Value
Type	string
Required	false
Format	date-time.

8.6 status

Order Status

Table 8.6: Properties for Order::status

Property	Value
Type	string
Required	false
Example	approved.

Chapter 9

Pet

9.1 category

Table 9.1: Properties for Pet::category

Property	Value
Type	object
Required	false
Reference	See chapter 7 on page 26.

9.2 id

Table 9.2: Properties for Pet::id

Property	Value
Type	integer
Required	false
Format	int64.
Example	10.

9.3 name

Table 9.3: Properties for Pet::name

Property	Value
Type	string
continued on next page	

continued from previous page	
Required	false
Example	doggie.

9.4 photoUrls

Table 9.4: Properties for Pet::photoUrls

Property	Value
Type	array
Required	false
Schema	

9.5 status

pet status in the store

Table 9.5: Properties for Pet::status

Property	Value
Type	string
Required	false

9.6 tags

Table 9.6: Properties for Pet::tags

Property	Value
Type	array
Required	false
Reference	See section 10 on page 31.

Chapter 10

Tag

10.1 id

Table 10.1: Properties for Tag::id

Property	Value
Type	integer
Required	false
Format	int64.

10.2 name

Table 10.2: Properties for Tag::name

Property	Value
Type	string
Required	false

Chapter 11

User

11.1 email

Table 11.1: Properties for User::email

Property	Value
Type	string
Required	false
Example	john@email.com.

11.2 firstName

Table 11.2: Properties for User::firstName

Property	Value
Type	string
Required	false
Example	John.

11.3 id

Table 11.3: Properties for User::id

Property	Value
Type	integer
Required	false
continued on next page	

continued from previous page	
Format	int64.
Example	10.

11.4 lastName

Table 11.4: Properties for User::lastName

Property	Value
Type	string
Required	false
Example	James.

11.5 password

Table 11.5: Properties for User::password

Property	Value
Type	string
Required	false
Example	12345.

11.6 phone

Table 11.6: Properties for User::phone

Property	Value
Type	string
Required	false
Example	12345.

11.7 userStatus

User Status

Table 11.7: Properties for User::userStatus

Property	Value
Type	integer
Required	false
Format	int32.
Example	1.

11.8 username

Table 11.8: Properties for User::username

Property	Value
Type	string
Required	false
Example	theUser.

List of Tables

1.1	API Information	1
1.2	Server Information	1
1.3	Security Schemes	2
2.1	Request body for addPet	4
2.2	Responses for addPet	5
2.3	Request body for updatePet	5
2.4	Responses for updatePet	6
2.5	Responses for findPetsByStatus	6
2.6	Responses for findPetsByTags	7
2.7	Responses for updatePetWithForm	8
2.8	Responses for getPetById	9
2.9	Responses for deletePet	10
2.10	Request body for uploadFile	11
2.11	Responses for uploadFile	11
3.1	Responses for getInventory	12
3.2	Request body for placeOrder	13
3.3	Responses for placeOrder	13
3.4	Responses for getOrderById	14
3.5	Responses for deleteOrder	15
4.1	Request body for createUser	16
4.2	Responses for createUser	17
4.3	Request body for createUsersWithListInput	17
4.4	Responses for createUsersWithListInput	17
4.5	Responses for loginUser	18
4.6	Responses for logoutUser	19
4.7	Request body for updateUser	19
4.8	Responses for updateUser	20
4.9	Responses for getUserByName	20
4.10	Responses for deleteUser	21
5.1	Properties for Address::city	23
5.2	Properties for Address::state	23
5.3	Properties for Address::street	23
5.4	Properties for Address::zip	24

6.1	Properties for ApiResponse::code	25
6.2	Properties for ApiResponse::message	25
6.3	Properties for ApiResponse::type	25
7.1	Properties for Category::id	26
7.2	Properties for Category::name	26
8.1	Properties for Order::complete	27
8.2	Properties for Order::id	27
8.3	Properties for Order::petId	27
8.4	Properties for Order::quantity	28
8.5	Properties for Order::shipDate	28
8.6	Properties for Order::status	28
9.1	Properties for Pet::category	29
9.2	Properties for Pet::id	29
9.3	Properties for Pet::name	29
9.4	Properties for Pet::photoUrls	30
9.5	Properties for Pet::status	30
9.6	Properties for Pet::tags	30
10.1	Properties for Tag::id	31
10.2	Properties for Tag::name	31
11.1	Properties for User::email	32
11.2	Properties for User::firstName	32
11.3	Properties for User::id	32
11.4	Properties for User::lastName	33
11.5	Properties for User::password	33
11.6	Properties for User::phone	33
11.7	Properties for User::userStatus	33
11.8	Properties for User::username	34

Index

pet, [4](#)

store, [12](#)

user, [16](#)