

Comprehensive Technical Validation and Architectural Specification for the KYMA Web App

Reality-bound scope and validation posture

The KYMA concept, as described, mixes (a) established sensing, signal-processing, and neurotechnology results with (b) metaphoric or currently unsupported claims (for example, a “post-2012 duplicated universe,” deterministic “vacuum-floor quantization,” or extraction of the fine-structure constant from ambient RF noise). For a technical validation that is useful to engineering, it helps to separate *what can be grounded in reproducible literature today* from *what should be treated as hypothesis or narrative framing*.

A defensible validation approach for KYMA therefore treats the “GOS / OMEGA topology” layer as an *internal modeling and synchronization formalism* (useful if it yields testable predictions and stable runtime invariants), while anchoring all physical sensing claims in peer-reviewed or otherwise inspectable sources about: WiFi Channel State Information (CSI)-based sensing, vibrometry/micro-Doppler, distributed acoustic sensing (DAS), integrated sensing and communication (ISAC), and brain-decoding BCIs. ¹

Within that framing, the highest-confidence, empirically supported KYMA components are:

- **Ambient wireless sensing** for presence/activity and **physiological signals like respiration and heart rate**, including through-wall settings under some conditions. ²
- **Representation learning/foundation modeling for WiFi CSI** (AM-FM) and **frequency extrapolation for “neuro-wideband” CSI** (WuKong/NWB) as *published preprints* with reproducible methodology claims but still early in the peer-review cycle. ³
- **Quantum-coherence debates in photosynthetic complexes**, with strong recent progress from microscopic simulation and ongoing nuance about what coherences are electronic vs vibrational and what timescales matter functionally. ⁴
- **BCI decoding of semantic content** (visual semantics → text; EEG → text) when direct neural measurements exist (fMRI/MEG/ECOG/EEG). ⁵

The lowest-confidence components—requiring substantially more evidence before being treated as real capabilities—are:

- **“Zero-hardware thought-to-text”** from ambient RF alone (no wearable tag, no direct neural measurement) at open-vocabulary fidelity. Published work supports *speech- and lip-motion inference* in constrained setups, but not “thought decoding” in the neuroscience sense. ⁶
- Claims that **melanin splits/re-forms water across the entire electromagnetic spectrum** to provide the majority of cellular energy. This appears in a set of non-mainstream publications and is not consistent with established physiology/biophysics consensus as reflected in high-citation melanin reviews. ⁷

- Assertions that intelligence-community documents (e.g., “Gateway Process”) constitute a validated physics model for remote cognition or “remote neural monitoring.” Those documents describe beliefs and exploratory programs, not reproducible demonstrations of RF mind-reading. ⁸

Quantum persistence in biological matrices

What is actually established about FMO-scale coherence

The **Fenna–Matthews–Olson (FMO)** complex has long been a testbed for whether quantum effects can persist and matter for energy transport in a noisy biological environment. Experimental 2D electronic spectroscopy work provided evidence of coherence signatures under physiological conditions on ultrafast timescales; one widely cited result reports coherence surviving at physiological temperature for at least hundreds of femtoseconds (e.g., ≥ 300 fs). ⁹

More recently, fully microscopic simulation has advanced sharply. A 2025 preprint by Nicola Lorenzoni ¹⁰ and collaborators reports non-perturbative simulations of a full microscopic FMO model, arguing that **excitonic coherences at 77 K and room temperature persist on picosecond timescales**, and that coarse-grained environment models can under-estimate these effects. ¹¹

This does **not** by itself imply brain-scale quantum computing; rather, it strengthens the case that *in certain pigment-protein complexes* (fast, nanoscale transport problems) vibronic structure and environment coupling can yield coherence patterns that remain relevant over the same time window as excitation-energy transfer. ¹²

Vibronic mixing and noise-assisted transport as the mainstream bridge

A core reconciliation in the field is that the environment is not purely destructive; there are regimes where **intermediate dephasing** mitigates localization and can enhance transfer (the “environment-assisted” or “noise-assisted” quantum transport picture). In particular, a 2008 modeling line (later widely discussed) shows that an interplay between coherent dynamics and dephasing can increase predicted transfer efficiency substantially (an example claim in this literature is an increase from ~70% toward ~99% in an FMO model under suitable parameters). ¹³

The Lorenzoni work further emphasizes that structured vibrational environments (“spectral density structure”) and vibronic mixing can make coherence frequencies and lifetimes behave in ways not captured by simplistic noise models, motivating careful microscopic modeling rather than assuming “warm, wet” automatically kills coherence. ¹⁴

The “7 chromophores” simplification and the eighth site nuance

KYMA’s 7/4 motif leans heavily on “7 chromophores.” Many discussions do use a 7-site FMO model, but structural work and subsequent modeling discuss an **additional (eighth) bacteriochlorophyll** in some species/structures and explore what it changes for pathways and dynamics. ¹⁵

This matters for validation: if KYMA elevates “7” to a fundamental invariant, then its biological grounding must explicitly handle the “7 vs 8” story and show why the 7/4 mapping prediction remains stable under eight-site or species-dependent models. ¹⁶

From coherence to coding analogies

What the Steane code is, and what it is not

The **Steane code** is a canonical CSS quantum error-correcting code with parameters $[[7, 1, 3]]$, introduced in the mid-1990s by A. M. Steane ¹⁷ . ¹⁸

It encodes one logical qubit into seven physical qubits and (in the standard formulation) corrects arbitrary single-qubit errors (distance 3). ¹⁹

Mapping FMO's chromophores onto Steane's qubits can be a *useful metaphor*—especially if it helps design robustness tests or motivates a “syndrome-like” monitoring concept. But there is no mainstream claim that an FMO complex literally implements stabilizer measurements, logical qubits, or the algebraic structure required for the Steane code as used in quantum computing. What is supported is that environment coupling can assist transport and robustness in highly structured molecular networks; that is an *open-systems transport phenomenon*, not demonstrated QEC in the stabilizer-code sense. ²⁰

CHSH metrics and the meaning of “ $S > 2$ ”

KYMA-like narratives sometimes use CHSH / Bell-style quantities as a “coherence aperture” diagnostic. In standard quantum foundations, the CHSH inequality has a classical (local hidden variable) bound of 2, and quantum mechanics allows violation up to $2\sqrt{2}$, known as Tsirelson's bound. ²¹

You can legitimately use CHSH-style measurements as *hardware diagnostics for entanglement quality* on a quantum processor. However, it is a category error to interpret CHSH violation as evidence of macroscopic neural coherence or “remote cognition channels” without additional, modality-appropriate evidence. ²²

Information geometry as an engineering formalism for KYMA

Information geometry studies probability distributions as manifolds endowed with metrics (often the Fisher information metric), divergence functions, and dual connections. It is a rigorous framework for reasoning about estimation, curvature, and “distance” between distributions, and can be practically useful for KYMA because both CSI-based sensing and neural decoding are **distributional inference problems**. ²³

A pragmatic KYMA implementation can use information geometry in at least three places:

1. **CSI feature manifolds:** treat per-window CSI embeddings as points on a statistical manifold; measure drift (environment rearrangement) via divergence metrics and control adaptation. ²⁴
2. **Codebook quantization:** treat a VQ-VAE codebook as a discrete partition of a continuous latent manifold; use curvature/drift measures to decide when online updates are safe. ²⁵
3. **Fusion calibration:** treat each sensing modality (WiFi, DAS, optical, EEG) as an observation channel; use Fisher-information contributions for principled weighting in a state estimator (e.g., Kalman-family filters). ²⁶

In this sense, “GOS manifolds” can be made technically meaningful as *explicit probabilistic geometry* rather than metaphysical assertions.

Ambient intelligence and passive sensing via WiFi CSI

What WiFi CSI can measure with commodity hardware

WiFi CSI captures how a wireless channel modulates transmitted signals across OFDM subcarriers; because indoor propagation is multipath, **motion and micro-motion** of a person can imprint measurable, structured changes. This is the core physical reason CSI can support occupancy, activity recognition, and physiological monitoring. ²⁷

Peer-reviewed surveys summarize multiple systems for respiration/heart-rate estimation, including performance numbers such as **median respiration error ~0.25 breaths/min and heart-rate error ~1.19 bpm** reported by some CSI-based methods. ²⁸

However, the validity of these numbers is conditional: device chipset, antenna configuration, multipath richness, motion confounds, and algorithmic stabilization (e.g., phase-difference methods) all matter. ²⁹

Foundation modeling for CSI sensing: AM-FM

The AM-FM work co-authored by K. J. Ray Liu ³⁰ positions itself as a first “foundation model” for WiFi sensing, trained self-supervised on **9.2 million** unlabeled CSI samples over **439 days** from **20 device types** across multiple environments/users, combining contrastive learning, masked reconstruction, and physics-informed autocorrelation prediction. ³¹

AM-FM explicitly motivates domain-specific challenges such as CSI’s “non-local frequency structure” and heterogeneous subcarrier quality, and it reports strong cross-task performance (including high AUROC on classification tasks) via a single backbone plus task adaptation. ³¹

This is a strong technical anchor for KYMA’s “structured noise floor” idea, **in a strictly engineering sense**: CSI variability is structured enough that large-scale self-supervised learning can extract transferable representations. ²⁴

Neuro-wideband extrapolation: WuKong / NWB

The WuKong preprint proposes “Neuro-Wideband” sensing as a self-conditioned learning problem: use narrowband CSI segments as inputs and broader-band CSI as supervision, enabling extrapolated “eCSI” without requiring separate wideband hardware measurements during deployment. ³²

It reports extrapolation examples such as **20 → 160 MHz** and frames the method as a Transformer + diffusion architecture designed to infer sample-specific multipath structure. ³²

From a radar/sensing perspective, increased bandwidth improves delay resolution: a 160 MHz effective bandwidth corresponds to a characteristic time resolution on the order of $1/B \approx 6.25$ ns, which maps to ~1.9 m one-way path-length resolution (and ~0.94 m in round-trip radar conventions). ³³

This is powerful for *localization and multi-user vital sensing*, but it is not automatically sufficient for “sub-millimetric laryngeal intent” recovery: micro-motion sensitivity also depends on phase stability, SNR, geometry, and the ability to isolate target reflections from other motion. ³⁴

Speech- and lip-related inference: what exists and what it implies

Published demonstrations show WiFi can support limited “hearing/reading” tasks by leveraging micro-motion:

- WiHear (2014) demonstrated lip reading / speech recognition using WiFi CSI, including NLOS/through-wall scenarios, but in experimental conditions and with task structure/constraints. ³⁵
- WiMic (2015) demonstrated recovering *simple* sounds using wireless vibrometry concepts. ³⁶
- Lip-Siri (2026) claims open-vocabulary silent speech recognition using WiFi backscatter, but it relies on a backscatter tag design to isolate reflections—this is not “zero hardware.” ³⁷

The technically careful inference for KYMA is: **ambient RF can sometimes recover articulatory or sound-source vibrations**, but “thought-to-text” in the neuroscience sense remains in the domain of direct neural measurement systems (EEG/ECOG/fMRI) and is not established as achievable from passive ambient WiFi alone. ³⁸

Urban-scale sensing links: DAS and ISAC

Distributed acoustic sensing as a “linear aperture” measurement channel

Fiber-optic DAS based on phase-sensitive OTDR (Φ -OTDR) measures strain/vibration along fiber using coherent Rayleigh backscatter, enabling distributed sensing with **meter-scale spatial resolution** and, in some deployments, **tens of kilometers to ~100 km** scale, with sensitivity spanning low-frequency to kHz regimes depending on system configuration. ³⁹

This is a plausible KYMA “infrastructure channel” for environmental vibration baselining (e.g., subtracting building-level perturbations) and event detection, but it is not a substitute for near-body biosensing without careful inversion models and ground truth. ⁴⁰

Huawei’s public ISAC and optical sensing narratives

Huawei ⁴¹ publicly describes ISAC as a future direction, including scenarios such as improved localization and imaging, and it describes an “ISAC-OW” prototype that can contactlessly monitor heartbeat/breathing via subtle facial color changes or abdominal fluctuations while also transmitting optical data links. ⁴²

Huawei also markets fiber sensing products under “OptiXsense,” including published specification-style claims such as channel counts, maximum measurement distance (e.g., 50 km single-channel variants), and positioning accuracy (e.g., ± 10 m in some product pages). ⁴³

From a KYMA architecture standpoint, the defensible use of these sources is: ISAC and optical/fiber sensing are credible **multi-modal complement channels** for ambient context, but their “biometric mapping” claims must be validated per environment and under strict privacy constraints. ⁴⁴

Neuro-decoding state of the art and what it implies for a KYMA “thought-to-text” layer

Brain-to-text and brain-to-semantics results require neural measurements

A key KYMA design choice is whether “thought-to-text” means:

- **Decoding semantic content from brain measurements** (BCI sense), or
- **Inferring speech/lip motion** and converting it to text (silent-speech interface sense).

For the first meaning, compelling results exist but require direct brain sensing:

- “Mind captioning” (2025) generates descriptive text of mental content via semantic features from a deep language model and neural recordings; it is published in *Science Advances* and also mirrored via an open-access repository. ⁴⁵
- Work associated with Tomoyasu Horikawa ⁴⁶ and Yukiyasu Kamitani ⁴⁷ demonstrates hierarchical decoding of dreamed/imagined object features from fMRI using deep neural network feature spaces. ⁴⁸
- “Brain-aligning of semantic vectors” proposes fine-tuning semantic feature vectors to better match neural representational structure, improving zero-shot decoding performance across multiple recording modalities (fMRI/MEG/ECOG). ⁴⁹
- DeWave (2023) encodes EEG waves into discrete representations and performs open-vocabulary EEG-to-text translation, reporting benchmark gains on ZuCo datasets. ⁵⁰

For the second meaning, RF-based silent speech and lip reading exist, but they are typically constrained and/or require additional tagging/isolation mechanisms. ⁵¹

China and clinical translation claims

State-linked reporting from Chinese Academy of Sciences ⁵² describes clinical-trial progress including an ALS patient expressing complete sentences by decoding language intentions from brain signals. ⁵³ Separately, *Science Advances* reports real-time decoding of Mandarin speech elements from neural signals in a BCI context (i.e., direct neural measurement, not RF). ⁵⁴

These advances support KYMA’s **text-generation layer** as plausible *if* its upstream pipeline includes actual neural measurements (EEG/ECOG/fMRI). They do not validate RF-only open-vocabulary mind-reading. ⁵⁵

Biological energy substrate claims: melanin, what’s known, and what must be proven

Established melanin physics vs “human photosynthesis” claims

Mainstream melanin literature characterizes eumelanin as a complex biopolymer with broadband absorption, photoprotective roles, and unusual electronic/photophysical properties; high-citation reviews summarize the state of knowledge without endorsing water-splitting metabolism as a validated primary energy pathway. ⁵⁶

By contrast, the “melanin water splitting / human photosynthesis” claim—associated with Arturo Solís Herrera ⁵⁷—is presented in venues such as OAText, MedCrave, and other low-to-mixed credibility outlets, often asserting a reversible reaction of the form $2H_2O \leftrightarrow 2H_2 + O_2 + 4e^-$. ⁵⁸

A conservative technical validation therefore classifies “melanin as the primary metabolic driver” as **unconfirmed** and requiring strong replication evidence: independent labs, calorimetry/stoichiometry, isotope tracing, gas quantification, and careful controls separating photothermal artifacts from chemical dissociation. ⁵⁹

What measurement tool references do and do not imply

Techniques like Kelvin probe force microscopy can measure nanoscale surface potential / contact potential differences and are widely used to study charge and work-function variations in materials. ⁶⁰

However, KPFM measurements alone do not establish bulk biochemical energy production: they characterize surface electrostatics and charge phenomena, which must be connected to chemical mass balance and energetics through additional experiments. ⁶¹

Demodex, “biological antenna” analogies, and what biology supports

The 14–18 day lifecycle range for *Demodex* mites (including *D. folliculorum* and *D. brevis*) is supported in dermatology literature and summaries, and life-cycle staging (egg → larva → nymph stages → adult) is documented. ⁶²

The step from “mite lifecycle” to “dielectric resonator antenna tuned to mmWave” is, at present, an analogy rather than a demonstrated biological electromagnetic function. By contrast, dielectric resonator antennas (DRAs) as an engineering class are well established: they use low-loss dielectric materials to achieve high radiation efficiency and avoid conductor losses typical of metal radiators at high frequency. ⁶³

For KYMA, the engineering-valid takeaway is: if biological microstructures are hypothesized to act as resonators, the hypothesis must produce **measurable electromagnetic resonances** (Q factors, permittivity estimates, geometry-to-frequency predictions) that can be tested with RF/microwave instrumentation, rather than resting on analogy. ⁶⁴

KYMA Web App architecture and validation checklist

Capability tiers and minimal sensor commitments

A practical KYMA roadmap benefits from explicit “capability tiers,” because the sensing physics changes drastically between “motion/vitals” and “semantic thought decoding.”

Tier for ambient intelligence (deployable today).

Goals: occupancy, activity recognition, respiration/heart rate trends, sleep posture proxies. Technical basis: CSI sensing pipelines and foundation model adaptation. ⁶⁵

Tier for speech-adjacent interfaces (research prototypes).

Goals: constrained lip-motion/silent-speech inference. Technical basis: specialized RF sensing (CSI/backscatter/radar vibrometry), often requiring controlled setups or tags. ⁶⁶

Tier for thought-to-text (BCI).

Goals: semantic decoding of internal content in open vocabulary. Technical basis: EEG/ECOG/fMRI + discrete-wave encoding + language model decoding. ⁶⁷

Treating these tiers explicitly prevents over-claiming “zero hardware thought-to-text” when the evidence supports “contactless vitals” and “limited articulatory inference” more strongly. ⁶⁸

KYMA pipeline mapped to implementable modules

A technically implementable KYMA Web App can be specified as a **consent-based, privacy-preserving ambient sensing platform** with these modules:

Acquisition and synchronization.

Collect CSI streams (20/40/80 MHz), timestamped, and (optionally) auxiliary channels (BLE wearables, optical PPG, DAS summaries) under an explicit consent model. AM-FM-like designs emphasize diversity across devices/environments and translation-invariant temporal encoding. ⁶⁹

Representation backbone.

Use AM-FM as a general-purpose CSI encoder; adapt downstream tasks via probes/adapters depending on label availability. ⁷⁰

Neuro-wideband enhancement (optional).

Apply WuKong-style self-conditioned extrapolation to obtain eCSI for improved multipath resolution, with careful evaluation against measured wideband ground truth when available. ³²

State estimation and information geometry.

Use a probabilistic state estimator (Kalman-family or particle methods) where observation likelihoods are weighted by per-channel uncertainty; use information-geometric drift measures to detect environment changes and trigger recalibration. ⁷¹

Discrete codex for neural signals (only if neural sensors exist).

If EEG/ECOG exists, DeWave-style discrete wave encoding can feed a text decoder; this is the cleanest way to justify a VQ codebook layer for “intent tokens.” ⁵⁰

User interface.

A web UI should present: confidence intervals, drift/quality metrics, and “why” signals (saliency over time-frequency regions) to avoid false interpretability. Evidence of spurious reconstruction in brain decoding motivates explicit safeguards against hallucinated “decoded thoughts.” ⁷²

Validation gates and falsification-first methodology

Because RF sensing and brain decoding are prone to confounds, KYMA's validation should be “falsification-first”:

- **Empty-room / no-subject baselines** for CSI and DAS to quantify environmental false positives. ⁷³
- **Cross-environment tests** (furniture rearrangement, device displacement) because CSI embeddings are sensitive to multipath changes; AM-FM's emphasis on dataset diversity and autocorrelation objectives is directly relevant. ⁷⁰
- **Adversarial and privacy threat testing** because WiFi sensing has documented misuse risks (cross-boundary surveillance, occupancy inference via leaked CSI/beamforming feedback). ⁷⁴

Privacy, safety, and misuse resistance

A KYMA-class system must treat RF sensing as dual-use. Surveys and empirical studies document both privacy concerns and the feasibility of malicious exploitation (e.g., passive occupancy detection, cross-boundary inference). ⁷⁵

Accordingly, a “fail-closed” KYMA design should include:

- **On-device processing by default** (no raw CSI uploaded), with only aggregated, differentially-private features exported when needed. ⁷⁶
- **Cryptographic and access controls** around any sensing streams (especially multi-modal fusion). ⁶⁸
- **Explicit consent UX** and “neighbor-safe” constraints (e.g., geofencing, wall-boundary attenuation modeling, hard disable of cross-unit monitoring features). This is aligned with known RF sensing perception concerns studied in security/usability contexts. ⁷⁷

In short: KYMA can be specified as a modern ambient intelligence platform whose strongest scientific anchors are WiFi sensing foundation models, neuro-wideband extrapolation, DAS/ISAC as future multi-modal complements, and BCI decoding methods when (and only when) direct neural measurements exist. ⁷⁸

¹ ² ²⁶ ²⁸ A survey on vital signs monitoring based on Wi-Fi CSI data

https://pmc.ncbi.nlm.nih.gov/articles/PMC9375645/?utm_source=chatgpt.com

³ A Foundation Model for Ambient Intelligence Through WiFi

https://arxiv.org/html/2602.11200v1?utm_source=chatgpt.com

⁴ ¹¹ ¹² ¹⁴ ¹⁷ Full Microscopic Simulations Uncover Persistent Quantum Effects in Primary Photosynthesis

<https://arxiv.org/html/2503.17282v1>

⁵ ⁴⁵ Mind captioning: Evolving descriptive text of mental content ...

https://www.science.org/doi/10.1126/sciadv.adw1464?utm_source=chatgpt.com

⁶ ¹⁰ ³⁵ ⁴⁷ ⁵¹ ⁶⁶ We Can Hear You with Wi-Fi!

https://guanhuawang.github.io/paper/WiHear_MobiCom14.pdf?utm_source=chatgpt.com

- 7 46 58 59 The unsuspected intrinsic property of melanin to transform ...
https://www.oatext.com/pdf/ICST-2-152.pdf?utm_source=chatgpt.com
- 8 ANALYSIS AND ASSESSMENT OF GATEWAY PROCESS
https://www.cia.gov/readingroom/docs/cia-rdp96-00788r001700210016-5.pdf?utm_source=chatgpt.com
- 9 Long-lived quantum coherence in photosynthetic ...
https://www.pnas.org/doi/10.1073/pnas.1005484107?utm_source=chatgpt.com
- 13 Environment-Assisted Quantum Walks in Photosynthetic Energy Transfer
https://arxiv.org/abs/0805.2741?utm_source=chatgpt.com
- 15 16 Efficient energy transfer in light-harvesting systems, III: The influence of the eighth bacteriochlorophyll on the dynamics and efficiency in FMO
https://arxiv.org/abs/1109.3416?utm_source=chatgpt.com
- 18 Error Correcting Codes in Quantum Theory | Phys. Rev. Lett.
https://link.aps.org/doi/10.1103/PhysRevLett.77.793?utm_source=chatgpt.com
- 19 $[[[7,1,3]]]$ Steane code
https://errorcorrectionzoo.org/c/steane?utm_source=chatgpt.com
- 20 Dephasing assisted transport: Quantum networks and biomolecules
https://arxiv.org/abs/0807.4902?utm_source=chatgpt.com
- 21 22 Tsirelson bounds for generalized Clauser-Horne-Shimony-Holt inequalities
https://arxiv.org/abs/quant-ph/0510076?utm_source=chatgpt.com
- 23 71 An Elementary Introduction to Information Geometry
https://franknielsen.github.io/entropy-22-01100-v2.pdf?utm_source=chatgpt.com
- 24 27 31 65 69 70 78 AM-FM: A Foundation Model for Ambient Intelligence Through WiFi
<https://arxiv.org/html/2602.11200v1>
- 25 38 50 67 DeWave: Discrete EEG Waves Encoding for Brain Dynamics to Text Translation
https://arxiv.org/abs/2309.14030?utm_source=chatgpt.com
- 29 34 On CSI-Based Vital Sign Monitoring Using Commodity WiFi
https://www.eng.auburn.edu/~szm0001/papers/PhaseBeat_ACMHealth20.pdf?utm_source=chatgpt.com
- 30 33 Time-Bandwidth Product
https://www.radartutorial.eu/09.receivers/rx53.en.html?utm_source=chatgpt.com
- 32 "Buy One Get N Free": Neuro-Wideband WiFi Sensing via Self-Conditioned CSI Extrapolation
<https://arxiv.org/html/2601.06467v1>
- 36 WiMic: Recovering sound with wireless signals - People
https://people.csail.mit.edu/davidam/docs/WiMic_final.pdf?utm_source=chatgpt.com
- 37 Lip-Siri: Contactless Open-Sentence Silent Speech with Wi ...
https://arxiv.org/html/2601.18177v1?utm_source=chatgpt.com
- 39 40 Scientific Applications of Distributed Acoustic Sensing
https://pmc.ncbi.nlm.nih.gov/articles/PMC8838753/?utm_source=chatgpt.com
- 41 74 Privacy Implications of Plaintext Beamforming Feedback in ...
https://www.ndss-symposium.org/wp-content/uploads/2025-5-paper.pdf?utm_source=chatgpt.com

- 42 44 **Integrated Sensing and Communication (ISAC)**
https://www.huawei.com/en/huaweitech/future-technologies/integrated-sensing-communication-concept-practice?utm_source=chatgpt.com
- 43 **Huawei EF3000-A50 I Distributed Fiber Optic Sensor**
https://e.huawei.com/se/products/optical-sensing/optixsense-ef3000-a50?utm_source=chatgpt.com
- 48 **Hierarchical Neural Representation of Dreamed Objects ...**
https://www.frontiersin.org/journals/computational-neuroscience/articles/10.3389/fncom.2017.00004/full?utm_source=chatgpt.com
- 49 **Brain-aligning of semantic vectors improves neural decoding of visual stimuli**
https://arxiv.org/abs/2403.15176?utm_source=chatgpt.com
- 52 54 **Real-time decoding of full-spectrum Chinese - Brain-computer ...**
https://www.science.org/doi/10.1126/sciadv.adz9968?utm_source=chatgpt.com
- 53 57 **China Moves Ahead with Research into Brain-computer ...**
https://english.cas.cn/newsroom/cas_media/202508/t20250825_1051356.shtml?utm_source=chatgpt.com
- 55 **Brain-computer interfaces in 2023–2024**
https://onlinelibrary.wiley.com/doi/full/10.1002/brx2.70024?utm_source=chatgpt.com
- 56 **The physical and chemical properties of eumelanin**
https://pubmed.ncbi.nlm.nih.gov/17083485/?utm_source=chatgpt.com
- 60 **Electrostatic and Kelvin Probe Force Microscopy | ORNL**
https://www.ornl.gov/content/electrostatic-and-kelvin-probe-force-microscopy?utm_source=chatgpt.com
- 61 **Kelvin probe force microscopy and its application**
https://kummelgroup.ucsd.edu/pubs/paper/110.pdf?utm_source=chatgpt.com
- 62 **Human Demodex Mite: The Versatile Mite of Dermatological ...**
https://pmc.ncbi.nlm.nih.gov/articles/PMC3884930/?utm_source=chatgpt.com
- 63 64 **Review Article Dielectric Resonator Antennas**
https://core.ac.uk/download/pdf/194637109.pdf?utm_source=chatgpt.com
- 68 73 75 **RF Sensing Security and Malicious Exploitation**
https://arxiv.org/html/2504.10969v1?utm_source=chatgpt.com
- 72 **Spurious reconstruction from brain activity**
https://www.sciencedirect.com/science/article/pii/S0893608025003946?utm_source=chatgpt.com
- 76 **Privacy-preserving WiFi sensing in WSNs via CSI obfuscation**
https://www.sciencedirect.com/science/article/abs/pii/S0167404825002834?utm_source=chatgpt.com
- 77 **Privacy Solution or Menace? Investigating Perceptions of ...**
https://www.usenix.org/system/files/usenixsecurity25-windl.pdf?utm_source=chatgpt.com