Waqtuk – Developer dependencies

Nov 7, 2026 · @Hammad Albalawi

Appendix to "Waqtuk – Developer work split and shared agreements". The work is split so that all four developers work in parallel. A small number of pieces are needed by other people, and each one has a workaround so nobody has to stop. Names, props and function signatures are fixed in sections 2 to 5 of the main document, so you build against the agreed name, and the real piece replaces the placeholder underneath without changing that name.

1. Who pushes what, and who waits for it

Piece	Pushed by	Needed by	How nobody has to wait
Skeleton (every file and route, as placeholders)	Dev 4 (Saeed)	Everybody	The only piece that stops everybody, for about 30 minutes. Afterwards everyone imports the real names. Meanwhile read the document and the prototype.
`theme.css` and `global.css`	Dev 1 (Hammad)	The CSS of every page and component	First hour. Build with the variable names of section 3; the result shows when it merges.
`DataContext`	Dev 2 (Fahad)	Every page that calls `useData()`	About 2 hours. Before it, the placeholders return empty lists; after it, the real data appears.
Form controls: `Button`, `Input`, `Select`, `Textarea`, `Card`, `PageHeader`	Dev 2 (Fahad)	Every page and form	Pushed on day 1. Before that, use the placeholder with the same props (section 5.4).

Piece	Pushed by	Needed by	How nobody has to wait
`Modal`, `ConfirmDialog`, `Table`, `SegmentedControl`	Dev 3 (Abdallah)	Forms, tables and dialogs of all four developers	Same way: names and props are fixed.
`AppShell`, `Topbar` (Dev 3), `Sidebar` (Dev 2), `AuthContext` (Dev 4)	Dev 3, Dev 2, Dev 4	Trying your page with navigation and sign in	Open your page directly on its route from the start, even if the shell is not finished.
`utils/time.js` and `utils/stats.js`	Dev 1 (Hammad)	Dashboard, Reports, Goals, mentor pages	About day 1. Rely on the signatures of section 5.6.
`utils/goals.js` (goal progress)	Dev 3 (Abdallah)	Goals page, and the goals table in Reports (Dev 1)	The signatures are fixed; build against the name.
`BarChart` (Dev 1) and `DonutChart` (Dev 4)	Dev 1, Dev 4	Dashboard, Reports, `MentorStudent` (Dev 3)	Build the page without the chart; it appears when the chart merges.
`getSharedData` and the mentor access rule	Dev 4 (Saeed)	`MentorStudent` and `MentorGoal` (Dev 3)	A placeholder returns empty data; the real rule lands in Phase 1.
`usageFor(from, to)`	Dev 4 (Saeed)	`AdminDashboard` (Dev 1)	Same way.

2. Rough timeline

When	What happens
First 30 minutes	Dev 4 pushes the skeleton straight to `main` (the only direct push in the project). The others read and prepare their branches.
First hour	Dev 1 pushes `theme.css` and `global.css`.

When	What happens
First 2 hours	Dev 2 pushes `DataContext` wired up (each developer's actions are placeholders until they push).
Day 1	Form controls (Dev 2), dialogs, tables and shell (Dev 3), `AuthContext` and the login page (Dev 4), `time.js` and `stats.js` (Dev 1).
After day 1	The dependencies are almost gone. Everyone works alone on their own pages and merges small pull requests.

3. The rule

Whoever is late does not stop anybody, because names, props and function signatures are fixed. A placeholder is replaced by the real piece and nothing changes for the people who use it. If you miss something, ask the owner of that file in a pull request comment and they add it the same day.

The only dependency that can come back at any time is a contract change (a prop name, a function name, a data shape). It goes through the team leader, the document is edited first, and then the owner changes the code. Adding is always allowed; renaming or removing is not.

4. Where the risk is

- **Dev 4 (Saeed):** a delay stops everybody, so the skeleton is the first thing he pushes.
- **Dev 2 (Fahad):** most pages depend on `DataContext` and the form controls, so push them early and then move on to your pages.
- **Dev 3 (Abdallah):** every form of the four developers needs `Modal`, so push it before your pages.
- **Dev 1 (Hammad):** `theme.css` in the first hour, then `time.js` and `stats.js`.