CYBER SITH NOON INTRUSION REPORT

Team 4: Urbandale IA

WMS - Vulnerabilities and remediation

We lost both of our WMS flags to an exploit that was able to get in through the use of multiple CDC users with default permissions to access, and while in, they were able to:

- Override our flag with an echo command
- Create an elevated user named killer-bob
- Gain access to out /etc/ file (flag)
- Access the root user and permissions (flag)



```
209  locate wms.jar
210  mv wms.jar.original wms.jar
211  java -jar wms.jar
212  mv wms.jar.original wmsf.jar
213  mv wms.jar.original wms.jar
214  exit
215  locate users
216  locate password
217  locate user password
218  users
219  userid cdc
220  user -i
221  users -i
222  cat /etc/password | grep cdc
223  cat /etc/passwd | grep cdc
224  cat -a /etc/passwd
225  cat -A /etc/passwd
226  exit
227  ip a
228  nano /etc/hosts
229  echo VXmAmMUg12x0ChwP6eakQGCLoD7Drs9JIPCXYtEfI5THwHmlyb> /root/team4_wms-root.flag
230  adduser killer.bob -p WhoKilledLauraPalmer
231  adduser killer.bob
232  adduser killer-bob
233  usermod -aG wheel killer-bob
234  usermod -aG sudo killer-bob
235  ls /root/
236  ls /etc/ | grep flag
237  cat /etc/team4_wms-etc.flag
238  echo "Fire walk with me!" > /tmp/fromtheblacklodge
239  exit
```

(above is a screenshot of the history of malicious commands made on root)

Remediation: In attempts to remediate this, we rolled the server and changed the root password to prevent a similar exploit from getting as far in the future. We also set stricter firewall access to prevent further remote access.

WWW - vulnerabilities and remidation