

Formal Analysis of Policies in Wireless Sensor Network Applications

Marco Patrignani Nelson Matthys José Proença Danny
Hughes Dave Clarke

K.U.Leuven

May 31, 2012

Outline

WSN Applications with CaPI

Policies

Analysis with mCRL2

Prototype Tool

Recap & Future Work

Outline

WSN Applications with CaPI

Policies

Analysis with mCRL2

Prototype Tool

Recap & Future Work

Wireless Sensor Network Applications with CaPI

- ▶ Application: high level of abstraction (no routing, no low level communication).


Wireless Sensor Network Applications with CaPI

- ▶ Application: high level of abstraction (no routing, no low level communication).
- ▶ Key elements of CaPI middleware:
 - ▶ Components
 - ▶ Wires
 - ▶ Policies


Graphical Representation of Components




Graphical Representation of Components




Graphical Representation of Wires




Graphical Representation of Wires



Graphical Representation of Wires



Graphical Representation of Wires



Policies


- ▶ Take care of non functional requirements via domain-specific actions.

Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.


Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.
- ▶ Executed at 4 entry points: from components, to components, from network, to network.




Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.
- ▶ Executed at 4 entry points: from components, to components, from network, to network.




Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.
- ▶ Executed at 4 entry points: from components, to components, from network, to network.




Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.
- ▶ Executed at 4 entry points: from components, to components, from network, to network.




Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.
- ▶ Executed at 4 entry points: from components, to components, from network, to network.



Policies

- ▶ Take care of non functional requirements via domain-specific actions.
- ▶ Triggered by messages when messages leave and enter a node.
- ▶ Executed at 4 entry points: from components, to components, from network, to network.



Problems Related to Policies

Policies generate problems like:

Problems Related to Policies

Policies generate problems like:

- ▶ security holes;

Problems Related to Policies

Policies generate problems like:

- ▶ security holes;
- ▶ wastage of resources;

Problems Related to Policies

Policies generate problems like:

- ▶ security holes;
- ▶ wastage of resources;
- ▶ other (logging encrypted data).

Problems Related to Policies

Policies generate problems like:

- ▶ security holes;
- ▶ wastage of resources;
- ▶ other (logging encrypted data).

because:

- ▶ they are deployed over time;

Problems Related to Policies

Policies generate problems like:

- ▶ security holes;
- ▶ wastage of resources;
- ▶ other (logging encrypted data).

because:

- ▶ they are deployed over time;
- ▶ they change over time;

Problems Related to Policies

Policies generate problems like:

- ▶ security holes;
- ▶ wastage of resources;
- ▶ other (logging encrypted data).

because:

- ▶ they are deployed over time;
- ▶ they change over time;
- ▶ their semantics can conflict.

Outline

WSN Applications with CaPI

Policies

Analysis with mCRL2

Prototype Tool

Recap & Future Work

Policies Example


 $P_1 @ N_1$

```
on event (T) as e
  if (true) then
    encrypt e;
```

Policies Example

 $P_1 @ N_1$

```
on event (T) as e
  if (true) then
    encrypt e;
```




Policies Composition Example

$P_1@N_1$	$P_2@N_1$
on event (T) as e if (true) then encrypt e;	on event ($^{\circ}\text{C}$) as e if (lowBatt()) then deny e;

Policies Composition Example

$P_1@N_1$	$P_2@N_1$
on event (T) as e if (true) then encrypt e;	on event ($^{\circ}\text{C}$) as e if (lowBatt()) then deny e;




Policies Network Composition Example

$P_1@N_1$	$P_2@N_2$
on event (T) as e if (true) then encrypt e;	on event (Any) as e if (true) then decrypt e;

Policies Network Composition Example

$P_1@N_1$	$P_2@N_2$
on event (T) as e if (true) then encrypt e;	on event (Any) as e if (true) then decrypt e;

Wires on Any messages.



Policy Programs

<i>Policy Program</i> $P ::=$	$\text{on}(t)\{P\}$	<i>Type</i> $t \in \mathcal{T}$
	$ \text{if}(g)\{P\}$	<i>If-Guard</i> $g \in \mathcal{L}$
	$ a$	<i>Action</i> $a \in \mathcal{A}$
	$ P; P'$	

$\mathcal{A} ::= \{\text{allow, deny, encrypt, decrypt, sign, verify, persist, delete}\}.$

Semantics Function

The idea is to capture what was drawn before: all paths of a tree of execution.

$$\llbracket \text{on}(t)\{P\} \rrbracket_C = \{\tau \mid \tau \in \llbracket P \rrbracket_{C \cap \{t\}}, C \frown t\} \cup \{(\epsilon; C \cap \{\neg t\}) \mid C \frown \neg t\}$$

$$\llbracket \text{if}(g)\{P\} \rrbracket_C = \{\tau \mid \tau \in \llbracket P \rrbracket_{C \cup \{g\}}, C \frown g\} \cup \{(\epsilon; C \cup \{\neg g\}) \mid C \frown \neg g\}$$

$$\llbracket a \rrbracket_C = \{(a; C)\}$$

$$\llbracket P; P' \rrbracket_C = \{(\bar{a} \bar{a}'; C') \mid (\bar{a}; C'') \in \llbracket P \rrbracket_C, (\bar{a}'; C') \in \llbracket P' \rrbracket_{C''}\}$$

Outline

WSN Applications with CaPI

Policies

Analysis with mCRL2

Prototype Tool

Recap & Future Work

Analysis

Specification of undesired/desired properties via modal logic:

```
[true*.encrypt.true*. $\frac{1}{2}$ .(!decrypt)*]<true*.decrypt> true;
                                                    (dec-after-enc)

[true*.encrypt.true*.encrypt] false;                (enc-most-once)

[true*.encrypt]<true*. $\frac{1}{2}$ > true;                        (snd-after-enc)
```

Outline

WSN Applications with CaPI

Policies

Analysis with mCRL2

Prototype Tool

Recap & Future Work

Tool

We developed a tool in Scala that:

Tool

We developed a tool in Scala that:

- ▶ extracts the formalization of policies;

Tool

We developed a tool in Scala that:

- ▶ extracts the formalization of policies;
- ▶ calculates the semantics of policy programs;

Tool

We developed a tool in Scala that:


- ▶ extracts the formalization of policies;
- ▶ calculates the semantics of policy programs;
- ▶ analyzes the constrained trace semantics against some user-defined properties via mCRL2;

Tool

We developed a tool in Scala that:

- ▶ extracts the formalization of policies;
- ▶ calculates the semantics of policy programs;
- ▶ analyzes the constrained trace semantics against some user-defined properties via mCRL2;
- ▶ scales linearly in terms of connections between nodes and number of policies (with similar logical conditions).

Tool- feedback



```

<terminated> ScalaAnalyze [Scala Application] /System/Library/Java/JavaVirtualMachines/1.6.0.jdk/Contents/Home/b
Extraction of constrained traces: ...
Fast analysis.
    Checking formula generalWastefulDeny           Failed
    Checking formula signBeforeVerify             OK
    Checking formula encryptBeforeDecrypt         OK
    Checking formula verifyAtmostOnce             OK
    Checking formula decryptAfterEncrypt          Failed
    Checking formula decryptAtmostOnce            OK
    Checking formula signAtmostOnce               OK
    Checking formula persistBeforeDelete          OK
    Checking formula sendAfterEncrypt             Failed
    Checking formula networkAtmostOnce            OK
    Checking formula sendAfterSign                OK
    Checking formula generalWastefulDenyAfter      OK
    Checking formula verifyAfterSign              OK
    Checking formula encryptAtmostOnce            OK
Total time: 1353 milliseconds.
### WARNING ### errors discovered ### WARNING ###
Running in-depth analysis...
Analyzing node n6
Analyzing node n7
Analyzing node n0
    Analyzing trace n0 encrypt.allw.decrypt.allw n0
  
```

Tool- feedback

```
Analyzing trace n0 encrypt.allw.NW.decrypt.allw n6
Analyzing trace n0 encrypt.allw.deny n6
    Violation of sendAfterEncrypt by trace: Trace: n0 "encrypt.allw.deny" n6
Assumptions:    types: 6
                guard: true

    Violation of generalWastefulDeny by trace: Trace: n0 "encrypt.allw.deny" n6
Assumptions:    types: 6
                guard: true

Analyzing trace n0 encrypt.allw.NW n7
    Violation of decryptAfterEncrypt by trace: Trace: n0 "encrypt.allw.NW" n7
Assumptions:    types: 2
                guard: true
```

Outline

WSN Applications with CaPI

Policies

Analysis with mCRL2

Prototype Tool

Recap & Future Work

Recap & Future Work

Recap

- ▶ Formalized policies and their semantics in CaPI-driven WSN applications;
- ▶ Created a prototype for the analysis of policies in real-world deployment.

Recap & Future Work

Recap

- ▶ Formalized policies and their semantics in CaPI-driven WSN applications;
- ▶ Created a prototype for the analysis of policies in real-world deployment.

Future Work

- ▶ Model dynamic actions of Policies;

Recap & Future Work

Recap

- ▶ Formalized policies and their semantics in CaPI-driven WSN applications;
- ▶ Created a prototype for the analysis of policies in real-world deployment.

Future Work

- ▶ Model dynamic actions of Policies;
- ▶ Provide a concurrency model for the modeled application.