

```

from google.colab import drive

drive.mount('/content/gdrive')

Mounted at /content/gdrive

"""
Minimal character-level Vanilla RNN model. Written by Andrej Karpathy (@karpathy)
BSD License
"""

import numpy as np

# data I/O
data = open('/content/gdrive/MyDrive/project_7/data/tinyshakespeare/input.txt', 'r').read() #
chars = list(set(data))
data_size, vocab_size = len(data), len(chars)
print('data has %d characters, %d unique.' % (data_size, vocab_size))
char_to_ix = { ch:i for i,ch in enumerate(chars) }
ix_to_char = { i:ch for i,ch in enumerate(chars) }

    data has 1115394 characters, 65 unique.

# hyperparameters
hidden_size = 100 # size of hidden layer of neurons
seq_length = 25 # number of steps to unroll the RNN for
learning_rate = 1e-1
epoch = 50

# model parameters
Wxh = np.random.randn(hidden_size, vocab_size)*0.01 # input to hidden
Whh = np.random.randn(hidden_size, hidden_size)*0.01 # hidden to hidden
Why = np.random.randn(vocab_size, hidden_size)*0.01 # hidden to output
bh = np.zeros((hidden_size, 1)) # hidden bias
by = np.zeros((vocab_size, 1)) # output bias

def lossFun(inputs, targets, hprev):
    """
    inputs,targets are both list of integers.
    hprev is Hx1 array of initial hidden state
    returns the loss, gradients on model parameters, and last hidden state
    """
    xs, hs, ys, ps = {}, {}, {}, {}
    hs[-1] = np.copy(hprev)
    loss = 0
    # forward pass
    for t in range(len(inputs)):
        xs[t] = np.zeros((vocab_size,1)) # encode in 1-of-k representation

```

```

xs[t][inputs[t]] = 1
hs[t] = np.tanh(np.dot(Wxh, xs[t]) + np.dot(Whh, hs[t-1]) + bh) # hidden state
ys[t] = np.dot(Why, hs[t]) + by # unnormalized log probabilities for next chars
ps[t] = np.exp(ys[t]) / np.sum(np.exp(ys[t])) # probabilities for next chars
loss += -np.log(ps[t][targets[t],0]) # softmax (cross-entropy loss)
# backward pass: compute gradients going backwards
dWxh, dWhh, dWhy = np.zeros_like(Wxh), np.zeros_like(Whh), np.zeros_like(Why)
dbh, dby = np.zeros_like(bh), np.zeros_like(by)
dhnext = np.zeros_like(hs[0])
for t in reversed(range(len(inputs))):
    dy = np.copy(ps[t])
    dy[targets[t]] -= 1 # backprop into y. see http://cs231n.github.io/neural-networks-case-s
    dWhy += np.dot(dy, hs[t].T)
    dby += dy
    dh = np.dot(Why.T, dy) + dhnext # backprop into h
    dhraw = (1 - hs[t] * hs[t]) * dh # backprop through tanh nonlinearity
    dbh += dhraw
    dWxh += np.dot(dhraw, xs[t].T)
    dWhh += np.dot(dhraw, hs[t-1].T)
    dhnext = np.dot(Whh.T, dhraw)
for dparam in [dWxh, dWhh, dWhy, dbh, dby]:
    np.clip(dparam, -5, 5, out=dparam) # clip to mitigate exploding gradients
return loss, dWxh, dWhh, dWhy, dbh, dby, hs[len(inputs)-1]

```

```

def sample(h, seed_ix, n):
    """
    sample a sequence of integers from the model
    h is memory state, seed_ix is seed letter for first time step
    """
    x = np.zeros((vocab_size, 1))
    x[seed_ix] = 1
    ixes = []
    for t in range(n):
        h = np.tanh(np.dot(Wxh, x) + np.dot(Whh, h) + bh)
        y = np.dot(Why, h) + by
        p = np.exp(y) / np.sum(np.exp(y))
        ix = np.random.choice(range(vocab_size), p=p.ravel())
        x = np.zeros((vocab_size, 1))
        x[ix] = 1
        ixes.append(ix)
    return ixes

```

```

n, p, e = 0, 0, 0
mWxh, mWhh, mWhy = np.zeros_like(Wxh), np.zeros_like(Whh), np.zeros_like(Why)
mbh, mby = np.zeros_like(bh), np.zeros_like(by) # memory variables for Adagrad
smooth_loss = -np.log(1.0/vocab_size)*seq_length # loss at iteration 0
while e < epoch + 1:
    # prepare inputs (we're sweeping from left to right in steps seq_length long)
    if p+seq_length+1 >= len(data) or n == 0:

```

```

hprev = np.zeros((hidden_size,1)) # reset RNN memory
p = 0 # go from start of data
print("end of data.... new epoch")
e += 1
inputs = [char_to_ix[ch] for ch in data[p:p+seq_length]]
targets = [char_to_ix[ch] for ch in data[p+1:p+seq_length+1]]

# sample from the model now and then
if n % 100 == 0:
    sample_ix = sample(hprev, inputs[0], 200)
    txt = ''.join(ix_to_char[ix] for ix in sample_ix)
    print('----\n %s \n----' % (txt, ))
    print("epoch: ", e)

# forward seq_length characters through the net and fetch gradient
loss, dWxh, dWhh, dWhy, dbh, dby, hprev = lossFun(inputs, targets, hprev)
smooth_loss = smooth_loss * 0.999 + loss * 0.001
if n % 100 == 0: print('iter %d, loss: %f' % (n, smooth_loss))# print progress

# perform parameter update with Adagrad
for param, dparam, mem in zip([Wxh, Whh, Why, bh, by],
                              [dWxh, dWhh, dWhy, dbh, dby],
                              [mWxh, mWhh, mWhy, mbh, mby]):
    mem += dparam * dparam
    param += -learning_rate * dparam / np.sqrt(mem + 1e-8) # adagrad update

p += seq_length # move data pointer
n += 1 # iteration counter

```

MAUSTI:

Agaile erither'd.

MARCAUS:

A howry for,--Guct for that them and fairs he prinkns; the of mase Of it norled it hi
ste, will shourd the

epoch: 50

iter 2230400, loss: 47.414627

ENEPTO, CINGHRWICKIV:

For up.

I awar: I gom!

Now 'tit sew burying

To, I

irru; chang, an strie ous by ent't. In anaem liesamebloigh longs; with havger, Tith m

BOLIALAT:

I breed the vany sprise alas a

epoch: 50

iter 2230500, loss: 47.513366

sure and what sild the he amy he fitherise't from-I pliavy gone aswitors of the thut

```

we
wovt whickt prey puck, I'd,
Girpo my dist:
Bat
What oure; whish take cear eneman?

BOTHORINE:
I sly,
If
----
epoch: 50
iter 2230600, loss: 47.529963
----
In have
Asem's in co mafferpentt to?
A is wazly
To said.

MINA:
A Hourre'd sill 'Sis onderer. I this.

HONVOLIN:
Secaepicy'ds tim, Lorr orrend; yeleng, saice.

```

```

ADY:
And prarew, if hastee,
I appory?
Oy
----
epoch: 50
iter 2230700, loss: 47.523367
end of data.... new epoch

```

```

# gradient checking
from random import uniform
def gradCheck(inputs, target, hprev):
    global Wxh, Whh, Why, bh, by
    num_checks, delta = 10, 1e-5
    _, dWxh, dWhh, dWhy, dbh, dby, _ = lossFun(inputs, targets, hprev)
    for param, dparam, name in zip([Wxh, Whh, Why, bh, by], [dWxh, dWhh, dWhy, dbh, dby], ['Wxh',
        s0 = dparam.shape
        s1 = param.shape
        assert s0 == s1, "Error dims dont match: %s and %s." % (`s0`, `s1`)
        print(name)
        for i in range(num_checks):
            ri = int(uniform(0, param.size))
            # evaluate cost at [x + delta] and [x - delta]
            old_val = param.flat[ri]
            param.flat[ri] = old_val + delta
            cg0, _, _, _, _, _ = lossFun(inputs, targets, hprev)
            param.flat[ri] = old_val - delta
            cg1, _, _, _, _, _ = lossFun(inputs, targets, hprev)

```

```

param.flat[ri] = old_val # reset old value for this parameter
# fetch both numerical and analytic gradient
grad_analytic = dparam.flat[ri]
grad_numerical = (cg0 - cg1) / ( 2 * delta )
rel_error = abs(grad_analytic - grad_numerical) / abs(grad_numerical + grad_analytic)
print('%f, %f => %e ' % (grad_numerical, grad_analytic, rel_error))
# rel_error should be on order of 1e-7 or less

```

```
gradCheck(inputs, targets, hprev)
```

```

↳ Wxh
-0.000000, -0.000000 => 1.919804e-04
0.000000, 0.000000 => nan
0.000000, 0.000000 => nan
0.000000, 0.000000 => nan
0.000000, 0.000000 => nan
0.000000, 0.000000 => 2.210564e-03
0.000000, 0.000000 => nan
0.000000, 0.000000 => nan
0.000000, 0.000000 => nan
0.000000, 0.000000 => nan
Whh
-0.250134, -0.250134 => 5.119078e-10
-0.250339, -0.250339 => 1.429974e-09
-0.013894, -0.013894 => 8.121409e-09
0.257753, 0.257753 => 1.133796e-09
-0.241636, -0.241636 => 2.012495e-09
0.302814, 0.302814 => 7.860756e-10
-0.000006, -0.000006 => 5.244733e-05
1.624901, 1.624901 => 3.365265e-10
-0.029429, -0.029429 => 8.710345e-09
/usr/local/lib/python3.7/dist-packages/ipykernel_launcher.py:24: RuntimeWarning: invalid
0.014200, 0.014200 => 2.231149e-08
Why
-0.222701, -0.222701 => 4.014291e-10
-1.367862, -1.367862 => 1.438322e-10
-0.022143, -0.022143 => 1.052400e-08
-0.462337, -0.462337 => 7.809829e-10
-0.591984, -0.591984 => 5.575908e-10
-0.027522, -0.027522 => 7.260117e-10
0.782260, 0.782260 => 2.776090e-11
0.000011, 0.000011 => 1.322089e-05
-0.072068, -0.072068 => 5.415596e-10
0.974359, 0.974359 => 3.378459e-10
bh
-0.103110, -0.103110 => 1.768988e-09
-0.001309, -0.001309 => 9.358071e-08
-0.115272, -0.115272 => 3.400147e-09
-0.081141, -0.081141 => 7.612434e-09
0.387334, 0.387334 => 4.573047e-10
0.017428, 0.017428 => 2.319949e-08
-0.530978, -0.530978 => 1.323936e-09
0.024537, 0.024537 => 6.821674e-09
-0.032201, -0.032201 => 6.828380e-09
0.000274, 0.000274 => 1.013781e-06

```

```
by
0.211464, 0.211464 => 1.637782e-10
0.000011, 0.000011 => 3.318801e-06
-1.229797, -1.229797 => 1.836999e-10
0.520387, 0.520387 => 4.424100e-10
0.106473, 0.106473 => 3.498653e-09
0.012258, 0.012258 => 7.508084e-09
0.000158, 0.000158 => 2.823082e-07
0.025434, 0.025434 => 5.797659e-10
0.021859, 0.021859 => 5.018161e-09
-1.229797, -1.229797 => 1.836999e-10
```



✓ 3h 6m 0s completed at 1:06 AM

