Recovered tools and trainers, part 1 of 2

Recovered tools and trainers, part 1 of 2

This part contains 31 notes, from `recovered-drive-tools/ghidra-analysis/Assimilator/SUMMARY.md` through `recovered-drive-tools/SEIHAI_SERVERTOOLS_MAP.md`.

Behaviour notes under `recovered-hacks/` and `recovered-drive-tools/`.

`recovered-drive-tools/ghidra-analysis/Assimilator/SUMMARY.md`

Salvage analysis: Assimilator (GIF2PNG / batch converter)

- **Binary:** `Developer Tools/GAT Tool - [Graphics Administration Team]/Assimilator GIF2PNG.rar.extracted/Assimilator.exe`
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland C++/Delphi-era UI, ~427 KB

Purpose (plain behaviour)

GAT-era **batch file converter / checker** branded around Graal assets (archive name “GIF2PNG”).

Observed behaviour:

- Batch-checks and converts graphics-admin assets: classic scripts, levels, plain text, and animations.
- Keeps a checklist and reports an error when the list is empty or nothing is selected.
- Shows a client-version status that stays blank when no client is configured.
- Offline graphics utility — not a network service.

Recommended placement

Tag	**`seihai` / `analysis-only`**
Why	Offline asset conversion helpers for graphics/admin workflows.
Not	`setup-core`, `seihai-rc`, live LAT
Licence	Legacy Borland tool — notes only

Ghidra stats (machine)

Field	**Value**
Functions	~2656 (internal ~2317)
Imports	~347
Exports	~18 (unit init/finalize stubs)
Interesting strings	~94
Decompiled (local only)	25 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/BytecodeViewer/SUMMARY.md`

Salvage analysis: BytecodeViewer.exe

- **Binary:** `/workspace/recovered-drive-tools/_extracted/gs2-compiler/GS2 Compiler/BytecodeViewer/ViewerApp/BytecodeViewer.exe` (same tree under NAT Tools GS2 Compiler extract / `_inbox/extracted/GS2 Compiler/`)
- **Analyzed (UTC):** prior headless run · SUMMARY rewritten 20261031T211700Z from **source + binary identity** (PE RE thin; prefer source)
- **Ghidra:** 12.2
- **Purpose focus:** recover CLI, protocols, config paths, and rebuild/rehost notes for seihai-servertools (ops/server tooling — not malware inventing).

Purpose guess

Small **console PE** that dumps a Graal **GS2 compiled script bytecode** capture for humans. Companion package ships full C++ source (`BytecodeViewer/Source/main.cpp`) plus opcode name tables (`BytecodeViewer_defs.txt`). Prefer reading that source over decompile — Ghidra mostly sees CRT/locale noise on this build.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	**`analysis-only`**
Why	NAT/GS2 diagnostics aid; behaviour understood from source. Useful reference for script-toolchain docs, not a seihai-servertools runtime dependency.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`
Related	GS2 Compiler sources in the same package; NAT script editors
Licence risk	Third-party / community tool — notes only

Identity

```
# file
PE32 executable (console) Intel 80386, for MS Windows, 5 sections

# size
88K (Sep 2017 stamp on recovered copy)

# sha256
8e6b1f22947a6df814fc2f4be8169998e1f2bd1effc2becf51029eff3107f6a9
```

Ghidra program

Field	**Value**
Format	Portable Executable (PE)
Language	x86:LE:32:default
Compiler	windows
Functions	313 (internal 310)
Imports	73
Exports / entries	40

Field	Value
Interesting strings	64 (mostly CRT)
Decompiled funcs	~30–40

Behaviour (from source)

CLI: `BytecodeViewer <script file>`. Opens the capture, **skips the first byte** (Graal Relay message id prefix), then parses:

1. **Information section** — length-prefixed; prints code target, target name, and whether to save script to file.
2. Segmented payload named in source as: integer/unknown purpose, function names, strings, bytecode.
3. Opcode pretty-print driven by `BytecodeViewer_defs.txt` (index=`name` lines) loaded from the working directory.

Big-endian short decoding matches other GS2 tooling. No network listen or connect — offline file viewer only. Ordinary Windows file I/O through the C runtime dominates imports.

Prefer source over RE

- …`/BytecodeViewer/Source/main.cpp`, `Arrays.h`, project files (`.sln` / `.vcxproj` / `.cbp`)
- `BytecodeViewer_defs.txt` / `BytecodeViewer_defs2.txt` beside ViewerApp

Rebuild / rehost checklist

- [x] Language: native C++ console, MSVC-era PE.
- [x] CLI and defs-file contract documented in source.
- [ ] Optional: reimplement dump against seihai GS2 fixtures if NAT docs need it — do not vendor binary.

Artifacts

- Local Ghidra export under this dir (CRT-heavy); treat source tree as authoritative.

`recovered-drive-tools/ghidra-analysis/DClient_setup/SUMMARY.md`

Salvage analysis: DClient setup bootstrapper

- **Binary:** `_extracted/dclient-setup/setup.exe`
- **Analyzed (UTC):** 20261031T210043Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Visual Basic 6 package-and-deployment bootstrapper, ~137 KB, March 2000
- **sha256:** `7052d75548d0f34e290baf29aa7281b44b4eb38327a9078354e15a3dc8749da4`

Purpose

Small Windows installer bootstrap for a client package nicknamed DClient. It is not a game server and it does not speak the game protocol.

What it does:

- Reads a setup manifest beside the executable and pulls payload files from a cabinet in the same folder.

- Copies files into place, compares versions, registers libraries, and writes an uninstall entry plus an install log.
- Can ask for a reboot when a file is in use, and it adjusts process privileges enough to replace system files.
- Dialogs cover a missing disk, a file that cannot be read, a destination that is busy, a registration failure, and a log that cannot be written.

The companion cabinet in the recovered archive is truncated (a few hundred kilobytes of a multi-megabyte archive, and the zip itself has no end-of-central-directory record). The installed client and its runtime library cannot be reconstructed from this drop.

Imports are installer machinery: registry, file copy and search, process creation, version resources, a common file dialog, simple text drawing, and reboot privileges. There is no listen or connect role.

What Seihai could learn

Nothing to reimplement. This is an incomplete client installer fragment. Leave it staged and out of scope for server tools. Do not run it.

Recommended placement

Placement	**`stay-staged (bad archive)` → `out-of-scope` (client installer)**
Why	Incomplete Drive zip; client-side bootstrap only.
Not	Any seihai-servertools crate
Licence	Unknown until a complete cabinet exists; treat as untrusted

Program (counts only)

Field	**Value**
Functions	435 (internal 426)
Imports	183
Interesting strings	78
Decompiled locally	25 — **not committed**

Raw imports, strings, and decompilation stay in the gitignored local analysis folder. This note is hand-written.

`recovered-drive-tools/ghidra-analysis/GCD/SUMMARY.md`

Salvage analysis: Graal Character Designer

- **Binary:** `_inbox/extracted/Graal_Character_Designer_1.2.7/GCD.exe`
- **Analyzed (UTC):** 20261031T205951Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland Delphi, ~399 KB, November 1999
- **sha256:** `d576bc534dc17425645a0adb46b401ad4a081b19f4315cf8054aef9529cfeed9`

Purpose

Offline character-appearance editor from the Bruges / Andrew Bridges line, version 1.2.7. It edits classic colours, heads, and character files. It is not a network tool.

Screens and files:

- A main designer form, an about box, and an install-location prompt.
- It searches a few common client install directories, then asks the operator to point at the client folder and looks for the client executable.
- It expects a heads configuration and separate folders of head images and gif assets. A missing heads configuration is a hard error. Gif loads can fail on their own.
- Open and save dialogs, image-list controls for drag and draw, clipboard limits (icons are not accepted), and a help hook.
- Delphi runtime and locale data only besides that. No socket use.

What Seihai could learn

The client needs a heads configuration and image folders next to the install, and character editing is an offline document workflow. That belongs in client appearance tooling if it is ever rebuilt. It does not inform server, listserver, or remote-control work. Do not paste the Delphi UI.

Recommended placement

Placement	**`out-of-scope / seihai (client)`**
Why	Offline character and sprite tooling.
Not	`setup-core` / `lat-core` / `seihai-rc`
Licence	Legacy third-party Delphi tool — notes only

Program (counts only)

Field	**Value**
Compiler	Borland Delphi
Functions	1884 (internal 1530)
Imports	375 (registry, image lists, file dialogs, a large GDI surface)
Interesting strings	88
Decompiled locally	30 — **not committed**

Most symbols are anonymous Delphi stubs. Behaviour above is from the import shape and the string table, paraphrased. Raw dumps are not committed.

`recovered-drive-tools/ghidra-analysis/GChar/SUMMARY.md`

Salvage analysis: GChar (character generator)

- **Binary:** `_inbox/extracted/charactergenerator/charactergenerator/GChar.exe`
- **Analyzed (UTC):** 20261031T210011Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland Delphi, ~407 KB
- **sha256:** `fe73e10fff6db1a9db88fc054315df05623a36f4fedc6ff6cf9c0f92038a60ea`

Purpose

Offline character generator, same Bruges lineage as the Character Designer and labelled as a 1.0 sibling. Same job: edit classic character and head files without a network session.

Screens and files:

- Designer forms for appearance, plus an about box and a prompt for the client install directory.
- Looks for the client executable, a heads configuration, and head and gif asset folders. Missing heads configuration is an error.
- Keeps a private ini and can write a local error log. A log-errors switch is present.
- Image lists, open and save dialogs, and the usual Delphi drawing surface. Gif loads can fail. No sockets.

What Seihai could learn

Same as the Character Designer: client-folder discovery and offline character files. Useful only as a note next to client appearance editors. Not a servertools target.

Recommended placement

Placement	**`out-of-scope / seihai (client)`**
Why	Client character tooling.
Not	`setup-core` / `lat-core` / `seihai-rc`
Licence	Legacy third-party tool — notes only

Program (counts only)

Field	**Value**
Compiler	Borland Delphi
Functions	1934 (internal 1562)
Imports	375 (same Delphi GUI shape as the Character Designer)
Interesting strings	90
Decompiled locally	30 — **not committed**

Raw imports and strings stay in the gitignored local analysis folder.

`recovered-drive-tools/ghidra-analysis/Graal_Auto_Key/SUMMARY.md`

Salvage analysis: Graal Auto Key

- **Binary:** `_extracted/unpacked/Graal_Auto_Key.unpacked.exe` (static unpack of the UPX sample; the PE was never executed)
- **Analyzed (UTC):** 20261031T210030Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), ~85 KB unpacked
- **sha256:** `a99410a422694d84eb5ad1b93e2406c15f14a83a9d9d818bad3ab6f289ebf0f0`

Purpose

Client trainer that sends keyboard and mouse input to the focused window. The shipped sample is UPX-packed. The unpacked image is an AutoIt 2.64 script host: script line errors, a file picker, registry access, token privileges, and a vendor banner. Named symbols are C runtime heap and locale helpers, not game logic. Exports are runtime entry stubs.

It does not speak a server protocol. It is the same class of tool as other recovered trainers.

What Seihai could learn

Nothing for server tools. A host indicator is the file hash plus AutoIt-on-UPX packaging. Do not reimplement the macro, and do not run the sample.

Recommended placement

Placement	**`out-of-scope`**
Why	Client trainer. Decision tree: do not place in seihai-servertools.
Defence note	Same class as recovered-hacks trainers.
Licence	Untrusted third-party binary

Program (counts only)

Field	**Value**
Functions	303 (internal 301)
Imports	158 (file, registry, process, and input-capable Win32 surface)
Exports	13 runtime stubs
Interesting strings	34
Decompiled locally	30 — **not committed**

Raw import and string lists stay in the gitignored local analysis folder.

`recovered-drive-tools/ghidra-analysis/Graal_Digger/SUMMARY.md`

Salvage analysis: Graal Digger

- **Binary:** `_inbox/extracted/Graal_Digger/Graal Digger.exe`
- **Analyzed (UTC):** 20261031T210058Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), UPX-compressed, 3 sections, ~36 KB, December 2002
- **sha256:** `876723732378b36e8fd31d09120ec5a1b584cf46fb672ab9d5cf7a0a4f8b56d4`

Purpose

Client auto-dig / away-from-keyboard shovel helper. A short howto ships in the pack. The file is the same truncated UPX image as the trainers copy (hash match). A static unpack fails because the overlay is corrupt. Ghidra sees only the packer stub: one internal function, no imports, and no application strings. Bytes that survive a string filter are packer noise, not UI text. Packed-stream hints point at an AutoIt 2.63 host, which matches the other trainer, but that script was not recovered.

What Seihai could learn

Nothing. Out of scope. See also the trainers note under `recovered-hacks/ghidra-analysis/Graal_Digger/SUMMARY.md`. Do not run the PE.

Recommended placement

Placement	**`out-of-scope`**
Why	Client digger. Corrupt packer overlay.

Placement	**`out-of-scope`**
Licence	Untrusted third-party binary

Program (counts only)

Field	**Value**
Functions	1 (internal 1)
Imports	0
Interesting strings	0 readable
Decompiled locally	1 stub — **not committed**

`recovered-drive-tools/ghidra-analysis/GraalLevelGenNW/SUMMARY.md`

Salvage analysis: GraalLevelGenNW

- **Binary:** `Developer Tools/LAT Tool - [Level Administration Team]/Level Generators/GraalOnline Level Generator - NW - [2001-10-08].rar.extracted/GraalLevelGenNW/GraalLevelGenNW.exe`
- **Analyzed (UTC):** 20261031T211951Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland Delphi, ~422 KB

Purpose (plain behaviour)

Offline **New World level / world generator**. The window is branded as a level generator, and the output file starts with a short magic that marks a New World level. The operator loads a map image, then generates a world into a levels directory. The pack also holds a sample map image and a large map text table. Strings cover New World calendar fields (year, month, day, hour, and smaller units) and per-level options such as whether warping is allowed. Not a network service.

Sibling LAT generators exist for classic Graal, terrain, and dungeon variants — same offline-content role.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	**`lat-core` (content tooling) / `analysis-only` for the PE**
Why	Offline world/level generation aids LAT workflows; promote behaviour into generators/docs, not binary reuse.
Not	`setup-core` / `seihai-rc`
Related	`GraalLevelGen.exe` (classic), TerrainGenerator, dungeongen, Graal Map Generator (2024 src)
Licence	Legacy Delphi — clean-room notes only

Ghidra stats (machine)

Field	**Value**
Functions	~2038 (internal ~1678)
Imports	~375
Interesting strings	~118
Decompiled (local only)	20 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/gserver-linux/SUMMARY.md`

Salvage analysis: gserver (Linux ELF from GServersource)

- **Binary:** `/workspace/recovered-drive-tools/_inbox/extracted/GServersource/gserver`
- **Analyzed (UTC):** prior headless · SUMMARY rewritten 20261031T211700Z — **prefer paired C++ source**
- **Ghidra:** 12.2
- **Purpose focus:** recover CLI, protocols, config paths, and rebuild/rehost notes for seihai-servertools (ops/server tooling — not malware inventing).

Purpose guess

Classic **Graal game server** daemon (ELF32, dynamically linked, not stripped, ~Jun 2002). Same tree as Windows `gserver.exe` and full sources (`gserver.cpp`, `npcs.cpp`, `levels.cpp`, MySQL account helpers, password crypto). Headless RE confirms symbols already named in source (`startServer`, `parse`, `enterLevel`, `SendAccount`, RC player-prop paths, DB load/save).

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	**`analysis-only`**
Why	Canonical legacy gserver; licence/GPL-adjacent. Seihai already has its own server — use only as protocol/behaviour reference.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc` (do not paste sources into MIT crates)
Related	`gserver-win`, `gserver_pe_GServersource`, `gserver13`, Matriark 1.39 build
Licence risk	High — source tree includes `passwords.h` / crypto; clean-room notes only

Identity

```
# file
ELF 32-bit LSB executable, Intel 80386, dynamically linked, for GNU/Linux 2.2.5, not stripped

# size
~1.3M

# sha256
56d9f0f8ba666c2e9ceb556932c01317374cf9d0e56c730b4d2643ce56947f9e
```

Ghidra program

Field	**Value**
Format	ELF

Field	Value
Language	x86:LE:32:default / gcc
Functions	628 (internal 419)
Imports	105
Interesting strings	641
Decompiled funcs	40

Behaviour (source-led)

From `gserver.h` / `gserver.cpp`: listens on a configured port (`startServer`), accepts players and Remote Control sessions, parses client package types (level warp, board modify, player/NPC props, bombs, horses, arrows, flags, chests, weapons, PMs, …). Account persistence via MySQL (`connecttodb`, `LoadDBAccount` / `SaveDBAccount`) and/or file-era helpers; password encryption helper present. RC-facing paths update player/account props and write RC log lines. Level/NPC/weapon loaders (`LoadNW`, `LoadWeapons`, `enterLevel`) drive world state.

Do not deep-decompile further while this source tree is available.

Prefer source trees

- `_inbox/extracted/GServersource/` (and Developer Tools `GServer Source/GServersource.rar.extracted/`)
- Older `gserver_source/` for `gserver13` / stats tools

Artifacts

- Local Ghidra export retained for symbol cross-check; authoritative behaviour = source.

`recovered-drive-tools/ghidra-analysis/gserver-win/SUMMARY.md`

Salvage analysis: gserver.exe (Win32 from GServersource)

- **Binary:** `/workspace/recovered-drive-tools/_inbox/extracted/GServersource/gserver.exe`
- **Analyzed (UTC):** prior headless · SUMMARY rewritten 20261031T211700Z — **prefer paired C++ source**
- **Ghidra:** 12.2

Purpose guess

Windows console PE of the **same classic gserver** as `gserver-linux` (same tree, same era, sha256 `ad146b971eb1af76471d439f3f48b843e44c03b9b85f0ec9995877d6ba91bc01`). Symbols mirror Linux: `startServer`, parse/chat, account send, NW level load, RC player props, MySQL connect/bind/listen/accept, password encrypt.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	`analysis-only`
Why	Duplicate of Linux ELF behaviour; source tree authoritative.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`

Placement	`analysis-only`
Related	`gserver-linux`, `gserver_pe_GServersource` (same PE analyzed under alternate dir name)
Licence risk	Same as Linux twin — clean-room only

Identity

```
PE32 executable (console) Intel 80386, for MS Windows, 6 sections · ~2.8M
```

Ghidra program

Field	Value
Functions	1051 (internal 1007)
Imports	141
Interesting strings	1762
Decompiled funcs	~29–39

Note

`gserver_pe_GServersource/` analyzes the **same binary path/hash**. Keep one behavioural story; avoid duplicate deep RE.

`recovered-drive-tools/ghidra-analysis/gserver13/SUMMARY.md`

Salvage analysis: gserver13

- **Binary:** `/workspace/recovered-drive-tools/_inbox/extracted/gserver_source/gserver13`
- **Analyzed (UTC):** prior headless · SUMMARY rewritten 20261031T211700Z — **prefer source/tree notes**
- **Ghidra:** 12.2

Purpose guess

Earlier classic **Linux gserver** ELF32 (not stripped, ~Dec 1999, dynamically linked). Sibling sources/objects in `gserver_source/` (`gserver.cpp`, makefile, zlib). Symbols cover account parse/apply, level enter/update, guild name verify, ban-IP checks, inflate helpers, RC-related NPC/server string types — same product family as later GServersource, older build.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	`analysis-only`
Why	Historical gserver; compare against later source tree rather than paste.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`
Related	`gserverstat` / `gserverstat2` / `statmaker` in same folder
Licence risk	Legacy/GPL-adjacent

Identity

```
ELF 32-bit LSB executable, Intel 80386, dynamically linked, for GNU/Linux 2.0.0, not stripped
~870K · sha256 be1c397d2c21049c7848a7c922455861ee0a4b413967c867c2e7efa90a7c9997
```

Ghidra program

Field	Value
Functions	1128 (internal 915)
Imports	106
Interesting strings	448
Decompiled funcs	40

Prefer source

`_inbox/extracted/gserver_source/` — do not deep-decompile further for salvage docs.

`recovered-drive-tools/ghidra-analysis/gserver_pe_GServersource/SUMMARY.md`

Salvage analysis: gserver.exe (alias of GServersource Win PE)

- **Binary:** `/workspace/recovered-drive-tools/_inbox/extracted/GServersource/gserver.exe`
- **Note:** Identical sample to `gserver-win/` (same sha256). SUMMARY points there.

Recommended placement

`analysis-only` — see `../gserver-win/SUMMARY.md` and `../gserver-linux/SUMMARY.md`. Prefer `_inbox/extracted/GServersource/` C++ sources; watch `passwords.h` (do not copy).

`recovered-drive-tools/ghidra-analysis/gserverstat/SUMMARY.md`

Salvage analysis: gserverstat

- **Binary:** `_inbox/extracted/gserver_source/gserverstat`
- **Analyzed (UTC):** 20261031T205919Z · Ghidra 12.2 · static only
- **Format:** ELF32, dynamically linked, not stripped, egcs-era, for early GNU/Linux, ~513 KB, December 1999
- **sha256:** `b8ae1a13147567d6544fb30ab383359e6c1c19849deb9d87d219f7cf90af867d`

Purpose

Offline HTML leaderboard generator for classic gserver account stats. It is not a network service.

What it does:

- Reads the on-disk account store and optional name lists that a CGI-style helper would have written beside the server tree.
- Emits a simple themed HTML table (a fixed green page, a background image, muted text and links) that points at a local startup script.
- A companion shell runs the binary once per board — kills, deaths, currency, high and low alignment, and time online — and redirects the HTML into a stats directory under the web tree.
- The image is unstripped and shares account parse, load, and save helpers with classic gserver, including temporary accounts, weapon name lists, and buffer compression. A server-frame type from that tree is present, but this program only formats stats.

- Imports are libc file and formatted I/O. There is no listen, bind, or socket use.

Build leftovers place the compile in the late-1990s gserver stats tree (the same folder as the classic server sources) with an egcs and glibc 2.1-era toolchain.

What Seihai could learn

Lab status does not need this emitter. If a world folder already writes plain count files, `setup-core` can read those. Do not copy the HTML theme, the CGI paths, or this binary. Prefer the paired sources in `gserver_source/` over further decompilation.

Recommended placement

Placement	**`analysis-only`**
Why	Legacy account-dump tooling. Behaviour notes only.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`
Related	`statmaker` and the Server Lister stats script in the same era
Licence	Legacy gserver-era C++ — clean-room notes only

Program (counts only)

Field	**Value**
Functions	899 (internal 744)
Imports	77 (stdio and libc; no sockets)
Exports / entries	1296 (unstripped C++ helpers, not a network API)
Interesting strings	223
Decompiled locally	50 — **not committed**

Mangled names, import tables, and string text stay in the gitignored local analysis folder.

`recovered-drive-tools/ghidra-analysis/gserverstat2/SUMMARY.md`

Salvage analysis: gserverstat2

- **Binary:** `_inbox/extracted/gserver_source/gserverstat2`
- **Analyzed (UTC):** 20261031T205935Z · Ghidra 12.2 · static only
- **Format:** ELF32, dynamically linked, not stripped, same era and size class as `gserverstat`, ~513 KB, December 1999
- **sha256:** `966feaab46fea8b93e8b6c8a23cc333b9161f8f08f246b376cf4bfdb375fedbd`

Purpose

Admin sibling of `gserverstat`. Same offline account scan and the same libc file I/O. It does not listen.

The companion shell drives weapon and power boards — sword, gloves, bombs, shield, maximum power, and high alignment — and writes them under an admin stats directory. The page theme matches the public leaderboards: a fixed green table, a background image, and a pointer at a local startup script. Account input is the same store and the same optional CGI-style name lists.

Symbols match the public tool: account parse, load, and save, plus list and compression helpers shared with classic gserver. Imports are formatted stdio only.

What Seihai could learn

Same as `gserverstat`: optional lab status can read plain count files if a profile emits them. Do not rehost this HTML generator and do not paste its strings. Prefer `gserver_source/` over decompilation.

Recommended placement

Placement	**`analysis-only`**
Why	Admin weapon and power leaderboards from the same gserver-era tree.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`
Related	`gserverstat`, `statmaker`
Licence	Legacy gserver-era C++ — behaviour notes only

Program (counts only)

Field	**Value**
Functions	899 (internal 744)
Imports	77 (stdio and libc; no sockets)
Exports / entries	1296
Interesting strings	223
Decompiled locally	50 — **not committed**

Raw exports and strings stay in the gitignored local analysis folder.

`recovered-drive-tools/ghidra-analysis/ListServer/SUMMARY.md`

Salvage analysis: ListServer (UPX-unpacked)

- **Binary:** `_extracted/unpacked/ListServer.unpacked.exe` (static `upx -d` of recovered Win32 ListServer; PE never executed)
- **Analyzed (UTC):** 20261031T204840Z · SUMMARY placement pass 20261031T212200Z
- **Ghidra:** 12.2
- **Format:** PE32 GUI (x86), Borland Delphi

Purpose guess

Windows **list / server-directory** helper for classic Graal. Delphi visual library plus Winsock listen, bind, connect, and close. It reads an ini list of servers, stores client preferences in the application registry, and shows a connect dialog with version and player-count fields. Bundled deflate. Companion to the ELF listserver — different packaging, same product niche.

Do not run this PE (or the packed original) against public networks.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	**`analysis-only`**
Why	Legacy Delphi listserver UI; prefer C# rewrite notes under `_extracted/listserver-nested/graal-listserver/` and ELF `serverlist3` behaviour notes.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`
Related	`serverlist3`
Licence	Legacy third-party — clean-room only

Ghidra program

Field	**Value**
Functions	3299 (internal 2874)
Imports	430 (ADVAPI32 registry, COMCTL32, GDI32, WSOCK32)
Exports	3
Interesting strings	112
Decompiled (local only)	40 — **not committed**

Behaviour (plain prose)

Most symbols are anonymous Delphi stubs. Behaviour comes from the import surface and the string table: a socket listen and connect path, a local server-list config, a client preferences hive, and JPEG UI chrome. No database client (unlike the static ELF listserver) — this build looks like a lightweight Windows lister rather than the full Linux auth directory.

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/Matriark_gserver/SUMMARY.md`

Salvage analysis: Matriark's GServer (1.39)

- **Binary (ELF):** `Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.39.rar.extracted/GServer 1.39/Matriark's GServer/gserver`
- **Also in pack:** Win32 `GServer.exe`, `dbsetup.exe`, `GStats.exe`, `gserverstats.pl` / `gserverstats2.pl`, `wingserver.zip`, short bugs note
- **Analyzed (UTC):** 20261031T212013Z · Ghidra 12.2 · static only
- **Format:** ELF 32-bit LSB (x86), **statically linked, stripped**, ~1.4 MB (hash differs from unstripped `GServersource/gserver`)

Purpose (plain behaviour)

Community **Matriark** build of classic **gserver** (pack labelled 1.39). Same product niche as `gserver-linux` / `gserver13` / Win PE twins: world daemon with database account and profile tables, a guilds path, remote-control and NPC session surfaces, and leaderboard-style queries (kills, deaths, time online, alignment). Static link and

strip hide symbols. Strings show account load and save failures, admin-level lookups, decompress errors, and a local database file name.

Pack-local bugs note (behaviour only): head, shield, and sword path checks disagree with the paths used when sending level files; a guild nickname clash requires a marker prefix; a possible server-flag or account overflow is mentioned without detail. Prefer the **GServersource C++ trees** over deep decompile of this stripped image.

Do not run against public networks.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	**`analysis-only`**
Why	Alternate classic gserver binary; clean-room protocol/ops notes only. Prefer paired sources under `_inbox/extracted/GServersource/` / `gserver_source/`.
Related	`gserver-linux/`, `gserver13/`, `gserver-win/`, `gserver_pe_GServersource/`
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc` as a drop-in binary
Licence	Legacy third-party — clean-room only

Ghidra stats (machine)

Field	**Value**
Functions	~3658 (internal ~3658)
Imports	0 (static)
Exports / entries	~2
Interesting strings	~407
Decompiled (local only)	20 — **not committed**

Prefer source / unstripped twins

- `_inbox/extracted/GServersource/` (`gserver.cpp`, `npcs.cpp`, `levels.cpp`, …)
- `_inbox/extracted/gserver_source/` (`gserver13`, stats tools)
- Do not deep-decompile this stripped static ELF further for salvage docs.

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/NPCControl/SUMMARY.md`

Salvage analysis: NPCControl

- **Binary:** `Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/nc7132001 [V2].rar.extracted/nc7132001/NPCControl.exe`
- **Same-size twin:** `nc7132001.exe` in the same pack / `nc7132001.rar`
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), **Borland Delphi**, ~471 KB

Purpose (plain behaviour)

Classic **NPC Control** staff client for an NPC server or world control port. The banner dates it to a July 2001 GServer2-era build.

Observed behaviour:

- Reads a small text config for the server name, port, and password, and mirrors those preferences in the application registry.
- The window is titled as NPC Control. It reports a connected port, a failed connect, and a decompression failure.
- Manages NPCs and weapons: delete confirms, take a script from a class, edit a weapon script, and a local-NPC list.
- Opens rich-text and plain script files, and references a local startup script plus sample level names (ignore any embedded world names).
- Ships deflate helpers for compressed wire or packed payloads.

Sibling pack also includes `RemoteControl-NW.exe` (see that SUMMARY) for the RC side of the same era.

Do not run against public hosts.

Recommended placement

Tag	**`seihai-rc`**
Why	Live NC session / NPC+weapon script admin over the wire.
Also	PE stays staged (`analysis-only` dumps).
Not	`setup-core`, `lat-core`, client trainers
Licence	Legacy Delphi — clean-room notes only

Ghidra stats (machine)

Field	**Value**
Functions	~2428 (internal ~2052)
Imports	~394
Interesting strings	~102
Decompiled (local only)	30 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/PNGView/SUMMARY.md`

Salvage analysis: PNGView

- **Binary:** `Developer Tools/GAT Tool - [Graphics Administration Team]/PNGView.rar.extracted/PNGView/PNGView.exe`
- **Analyzed (UTC):** 20261031T212141Z · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland Delphi, ~800 KB

Purpose (plain behaviour)

GAT-era **offline PNG / image viewer** helper. Graphics-admin utility for inspecting asset files — not a network service. Useful only as a behaviour/context note next to other GAT converters (`Assimilator`, tile editors); not a rewrite priority.

Recommended placement

Tag	**`analysis-only`**
Why	Offline viewer; no protocol or server placement.
Related	`Assimilator/`, `TilesEditor/`
Not	`setup-core`, `seihai-rc`, `lat-core`
Licence	Legacy Delphi — notes only

Ghidra stats (machine)

Field	**Value**
Functions	~3348 (internal ~2965)
Imports	~388
Exports / entries	~3
Interesting strings	~120
Decompiled (local only)	20 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/README.md`

Ghidra salvage analyses

Produced by `/workspace/tools/ghidra/analyze_tool.sh`.
Pipeline docs: `/workspace/tools/ghidra/README.md`.
Placement: `seihai-servertools/docs/design/SALVAGE_PLACEMENT.md` · inventory: `../INVENTORY.md`.

Focus: purpose, CLI, protocols, and config roles for rebuild notes. Do **not** paste decompiled Delphi/GPL or GServer-v2 sources into MIT crates. Committed `SUMMARY.md` files are hand-written prose only: no string dumps, import lists, decompiler names, or binary offsets. Raw exporter output belongs in gitignored `tools/ghidra/local-out/`.

Completed

Dir	**Binary**	**Placement**	**Highlights**
`RemoteControl3/`	`windows_rc3_beta` / v5 `RemoteControl3.exe`	`seihai-rc`	GTK Win32 RC; listserver + NPC-server connect; player/NPC/account/file UI.
`remotecontrol_custom/`	Custom `remotecontrol.exe` (+ UPX `Agret_RC.exe`)	`seihai-rc`	Delphi Agret “Blue RC”; `controlconfig.txt` / `Software\Graal`.
`RemoteControl_classic/`	`rc.rar` `RemoteControl.exe`	`seihai-rc`	Stock Delphi RC baseline vs Agret/NW.

Dir	Binary	Placement	Highlights
`RemoteControl-NW/`	NW2 / NC-pack `RemoteControl-NW.exe`	`seihai-rc`	NW-era Delphi RC; admin/account/ban/update-level.
`NPCControl/`	`nc7132001` `NPCControl.exe`	`seihai-rc`	NC client; `controlconfig.txt`; NPC/weapon/class scripts.
`scripteditor/`	Senolen `scripteditor.exe` 2.53	`analysis-only`	NAT GS1 script editor UX; prefer GS2 sources for modern notes.
`PNGView/`	GAT `PNGView.exe`	`analysis-only`	Offline PNG viewer beside Assimilator.
`serverlist3/`	`slist/serverlist3`	`analysis-only`	ELF32 classic listserver; `clientsport`/`serversport`/`playerlimit`. Prefer C# rewrite tree.
`ListServer/`	UPX-unpacked `ListServer.exe`	`analysis-only`	Win32 Delphi plus Winsock; an ini server list. Do not run.
`gserver-linux/`	`GServersource/gserver`	`analysis-only`	ELF32 — prefer paired C++ source.
`gserver-win/`	`GServersource/gserver.exe`	`analysis-only`	Win32 PE same era/hash as pe alias.
`gserver13/`	`gserver_source/gserver13`	`analysis-only`	Classic Linux gserver ELF.
`gserver_pe_GServersource/`	same PE as `gserver-win`	`analysis-only`	Alias; watch `passwords.h` in sources.
`Matriark_gserver/`	Matriark 1.39 static ELF `gserver`	`analysis-only`	Stripped static; prefer GServersource notes + pack bugs.txt.
`BytecodeViewer/`	GS2 `BytecodeViewer.exe`	`analysis-only`	Console dump of Relay bytecode; **source authoritative**.
`TextConvert/`	`TextConvert.exe`	`analysis-only` / client-adjacent	Graal→NW text helper.
`Assimilator/`	GAT GIF2PNG `Assimilator.exe`	`seihai` / `analysis-only`	Offline Graal asset batch checker/converter.
`TilesEditor/`	39ster `TilesEditor.exe`	`seihai` · later `lat-core`	Qt64 offline level/NPC/chest editor.
`GraalLevelGenNW/`	`GraalLevelGenNW.exe`	`lat-core` / `analysis-only`	Offline NW world generator from map image.
`gserverstat/`	`gserverstat`	`analysis-only`	HTML leaderboards; `statmaker` loop.
`gserverstat2/`	`gserverstat2`	`analysis-only`	Admin power/weapon HTML stats.
`GCD/`	`GCD.exe`	`out-of-scope / seihai (client)`	Character Designer 1.2.7 (Delphi).
`GChar/`	`GChar.exe`	`out-of-scope / seihai (client)`	Character generator sibling.
`Graal_Auto_Key/`	UPX-unpacked Auto Key	`out-of-scope`	AutoIt v2.64 key sender trainer.
`Graal_Digger/`	truncated UPX digger	`out-of-scope`	Trainer overlap; UPX corrupt.
`DClient_setup/`	salvaged `setup.exe`	`stay-staged` / client `out-of-scope`	VB6 bootstrapper; CAB truncated on Drive.

Prefer source over RE when present

- `_inbox/extracted/GServersource/` — `gserver.cpp`, `npcs.cpp`, `levels.cpp`, makefiles, MySQL bits.
- `_inbox/extracted/gserver_source/` — `gserver13`, `gserverstat*`, `statmaker`.
- `_extracted/listserver-nested/graal-listserver/` — C# listserver rewrite.
- `_extracted/gs2-compiler/GS2 Compiler/BytecodeViewer/Source/` — BytecodeViewer C++.
- `_extracted/gs2-compiler/GS2 Compiler/BytecodeCompiler/` — C++ compiler sources.

Blockers

Item	Reason
`DClientSetup1198.zip`	Truncated on Drive (no EOCD).

Item	Reason
`GServer Stats.zip` (Drive)	Google `cannotDownloadAbusiveFile` — skipped.
Other malware-blocked Drive archives	See `INVENTORY.md` (`Account Manager.rar`, cracked client rars, `apcalc.exe`, …) — skipped.
`Graal Digger.exe`	Corrupt UPX overlay; trainer overlap.
Matriark / some Delphi PEs	Headless may exit nonzero after successful export (`rc=1`); artifacts still present — treat SUMMARY prose as authoritative.

Re-run

```
/workspace/tools/ghidra/analyze_tool.sh \
  /path/to/bin \
  /workspace/recovered-drive-tools/ghidra-analysis/<name> [max_decomp]
```

Raw files land in gitignored `tools/ghidra/local-out/<tool>/`. Edit `SUMMARY.md` by hand; the script will not overwrite it and will not paste strings or imports into it.

`recovered-drive-tools/ghidra-analysis/RemoteControl-NW/SUMMARY.md`

Salvage analysis: RemoteControl-NW

- **Binary:** `Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2 - New World/GraalNW2.rar.extracted/GraalNW2/$Graal-NW/RemoteControl-NW.exe`
- **Also in:** `NC [NPC Control]/nc7132001 [V2].rar.extracted/…/RemoteControl-NW.exe` (same size class)
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), **Borland Delphi**, ~588 KB

Purpose (plain behaviour)

New World–era Remote Control Delphi client bundled with NW client packs and the NC V2 pack.

Same family as classic `rc.rar` / Custom Agret RC:

- Reads the same kind of text config as the other Delphi remote controls. Account and player editors, and a database account list that can search attributes such as admin level, admin worlds, and block state.
- Staff actions: admin message and broadcast, edit account, update level, disconnect, ban, mark a player away when the list closes, and a toggle for HTML in private messages.
- Winsock connect path; zlib deflate embedded.
- Comparative sample for NW protocol quirks vs v1 RC / GTK RC3.

Do not run on public networks.

Recommended placement

Tag	`seihai-rc`
Why	Staff RC binary (NW variant).
Also	Staged PE / dumps = `analysis-only`
Not	`setup-core` / trainers

Ghidra stats (machine)

Field	Value
Functions	~2667 (internal ~2263)
Imports	~418
Interesting strings	~106
Decompiled (local only)	30 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/RemoteControl3/SUMMARY.md`

Salvage analysis: RemoteControl3

- **Binary:** `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/windows_rc3_beta.rar.extracted/RemoteControl3.exe`
- **Also same PE in:** Main Client `v5/Graalv5.rar.extracted/…/RemoteControl3.exe`
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Windows toolchain, ~2.2 MB, heavily sectioned (16)

Purpose (plain behaviour)

Staff **Remote Control** client for classic Graal servers. UI is **GTK** on Windows (gdk/glib/pixbuf imports) rather than Delphi.

Observed behaviour from symbols and strings (no offsets):

- Shows a server list, a version field, a password field that need not be saved, and a connect action.
- Talks to a listserver or server-pick path and to a separate NPC server, with a label once that NPC server is connected.
- After connect: a player list (refresh, mass private message, admin message), an NPC list and local NPCs, a level-NPC dump, folder and config pages, and profile, rights, account, and access editors.
- Staff actions: ban with time and reason, warp to a player, warp players, disconnect, update level, away mode when the player list closes, and an option to keep NPC-control chat separate from remote-control chat.
- Embeds bzip2 and zlib compress helpers and password encrypt/decrypt helpers. Treat the wire encoding as opaque for clean-room notes.
- Syntax highlighters for Graal script, ini, Pascal, and C++ — an in-client script editing surface.

Do not run this PE against public hosts; lab loopback only if ever needed.

Recommended placement

Tag	`seihai-rc`
Why	Live RC/NC session, staff file/NPC/player tooling over the wire.
Also	Raw PE + Ghidra dumps stay staged here (`analysis-only` artifacts).

Tag	`seihai-rc`
Not	`setup-core`, `lat-core` (until shared edit crates exist), MIT paste of decompile
Licence	Proprietary/legacy client — clean-room protocol notes only

Ghidra stats (machine)

Field	Value
Functions	~3653 (internal ~3562)
Imports	~529 (Win32 + GTK stack + Winsock/IPHLPAPI)
Interesting strings	~405
Decompiled (local only)	25 — **not committed**

Named areas, without addresses: sorting and init, listserver connect, NPC-server connect, connect to the selected server, password encrypt and decrypt, socket bind and connect, compression handling, and window builders for the player list, profile, rights, account, options, and access.

Artifacts (local, gitignored except this SUMMARY)

`prelim/`, `functions.txt`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/RemoteControl_classic/SUMMARY.md`

Salvage analysis: RemoteControl (classic `rc.rar`)

- **Binary:** `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc.rar.extracted/RemoteControl.exe`
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland Delphi, ~888 KB

Purpose (plain behaviour)

Stock **Graal Remote Control** from the classic `rc.rar` line (sibling of `rc2.rar` / Custom Agret builds).

Observed behaviour:

- Classic remote-control window title and a server-list connect screen (connecting, disconnect, and cannot-connect messages).
- Preferences live in the application registry. A local startup script and password fields appear.
- NPC tooling: attributes, script and flags from an NPC, an NPC level list, local NPCs, and a delete confirmation. It reports when the NPC server is connected, and it shows a player count.
- Account and player editors. Winsock connect. Embedded deflate.

Comparative baseline for `remotecontrol_custom/` (Agret) and `RemoteControl-NW/`.

Do not run against public hosts.

Recommended placement

Tag	`seihai-rc`
Why	Canonical Delphi RC client for clean-room staff-session behaviour.
Staging	PE/dumps remain `analysis-only` artifacts
Not	`setup-core`, trainers

Ghidra stats (machine)

Field	Value
Functions	~3623 (internal ~3163)
Imports	~466
Interesting strings	~137
Decompiled (local only)	20 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/remotecontrol_custom/SUMMARY.md`

Salvage analysis: remotecontrol (Custom / Agret)

- **Binary:** `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/Custom RemoteControl.rar.extracted/Custom RemoteControl/remotecontrol.exe`
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), **Borland Delphi**, ~1.0 MB

Purpose (plain behaviour)

Community-modified remote control (Agret branding, a blue theme, and a text config with nickname and UI colour keys). Classic Delphi visual library rather than the GTK RemoteControl3 line. Companion **`Agret_RC.exe`** in the same folder is a **UPX-packed** PE; a static unpack yields a different hash from this `remotecontrol.exe` (variant build, not a byte-identical pack).

Observed behaviour:

- Classic remote-control window title. Winsock connect to a server chosen from a server list, with connecting, failure, and disconnect messages.
- Tracks the player count and whether the NPC server is connected.
- Preferences live in the application registry, next to a local startup script, a flag to avoid saving the password, and toggles for the player list, the NPC list, and local NPCs.
- NPC tooling: attributes, script and flags taken from an NPC, an NPC level list, local NPCs, and a delete confirmation.
- Account and player editors.
- Same general staff RC role as stock Delphi RC packs (`rc.rar` / `rc2.rar` lineage) — useful comparative sample for `seihai-rc` wire behaviour.

Do not run against public servers.

Recommended placement

Tag	**`seihai-rc`**
Why	Staff RC session client; protocol/UI behaviour for clean-room RC.
Also	Keep PE staged; `analysis-only` for raw dumps.
Not	`setup-core` / `lat-core` / trainer scope
Licence	Legacy Delphi client — notes only, no decompile paste

Ghidra stats (machine)

Field	**Value**
Functions	~3707 (internal ~3241)
Imports	~471 (typical Delphi + WSOCK32/advapi/comctl)
Exports	PE entry stubs only (~3)
Interesting strings	~159
Decompiled (local only)	30 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/ghidra-analysis/scripteditor/SUMMARY.md`

Salvage analysis: scripteditor (Senolen 2.53)

- **Binary:** `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Script Editors/scripteditor253.rar.extracted/Script Editor/scripteditor.exe`
- **Mirrors:** Tools `scripteditor253.zip` / `.7z`; “player added files” rar variant
- **Analyzed (UTC):** 2026-10-31 · static strings + file(1); Ghidra optional follow-up in same dir
- **Format:** PE32 GUI (x86), ~1.0 MB

Purpose (plain behaviour)

Script Editor by Senolen (v2.53 pack; upgrade UI mentions 2.54). GS1-era NPC/weapon scripting helper, not the later GS2 compiler.

Observed menu/behaviour surface:

- Open, close, play, and test documents, and set the client folder.
- Insert templates: NPC script, weapon, baddy scripting, chat command, function, conditional, take-item, horse and leap placement, and a note about a 3D light NPC.
- A find-NPC helper backed by a rich-text guide, paste script, save and save-as.
- Built-in “upgrade/download” path (do **not** use — external fetch; ignore for lab).

Prefer GS2 compiler **source** under `GS2 Compiler.rar` for modern script tooling notes; this editor is historical UX reference only.

Recommended placement

Tag	`analysis-only`
Why	Legacy GS1 script UX; not a clean-room target for MIT crates as-is.
Related	`BytecodeViewer/` + GS2 compiler sources
Not	`setup-core`, live `seihai-rc` session code

Notes

Re-run Ghidra into this folder if deeper import graphs are needed; keep SUMMARY free of offsets and anonymous decompiler names.

`recovered-drive-tools/ghidra-analysis/serverlist3/SUMMARY.md`

Salvage analysis: serverlist3

- **Binary:** `/workspace/recovered-drive-tools/_extracted/server-lister/Server Lister/slist/serverlist3` (also under `_inbox/extracted/Server Lister/slist/` and Developer Tools Server Lister extract)
- **Analyzed (UTC):** 20261031T204000Z (artifacts) · SUMMARY rewritten 20261031T211700Z
- **Ghidra:** 12.2
- **Purpose focus:** recover CLI, protocols, config paths, and rebuild/rehost notes for seihai-servertools (ops/server tooling — not malware inventing).

Purpose guess

Classic **list / login server** (ELF32, statically linked, not stripped). One process listens for client and game-server connections, serves the public server directory, and backs account auth against a database. It takes a full path to a configuration file as its only argument and refuses to start if that file is missing. The console reports that the lister has started, with the client and game-server port context, player-limit accounting, and disconnect notices.

Recommended placement (`SALVAGE_PLACEMENT.md`)

Placement	`analysis-only`
Why	Legacy GPL-adjacent listserver binary; behaviour notes only. Prefer the recovered C# listserver rewrite tree under `_extracted/listserver-nested/graal-listserver/` for any modern rehost design.
Not	`setup-core` / `lat-core` / `seihai` / `seihai-rc`
Related	Win32 `ListServer` (Delphi), Server Lister package scripts (`gserverstats.pl`)
Licence risk	Legacy/static glibc+MySQL client — never paste into MIT crates

Identity

```
# file
ELF 32-bit LSB executable, Intel 80386, version 1 (SYSV), statically linked, for GNU/Linux 2.2.5, not stripped

# size
~3.3M
```

```
# sha256
eb5272ab1653f93fc00b41368caa52d7af565f16e3d575a18e4c1ba1e1da87c3
```

Ghidra program

Field	Value
Format	Executable and Linking Format (ELF)
Language	x86:LE:32:default
Compiler	gcc
Functions	2197 (internal 2197)
Imports	0 (static link)
Exports / entries	4486
Interesting strings	2375
Decompiled funcs	50

Behaviour (plain prose)

The config covers the client listen port, the game-server listen port, and a player cap. Side files track the free and used player budget: a maximum, a live count, and a small stats file.

Database shapes (behaviour only): account rows hold an encrypted password, email, block and ban fields, and admin level and worlds. Directory rows hold the world name, language, description, a homepage, client version, player count, address, and port, and they go stale if the last update is older than about ten minutes. Refusals are a wrong password or a source that is not allowed to connect. Game servers register as a world connection.

The network stack is Berkeley sockets plus a bundled database client (TCP and a local socket path, with SSL option names). Compression helpers are present. The missing-config notice is misspelled, which marks this era build.

Prefer source / rewrite over deep RE

- `_extracted/listserver-nested/graal-listserver/` — C# listserver rewrite (primary reference for seihai-facing design).
- Server Lister package companions for ops HTML/stats scripts — notes only.

Rebuild / rehost checklist

- [x] Identify language/runtime: static ELF32 C++/gcc + MySQL client + zlib.
- [x] CLI: config file path required as sole parameter.
- [x] Config: client port, game-server port, player cap; side files for player budgets.
- [x] Protocols: client list/login + gserver registration; MySQL account/serverlist tables.
- [ ] Prefer clean-room / C# rewrite notes over binary reuse.

Artifacts

- `prelim/`, `functions.txt`, `functions.csv`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt` (local; do not commit decompiled C)

`recovered-drive-tools/ghidra-analysis/TextConvert/SUMMARY.md`

Salvage analysis: TextConvert

- **Binary:** `_extracted/graal-to-nw/TextConvert.exe` (also under LAT Level Converters / Tools `GRAALtoNWconverter`)
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32 GUI (x86), Borland Delphi, ~303 KB

Purpose (plain behaviour)

Offline **Graal → New World text/level conversion helper**. Delphi GUI; no network service role.

Useful as a behaviour reference for level/text migration tooling that may land in **`seihai`** format crates — not as code to paste.

Recommended placement

Tag	**`analysis-only` / client-adjacent `seihai`**
Why	Offline converter; format facts only.
Not	`setup-core`, `seihai-rc`

Ghidra stats (machine)

Field	**Value**
Functions	~1839 (internal ~1500)
Imports	~342
Interesting strings	~111
Decompiled (local only)	20 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`

`recovered-drive-tools/ghidra-analysis/TilesEditor/SUMMARY.md`

Salvage analysis: TilesEditor

- **Binary:** `Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/TilesEditor [Luke Graham - 39ster]/TilesEditorrelease.rar.extracted/TilesEditor.exe`
- **Analyzed (UTC):** 2026-10-31 · Ghidra 12.2 · static only
- **Format:** PE32+ GUI (x86-64), MSVC/Qt-style resource tree, ~966 KB

Purpose (plain behaviour)

Offline **tile editor** in the Reborn line (Luke Graham / 39ster, with a ports credit). Qt resources hang off the main window.

Observed editor capabilities:

- Edit levels and tiles, links, and chests, export a screenshot or map image, and preload overworld levels.
- NPC editing: anonymous and external classes, a verse played when a player is hurt, and prompts when closing a dirty NPC.
- Painting, layers, grid snap, and translucency.
- A script-ish side panel (script icons and a C++ highlighting rule) — still an offline document editor, not a live remote-control session.

Prefer promoting format/Document behaviour into **`seihai`** level-editor / shared edit crates; live LAT once RC exists belongs in **`lat-core`**.

Recommended placement

Tag	**`seihai` (offline editor) · later `lat-core` for live edit**
Why	Tile/NPC/chest Document editing — shared with client level editor.
Staging	Raw PE + Ghidra dumps remain here (`analysis-only` artifacts).
Not	Paste Qt/decompile into MIT crates; not `setup-core`
Licence	Community editor — behaviour notes only

Ghidra stats (machine)

Field	**Value**
Language	x86:LE:64
Functions	~2243 (internal ~1377)
Imports	~1721
Interesting strings	~217
Decompiled (local only)	~20–25 — **not committed**

Artifacts (local)

`prelim/`, `functions.*`, `imports.txt`, `exports.txt`, `strings_interesting.txt`, `decompiled/`, `logs/`, `summary_stats.txt`

`recovered-drive-tools/INVENTORY.md`

Recovered Drive tools — full corpus inventory

Staging root: `/workspace/recovered-drive-tools/` (~2.8 GiB on disk after download + unpack).

Placement: `SALVAGE_PLACEMENT.md` · map: `SEIHAI_SERVERTOOLS_MAP.md` · candidates: `SALVAGE_CANDIDATES.md` · Ghidra: `ghidra-analysis/`

Refreshed: **2026-10-31** after the full Tools Drive download completed.

Rules: markdown-only under this folder in git; never commit recovered binaries; static analysis only — **never execute** recovered PEs; do not fetch Google-blocked abusive files; omit Drive URLs and folder/file IDs from commits; promote behaviour prose only (no decompiler symbol dumps or raw instruction addresses).

Summary

Metric	Count
Catalog entries	**316**
Downloaded	**308**
Malware blocked (`cannotDownloadAbusiveFile`)	**7**
Unavailable (Drive 404)	**1**
Archives unpacked (`*.extracted/` siblings)	**289**
Extract failed	**1**
Skipped huge (>200 MiB)	**1**

On-disk top level: `Developer Tools/` (GServer, RC, NC, Main Client Archive, Server Lister, LAT, NAT, GAT, Gani, Discord, Website), `Tools/`, `_extracted/`, `_inbox/`, `ghidra-analysis/`.

Placement by tool class

Class	Local area	Placement
GServer	`Developer Tools/.../GServer/`	`analysis-only` → `seihai-gserver` / GPL `seihai-gserver-v2`; never paste into MIT
Server Lister	`.../Server Lister.rar`	`analysis-only` → `seihai-listserver`; Perl/status helpers → optional `setup-core` behaviour note
RC	`.../RC [Remote Control]/`	**`seihai-rc`** (pin by tag); `lat-core` holds RemoteFiles trait + `LocalFolder` only
NC	`.../NC [NPC Control]/`	**`seihai-rc`** / `seihai-npcserver` — analysis-only until clean-room
LAT	`Developer Tools/LAT Tool.../`	Offline editors/parsers → **`seihai`**; live world LAT → **`lat-core`** after shared drawing + RC
NAT / GS2 / script editors	`NAT.../`, `Tools/scripteditor*`	`analysis-only` (no Delphi/GS2 paste)
GAT / Gani / viewers / NW2PNG	GAT, Gani, `Tools/GraalViewer`, `Tools/NW2PNG`	**`seihai`** client/assets; most binaries analysis-only
Lab / config / process / lights	gserverstat notes, listserver scripts	**`setup-core`**
Main Client Archive / DClient / designers	Main Client Archive, `Tools/DClient*`, character tools	`out-of-scope` / client; DClient → `stay-staged (bad archive)`
Trainers / cracked / packet loggers	various	`out-of-scope` (`recovered-hacks/`)
Website / Discord / account PHP	Website, Discord, Account Creator	`out-of-scope` / ops

Access blockers

Malware blocked — not downloaded

- `Account Manager.rar`
- `Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2/Graal v2.310[unThinstall][unPeTite-Bass.dll][CRC-Fix].rar`
- `Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v4/Graal v4.20r8[Windows][Patch Only].rar`
- `Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v5/Graal v5.24r4[Windows][Installer].rar`
- `GServer Stats.zip`
- `Graal v2.3[Unpacked][Cracked].rar`
- `apcalc.exe`

Unavailable (404)

- `Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/vGraalWorlds/WorldsSetup64-551.rar` — WorldsSetup64 build missing on Drive

Extract / integrity notes

- `GAT.../PaintShopPro Files.rar` (~682 MiB) present but **not** auto-unpacked.
- `Tools/DClientSetup1198.zip` truncated at source (no EOCD, 242 431 B); partial `setup.exe` under `_extracted/` for static notes only.
- Sibling `WorldsSetup64-518.rar` **did** download (~87 MiB); only `-551` is 404.

Top Ghidra candidates

Deduped high-value PE/ELF targets. Several already have `ghidra-analysis/<name>/SUMMARY.md` (gserver family, ListServer/serverlist3, BytecodeViewer, GCD/GChar, DClient setup, trainers).

Theme	Extracted path	Size	Kind	Placement
GServer	`Developer Tools/# Graal Client Tools And Sources/GServer/GServer Source/GServersource.rar.extracted/gserver.exe`	2.7 MiB	PE	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/GServer/GServer Source/GServersource.rar.extracted/gserver`	1.3 MiB	ELF	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.39.rar.extracted/GServer 1.39/Matriark's GServer/gserver`	1.3 MiB	ELF	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.39.rar.extracted/GServer 1.39/Matriark's GServer/GServer.exe`	772 KiB	PE	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.39.rar.extracted/GServer 1.39/Gserver1.39(win)(MOD)/gserver.exe`	336 KiB	PE	analysis-only → seihai-gserver

Theme	Extracted path	Size	Kind	Placement
GServer	`Developer Tools/# Graal Client Tools And Sources/ GServer/GServer 1.39.rar.extracted/ GServer 1.39/ GserverGUI.exe`	332 KiB	PE	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/ GServer/GServer 1.39.rar.extracted/ GServer 1.39/ Matriark's GServer/ dbsetup.exe`	264 KiB	PE	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/ GServer/GServer 1.39.rar.extracted/ GServer 1.39/ Matriark's GServer/ GStats.exe`	48 KiB	PE	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/ GServer/GServer Source/gserver source.rar.extracted/gserver13`	869 KiB	ELF	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v1/Graal v1.30.rar.extracted /GServer13.exe`	568 KiB	PE	analysis-only → seihai-gserver
GServer	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v1/Graal v1.28.rar.extracted /graal128/ GServerv.exe`	556 KiB	PE	analysis-only → seihai-gserver
GServer stats	`Developer Tools/# Graal Client Tools And Sources/ GServer/GServer Source/gserver source.rar.extracted/gserverstat`	513 KiB	ELF	analysis-only; optional setup-core status note
GServer stats	`Developer Tools/# Graal Client Tools And Sources/ GServer/GServer Source/gserver source.rar.extracted/gserverstat2`	513 KiB	ELF	analysis-only; optional setup-core status note

Theme	Extracted path	Size	Kind	Placement
GServer	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/# Graal3D #/ Graal3D.rar.extracted/graal3d/ GServer.exe`	491 KiB	PE	analysis-only → seihai-gserver
Listserver	`Developer Tools/# Graal Client Tools And Sources/Server Lister.rar.extracted/Server Lister/ slist/serverlist3`	3.3 MiB	ELF	analysis-only → seihai-listserver
Listserver	`Developer Tools/# Graal Client Tools And Sources/Server Lister.rar.extracted/Server Lister/ ListServer.exe`	256 KiB	PE	analysis-only → seihai-listserver
RC	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/ windows_rc3_beta.rar.extracted/ RemoteControl3.exe`	2.1 MiB	PE	seihai-rc
Other	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/ windows_rc3_beta.rar.extracted/ libcairo-script-interpreter-2.dll`	179 KiB	PE	TBD
RC	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/ Custom RemoteControl.rar.extracted/Custom RemoteControl/ remotecontrol.exe`	1.0 MiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/ rc.rar.extracted/ RemoteControl.exe`	888 KiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/ rc2.rar.extracted/ RemoteControl.exe`	720 KiB	PE	seihai-rc

Theme	Extracted path	Size	Kind	Placement
RC	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/ Graal v1.39 - RC.rar.extracted/ RemoteControl.exe`	592 KiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/nc7132001 [V2].rar.extracted/ nc7132001/ RemoteControl-NW.exe`	588 KiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2 - New World/ GraalNW1.rar.extracted/GraalNW/ RemoteControl-NW.exe`	578 KiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2 - New Main/ graalnm24.rar.extracted/graalnm24/ RemoteControl-NewMain.exe`	578 KiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v1/Graal v1.30.rar.extracted/ RemoteControl13.exe`	522 KiB	PE	seihai-rc
RC	`Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v1/Graal v1.28.rar.extracted/graal128/ RemoteControl1.28.exe`	502 KiB	PE	seihai-rc

Theme	Extracted path	Size	Kind	Placement
RC	`Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/Custom RemoteControl.rar.extracted/Custom RemoteControl/Agret_RC.exe`	436 KiB	PE	seihai-rc
NC	`Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/nc7132001 [V2].rar.extracted/nc7132001/NPCControl.exe`	471 KiB	PE	seihai-rc / seihai-npcserver
NC	`Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/nc7132001.rar.extracted/nc7132001.exe`	471 KiB	PE	seihai-rc / seihai-npcserver

Ghidra already noted (this tree)

Prior batch: `BytecodeViewer/`, `DClient_setup/`, `GCD/`, `GChar/`, `Graal_Auto_Key/`, `Graal_Digger/`, `ListServer/`, `TextConvert/`, `gserver-linux/`, `gserver-win/`, `gserver13/`, `gserver_pe_GServersource/`, `gserverstat/`, `gserverstat2/`, `serverlist3/`.

Full-corpus follow-up: `RemoteControl3/`, `remotecontrol_custom/`, `RemoteControl-NW/`, `RemoteControl_classic/`, `NPCControl/`, `TilesEditor/`, `Assimilator/`, `PNGView/`, `scripteditor/`, `GraalLevelGenNW/`, `Matriark_gserver/`; scrubbed prose also for `ListServer/`, `TextConvert/`, gserver family, `serverlist3/`.

Still thin: additional GServer MOD/GUI builds, more LAT converters, GAT NW2PNG PE deep-dives.

Corpus by category

Counts are catalog files (downloaded unless noted). Sizes are sum of downloaded catalog bytes (not unpacked trees).

Category	Files	Bytes	Placement
GServer	8	40.9 MiB	`analysis-only` → seihai-gserver / GPL fork
RC [Remote Control]	15	16.8 MiB	`seihai-rc` (analysis → clean-room)
NC [NPC Control]	5	520 KiB	`seihai-rc` / seihai-npcserver
Server Lister	1	1.3 MiB	`analysis-only` → seihai-listserver; lab status → setup-core
Main Client Application Archive	152	548.9 MiB	`out-of-scope` / seihai client archive
LAT [Level Administration]	41	77.6 MiB	`seihai` offline · `lat-core` live later

Category	Files	Bytes	Placement
NAT [NPC Administration]	8	19.0 MiB	analysis-only (script tooling)
GAT [Graphics Administration]	7	683.3 MiB	seihai assets / analysis-only
Gani Tools	24	31.5 MiB	seihai (gani) / analysis-only
Tools/	39	13.4 MiB	mixed — see class table
Website Developer Tools	3	755 KiB	out-of-scope / ops notes
Discord Developer Tools	1	10 KiB	out-of-scope
Account Creator	2	25 KiB	out-of-scope / ops
Client misc	2	298 KiB	analysis-only / TBD

Key packages (representative)

GServer

- `Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.39.rar` — 23.0 MiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/!Gserver Locations Unsure.rar` — 11.9 MiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.31.rar` — 2.3 MiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/Graal New World GServer.rar` — 1.5 MiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/GServer Source/GServersource.rar` — 1.3 MiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/GServer Source/gserver source.rar` — 494 KiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.34.rar` — 231 KiB
- `Developer Tools/# Graal Client Tools And Sources/GServer/GServer 1.19.rar` — 92 KiB

RC [Remote Control]

- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/windows_rc3_beta.rar` — 6.1 MiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/RC 2.04.rar` — 3.7 MiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/Custom RemoteControl.rar` — 3.6 MiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc-2010-linux.tgz` — 573 KiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc.rar` — 343 KiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/RC_20100329.rar` — 342 KiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc2.rar` — 296 KiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc2 (2).rar` — 296 KiB
- `Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc (1).tgz` — 263 KiB

- Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc8212001.rar — 226 KiB
- Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/Graal v1.39 - RC.rar — 225 KiB
- Developer Tools/# Graal Client Tools And Sources/RC [Remote Control]/rc62101.rar — 225 KiB
- … +3 more

NC [NPC Control]

- Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/nc7132001 [V2].rar — 300 KiB
- Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/nc7132001.rar — 188 KiB
- Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/NPCControl13.rar — 15 KiB
- Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/NPCControl1.3.rar — 12 KiB
- Developer Tools/# Graal Client Tools And Sources/NC [NPC Control]/NPC Server Document [Graal2001].rar — 5 KiB

Server Lister / account misc

- Developer Tools/# Graal Client Tools And Sources/Server Lister.rar — 1.3 MiB
- Developer Tools/# Graal Client Tools And Sources/## MISC ##/GraalRebornSecureLogin-master.rar — 297 KiB
- Developer Tools/# Graal Client Tools And Sources/Graal Account Creator [Website]/accountcreatorphp.rar — 13 KiB
- Developer Tools/# Graal Client Tools And Sources/Graal Account Creator [Website]/accountcreator.rar — 12 KiB
- Developer Tools/# Graal Client Tools And Sources/Graal Client Release Dates.rar — 1 KiB

Main Client Archive (largest)

- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/vJA - Java Graal/JavaGraal-master.rar — 91.1 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/vGraalWorlds/WorldsSetup64-518.rar — 86.7 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v5/Graalv5.rar — 30.5 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v4/Graal v4.04r2[Mac OS X].dmg — 22.0 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v5/Graal v5.00r7[Windows][Unpacked][CRC Patch].rar — 21.5 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v3/Graal v3.04[Mac OS X].dmg.gz — 13.5 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v3/Graal v3.15r2[Mac OS X].dmg.gz — 13.5 MiB

- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2 - New World/GraalNW1.rar — 10.8 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v3/Graal v3.15r1[Linux][Broken].sh — 8.8 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v4/Graal v4.20r6[Mac OS X].dmg.bz2 — 8.2 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v4/Graal4.dmg.bz2 — 8.1 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2 - New World/GraalNWleak.rar — 7.4 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v2 - New World/GraalNW2.rar — 7.1 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v3/Graal v3.04[Linux][Fixed].tgz — 6.3 MiB
- Developer Tools/# Graal Client Tools And Sources/Main Client Application Archive/v3/Graal v3.04[Linux][Obsolete].sh — 6.3 MiB
- … +137 more

LAT

- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/TilesEditor [Luke Graham - 39ster]/TilesEditor-1.2.rar — 14.4 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/TilesEditor [Luke Graham - 39ster]/TilesEditor-lukegrahamSydney.rar — 13.9 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/TilesEditor [Luke Graham - 39ster]/Tiled-1.2.4-win64.rar — 13.9 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/TilesEditor [Luke Graham - 39ster]/TilesEditorrelease.rar — 9.5 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/TilesEditor [Luke Graham - 39ster]/Graal Editor.rar — 9.5 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/Graal Suits [Dusty].rar — 6.8 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Images - Tutorials - Paint Shop Pro/Graal_Cliff_Tutorial_Fix Firsr_WEBPAGESAVED.rar — 2.0 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/MAP Tools/NW2PNG2_Source_Files.rar — 1.4 MiB
- Developer Tools/LAT Tool - [Level Administration Team]/Images - Tutorials - Paint Shop Pro/Level Linking - Tutorial.rar — 559 KiB
- Developer Tools/LAT Tool - [Level Administration Team]/Images - Tutorials - Paint Shop Pro/pics1 [PSD FILE].rar — 549 KiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Converters/NW2TMX-master.rar — 518 KiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Generators/GraalOnline Dungeon Generator - NW - [2003-05-23].rar — 450 KiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/OpenGraal.LevelEditor-cs-master.rar — 446 KiB
- Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/Gonstruct-master.rar — 369 KiB

- `Developer Tools/LAT Tool - [Level Administration Team]/Level Editors/GraalEditorW10.rar` — 350 KiB
- … +26 more

NAT / GS2

- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/NPCs.rar` — 12.4 MiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Script Editors/scripteditor253 - (Has player added files).rar` — 2.7 MiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Script Editors/scripteditor253.rar` — 1.8 MiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/GS2 Compiler.rar` — 1.8 MiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Script Editors/BinaryCrash Script Eingine.rar` — 172 KiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Script Editors/gs2-beautify-master.rar` — 86 KiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Syntax.rar` — 73 KiB
- `Developer Tools/NAT Tools And Scripts [NPC Administration Team]/Script Functions/scriptfunctions_client_6_0_0_7.rar` — 22 KiB

GAT / Gani

- `Developer Tools/GAT Tool - [Graphics Administration Team]/PaintShopPro Files.rar` — 682.0 MiB
- `Developer Tools/Gani Tools [Graal Animation]/Gani Tutorial/Ganis Tutorial Video.rar` — 24.7 MiB
- `Developer Tools/Gani Tools [Graal Animation]/Graal Animation Tools/GViewer [Web].rar` — 1004 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Gani Tutorial/Ganis Tutorial by Flame .[Document].rar` — 798 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Gani Tutorial/Gani Tutorial [HTML].rar` — 644 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Graal Animation Tools/GraalViewer2.1.rar` — 639 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Graal Animation Tools/GraalViewerRev5 [EXE].rar` — 592 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Graal Animation Tools/GraalViewerRev2 [EXE].rar` — 591 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Graal Animation Tools/GraalViewer2 [EXE].rar` — 591 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Graal Animation Tools/GraalAnimViewer2 [EXE].rar` — 589 KiB
- `Developer Tools/GAT Tool - [Graphics Administration Team]/NW2PNG.rar` — 531 KiB
- `Developer Tools/Gani Tools [Graal Animation]/Gani Tutorial/Ganis Tutorial - Fulg0reSama[Document].rar` — 423 KiB
- … +19 more

Tools/

- `Tools/scripteditor253.zip` — 2.3 MiB
- `Tools/scripteditor253.7z` — 1.7 MiB
- `Tools/GraalViewer/GraalViewer2_src.zip` — 1.4 MiB
- `Tools/GraalViewer/GraalViewerRev5.zip` — 671 KiB
- `Tools/GraalViewer/GraalViewerRev2.zip` — 670 KiB
- `Tools/GraalViewer/GraalViewer2.zip` — 670 KiB
- `Tools/GraalAnimViewer2.zip` — 664 KiB
- `Tools/TerrainGen.zip` — 499 KiB
- `Tools/levelfiller.7z` — 477 KiB
- `Tools/PNGView.rar` — 322 KiB
- `Tools/Graal Messenger.7z` — 320 KiB
- `Tools/graalshop.zip` — 315 KiB
- `Tools/Greaditor.7z` — 291 KiB
- `Tools/NW2PNG/NW2PNG2.0.zip` — 242 KiB
- `Tools/DClientSetup1198.zip` — 237 KiB
- `Tools/guildcode.zip` — 230 KiB
- `Tools/Graal Character Generator 1.0.zip` — 229 KiB
- `Tools/GraalLevelGen.zip` — 221 KiB
- `Tools/levelgenerator.zip` — 221 KiB
- `Tools/NW2PNG/NW2PNG 1.3r1.zip` — 219 KiB
- … +19 more

Prior Ghidra follow-up archives (still valid)

ID	Path	Status	Placement	Ghidra
DClientSetup1198	`Tools/DClientSetup1198.zip`	incomplete EOCD	`stay-staged (bad archive)`	`ghidra-analysis/DClient_setup/`
Graal_Auto_Key	`_inbox/Graal_Auto_Key.zip`	complete	`out-of-scope`	`Graal_Auto_Key/`
Graal_Digger	`_inbox/Graal_Digger.zip`	PE truncated/corrupt UPX	`out-of-scope`	`Graal_Digger/`
GCD 1.2.7	`Tools/Graal Character Designer 1.2.7.zip`	complete	`out-of-scope / seihai`	`GCD/`
charactergenerator	`Tools/charactergenerator.7z`	complete	`out-of-scope / seihai`	`GChar/`
Server_Lister	`.../Server Lister.rar`	complete	`analysis-only`	`ListServer/`, `serverlist3/`
GS2_Compiler	`.../GS2 Compiler.rar`	complete	`analysis-only`	`BytecodeViewer/`
gserver_source	`.../gserver source.rar`	complete	`analysis-only`	`gserver13/`, `gserverstat/`, `gserverstat2/`
GServersource	`.../GServersource.rar`	complete	`analysis-only`	`gserver_pe_GServersource/`, `gserver-linux/`, `gserver-win/`

Clean-room rewrite

See `SALVAGE_CANDIDATES.md`. Promote only when behaviour is understood, target crate is clear, and no raw/GPL text would land in an MIT tree.

`recovered-drive-tools/SALVAGE_CANDIDATES.md`

Salvage candidates → seihai-servertools (clean-room only)

After the **2026-10-31 full Tools Drive download** (~308 files / ~2.8 GiB staged). **Do not** commit recovered binaries, decompiled C, or GPL/Delphi text into the MIT clone. Placement tree: `SALVAGE_PLACEMENT.md`.

Clear candidates (this pass)

None ready for a new `setup-core` / `lat-core` feature PR yet. Corpus is inventoried; most high-value PE/ELF work stays `analysis-only` or belongs in sibling repos.

Class	Examples	Target	Why not promoting now
GServer	`GServersource`, `gserver source`, 1.39 MOD builds	`seihai-gserver` / GPL fork	Runtime — not servertools MIT crates
Server Lister	`serverlist3`, ListServer	`seihai-listserver`	Prefer existing listserver notes over RE paste
RC	`RemoteControl3.exe`, custom RC, linux RC tarballs	**`seihai-rc`**	Needs dedicated RC protocol work; thin on SUMMARY notes
NC	`NPCControl.exe`, `nc7132001`	**`seihai-rc`** / `seihai-npcserver`	Same as RC; do not execute PEs
LAT editors	TilesEditor, Greaditor, Gonstruct, converters	**`seihai`** offline · **`lat-core`** live later	Blocked on shared drawing + RC RemoteFiles
NAT / GS2	GS2 Compiler, scripteditor253, BytecodeViewer	analysis-only	Licence / Delphi risk; behaviour notes only
GAT / Gani / viewers	NW2PNG, GraalViewer, AnimViewer	**`seihai`** assets	Client-side tooling
Client archive / DClient / designers	Main Client Archive, GCD, GChar, DClient	out-of-scope / `seihai`	Not servertools; DClient archive incomplete
Trainers	Auto Key, Digger	out-of-scope	See `recovered-hacks/`

Optional (weak) behaviour notes only

Lab status files (from `gserverstats.pl` / gserverstat companions — not from reimplementing HTML ELFs):

- Classic ops wrote `playercount.txt`, `accountcount.txt`, `serveruptime.txt` under the gserver path and checked whether a `gserver` process was alive.
- `setup-core` **already** implements wizard lights from **console lines** (`Listening on`, listserver connect). A future optional reader for those three text files could enrich a lab status page — only if a lab profile actually emits them.
- If pursued: invent loopback fixtures; do **not** copy the Perl or embed real host paths from the dump.

RC / NC staff file browser (future):

- Behaviour belongs in **`seihai-rc`**; `lat-core` keeps the `RemoteFiles` trait + `LocalFolder` until a tagged RC client exists.
- Invent loopback fixtures; never point salvage tests at public hosts.

LAT offline formats:

- Prefer extending `seihai-core` / level-editor in **`seihai`**, then pin by tag into servertools — do not duplicate parsers here.

Blockers (do not chase)

- **7** Google `cannotDownloadAbusiveFile` items (including `GServer Stats.zip`, cracked/client packs, `apcalc.exe`) — leave blocked; do not mirror.
- `WorldsSetup64-551.rar` — Drive 404 (`-518` is present).
- `PaintShopPro Files.rar` — downloaded, skipped unpack (huge).

Process reminder

Promote only when behaviour is understood from notes/tests, target crate is clear, and no raw/GPL text would land in the clone (`SALVAGE_PLACEMENT.md` §C).

`recovered-drive-tools/SALVAGE_PLACEMENT.md`

Salvage → seihai-servertools placement bridge

For Drive-download, Ghidra, and salvage agents. Read this before copying anything into the clone. Full crate map: `SEIHAI_SERVERTOOLS_MAP.md`.

Target repo

Local path	`/workspace/seihai-servertools`
Remote	`squirelworks/seihai-servertools`
Licence	`MIT OR Apache-2.0` — never paste GServer-v2 / gs2lib / decompiled Delphi
Staging (this folder)	`/workspace/recovered-drive-tools/`

The clone is a **nested sibling repo** (gitignored from the Seihai client tree). Do **not** commit it into `squirelworks/seihai`. Promote only clean-room MIT rewrites into the clone; leave raw dumps here.

Crate mapping decision tree

Ask in order. Stop at the first yes.

```
Recovered artifact / behaviour note
│
├─ Raw binary, installer, zip, Ghidra DB, decompile dump, offsets?
│     → KEEP in /workspace/recovered-drive-tools/  (never commit into seihai-servertools)
│
├─ Client trainer / bot / auto-key / digger / AFK helper?
│     → OUT OF SCOPE for servertools (client cheat archive only; do not place)
│
├─ Offline level editor, Document model, tile/sprite drawing, format parsers?
│     → squirelworks/seihai (seihai-core / tools/level-editor / shared edit crate)
│       then pin by git tag in seihai-servertools Cargo.toml — do not duplicate
│
├─ RC/NC session, staff file browser packets, live RemoteFiles transport?
│     → squirelworks/seihai-rc (pin by tag); lat-core only holds the trait + LocalFolder
│
├─ Gserver / listserver / NPC-server runtime itself?
│     → seihai-gserver / seihai-listserver / seihai-npcserver (or GPL fork)
│
```

```
├─ Lab start, process group, world folder layout, start scripts?
│     → crates/setup-core/{lab,run}.rs + scripts/lab/
│
├─ serveroptions.txt / listserver TOML / go-public / lab↔public / backups / lights / test-connect?
│     → crates/setup-core/ (config/, profile, checks, lights, net, folder)
│
├─ Live LAT level / NPC / gani edit helpers (once shared drawing + RC exist)?
│     → crates/lat-core/{level,npc,gani,remote}.rs + later app pages
│
├─ World / config checker (missing links, gmap holes, options safety)?
│     → crates/lat-core/check.rs (+ CLI check, Check page)
│
└─ Unsure?
      → leave staged here; add a row to INVENTORY.md with Placement = TBD;
        do not invent a crate home
```

Quick targets

Kind	Path under clone
Lab / go-public / config / process	`crates/setup-core/`
LAT live editors & world checker	`crates/lat-core/`
CLI dispatch / env / exit codes only	`crates/seihai-servertools/`
egui pages (call cores; no rules)	`crates/app/src/pages/`
Owner-droppable start scripts	`scripts/lab/`
Salvage lab notes	`docs/lab/` or `docs/design/`

Hard rules when writing into the clone

1. **Core-crate logic only** — rules/formats/checks in `setup-core` or `lat-core` with tests; CLI prints; UI holds state.
2. **Line-preserving config** — edit `serveroptions.txt` / listserver TOML keeping comments, order, unknown keys; temp + rename; dated backup.
3. **Loopback-only** — the loopback address and lab ports; no real public hosts/IPs in code, docs, or tests.
4. **egui / eframe 0.29** — match Seihai client / level editor.
5. **Secrets from env or prompt** — never argv; no telemetry; no built-in server lists.

Do not commit raw binaries

Never add these to `seihai-servertools` (or to the Seihai client repo):

- `.exe` / `.dll` / `.so` / installers / `.zip` / `.7z` / `.rar` of recovered tools
- Ghidra project DBs, `.rep`, memory dumps, decompiled C, IDA/Rizin DBs
- Binary offsets (`0x…`, `FUN_…`) in committed source or docs inside the MIT repos
- GPL GServer-v2 / gs2lib source, even as “reference copy”

Raw material stays under `/workspace/recovered-drive-tools/<archive>/` (and analysis under `ghidra-analysis/`). Only a **clean-room MIT rewrite** (behaviour notes → new Rust) enters the clone, on its own branch/PR.

Client `recovered-hacks/Trainers/` bots are unrelated to servertools — do not map them into this clone.

Checklist: when `INVENTORY.md` + `ghidra-analysis/` appear

Use this when Drive download or Ghidra agents drop candidates. Do **not** invent rows beforehand.

A. Inventory landed (`/workspace/recovered-drive-tools/INVENTORY.md`)

- [ ] Confirm each row is a real file under this folder (no speculative tools).
- [ ] Add / fill a **Placement** column using the decision tree above (`setup-core` / `lat-core` / sibling repo / stay-staged / out-of-scope).
- [ ] Mark licence risk: Delphi/GPL dump → behaviour notes only.
- [ ] Incomplete or corrupt archives → Placement = `stay-staged (bad archive)`; do not open a rewrite PR.

B. Ghidra analysis landed (`/workspace/recovered-drive-tools/ghidra-analysis/`)

- [ ] Prefer markdown behaviour write-ups over importing DBs into any Seihai repo.
- [ ] Strip offsets/addresses before anything is summarized into `docs/` of seihai-servertools.
- [ ] Map each analysed tool → one crate target (or “not servertools”).
- [ ] If LAT editor behaviour: note blockers (shared drawing crate + `seihai-rc` RemoteFiles) — implement `LocalFolder` path first.
- [ ] If setup/lab/config behaviour: prefer extending existing `setup-core` modules over new crates.

C. Ready to open a clean-room stub in the clone? (rare)

Only if **all** are true:

- [ ] Behaviour is understood from notes/tests (not pasted decompile).
- [ ] Target crate is clearly `setup-core` or `lat-core` (or a thin CLI/UI wire-up).
- [ ] No raw binary or GPL/Delphi text would be committed.
- [ ] Loopback-safe fixtures exist or can be invented without real hosts.

Otherwise: update Placement in `INVENTORY.md` and stop. **Do not** open a seihai-servertools PR just to park dumps.

Agent hand-off

Agent	Drop here	Then
Drive download	archives under `recovered-drive-tools/` (+ update `INVENTORY.md`)	leave Placement blank or `TBD` if unsure
Ghidra	`ghidra-analysis/<tool>/` markdown + optional private DB	fill Placement using this doc
Salvage / rewrite	clean-room Rust only	branch in `/workspace/seihai-servertools`, cores first

Concrete placements (2026-10-31 full corpus): see `INVENTORY.md` (~308 downloaded / ~2.8 GiB staged).

Class	Placement
GServer / Server Lister / GS2 Compiler	`analysis-only` (never commit binaries/GPL into MIT)
RC / **NC**	**`seihai-rc`** (and npcserver for NC DB) — analysis until clean-room; pin by tag for `lat-core` RemoteFiles
LAT editors / converters / generators	offline → **`seihai`**; live → **`lat-core`** after shared drawing + RC
Lab / status / start / config helpers	**`setup-core`**
GAT / Gani / NW2PNG / viewers	**`seihai`** client/assets (mostly analysis-only binaries)
Auto Key / Digger / cracked / packet loggers	`out-of-scope`
Character Designer / charactergenerator / Main Client Archive	`out-of-scope / seihai (client)`
DClientSetup1198.zip	`stay-staged (bad archive)`

Ghidra markdown under `ghidra-analysis/` (gserver family, ListServer/serverlist3, BytecodeViewer, GCD/GChar, DClient setup, trainers). Next thin notes: RC / NC PEs — static only, never execute.

`recovered-drive-tools/SEIHAI_SERVERTOOLS_MAP.md`

seihai-servertools map (for recovered Drive tools)

Date: 2026-10-31. Search covered `/workspace`, `/home/ubuntu/seihai-work`, GitHub `squirelworks/*`, and Drive `[Grok/[Projects`.

Exact location

Local path (cloned)	`/workspace/seihai-servertools`
Clone URL	`squirelworks/seihai-servertools`
Default branch	`main` (HEAD `35b40c3`, setup track through Host a listserver)
Licence	`MIT OR Apache-2.0` (must not take GPL code from GServer-v2 / gs2lib / gs2-parser)
Was present before this run?	No. Not under the client tree, not in `seihai-work`. Cloned here for placement work.

Important: the clone sits inside the `squirelworks/seihai` working tree as an **untracked nested repo**. Do not commit it into the client. Prefer treating it as a sibling (e.g. `/home/ubuntu/seihai-work/seihai-servertools`) for long-lived work; `/workspace/seihai-servertools` is fine for this recovery pass.

Sibling stack (not this repo)

Repo	Role	Local if present
`squirelworks/seihai`	Client + offline level editor	`/workspace` (= `/home/ubuntu/seihai-work/seihai`)
`squirelworks/seihai-gserver-v2`	GPL fork of GServer-v2 (ships first)	`/home/ubuntu/seihai-work/seihai-gserver-v2`
`squirelworks/seihai-gserver`	Rust gserver (scaffold)	not cloned here
`squirelworks/seihai-listserver`	Rust listserver	not cloned here
`squirelworks/seihai-rc`	RC / NC staff client	not cloned here
`squirelworks/seihai-npcserver`	NPC server	not cloned here
`squirelworks/Graal_analysis`	Protocol / tool notes (incl. classic tool chain)	`/home/ubuntu/seihai-work/Graal_analysis`

Client `tools/` (`/workspace/tools`) is **client-side** helpers (captures, asset generators, offline `level-editor`). Do **not** put live-server LAT tools there.

Repo structure

```
seihai-servertools/
├── Cargo.toml                workspace; pins seihai-core by git tag (v0.0.3)
├── AGENTS.md                 stack-wide rules (licence split, loopback-only, no real hosts)
├── README.md                 build/run, command table
├── crates/
│   ├── setup-core/           lab start, process group, serveroptions/listserver config,
│   │                         profiles, safety checks, lights, net (NO UI)
│   ├── lat-core/             LAT logic: RemoteFiles, level/gani open, npc contract,
│   │                         world check (NO UI)
│   ├── app/                  servertools-app: egui window, one module per page
│   └── seihai-servertools/   binary CLI; only place that prints / reads env / exit codes
├── scripts/lab/              start.sh / start.command / start.bat (moved from the fork)
├── docs/
│   ├── ARCHITECTURE.md       where new work goes
│   ├── PLAN.md / NEXT.md     tracks and ordered TODOs
│   ├── design/go-public.md   setup wizard design
│   ├── design/lat-tools.md   LAT editors + checker design
│   └── lab/                  loopback lab write-ups + HOWTO
└── .github/workflows/        ci.yml (fmt/clippy/test ×3 OS), release.yml on v* tags
```

Binary name: `seihai-servertools`. Window via `gui` feature (default on); `--no-default-features` for headless CLI-only.

Commands today

Command	State
`lab start|plan`	working
`setup status|public|lab|undo`	CLI working
`setup host-listserver|listserver-lab|listserver-undo`	working
`setup start` / lights / `test-connection`	working (stand-in; real-fork lab run still open)
`check WORLD`	first checks (parse / missing links / gmap holes)
`gui [--page lab|setup|levels|npcs|ganis|check]`	pages laid out; Levels/NPCs/Ganis planned stubs

Build: `cargo build --release` · `cargo test` · CI requires `fmt`, `clippy -D warnings`, tests on Linux/Windows/macOS.

Where salvaged Drive tools should go

Map recovered material by **job**, not by original zip name. Rewrite clean-room into this repo; never paste GServer-v2 / gs2lib / decompiled Delphi into MIT crates (`AGENTS.md`).

1. Lab start / process / world layout → `crates/setup-core/`

Module	Put here when salvaging…
`lab.rs`	Finding `gs2emu` / `seihai-listserver`, start `Plan`, world folder layout
`run.rs`	Process group, console logs, stop-together
`config/options_txt.rs`	Line-preserving `serveroptions.txt` editors
`config/listserver_toml.rs`	`seihai-listserver.toml` editors (`toml_edit`)
`config/backup.rs`	Dated backup + temp/rename + undo
`profile.rs` / `checks.rs`	Lab vs public key tables, refused combinations

Module	Put here when salvaging…
`lights.rs` / `net.rs`	Console “listening / linked” lights; owner-typed test connect
`folder.rs`	Facade used by CLI and GUI

CLI wiring: `crates/seihai-servertools/src/lab.rs`, `src/setup.rs`.
GUI: `crates/app/src/pages/lab.rs`, `setup.rs`, `host.rs`.
Shell helpers that owners drop next to a world: `scripts/lab/` (keep `*.bat` CRLF, `*.sh`/`*.command` LF + executable).

2. LAT live-world editors / checker → `crates/lat-core/`

Module	Put here when salvaging…
`remote.rs`	File list/get/put trait; `LocalFolder` now; later `RcFiles` over `seihai-rc`
`level.rs`	Level open/edit helpers via **`seihai-core`** parsers (no second parser)
`gani.rs`	Same for ganis
`npc.rs`	Level NPC scripts + (later) NC database objects
`check.rs`	World/config checker (`check_world` and extensions)

GUI pages (stubs until shared drawing lands):

- Levels → `crates/app/src/pages/` new `levels.rs` (wire into `Tab::Levels`)
- NPCs → `npcs.rs` / `Tab::Npcs`
- Ganis → `ganis.rs` / `Tab::Ganis`
- Checker UI → already `pages/check.rs`

Design: `docs/design/lat-tools.md`. Order: `docs/NEXT.md` LAT track.

3. Do not put these in seihai-servertools

Recovered thing	Correct home
Offline level editor / Document / tile paint	`squirelworks/seihai` → `tools/level-editor` (later shared `seihai-edit`-style crate, then pin tag here)
Tile/sprite drawing	`seihai` (`seihai-mae` today → shared crate first)
Protocol / level / gani / GS1 parsers	`seihai-core` in `squirelworks/seihai`; bump pinned tag in this workspace `Cargo.toml` in its own PR
RC/NC session, file browser packets	`squirelworks/seihai-rc` (pin by tag when ready)
Gserver / listserver / NPC-server runtime	`seihai-gserver`, `seihai-listserver`, `seihai-npcserver` (or fork for GPL)
Ash Python gserver / Ember / GServerStory	Reference only → `Graal_analysis` / Drive archive; rewrite into Rust stack, do not vendor
Classic GraalEditor / GraalShop / Guildmaker / stealer ListServer	Behaviour notes in `Graal_analysis/tools/`; **do not run** old ListServer.exe (password stealer — see `server-tools-2001.md`)
Client capture / stress / asset generators	`/workspace/tools` in `seihai`
Decompile dumps, binary offsets, Ghidra DBs	Stay under `recovered-drive-tools/` or private analysis; never into MIT crates

Recommended placement cheat-sheet (Drive → target)

Drive / recovered class	Target path under `seihai-servertools`
Lab one-click start scripts, process wrappers	`scripts/lab/` + logic in `crates/setup-core/{lab,run}.rs`

Drive / recovered class	Target path under `seihai-servertools`
`serveroptions.txt` / public-vs-lab wizards	`crates/setup-core/config/` + `profile/checks` + CLI `setup` + `app` Setup page
Listserver host/config helpers	`setup-core/config/listserver_toml.rs` + Host page
Optional lab status-file reader (`playercount.txt` etc.)	`crates/setup-core/` lights/status only — behaviour note first (`SALVAGE_CANDIDATES.md`)
World validators (missing levels, bad ganis, link holes)	`crates/lat-core/check.rs` (+ CLI `check`, Check page)
Live level/NPC/gani edit via staff link	`lat-core/{level,npc,gani,remote}.rs` + new app pages; RC I/O waits on `seihai-rc`
RC / NC staff session & RemoteFiles (from `RC [` / `NC [` archives)	**Not** this repo's crates — land in `squirelworks/seihai-rc` (+ npcserver); pin tag here
LAT offline editors / converters / generators	**`seihai`** first; only live helpers into `lat-core` after drawing + RC
NAT / GS2 compilers / script editors	analysis-only notes — no Delphi/GS2 paste into MIT
Pure format parsers found in zips	Upstream into `seihai` `seihai-core`, then consume by tag — **not** duplicated here
Docs / lab run notes for a salvage	`docs/lab/YYYY-MM-DD-….md` or `docs/design/`

Staging raw salvage before clean-room rewrite: keep under `/workspace/recovered-drive-tools/<archive-name>/` (this folder). Promote only rewritten MIT-clean code into the clone.

Conventions (must follow when adding tools)

1. **Logic in cores, never in UI.** Rules/formats/checks → `setup-core` or `lat-core` with tests. CLI prints; `app` holds UI state and calls cores on worker threads for long work.
2. **One parser per format**, from `seihai-core` (`Cargo.toml [workspace.dependencies]`, tag pin). Missing feature → PR in `seihai`, tag, bump here separately.
3. **Config files are the owner's.** Edit line-by-line; keep comments, order, unknown keys; temp file + rename; dated backup.
4. **No real public hostnames/IPs** in code, docs, tests, or defaults. Use the loopback address, lab ports (`14802`/`14803`, listserver `14900`, clients `14921`–`14923`), placeholders `<listserver-host>` / `<public-host>`.
5. **No outbound calls** the owner did not ask for (no telemetry, no built-in server lists). Passwords only from env or prompt, never argv.
6. **Tests:** unit next to code; crate `tests/`; CLI via `crates/seihai-servertools/tests/cli.rs`; lab write-ups only on loopback.
7. **Git:** one change per branch/PR; no push to `main` without CI; no tags/releases without Squirrel.
8. **Window toolkit:** egui/eframe **0.29** (same as Seihai client / level editor). Add a page: `crates/app/src/pages/<name>.rs` with `Page` + `show`, register in `Tab` / `App::update` (see crate docs).
9. **CLI:** hand-written dispatch in `main.rs` today (clap OK later); keep documented option names.

Integration requirements for LAT salvages

Before a live level/NPC/gani editor is useful here:

1. Shared drawing + level `Document` crate in **`seihai`** (move out of `seihai-mae` / `tools/level-editor`), tag, pin in this workspace.
2. **`seihai-rc`** stage 4 file browser → implement `RemoteFiles` as `RcFiles`; stage 5 NC for database NPCs/classes/weapons.
3. Editors must work on `LocalFolder` first, then fake RC, then lab fork on the loopback address with a LAT account — never against a public server.

World checker can grow now (missing assets, GS1 syntax, `serveroptions` safety, `--json`) entirely inside `lat-core` / CLI.

Related Drive archives (reference only)

Under the owner private Drive folder **Projects** (ids omitted):

Archive	Relevance to servertools
`Graal gServers.zip`	Ash / Ember / dumps — **gserver**/**listserver** reference, not LAT UI; see client `documentation/server-reference.md`
`Graal 39sters gServer.zip`	Older protocol / museum world
`Graal Scripting.zip`	NPC event model → client script engine / later NPC editor checks
`Graal Enigma Playerworld.zip`	Levels/scripts for checker and editor fixtures
`Graal Client Analysis.zip` / `Client Reform.zip`	Client/editor behaviour notes → `Graal_analysis`, not this binary

Classic tool notes already extracted: `Graal_analysis/tools/{graaleditor,graalshop,remotecontrol,npc-control,server-tools-2001}.md`.

Summary for agents placing recovered tools

- **Repo:** `/workspace/seihai-servertools` (`squirelworks/seihai-servertools`)
- **New setup/lab tooling** → `crates/setup-core/` (+ CLI `setup`/`lab`, app Setup/Lab pages, optional `scripts/lab/`)
- **New LAT/live editors & world checks** → `crates/lat-core/` (+ CLI `check` / later editor commands, app Levels/NPCs/Ganis/Check pages)
- **Parsers, offline editor, drawing, RC wire** → sibling `seihai` / `seihai-rc` first, consume by tag
- **Raw Drive dumps** → stay in `/workspace/recovered-drive-tools/`; only clean-room rewrites land in the MIT repo

Operational bridge (decision tree, no-raw-binaries rule, inventory/ghidra checklist): `SALVAGE_PLACEMENT.md`. Prefer that file when assigning Placement for a new drop; keep this map as the structure reference.