Appendix G — SoftICE

The command card for the Windows 98 sessions. SoftICE and the Watcom debugger do not share a syntax. Do not type these lines into WDW. Appendix H is that debugger.

Date: 16 October 2026

SoftICE field work as the standing host closed on 11 October 2026. The kit that loaded was `SI405w9x` plus ICEDUMP 6.021, loader `w9x/4.05.334/icedump.exe`, and only after `winice.dat` listed the exports of both `kernel32.dll` and `user32.dll`. The night of 15 October still needed this card. The book-open read below is that night. The host was the Win98 VM. XP NTVDM is not a clean 16-bit host.

G.1 The screen

Ctrl-D pops SoftICE over Windows. Ctrl-D again returns to Windows if the machine is running. While it is popped, Windows is stopped.

The screen is four regions, top to bottom, and you can turn each one on or off:

Region	What it is	Command that toggles it
Register	AX BX CX DX, SI DI BP SP, DS ES SS CS IP, and the flags	`WR`
Data	Hex on the left, ASCII on the right. This is where a dump lands.	`WD`
Code	The disassembly at CS:IP. The current instruction is highlighted.	`WC`
Command	One line at the bottom. History with the up arrow.	always there

There is no Locals pane and no Calls pane. The stack is memory at SS:SP. The frame, after `ENTER`, is memory at SS:BP. If you want a call chain you walk return addresses yourself, or you use the Watcom Calls window (Appendix H). SoftICE will not draw it for you.

`MAP` output is a list of segments for one module. The segment numbers in that list are hex. The selector beside each segment is this boot only.

G.2 Commands that were actually used

Clear before you set. A breakpoint left over from the polygon painter (`GDI!POLYGON`, or BAS `1408:0376`) freezes SoftICE as soon as a page scrolls.

```
BC *
BL
```

`BC *` clears every breakpoint. `BL` lists what is still set. `BC n` clears one, by the number `BL` printed. `BD n` disables one without deleting it. `BE n` enables it again.

Break on an export. The ordinal form survives a reboot. A selector does not.

```
EXP TB80BAS
BPX TB80BAS.Ordinal_8
BPX TB80BAS!OBJFILEOPEN
```

`EXP` lists the exports. Ordinal 8 is `CDBFILEOPEN` on every boot. The `!` is SoftICE's module mark. Watcom uses `@` for the same idea. `BAS(82)` and `BAS(83)` are not addresses. SoftICE rejects them.

Break on a live instruction, and do something when it hits:

```
MAP TB80BAS
BPX <selector>:0376 DO "D SS:BP-4 L 4; D DS:30AC L 40"
```

`MAP TB80BAS` prints the live selector for each NE segment. You read the selector for the segment you want, then you type that selector. `DO` runs the quoted commands and, unless one of them stops, continues. `D` is a dump. `L` is the length. `SS:BP-4` is the saved word just under the frame. `DS:30AC` is the point buffer the polygon painter copies into.

Run and step:

Command	Effect
`G`	Go. Run until a breakpoint or a fault.
`T`	Trace. Step into a `CALL`. F8 is the same key.
`P`	Proceed. Step over a `CALL`. F10 is the same key.
`P RET`	Run until the next `RET` or `RETF` in this frame. This is how you leave a function without tracing every instruction inside it.
`U <addr>`	Unassemble at an address without moving CS:IP.
`R`	Show the registers. `R AX=1` sets one.

Dump:

Command	Effect
`D <addr>`	Dump bytes at a far address.
`D <addr> L <n>`	Dump `n` bytes.
`DB`, `DW`, `DD`	Bytes, words, dwords. A word dump is the one that matches a stack slot.
`D SS:BP+6`	The first stack argument after a far frame. See Appendix I for why `+6`.

`/DUMP`, from ICEDUMP, writes the SoftICE console unless the dump experts are set. It does not write the address you think you named. A file that starts with the command log, or with the DOS device chain (`CON`, `AUX`, `PRN`), is not a book. A dump is real when it contains book strings at offsets already known. `page.bin01511` did: `ASYM_TpID`, `Page#`, matching `9e954d01.tbk` at `0xB8B51`.

Do not search all of memory for a byte pattern. A wide search for `80 65` GPFed the VM.

G.3 What not to step into

A GPF in this host is usually a segment that is not present, or a far call into `KERNEL` that you traced into.

- Do not `T` into an unloaded NE segment. `MAP` the module first. If the segment is not in the list, it is not in memory. Set the breakpoint and `G` until the program loads it.
- Do not `T` a far `CALL` into `KERNEL`, `USER`, or `GDI` unless that segment is already present. Use `P`.
- The CMP expand host died in `TB80W16` at `001c:00000015` on the bytes `9A 9C 06 57 2A` (a far call, segment not present). That fault is parked. It is not the book-open path.
- `TBCBT` segment 7 holds the cipher exports. A module list that showed segments `01`, `0E`, `02`, `0B`, `08`, `0D`, `04`, `03` had not loaded segment 7. Breaking there before it is mapped faults. Searching memory for the leftover constants `0xA01` and `0x300` finds the call site while segment 7 is still unloaded.

If SoftICE will not pop, or the VM is wedged, the fallback on that VM is DEBUG.COM. It is a smaller language. `T` traces. `D` dumps. There is no `P`, no `BPX`, no `DO`, and no module name. `Q` quits DEBUG. Do not type SoftICE lines into it.

G.4 The 15 October book-open read

This is the path that was on the screen, from the call that asks for 4 bytes down to the buffer those 4 bytes were not.

The stable names, in order:

1 `CDBFILEOPEN` is BAS ordinal 8. Break there on a lesson open. Do not break ordinal 51. Ordinal 51 is `CDBSENDCREATE`, the author create path. A lesson does not call it.

2 From there the open goes through CDBCREATEBOOKREF, then FUN_1048_1cc4, then FUN_1048_2174, then OBJFILEOPEN.

3 OBJFILEOPEN calls FUN_1160_03de. That function is the read wrapper. On that boot the call site was 36E7:201B and the callee was 36F7:03DE.

Those selectors died at the next reboot. The NE numbers did not. 36E7 was NE segment 2F (Ghidra 1170). 36F7 was NE segment 2D (Ghidra 1160). The check is (NE index − 1) × 8 + 0x1000. Segment 0x2D is 45 decimal, and (45 − 1) × 8 + 0x1000 = 0x1160. The breakpoint that survives the reboot is not a selector and not a segment number. It is BPX TB80BAS!OBJFILEOPEN or BPX TB80BAS.Ordinal_8, then T into the CALL. BPX BAS(2D):03DE is the notation already rejected. MAP gives the selector. The offset 03DE is the part you copy.

At the call site the bytes were:

```
36E7:2019  PUSH 04
36E7:201B  CALL 36F7:03DE
```

PUSH 04 is the length. Four bytes. The far pointer to the buffer is already on the stack under it.

FUN_1160_03de begins with ENTER 0022,00. Until that instruction has executed, SS:BP is still the caller's frame. Dumping SS:BP+6 at the call site dumps the caller's locals. That was the first wrong dump of the night. Step in with T once so CS:IP lands on the callee, T again past ENTER, and only then dump.

```
T
T
DW SS:BP+6 L 1
DW SS:BP+8 L 2
```

On that hit, [BP+6] was 0004. The far pointer at [BP+8] was 3DD7:9086. Dumping that address:

```
DB 3DD7:9086 L 4
DB 3DD7:9070 L 30
```

The four bytes were FC B5 BD B0. That is an internal pointer sitting in the buffer, not a page header. A page header that is the book signature is 03 4A 42 4F (JBO, with a length byte in front). A record header that is the one being hunted starts 14 00. Neither of those was in the four bytes. The wider dump showed 4F 46 (OF) nearby, at 9092. Nearby ASCII is not the bytes you just read. Read the four at the pointer, then stop.

Inside FUN_1160_03de there are two ways to satisfy the read:

- At offset 048F it calls FUN_1258_00a8, the buffered path.
- The next test, at 049A, is JZ 0516. When the buffer already held the bytes, that jump was taken.
- Offset 04F3 is the raw DOS read (INT 21h, AH=3F). It was skipped. Setting a breakpoint only on 04F3 and watching it never hit is the correct observation. It is not a broken breakpoint.

So a 4-byte read that returns FC B5 BD B0 is the wrapper doing its job on something that is not yet a record. The next useful hit is the same function again, on a later call, when the length is larger than 4 or the buffer starts with 14 00 or with 03 4A 42 4F. Do not single-step the whole of FUN_1258_00a8 looking for a compare against 0x14. Chapter 4 already closed the static candidates. The live test is the buffer about to become an object.

G.5 A session, in order

```
BC *
MAP TB80BAS
BPX TB80BAS!OBJFILEOPEN
G
```

Open the lesson. When it breaks:

```
T
```

only if the highlighted instruction is the `CALL` you mean to enter. Otherwise `P`. When CS:IP is inside `FUN_1160_03de` and past `ENTER`:

```
DW SS:BP+6 L 1
DW SS:BP+8 L 2
DB <segment>:<offset> L 10
```

Write down the length and the first bytes. `G` to the next hit. If the machine faults, `BC *` before you set anything else.

G.6 What transfers to Watcom

The discipline transfers. The words do not.

- Break a stable export, not a selector copied from last boot.
- Dump the frame only after `ENTER`.
- Step over `KERNEL`. Do not trace into a segment `MAP` did not list.
- A 4-byte buffer that is not `14 00` is data. Record it and continue.
- Ordinal 51 is the wrong function.

Appendix H has the Watcom words for each of those.