

Mark Scheme (Results)

January 2022

Pearson Edexcel International Advanced Subsidiary Level In Physics (WPH12) Paper 01: Waves and Electricity

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.edexcel.com, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus.

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

January 2022

Question Paper Log Number P69435A

Publications Code WPH12_01_2201_MS

All the material in this publication is copyright

© Pearson Education Ltd 2022

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Question Number	Answer	Mark
1	C is the correct answer as $V = W/Q$	(1)
	A is not the correct answer as volts are not equivalent to energy/time	
	B is not the correct answer as volts are not equivalent to power/time	
	D is not the correct answer as volts are not equivalent to power/charge	
2	A is the correct answer as $v = h/m\lambda$	(1)
	B is not the correct answer as v is not = $h/q\lambda$	
	C is not the correct answer as v is not = $m\lambda/h$	
	D is not the correct answer as v is not = $q\lambda/h$	
3	D is the correct answer as the sum of e.m.f. = the sum of p.d.	(1)
	A is not the correct answer as this does not include the p.d. across R_2	
	B is not the correct answer as this does not include the p.dacross R_2	
	C is not the correct answer as this does not include the p.d. across R_1	
ļ	B is the correct answer as a thermistor is a semiconductor	(1)
	A is not the correct answer as this would occur when temperature decreases	
	C is not the correct answer as this would occur when temperature decreases	
	D is not the correct answer as this, although it does occur, has a lesser effect	
	than the release of more conduction electrons	
5	B is the correct answer as the light bends towards the normal when	(1)
	travelling from L to M (so $v_L > v_M$) but bends away from the normal when	
	travelling from M to N, but there is not as much of a change of direction	
	as there was from L to M.	
	A is not the correct answer as light bends away from the normal travelling	
	from M to N so v_N must be greater than v_M	
	C is not the correct answer as light bends towards the normal travelling from L	
	to M so v_L must be greater than v_M	
	D is not the correct answer as light bends away from the normal travelling	
	from M to N, so v_N must be greater than v_M	
6	C is the correct answer as light travels faster in L than in M	(1)
	A is not the correct answer as light travels faster in L than in M	
	B is not the correct answer as light travels faster in L than in N	
	D is not the correct answer as light travels faster in N than in M	
7	D is the correct answer as X and Z are in two adjacent node to node	(1)
	sections, which will always be in antiphase with each other	
	A is not the correct answer as W and X are between the same pair of nodes,	
	between which all points are in phase	
	B is not the correct answer as W and Y are in two adjacent node to node	
	sections, which will always be in antiphase with each other	
	C is not the correct answer as X and Y are in two adjacent node to node	
8	sections, which will always be in antiphase with each other A is the correct answer as the graph shown is a V-I graph for a diode	(1)
	B is not the correct answer as the graph is not that for a filament lamp	
	C is not the correct answer as the graph is not that for an ohmic conductor	
	D is not the correct answer as the graph is not that for a thermistor	

9	B is the correct answer as $\lambda/8$ is one eighth of a full wave cycle, and so is $\pi/4$ radians	(1)
	A is not the correct answer as this is equivalent to a path difference of $\lambda/4$ C is not the correct answer as this is equivalent to a path difference of $\lambda/16$ D is not the correct answer as this is equivalent to a path difference of $\lambda/32$	
10	C is the correct answer as power for the whole circuit = $\mathcal{E} \times I$ and I increases whilst e.m.f. remains the same	(1)
	A is not the correct answer as increased intensity increases the number of conduction electrons released by the LDR B is not the correct answer as the potential difference across the LDR will decrease, causing the potential difference across the resistor to increase D is not the correct answer as the resistance of an LDR decreases as light	
	intensity increases	

Question Number	Answer		Mark
11a	Use of $R = \rho l/A$ $\rho = 1.1 \times 10^{-6} \Omega \mathrm{m}$ $\frac{\text{Example of calculation}}{\rho = \frac{RA}{l}} = \frac{(2.0 \Omega) (2.5 \times 10^{-7} \mathrm{m}^2)}{0.45 \mathrm{m}} = 1.11 \times 10^{-6} \Omega \mathrm{m}$	(1) (1)	2
11b	Use of $R = V/I$ Use of $I = nqvA$ $v = 4.2 \times 10^{-4} \text{ m s}^{-1}$ $\frac{\text{Example of calculation}}{I = V/R = (3.0 \text{ V}) / 2.0 \Omega} = 1.5\text{A}$ $v = \frac{I}{nqA} = \frac{1.5 \text{ A}}{(9.0 \times 10^{28} \text{ m}^{-3})(1.60 \times 10^{-19} \text{ C}) (2.5 \times 10^{-7} \text{m}^2)}$ $= 4.17 \times 10^{-4} \text{ m s}^{-1}$	(1) (1) (1)	3
11c	Halving length halves resistance Which doubles the current I = nqvA related to drift velocity doubling (so suggestion is correct)	(1) (1) (1)	3
	Total for question 11		8

Question Number	Answer		Mark
12a	Either		
	Ultrasound is (partially) <u>reflect</u> ed (from boundaries)	(1)	
	(Measure) the <u>time</u> taken or <u>time</u> delay (for signal to return)	(1)	
	Calculate expected time for pulse to return (if no air gap) Or Compare to known time for pulse to return	(1)	
	If time for pulse to return < time calculated, air gap is present	(1)	
	Or		
	Ultrasound is (partially) <u>reflect</u> ed (from boundaries)	(1)	
	(Measure) the <u>time</u> taken or <u>time</u> delay (for signal to return)	(1)	
	Calculate distance for pulse to travel	(1)	
	If distance pulse returns from < thickness of RSJ, air gap is present Or If distance pulse returns from = thickness of RSJ, no air gap	(1)	4
12b	(Higher frequency) gives smaller wavelength	(1)	
	(Smaller wavelength leads to) high level of detail/resolution	(1)	
	(Smaller wavelength) can detect small(er) objects/gaps Or (With 20kHz) the detail would not be sufficient to identify air gaps Or (With 20kHz,) air gaps might be smaller than the wavelength	(1)	3
	Total for question 12		7

Question Number	Answer				Mark
*13	structured answ awarded for inc	ver with linkage dicative conten- ing. The follow	es and fully-sustain t and for how the a	a coherent and logically ed reasoning. Marks are nswer is structured and shows w the marks should be awarded	
	IC points	IC mark	Max linkage mark	Max final mark	
	6	4	2	6	
	5	3	2	5	
	4	3	1	4	
	3	2	1	3	
	2	2	0	2	
	1	1	0	1	
	0	0	0	0	
	lines of reasoni		w the marks should	be awarded for structure and Number of marks awarded for structure	
				of answer and sustained line of reasoning	
		coherent and logic y sustained lines of oughout		2	
	Answer is partial and lines of reason	ly structured with s	some linkages	1	
	Answer has no lin	nkages between po	ints and is	0	
	 One t A mi Releat Frequ 	on energy is to one intera- nimum energase of electronium affects	gy/frequency is ons is instantane the kinetic energy	hotons and electrons required (for electron release)	6
	Total for que	estion 13			6

Question Number	Answer		Mark
14a	Calculates θ (using tan)	(1)	
	Calculates d using $\frac{1}{\text{number of lines per m}}$	(1)	
	Use of $n\lambda = d\sin\theta$	(1)	
	$\lambda = 6.3 \times 10^{-7} \mathrm{m}$	(1)	4
	Example of calculation $\tan \theta = \frac{0.500 \text{ m}}{1.690 \text{ m}}$, therefore $\theta = 16.5^{\circ}$ $d = \frac{1}{450,000} = 2.22 \times 10^{-6} \text{ m}$. $\lambda = \frac{d\sin \theta}{n} = \frac{(2.22 \times 10^{-6} \text{m})(\sin 16.5^{\circ})}{(1)} = 6.31 \times 10^{-7} \text{ m}$		
14b	(Waves from the different slits meet and) superposition/interference takes place	(1)	
	(Bright dots are where) waves are in phase	(1)	
	(Superposition/interference) is constructive	(1)	3
14c	White dot at O	(1)	
	Spectra seen (either side of O)	(1)	2
	Total for question 14		9

Question	Answer		Mark
Number			
15a	Difficult to judge/measure the exact position of node		
	Or Ruler is not close to the string (so there might be parallax error)	(1)	1
15bi	Calculates gradient by best fit or plotted points from graph	(1)	
	Recognises distance between adjacent nodes = $\lambda/2$ Or Recognises that speed of waves on the string = 2 × gradient	(1)	
	Use of $v = \sqrt{\frac{T}{\mu}}$ to find T	(1)	
	Use of $T = mg$ with $g = 9.81$ Nkg ⁻¹ (accept $W = mg$)	(1)	
	m = 0.21 kg	(1)	5
	Example of calculation Gradient = $\frac{2.7 \text{ m}}{0.080 \text{ s}}$ = 33.75 ms ⁻¹ Speed = 2 × gradient = 67.5 ms ⁻¹ v = $\sqrt{T/\mu}$, 67.5 ms ⁻¹ = $\sqrt{\frac{T}{4.5 \times 10^{-4} \text{ kg m}^{-1}}}$ T = 2.05 N m = $\frac{W}{g} = \frac{T}{g} = \frac{2.05 \text{N}}{9.81 \text{ Nkg}^{-1}} = 0.209 \text{ kg}$		
15bii	Straight line with shallower gradient drawn, starting from origin Line has a gradient of around $0.7 \times \text{line}$ drawn (Graph line if continued to the last value for $1/f$ should be between 1.8 and 2.0m for d).	(1) (1)	2
	Total for question 15		8

Question	Answer		Mark
Number 16a 16bi	Transverse: vibrations/oscillations are perpendicular to the direction of (wave) travel Longitudinal: vibrations/oscillations are parallel to the direction of (wave) travel The light is (incident on the boundary) along the normal Or The angle of incidence is 0° Or The light hits (prism A) at right angles	(1) (1)	2
16bii	Normal line correctly drawn at right angles to boundary (by eye) Reflected ray in correct direction from boundary (by eye) Refracted ray in correct direction from boundary (by eye)	(1)(1)(1)	
	Correct refraction at the right hand side of the glass block (by eye) and either TIR or correct direction refraction at the left hand side (by eye) air glass A 60° MP4 incident ray MP4 air	(1)	4
16biii	Use of $n_1 \sin \theta_1 = n_2 \sin \theta_2$ with 30°, 1.40 and 1.55 substituted correctly Angle of refraction = 27° $\frac{\text{Example of calculation}}{n_1 \sin \theta_1 = n_2 \sin \theta_2}, \text{ so } 1.40 \text{ (sin } 30^\circ) = 1.55 \text{ (sin } r), r = 26.8^\circ$	(1) (1) (1)	3
16c	Light (emerging) is polarised Only transverse waves can be polarised	(1) (1)	2
	Total for question 16		12

Question	Answer		Mark
Number 17a	Either		
1/4	Uses resistors in parallel formula correctly	(1)	
	Adds series resistance	(1)	
	Use of $V = IR$ to find whole circuit current	(1)	
	Current in the 6.0 Ω resistor = 0.67(A)	(1)	
	Use of $Q = It$	(1)	
	$4.2 \times 10^{18} \text{ (electrons)}$	(1)	
	Or		
	Uses resistors in parallel formula correctly	(1)	
	Uses potential divider to calculate <i>V</i> across parallel section	(1)	
	Use of $V = IR$ to find current in 6.0 Ω resistor	(1)	
	Current in the 6.0 Ω resistor = 0.67(A)	(1)	
	Use of $Q = It$	(1)	
	4.2×10^{18} (electrons)	(1)	6
	Example of calculation		
	$\frac{1}{1} = \frac{1}{1} + \frac{1}{1}$ so R $y = 2.0 \Omega$		
	$\frac{1}{Rp} = \frac{1}{3.0\Omega} + \frac{1}{6.0\Omega}$, so R _{parallel} = 2.0 Ω		
	Total circuit resistance = $4.0 \Omega + 2.0 \Omega = 6.0 \Omega$		
	$I = V / R = 12 \text{ V} / 6.0 \Omega = 2.0 \text{ A}$		
	Current in 6.0 Ω resistor is 1/3 of 2.0A = 0.67 A		
	No. of electrons per second = $\frac{\text{current}}{\text{charge per electron}} = \frac{0.67 \text{ A}}{1.60 \times 10^{-19} \text{ C}}$		
481	$= 4.2 \times 10^{18}$ electrons per second	(1)	
17b	(Student is correct that) resistance in circuit/parallel is greater	(1)	
	V is the same	(1) (1)	
	So if student uses $P = V^2/R$	(1)	
	Power in whole circuit would be less, so student incorrect	(1)	
	Or (Student is correct that) resistance in circuit/parallel is greater		
	This leads to current being lower	(1)	
	So if student used $P = VI$ with same V	(1)	
	Power in whole circuit would be less, so student incorrect	(1) (1)	
	Or		
	(Student is correct that) resistance in circuit/parallel is greater	(1)	
	This leads to current being lower	(1) (1)	
	Effect of decreasing current > the effect of increasing resistance	(1)	
	Power in whole circuit would be less, so student incorrect	(1)	4
	(MP4 via any method is dependent on awarding MP2 & MP3)		
<u> </u>	Total for question 17		10

Question Number	Answer		Mark
18a	Conversion of eV into J Use of $E = hf$ Use of $v = f\lambda$ with $v = 3.00 \times 10^8 \text{ ms}^{-1}$ $\lambda = 654 \text{ (nm)}$, so light (for this transition) is red $\frac{\text{Example of calculation}}{1.9 \text{ eV} \times (1.60 \times 10^{-19} \text{ JeV}^{-1})} = 3.04 \times 10^{-19} \text{ J}$ $f = \frac{E}{h} = \frac{3.04 \times 10^{-19} \text{ J}}{6.63 \times 10^{-34} \text{Js}} = 4.59 \times 10^{14} \text{ Hz}$ $\lambda = \frac{v}{f} = \frac{3.00 \times 10^8 \text{ ms}^{-1}}{4.59 \times 10^{14} \text{ Hz}} = 6.54 \times 10^{-7} \text{ m}$ Converts 8.60 light years into metres	(1) (1) (1) (1) (1)	4
	Use of $I = P/A$ Use of $A = 4\pi r^2$ Power of Sirius $A = 9.73 \times 10^{27}$ W $\frac{\text{Example of calculation}}{8.60 \times 365 \times 24 \times 60 \times 60 \times (3.00 \times 10^8 \text{ ms}^{-1})} = 8.14 \times 10^{16} \text{ m}$ $P = I \times A = (1.17 \times 10^{-7} \text{ Wm}^{-2}) (4\pi) (8.14 \times 10^{16} \text{ m})^2 = 9.73 \times 10^{27} \text{ W}$	(1) (1) (1)	4
18c	Atoms have fixed/certain/discrete energy levels Or Emitted photons have discrete energy Only certain transitions are possible (in a hydrogen atom) Or Some transitions are not possible (in a hydrogen atom) (For MP2, allow "differences in energy (levels)" for "transitions")	(1)	2
	Total for question 18		10