TCS CORPORATE WEBSITE

Button — Authoring Guide

Role / audience	Authoring — Content authors, content managers, AEM authoring leads
Version	1.0
Status	Draft for review
Owner	Content Lead / AEM Authoring Lead (proposed)
Last validated	2026-11-08
Documents	1
Classification	INTERNAL — classification to be confirmed

Generated from the Markdown sources of docs/handover (branch migrated-page-content-edam); do not edit this PDF.

Contents

Button — Authoring Guide
- Where to see it
- For Content Authors
- Authorable Fields
- Screenshot-Based Authoring Steps
- Variations
- Complete Authoring Example
- Content and Asset Guidelines
- Troubleshooting
- Screenshots
- Known limitations
- Open items
- Change history

Button — Authoring Guide

Attribute	Value
Document ID	AUT-C-button-block
Audience	Content authors, content managers, AEM authoring leads
Purpose	How to add, fill in and check the Button component
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	8 November 2026
Last validated	8 November 2026
Source files	blocks/button-block/README.md, blocks/button-block/_button-block.json
Related documents	—
Related AEM paths	—

1. Where to see it

No block library page.

2. For Content Authors

1. **Add the block.** Select a Section, a Columns Container column or a Tabs Container tab, choose Add (+) and pick **Button**.
2. **Open its properties.** Select the block; the panel has the **Content**, **Style** and **Additional** tabs.
3. **Enter the content (Content tab).** Pick the page or asset, or enter a URL, in **Link**; write the label in **Text** (the accessible name of an icon button); add a **Title** only for extra context (a tooltip).
4. **Choose the look (Style tab). View**: Button, Icon or Link. **Type** (Button and Icon views): Primary, Secondary or Tertiary. **Icon** (Icon view): Arrow right, Chevron right, Chevron down or Search. **Alignment**: Left, Center or Right.
5. **Optional: Additional tab** (Anchor ID, Hide block, animation, spacing).
6. **Preview** at desktop, tablet and mobile widths; check the label isn't clipped.
7. **Publish** the page; publish the target page too.
8. **Validate the published output:** the button has the chosen look and opens the target.

Minimum required: Link (without it nothing is shown on the page; in the editor the block says what to add). **Recommended:** Text. **Optional:** Title, Style tab values, Additional tab.

3. Authorable Fields

Button (`button-block`)

Model `button-block`; template name "Button Block" (the block class AEM renders); key-value block (one row per property).

Stored on a new component (definition template): `buttonView` = `"button"`, `buttonVariant` = `"primary"`, `buttonAlignment` = `"left"`.

Content tab — Button

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Link	`link`	aem-content	No	—	—	An AEM page, an asset or a URL.	/design-block-master/en/curated-design-pages
Text	`linkText`	text	No	—	—	The label of the button (the accessible name of an icon button). Delivered with `link` (field collapse).	Curated design pages
Title	`linkTitle`	text	No	—	—	Optional tooltip (most buttons need none). Delivered with `link` (field collapse).	Contact the TCS team

Style tab — Button

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
View	`buttonView`	select	No	`button`	Button (`button`), Icon (`icon`), Link (`link`)	Button, an icon-only button (choose its Icon) or a text link.	button
Type	`buttonVariant`	select	No	`primary`	Primary (`primary`), Secondary (`secondary`), Tertiary (`tertiary`)	The emphasis of the Button and Icon views. Shown when `buttonView` is off or empty or `buttonView` is `button` or `buttonView` is `icon`.	secondary
Icon	`buttonIcon`	select	No	`arrow-right`	Arrow right (`arrow-right`), Chevron right (`chevron-right`), Chevron down (`chevron-down`), Search (`search`)	The icon of the Icon view; the Text becomes its accessible name. Shown when `buttonView` is `icon`.	search
Alignment	`buttonAlignment`	select	No	`left`	Left (`left`), Center (`center`), Right (`right`)	Where the button sits in its section or column.	left
Text Decoration	`textDecoration`	select	No	`none`	Default (`none`), Overline (`overline`), line-Through (`line-through`), Underline (`underline`), underline overline (`underline overline`)	The text decoration of the button.	—

Additional tab — Button

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Anchor ID	`classes_anchor`	text	No	—	regExp: ^anchor-[a-z0-9][a-z0-9-]*$; customErrorMsg: Start with anchor-, then lower-case letters, digits and hyphens.	A unique ID of the block on the page, starting with anchor-, e.g. anchor-our-services; link to it with #anchor-our-services. Delivered as a block class.	—
Hide block	`classes_hideblock`	boolean	No	false	on / off	Hides the whole block on the page until it is turned off (shown faded in the editor). Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Animation Type	`classes_animation`	select	No	""	None (""), Fade in (`motion-fade-in`), Fade up (`motion-fade-up`), Fade down (`motion-fade-down`), Fade left (`motion-fade-left`), Fade right (`motion-fade-right`), Slide up (`motion-slide-up`), Slide down (`motion-slide-down`), Slide left (`motion-slide-left`), Slide right (`motion-slide-right`), Scale in (`motion-scale-in`)	How the block's content appears; repeated items (cards, list items, accordion items, columns) appear one after another. None: shown as is. Not played in the editor or when the visitor prefers reduced motion. Delivered as a block class.	—
Motion Speed	`classes_animationspeed`	select	No	""	Medium (""), Fast (`motion-fast`), Slow (`motion-slow`)	How fast the animation runs: 0.3, 0.6 or 0.9 seconds. Shown when `classes_animation` is set and `classes_animation` is not empty. Delivered as a block class.	—
Animation Trigger	`classes_animationtrigger`	select	No	""	On Scroll / Viewport Entry (""), On Page Load (`motion-on-load`)	When the block's animations run. On Scroll: when the block comes into view (at once if it is in view when the page opens). On Page Load: as soon as the block is ready, wherever it is on the page. Shown when `classes_animation` is set and `classes_animation` is not empty. Delivered as a block class.	—
Padding left	`classes_paddingleft`	select	No	""	Default (""), 0 (none) (`pl-0`), 0.25rem (space-100) (`pl-100`), 0.5rem (space-200) (`pl-200`), 0.75rem (space-300) (`pl-300`), 1rem (space-400) (`pl-400`), 1.25rem (space-500) (`pl-500`), 1.5rem (space-600) (`pl-600`), 2rem (space-800) (`pl-800`), 2.5rem (space-1000) (`pl-1000`), 3rem (space-1200) (`pl-1200`), 4rem (space-1600) (`pl-1600`), 5rem (space-2000) (`pl-2000`), 6rem (space-2400) (`pl-2400`), 7.5rem (space-3000) (`pl-3000`)	Delivered as a block class.	—
Padding right	`classes_paddingright`	select	No	""	Default (""), 0 (none) (`pr-0`), 0.25rem (space-100) (`pr-100`), 0.5rem (space-200) (`pr-200`), 0.75rem (space-300) (`pr-300`), 1rem (space-400) (`pr-400`), 1.25rem (space-500) (`pr-500`), 1.5rem (space-600) (`pr-600`), 2rem (space-800) (`pr-800`), 2.5rem (space-1000) (`pr-1000`), 3rem (space-1200) (`pr-1200`), 4rem (space-1600) (`pr-1600`), 5rem (space-2000) (`pr-2000`), 6rem (space-2400) (`pr-2400`), 7.5rem (space-3000) (`pr-3000`)	Delivered as a block class.	—
Padding top	`classes_paddingtop`	select	No	""	Default (""), 0 (none) (`pt-0`), 0.25rem (space-100) (`pt-100`), 0.5rem (space-200) (`pt-200`), 0.75rem (space-300) (`pt-300`), 1rem (space-400) (`pt-400`), 1.25rem (space-500) (`pt-500`), 1.5rem (space-600) (`pt-600`), 2rem (space-800) (`pt-800`), 2.5rem (space-1000) (`pt-1000`), 3rem (space-1200) (`pt-1200`), 4rem (space-1600) (`pt-1600`), 5rem (space-2000) (`pt-2000`), 6rem (space-2400) (`pt-2400`), 7.5rem (space-3000) (`pt-3000`)	Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Padding bottom	classes_paddingbottom	select	No	""	Default (""), 0 (none) (pb-0), 0.25rem (space-100) (pb-100), 0.5rem (space-200) (pb-200), 0.75rem (space-300) (pb-300), 1rem (space-400) (pb-400), 1.25rem (space-500) (pb-500), 1.5rem (space-600) (pb-600), 2rem (space-800) (pb-800), 2.5rem (space-1000) (pb-1000), 3rem (space-1200) (pb-1200), 4rem (space-1600) (pb-1600), 5rem (space-2000) (pb-2000), 6rem (space-2400) (pb-2400), 7.5rem (space-3000) (pb-3000)	Delivered as a block class.	—
Margin left	classes_marginleft	select	No	""	Default (""), 0 (none) (ml-0), 0.25rem (space-100) (ml-100), 0.5rem (space-200) (ml-200), 0.75rem (space-300) (ml-300), 1rem (space-400) (ml-400), 1.25rem (space-500) (ml-500), 1.5rem (space-600) (ml-600), 2rem (space-800) (ml-800), 2.5rem (space-1000) (ml-1000), 3rem (space-1200) (ml-1200), 4rem (space-1600) (ml-1600), 5rem (space-2000) (ml-2000), 6rem (space-2400) (ml-2400), 7.5rem (space-3000) (ml-3000)	Delivered as a block class.	—
Margin right	classes_marginright	select	No	""	Default (""), 0 (none) (mr-0), 0.25rem (space-100) (mr-100), 0.5rem (space-200) (mr-200), 0.75rem (space-300) (mr-300), 1rem (space-400) (mr-400), 1.25rem (space-500) (mr-500), 1.5rem (space-600) (mr-600), 2rem (space-800) (mr-800), 2.5rem (space-1000) (mr-1000), 3rem (space-1200) (mr-1200), 4rem (space-1600) (mr-1600), 5rem (space-2000) (mr-2000), 6rem (space-2400) (mr-2400), 7.5rem (space-3000) (mr-3000)	Delivered as a block class.	—
Margin top	classes_margintop	select	No	""	Default (""), 0 (none) (mt-0), 0.25rem (space-100) (mt-100), 0.5rem (space-200) (mt-200), 0.75rem (space-300) (mt-300), 1rem (space-400) (mt-400), 1.25rem (space-500) (mt-500), 1.5rem (space-600) (mt-600), 2rem (space-800) (mt-800), 2.5rem (space-1000) (mt-1000), 3rem (space-1200) (mt-1200), 4rem (space-1600) (mt-1600), 5rem (space-2000) (mt-2000), 6rem (space-2400) (mt-2400), 7.5rem (space-3000) (mt-3000)	Delivered as a block class.	—
Margin bottom	classes_marginbottom	select	No	""	Default (""), 0 (none) (mb-0), 0.25rem (space-100) (mb-100), 0.5rem (space-200) (mb-200), 0.75rem (space-300) (mb-300), 1rem (space-400) (mb-400), 1.25rem (space-500) (mb-500), 1.5rem (space-600) (mb-600), 2rem (space-800) (mb-800), 2.5rem (space-1000) (mb-1000), 3rem (space-1200) (mb-1200), 4rem (space-1600) (mb-1600), 5rem (space-2000) (mb-2000), 6rem (space-2400) (mb-2400), 7.5rem (space-3000) (mb-3000)	Delivered as a block class.	—

What the tables don't show:

- **Link** / **Text** / **Title** arrive as one link (Text and Title collapse into it): Text is the link's label, Title its `title` attribute. The Button and Link views have a tooltip only when Title is authored; the Icon view sets the tooltip to its accessible name when Title is empty.
- **View** renders `a.button.{type}` (Button), `a.button.{type}.icon-button` with the icon as a CSS mask and the Text hidden in a `span` and used as `aria-label` (Icon), or `a.link-button` (Link; Type is ignored and hidden in the dialog).
- **Type** is stored as `buttonVariant`: a field ending in `Type` would collapse into the link.

- **Icon** is read only for the Icon view (default Arrow right); the icon is `/icons/{name}.svg`.
- **Alignment** adds `button-align-{value}` to the paragraph around the link (`text-align` start, center or end).
- **Accessibility impact:** Text is the accessible name in every view; never leave it empty for the Icon view.
- **Data-layer impact:** none of the fields adds tracking attributes; the click is tracked centrally on the block.
- **Legacy mapping:** unknown or empty values fall back to the defaults (Button, Primary, Left). Buttons authored before with the built-in Button keep working with Primary or Secondary (bold / italic); replace one with a Button block to use the other options.
- **Additional tab:** as on every block (AGENTS.md "Additional tab"; Animation Type moves the block).

4. Screenshot-Based Authoring Steps

Authoring Step 1: Add the Button and set the link

```
[Screenshot Placeholder]

File name:
button-block-authoring-step-1.png

Purpose:
The Button added from the section's Add (+), the Content tab with Link and Text filled.

Annotations:
A = Add (+)
B = Link
C = Text
D = Title
```

Values to Enter

Callout	Field	Value	Reason	Expected result
B	Link	/language-masters/en/curated-design-pages	The target page	The button links to the page
C	Text	Curated design pages	Visible label	The pill shows the label with an arrow
D	Title	(empty)	Most buttons need no tooltip	No `title` attribute

Author action: add the Button, pick the page and write the label. **Expected preview:** a black primary pill, left aligned. **Expected published result:** the same, linking to the published path. **Business rules:** without a Link nothing is shown. **Validation:** click and keyboard (Tab, Enter) open the page. **Common mistakes:** the label equals the URL; an unpublished target page.

Authoring Step 2: Choose the view and type

```
[Screenshot Placeholder]

File name:
button-block-authoring-step-2.png

Purpose:
The Style tab with View Button and Type Secondary, and the outlined pill on the canvas.

Annotations:
A = View
B = Type
C = The secondary button
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	View	Button	A pill button	`a.button`
B	Type	Secondary	Next to a primary action	Outlined pill

Author action: set View and Type. **Expected result:** the outlined secondary pill. **Business rules:** one primary per section; Type is hidden for the Link view. **Validation:** hover shows the brand-blue state. **Common mistakes:** Type missing in the dialog because View is Link.

Authoring Step 3: An icon button

```
[Screenshot Placeholder]

File name:
button-block-authoring-step-3.png

Purpose:
View Icon with Icon Search, and the round search icon button on the canvas.

Annotations:
A = View
B = Icon
C = Text (the accessible name)
D = The icon button
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	View	Icon	Icon-only button	Round 2.75rem button
B	Icon	Search	The action's icon	The search icon
C	Text	Search	Accessible name and tooltip	Announced "Search"

Author action: set View Icon, choose the Icon and keep a Text. **Expected result:** a round icon button with the label hidden on screen. **Business rules:** the Icon field shows only for the Icon view. **Validation:** a screen reader announces the Text. **Common mistakes:** empty Text (the name falls back to the Title or the icon name).

Authoring Step 4: Align the button

```
[Screenshot Placeholder]

File name:
button-block-authoring-step-4.png

Purpose:
Alignment Center and the button centred in the section.

Annotations:
A = Alignment
B = The centred button
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Alignment	Center	Centred layout	The button centred in its section or column

Author action: choose the alignment. **Expected result:** `button-align-center` on the paragraph. **Validation:** check at 390 px too. **Common mistakes:** right-aligning an important action.

5. Variations

Primary, Secondary, Tertiary (Button view)

- **Purpose:** the emphasis of a call to action; one primary per section.
- **Fields:** Link, Text; View Button; Type.
- **Rendering:** `a.button.primary|secondary|tertiary` with a trailing arrow (`icons/arrow-right.svg` as a CSS mask); min height `--button-height` (3.125rem); labels don't wrap (`white-space: nowrap`) and are clipped at the container width.
- **Accessibility / data layer:** a link named by its Text; `cmp:click` on click.
- **Fallback:** an unknown Type renders Primary.

Icon view

- **Purpose:** compact actions (search, arrow, chevron). **Fields:** Link, Text, View Icon, Icon, Type.
- **Rendering:** a round `--icon-button-size` (2.75rem) button; the Text kept in a hidden `span`, as `aria-label` and as tooltip.

```
[Screenshot Placeholder]

File name:
button-block-icon-types-mobile.png

Purpose:
The three icon button types with each of the four icons at 390 px.

Annotations:
A = Primary icon buttons
B = Secondary icon buttons
C = Tertiary icon buttons
```

Link view

- **Purpose:** a text call to action ("View all insights"). **Rendering:** `a.link-button`, underlined, semibold, with a trailing chevron (`icons/chevron-right.svg`); Type ignored.

Alignment Left, Center, Right

- **Rendering:** `p.button-wrapper.button-align-left|center|right` (`text-align` start / center / end, so it follows the reading direction).

6. Complete Authoring Example

Scenario: the primary call to action of a services section.

Field	Example value	Guidance
Link	/language-masters/en/curated-design-pages	Pick with the picker
Text	Contact us	Verb first, short

Field	Example value	Guidance
Title	Contact the TCS team	Only extra context
View	Button	Default
Type	Primary	One per section
Alignment	Left	Default

Steps: add the Button after the section's text, fill the Content and Style tabs, preview, publish.

Expected output: a black primary pill "Contact us" with an arrow, left aligned, tooltip "Contact the TCS team".

Responsive: same size at every viewport; check the label fits at 390 px.

Accessibility: a link named "Contact us"; visible focus outline.

Analytics / data layer: `tcs-corp/components/button-block` (`button-block-1`); a click pushes `cmp:click` with `interaction` `link`.

Personalization fallback: none.

Pre-publish checklist:

1. Link set and the target published.
2. Text describes the outcome (not "Click here").
3. One primary per section.
4. Label fits at 390 px.
5. Icon buttons have a Text.

7. Content and Asset Guidelines

- **Labels:** start with a verb, describe the outcome; keep them short (labels don't wrap and are clipped).
- **Title:** optional context only; mention the format of downloads.
- **Links:** internal pages with the picker; external URLs open in the same tab (no new-tab option).
- **Icons:** Arrow right, Chevron right, Chevron down, Search (files in `/icons`).
- **Tags and metadata:** none.
- **Min / max items:** one link per block. No verified technical limit was identified.
- **Missing content:** no Link: nothing on the page; the editor hint (placeholder `buttonBlockEmpty`, "Button: add a Link and a Text.").

8. Troubleshooting

Symptom	Likely cause	Diagnostic steps	Resolution	Verification
Nothing on the page	No Link	Editor shows the hint	Set the Link	Button renders
Options have no effect	It's a built-in Button ("Button (basic)") authored before	Content tree component name	Replace it with a Button block	Options apply
Icon view shows no icon	Icon value unknown	Inspect `--icon-url`	Choose an Icon	Icon visible
Label clipped on mobile	Labels never wrap	390 px preview	Shorten the label	Fits
External link opens in the same tab	No new-tab option	Inspect `target`	Accept, or use a block with a new-tab option	—

Symptom	Likely cause	Diagnostic steps	Resolution	Verification
No click in the data layer	Tested in edit mode, or `data-analytics="off"` ancestor	`adobeDataLayer` on preview	Test on preview / live	`cmp:click` appears

Evidence to collect (no secrets): page URL, `.plain.html` of the block, the rendered link's classes and attributes, the data-layer entry.

9. Screenshots

> **Screenshot required**
>
> - Required screen: Button dialog in Universal Editor (every tab, including Additional)
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

10. Known limitations

- Universal Editor screenshots are placeholders: no author access in this program.

11. Open items

- None.

12. Change history

Version	Date	Author	Change
1.0	8 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages