TCS CORPORATE WEBSITE

Hero — Authoring Guide

Role / audience	Authoring — Content authors, content managers, AEM authoring leads
Version	1.0
Status	Draft for review
Owner	Content Lead / AEM Authoring Lead (proposed)
Last validated	2026-11-13
Documents	1
Classification	INTERNAL — classification to be confirmed

Generated from the Markdown sources of docs/handover (branch migrated-page-content-edam); do not edit this PDF.

Contents

Hero — Authoring Guide
- Where to see it
- For Content Authors
- Authorable Fields
- Screenshot-Based Authoring Steps
- Variations
- Complete Authoring Example
- Content and Asset Guidelines
- Troubleshooting
- Screenshots
- Known limitations
- Open items
- Change history

Hero — Authoring Guide

Attribute	Value
Document ID	AUT-C-hero
Audience	Content authors, content managers, AEM authoring leads
Purpose	How to add, fill in and check the Hero component
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	blocks/hero/README.md, blocks/hero/_hero.json
Related documents	—
Related AEM paths	—

1. Where to see it

- https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/block-library/hero
- https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/block-library/hero/hero-ctas
- https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/block-library/hero/hero-motion
- https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/block-library/hero/hero-overview
- https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/block-library/hero/hero-styles

2. For Content Authors

1. **Add the block.** In Universal Editor select a Section, a Columns Container column, a Gen Carousel or a Tabs Container in the content tree, choose **Add (+)** and pick **Hero**. A new Hero stores Vertical Alignment Middle, Horizontal Alignment Center, Text Alignment Center align and Title heading level H1.
2. **Open its properties.** Select the Hero in the content tree; the properties panel shows the **Content**, **Style** and **Additional** tabs.
3. **Enter content (Content tab).** Choose a **Hero Image Path** and enter its **Hero Image alt text** (leave the alt empty only for a decorative image). Enter the **Eyebrow**, **Title** and **Description**; set **Title heading level** to H1 for the page's main Hero, H2 for any other. Add an **Icon** (with **Icon Image Alt Text**) only if the design needs it.
4. **Select variations.** For an animation set **Hero Image type** to Lotto and choose a Lottie `.json` file as the Hero Image Path. For an illustration that must be shown whole set **Hero View** to Contained image. On the **Style** tab choose **Vertical Alignment**, **Horizontal Alignment**, **Text Alignment** and **BG Color**.
5. **Add CTAs.** Select the Hero, choose **Add (+)** and pick **CTA**. Fill **CTA Link** (required) and **CTA Title**; choose **CTA view** (Default text link, Primary, Secondary), **CTA Arrow** (Auto, Right, Down) and **CTA Link Type** (Open in New Window only when needed). Reorder CTAs by dragging them in the content tree; the page shows them in that order.

6. **Additional tab.** Set an Anchor ID, Hide block, animations or spacing only when needed (see Authorable Fields).
7. **Preview.** Switch Universal Editor to Preview (animations play only there) or open the page on aem.page; check desktop, tablet and mobile widths.
8. **Publish.** Publish the page with its referenced assets. A Lottie `.json` file is served only once it is published itself (images travel with the page).
9. **Validate the published output.** On aem.live check the image loads with its alt text, exactly one H1 is on the page, every CTA goes to the right target, and a Lottie animation plays and pauses.

Minimum required content: a Title (a Hero without one renders, but has no heading). **Recommended:** a Hero Image with alt text, an Eyebrow, a Description and one or two CTAs. **Optional:** Icon, Lotto, Contained image, alignments, BG Color, Additional tab options.

3. Authorable Fields

Hero (`hero`)

Model `hero`; template name "Hero" (the block class AEM renders); children: `hero-cta`.

Stored on a new component (definition template): `classes_alignment` = `"align-middle"`, `content_titleType` = `"h1"`, `classes_horizontal` = `"align-center"`, `classes_textAlignment` = `"text-center"`.

Content tab — Hero

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Icon	`content_icon`	reference	No	—	—	—	/content/dam/tcs-corp/block-library/images/square-sample-3.jpg
Icon Image Alt Text	`content_iconAlt`	text	No	—	—	Leave empty if the icon is decorative. Delivered with `content_icon` (field collapse).	—
Hero Image type	`classes_media`	select	No	""	Default (""), Lotto (`lottie`)	Default: the Hero Image Path is an image. Lotto: it is a Lottie animation file (.json), played as the hero background. Delivered as a block class.	lottie
Hero Image Path	`image`	reference	No	—	—	Default: an image. Lotto: a Lottie animation file (.json).	/content/dam/tcs-corp/block-library/images/wide-sample.jpg
Hero Image alt text	`imageAlt`	text	No	—	—	Leave empty if the image or animation is decorative. Delivered with `image` (field collapse).	Consultants reviewing a transformation roadmap
Hero View	`classes`	select	No	""	Default (""), Contained image (`media-contained`)	Default: the image fills the hero behind the content. Contained image: the image (e.g. an illustration) is shown whole, centered behind the content.	media-contained
Eyebrow	`content_eyebrow`	text	No	—	—	—	Enterprise AI

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Title	`content_title`	text	No	—	—	—	Building on belief
Title heading level	`content_titleType`	select	No	`h1`	H1 (`h1`), H2 (`h2`)	Use H1 for the first hero of a page, H2 for the others. Delivered with `content_title` (field collapse).	h1
Description	`content_description`	richtext	No	`""`	—	—	—
CTA List	`ctas`	container (multiple)	No	—	—	CTAs authored before CTA items. Add CTAs to the hero with Add (CTA) instead.	—
CTA List › CTA Title	`ctaText`	text	No	—	—	—	—
CTA List › CTA Text color	`ctaTextColor`	select	No	`cta-text-black`	Default (Black) (`cta-text-black`), White (`cta-text-white`)	Text Color of CTA	—
CTA List › CTA Link	`cta`	aem-content	No	—	—	—	—
CTA List › CTA Link Type	`ctaTarget`	select	No	`same-window`	Default (`same-window`), Open in New Window (`new-window`)	—	—
CTA List › CTA view	`ctaType`	select	No	`default`	Default (`default`), Primary (`primary`), Secondary (`secondary`)	—	—
CTA List › Primary CTA BG Color (Primary only)	`ctaPrimaryBackground`	select	No	`primary-bg-default`	Default (`primary-bg-default`), Blue-cyan (azure) (`primary-bg-azure`)	Background Color of Primary CTA	—
CTA List › Secondary CTA BG Color (Secondary only)	`ctaBackground`	select	No	`secondary-bg-default`	Default (transparent) (`secondary-bg-default`), Light grey (`secondary-bg-light-grey`), Black 40% (`secondary-bg-black-40`)	Background Color of Secondary CTA	—
CTA List › Secondary CTA Border color (Secondary only)	`ctaBorder`	select	No	`secondary-border-default`	Default (as the BG Color) (`secondary-border-default`), Black (`secondary-border-black`), White (`secondary-border-white`)	Border Color of Secondary CTA	—
CTA List › CTA Arrow	`ctaArrow`	select	No	`right`	Right (`right`), Down (`down`)	Direction of the arrow next to the CTA text.	—

Style tab — Hero

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Vertical Alignment	classes_alignment	select	No	align-middle	Top (align-top), Middle (align-middle), Bottom (align-bottom)	Position of the content block: top, middle or bottom of the hero. Delivered as a block class.	align-top
Horizontal Alignment	classes_horizontal	select	No	align-center	Left (align-left), Center (align-center), Right (align-right)	Position of the content block: left, center or right of the hero (on desktop). Delivered as a block class.	align-left
Text Alignment	classes_textAlignment	select	No	text-center	Left align (text-left), Center align (text-center), Right align (text-right)	Alignment of the icon, text and CTAs inside the content block. Delivered as a block class.	text-left
BG Color	classes_background	select	No	""	Default (""), Light, no overlay (bg-light), Dark blue (bg-dark), Dark blue (subtle) (bg-dark-subtle), Black (bg-black), Charcoal Black 80 (cool charcoal) (bg-charcoal-80), Midnight Navy 60 (bg-navy-60), Charcoal Black 40 (deep charcoal) (bg-charcoal-40)	Default: light, the image under a white overlay. Light, no overlay: the image as is (e.g. a light gradient) with dark text. The dark options put white text over a navy, black or charcoal overlay. Delivered as a block class.	bg-dark
Icon color	classes_iconcolor	select	No	""	Default (as authored) (""), Black (icon-black), White (icon-white), Blue (icon-blue), Pale blue (icon-pale-blue)	Colour of the icon above the title, for a single-colour SVG icon. Default keeps the icon as authored. Delivered as a block class.	—
Eyebrow color	classes_eyebrowcolor	select	No	""	Default (royal blue) (""), Royal blue (eyebrow-royal-blue), Soft sky blue (eyebrow-sky-blue)	Colour of the eyebrow above the title. Delivered as a block class.	—
Title color	classes_titlecolor	select	No	""	Default (""), Black (title-black), White (title-white)	Colour of the title. Default: as the BG Color sets it (black on Default and Light, white on the dark options). Delivered as a block class.	—
Description color	classes_descriptioncolor	select	No	""	Default (""), Black (description-black), White (description-white)	Colour of the description. Default: as the BG Color sets it (black on Default and Light, white on the dark options). Delivered as a block class.	—

Additional tab — Hero

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Anchor ID	classes_anchor	text	No	—	regExp: ^anchor-[a-z0-9][a-z0-9-]*$; customErrorMsg: Start with anchor-, then lower-case letters, digits and hyphens.	A unique ID of the block on the page, starting with anchor-, e.g. anchor-our-services; link to it with #anchor-our-services. Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Hide block	`classes_hideblock`	boolean	No	false	on / off	Hides the whole block on the page until it is turned off (shown faded in the editor). Delivered as a block class.	—
Animation Type	`classes_animation`	select	No	""	None (""), Fade in (`motion-fade-in`), Fade up (`motion-fade-up`), Fade down (`motion-fade-down`), Fade left (`motion-fade-left`), Fade right (`motion-fade-right`), Slide up (`motion-slide-up`), Slide down (`motion-slide-down`), Slide left (`motion-slide-left`), Slide right (`motion-slide-right`), Scale in (`motion-scale-in`)	How the block's content appears; repeated items (cards, list items, accordion items, columns) appear one after another. None: shown as is. Not played in the editor or when the visitor prefers reduced motion. Delivered as a block class.	`motion-fade-in`
Motion Speed	`classes_animationspeed`	select	No	""	Medium (""), Fast (`motion-fast`), Slow (`motion-slow`)	How fast the block's animations run (Animation Type 0.3 / 0.6 / 0.9 s; the Background animation takes 1.5 times as long). Shown when (`classes_animation` is set and `classes_animation` is not empty) or (`classes_bganimation` is set and `classes_bganimation` is not empty). Delivered as a block class.	`motion-slow`
Animation Trigger	`classes_animationtrigger`	select	No	""	On Scroll / Viewport Entry (""), On Page Load (`motion-on-load`)	When the block's animations run. On Scroll: when the block comes into view (at once if it is in view when the page opens). On Page Load: as soon as the block is ready, wherever it is on the page. Shown when (`classes_animation` is set and `classes_animation` is not empty) or (`classes_bganimation` is set and `classes_bganimation` is not empty). Delivered as a block class.	`motion-on-load`
Background animation	`classes_bganimation`	select	No	""	None (""), Fade in (`bg-motion-fade-in`), Reveal from the centre (`bg-motion-reveal`), Wipe left to right (`bg-motion-wipe-right`), Wipe right to left (`bg-motion-wipe-left`), Wipe bottom to top (`bg-motion-wipe-up`), Scale reveal (`bg-motion-scale`)	How the block's background (its colour, image or overlay as set in the block) appears. It doesn't animate the content: see Animation Type. Motion Speed and Animation Trigger apply to it too. Not played in the editor or when the visitor prefers reduced motion. Delivered as a block class.	`bg-motion-scale`
Padding left	`classes_paddingleft`	select	No	""	Default (""), 0 (none) (`pl-0`), 0.25rem (space-100) (`pl-100`), 0.5rem (space-200) (`pl-200`), 0.75rem (space-300) (`pl-300`), 1rem (space-400) (`pl-400`), 1.25rem (space-500) (`pl-500`), 1.5rem (space-600) (`pl-600`), 2rem (space-800) (`pl-800`), 2.5rem (space-1000) (`pl-1000`), 3rem (space-1200) (`pl-1200`), 4rem (space-1600) (`pl-1600`), 5rem (space-2000) (`pl-2000`), 6rem (space-2400) (`pl-2400`), 7.5rem (space-3000) (`pl-3000`)	Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Padding right	classes_paddingright	select	No	""	Default (""), 0 (none) (pr-0), 0.25rem (space-100) (pr-100), 0.5rem (space-200) (pr-200), 0.75rem (space-300) (pr-300), 1rem (space-400) (pr-400), 1.25rem (space-500) (pr-500), 1.5rem (space-600) (pr-600), 2rem (space-800) (pr-800), 2.5rem (space-1000) (pr-1000), 3rem (space-1200) (pr-1200), 4rem (space-1600) (pr-1600), 5rem (space-2000) (pr-2000), 6rem (space-2400) (pr-2400), 7.5rem (space-3000) (pr-3000)	Delivered as a block class.	—
Padding top	classes_paddingtop	select	No	""	Default (""), 0 (none) (pt-0), 0.25rem (space-100) (pt-100), 0.5rem (space-200) (pt-200), 0.75rem (space-300) (pt-300), 1rem (space-400) (pt-400), 1.25rem (space-500) (pt-500), 1.5rem (space-600) (pt-600), 2rem (space-800) (pt-800), 2.5rem (space-1000) (pt-1000), 3rem (space-1200) (pt-1200), 4rem (space-1600) (pt-1600), 5rem (space-2000) (pt-2000), 6rem (space-2400) (pt-2400), 7.5rem (space-3000) (pt-3000)	Delivered as a block class.	—
Padding bottom	classes_paddingbottom	select	No	""	Default (""), 0 (none) (pb-0), 0.25rem (space-100) (pb-100), 0.5rem (space-200) (pb-200), 0.75rem (space-300) (pb-300), 1rem (space-400) (pb-400), 1.25rem (space-500) (pb-500), 1.5rem (space-600) (pb-600), 2rem (space-800) (pb-800), 2.5rem (space-1000) (pb-1000), 3rem (space-1200) (pb-1200), 4rem (space-1600) (pb-1600), 5rem (space-2000) (pb-2000), 6rem (space-2400) (pb-2400), 7.5rem (space-3000) (pb-3000)	Delivered as a block class.	—
Margin left	classes_marginleft	select	No	""	Default (""), 0 (none) (ml-0), 0.25rem (space-100) (ml-100), 0.5rem (space-200) (ml-200), 0.75rem (space-300) (ml-300), 1rem (space-400) (ml-400), 1.25rem (space-500) (ml-500), 1.5rem (space-600) (ml-600), 2rem (space-800) (ml-800), 2.5rem (space-1000) (ml-1000), 3rem (space-1200) (ml-1200), 4rem (space-1600) (ml-1600), 5rem (space-2000) (ml-2000), 6rem (space-2400) (ml-2400), 7.5rem (space-3000) (ml-3000)	Delivered as a block class.	—
Margin right	classes_marginright	select	No	""	Default (""), 0 (none) (mr-0), 0.25rem (space-100) (mr-100), 0.5rem (space-200) (mr-200), 0.75rem (space-300) (mr-300), 1rem (space-400) (mr-400), 1.25rem (space-500) (mr-500), 1.5rem (space-600) (mr-600), 2rem (space-800) (mr-800), 2.5rem (space-1000) (mr-1000), 3rem (space-1200) (mr-1200), 4rem (space-1600) (mr-1600), 5rem (space-2000) (mr-2000), 6rem (space-2400) (mr-2400), 7.5rem (space-3000) (mr-3000)	Delivered as a block class.	—
Margin top	classes_margintop	select	No	""	Default (""), 0 (none) (mt-0), 0.25rem (space-100) (mt-100), 0.5rem (space-200) (mt-200), 0.75rem (space-300) (mt-300), 1rem (space-400) (mt-400), 1.25rem (space-500) (mt-500), 1.5rem (space-600) (mt-600), 2rem (space-800) (mt-800), 2.5rem (space-1000) (mt-1000), 3rem (space-1200) (mt-1200), 4rem (space-1600) (mt-1600), 5rem (space-2000) (mt-2000), 6rem (space-2400) (mt-2400), 7.5rem (space-3000) (mt-3000)	Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Margin bottom	`classes_marginbottom`	select	No	""	Default (""), 0 (none) (`mb-0`), 0.25rem (space-100) (`mb-100`), 0.5rem (space-200) (`mb-200`), 0.75rem (space-300) (`mb-300`), 1rem (space-400) (`mb-400`), 1.25rem (space-500) (`mb-500`), 1.5rem (space-600) (`mb-600`), 2rem (space-800) (`mb-800`), 2.5rem (space-1000) (`mb-1000`), 3rem (space-1200) (`mb-1200`), 4rem (space-1600) (`mb-1600`), 5rem (space-2000) (`mb-2000`), 6rem (space-2400) (`mb-2400`), 7.5rem (space-3000) (`mb-3000`)	Delivered as a block class.	—

CTA (`hero-cta`)

Model `hero-cta`; template name "CTA" (the block class AEM renders).

Fields — CTA

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
CTA Link	`link`	aem-content	Yes	—	—	—	—
CTA Title	`linkText`	text	No	—	—	Delivered with `link` (field collapse).	—
CTA Link Type	`linkTarget`	select	No	""	Default (""), Open in New Window (`new-window`)	—	—
CTA view	`linkStyle`	select	No	""	Default (""), Primary (`primary`), Secondary (`secondary`)	—	—
CTA Arrow	`linkArrow`	select	No	""	Auto (down for links to sections of this page) (""), Right (`right`), Down (`down`)	Direction of the arrow next to the CTA text.	—

Notes on the significant fields (the tables above list every field, default and allowed value):

- **Hero Image Path / Hero Image type.** With Default the reference renders as a `<picture>` covering the banner (`object-fit: cover`). With Lotto and a `.json` link the Lottie player renders an SVG animation instead (`createAnimation`, class `hero-animation`). With Lotto and an image, the image is shown; with Default and a `.json` link, no media is rendered.
- **Hero Image alt text.** Becomes the image's `alt`. For a Lottie file AEM delivers the alt as the link text; `animationLabel` (`utils/media.js`) reads it and the animation gets `role="img"` and `aria-label`; without an alt it is `aria-hidden="true"`.
- **Icon / Icon Image Alt Text.** The first stand-alone picture before the title becomes `div.hero-icon` (`--icon-size-l`, 3rem from 900px); further pictures go to the description.
- **Eyebrow.** Rendered as `p.hero-eyebrow` only when there is a Title; without a Title every text element goes to the description.
- **Title / Title heading level.** The heading level collapses into the title (AEM delivers an `h1` or `h2`); it becomes `.hero-title`. Accessibility and SEO: one H1 per page.
- **Description.** Rich text in `div.hero-description` (omitted when empty).
- **CTA (item) fields.** CTA view Primary / Secondary render `a.button.primary` / `a.button.secondary`; Default renders `a.button.tertiary` (text with an arrow). CTA Arrow Down, or Auto with a link starting with `#`, adds `hero-cta-down` (down arrow). Open in New Window sets `target="_blank"`, `rel="noopener noreferrer"` and appends the visually hidden placeholder text `opensInNewTab` ("(opens in a new tab)"). A CTA without a link isn't rendered (in Universal Editor it is a dashed placeholder).

- **BG Color.** Default: white overlay at 80 %. Light, no overlay: the image as is. Dark blue: navy overlay at 80 %; Dark blue (subtle): 60 %; Black: black at 80 %; the dark options switch the title to white, the description to 50 % white (85 % on Dark blue (subtle)), the eyebrow to `--brand-300` (white on Dark blue (subtle)) and Secondary / Default CTAs to white. Without media no overlay is drawn.
- **Alignments.** Vertical and Horizontal Alignment position the content block (nine positions); Text Alignment aligns the icon, text and CTAs inside it. Heroes authored before Text Alignment existed follow their Horizontal Alignment.
- **Data-layer impact.** None of the fields changes the data-layer entry except the Title (its text is the component's `dc:title`) and Anchor ID (the component id).
- **Legacy mapping.** CTAs authored in the former **CTA List** composite multifield (`ctas`: CTA Title, CTA Link, CTA Link Type, CTA view as bold / italic, CTA Arrow) are still read and shown before the CTA items. A Primary one can have a **Primary CTA BG Color** (Blue-cyan (azure), `#216AC3` `--color-bg-brand` with white text, also in dark sections), a Secondary one a **Secondary CTA BG Color** (Light grey, Black 40%) and **Secondary CTA Border color** (Black, White), labelled "(Primary only)" / "(Secondary only)" and always shown in the dialog (Universal Editor doesn't support conditions inside multifields), applied only for their CTA view; any CTA can also have a **CTA Text color** (Default (Black) or White, the field's default Default (Black) for new CTAs: the chosen colour of the text and arrow whatever the CTA view and background, also on Blue-cyan (azure) and in dark sections; choose the one that reads on the background: White on a black button, Black on azure or a light background; CTAs authored before without a value keep their colour): their values (`primary-bg-azure`, `secondary-bg-*`, `secondary-border-*`, `CTA_OPTIONS`, and `cta-text-black`, `cta-text-white`, `CTA_TEXT_COLORS` in `hero.js`) become classes of that CTA's button, which `hero.css` styles (hover and focus keep the button's own style); CTA items don't have them (KB-D-062). The former **Motion Type** values (`motion-fade`, `motion-slide`, `motion-zoom`) are mapped by `mapLegacyMotion` to Fade in, Fade up and Background Scale reveal, played Slow unless a Motion Speed is set, and only when the block has no Animation Type / Background animation of its own.
- **Additional tab.** Anchor ID, Hide block, spacing, Animation Type, Motion Speed, Animation Trigger and, because the Hero has an authored background, **Background animation**: see AGENTS.md "Additional tab" and "Animation and skeletons". The content animation moves `.hero-content`; the background animation the media and the overlay.

4. Screenshot-Based Authoring Steps

Authoring Step 1: Add the Hero

```
[Screenshot Placeholder]

File name:
hero-authoring-step-1.png

Purpose:
The Hero added to the first Section of the page in Universal Editor.

Annotations:
A = Section selected in the content tree
B = Add (+) menu with Hero
C = New Hero with the template defaults
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	(content tree)	First Section of the page	The opening Hero is the LCP element	Section selected
B	Add (+)	Hero	Adds the block	An empty Hero appears
C	(properties)	—	Template defaults are stored	Middle, Center, Center align, H1

Author action: select the Section, choose Add (+), pick Hero. Expected preview: an empty banner of the minimum height. Expected published result: nothing visible until content is entered. Business rule: only containers whose filter lists `hero` offer it. Validation: the Hero appears in the content tree under the Section. Common mistake: adding the Hero inside a Tabs Container's tab when it should open the page; resolution: move it to the first Section.

Authoring Step 2: Image and content

```
[Screenshot Placeholder]

File name:
hero-authoring-step-2.png

Purpose:
The Content tab with the image, alt text, eyebrow, title, heading level and description filled.

Annotations:
A = Hero Image Path
B = Hero Image alt text
C = Eyebrow
D = Title
E = Title heading level
F = Description
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Hero Image Path	/content/dam/tcs-corp/block-library/images/wide-sample.jpg	Cover image	The image fills the banner under the white overlay
B	Hero Image alt text	Consultants reviewing a transformation roadmap	Text alternative (WCAG 1.1.1)	`alt` on the image
C	Eyebrow	Enterprise AI	Topic label above the title	Brand-coloured eyebrow
D	Title	Building on belief	The page's headline	Large title
E	Title heading level	H1	First Hero of the page	`h1.hero-title`
F	Description	Our AI-led services help enterprises grow, transform and compete with confidence.	Supporting sentence	Grey description below the title

Author action: open the Content tab and enter the values. Expected preview: centred eyebrow, title and description over the softened image. Expected published result: the same, the image loaded eagerly with high priority in the first section. Business rule: the eyebrow only shows when there is a title. Validation: one `h1` on the page. Common mistake: leaving the alt empty for an informative image; resolution: describe the image.

Authoring Step 3: CTAs

```
[Screenshot Placeholder]

File name:
hero-authoring-step-3.png

Purpose:
Two CTA items added to the Hero with Add, the first one's dialog open.

Annotations:
```

```
A = CTA Link
B = CTA Title
C = CTA view
D = CTA Arrow
E = CTA Link Type
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	CTA Link	/en/contact (first CTA), /en/services (second CTA)	Destination	Links rendered
B	CTA Title	Talk to our experts / Explore our services	Visible label and accessible name	Button labels
C	CTA view	Primary / Secondary	Primary action first	Filled and outline pill buttons
D	CTA Arrow	Auto	Arrow right for other pages, down for # links	Right arrows
E	CTA Link Type	Default	Same tab	No `target` attribute

Author action: select the Hero, Add (+) › CTA, fill the dialog; repeat for the second CTA. Expected preview: two CTAs side by side below the description, wrapping when they don't fit. Expected published result: the same. Business rule: CTA Link is required; a CTA without a link isn't rendered. Validation: both CTAs open their pages. Common mistake: entering a CTA Title without a CTA Link (the editor shows a dashed placeholder); resolution: fill CTA Link.

Authoring Step 4: Style

```
[Screenshot Placeholder]

File name:
hero-authoring-step-4.png

Purpose:
The Style tab with the content block moved to the left and a dark overlay.

Annotations:
A = Vertical Alignment
B = Horizontal Alignment
C = Text Alignment
D = BG Color
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Vertical Alignment	Middle	Content in the vertical centre	Centred vertically
B	Horizontal Alignment	Left	Keep the image subject on the right free	Content block on the left, at most 47.5rem wide from 900px
C	Text Alignment	Left align	Text follows the block's position	Text and CTAs start at the left
D	BG Color	Dark blue	Brand statement with white text	Navy overlay, white title, light eyebrow

Author action: open the Style tab and choose the values. Expected preview: white text on the navy overlay, content on the left. Expected published result: the same. Business rule: Text Alignment is independent of

Horizontal Alignment. Validation: text contrast is readable at the text position. Common mistake: Light, no overlay over a busy photograph; resolution: choose Default or a dark BG Color.

Authoring Step 5: Preview, publish and verify

```
[Screenshot Placeholder]

File name:
hero-authoring-step-5.png

Purpose:
The Hero in Universal Editor Preview at desktop width, compared with the published page.

Annotations:
A = Preview toggle
B = Published Hero
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Preview	On	Animations play only in Preview	The Hero as visitors see it
B	Publish	Publish with referenced assets	The image must be published	The Hero on aem.live

Author action: switch to Preview, then publish. Expected result: the published Hero matches the preview. Validation: image request succeeds, alt text present, CTAs work. Common mistake: a Lotto Hero whose `.json` asset wasn't published (empty background on the published page); resolution: publish the asset.

5. Variations

The variations are the select values of the model (`blocks/hero/_hero.json`), delivered as block classes. They combine freely.

Default image (Hero Image type Default, Hero View Default)

Purpose: a photograph covering the whole banner. Use for most heroes; not for illustrations that must not be cropped. Required: Hero Image Path, alt text (or decorative). Rendering: `div.hero-media > picture` absolutely positioned behind the content, `object-fit: cover`, under the BG Color overlay; the block gets `hero-has-media`. Desktop / tablet / mobile: the image is cropped around its centre into the banner's height. Accessibility: the `alt` names the image. Data layer: no change. Personalization and fallback: no personalization; without an image the hero renders without media.

```
[Screenshot Placeholder]

File name:
hero-default-image-mobile.png

Purpose:
The Default image Hero at 375px: the image cropped to the centre of the 35rem banner.

Annotations:
A = Cropped cover image
B = Content block
```

Lotto (`lottie`)

Purpose: a looping Lottie animation as the background. Use for campaign pages with an approved Lottie JSON; not when the animation carries information the text doesn't. Required: Hero Image type Lotto, Hero Image Path a `.json` file; optional alt text. Rendering: `div.hero-media > div.hero-animation` (SVG renderer, `xMidYMid meet`, looping) and a pause / play `button.animation-toggle` appended to the block, 1rem (`--space-400`) from the bottom-right corner. The player loads when the hero is within 200px of the viewport, in idle time; the animation pauses off screen and starts paused on its first frame for reduced motion. If the file fails, the animation and its button are hidden. Accessibility: WCAG 2.2.2 pause control with localised labels (`pauseAnimation`, `playAnimation`). Data layer: a click on the button is a `cmp:click` with `interaction: animation`. Fallback: with Lotto and an image, the image is shown.

```
[Screenshot Placeholder]

File name:
hero-lottie-tablet.png

Purpose:
The Lotto Hero at 768px with the pause / play button in the bottom-right corner.

Annotations:
A = Lottie animation
B = Pause / play button
```

Contained image (`media-contained`)

Purpose: show an illustration or chart whole, centred behind the content. Use for artwork that must not be cropped; not for photographs meant to fill the banner. Rendering: the media becomes a centred flex box with `--space-600` padding and the image `object-fit: contain`. Usually paired with BG Color Light, no overlay. Accessibility and data layer as Default.

```
[Screenshot Placeholder]

File name:
hero-contained-image-mobile.png

Purpose:
The Contained image Hero at 375px: the whole illustration visible inside the banner.

Annotations:
A = Contained illustration
B = Content block
```

Text only (no media)

Purpose: a plain banner without image. Rendering: no `hero-media`, no `hero-has-media`, no overlay; the block background is `--color-bg-default` (navy or black with the dark BG Colors). Use for simple statement pages.

BG Color: Default, Light no overlay (`bg-light`), Dark blue (`bg-dark`), Dark blue subtle (`bg-dark-subtle`), Black (`bg-black`), Charcoal Black 80 (`bg-charcoal-80`), Midnight Navy 60 (`bg-navy-60`), Charcoal Black 40 (`bg-charcoal-40`)

Purpose: readability of the text over the media. Rendering and colours as in Authorable Fields; Charcoal Black 80 is a `rgba(34, 35, 41, 0.8)` overlay, Midnight Navy 60 `rgba(1, 18, 31, 0.6)` (the Dark blue subtle overlay with the 50 % white description of the other dark options), Charcoal Black 40 `rgba(12, 12, 13, 0.4)`; all three are dark options (white text, the header keeps its band). Use a dark option for white text on photographs; Light, no overlay only with light, calm images. Accessibility: the dark colours were adjusted for WCAG 1.4.3 (re-audit R-B-4); the Default overlay's eyebrow contrast awaits design sign-off.

```
[Screenshot Placeholder]

File name:
hero-bg-dark-subtle-mobile.png

Purpose:
BG Color Dark blue (subtle) at 375px: white eyebrow, white title and 85 % white description over the 60
% navy overlay.

Annotations:
A = White eyebrow
B = Description at 85 % white
C = White Secondary CTA
```

Vertical Alignment: Top, Middle, Bottom (`align-top`, `align-middle`, `align-bottom`)

Positions the content block in the banner's height (`justify-content`). Middle is the template default.

Horizontal Alignment: Left, Center, Right (`align-left`, `align-center`, `align-right`)

Positions the content block across the banner. From 900px Left and Right limit the content block to 47.5rem; below 900px it is full width.

Text Alignment: Left, Center, Right align (`text-left`, `text-center`, `text-right`)

Aligns the icon, text and CTAs inside the content block. Center align is the template default.

CTA view, CTA Arrow and CTA Link Type (item options)

Default (text with arrow, `tertiary`), Primary, Secondary; Arrow Auto / Right / Down; Link Type Default / Open in New Window. See Authorable Fields.

Title heading level H2

For any Hero other than the page's main one: the title renders as `h2.hero-title` with the same styles as an H1.

6. Complete Authoring Example

Scenario: the opening banner of the English Enterprise AI landing page.

Field	Example value	Guidance
Hero Image type	Default	A photograph
Hero Image Path	/content/dam/tcs-corp/block-library/images/wide-sample.jpg	A wide image with a centred subject
Hero Image alt text	Consultants reviewing a transformation roadmap	Describe what the image shows
Eyebrow	Enterprise AI	Short topic label
Title	Building on belief	One headline
Title heading level	H1	The page's only H1
Description	Our AI-led services help enterprises grow, transform and compete with confidence.	One or two sentences
CTA 1	Talk to our experts, /en/contact, Primary, Auto	The main action
CTA 2	Explore our services, /en/services, Secondary, Auto	The secondary action

Field	Example value	Guidance
Vertical / Horizontal / Text Alignment	Middle / Center / Center align	Template defaults
BG Color	Default	White overlay, dark text

Steps: add the Hero to the first Section (Authoring Step 1), fill the Content tab (Step 2), add the two CTAs (Step 3), keep the Style defaults, preview and publish (Step 5).

Expected output: a centred banner with the brand-blue eyebrow, the dark H1, the grey description and a filled and an outline button side by side over the softened photograph.

Responsive: 35rem high on phones, 40rem from 600px, 53.125rem from 900px (at most the first screen below the header in the first section); CTAs wrap when they don't fit.

Accessibility: one H1, image alt text, CTAs with meaningful text, keyboard reachable.

Analytics / data layer: the Hero is `hero-1` (or its Anchor ID) with `dc:title` "Building on belief"; each CTA click is a `cmp:click`.

Personalization fallback: none; the authored content is what renders.

Pre-publish checklist:

- [ ] Exactly one H1 on the page.
- [ ] Image alt text entered (or the image is decorative).
- [ ] Every CTA has a CTA Link and a meaningful CTA Title.
- [ ] Open in New Window used only where needed.
- [ ] Text readable over the image at desktop, tablet and mobile.
- [ ] Referenced assets (and any Lottie `.json`) published.
- [ ] Hide block is off.

7. Content and Asset Guidelines

- **Titles.** One message; use H1 only for the page's main Hero.
- **Descriptions.** One or two sentences; the description is limited to 53.125rem wide, the title to 72.5rem.
- **Eyebrows.** A short topic label; shown only with a title.
- **CTAs and links.** Action-oriented labels that make sense out of context; use Down arrows only for in-page anchors (`#anchor-...`). No verified technical limit on the number of CTAs was identified; the row wraps.
- **Images and alt text.** Wide images with the subject in the centre (the cover crop keeps the centre); describe informative images, leave the alt empty only for decorative ones. No verified aspect ratio or minimum size is enforced by the code.
- **Icons.** A small square image or SVG; shown at the `--icon-size-l` token size, 3rem from 900px.
- **Lottie.** A Lottie JSON for the SVG renderer from AEM Assets; it must be published separately (non-image DAM files aren't delivered with the page).
- **Tags and metadata.** None: the Hero has no tag field and reads no metadata.
- **Min / max items.** No verified technical limit was identified (CTAs, description length).
- **Asset source.** AEM Assets (DAM).
- **Loading.** In the first section of the page the hero image gets `loading="eager"` and `fetchpriority="high"`; elsewhere the delivered loading applies. The Lottie player loads lazily near the viewport.
- **Missing asset fallback.** Without media the Hero renders as a text banner without overlay; a Lottie that fails is hidden with its button.

8. Troubleshooting

Symptom	Likely cause	Diagnostic steps	Resolution	Verification
No animation behind the content	Hero Image type Default with a `.json` file; JSON asset not published; invalid Lottie	Check the block has class `lottie`; Network: `.json` status; console `failed to play the Lottie animation`	Set Lotto; publish the asset; re-export the Lottie	Animation plays on the published page
Animation shows its first frame only	Visitor prefers reduced motion	Check the OS setting	Expected; Play starts it	Toggle plays it
Two H1s on the page	Several Heroes with H1, or a Hero on a templated page with Page Header	Search the DOM for `h1`	Set Title heading level H2 on the others; use the Page Header on templated pages	One `h1`
A CTA is missing	CTA item without CTA Link	Open the CTA item	Fill CTA Link	CTA renders
CTA arrow points down for a normal link	CTA Arrow Down, or Auto with a # link	Check CTA Arrow / CTA Link	Set CTA Arrow Right	Right arrow
Text hard to read	Light, no overlay on a busy image; Dark blue (subtle) on a bright image	Contrast checker at the text	Choose Default or a dark BG Color, or another image	Contrast at least 4.5:1 (3:1 large text)
Hero missing on the published page	Hide block on	Block has class `hideblock`	Turn Hide block off and publish	Hero visible
Old Motion Type can't be changed	Legacy `motion-*` class from content authored before	Inspect the authored classes	Migrate to Animation Type (re-audit R-B-6)	Animation as chosen
Slow LCP on a page opening with a Hero	Background animation on the first Hero (F-94)	Lighthouse LCP	Use Background animation below the fold	LCP improves

Evidence to collect (no secrets): page URL, viewport, the block's classes and rendered HTML, console errors, Network status of the image / `.json`, the data-layer entries.

9. Screenshots



Figure: Hero as published (block library) — desktop 1440 × 900 (/design-block-master/en/block-library/hero/hero-ctas, captured 2026-11-08).




Figure: Hero as published (block library) — mobile 375 × 812 (/design-block-master/en/block-library/hero/hero-ctas, captured 2026-11-08).

> **Screenshot required**

> - Required screen: Hero dialog in Universal Editor (every tab, including Additional)
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

10. Known limitations

- Universal Editor screenshots are placeholders: no author access in this program.

11. Open items

- None.

12. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages