TCS CORPORATE WEBSITE

Media Contacts — Authoring Guide

Role / audience	Authoring — Content authors, content managers, AEM authoring leads
Version	1.0
Status	Draft for review
Owner	Content Lead / AEM Authoring Lead (proposed)
Last validated	2026-11-13
Documents	1
Classification	INTERNAL — classification to be confirmed

Generated from the Markdown sources of docs/handover (branch migrated-page-content-edam); do not edit this PDF.

Contents

Media Contacts — Authoring Guide
- Where to see it
- For Content Authors
- Authorable Fields
- Screenshot-Based Authoring Steps
- Variations
- Complete Authoring Example
- Content and Asset Guidelines
- Troubleshooting
- Screenshots
- Known limitations
- Open items
- Change history

Media Contacts — Authoring Guide

Attribute	Value
Document ID	AUT-C-media-contacts
Audience	Content authors, content managers, AEM authoring leads
Purpose	How to add, fill in and check the Media Contacts component
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	blocks/media-contacts/README.md, blocks/media-contacts/_media-contacts.json
Related documents	—
Related AEM paths	—

1. Where to see it

No block library page.

2. For Content Authors

1. **Add the block.** In Universal Editor, select a Section (or a Columns Container column or a Tabs Container), choose Add (+) and pick **Media Contacts**.
2. **Open its properties.** Select the block in the canvas or the content tree. It has two tabs: Content and Additional.
3. **Enter the title.** Title, e.g. "TCS media contacts", and Title Type (H2 by default; the group headings are one level below).
4. **The contacts.** They aren't typed into the block: they come from the locale's Media Contacts sheet (`/content/tcs-corp/{country}/{language}/data/media-contacts`). Ask whoever maintains the sheet to add or change a contact; every page with the block updates.
5. **Region.** The page's `region` metadata (metadata sheet) selects the contacts of that region; without matching rows (or without a region, e.g. Global) all contacts show.
6. **Child items:** none.
7. **Preview** at desktop and mobile widths, then **publish** the page. Publish the sheet too when it changed.
8. **Validate** on the published page: the groups, the links (mailto: / tel:) and the heading levels.

Minimum content: none (without a Title the heading is "Media contacts"). Recommended: Title. Required elsewhere: at least one row in the Media Contacts sheet.

3. Authorable Fields

Media Contacts (`media-contacts`)

Model `media-contacts`; template name "Media Contacts" (the block class AEM renders); key-value block (one row per property).

Stored on a new component (definition template): `titleType` = `"h2"`.

Content tab — Media Contacts

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Title	`title`	text	No	—	—	The heading above the contacts, e.g. "TCS media contacts". Empty: "Media contacts" (placeholder mediaContacts). The contacts come from the locale's Media Contacts sheet (data/media-contacts): those of the page's region, else all of them.	Media contacts
Title Type	`titleType`	select	No	h2	H1 (h1), H2 (h2), H3 (h3), H4 (h4), H5 (h5), H6 (h6)	Heading level of the Title; the contact groups are one level below. Delivered with `title` (field collapse).	h2

Additional tab — Media Contacts

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Anchor ID	`classes_anchor`	text	No	—	regExp: ^anchor-[a-z0-9][a-z0-9-]*$; customErrorMsg: Start with anchor-, then lower-case letters, digits and hyphens.	A unique ID of the block on the page, starting with anchor-, e.g. anchor-our-services; link to it with #anchor-our-services. Delivered as a block class.	—
Hide block	`classes_hideblock`	boolean	No	false	on / off	Hides the whole block on the page until it is turned off (shown faded in the editor). Delivered as a block class.	—
Animation Type	`classes_animation`	select	No	""	None (""), Fade in (`motion-fade-in`), Fade up (`motion-fade-up`), Fade down (`motion-fade-down`), Fade left (`motion-fade-left`), Fade right (`motion-fade-right`), Slide up (`motion-slide-up`), Slide down (`motion-slide-down`), Slide left (`motion-slide-left`), Slide right (`motion-slide-right`), Scale in (`motion-scale-in`)	How the block's content appears; repeated items (cards, list items, accordion items, columns) appear one after another. None: shown as is. Not played in the editor or when the visitor prefers reduced motion. Delivered as a block class.	motion-fade-up
Motion Speed	`classes_animationspeed`	select	No	""	Medium (""), Fast (`motion-fast`), Slow (`motion-slow`)	How fast the block's animations run (Animation Type 0.3 / 0.6 / 0.9 s; the Background animation takes 1.5 times as long). Shown when (`classes_animation` is set and `classes_animation` is not empty) or (`classes_bganimation` is set and `classes_bganimation` is not empty). Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Animation Trigger	classes_animationtrigger	select	No	""	On Scroll / Viewport Entry (""), On Page Load (motion-on-load)	When the block's animations run. On Scroll: when the block comes into view (at once if it is in view when the page opens). On Page Load: as soon as the block is ready, wherever it is on the page. Shown when (classes_animation is set and classes_animation is not empty) or (classes_bganimation is set and classes_bganimation is not empty). Delivered as a block class.	—
Padding left	classes_paddingleft	select	No	""	Default (""), 0 (none) (pl-0), 0.25rem (space-100) (pl-100), 0.5rem (space-200) (pl-200), 0.75rem (space-300) (pl-300), 1rem (space-400) (pl-400), 1.25rem (space-500) (pl-500), 1.5rem (space-600) (pl-600), 2rem (space-800) (pl-800), 2.5rem (space-1000) (pl-1000), 3rem (space-1200) (pl-1200), 4rem (space-1600) (pl-1600), 5rem (space-2000) (pl-2000), 6rem (space-2400) (pl-2400), 7.5rem (space-3000) (pl-3000)	Delivered as a block class.	—
Padding right	classes_paddingright	select	No	""	Default (""), 0 (none) (pr-0), 0.25rem (space-100) (pr-100), 0.5rem (space-200) (pr-200), 0.75rem (space-300) (pr-300), 1rem (space-400) (pr-400), 1.25rem (space-500) (pr-500), 1.5rem (space-600) (pr-600), 2rem (space-800) (pr-800), 2.5rem (space-1000) (pr-1000), 3rem (space-1200) (pr-1200), 4rem (space-1600) (pr-1600), 5rem (space-2000) (pr-2000), 6rem (space-2400) (pr-2400), 7.5rem (space-3000) (pr-3000)	Delivered as a block class.	—
Padding top	classes_paddingtop	select	No	""	Default (""), 0 (none) (pt-0), 0.25rem (space-100) (pt-100), 0.5rem (space-200) (pt-200), 0.75rem (space-300) (pt-300), 1rem (space-400) (pt-400), 1.25rem (space-500) (pt-500), 1.5rem (space-600) (pt-600), 2rem (space-800) (pt-800), 2.5rem (space-1000) (pt-1000), 3rem (space-1200) (pt-1200), 4rem (space-1600) (pt-1600), 5rem (space-2000) (pt-2000), 6rem (space-2400) (pt-2400), 7.5rem (space-3000) (pt-3000)	Delivered as a block class.	—
Padding bottom	classes_paddingbottom	select	No	""	Default (""), 0 (none) (pb-0), 0.25rem (space-100) (pb-100), 0.5rem (space-200) (pb-200), 0.75rem (space-300) (pb-300), 1rem (space-400) (pb-400), 1.25rem (space-500) (pb-500), 1.5rem (space-600) (pb-600), 2rem (space-800) (pb-800), 2.5rem (space-1000) (pb-1000), 3rem (space-1200) (pb-1200), 4rem (space-1600) (pb-1600), 5rem (space-2000) (pb-2000), 6rem (space-2400) (pb-2400), 7.5rem (space-3000) (pb-3000)	Delivered as a block class.	—
Margin left	classes_marginleft	select	No	""	Default (""), 0 (none) (ml-0), 0.25rem (space-100) (ml-100), 0.5rem (space-200) (ml-200), 0.75rem (space-300) (ml-300), 1rem (space-400) (ml-400), 1.25rem (space-500) (ml-500), 1.5rem (space-600) (ml-600), 2rem (space-800) (ml-800), 2.5rem (space-1000) (ml-1000), 3rem (space-1200) (ml-1200), 4rem (space-1600) (ml-1600), 5rem (space-2000) (ml-2000), 6rem (space-2400) (ml-2400), 7.5rem (space-3000) (ml-3000)	Delivered as a block class.	—

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Margin right	`classes_marginright`	select	No	""	Default (""), 0 (none) (`mr-0`), 0.25rem (space-100) (`mr-100`), 0.5rem (space-200) (`mr-200`), 0.75rem (space-300) (`mr-300`), 1rem (space-400) (`mr-400`), 1.25rem (space-500) (`mr-500`), 1.5rem (space-600) (`mr-600`), 2rem (space-800) (`mr-800`), 2.5rem (space-1000) (`mr-1000`), 3rem (space-1200) (`mr-1200`), 4rem (space-1600) (`mr-1600`), 5rem (space-2000) (`mr-2000`), 6rem (space-2400) (`mr-2400`), 7.5rem (space-3000) (`mr-3000`)	Delivered as a block class.	—
Margin top	`classes_margintop`	select	No	""	Default (""), 0 (none) (`mt-0`), 0.25rem (space-100) (`mt-100`), 0.5rem (space-200) (`mt-200`), 0.75rem (space-300) (`mt-300`), 1rem (space-400) (`mt-400`), 1.25rem (space-500) (`mt-500`), 1.5rem (space-600) (`mt-600`), 2rem (space-800) (`mt-800`), 2.5rem (space-1000) (`mt-1000`), 3rem (space-1200) (`mt-1200`), 4rem (space-1600) (`mt-1600`), 5rem (space-2000) (`mt-2000`), 6rem (space-2400) (`mt-2400`), 7.5rem (space-3000) (`mt-3000`)	Delivered as a block class.	—
Margin bottom	`classes_marginbottom`	select	No	""	Default (""), 0 (none) (`mb-0`), 0.25rem (space-100) (`mb-100`), 0.5rem (space-200) (`mb-200`), 0.75rem (space-300) (`mb-300`), 1rem (space-400) (`mb-400`), 1.25rem (space-500) (`mb-500`), 1.5rem (space-600) (`mb-600`), 2rem (space-800) (`mb-800`), 2.5rem (space-1000) (`mb-1000`), 3rem (space-1200) (`mb-1200`), 4rem (space-1600) (`mb-1600`), 5rem (space-2000) (`mb-2000`), 6rem (space-2400) (`mb-2400`), 7.5rem (space-3000) (`mb-3000`)	Delivered as a block class.	—

Notes on the significant fields:

- **Title / Title Type:** the heading of the block at the Title Type level (`buildHeading`); empty, it is the placeholder `mediaContacts` ("Media contacts") at that level. The group headings are one level below (H3 under an H2, at most H6).
- **The sheet's columns:** `id`, `name`, `designation`, `email`, `phone`, `region`. A row needs an id, a name, an e-mail address or a phone number. Rows with the same designation and region (case and spacing ignored) are one group, in the sheet's order; the group heading is "designation & region", or the one that is set. A name, when set, is shown above its contact's links.
- **Additional tab:** Anchor ID, Hide block, the animations (the title and the groups animate one after another) and Padding / Margin, as described in AGENTS.md "Additional tab".

4. Screenshot-Based Authoring Steps

Authoring Step 1: Add the Media Contacts block

Select the Section at the end of the press release, choose Add (+) and pick Media Contacts.

Values to Enter

Field	Value
(none)	The block is added with Title Type H2

Authoring Step 2: Title

Open the properties panel (Content tab).

Values to Enter

Field	Value
Title	TCS media contacts
Title Type	H2

Authoring Step 3: Check the contacts

Switch to Preview: the groups of the Media Contacts sheet appear. If the hint "The contacts come from the Media Contacts sheet …" shows, the sheet has no rows yet.

Values to Enter

Field	Value
Media Contacts sheet	One row per e-mail address or phone number: `designation` (e.g. Corporate Communications), `region` (e.g. India), `email`, phone

5. Variations

Default (all contacts)

A page whose `region` is Global (or empty, or without matching rows) lists every contact of the sheet.

Regional

A page whose `region` matches rows of the sheet (e.g. `Europe`) lists only those rows.

Without a Title

The heading is the placeholder "Media contacts".

6. Complete Authoring Example

Scenario: the migrated press release "TCS BaNCS for Treasury marks its entry into Sri Lanka with Indian Bank" (`/content/tcs-corp/language-masters/en/curated-design-pages/forms/…`).

Field	Example value	Guidance
Title	TCS media contacts	As on tcs.com
Title Type	H2	Under the page's H1
Page metadata `region`	Global	All contacts
Sheet rows	12 rows: Corporate Communications / India × 3 e-mail addresses; Asia Pacific, Canada, Latin America, Australia and New Zealand, Europe, Japan, Middle East & Africa, UK, USA with an e-mail address and a phone number each	One row per contact

- **Expected output:** "TCS media contacts", then 10 groups in two columns (5 + 5) from 900px.
- **Accessibility:** an `<h2>`, ten `<h3>` group headings, lists of links named "Email: …" / "Phone: …".

- **Analytics / data layer:** a `tcs-corp/components/media-contacts` entry; clicks as `cmp:click` with `interaction` email / phone and the group as `value`, without the address.
- **Personalization fallback:** all contacts when the page's region has none.

Pre-publish checklist: the sheet is published; the designations and regions are spelled the same in every row of a group; the title fits the page outline.

7. Content and Asset Guidelines

- **Title:** short ("TCS media contacts", "Press contacts").
- **Sheet:** one row per e-mail address or phone number; write phone numbers as they should read (+65 9270 4560); the link keeps only the digits and a leading +.
- **Personal data:** the sheet is published as JSON (`/{locale}/data/media-contacts.json`); list business contact details that may be public only.
- **Icons:** `icons/mail.svg` and `icons/phone.svg`, coloured by CSS (brand blue).
- **Limits:** no verified technical limit; long addresses wrap.

8. Troubleshooting

Symptom	Likely cause	Diagnostic steps	Resolution	Verification
The block doesn't show on the page	The sheet has no rows (or isn't published)	Open `/{locale}/data/media-contacts.json`	Add rows and publish the sheet	The groups appear
A group appears twice	Different spelling of the designation or region	Compare the rows	Spell them the same	One group
Only some contacts show	The page's `region` matches some rows	Check the page's `region` metadata	Change the region, or the rows' regions	The expected rows
A phone link dials a wrong number	Letters or extra characters in phone	Check the cell	Write the number with digits, spaces and a leading +	`tel:` link correct

9. Screenshots

> **Screenshot required**
>
> - Required screen: Media Contacts dialog in Universal Editor (every tab, including Additional)
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

10. Known limitations

- Universal Editor screenshots are placeholders: no author access in this program.

11. Open items

- None.

12. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages