TCS CORPORATE WEBSITE

Tab — Authoring Guide

Role / audience	Authoring — Content authors, content managers, AEM authoring leads
Version	1.0
Status	Draft for review
Owner	Content Lead / AEM Authoring Lead (proposed)
Last validated	2026-11-13
Documents	1
Classification	INTERNAL — classification to be confirmed

Generated from the Markdown sources of docs/handover (branch migrated-page-content-edam); do not edit this PDF.

Contents

Tab — Authoring Guide
- Where to see it
- For Content Authors
- Authorable Fields
- Screenshot-Based Authoring Steps
- Variations
- Complete Authoring Example
- Content and Asset Guidelines
- Troubleshooting
- Screenshots
- Known limitations
- Open items
- Change history

Tab — Authoring Guide

Attribute	Value
Document ID	AUT-C-tab
Audience	Content authors, content managers, AEM authoring leads
Purpose	How to add, fill in and check the Tab component
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	blocks/tab/README.md, blocks/tab/_tab.json
Related documents	—
Related AEM paths	—

1. Where to see it

No block library page.

2. For Content Authors

1. Select a Tabs Container in the content tree, choose Add (+) and pick **Tab** (the Tab is offered only there).
2. Open the Tab's properties. In **Content**, enter the **Title** (required: the tab label).
3. Optionally enter an **ID** (lower-case letters, digits and hyphens, e.g. `cloud`): links to `#cloud` open the tab. Leave it empty for an id made from the Tabs Container's Anchor name (`{anchor}-item-{n}`).
4. Turn on **Active tab** on the one tab that should be shown when the page loads (none: the first tab).
5. If the tab's content has Column Breaks, choose **Columns per row** (Automatic, 1, 2, 3, 4).
6. After the Tab, add the tab's components. Add the next Tab after them.
7. To move a tab, move the Tab and its components together; to remove a tab from the page temporarily, turn on **Hide block** in the **Additional** tab.
8. Preview: click the tab in the tab list; publish the page; on the published page check the label, the content and links to the ID.

Minimum required: Title. **Recommended:** an ID on tabs that are linked to. **Optional:** Active tab, Columns per row, Hide block.

3. Authorable Fields

Tab (`tab`)

Model `tab`; template name "Tab" (the block class AEM renders); key-value block (one row per property).

Content tab — Tab

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Title	`title`	text	Yes	—	—	The label of the tab. The components after this Tab, up to the next Tab, are its content.	Consulting
ID	`tabId`	text	No	—	regExp: ^#?[a-z0-9][a-z0-9-]*$; customErrorMsg: Lower-case letters, digits and hyphens, e.g. overview.	Links to #ID open this tab (deep link), e.g. overview (lowercase, no spaces). Leave empty for an id from the Tabs ID.	consulting
Active tab	`activeTab`	boolean	No	—	on / off	Shows this tab when the page loads (the first tab if no tab is active).	true
Columns per row	`classes_perrow`	select	No	""	Automatic (""), 1 (`per-row-1`), 2 (`per-row-2`), 3 (`per-row-3`), 4 (`per-row-4`)	When the tab's content has Column Breaks: how many columns sit side by side (Automatic: as many as there are Column Breaks, at most 4). Delivered as a block class.	per-row-2

Additional tab — Tab

Field label	Property	Type	Required	Default	Allowed values	Author guidance	Example
Hide block	`classes_hideblock`	boolean	No	`false`	on / off	Hides the tab and its content on the page (shown dimmed in the editor). Delivered as a block class.	—

Notes on the fields:

- **Title** (`title`): the tab button's text and the `dc:title` of the panel in the data layer; empty: "Tab {n}" (placeholder `tabNumber`, applied by the Tabs). Changing it in the editor updates the tab button at once (`tabs:tab-update`).
- **ID** (`tabId`): normalized with `toClassName` and used as the panel's `id` and `data-tab-id`; an id already on the page gets `-2`, `-3`. A link to `#id` (or the Anchor List) opens the tab and scrolls to it.
- **Active tab** (`activeTab`): only the value `true` counts; with several active Tabs the first wins; a `#hash` naming another tab wins over it.
- **Columns per row** (`classes_perrow`, block class `per-row-1` to `per-row-4`): applied to the columns the Tabs build from the tab's Column Breaks; Automatic: as many as there are Column Breaks, at most 4. No effect without Column Breaks.
- **Hide block** (`classes_hideblock`): the Additional tab has only this field (see AGENTS.md "Additional tab" for its general behavior). On a Tab it hides the tab button and its whole content on the page; in edit mode the tab stays and its chip is dimmed.
- **Legacy mapping:** `readTab` reads key-value rows (`title`, `tabid`, `activetab`) and, if none, one row per field in dialog order (the last cell of each row).
- **Template:** a new Tab stores no Title (the definition template has none), so an untouched Tab is labelled "Tab {n}".

4. Screenshot-Based Authoring Steps

Authoring Step 1: Add a Tab

```
[Screenshot Placeholder]

File name:
tab-authoring-step-1.png
```

```
Purpose:
The Add (+) menu of a selected Tabs Container with Tab highlighted, and the new Tab's dashed chip in the
panel.

Annotations:
A = Tabs Container selected in the content tree
B = Tab in the component list
C = New Tab chip
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Content tree	Tabs Container	The Tab is offered only in a Tabs Container	Add (+) lists Tab
B	Add (+)	Tab	Starts a new tab	A new tab button "Tab {n}" until a Title is entered

Author action: select the Tabs Container, add a Tab. Expected preview: a new tab button and, in edit mode, the chip. Published: the tab button. Business rule: the Tab is the first item of its tab. Validation: the new tab appears in the tab list. Common mistake: adding the components before the Tab; resolution: move them after it.

Authoring Step 2: Enter Title and ID

```
[Screenshot Placeholder]

File name:
tab-authoring-step-2.png

Purpose:
The Tab's Content tab with Title Consulting and ID consulting entered.

Annotations:
A = Title
B = ID
C = Tab button updated with the Title
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Title	Consulting	The tab label	Tab button "Consulting"
B	ID	consulting	Deep links (`#consulting`)	Panel id `consulting`

Author action: enter the Title and ID. Expected preview: the label updates at once; the ID applies after the container is rendered again (reload the editor). Published: `page#consulting` opens the tab. Business rule: IDs are lower case with hyphens (validated). Validation: inspect the panel id or follow the link. Common mistake: `#My Tab` in links; resolution: use the exact ID.

Authoring Step 3: Choose the tab shown first

```
[Screenshot Placeholder]

File name:
tab-authoring-step-3.png

Purpose:
```

```
Active tab turned on for the Cloud Tab, and the page loaded with Cloud selected.

Annotations:
A = Active tab toggle
B = Cloud selected on load
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Active tab	On	Show Cloud first	Cloud selected on load

Author action: turn on Active tab on one Tab only. Expected preview: after a reload, the tab is selected. Published: selected on a fresh load (without a `#hash`). Business rule: the first active Tab wins; the editor keeps the tab shown before a re-render. Validation: load the page without a hash. Common mistake: several Tabs active; resolution: leave one.

Authoring Step 4: Lay out the tab in columns

```
[Screenshot Placeholder]

File name:
tab-authoring-step-4.png

Purpose:
Columns per row 2 on the Tab, with two Column Breaks after it, and the resulting two columns.

Annotations:
A = Columns per row
B = First Column Break
C = Second Column Break
```

Values to Enter

Callout	Field	Value	Reason	Expected result
A	Columns per row	2	Two columns side by side	`per-row-2` on the columns in the panel
B / C	Column name (Column Break)	Image / Text	Editor labels	Labels in edit mode only

Author action: set Columns per row, add Column Breaks and their components after the Tab. Expected preview: two columns from 900px (after a reload for a changed Columns per row). Published: the same. Business rule: content between the Tab and the first Column Break stays above the columns. Validation: check at desktop and mobile widths. Common mistake: expecting Columns per row without Column Breaks to do anything; resolution: add Column Breaks.

5. Variations

Standard Tab

Title only (ID empty, Active tab off). Renders a tab button with the Title; the panel id is `{base}-item-{n}`. Use it for tabs nobody links to.

```
[Screenshot Placeholder]

File name:
tab-standard-mobile.png

Purpose:
```

```
A standard Tab at mobile width: its tab button in the scrolling tab list and its panel content stacked.

Annotations:
A = Tab button
B = Panel content
```

Active Tab

Active tab on: the tab shown when the page loads (unless a `#hash` or an editor re-render chooses another). Use it on one Tab at most.

Tab with ID (deep link)

ID set: the panel's id is the ID, so `#id` links and Anchor List links open the tab and scroll to it below the fixed header. Keep IDs identical across locales.

Tab with columns (Columns per row)

With Column Breaks in its content, the tab's content from the first Column Break is laid out by a Columns Container block in the panel with the chosen Columns per row; gap medium, top alignment, side by side from 900px. See Column Break.

Hidden Tab (Hide block)

Hide block on: the tab and its content are left out of the page (the group is dropped when not in edit mode); in edit mode the tab stays and its chip is dimmed, so the author can turn it off again.

6. Complete Authoring Example

Scenario: the Cloud tab of a services Tabs Container, linked from an email and shown first, with an image and a text side by side.

Field	Example value	Guidance
Title	Cloud	1 to 3 words, unique in the Tabs
ID	cloud	Lower case; the same in every locale
Active tab	On	Only this Tab
Columns per row	2	With two Column Breaks after the Tab
Hide block	Off	—

Steps: add the Tab after the Consulting tab's content (Step 1), enter Title and ID (Step 2), turn on Active tab (Step 3), add a Title "Cloud migration and operations", then Column Break, Image (with alt text), Column Break, Text (Step 4).

Expected output: the tab button "Cloud" selected on load; `#cloud` opens it. Responsive: the two columns stack below 900px. Accessibility: the button is a `role="tab"` named "Cloud", its panel labelled by it. Analytics: the panel is a `tcs-corp/components/tabs/item` named "Cloud"; showing it later pushes `cmp:show`. Personalization fallback: none.

Pre-publish checklist: Title entered; ID unique and used exactly in links; one Active tab in the container; the components sit after the Tab and before the next one.

7. Content and Asset Guidelines

- **Title:** short and descriptive (the handover recommends 1 to 3 words, about 25 characters); avoid "Tab 1" style labels; translate per locale.
- **ID:** lower-case letters, digits and hyphens (validated `^#?[a-z0-9][a-z0-9-]*$`); unique on the page.
- **Content:** start the tab's content with a heading that repeats or extends the Title.
- **Images, icons, CTAs, tags:** none on the Tab itself (they belong to the components after it).
- **Min / max:** no verified technical limit was identified.

8. Troubleshooting

Symptom	Likely cause	Diagnostic steps	Resolution	Verification
Label "Tab 2" instead of the Title	Empty Title, or content before the first Tab	Select the Tab; check the tree order	Enter the Title; move stray components	Labels are the Titles
Chip visible on the page	The Tab isn't in a Tabs Container	Check the section for `tabs-section`	Move or delete the Tab	No chip
ID doesn't work in links	Normalized or de-duplicated id	Inspect the panel id	Use the exact ID	Link opens the tab
Active tab ignored	Another active Tab, a #hash, or the editor keeps the shown tab	Load without hash; check all Tabs	One Active tab; reload	Correct tab on load
ID, Active, Columns per row or Hide block change has no effect in the editor	Applied when the container is rendered again (R-C-7)	Reload the editor	Reload	Applied
Component in the wrong tab	Its position in the tree	Check the tree order	Move it after its Tab	Correct panel

Evidence to collect: page URL, the Tab's data attributes (`data-tab-*`) and classes, the panel ids.

9. Screenshots

> **Screenshot required**
>
> - Required screen: Tab dialog in Universal Editor (every tab, including Additional)
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

10. Known limitations

- Universal Editor screenshots are placeholders: no author access in this program.

11. Open items

- None.

12. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages