TCS CORPORATE WEBSITE

Authoring Guide

Role / audience	Authoring — Content authors, content managers, AEM authoring leads
Version	1.0
Status	Draft for review
Owner	Content Lead / AEM Authoring Lead (proposed)
Last validated	2026-11-13
Documents	17
Classification	INTERNAL — classification to be confirmed

Generated from the Markdown sources of docs/handover (branch migrated-page-content-edam); do not edit this PDF.

Contents

Authoring Guide
- Where to author
- Systems an author uses
- The Universal Editor flow
- Creating and editing pages
- Adding and configuring blocks
- Containers and child items
- Previewing
- Publishing
- Corrective publishing
- Assets
- Links and CTAs
- Metadata
- Taxonomy
- Placeholders
- References: navigation, footer and 404
- Localization
- Accessibility responsibilities
- Analytics authoring fields
- Personalization fields
- Pre-publish checklist
- Post-publish validation
- Troubleshooting
- Related
- Screenshots
- Known limitations
- Open items
- Change history

Accessibility Authoring Guide
- Accessibility responsibilities
- Images, alt text and decorative images
- Links and buttons
- Responsibilities
- Screenshots
- Known limitations
- Open items
- Change history

Asset Authoring Guide
- Dynamic Media (KB-D-067)
- Assets
- Accessibility responsibilities
- Screenshots
- Known limitations
- Open items
- Change history

Authoring Checklist
- Pre-publish checklist
- Post-publish validation
- Screenshots
- Known limitations

- Open items
- Change history

Common Authoring Errors
- Troubleshooting
- Common Errors
- Screenshots
- Known limitations
- Open items
- Change history

Curated Design Page Authoring Guide
- Where they are
- Pages
- Screenshots
- Known limitations
- Open items
- Change history

Data Sheets Guide
- Data sheets
- Redirects
- Redirects sheet (8 November 2026)
- Screenshots
- Known limitations
- Open items
- Change history

Getting Started (authors)
- Access you need
- Where to author
- Systems an author uses
- The Universal Editor flow
- Screenshots
- Known limitations
- Open items
- Change history

Localization Guide
- The language master
- Site and locale hierarchy
- Localization
- Localization
- Screenshots
- Known limitations
- Open items
- Change history

Metadata Guide
- Bulk metadata columns
- Metadata model
- Metadata
- Screenshots
- Known limitations
- Open items
- Change history

Page Creation Guide
- Creating and editing pages
- Adding and configuring blocks

- Containers and child items
- Screenshots
- Known limitations
- Open items
- Change history

Page Properties Guide
- Page properties (model page-metadata)
- Metadata model
- Screenshots
- Known limitations
- Open items
- Change history

Placeholders Guide
- Placeholders
- Placeholders
- Screenshots
- Known limitations
- Open items
- Change history

Preview, Publish and Unpublish Guide
- Previewing
- Publishing
- Corrective publishing
- Publishing and the Admin API
- Screenshots
- Known limitations
- Open items
- Change history

SEO Authoring Guide
- Metadata model
- Screenshots
- Known limitations
- Open items
- Change history

Taxonomy and Tagging Guide
- Taxonomy
- Taxonomy
- Screenshots
- Known limitations
- Open items
- Change history

Versioning and Rollback Guide
- Versions in AEM Sites
- Rollback
- Screenshots
- Known limitations
- Open items
- Change history

Authoring Guide

Attribute	Value
Document ID	AUT-000
Audience	Content authors, content managers, AEM authoring leads
Purpose	Step-by-step guide for a new content author: systems, pages, blocks, assets, metadata, publishing and checks
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	docs/handover/knowledge-base/authoring.md
Related documents	—
Related AEM paths	/content/tcs-corp/language-master/en, /content/tcs-corp/language-masters/en, /content/tcs-corp/design-block-master/en

1. Where to author

Tree (AEM Sites)	Use it for
/content/tcs-corp/language-masters/en	The real language master content (the migrated tcs.com pages) and its sheets; validated before it becomes the global site and the regions
/content/tcs-corp/language-master/en	Testing page functionality with dummy content and content limitations
/content/tcs-corp/design-block-master/en	The block library (every block and variation) and the curated design pages
/content/tcs-corp/<country>/<language>	The 13 locale sites (/en, /de-de, ...)

2. Systems an author uses

System	Purpose	Notes
AEM as a Cloud Service author, Sites console	Browse `/content/tcs-corp`, create, copy, move, publish, unpublish, page versions	Host and program ids are not repeated here; ask the AEM administrator
Universal Editor	Visual editing: canvas, Content tree, Properties panel	Opened from the Sites console with **Edit**
AEM Assets	Images and documents under `/content/dam/tcs-corp/`	`/content/dam/tcs-corp/` is in the `includes` of paths.json
Preview site	`https://main--tcs-corp--sradha-tcs.aem.page/{locale}/…`	Content published to preview
Live site	`https://main--tcs-corp--sradha-tcs.aem.live/{locale}/…`	Production origin; production domain and CDN: Not recorded

System	Purpose	Notes
AEM Sidekick (optional)	Preview / live status and switching on the Edge Delivery hosts	tools/sidekick/config.json labels the edit link "AEM Editor"

Access and permissions: AEM user groups, permissions per locale and a publish approval workflow are not part of the repository and are not recorded (handover Part 5, 5.1.2, "To be confirmed"; open item O-06). See administration-and-operations.md.

3. The Universal Editor flow



- Edits save automatically. After each change scripts/editor-support.js re-decorates only the changed block, section or default content; when it can't, the canvas reloads (expected).
- **Edit mode** (`html.adobe-ue-edit`, `isEditing()` in utils/environment.js): clicks select components; blocks with Hide block are shown faded with a dashed outline; animations don't play and aren't used up; List, Cards, Filter List and new items show editor hints and placeholders (decorators/editor-item-decorator.js).
- **Preview mode** and the published site: links work, hidden blocks are gone, animations and carousels run.
- On AEM author there is no query index: Lists from child pages or tags and Filter Lists say their pages show on the published page; sheets (placeholders, taxonomy) may not resolve, so the editor can show English fallbacks and ID-derived tag labels. Validate those on `aem.page` (handover Part 14, Known Limitations #18).
- Device sizes: check mobile (below 600 px), tablet (600–1199 px) and desktop (1200 px and above), the breakpoints of AGENTS.md.

4. Creating and editing pages

Where pages live

The 13 locale sites and their published paths are listed in AGENTS.md and defined in `LOCALES` of utils/site.js.

Location (below `/content/tcs-corp/{country}/{language}`)	Contents	Published
The locale page itself	The locale's Home page	Yes, at `/{locale}/`
Content pages below it	All content pages	Yes
`references/`	Navigation (`nav`), `footer`, other fragments	Yes (read by other pages)
`error-pages/`	`404` (used by the site); `403` / `500` (for a CDN, not used by code)	Yes
`block-library/`	Every block variation in the locale's language	No (excludes of paths.json)
`/content/tcs-corp/site-global-templates/`	Template pages to copy (home, article, blog, press release)	No

Creating a page

1. In the Sites console copy the template page from `site-global-templates` and paste it into the locale folder; rename it (the page name becomes the URL segment). For pages without a template use **Create > Page** (the AEM page template offered there is not recorded).
2. Open it with **Edit**, set the page properties, edit the content, then preview and publish.

3. Values that aren't page properties (author, dates, reading time, region, images, card values, SEO and social columns) come from the locale's bulk metadata sheet (see Metadata).

Walkthrough: handover Part 5, 5.3, and the cheat sheet in Part 15, 15.5.1.

Page properties

The page model is `page-metadata` in models/_page.json:

Field	Name	Notes
Title	`jcr:title`	Browser, SEO and social title; Page Header heading; card title fallback
Description	`jcr:description`	Meta description; Page Header description; card description fallback
Keywords	`keywords`	Meta keywords
Page Type	`page-type`	Default, Home, Article, Blog, Press Release: loads `templates/{name}/` (templates/README.md); overrides the sheet's `page-type`
Navigation	`nav`	Inherited (see References)
Footer	`footer`	Inherited
404 Page	`error-page`	Inherited

`TEMPLATES` in scripts/scripts.js is `home`, `article`, `blog`, `press-release`; another value loads no template code but is still added as a body class.

Sections

A section is a band of the page with default content and blocks. Its fields (Section Name, Style Default / Grey / Dark / Dark Green, Width Type, Rounded edge, Background Image and its alt text, Anchor name) are in models/_section.json; the backgrounds and the dark theme contract are described in AGENTS.md ("Backgrounds and theme"). Sections don't get `classes_*` fields delivered, so a section has no Additional tab; the container sections use `container*` fields instead.

5. Adding and configuring blocks

Where components can be added

What the **Add (+)** picker offers is defined by the filters in component-filters.json (aggregated from models/_component-filters.json, models/_section.json and each block's `_<block>.json`):

Container	Allowed components
Main (the page)	Section, Gen Carousel, Tabs Container, Columns Container
Section	Text, Image, Button (Button Block), Title, Page Header, Hero, Teaser, Quote, Testimonial, Anchor List, Accordion, Tabs (block), Table, Table List, List, Separator, Embed, Video, Modal, Form Variations, Filter List, Conversation Canvas, Cards, Fragment, Footer, TCS Header
Columns Container	Column Break, then the Section's components except Page Header, Footer and TCS Header
Tabs Container	Tab, Column Break, then the Section's components except Page Header, Conversation Canvas, Footer and TCS Header

Container	Allowed components
Gen Carousel	Hero, Teaser

The item filters of each block (Accordion Item, Card, List Item, CTA, Link, Stat, form fields, Table rows, ...) are listed in blocks/README.md. Not offered in any filter: the built-in Columns (compatibility only), the built-in Button ("Button (basic)"), and Interactive Dashboard (placeholder) (blocks/README.md).

Block reference

Each block README holds the dialog fields per tab (generated from the models), the variations, authoring steps, accessibility, data layer and troubleshooting. Don't repeat fields elsewhere; read them there.

Block	README	Added in	Status
Accordion	accordion	Section, Columns Container, Tabs Container	Active
Anchor List	anchor-list	Section, Columns Container, Tabs Container	Active
Button (Button Block)	button-block	Section, Columns Container, Tabs Container	Active
Cards	cards	Section, Columns Container, Tabs Container	Active
Column Break	column-break	Columns Container, Tabs Container	Active
Columns (built-in)	columns	None (no longer offered)	Compatibility-only
Columns Container	columns-container	Main (page)	Active
Conversation Canvas	conversation-canvas	Section, Columns Container	Active
Embed	embed	Section, Columns Container, Tabs Container	Active
Filter List	filter-list	Section, Columns Container, Tabs Container	Active
Footer	footer	Section (on the footer reference page)	Active
Form Variations	form-variations	Section, Columns Container, Tabs Container	Active
Fragment	fragment	Section, Columns Container, Tabs Container	Active
Gen Carousel	gen-carousel	Main (page)	Active
Header	header	Not a component: built from the nav page	Active
Hero	hero	Section, Columns Container, Tabs Container, Gen Carousel	Active
Interactive Dashboard	interactive-dashboard	None	Experimental
List	list	Section, Columns Container, Tabs Container	Active
Modal	modal	Section, Columns Container, Tabs Container	Active
Page Header	page-header	Section	Active
Quote	quote	Section, Columns Container, Tabs Container	Active
Separator	separator	Section, Columns Container, Tabs Container	Active
Tab	tab	Tabs Container	Active
Table	table	Section, Columns Container, Tabs Container	Active
Table List	table-list	Section, Columns Container, Tabs Container	Active
Tabs Container and Tabs (block)	tabs	Main (container); Section, Columns Container, Tabs Container (block)	Active
TCS Header	tcs-header	Section (on the nav page)	Active

Block	README	Added in	Status
Teaser	teaser	Section, Columns Container, Tabs Container, Gen Carousel	Active
Testimonial	testimonial	Section, Columns Container, Tabs Container	Active
Video	video	Section, Columns Container, Tabs Container	Active

Default content (Text, Title, Image) uses AEM's built-in components (handover Part 6, chapters 6.6 to 6.8).

The Additional tab

Every block model except the header and footer ends with an **Additional** tab (rules in AGENTS.md, "Additional tab" and "Animation and skeletons"):

Field	Name	Effect
Anchor ID	`classes_anchor`	Must match `anchor-…` (lower case, digits, hyphens); becomes the block's `id` (decorators/block-options-decorator.js), de-duplicated as `-2`, `-3`; also the block's data layer id
Hide block	`classes_hideblock`	Hidden on the site and in Preview; faded in edit mode; the content stays in the delivered HTML (not an embargo mechanism)
Padding / Margin Left, Right, Top, Bottom	`classes_padding*`, `classes_margin*`	`--space-*` tokens, the same at every breakpoint
Animation Type, Motion Speed, Animation Trigger	`classes_animation*`	Content animation on 19 blocks; never in edit mode or for reduced motion (docs/animation/README.md)
Background animation	`classes_bganimation`	Hero, Teaser, Quote, Testimonial, Form Variations, Conversation Canvas

Container sections (Columns Container, Tabs Container, Gen Carousel) carry the same options as `container*` fields (`containerAnchor`, `containerHide`, …), applied by `applySectionBlockOptions` in scripts/scripts.js.

6. Containers and child items

- **Section containers** are added at page level (Main): a Columns Container holds Column Breaks and the components of each column; a Tabs Container holds Tabs (and Column Breaks inside a tab: a section can't hold a section); a Gen Carousel holds Heroes and Teasers as slides. `scripts.js` wraps each in a synthetic block.
- **Column Break** (README) starts a column: the components after it belong to that column. In a Tab, content before the first Column Break stays above the columns; the Tab's **Columns per row** sets the layout.
- **Item children**: repeating content is added to the block with **Add (+)**, not with composite multifields: List Items, Cards, Hero and Page Header CTAs, Teaser Links and Stats, Testimonial Stats, Anchor Links, Filter List tags / categories / pages, Footer Links, form fields, Table rows, Canvas buttons (AGENTS.md, "Item children"). The multifields authored before are still read but don't render from content packages (handover finding F-87).
- An item without content yet is a dashed placeholder in the editor (placeholder key `itemEditorHint`).
- Universal Editor collapses a dialog's tabs into a dropdown when they don't fit; models keep at most three tabs, the last one Additional.
- Built-in **Columns** and **Button (basic)** authored before stay editable but aren't offered; use a Columns Container and the Button block.

7. Previewing

1. Switch the Universal Editor to **Preview** and check the three device sizes: no editor hints left, hidden blocks gone, animations play.

2. Publish to the preview tier and open `https://main--tcs-corp--sradha-tcs.aem.page/{locale}/{path}`; Lists, Filter Lists, placeholders and taxonomy labels only resolve there (not on author).
3. Use a private window or a cache-busting query to bypass the browser cache.

Which publish destinations the Universal Editor offers in this program (Preview and / or Live) is not recorded (handover Part 5, 5.7.2).

8. Publishing

Task	Where	Verify
One page	Universal Editor **Publish** (keep changed references selected)	Live URL in a private window
Several pages or a branch	Sites console **Manage Publication** (include children; schedule Later)	Sample URLs, `/query-index.json`
Quick publish	Sites console **Quick Publish**	Live URL
A sheet or data sheet	Select the sheet, **Quick Publish**	`/{locale}/{sheet}.json`
Take down	**Manage Publication > Unpublish** (add a redirect first if the URL was public)	The locale's 404 page
Undo a change	**Timeline > Revert to this Version**, then publish	Live URL

Published separately. A change to these items only takes effect when the item itself is published: `references/` pages (nav, footer, fragments), error pages, the sheets (`placeholders`, `metadata`, `taxonomy`, `redirects`), the data sheets (`data/authors`, `locations`, `partners`, `social-links`, `media-contacts`) and assets. A published nav, footer or fragment change shows on every page that loads it without republishing those pages.

Order when content depends on new code or data. Code first (merged and synced), then sheets (placeholders, taxonomy, data, metadata), then fragments (nav, footer), then pages (handover Part 12, 12.4.2).

Pages under `block-library/` and `site-global-templates/` can't be published (`excludes` of paths.json); during the language master review its block library is published for the review (handover revision 2.20).

9. Corrective publishing

Re-publication after a correction is the verified recovery path, recorded in the handover revision history:

- Package 1.0.9 was published; on `aem.live` the container sections' Additional tab had no effect (re-audit finding R-L-1). The code was corrected (PR #121), package 1.0.10 installed, and its 312 pages previewed, published and reindexed (312 / 312) (handover revisions 2.30, 2.31; REAUDIT-2026-10-20.md).
- Package 1.0.12: one page timed out on its first preview and went through on retry (handover revision 2.35).

For one page: fix the content (or restore a version), check it in Preview mode, publish to preview, verify, then publish to live. If a correction is not visible, check that the referenced item (fragment, sheet, asset) was published too, then escalate to L1 (Admin API status, re-preview and cache operations are for administrators; see administration-and-operations.md).

10. Assets

- Images and documents live in AEM Assets under `/content/dam/tcs-corp/`; image fields (`reference`) open the Assets picker.

- **Images travel with the page**: on publish, Edge Delivery copies each referenced image to the media bus (`media_…` URLs) and serves responsive renditions. The first image of the first section loads eagerly (LCP), the others lazily.
- **Non-image DAM files** (Lottie `.json`, videos, WebVTT captions, PDFs) are served only once they are published themselves; until then they return 404 on `aem.page` (AGENTS.md, "AEM delivery rules"; re-audit operations R-B-2, R-D-6). Publish them from AEM Assets.
- A non-image reference is delivered as a link whose text is its **Alt**: fill the Alt field of Lottie and other file references (`animationLabel` in utils/media.js).
- Alt text: describe informative images; leave it empty only for decorative images (the code then sets `alt=""`); don't put text inside images. Rules and image guidance: handover Part 5, 5.5.
- Image licensing rules and the DAM folder convention per locale are not recorded.

11. Links and CTAs

- Buttons authors add are **Button** blocks (`button-block`: Link, View, Type `buttonVariant`, Icon, Alignment); see blocks/button-block/README.md and AGENTS.md ("Button").
- In default content, a standalone link in its own paragraph becomes a button: bold / italic (or a Type) gives a button, otherwise a link button; inline links stay links (decorators/content-buttons-decorator.js).
- CTAs of Hero, Page Header and Teaser are item children (CTA, Link); see each block README.
- Link to published paths (`/en/...`), not `/content/tcs-corp/...`. Links set to open in a new tab are announced to screen readers (placeholder `opensInNewTab`).
- Anchors: a section's **Anchor name** (normalised to lower case with hyphens) or a block's **Anchor ID** (`anchor-…`), linked as `#…`; the `tabs:reveal` event opens the tab holding a deep-link target.
- The per-locale `redirects` sheet is not applied by the platform; the List links its cards to the redirect targets (utils/redirects.js). Add a redirect row before moving or unpublishing a public page, but a mechanism that applies it is not configured (see administration-and-operations.md).

12. Metadata

Source	What it sets	Notes
Page properties	Title, Description, Keywords, Page Type, Navigation, Footer, 404 Page	models/_page.json
Bulk metadata sheet `{locale}/metadata`	Every other page-level value: `author-id`, `publish-date`, `reading-time`, `region`, `content-type`, `featured-image`, card values (`card-title`, `card-style`, …), SEO and social columns	Column list in AGENTS.md; URL patterns must start with the locale (`/de-de/**`)

The bulk sheets apply only once the administrator lists all 13 in the site configuration's `metadata.source`; whether that is done is not recorded (handover open item O-04). The Page Header takes all its content from metadata (only its Layout and CTAs are authored). Republish a page after its card values changed so the query index row updates. Field reference: handover Part 8 — Metadata Documentation.

13. Taxonomy

- Tags are AEM tags (`tcs-corp:` namespace) set in page properties and in block tag fields (Teaser, Cards, List Items, List, Filter List).
- Labels come from the locale's taxonomy page (`/{locale}/taxonomy.json`; a language sheet such as `de` when translated) through utils/taxonomy.js; a tag missing there shows a label derived from its ID.
- Publish the taxonomy page after a change; Lists and Filter Lists match tags from the query index, so republish pages after re-tagging. Governance: handover Part 7 — Taxonomy Documentation.

14. Placeholders

All UI text of the blocks (button labels, ARIA labels, editor hints) comes from the locale's `placeholders` sheet (Key, Text; Description and Category are for authors) through utils/placeholders.js. Keys match without case or separators; a missing key shows the code's English fallback (not the `/en` sheet's text). Keep `{n}`, `{total}`, `{title}` and similar variables. The key list is in handover Part 4, 4.5 and Part 14, 14.8.3.

15. References: navigation, footer and 404

Value	Resolution (first match wins)
Navigation (`nav`)	The page's own value (page property or the sheet's `nav`), else the nearest parent page's up to the locale Home, else `{locale}/references/nav`
Footer (`footer`)	The same chain, else `{locale}/references/footer`
404 Page (`error-page`)	The same chain, else `/{locale}/error-pages/404`, else `/en/error-pages/404`, else the built-in content

Implemented by `getInheritedMetadata` in utils/inherited-metadata.js and `resolvePagePath` / `getParentPages` in utils/site.js. Leave the three fields empty on ordinary pages; set them on the top page of a sub-site. Values may be AEM paths, published paths or paths relative to the locale root (`references/nav-careers`). Inherited values are cached per browser session (`sessionStorage` key `tcs-inherited-metadata`): check a change in a new private window. Header and footer authoring: blocks/header/README.md, blocks/tcs-header/README.md, blocks/footer/README.md.

16. Localization

- Each of the 13 locales is a separate page tree with its own references, error pages, sheets, data and block library; locales share no content. Link only to the locale's own references and sheets.
- The page language (`<html lang>`) is the page's `language` metadata when valid, else the locale's tag (decorators/seo-decorator.js).
- Creating a locale's content, translation projects, MSM live copies, a language switcher and `hreflang` are not implemented in code; the translation process is not recorded (handover Part 4, 4.9.6; open item O-12).
- Month abbreviations in formatted dates are English in every locale; prefer the numeric date formats where a block offers a choice (handover 4.9.7).
- Temporary: pages below `/language-masters/en` read the language master's own references, sheets and index rows until its rollout to `/en` (`REVIEW_*` in utils/site.js).

17. Accessibility responsibilities

The code implements WCAG 2.1 AA behaviour (AGENTS.md, "Accessibility"); authors are responsible for the content:

- One `h1` per page (Page Header, a Hero with H1 or a Title h1) and heading levels in order; don't choose a level for its size.
- Alt text for every informative image and every Lottie / file reference; empty only for decorative images.
- Meaningful link and button text (not "click here"); the Accessibility label fields of List Items and Cards where the visible text isn't enough.
- Captions for videos with speech (WebVTT, published as an asset).
- Don't rely on colour alone; use the Section Style and BG Color options, which keep the theme contrast.
- Use animations sparingly (one or two effects per page); reduced motion is honoured by the code.

18. Analytics authoring fields

Every block is in the Adobe Client Data Layer (`window.adobeDataLayer`), populated centrally by decorators/data-layer-decorator.js. Adobe Tags and the AEP Web SDK are not configured (blocked: measurement plan), so nothing is collected yet.

Field	Where	Effect
Anchor ID (`classes_anchor`)	Additional tab of every block	The block's `id` and its data layer component id: renaming it changes the analytics id
Analytics (`analyticsEnabled`)	List, Cards (default on), Separator (default off)	On: component state and card events in the data layer; off: `data-analytics="off"`
Analytics label (`analyticsLabel`)	List Item, Card, Separator	`data-analytics-label` and the data layer `dc:title` (else the title)
Component ID (`componentId`)	Separator	Its own id

Keep personal data out of Anchor IDs, Component IDs and analytics labels. Event details: handover Part 11 — Analytics & Data Layer, and each block README's Data Layer section.

19. Personalization fields

None. No verified personalization field exists in the models; the Teaser's Personalization option (a marker nothing read) was removed in the block audit (D-B-3). No Adobe Target, AJO or CJA integration exists; every block renders its authored default content.

20. Pre-publish checklist

- ☐ Title and Description set; Page Type correct; Navigation, Footer and 404 Page empty unless the page needs its own.
- ☐ One `h1`; headings in order.
- ☐ Alt text on informative images and file references; decorative images empty.
- ☐ Links point to published paths and to pages that are published; new-tab links only where needed.
- ☐ No block unintentionally hidden (faded blocks in edit mode); no confidential content anywhere on the page.
- ☐ Anchor IDs start with `anchor-` and are used once per page.
- ☐ Checked in Preview mode at mobile, tablet and desktop.
- ☐ Referenced fragments, sheets and non-image assets are published or selected in the Publish dialog.
- ☐ New placeholder keys and tags exist in the locale's sheets.
- ☐ Bulk metadata rows cover the page (URL pattern starts with the locale).

21. Post-publish validation

- ☐ The live URL in a private window shows the change, with the locale's header and footer.
- ☐ Lists and Filter Lists that should show the page list it (after a few minutes) and `/query-index.json` has its row.
- ☐ UI labels are translated (locale `placeholders.json` published) and tags show titles.
- ☐ Lottie, video and caption files load (published assets).
- ☐ The page head has the expected `description`, `page-type` and tags.

This is the author definition of done V-01 of handover Part 17 — Operations Guide.

22. Troubleshooting

Symptom	Likely cause	Handover chapter (Part 13 — Global Troubleshooting Guide)
Page not updated after publish	Published to preview only, reference not published, browser cache	13.2
Dialog fields missing or outdated	Editor not reloaded after a code release	13.5
Wrong header or footer	Inherited Navigation / Footer value; session cache	13.6
English or built-in 404 in a locale	Locale 404 page not published	13.7
Page missing from List / Filter List	Not published, excluded, `hide-in-nav`, filters	13.9, 13.11
List or Filter List empty in the editor	No query index on author (expected)	13.10
UI text in English	Key missing or sheet not published	13.13
Tag shows an ID-like label	Taxonomy title missing or not published	13.14
Bulk metadata ignored	`metadata.source` not configured or pattern wrong	13.17
Block missing on the site	Hide block on	13.18
Anchor link doesn't jump	Missing `anchor-` prefix or duplicate id	13.19
Lottie, video or captions 404	Non-image asset not published	13.30 and REAUDIT-2026-10-20.md
Fragment, modal or tab content missing	Fragment not published	13.31

Escalate to L1 with the AEM and published path, locale, steps, screenshot and time (handover Part 14, 14.5).

23. Related

- administration-and-operations.md and deployment-and-release.md
- blocks.md, content-architecture.md, indexing-and-search.md, data-layer-and-analytics.md, personalization.md, design-system.md
- blocks/README.md and each block README
- AGENTS.md: AEM delivery rules, Additional tab, item children, site structure and site data
- docs/animation/README.md, templates/README.md
- Handover (TCS-CORP-HANDOVER.md): Part 5 — Authoring Fundamentals, Part 6 — Component Library, Part 7 — Taxonomy, Part 8 — Metadata, Part 9 — Data Sheets, Part 15 — Appendix (15.5 Authoring Cheat Sheets), Part 18 — New Joiner Training Guide
- docs/audit/README.md: block audit and re-audit

24. Screenshots

> **Screenshot required**
>
> - Required screen: Authoring Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor

- Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
- Owner: Content Lead / AEM Authoring Lead (proposed)
- Target completion date: To be confirmed

25. Known limitations

- None recorded for this document.

26. Open items

- None.

27. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Accessibility Authoring Guide

Attribute	Value
Document ID	AUT-016
Audience	Content authors, content managers, AEM authoring leads
Purpose	What authors must do for accessibility
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	—
Related documents	—
Related AEM paths	—

1. Accessibility responsibilities

The code implements WCAG 2.1 AA behaviour (AGENTS.md, "Accessibility"); authors are responsible for the content:

- One `h1` per page (Page Header, a Hero with H1 or a Title h1) and heading levels in order; don't choose a level for its size.
- Alt text for every informative image and every Lottie / file reference; empty only for decorative images.
- Meaningful link and button text (not "click here"); the Accessibility label fields of List Items and Cards where the visible text isn't enough.
- Captions for videos with speech (WebVTT, published as an asset).
- Don't rely on colour alone; use the Section Style and BG Color options, which keep the theme contrast.
- Use animations sparingly (one or two effects per page); reduced motion is honoured by the code.

2. Images, alt text and decorative images

- Image fields have alt text fields; an empty alt marks the image as decorative (`alt=""`). Section backgrounds have their own alt field (`backgroundimagealt`) and default to decorative (`buildSectionBackground` in `scripts/scripts.js`).
- Authored icons are `img` with an empty alt (`decorateIcons` in `scripts/aem.js`); button arrows and list arrows are CSS masks, not content.
- Lottie animations: `role="img"` with the label, or `aria-hidden` without one; a non-image reference's link text is its Alt (`animationLabel`, `utils/media.js`; AGENTS.md "AEM delivery rules").
- Background videos are `aria-hidden` and their iframe has `tabindex="-1"`.
- Text over images (Hero, Teaser Background image / Card) relies on overlays; axe can't judge text over images, so the re-audit tested them in targeted browser checks (re-audit, section 2).

3. Links and buttons

- Actions are `<button>` elements; navigation is `<a href>`. Every button and link button goes through the button decorators (`decorators/button-decorator.js`, `icon-button-decorator.js`, `content-buttons-decorator.js`).
- **New tab**: `setLinkTarget` sets `target="_blank"` and `rel="noopener noreferrer"`; `announceNewTab(a, hint)` adds visually hidden text, or extends an existing `aria-label`, with the `opensInNewTab` placeholder (WCAG 3.2.5 practice). Used by the button decorator, card lists, Teaser, Page Header and Footer; social links add the hint to their hidden label. **Open**: the article author bio's "View LinkedIn profile" link opens a new tab without the hint (`decorators/author-bio-decorator.js`; handover F-52).
- Links in running text are underlined on dark backgrounds so they are not told apart by colour alone (theme contract).
- Disabled buttons use `aria-disabled="true"` or `:disabled`.

4. Responsibilities

Role	Responsibilities
Content authors	Write meaningful alt text, or leave it empty only for decorative images; choose heading levels in a logical order (one H1 per page, from the Page Header or the first Title); write link and button text that makes sense out of context; add captions / transcripts to videos; don't put information only in an animation, image or colour; check pages in the block library's language; keep placeholders translated
Developers	Use semantic elements and the shared decorators (buttons, links, headings, `announceNewTab`, `hideVisually`); keep all UI text in placeholders with an English fallback; keyboard support (Tab, Shift+Tab, Enter, Space, Escape, arrows, Home / End where the pattern needs it); visible focus; pause controls for moving content; reduced motion; semantic tokens for text colours so the theme contract applies; update the block README's Accessibility section
Designers	Provide colours that pass 4.5:1 (text) and 3:1 (non-text, focus) on every background, including the dark bands; sign off the contrast token change (audit); define focus, hover, disabled and error states; keep targets at least 1.5rem (24px, WCAG 2.5.8); design dark and Grey island combinations
QA	Run the axe harness at 1440 and 390px on the block library and curated pages; keyboard-test each changed block; check reduced motion, 200% zoom and 320px reflow; screen-reader runs when available; record results with the test vocabulary (Passed, Failed, Corrected and passed, Blocked, Not applicable)
Site administrators	Keep the placeholders (`/{locale}/placeholders.json`) complete per locale, including the accessibility strings (`opensInNewTab`, `pauseAnimation`, `playAnimation`, slide labels); publish error pages per locale; keep `<html lang>`-relevant metadata (language) correct
AI agents	Follow AGENTS.md "Accessibility" and this page; never claim a test that wasn't run; use `announceNewTab`, placeholders and the button decorators instead of re-implementing them; check new blocks inside the dark theme contract; record gaps as "Not recorded" or "Blocked"

5. Screenshots

> **Screenshot required**
>
> - Required screen: Accessibility Authoring Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

6. Known limitations

- None recorded for this document.

7. Open items

- None.

8. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Asset Authoring Guide

Attribute	Value
Document ID	AUT-007
Audience	Content authors, content managers, AEM authoring leads
Purpose	Adding assets, alt text, and the Dynamic Media decision
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	docs/handover/knowledge-base/authoring.md
Related documents	—
Related AEM paths	—

1. Dynamic Media (KB-D-067)

The assets are in the Sites author's DAM (`/content/dam/tcs-corp`). Dynamic Media with OpenAPI delivers **approved** assets; the migrated pages below `/language-masters/en` reference them by delivery URL once rebuilt. Authors will pick assets with the Dynamic Media asset picker after the administrator set-up (pull request #200, not merged yet); until then the image fields keep the standard asset picker.

2. Assets

- Images and documents live in AEM Assets under `/content/dam/tcs-corp/`; image fields (`reference`) open the Assets picker.
- **Images travel with the page**: on publish, Edge Delivery copies each referenced image to the media bus (`media_…` URLs) and serves responsive renditions. The first image of the first section loads eagerly (LCP), the others lazily.
- **Non-image DAM files** (Lottie `.json`, videos, WebVTT captions, PDFs) are served only once they are published themselves; until then they return 404 on `aem.page` (AGENTS.md, "AEM delivery rules"; re-audit operations R-B-2, R-D-6). Publish them from AEM Assets.
- A non-image reference is delivered as a link whose text is its **Alt**: fill the Alt field of Lottie and other file references (`animationLabel` in utils/media.js).
- Alt text: describe informative images; leave it empty only for decorative images (the code then sets `alt=""`); don't put text inside images. Rules and image guidance: handover Part 5, 5.5.
- Image licensing rules and the DAM folder convention per locale are not recorded.

3. Accessibility responsibilities

The code implements WCAG 2.1 AA behaviour (AGENTS.md, "Accessibility"); authors are responsible for the content:

- One `h1` per page (Page Header, a Hero with H1 or a Title h1) and heading levels in order; don't choose a level for its size.
- Alt text for every informative image and every Lottie / file reference; empty only for decorative images.
- Meaningful link and button text (not "click here"); the Accessibility label fields of List Items and Cards where the visible text isn't enough.
- Captions for videos with speech (WebVTT, published as an asset).
- Don't rely on colour alone; use the Section Style and BG Color options, which keep the theme contrast.
- Use animations sparingly (one or two effects per page); reduced motion is honoured by the code.

4. Screenshots

> **Screenshot required**
>
> - Required screen: Asset Authoring Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

5. Known limitations

- None recorded for this document.

6. Open items

- None.

7. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Authoring Checklist

Attribute	Value
Document ID	AUT-017
Audience	Content authors, content managers, AEM authoring leads
Purpose	Pre-publish and post-publish checks
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	—
Related documents	—
Related AEM paths	—

1. Pre-publish checklist

- ☐ Title and Description set; Page Type correct; Navigation, Footer and 404 Page empty unless the page needs its own.
- ☐ One `h1`; headings in order.
- ☐ Alt text on informative images and file references; decorative images empty.
- ☐ Links point to published paths and to pages that are published; new-tab links only where needed.
- ☐ No block unintentionally hidden (faded blocks in edit mode); no confidential content anywhere on the page.
- ☐ Anchor IDs start with `anchor-` and are used once per page.
- ☐ Checked in Preview mode at mobile, tablet and desktop.
- ☐ Referenced fragments, sheets and non-image assets are published or selected in the Publish dialog.
- ☐ New placeholder keys and tags exist in the locale's sheets.
- ☐ Bulk metadata rows cover the page (URL pattern starts with the locale).

2. Post-publish validation

- ☐ The live URL in a private window shows the change, with the locale's header and footer.
- ☐ Lists and Filter Lists that should show the page list it (after a few minutes) and `/query-index.json` has its row.
- ☐ UI labels are translated (locale `placeholders.json` published) and tags show titles.
- ☐ Lottie, video and caption files load (published assets).
- ☐ The page head has the expected `description`, `page-type` and tags.

This is the author definition of done V-01 of handover Part 17 — Operations Guide.

3. Screenshots

> **Screenshot required**
>
> - Required screen: Authoring Checklist
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Common Authoring Errors

Attribute	Value
Document ID	AUT-018
Audience	Content authors, content managers, AEM authoring leads
Purpose	Frequent authoring mistakes and how to recover
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	—
Related documents	—
Related AEM paths	—

1. Troubleshooting

Symptom	Likely cause	Handover chapter (Part 13 — Global Troubleshooting Guide)
Page not updated after publish	Published to preview only, reference not published, browser cache	13.2
Dialog fields missing or outdated	Editor not reloaded after a code release	13.5
Wrong header or footer	Inherited Navigation / Footer value; session cache	13.6
English or built-in 404 in a locale	Locale 404 page not published	13.7
Page missing from List / Filter List	Not published, excluded, `hide-in-nav`, filters	13.9, 13.11
List or Filter List empty in the editor	No query index on author (expected)	13.10
UI text in English	Key missing or sheet not published	13.13
Tag shows an ID-like label	Taxonomy title missing or not published	13.14
Bulk metadata ignored	`metadata.source` not configured or pattern wrong	13.17
Block missing on the site	Hide block on	13.18
Anchor link doesn't jump	Missing `anchor-` prefix or duplicate id	13.19
Lottie, video or captions 404	Non-image asset not published	13.30 and REAUDIT-2026-10-20.md
Fragment, modal or tab content missing	Fragment not published	13.31

Escalate to L1 with the AEM and published path, locale, steps, screenshot and time (handover Part 14, 14.5).

2. Common Errors

Symptom	Cause	Fix
Dialog field missing or outdated in Universal Editor	`component-*.json` not rebuilt or not deployed	`npm run build:json`, commit, wait for code sync (handover 13.5)
Value saved but not on the page	Collapse suffix, grouped field in a key-value block, or `classes_*` on a section	Rename per the delivery rules; keep reading the old name
Block renders empty or shifted on aem.page but fine locally	An empty tab row or tab cell read as content; item first cell `<name>, <classes>`	Skip tab rows / cells (`withoutTabCells`), read by model
Every new item shows the same text	Sample text in the template or model default	Empty the template; use placeholders for UI text
`max-cells` lint error	Too many cells in a non key-value model	Make the block key-value, group or fold fields, or raise the limit with a reason in `.eslintrc.js`
Block class wrong or block code not loaded	Template name doesn't match the folder	Fix the template name (`test/models/block-names.test.mjs`)
Key lower-cased	Item name delivered in class-name form	A dedicated field (`fieldName`)

3. Screenshots

> **Screenshot required**
>
> - Required screen: Common Authoring Errors
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Curated Design Page Authoring Guide

Attribute	Value
Document ID	AUT-006
Audience	Content authors, content managers, AEM authoring leads
Purpose	Using the curated design pages as references when building pages
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	—
Related documents	—
Related AEM paths	/content/tcs-corp/design-block-master/en/curated-design-pages

1. Where they are

`/content/tcs-corp/design-block-master/en/curated-design-pages` (published at /design-block-master/en/curated-design-pages/). Each shows a page design of Figma built from the blocks; copy the composition, not the dummy content.

2. Pages

Page	Blocks in order	Live
case-study	page-header → anchor-list → video → teaser → video → table-list → teaser → teaser → teaser → teaser → teaser → testimonial → list	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/case-study
collection	page-header → teaser → filter-list → table-list → list	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/collection
forms/ar-landing	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/ar-landing
forms/csr	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/csr

Page	Blocks in order	Live
forms/csr-form	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/csr-form
forms/global-contact-us	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/global-contact-us
forms/inquizitive	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/inquizitive
forms/media-form	form-variations → button-block	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/media-form
forms/talk-to-an-expert-retail	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/talk-to-an-expert-retail
forms/website-feedback-form	form-variations	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/forms/website-feedback-form
home	hero → list → list → conversation-canvas → table-list → list → list → list → teaser	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/home
industry-landing-page	teaser → cards → video → columns-container → column-break → table-list → list → list → list → testimonial → table-list → list → list → cards → list	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/industry-landing-page
insights	hero → teaser → filter-list → testimonial	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/insights
media-and-investor	hero → teaser → filter-list → list → list → list → teaser → list → list → teaser	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/media-and-investor

Page	Blocks in order	Live
news-and-events	hero → teaser → filter-list → list → teaser	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/news-and-events
product	teaser → cards → teaser → cards → teaser → list → testimonial → table-list → list	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/product
services	teaser → cards → columns-container → column-break → column-break → teaser → teaser → cards → teaser → list → testimonial → list	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/services
story	page-header → anchor-list → tabs → tab → video → tab → video → tab → video → tab → video → columns-container → column-break → column-break → teaser → teaser → columns-container → column-break → column-break → columns-container → column-break → column-break → columns-container → column-break → column-break → teaser → teaser → columns-container → column-break → column-break → teaser → testimonial → list → teaser → teaser	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/story
what-we-do	hero → teaser → columns-container → teaser → teaser → teaser → teaser → teaser → columns-container → column-break → teaser → column-break → table-list → conversation-canvas → columns-container → column-break → column-break → button-block → teaser → teaser → teaser → table-list	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/what-we-do
who-we-are	hero → teaser → cards → teaser → testimonial → list → list → quote → gen-carousel → teaser → teaser → teaser → teaser → teaser → teaser	https://main--tcs-corp--sradha-tcs.aem.live/design-block-master/en/curated-design-pages/who-we-are

3. Screenshots

> **Screenshot required**
>
> - Required screen: Curated Design Page Authoring Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Data Sheets Guide

Attribute	Value
Document ID	AUT-012
Audience	Content authors, content managers, AEM authoring leads
Purpose	Authors, locations, partners, social links, media contacts and redirects sheets
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	utils/data.js
Related documents	—
Related AEM paths	—

1. Data sheets

Purpose. Shared structured data per locale, maintained by authors as AEM spreadsheets.

Structure and consumers (`utils/data.js`; each sheet loaded once per page view, values trimmed, missing sheets give empty lists):

Sheet (`/{locale}/data/…json`)	Columns	Read by
`authors`	`author-id`, `name`, `designation`, `bio`, `image`, `linkedin`, `region`	Page Header (`getAuthor`, case-insensitive id), article / blog templates, List feature card and Filter List spotlights (`getAuthors`)
`social-links`	`platform`, `url`, `icon`, `sort-order`	Footer (in `sort-order`, rows without one last)
`media-contacts`	`id`, `name`, `designation`, `email`, `phone`, `region`	Media Contacts block (`blocks/media-contacts`: `inRegion` by the page's `region`, else all; grouped by designation and region)
`locations`	`location-id`, `location-name`, `country`, `region`, `latitude`, `longitude`	`getLocations()` only; no component reads it (handover F-40)
`partners`	`partner-id`, `partner-name`, `logo`, `website`, `tier`, `description`	`getPartners()` only; no component reads it (handover F-40)

Rules. The query index excludes `/*/data/**`. Sheet JSON is public: the Authors and Media Contacts sheets publish names, e-mail addresses and phone numbers by design. Column reference and authoring steps: handover Part 9 — Data Sheets Documentation.

Common mistakes. An `author-id` on a page that differs from the sheet in case (Filter List and List match exactly; Page Header case-insensitively, handover F-30); unpublished sheets in non-English locales.

2. Redirects

Purpose. Per-locale lists of moved pages.

Structure. `/{locale}/redirects.json` with Source and Destination columns (either case).

Rules and status.

- The platform applies only a root `/redirects.json`; the per-locale sheets are **not applied** automatically. Redirects, including `/` → `/en/`, need another mechanism such as CDN rules (AGENTS.md "Notes"; handover Part 3.8; findings F-36, 16.4). Status: Requires validation (no mechanism configured).
- In code only the List block uses the sheet: `resolveRedirect` points card links to the final target, at most 5 hops, stopping at loops and external destinations (`utils/redirects.js`). Filter List, navigation and running text links aren't rewritten.
- Sources must start with `/` (rows without a destination are ignored); paths are compared without query, hash, `.html` and trailing slash.

Common mistakes. Expecting a sheet row to redirect visitors; chains of redirects (point sources at final destinations).

3. Redirects sheet (8 November 2026)

The consolidated redirects sheet maps the tcs.com path of each of the 8,432 migrated pages (e.g. `/careers`) to its page below `/language-masters/en`; per-locale redirects sheets aren't applied by the platform (a CDN rule is needed, on hold).

4. Screenshots

> **Screenshot required**
>
> - Required screen: Data Sheets Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

5. Known limitations

- None recorded for this document.

6. Open items

- None.

7. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Getting Started (authors)

Attribute	Value
Document ID	AUT-001
Audience	Content authors, content managers, AEM authoring leads
Purpose	The systems an author uses, access and the Universal Editor flow
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	docs/handover/knowledge-base/authoring.md
Related documents	—
Related AEM paths	—

1. Access you need

- An Adobe ID in the IMS organisation with the AEM Sites author product profile (Content Authors); the AEM administrator grants it.
- Universal Editor opens from the AEM Sites console (select a page > Edit).

2. Where to author

Tree (AEM Sites)	Use it for
/content/tcs-corp/language-masters/en	The real language master content (the migrated tcs.com pages) and its sheets; validated before it becomes the global site and the regions
/content/tcs-corp/language-master/en	Testing page functionality with dummy content and content limitations
/content/tcs-corp/design-block-master/en	The block library (every block and variation) and the curated design pages
/content/tcs-corp/<country>/<language>	The 13 locale sites (/en, /de-de, ...)

3. Systems an author uses

System	Purpose	Notes
AEM as a Cloud Service author, Sites console	Browse `/content/tcs-corp`, create, copy, move, publish, unpublish, page versions	Host and program ids are not repeated here; ask the AEM administrator
Universal Editor	Visual editing: canvas, Content tree, Properties panel	Opened from the Sites console with **Edit**
AEM Assets	Images and documents under `/content/dam/tcs-corp/`	`/content/dam/tcs-corp/` is in the `includes` of paths.json

System	Purpose	Notes
Preview site	`https://main--tcs-corp--sradha-tcs.aem.page/{locale}/…`	Content published to preview
Live site	`https://main--tcs-corp--sradha-tcs.aem.live/{locale}/…`	Production origin; production domain and CDN: Not recorded
AEM Sidekick (optional)	Preview / live status and switching on the Edge Delivery hosts	tools/sidekick/config.json labels the edit link "AEM Editor"

Access and permissions: AEM user groups, permissions per locale and a publish approval workflow are not part of the repository and are not recorded (handover Part 5, 5.1.2, "To be confirmed"; open item O-06). See administration-and-operations.md.

4. The Universal Editor flow



- Edits save automatically. After each change scripts/editor-support.js re-decorates only the changed block, section or default content; when it can't, the canvas reloads (expected).
- **Edit mode** (`html.adobe-ue-edit`, `isEditing()` in utils/environment.js): clicks select components; blocks with Hide block are shown faded with a dashed outline; animations don't play and aren't used up; List, Cards, Filter List and new items show editor hints and placeholders (decorators/editor-item-decorator.js).
- **Preview mode** and the published site: links work, hidden blocks are gone, animations and carousels run.
- On AEM author there is no query index: Lists from child pages or tags and Filter Lists say their pages show on the published page; sheets (placeholders, taxonomy) may not resolve, so the editor can show English fallbacks and ID-derived tag labels. Validate those on `aem.page` (handover Part 14, Known Limitations #18).
- Device sizes: check mobile (below 600 px), tablet (600–1199 px) and desktop (1200 px and above), the breakpoints of AGENTS.md.

5. Screenshots

> **Screenshot required**
>
> - Required screen: Getting Started (authors)
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

6. Known limitations

- None recorded for this document.

7. Open items

- None.

8. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Localization Guide

Attribute	Value
Document ID	AUT-010
Audience	Content authors, content managers, AEM authoring leads
Purpose	Locale sites, the language master and authoring per locale
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	utils/site.js
Related documents	—
Related AEM paths	—

1. The language master

`/content/tcs-corp/language-masters/en` holds the content that becomes the global site and the regions once final; MSM or separate regional content is not decided yet.

2. Site and locale hierarchy

Purpose. One Edge Delivery site serves 13 locale sites by path. Each locale owns its pages and its own references, error pages, sheets, data and block library.

Structure. The AEM tree `/content/tcs-corp/{country}/{language}` is published at a language-only path. The locales are defined once in `LOCALES` (`utils/site.js`); the first entry is the default (`DEFAULT_LOCALE`, `en`).

AEM folder	Published root	lang		AEM folder	Published root	lang
us/en	/en	en-US		se/sv-se	/sv-se	sv-SE
de/de-de	/de-de	de-DE		dk/da-dk	/da-dk	da-DK
fr/fr-fr	/fr-fr	fr-FR		no/no-no	/no-no	no-NO
ca/fr-ca	/fr-ca	fr-CA		cn/zh-cn	/zh-cn	zh-CN
es/es-es	/es-es	es-ES		jp/ja-jp	/ja-jp	ja-JP
pt/pt-pt	/pt-pt	pt-PT		kr/ko-kr	/ko-kr	ko-KR
nl/nl-nl	/nl-nl	nl-NL				

```
/content/tcs-corp/
├── {country}/{language}/   a locale site; the locale page itself is Home (published as /{locale}/)
│   ├── …                   content pages
│   ├── references/         nav, footer, alternative navs / footers, footer Canvas page, modals,
fragments
```

```
│   ├── error-pages/        404 (used by 404.html); 403 / 500 for a CDN
│   ├── block-library/      block validation pages; excluded from publishing
│   ├── placeholders        sheet: Key, Text, Description, Category
│   ├── metadata            sheet: bulk metadata
│   ├── taxonomy            taxonomy page (tag, title)
│   ├── redirects           sheet: Source, Destination
│   └── data/               sheets: authors, locations, partners, social-links, media-contacts
├── language-masters/en/     temporary: published at /language-masters/en for review
└── site-global-templates/  template pages authors copy; excluded from publishing
```

Path mapping (`paths.json`, generated by `npm run build:paths` from `LOCALES` and `REVIEW_ROOTS`). One generic set per site root: the folder mapping (`/content/tcs-corp/de/de-de/:/de-de/`: child pages and sheets), the Home page mapping (`/content/tcs-corp/de/de-de:/de-de/`) and the taxonomy page (`…/taxonomy:/de-de/taxonomy.json`): 39 mappings for the locales, 3 temporarily for the language master. The sheets (`placeholders`, `metadata`, `redirects`, `data/*`) need no mapping of their own: the folder mapping publishes them at the same path and spreadsheets get `.json` appended; the former 112 per-sheet mappings are kept commented in the generator. `includes`: the 13 locale pages, `/content/dam/tcs-corp/` and `/content/tcs-corp/language-masters/en`; `excludes`: each locale's `block-library` and `block-library/**`, and `site-global-templates` with its children. AEM applies the site configuration's `public.json` → `paths`, not the repository file (AGENTS.md "Notes").

Locale resolution (code). `getLocale(pathname)` reads the AEM path when editing (`/content/tcs-corp/de/de-de/…`) and the published path on the site (`/de-de/…`); pages outside a locale (Site Global Templates, drafts) get `en`. Helpers: `localePagePath`, `resolvePagePath`, `localeSheetPath`, `toPublishedPath`, `toAemPath`, `pageLink`, `getParentPages`, `sheetRows`.

Review roots (KB-D-068). There are three review roots, each published as a site of its own (KB-D-068): `/language-master/en` (testing page functionality with dummy content, content limitations), `/language-masters/en` (the language master: the migrated tcs.com content, validated with its real sheet data, later the source of the global site and the regions and languages; MSM or not is open until the content is final) and `/design-block-master/en` (the block library and the curated design pages). Pages below each (`REVIEW_ROOTS`) list their own pages from the query index (`indexRoot`), read their own placeholders, redirects, taxonomy and data sheets (`REVIEW_SHEETS`), use their own `references/` and `error-pages/` (`REVIEW_PAGES`) and inherit up to their root page. The temporary review of the language master ends with its rollout (handover Part 3.9, finding F-88).

Language master URLs (validated 23 October 2026). The mappings follow Adobe's path mapping rules (https://www.aem.live/developer/authoring-path-mapping): the folder mapping `/content/tcs-corp/language-masters/en/:/language-masters/en/` covers every child page, and the page mapping `/content/tcs-corp/language-masters/en:/language-masters/en/` is the special case that publishes the root page as `/language-masters/en/index`, served at `/language-masters/en/` (the same pattern as `/en/`). No other mapping is needed. The mappings of every language master come from `REVIEW_ROOTS` (`utils/site.js`): `tools/paths/generate-paths.mjs` writes this set for each root, so another language master (e.g. `/language-masters/de`) is added to the code and to `paths.json` with one entry and `npm run build:paths`; `test/site/paths.test.mjs` checks every locale and language master is mapped this way and that `paths.json` is in step.

AEM page	Preview	Live
/content/tcs-corp/language-masters/en (Home)	https://main--tcs-corp--sradha-tcs.aem.page/language-master/en/	https://main--tcs-corp--sradha-tcs.aem.live/language-master/en/
/content/tcs-corp/language-masters/en/<path> (child pages)	https://main--tcs-corp--sradha-tcs.aem.page/language-master/en/<path>	https://main--tcs-corp--sradha-tcs.aem.live/language-master/en/<path>

The Home URL ends with `/` (`/language-masters/en` without it is a 404, as `/en`). On 23 October 2026 the child pages, sheets, references and error pages resolved, but the Home page was a 404 and wasn't in the query index: it has to be previewed and published from AEM (Manage Publication on `/content/tcs-corp/language-`

`masters/en`). If it still returns a 404 after publishing, check that the site configuration's `public.json` → `paths` has the page mapping (AEM applies that configuration, not the repository file).

Rules.

- Add or change a locale only in `LOCALES`, then run `npm run build:paths` and commit both files; the site administrator re-applies `public.json` and `metadata.source`.
- Nothing is published at `/`: a `/` → `/en/` redirect needs another mechanism (handover F-36).

Common mistakes. Editing `paths.json` by hand (it is overwritten by the generator); expecting a repository `paths.json` change to take effect without the site configuration; creating pages directly under `/content/tcs-corp` (not published).

3. Localization

Topic	Implementation	Status
Locale structure	13 separate page trees; locale resolved from the path	Active
`<html lang>`	`language` metadata when valid, else the locale's tag	Active
UI text	Placeholders sheet per locale; English fallback in code	Active
Tag labels	Taxonomy page per locale, language sheet when translated	Active (only `/en` taxonomy published when checked, F-09)
Bulk metadata	One sheet per locale; all 13 in `metadata.source`	Requires validation (F-11, open item O-04)
Data sheets	One set per locale	Active
Lists	Each locale lists only its own pages (`indexRoot`)	Active
Dates	`utils/dates.js` `formatDate`; English month abbreviations in every locale (handover Part 4.9.7)	Active
Translation process, MSM / language copies, language selector, `hreflang`	Not in code	Not recorded

4. Localization

- Each of the 13 locales is a separate page tree with its own references, error pages, sheets, data and block library; locales share no content. Link only to the locale's own references and sheets.
- The page language (`<html lang>`) is the page's `language` metadata when valid, else the locale's tag (decorators/seo-decorator.js).
- Creating a locale's content, translation projects, MSM live copies, a language switcher and `hreflang` are not implemented in code; the translation process is not recorded (handover Part 4, 4.9.6; open item O-12).
- Month abbreviations in formatted dates are English in every locale; prefer the numeric date formats where a block offers a choice (handover 4.9.7).
- Temporary: pages below `/language-masters/en` read the language master's own references, sheets and index rows until its rollout to `/en` (`REVIEW_*` in utils/site.js).

5. Screenshots

> **Screenshot required**
>
> - Required screen: Localization Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)

- Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
- Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
- Owner: Content Lead / AEM Authoring Lead (proposed)
- Target completion date: To be confirmed

6. Known limitations

- None recorded for this document.

7. Open items

- None.

8. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Metadata Guide

Attribute	Value
Document ID	AUT-008
Audience	Content authors, content managers, AEM authoring leads
Purpose	Page properties, the bulk metadata sheet and its columns
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	AGENTS.md, docs/handover/knowledge-base/content-architecture.md
Related documents	—
Related AEM paths	—

1. Bulk metadata columns

Bulk metadata columns: `url`, `page-type`, `meta-title`, `meta-description`, `meta-keywords`, `keyword-action`, `author-id`, `publish-date`, `modified-date`, `reading-time`, `og-title`, `og-description`, `og-image`, `og-type`, `twitter-card`, `twitter-title`, `twitter-description`, `twitter-image`, `canonical-url`, `robots`, `region`, `country`, `language`, `persona`, `thumbnail-image`, `featured-image`, `campaign-id`, `content-type`, `featured`, `priority`, `listen-link`, `author`, `card-title`, `card-description`, `card-image`, `card-image-alt`, `image-alt`, `eyebrow`, `category`, `hide-in-nav`, `card-style`, `card-theme`. Each column is published as `<meta name="{column}">`; the SEO decorator maps meta-title, meta-description, meta-keywords (with the page dialog's Keywords as `keyword-action` says: `default` or empty, the dialog's win; `override`, the sheet's win; `merge`, both, the dialog's first; `utils/keywords.js`), og-*, twitter-* and canonical-url to the standard tags in the browser (`robots` is standard and works server side). The Page Header takes all its content from metadata: page-type (default layout), title, description, tags, content-type (eyebrow / label), publish-date, reading-time, author-id (Authors sheet: name, designation, region, image, LinkedIn), featured-image (Landing) and listen-link (listen action; share and download come from code); only its Layout and CTA List are authored. The List block (`blocks/list`, see its README) lists child pages, a fixed list (List Items) or tagged pages from the query index, as cards from card-title, card-description, card-image, card-image-alt, eyebrow / category, tags, content-type and the dates (a List Item's authored fields win, field by field, over its linked page's; Card style and Card colour: List Item, else the List's unless Mixed (by page) / Default for the style, else the page's card-style / card-theme, else automatic) (pages with hide-in-nav = yes are left out; links go to the redirect targets of `/{locale}/redirects.json`), with grid or horizontal scroll per breakpoint. The Cards block (`blocks/cards`, see its README) is its manual authoring alternative: each Card holds its own image, eyebrow, title, rich text description, label, tags, date, link and call to action, with the List's presentation and block settings (shared: `models/_card-list.json` fields, `utils/card-list-config.js`, `decorators/card-list-decorator.js`, `styles/card-list.css`). The Filter List lists the locale's pages from the query index (`utils/query-index.js`, loaded once) below its Root path, of its Page types (page-type) and Content types (content-type), or a manual list, in its Sort order; its filter pills are curated tags (labels from the taxonomy), its advanced filter the tags below taxonomy roots. Cards are built from the metadata columns of its Card mapping (featured-image, else thumbnail-image; content-type; title; description; tags with reading-time; path; author, else author-id from the Authors sheet) with publish-date; the hero and

featured spotlight cards come from featured (yes / true) and priority (featured cards: featured, else priority <= 3); `feature-card` / `featured-priority` are read as fallbacks; the footer lists the Social Links sheet in sort-order.

2. Metadata model

Purpose. Page-level values (SEO, social, card content, page type, author, dates, flags) that code, the query index and the data layer read. Every value is a `<meta>` in the server-delivered head.

Sources and precedence.

Source	Where authored	Published as
Page properties (`models/_page.json`)	Universal Editor page properties	`<title>`, `description`, `keywords`, `page-type`, `nav`, `footer`, `error-page` metas
Standard AEM page properties	Sites console (e.g. Tags `cq:tags`)	`cq-tags` (one comma-separated meta)
Bulk metadata sheet	`/content/tcs-corp/{country}/{language}/metadata`	`/{locale}/metadata.json`; each column becomes `<meta name="{column}">` on pages matching the row's `url` pattern

Page-level values win over bulk metadata; bulk rows apply top to bottom (handover Part 8.1.2). The bulk sheets apply only once all 13 are listed in the site configuration's `metadata.source`, and each sheet's URL patterns must start with its locale (`/de-de/**`) (AGENTS.md "Notes").

Bulk metadata columns (AGENTS.md, 42 columns): `url`, `page-type`, `meta-title`, `meta-description`, `meta-keywords`, `keyword-action`, `author-id`, `publish-date`, `modified-date`, `reading-time`, `og-title`, `og-description`, `og-image`, `og-type`, `twitter-card`, `twitter-title`, `twitter-description`, `twitter-image`, `canonical-url`, `robots`, `region`, `country`, `language`, `persona`, `thumbnail-image`, `featured-image`, `campaign-id`, `content-type`, `featured`, `priority`, `listen-link`, `author`, `card-title`, `card-description`, `card-image`, `card-image-alt`, `image-alt`, `eyebrow`, `category`, `hide-in-nav`, `card-style`, `card-theme`.

Consumers.

Consumer	Reads	Source
SEO decorator (eager)	`meta-title` → `<title>`; `meta-description`; `meta-keywords` combined with the page dialog's Keywords by `keyword-action` (`default` or empty: the dialog's; `override`: the sheet's; `merge`: both, the dialog's first; `utils/keywords.js`); `og-*` (falling back to `meta-*`); `twitter-*` (falling back to `og-*`, `meta-*`); `canonical-url` → `<link rel="canonical">` and `og:url`; `language` → `<html lang>`	`decorators/seo-decorator.js`
`getPageMetadata()`	title, description, image (`featured-image`, else `og:image`), `page-type` (else `template`), `content-type`, `category`, tags, `author-id`, `author`, `publish-date` (else `publication-date`), `modified-date`, `reading-time`, `listen-link`, `thumbnail-image`, `featured-image`, `image-alt`, `region`, `country` (else the locale's), language, `persona`, `campaign-id`, `featured` (yes / true / 1 / on / y), `priority` (number)	`utils/metadata.js`
`getPageTags()`	`article:tag` metas and `cq-tags`, else a comma-separated `tags` meta	`utils/metadata.js`
`getPageLanguage()`	`language` when it is a language code, else the locale's `lang`	`utils/metadata.js`
Page Header, templates, data layer page entry	`getPageMetadata()`	page-header, `decorators/data-layer-decorator.js`
Query index	the server head (see indexing-and-search.md)	`helix-query.yaml`

Rules. The query index reads the server-delivered head, so values set by JavaScript (the SEO decorator's) aren't indexed (handover Part 8.1.3). `robots` is a standard name and works server side. Use `card-*`, `eyebrow`, `hide-in-nav`, `card-style`, `card-theme` for List cards (List README "Page metadata contract").

Example.

```
url                   | page-type      | hide-in-nav
/de-de/newsroom/**    | press-release  |
/de-de/insights/**    | article        |
/de-de/legal/imprint  |                | yes
```

Common mistakes. A sheet row pattern without the locale prefix; adding columns to a sheet that isn't listed in `metadata.source` (no effect); expecting a metadata change to reach lists before the page is republished and indexed. Field reference per column: handover Part 8 — Metadata Documentation (8.2, 8.4).

3. Metadata

Source	What it sets	Notes
Page properties	Title, Description, Keywords, Page Type, Navigation, Footer, 404 Page	models/_page.json
Bulk metadata sheet `{locale}/metadata`	Every other page-level value: `author-id`, `publish-date`, `reading-time`, `region`, `content-type`, `featured-image`, card values (`card-title`, `card-style`, ...), SEO and social columns	Column list in AGENTS.md; URL patterns must start with the locale (`/de-de/**`)

The bulk sheets apply only once the administrator lists all 13 in the site configuration's `metadata.source`; whether that is done is not recorded (handover open item O-04). The Page Header takes all its content from metadata (only its Layout and CTAs are authored). Republish a page after its card values changed so the query index row updates. Field reference: handover Part 8 — Metadata Documentation.

4. Screenshots

> **Screenshot required**
>
> - Required screen: Metadata Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

5. Known limitations

- None recorded for this document.

6. Open items

- None.

7. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Page Creation Guide

Attribute	Value
Document ID	AUT-002
Audience	Content authors, content managers, AEM authoring leads
Purpose	Creating pages, templates, sections and reordering, duplicating and deleting content
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	docs/handover/knowledge-base/authoring.md, models/_page.json
Related documents	—
Related AEM paths	—

1. Creating and editing pages

Where pages live

The 13 locale sites and their published paths are listed in AGENTS.md and defined in `LOCALES` of utils/site.js.

Location (below `/content/tcs-corp/{country}/{language}`)	Contents	Published
The locale page itself	The locale's Home page	Yes, at `/{locale}/`
Content pages below it	All content pages	Yes
`references/`	Navigation (`nav`), `footer`, other fragments	Yes (read by other pages)
`error-pages/`	`404` (used by the site); `403` / `500` (for a CDN, not used by code)	Yes
`block-library/`	Every block variation in the locale's language	No (excludes of paths.json)
`/content/tcs-corp/site-global-templates/`	Template pages to copy (home, article, blog, press release)	No

Creating a page

1. In the Sites console copy the template page from `site-global-templates` and paste it into the locale folder; rename it (the page name becomes the URL segment). For pages without a template use **Create > Page** (the AEM page template offered there is not recorded).
2. Open it with **Edit**, set the page properties, edit the content, then preview and publish.
3. Values that aren't page properties (author, dates, reading time, region, images, card values, SEO and social columns) come from the locale's bulk metadata sheet (see Metadata).

Walkthrough: handover Part 5, 5.3, and the cheat sheet in Part 15, 15.5.1.

Page properties

The page model is `page-metadata` in models/_page.json:

Field	Name	Notes
Title	`jcr:title`	Browser, SEO and social title; Page Header heading; card title fallback
Description	`jcr:description`	Meta description; Page Header description; card description fallback
Keywords	`keywords`	Meta keywords
Page Type	`page-type`	Default, Home, Article, Blog, Press Release: loads `templates/{name}/` (templates/README.md); overrides the sheet's `page-type`
Navigation	`nav`	Inherited (see References)
Footer	`footer`	Inherited
404 Page	`error-page`	Inherited

`TEMPLATES` in scripts/scripts.js is `home`, `article`, `blog`, `press-release`; another value loads no template code but is still added as a body class.

Sections

A section is a band of the page with default content and blocks. Its fields (Section Name, Style Default / Grey / Dark / Dark Green, Width Type, Rounded edge, Background Image and its alt text, Anchor name) are in models/_section.json; the backgrounds and the dark theme contract are described in AGENTS.md ("Backgrounds and theme"). Sections don't get `classes_*` fields delivered, so a section has no Additional tab; the container sections use `container*` fields instead.

2. Adding and configuring blocks

Where components can be added

What the **Add (+)** picker offers is defined by the filters in component-filters.json (aggregated from models/_component-filters.json, models/_section.json and each block's `_<block>.json`):

Container	Allowed components
Main (the page)	Section, Gen Carousel, Tabs Container, Columns Container
Section	Text, Image, Button (Button Block), Title, Page Header, Hero, Teaser, Quote, Testimonial, Anchor List, Accordion, Tabs (block), Table, Table List, List, Separator, Embed, Video, Modal, Form Variations, Filter List, Conversation Canvas, Cards, Fragment, Footer, TCS Header
Columns Container	Column Break, then the Section's components except Page Header, Footer and TCS Header
Tabs Container	Tab, Column Break, then the Section's components except Page Header, Conversation Canvas, Footer and TCS Header
Gen Carousel	Hero, Teaser

The item filters of each block (Accordion Item, Card, List Item, CTA, Link, Stat, form fields, Table rows, ...) are listed in blocks/README.md. Not offered in any filter: the built-in Columns (compatibility only), the built-in Button ("Button (basic)"), and Interactive Dashboard (placeholder) (blocks/README.md).

Block reference

Each block README holds the dialog fields per tab (generated from the models), the variations, authoring steps, accessibility, data layer and troubleshooting. Don't repeat fields elsewhere; read them there.

Block	README	Added in	Status
Accordion	accordion	Section, Columns Container, Tabs Container	Active
Anchor List	anchor-list	Section, Columns Container, Tabs Container	Active
Button (Button Block)	button-block	Section, Columns Container, Tabs Container	Active
Cards	cards	Section, Columns Container, Tabs Container	Active
Column Break	column-break	Columns Container, Tabs Container	Active
Columns (built-in)	columns	None (no longer offered)	Compatibility-only
Columns Container	columns-container	Main (page)	Active
Conversation Canvas	conversation-canvas	Section, Columns Container	Active
Embed	embed	Section, Columns Container, Tabs Container	Active
Filter List	filter-list	Section, Columns Container, Tabs Container	Active
Footer	footer	Section (on the footer reference page)	Active
Form Variations	form-variations	Section, Columns Container, Tabs Container	Active
Fragment	fragment	Section, Columns Container, Tabs Container	Active
Gen Carousel	gen-carousel	Main (page)	Active
Header	header	Not a component: built from the nav page	Active
Hero	hero	Section, Columns Container, Tabs Container, Gen Carousel	Active
Interactive Dashboard	interactive-dashboard	None	Experimental
List	list	Section, Columns Container, Tabs Container	Active
Modal	modal	Section, Columns Container, Tabs Container	Active
Page Header	page-header	Section	Active
Quote	quote	Section, Columns Container, Tabs Container	Active
Separator	separator	Section, Columns Container, Tabs Container	Active
Tab	tab	Tabs Container	Active
Table	table	Section, Columns Container, Tabs Container	Active
Table List	table-list	Section, Columns Container, Tabs Container	Active
Tabs Container and Tabs (block)	tabs	Main (container); Section, Columns Container, Tabs Container (block)	Active
TCS Header	tcs-header	Section (on the nav page)	Active
Teaser	teaser	Section, Columns Container, Tabs Container, Gen Carousel	Active
Testimonial	testimonial	Section, Columns Container, Tabs Container	Active
Video	video	Section, Columns Container, Tabs Container	Active

Default content (Text, Title, Image) uses AEM's built-in components (handover Part 6, chapters 6.6 to 6.8).

The Additional tab

Every block model except the header and footer ends with an **Additional** tab (rules in AGENTS.md, "Additional tab" and "Animation and skeletons"):

Field	Name	Effect
Anchor ID	`classes_anchor`	Must match `anchor-…` (lower case, digits, hyphens); becomes the block's `id` (decorators/block-options-decorator.js), de-duplicated as `-2`, `-3`; also the block's data layer id
Hide block	`classes_hideblock`	Hidden on the site and in Preview; faded in edit mode; the content stays in the delivered HTML (not an embargo mechanism)
Padding / Margin Left, Right, Top, Bottom	`classes_padding*`, `classes_margin*`	`--space-*` tokens, the same at every breakpoint
Animation Type, Motion Speed, Animation Trigger	`classes_animation*`	Content animation on 19 blocks; never in edit mode or for reduced motion (docs/animation/README.md)
Background animation	`classes_bganimation`	Hero, Teaser, Quote, Testimonial, Form Variations, Conversation Canvas

Container sections (Columns Container, Tabs Container, Gen Carousel) carry the same options as `container*` fields (`containerAnchor`, `containerHide`, …), applied by `applySectionBlockOptions` in scripts/scripts.js.

3. Containers and child items

- **Section containers** are added at page level (Main): a Columns Container holds Column Breaks and the components of each column; a Tabs Container holds Tabs (and Column Breaks inside a tab: a section can't hold a section); a Gen Carousel holds Heroes and Teasers as slides. `scripts.js` wraps each in a synthetic block.
- **Column Break** (README) starts a column: the components after it belong to that column. In a Tab, content before the first Column Break stays above the columns; the Tab's **Columns per row** sets the layout.
- **Item children**: repeating content is added to the block with **Add (+)**, not with composite multifields: List Items, Cards, Hero and Page Header CTAs, Teaser Links and Stats, Testimonial Stats, Anchor Links, Filter List tags / categories / pages, Footer Links, form fields, Table rows, Canvas buttons (AGENTS.md, "Item children"). The multifields authored before are still read but don't render from content packages (handover finding F-87).
- An item without content yet is a dashed placeholder in the editor (placeholder key `itemEditorHint`).
- Universal Editor collapses a dialog's tabs into a dropdown when they don't fit; models keep at most three tabs, the last one Additional.
- Built-in **Columns** and **Button (basic)** authored before stay editable but aren't offered; use a Columns Container and the Button block.

4. Screenshots

> **Screenshot required**
>
> - Required screen: Page Creation Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)

> - Target completion date: To be confirmed

5. Known limitations

- None recorded for this document.

6. Open items

- None.

7. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Page Properties Guide

Attribute	Value
Document ID	AUT-003
Audience	Content authors, content managers, AEM authoring leads
Purpose	The page properties and the bulk metadata columns
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	models/_page.json, docs/handover/knowledge-base/content-architecture.md
Related documents	—
Related AEM paths	—

1. Page properties (model page-metadata)

Label	Property	Type	Description
Title	`jcr:title`	text	—
Description	`jcr:description`	text	—
Keywords	`keywords`	text	Combined with the metadata sheet's meta-keywords as its keyword-action column says: default (or empty), these win; override, the sheet's win; merge, both, these first.
Page Type	`page-type`	select	The Site Global Template of the page (layout and template code). Overrides the page-type column of the metadata sheet.
Navigation	`nav`	aem-content	The header (nav) page of this page and, unless they set their own, its child pages. Empty: the nearest parent page's Navigation (or the metadata sheet's nav column), else the locale's references/nav.
Footer	`footer`	aem-content	The footer page of this page and, unless they set their own, its child pages. Empty: the nearest parent page's Footer (or the metadata sheet's footer column), else the locale's references/footer.
404 Page	`error-page`	aem-content	The page shown when a page below this one isn't found. Empty: the nearest parent page's 404 Page (or the metadata sheet's error-page column), else the locale's error-pages/404.

Navigation, Footer and 404 Page are inherited by child pages from the nearest parent that sets them, up to the root page; else the root's references/nav, references/footer and error-pages/404 are used.

2. Metadata model

Purpose. Page-level values (SEO, social, card content, page type, author, dates, flags) that code, the query index and the data layer read. Every value is a `<meta>` in the server-delivered head.

Sources and precedence.

Source	Where authored	Published as
Page properties (`models/_page.json`)	Universal Editor page properties	`<title>`, `description`, `keywords`, `page-type`, `nav`, `footer`, `error-page` metas
Standard AEM page properties	Sites console (e.g. Tags `cq:tags`)	`cq-tags` (one comma-separated meta)
Bulk metadata sheet	`/content/tcs-corp/{country}/{language}/metadata`	`/{locale}/metadata.json`; each column becomes `<meta name="{column}">` on pages matching the row's `url` pattern

Page-level values win over bulk metadata; bulk rows apply top to bottom (handover Part 8.1.2). The bulk sheets apply only once all 13 are listed in the site configuration's `metadata.source`, and each sheet's URL patterns must start with its locale (`/de-de/**`) (AGENTS.md "Notes").

Bulk metadata columns (AGENTS.md, 42 columns): `url`, `page-type`, `meta-title`, `meta-description`, `meta-keywords`, `keyword-action`, `author-id`, `publish-date`, `modified-date`, `reading-time`, `og-title`, `og-description`, `og-image`, `og-type`, `twitter-card`, `twitter-title`, `twitter-description`, `twitter-image`, `canonical-url`, `robots`, `region`, `country`, `language`, `persona`, `thumbnail-image`, `featured-image`, `campaign-id`, `content-type`, `featured`, `priority`, `listen-link`, `author`, `card-title`, `card-description`, `card-image`, `card-image-alt`, `image-alt`, `eyebrow`, `category`, `hide-in-nav`, `card-style`, `card-theme`.

Consumers.

Consumer	Reads	Source
SEO decorator (eager)	`meta-title` → `<title>`; `meta-description`; `meta-keywords` combined with the page dialog's Keywords by `keyword-action` (`default` or empty: the dialog's; `override`: the sheet's; `merge`: both, the dialog's first; `utils/keywords.js`); `og-*` (falling back to `meta-*`); `twitter-*` (falling back to `og-*`, `meta-*`); `canonical-url` → `<link rel="canonical">` and `og:url`; `language` → `<html lang>`	`decorators/seo-decorator.js`
`getPageMetadata()`	title, description, image (`featured-image`, else `og:image`), `page-type` (else `template`), `content-type`, `category`, tags, `author-id`, `author`, `publish-date` (else `publication-date`), `modified-date`, `reading-time`, `listen-link`, `thumbnail-image`, `featured-image`, `image-alt`, `region`, `country` (else the locale's), language, `persona`, `campaign-id`, `featured` (yes / true / 1 / on / y), `priority` (number)	`utils/metadata.js`
`getPageTags()`	`article:tag` metas and `cq-tags`, else a comma-separated `tags` meta	`utils/metadata.js`
`getPageLanguage()`	`language` when it is a language code, else the locale's `lang`	`utils/metadata.js`
Page Header, templates, data layer page entry	`getPageMetadata()`	page-header, `decorators/data-layer-decorator.js`
Query index	the server head (see indexing-and-search.md)	`helix-query.yaml`

Rules. The query index reads the server-delivered head, so values set by JavaScript (the SEO decorator's) aren't indexed (handover Part 8.1.3). `robots` is a standard name and works server side. Use `card-*`, `eyebrow`, `hide-in-nav`, `card-style`, `card-theme` for List cards (List README "Page metadata contract").

Example.

```
url                   | page-type      | hide-in-nav
/de-de/newsroom/**    | press-release  |
```

```
/de-de/insights/**    | article        |
/de-de/legal/imprint  |                | yes
```

Common mistakes. A sheet row pattern without the locale prefix; adding columns to a sheet that isn't listed in `metadata.source` (no effect); expecting a metadata change to reach lists before the page is republished and indexed. Field reference per column: handover Part 8 — Metadata Documentation (8.2, 8.4).

3. Screenshots

> **Screenshot required**
>
> - Required screen: Page Properties Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Placeholders Guide

Attribute	Value
Document ID	AUT-011
Audience	Content authors, content managers, AEM authoring leads
Purpose	The placeholders sheet (UI text) per locale and review root
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	utils/placeholders.js
Related documents	—
Related AEM paths	—

1. Placeholders

Purpose. All user-facing UI text in code is authorable and translated per locale (AGENTS.md "Accessibility": all UI text comes from placeholders).

Structure. `/{locale}/placeholders.json` with columns Key, Text, Description, Category; code uses Key and Text. Keys are compared without case and separators (`Pause Slides`, `pause-slides` and `pauseSlides` match `pauseSlides`). `{name}` variables are filled by `fillPlaceholder`.

Consumers. `const t = await getPlaceholders(); t('nextSlide', 'Next slide')` in every block with UI text, the header, footer and `scripts.js` (404 "Go back", key `goBack`). Source: `utils/placeholders.js`; key lists per block in the block READMEs ("For Site Administrators").

Rules. Code always passes an English fallback. There is no fallback from a locale's sheet to the English sheet: a key missing in `/de-de/placeholders.json` shows the code's English text (handover Part 4.9.3).

Common mistakes. Editing the sheet without publishing it; adding a new key in code without adding it to the 13 sheets. Full key list: handover Part 4.5.3.

2. Placeholders

All UI text of the blocks (button labels, ARIA labels, editor hints) comes from the locale's `placeholders` sheet (Key, Text; Description and Category are for authors) through utils/placeholders.js. Keys match without case or separators; a missing key shows the code's English fallback (not the `/en` sheet's text). Keep `{n}`, `{total}`, `{title}` and similar variables. The key list is in handover Part 4, 4.5 and Part 14, 14.8.3.

3. Screenshots

Screenshot required

- Required screen: Placeholders Guide
- Required role/access: AEM Sites author with Universal Editor (content author)
- Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
- Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
- Owner: Content Lead / AEM Authoring Lead (proposed)
- Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Preview, Publish and Unpublish Guide

Attribute	Value
Document ID	AUT-013
Audience	Content authors, content managers, AEM authoring leads
Purpose	Previewing, publishing, unpublishing and republishing
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	docs/handover/knowledge-base/authoring.md
Related documents	—
Related AEM paths	—

1. Previewing

1. Switch the Universal Editor to **Preview** and check the three device sizes: no editor hints left, hidden blocks gone, animations play.
2. Publish to the preview tier and open `https://main--tcs-corp--sradha-tcs.aem.page/{locale}/{path}`; Lists, Filter Lists, placeholders and taxonomy labels only resolve there (not on author).
3. Use a private window or a cache-busting query to bypass the browser cache.

Which publish destinations the Universal Editor offers in this program (Preview and / or Live) is not recorded (handover Part 5, 5.7.2).

2. Publishing

Task	Where	Verify
One page	Universal Editor **Publish** (keep changed references selected)	Live URL in a private window
Several pages or a branch	Sites console **Manage Publication** (include children; schedule Later)	Sample URLs, `/query-index.json`
Quick publish	Sites console **Quick Publish**	Live URL
A sheet or data sheet	Select the sheet, **Quick Publish**	`/{locale}/{sheet}.json`
Take down	**Manage Publication > Unpublish** (add a redirect first if the URL was public)	The locale's 404 page
Undo a change	**Timeline > Revert to this Version**, then publish	Live URL

Published separately. A change to these items only takes effect when the item itself is published: `references/` pages (nav, footer, fragments), error pages, the sheets (`placeholders`, `metadata`, `taxonomy`, `redirects`), the data sheets (`data/authors`, `locations`, `partners`, `social-links`, `media-contacts`) and assets. A

published nav, footer or fragment change shows on every page that loads it without republishing those pages.

Order when content depends on new code or data. Code first (merged and synced), then sheets (placeholders, taxonomy, data, metadata), then fragments (nav, footer), then pages (handover Part 12, 12.4.2).

Pages under `block-library/` and `site-global-templates/` can't be published (`excludes` of paths.json); during the language master review its block library is published for the review (handover revision 2.20).

3. Corrective publishing

Re-publication after a correction is the verified recovery path, recorded in the handover revision history:

- Package 1.0.9 was published; on `aem.live` the container sections' Additional tab had no effect (re-audit finding R-L-1). The code was corrected (PR #121), package 1.0.10 installed, and its 312 pages previewed, published and reindexed (312 / 312) (handover revisions 2.30, 2.31; REAUDIT-2026-10-20.md).
- Package 1.0.12: one page timed out on its first preview and went through on retry (handover revision 2.35).

For one page: fix the content (or restore a version), check it in Preview mode, publish to preview, verify, then publish to live. If a correction is not visible, check that the referenced item (fragment, sheet, asset) was published too, then escalate to L1 (Admin API status, re-preview and cache operations are for administrators; see administration-and-operations.md).

4. Publishing and the Admin API

- Authors publish from the Universal Editor or the Sites console (authoring.md); sheets, references and non-image assets are published on their own.
- The Edge Delivery Admin API (`https://admin.hlx.page`, authenticated; no credentials are recorded) performs the operations behind publishing. Path segments: org `sradha-tcs`, site `tcs-corp`, ref `main`.

Operation	Endpoint pattern	Use
Status	`GET /status/{org}/{site}/{ref}/{path}`	First check for "page not updating"
Preview	`POST /preview/{org}/{site}/{ref}/{path}`	Re-preview a path
Live	`POST /live/{org}/{site}/{ref}/{path}`	Re-publish a path
Unpublish	`DELETE /live/{org}/{site}/{ref}/{path}`	Emergency takedown when AEM can't unpublish
Cache	`POST /cache/{org}/{site}/{ref}/{path}`	Purge after a confirmed publish
Index	`POST /index/{org}/{site}/{ref}/{path}`	Re-index a path
Sitemap	`POST /sitemap/{org}/{site}/{ref}/{path}`	Regenerate a sitemap
Code	`POST /code/{org}/{site}/{ref}/{path}`	Re-sync code when Code Sync didn't run
Log	`GET /log/{org}/{site}/{ref}`	Who previewed, published, unpublished or synced what
Configuration	`/config/{org}/sites/{site}.json` and sub-resources (`public.json`, `metadata.json`)	Site configuration

Source: handover Part 12, 12.1.9. Admin API operations act immediately on the public site; bulk operations (`/*`) are agreed with the site owner and logged with the before / after JSON (handover Part 17, G-01). Per-

page `preview`, `live` and `index` calls were used to publish and reindex the block library packages (handover revisions 2.31, 2.35).

5. Screenshots

> **Screenshot required**
>
> - Required screen: Preview, Publish and Unpublish Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

6. Known limitations

- None recorded for this document.

7. Open items

- None.

8. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

SEO Authoring Guide

Attribute	Value
Document ID	AUT-015
Audience	Content authors, content managers, AEM authoring leads
Purpose	Titles, descriptions, social and robots metadata for authors
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	decorators/seo-decorator.js
Related documents	—
Related AEM paths	—

1. Metadata model

Purpose. Page-level values (SEO, social, card content, page type, author, dates, flags) that code, the query index and the data layer read. Every value is a `<meta>` in the server-delivered head.

Sources and precedence.

Source	Where authored	Published as
Page properties (`models/_page.json`)	Universal Editor page properties	`<title>`, `description`, `keywords`, `page-type`, `nav`, `footer`, `error-page` metas
Standard AEM page properties	Sites console (e.g. Tags `cq:tags`)	`cq-tags` (one comma-separated meta)
Bulk metadata sheet	`/content/tcs-corp/{country}/{language}/metadata`	`/{locale}/metadata.json`; each column becomes `<meta name="{column}">` on pages matching the row's `url` pattern

Page-level values win over bulk metadata; bulk rows apply top to bottom (handover Part 8.1.2). The bulk sheets apply only once all 13 are listed in the site configuration's `metadata.source`, and each sheet's URL patterns must start with its locale (`/de-de/**`) (AGENTS.md "Notes").

Bulk metadata columns (AGENTS.md, 42 columns): `url`, `page-type`, `meta-title`, `meta-description`, `meta-keywords`, `keyword-action`, `author-id`, `publish-date`, `modified-date`, `reading-time`, `og-title`, `og-description`, `og-image`, `og-type`, `twitter-card`, `twitter-title`, `twitter-description`, `twitter-image`, `canonical-url`, `robots`, `region`, `country`, `language`, `persona`, `thumbnail-image`, `featured-image`, `campaign-id`, `content-type`, `featured`, `priority`, `listen-link`, `author`, `card-title`, `card-description`, `card-image`, `card-image-alt`, `image-alt`, `eyebrow`, `category`, `hide-in-nav`, `card-style`, `card-theme`.

Consumers.

Consumer	Reads	Source
SEO decorator (eager)	`meta-title` → `<title>`; `meta-description`; `meta-keywords` combined with the page dialog's Keywords by `keyword-action` (`default` or empty: the dialog's; `override`: the sheet's; `merge`: both, the dialog's first; `utils/keywords.js`); `og-*` (falling back to `meta-*`); `twitter-*` (falling back to `og-*`, `meta-*`); `canonical-url` → `<link rel="canonical">` and `og:url`; `language` → `<html lang>`	`decorators/seo-decorator.js`
`getPageMetadata()`	title, description, image (`featured-image`, else `og:image`), `page-type` (else `template`), `content-type`, `category`, tags, `author-id`, `author`, `publish-date` (else `publication-date`), `modified-date`, `reading-time`, `listen-link`, `thumbnail-image`, `featured-image`, `image-alt`, `region`, `country` (else the locale's), language, `persona`, `campaign-id`, `featured` (yes / true / 1 / on / y), `priority` (number)	`utils/metadata.js`
`getPageTags()`	`article:tag` metas and `cq-tags`, else a comma-separated `tags` meta	`utils/metadata.js`
`getPageLanguage()`	`language` when it is a language code, else the locale's `lang`	`utils/metadata.js`
Page Header, templates, data layer page entry	`getPageMetadata()`	page-header, `decorators/data-layer-decorator.js`
Query index	the server head (see indexing-and-search.md)	`helix-query.yaml`

Rules. The query index reads the server-delivered head, so values set by JavaScript (the SEO decorator's) aren't indexed (handover Part 8.1.3). `robots` is a standard name and works server side. Use `card-*`, `eyebrow`, `hide-in-nav`, `card-style`, `card-theme` for List cards (List README "Page metadata contract").

Example.

```
url                   | page-type      | hide-in-nav
/de-de/newsroom/**    | press-release  |
/de-de/insights/**    | article        |
/de-de/legal/imprint  |                | yes
```

Common mistakes. A sheet row pattern without the locale prefix; adding columns to a sheet that isn't listed in `metadata.source` (no effect); expecting a metadata change to reach lists before the page is republished and indexed. Field reference per column: handover Part 8 — Metadata Documentation (8.2, 8.4).

2. Screenshots

> **Screenshot required**
>
> - Required screen: SEO Authoring Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

3. Known limitations

- None recorded for this document.

4. Open items

- None.

5. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Taxonomy and Tagging Guide

Attribute	Value
Document ID	AUT-009
Audience	Content authors, content managers, AEM authoring leads
Purpose	Tags, the taxonomy page and how lists use them
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	utils/taxonomy.js
Related documents	—
Related AEM paths	—

1. Taxonomy

Purpose. Tag IDs on pages and in block fields are turned into localised labels at runtime.

Structure. Tags are maintained in AEM Tagging; a taxonomy page per locale (`/content/tcs-corp/{country}/{language}/taxonomy`) is published as `/{locale}/taxonomy.json` with columns `tag` and `title`. With translated titles the JSON is multi-sheet: `loadTaxonomy()` reads the sheet named after the locale's ISO 639-1 language (`de`), else `default`, else the first sheet (`sheetRows`).

Consumers. `resolveTags(values)` (`utils/taxonomy.js`): a value with a taxonomy entry gets its title; a value containing `:` or `/` without an entry gets a label derived from the ID (`parseTag`, `utils/tags.js`); any other value is shown as written. Used by Teaser, Page Header, List, Cards, Filter List and Conversation Canvas.

Rules. The published namespace is `tcs-corp:` (handover Part 7.1.2; finding F-08: some help texts and examples use `tcs:`). Pick tags with the tag picker; the `aem-tag` fields don't restrict the namespace (handover Part 7.1.1). A selected tag also matches its child tags in List (`hasTag`, handover Part 7.2.2).

Example. `tcs-corp:region/europe` → `Europe` from `/en/taxonomy.json`; without a taxonomy entry, an ID-derived label.

Common mistakes. Typing tag IDs by hand; not publishing the locale's taxonomy page (labels fall back to IDs; handover F-09 records that only `/en/taxonomy.json` was published when checked); translating tag titles without republishing the taxonomy page. Governance and lifecycle: handover Part 7 — Taxonomy Documentation.

2. Taxonomy

- Tags are AEM tags (`tcs-corp:` namespace) set in page properties and in block tag fields (Teaser, Cards, List Items, List, Filter List).

- Labels come from the locale's taxonomy page (`/{locale}/taxonomy.json`; a language sheet such as `de` when translated) through utils/taxonomy.js; a tag missing there shows a label derived from its ID.
- Publish the taxonomy page after a change; Lists and Filter Lists match tags from the query index, so republish pages after re-tagging. Governance: handover Part 7 — Taxonomy Documentation.

3. Screenshots

> **Screenshot required**
>
> - Required screen: Taxonomy and Tagging Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages

Versioning and Rollback Guide

Attribute	Value
Document ID	AUT-014
Audience	Content authors, content managers, AEM authoring leads
Purpose	Page versions and restoring an earlier version
Scope	—
Prerequisites	—
Owner	Content Lead / AEM Authoring Lead (proposed)
Approver	Product Owner (to be confirmed)
Version	1.0
Status	Draft for review
Last updated	13 November 2026
Last validated	13 November 2026
Source files	—
Related documents	—
Related AEM paths	—

1. Versions in AEM Sites

1. AEM Sites console: select the page > Timeline (left rail) > select a version > **Restore to this version** (or **Preview version**).
2. Publish the page again so Edge Delivery gets the restored content.
3. A page deleted on author is also removed from Edge Delivery (unpublished): restore it from a version or a content package and publish again.

These are the standard AEM Sites functions; they were not exercised on this author in the program (Requires manual validation).

2. Rollback

No rollback has been recorded; the procedures below are the handover's (Part 12, 12.6) and Require validation.

Stream	Procedure
Code	Revert the merged PR in GitHub (a revert PR, checks, merge) or `git revert -m 1 <merge-commit>` on a branch, newest first; Code Sync deploys the previous code. Never force-push or rewrite `main`
Models	The revert restores partials and aggregated files; authors reload the editor; values saved with removed fields stay stored but aren't shown
Content	Sites console **Timeline > Revert to this Version** (or Restore Version), check, publish again; sheets the same way; unpublish when no good version exists
Configuration	Re-apply the saved JSON (`public.json` paths from a previous `paths.json`: `git show <commit>:paths.json`; the previous `metadata.source` list); repository configuration files by reverting the PR, then re-index or regenerate the sitemap
Content package	Reinstall the previous package version from the `home-content-package` branch (installing replaces the package's pages)

Emergency change approval and the hotfix path are not recorded (handover 12.6.1, Part 17 R-15).

3. Screenshots

> **Screenshot required**
>
> - Required screen: Versioning and Rollback Guide
> - Required role/access: AEM Sites author with Universal Editor (content author)
> - Required navigation steps: AEM Sites console > /content/tcs-corp/language-masters/en > open a page in Universal Editor
> - Reason unavailable: No AEM author access in the documentation program (access blocker AB-01)
> - Owner: Content Lead / AEM Authoring Lead (proposed)
> - Target completion date: To be confirmed

4. Known limitations

- None recorded for this document.

5. Open items

- None.

6. Change history

Version	Date	Author	Change
1.0	13 November 2026	Delivery team (documentation program)	First version of the role-specific documentation (master documentation prompt), generated from the repository and the published reference pages