TCS Corporate Website - Admin Guide

Date: October 11, 2026

Adobe

Table of Contents

TCS Corporate Website - Admin Guide 3
- Quick Reference 4
- Authentication 5
- Verify Configuration 5
- User Management 6
- Site Structure 7
- Path Mapping (`paths.json`) 9
- Bulk Metadata Sources (Required) 11
- Redirects (All Locales) 11
- Adding a Locale 12
- Error Pages 13
- Templates 13
- Content Operations 13
- Publishing Site Data 14
- Robots and Search Engines 15
- Indexing and Sitemap 16
- Code Operations 18
- Project-Specific Configuration 18
- Common Tasks 19
- Troubleshooting 20
- Resources 21

TCS Corporate Website - Admin Guide

Complete administration guide for managing the TCS Corporate Website, an AEM Edge Delivery Services project authored in AEM Sites as a Cloud Service with the Universal Editor.

> **Data source note:** This guide was generated on October 11, 2026. The Config Service API calls (`https://admin.hlx.page/config/sradha-tcs/sites.json` and `.../sites/tcs-corp.json`) returned **401 Unauthorized** because no credentials were used while generating the guide. The site name `tcs-corp` was confirmed through the public preview host (`https://main--tcs-corp--sradha-tcs.aem.page/query-index.json` responds). The code repository and content source come from the repository configuration (`fstab.yaml`, `paths.json`) and were **not** confirmed against the Config Service. After you log in, run the commands in Verify Configuration. In every command, `{your-auth-token}` is a placeholder for your own token.

> **What changed in this edition:** The site now has **13 locale sites**. Each is authored at `/content/tcs-corp/{country}/{language}/` and published at a **language-only URL** (`us/en` → `/en/`, `de/de-de` → `/de-de/`, ...). Each locale has its own references (nav, footer, fragments), error pages, **block library** (author only), placeholders, metadata, taxonomy and data sheets. `paths.json` is **generated** from the locale list (`npm run build:paths`, a developer task). It maps each locale folder, the locale's eight spreadsheets (placeholders, metadata, redirects and the five data sheets) and its taxonomy page. It includes only the 13 locale roots, and excludes every block library and the Site Global Templates. Each locale has its **own redirects sheet** (`/{locale}/redirects.json`), but the platform only applies a root `/redirects.json`, and there is none. **No redirects are applied automatically, including `/` → `/en/`.** Nothing is published at `/`, so set up the redirects at the CDN (see Redirects). Bulk metadata is the same for every locale: each sheet (English included, `/en/metadata.json`) is published at its locale path, and **all 13 sheets must be listed in `metadata.source`**. Until then, no bulk metadata applies. The query index excludes per locale (`/*/references/**`, ...), so a **reindex is required**. The published `/query-index.json` still has the old column set and no entries.

Status at Generation

These public, unauthenticated checks of the preview host (`https://main--tcs-corp--sradha-tcs.aem.page`) were run on October 11, 2026:

URL	Result	Meaning
`/en/`	404	English home not published at its locale path yet (path mapping not applied, or the page is not published)
`/en/metadata.json`	404	English metadata sheet not published at its locale path
`/en/placeholders.json`	404	English placeholders sheet not published at its locale path
`/query-index.json`	200, 0 entries	Index exists, but has the old column set (`pageCategory`, `storyTags`, `timeToRead`, ...) and no pages. Reindex needed
`/config.json`	404	No public configuration (path mapping) applied yet
`admin.hlx.page/config/sradha-tcs/sites.json`	401	Needs login. Not retried with credentials

Work through Configure Path Mapping, Bulk Metadata Sources, Publishing Site Data and Reindex After Changes in that order. Then run the checks again: each URL above (except the Admin API) should return 200, and the query index should list pages under `/en/`, `/de-de/`, ...

Quick Reference

URLs

Purpose	URL
Login	https://admin.hlx.page/login/sradha-tcs/tcs-corp
Config Service	https://admin.hlx.page/config/sradha-tcs/
Preview	https://main--tcs-corp--sradha-tcs.aem.page/
Live	https://main--tcs-corp--sradha-tcs.aem.live/
English home (us/en)	https://main--tcs-corp--sradha-tcs.aem.live/en/
Other locale homes	`https://main--tcs-corp--sradha-tcs.aem.live/{locale}/`, for example `/de-de/`, `/ja-jp/`
Site root	`/` has no content. Needs a CDN redirect to `/en/` (not applied by Edge Delivery Services, see Site Root Redirect)
Code repository	https://github.com/sradha-tcs/tcs-corp
Content source (AEM Author)	https://author-p220207-e2271469.adobeaemcloud.com
Public site config	https://main--tcs-corp--sradha-tcs.aem.page/config.json
Query index	https://main--tcs-corp--sradha-tcs.aem.live/query-index.json
Sitemap	https://main--tcs-corp--sradha-tcs.aem.live/sitemap.xml
Admin edit tool	https://tools.aem.live/tools/admin-edit/index.html

Project Context

Item	Value
Organization	`sradha-tcs`
Site	`tcs-corp`
Setup type	Standard (single site). Not confirmed by the Config Service, see the note above
Code owner / repo	`sradha-tcs` / `tcs-corp` (GitHub)
Branch	`main`
Authoring	AEM Sites as a Cloud Service with Universal Editor (xwalk)

Item	Value
Content mount	`https://author-p220207-e2271469.adobeaemcloud.com/bin/franklin.delivery/sradha-tcs/tcs-corp/main` (type `markup`, suffix `.html`)
Content root	`/content/tcs-corp/{country}/{language}/` mapped to `/{language-code}/` (13 locales, see Locales)
Locales	13: `en`, `de-de`, `fr-fr`, `fr-ca`, `es-es`, `pt-pt`, `nl-nl`, `sv-se`, `da-dk`, `no-no`, `zh-cn`, `ja-jp`, `ko-kr`

Sites

Site	Content Source	Preview	Live
tcs-corp	AEM Author `/content/tcs-corp/` (franklin.delivery), 13 locale folders	https://main--tcs-corp--sradha-tcs.aem.page/en/	https://main--tcs-corp--sradha-tcs.aem.live/en/

All 13 locales are folders of this **one site**. They share the code, the configuration and the query index. They are not separate repoless sites.

Authentication

All Admin API operations (`https://admin.hlx.page`) need an authenticated session or token.

Login

1. Open: https://admin.hlx.page/login/sradha-tcs/tcs-corp
2. Sign in with your Adobe ID (or the identity provider configured for the organization).
3. For command-line use, get an auth token from your session and pass it in the `x-auth-token` header in place of `{your-auth-token}`.

Never commit tokens to the repository or share them in chat, tickets or email.

Logout

```
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/logout/sradha-tcs/tcs-corp/main"
```

Verify Configuration

Run these commands after logging in to confirm the values in this guide.

```
# All sites in the organization (more than one = repoless setup)
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites.json"

# Full site configuration (code, content, access, headers, CDN, metadata, public)
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp.json"
```

```
# Status of the locale home page (preview / live / edit state)
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/status/sradha-tcs/tcs-corp/main/en/"

# Active path mapping and metadata sources
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/public.json"
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/metadata.json"
```

Admin API paths (`/preview`, `/live`, `/cache`, `/index`, `/status`) use the **published** path (`/de-de/about`), not the AEM path (`/content/tcs-corp/de/de-de/about`).

If `sites.json` lists more than one site, the project is **repoless**. Add each site to the Sites table using `https://main--{site}--sradha-tcs.aem.page/` and `https://main--{site}--sradha-tcs.aem.live/`.

User Management

The Config Service controls access to the Admin API, the Sidekick and preview/live operations. Authoring permissions in AEM (Universal Editor, page editing, publishing from AEM, editing sheets) are managed separately in AEM as a Cloud Service through the Adobe Admin Console and AEM user groups.

View Current Access

```
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/access.json"
```

Add User

Role	Command
Admin	`POST /config/sradha-tcs/sites/tcs-corp/access/admin.json` with `{"users": ["email"]}`
Author	`POST /config/sradha-tcs/sites/tcs-corp/access/author.json` with `{"users": ["email"]}`

```
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  -H "Content-Type: application/json" \
  -d '{"users": ["new.admin@example.com"]}' \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/access/admin.json"
```

Remove User

```
curl -X DELETE \
  -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/access/admin/{email}.json"
```

Role Summary

Role	Typical Permissions
Admin	Manage configuration and access, preview, publish, unpublish, purge cache, reindex, sync code
Author	Preview and publish content

Site Structure

The AEM content tree holds **13 locale sites**, one per country and language. Each locale site has its own pages, references, error pages, block library, sheets and data. It is published at a **language-only path**. The country folder is not part of the public URL.

Locales

AEM Folder	Published At	Language Tag		AEM Folder	Published At	Language Tag
`us/en`	`/en/`	en-US		`se/sv-se`	`/sv-se/`	sv-SE
`de/de-de`	`/de-de/`	de-DE		`dk/da-dk`	`/da-dk/`	da-DK
`fr/fr-fr`	`/fr-fr/`	fr-FR		`no/no-no`	`/no-no/`	no-NO
`ca/fr-ca`	`/fr-ca/`	fr-CA		`cn/zh-cn`	`/zh-cn/`	zh-CN
`es/es-es`	`/es-es/`	es-ES		`jp/ja-jp`	`/ja-jp/`	ja-JP
`pt/pt-pt`	`/pt-pt/`	pt-PT		`kr/ko-kr`	`/ko-kr/`	ko-KR
`nl/nl-nl`	`/nl-nl/`	nl-NL				

All AEM folders are under `/content/tcs-corp/`. For example, `/content/tcs-corp/de/de-de/about` is published as `/de-de/about`.

```
/content/tcs-corp/
├── us/en/                    # locale site, published at /en/
│   ├── index                 # Home and the content pages
│   ├── references/           # nav (header), footer, other fragments
│   ├── error-pages/          # 404, 403, 500
│   ├── block-library/        # block validation pages (author only)
│   ├── placeholders          # sheet: Key, Text, Description, Category
│   ├── metadata              # sheet: bulk metadata
│   ├── redirects             # sheet: source, destination (not
│   │                         #   applied by the platform, see Redirects)
│   ├── taxonomy              # taxonomy page (tag, title)
│   └── data/                 # sheets: authors, locations, partners,
│                             #   social-links, media-contacts
├── de/de-de/ ... kr/ko-kr/ # the other 12 locales, same layout
└── site-global-templates/  # template pages (author only)
```

In the table below, `{locale}` is the published code (`en`, `de-de`, ...). The examples use German.

Item	AEM Path (German)	Published As	Notes
Home	`/content/tcs-corp/de/de-de/index`	`/de-de/`	English: `/en/`

Item	AEM Path (German)	Published As	Notes
Header	`.../de/de-de/references/nav`	`/de-de/references/nav`	Default nav. Pages can use another nav through the Navigation page property or the `nav` column of the metadata sheet
Footer	`.../de/de-de/references/footer`	`/de-de/references/footer`	Default footer. Overridable like the nav (Footer property or `footer` column)
Fragments	`.../de/de-de/references/...`	`/de-de/references/...`	Reference pages loaded by other pages
Error pages	`.../de/de-de/error-pages/{404,403,500}`	`/de-de/error-pages/{404,403,500}`	See Error Pages
Placeholders	`.../de/de-de/placeholders`	`/de-de/placeholders.json`	UI text for blocks
Bulk metadata	`.../de/de-de/metadata`	`/de-de/metadata.json`	English: `/en/metadata.json`. All 13 sheets must be in `metadata.source`
Taxonomy	`.../de/de-de/taxonomy`	`/de-de/taxonomy.json`	Mapped per locale in `paths.json`
Redirects	`.../de/de-de/redirects`	`/de-de/redirects.json`	One sheet per locale. **Not applied by Edge Delivery Services** (it only reads a root `/redirects.json`). See Redirects
Data sheets	`.../de/de-de/data/{name}`	`/de-de/data/{name}.json`	authors, locations, partners, social-links, media-contacts
Block Library	`.../de/de-de/block-library/`	not published	Every block variation, to check blocks in the locale's language on author
Site Global Templates	`/content/tcs-corp/site-global-templates/`	not published	Template pages authors copy (home, article, blog, press release)

The site code works out the locale from the page path. In the Universal Editor it uses the AEM path (`/content/tcs-corp/de/de-de/...`). On the published site it uses the language path (`/de-de/...`). It then loads that locale's nav, footer, error pages, placeholders, taxonomy and data sheets, and sets `<html lang>` (`de-DE`). Pages outside a locale (Site Global Templates) use English (`en`).

Block Library per Locale

Each locale has its own `block-library/` with a page for every block variation, in that locale's language. Authors and developers use it on AEM author to check how blocks look with translated content: text length, CJK fonts, placeholders. The `paths.json` excludes stop it from being published. If an author tries to publish it, the publish is skipped or fails. This is expected.

Data Sheets

Sheet	Columns	Used By
`authors`	author-id, name, designation, bio, image, linkedin, region	Page Header and "About the author" (article / blog templates), matched by the page's `author-id`
`locations`	location-id, location-name, country, region, latitude, longitude	Location blocks
`partners`	partner-id, partner-name, logo, website, tier, description	Partner blocks

Sheet	Columns	Used By
`social-links`	platform, url, icon, sort-order	Footer social links
`media-contacts`	id, name, designation, email, phone, region	"Media contacts" on press releases (the page's `region`, else all)

If a sheet is missing or not published, the site shows the content without that data.

Path Mapping (`paths.json`)

Path mapping controls how AEM paths map to public URLs and which content AEM publishes to Edge Delivery Services. Its current definition is in `paths.json` in the repository. The file is **generated** from the `LOCALES` list in `utils/site.js` with `npm run build:paths` (`tools/paths/generate-paths.mjs`). This is a developer task: do not edit `paths.json` by hand. An excerpt (the first locale's entries):

```
{
  "mappings": [
    "/content/tcs-corp/us/en/:/en/",
    "/content/tcs-corp/de/de-de/:/de-de/",
    "... the other 10 locale folders ...",
    "/content/tcs-corp/kr/ko-kr/:/ko-kr/",
    "/content/tcs-corp/us/en/placeholders:/en/placeholders",
    "/content/tcs-corp/us/en/metadata:/en/metadata",
    "/content/tcs-corp/us/en/redirects:/en/redirects",
    "/content/tcs-corp/us/en/data/authors:/en/data/authors",
    "/content/tcs-corp/us/en/data/locations:/en/data/locations",
    "/content/tcs-corp/us/en/data/partners:/en/data/partners",
    "/content/tcs-corp/us/en/data/social-links:/en/data/social-links",
    "/content/tcs-corp/us/en/data/media-contacts:/en/data/media-contacts",
    "/content/tcs-corp/us/en/taxonomy:/en/taxonomy.json",
    "... the same nine entries for each of the other 12 locales ..."
  ],
  "includes": [
    "/content/tcs-corp/us/en/",
    "/content/tcs-corp/de/de-de/",
    "... the other 10 locale roots ...",
    "/content/tcs-corp/kr/ko-kr/"
  ],
  "excludes": [
    "/content/tcs-corp/us/en/block-library",
    "/content/tcs-corp/us/en/block-library/**",
    "/content/tcs-corp/de/de-de/block-library",
    "/content/tcs-corp/de/de-de/block-library/**",
    "... the same two entries for each of the other 10 locales ...",
    "/content/tcs-corp/kr/ko-kr/block-library",
    "/content/tcs-corp/kr/ko-kr/block-library/**",
    "/content/tcs-corp/site-global-templates",
    "/content/tcs-corp/site-global-templates/**"
  ]
}
```

The lists are shortened here. The file has 130 mappings (13 locale folders, then 9 entries per locale), 13 includes (the locale roots) and 28 excludes: two per locale (`block-library` and `block-library/**`) and two for `site-global-templates`.

Rule	Effect
13 locale mappings (`/content/tcs-corp/de/de-de/:/de-de/`)	Each locale is published at its language path. The country folder is dropped: `/content/tcs-corp/de/de-de/about` becomes `/de-de/about`
104 spreadsheet mappings, 8 per locale (`.../de/de-de/data/authors:/de-de/data/authors`)	The locale's `placeholders`, `metadata`, `redirects` and data sheets (`data/authors`, `data/locations`, `data/partners`, `data/social-links`, `data/media-contacts`). The platform appends `.json`: `/de-de/placeholders.json`, `/de-de/data/authors.json`
13 taxonomy mappings (`.../de/de-de/taxonomy:/de-de/taxonomy.json`)	Each locale's taxonomy page (not a sheet) is published as JSON. Taxonomy mappings need the explicit `.json`
`includes` (13 locale roots)	Only content inside a locale folder is published. `/content/tcs-corp` itself and the country folders (`/content/tcs-corp/de/`) are not published
`excludes`	Each locale's Block Library and the Site Global Templates stay on AEM author only

All sheets are published at their locale path (`/de-de/placeholders.json`, `/en/metadata.json`, `/de-de/redirects.json`). There is no root `/metadata.json` and no root `/redirects.json`. Mappings use prefix matching, and the last matching entry wins. That is why the sheet and taxonomy entries come after the locale folder entries.

Site Root Redirect (Required)

No mapping catches `/`, so `https://{domain}/` has no content. Edge Delivery Services does **not** redirect `/` to `/en/`: it only applies a root `/redirects.json`, and this site has none (redirects are per locale, see Redirects). **Add a CDN rule** that redirects `/` to `/en/` (301, or 302 if a language picker or geo-based routing may replace it later). Check it on the production domain. `https://main--tcs-corp--sradha-tcs.aem.live/` is not behind your CDN and keeps showing no content.

Configure Path Mapping in the Config Service

Path mapping for AEM authoring is applied through the **configuration service** (the site's `public.json`). The repository's `paths.json` is the reference definition. Apply it, or any change to it, with the admin edit tool (https://tools.aem.live/tools/admin-edit/index.html) or the Admin API. To avoid copying 171 entries (130 mappings, 13 includes, 28 excludes) by hand, send the file itself:

```
# Run from the repository root; wraps paths.json as {"paths": {...}}
jq '{paths: .}' paths.json | curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  -H "Content-Type: application/json" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/public.json" \
  --data @-
```

If the site's `public.json` already has other keys, merge them in first (`GET` the current file, replace only `paths`, then `POST`). Check the active configuration at https://main–tcs-corp–sradha-tcs.aem.page/config.json. When this guide was generated, that URL returned 404, so no public configuration had been applied yet. Until it is applied, AEM publishes with the old mapping and pages do not appear under `/en/`, `/de-de/`, … **Keep the Config Service and `paths.json` in sync.** When you change one, change the other.

Bulk Metadata Sources (Required)

Bulk metadata is the same for every locale: each locale's sheet is published at its own path, English included (`/en/metadata.json`). By default the platform reads only a root `/metadata.json`, and this site has none. **Until all 13 sheets are listed in the site configuration's `metadata.source`, no bulk metadata applies**, including the `robots noindex` rows. Set the full list of 13 through the Admin API:

```
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  -H "Content-Type: application/json" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/metadata.json" \
  --data '{
    "source": [
      "/en/metadata.json",
      "/de-de/metadata.json",
      "/fr-fr/metadata.json",
      "/fr-ca/metadata.json",
      "/es-es/metadata.json",
      "/pt-pt/metadata.json",
      "/nl-nl/metadata.json",
      "/sv-se/metadata.json",
      "/da-dk/metadata.json",
      "/no-no/metadata.json",
      "/zh-cn/metadata.json",
      "/ja-jp/metadata.json",
      "/ko-kr/metadata.json"
    ]
  }'

# Check
curl -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/config/sradha-tcs/sites/tcs-corp/metadata.json"
```

- Sheets are applied in list order. A later sheet overwrites a property set by an earlier one (unless the later value is empty), but never deletes it. Values on the page itself (page properties) win over all sheets.
- Each sheet's `url` patterns must start with its own locale (`/de-de/**`, `/de-de/newsroom/**`). Every sheet is applied to every page, so a pattern like `/**` in the German sheet would also change English pages.
- Publish each sheet, then republish the affected pages so the values are in their HTML and the query index.

Redirects (All Locales)

Each locale has its own redirects sheet (`source`, `destination`) at `/content/tcs-corp/{country}/{language}/redirects`, published as `/{locale}/redirects.json` (`/en/redirects.json`, `/de-de/redirects.json`, ...). This was chosen deliberately, so that each locale's authors manage their own redirects.

> **Important:** Edge Delivery Services only applies a root `/redirects.json`, and there is no setting to add other sheets. This site has no root sheet, so **no redirects are applied automatically**: not the per-locale sheets, not `/` → `/en/`, and not old `/us/en/...` URLs.

Admin action, one of:

- **CDN redirects (recommended):** a CDN rule or edge worker that, for a request under `/{locale}/`, reads `/{locale}/redirects.json` (cache it) and answers matching `source` paths with a 301 to `destination`. Add a

fixed rule for `/` → `/en/` (see Site Root Redirect), and rules or a sheet for old `/us/en/...` URLs (`/us/en/about` → `/en/about`).

- **Decide later to map one sheet to the root:** a developer changes `paths.json` so that one sheet (for example the English one) is published as `/redirects` (`/redirects.json`). That sheet would then have to hold the redirects of all locales, with full published paths.

Authors keep full published paths in the `source` column (`/de-de/alte-seite` → `/de-de/neue-seite`). Redirects should only apply where no published page exists at the source path. Publish the sheet after each change, and test on the production domain (the CDN), not on `*.aem.live`.

Adding a Locale

Adding a locale needs work by authors, a developer and an admin. Example: `it/it-it` published at `/it-it/`.

	Step	Who	What
1.	AEM folder	Author / admin	Create `/content/tcs-corp/it/it-it/` with the same layout as the others: `index`, `references/nav`, `references/footer`, `error-pages/404` (and 403, 500), `block-library/`, `placeholders`, `metadata`, `redirects`, `taxonomy`, `data/` sheets. Copying `us/en` (or a closer language) and translating it is the simplest way
2.	Code	Developer	Add `{ country: 'it', code: 'it-it', lang: 'it-IT' }` to LOCALES in `utils/site.js`, run `npm run build:paths` to regenerate `paths.json` (locale, sheet and taxonomy mappings, include, block-library excludes), commit both and merge to `main`
3.	Path mapping	Admin	Apply the updated `paths.json` to the Config Service (see Configure Path Mapping) and check `/config.json`
4.	Metadata source	Admin	Add `/it-it/metadata.json` to `metadata.source` (POST the full list, now 14 entries, see Bulk Metadata Sources). Without it, the new locale's metadata sheet has no effect
5.	Redirects and robots	Admin	Extend the CDN redirect rules to the new locale (`/it-it/redirects.json`, see Redirects). Add `noindex` rows to the locale's metadata sheet (see Robots and Search Engines)
6.	Publish	Author	Publish the pages, nav, footer, error pages, placeholders, metadata, redirects, taxonomy and data sheets (see Publishing Site Data), then check the index

The query index needs no change: its `/*/...` patterns already cover every locale.

Error Pages

Code	How It Is Served
404	Edge Delivery Services serves `404.html` (in the repository) for every unknown URL. `404.html` loads the authored error page of the requested URL's locale, for example `/de-de/error-pages/404` for `/de-de/missing-page` and `/ja-jp/error-pages/404` for `/ja-jp/missing-page`. URLs outside a locale use English (`/en/error-pages/404`). If the authored page is not published, the built-in "Page Not Found" content is shown. The Go home button leads to the locale's home page (`/de-de/`)
403	`/{locale}/error-pages/403` is a regular page. Edge Delivery Services does not serve it automatically. **Configure it in the CDN** as the custom response for 403
500	`/{locale}/error-pages/500` is a regular page. **Configure it in the CDN** as the custom response for 500 / origin errors. Many CDNs need a static copy, because the origin may be unavailable when a 500 occurs

For 403 and 500, the CDN can choose the locale from the first path segment (`/de-de/...` → `/de-de/error-pages/500`), falling back to `/en/error-pages/...`.

Admin checklist:

1. Make sure `error-pages/404`, `403` and `500` exist in **each of the 13 locales** and are **published**.
2. Open a missing URL on `*.aem.live` for a few locales (for example `https://main--tcs-corp--sradha-tcs.aem.live/de-de/does-not-exist`) and check that the authored 404 appears in the right language.
3. When the production CDN is set up, configure the 403 and 500 responses to serve the matching locale's error pages.
4. Add `noindex` rows for error pages (see Robots and Search Engines). They are already excluded from the query index and sitemap.

Templates

Site Global Templates (`/content/tcs-corp/site-global-templates/`) are author-only pages that authors copy into a locale to create new pages. They are shared by all 13 locales and excluded from publishing. A page's **Page Type** (a page property, or else the `page-type` column of the metadata sheet) selects the template code:

Page Type	Adds
`home`	Layout styles only
`article`	Page Header from page metadata, "About the author" from the Authors sheet
`blog`	Same structure as article
`press-release`	Page Header, "Media contacts" from the Media Contacts sheet

A new template needs a code change (see `templates/README.md`) and a template page under Site Global Templates.

Content Operations

Authors normally preview and publish from **AEM (Universal Editor / Sites console)**. AEM pushes content to Edge Delivery Services through the `franklin.delivery` endpoint. Use the Admin API operations below for bulk actions, recovery or automation.

Preview

Operation	Endpoint
Single page	`POST /preview/sradha-tcs/tcs-corp/main/{path}`
Bulk preview	`POST /preview/sradha-tcs/tcs-corp/main/*`

```
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/preview/sradha-tcs/tcs-corp/main/de-de/"
```

Use the published path (`/de-de/`, `/en/about`), not the AEM path. To work on one locale only, use its path prefix with `/*`, for example `POST /live/sradha-tcs/tcs-corp/main/de-de/*`.

Publish

Operation	Endpoint
Single page	`POST /live/sradha-tcs/tcs-corp/main/{path}`
Bulk publish	`POST /live/sradha-tcs/tcs-corp/main/*`
Unpublish	`DELETE /live/sradha-tcs/tcs-corp/main/{path}`

Cache

Operation	Endpoint
Purge path	`POST /cache/sradha-tcs/tcs-corp/main/{path}`
Purge all	`POST /cache/sradha-tcs/tcs-corp/main/*`

Publishing Site Data

Sheets and the taxonomy have **no effect on the website until they are published**. Previewing makes a change visible on `*.aem.page` only. Publishing makes it visible on `*.aem.live` and the production domain. Publish again after **every** change.

Each of the 13 locales has its own set. The table uses German (`de-de`). For English, replace `/de-de/` with `/en/`.

Item (per locale)	Check After Publishing	Notes
Metadata	`/de-de/metadata.json` (English: `/en/metadata.json`)	Must also be in `metadata.source`. Republish the affected pages afterwards so the metadata is in their HTML and the query index
Redirects	`/de-de/redirects.json`	Not applied by Edge Delivery Services. Takes effect only through the CDN redirect

Item (per locale)	Check After Publishing	Notes
		rules; test on the production domain
Taxonomy	`/de-de/taxonomy.json`	Republish after every tag change (add, rename, translate) and after changing the selected tags
Placeholders	`/de-de/placeholders.json`	Blocks fall back to built-in English text when a key is missing or the sheet is unpublished
Data sheets	`/de-de/data/authors.json` (etc.)	Publish each of the five sheets
Nav / Footer	`/de-de/references/nav`, `/de-de/references/footer`	Header and footer are empty if not published
Error pages	`/de-de/error-pages/404` (etc.)	The built-in 404 shows if not published

To publish, use **Quick Publish** or **Manage Publication** in the AEM Sites console. If a JSON URL returns 404, check that the page name and location match the structure above, that the path mapping is applied, and that the page is published. If a change does not appear, purge the cache for that path:

```
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/cache/sradha-tcs/tcs-corp/main/de-de/placeholders.json"
```

Bulk Metadata Columns

Every locale's metadata sheet supports these columns. Each column is published as `<meta name="{column}">` on matching pages:

`url`, `page-type`, `meta-title`, `meta-description`, `meta-keywords`, `author-id`, `publish-date`, `modified-date`, `reading-time`, `og-title`, `og-description`, `og-image`, `og-type`, `twitter-card`, `twitter-title`, `twitter-description`, `twitter-image`, `canonical-url`, `robots`, `region`, `country`, `language`, `persona`, `thumbnail-image`, `featured-image`, `campaign-id`, `content-type`, `featured`, `priority`, `nav`, `footer`

`url` holds the full published path or pattern, starting with the sheet's own locale (`/de-de/newsroom/**`, `/en/newsroom/**`). Page properties (Title, Description, Keywords, Page Type, Navigation, Footer) win over the sheet.

Robots and Search Engines

`*.aem.page` and `*.aem.live` always disallow all robots. On the production domain, `robots.txt` comes from the site configuration (`POST /config/sradha-tcs/sites/tcs-corp/robots.txt`, or https://tools.aem.live/tools/robots-edit/index.html).

Pages that are not real content pages should not be indexed by search engines. Add these rows to **each locale's metadata sheet**, using that locale's prefix, and publish it. The rows only apply once the sheet is listed in `metadata.source` (see Bulk Metadata Sources). German sheet example:

url	robots
`/de-de/error-pages/**`	`noindex, nofollow`
`/de-de/references/**`	`noindex, nofollow`
`/de-de/data/**`	`noindex, nofollow`

In the English sheet, use `/en/error-pages/**`, `/en/references/**` and `/en/data/**`. The `robots` column is a standard meta tag and works server side. Data sheets are delivered as JSON, where a meta tag does not apply. If they must also be hidden from crawlers, add an `x-robots-tag: noindex` response header for `/*/data/**` in the site's headers configuration (`/config/sradha-tcs/sites/tcs-corp/headers.json`).

Indexing and Sitemap

File	Purpose
`helix-query.yaml`	Builds `/query-index.json` from published pages
`helix-sitemap.yaml`	Builds `/sitemap.xml` from `/query-index.json` (lastmod `YYYY-MM-DD`)

There is **one index and one sitemap for all 13 locales**. Every entry's `path` starts with its locale (`/de-de/...`). Use the `language` and `country` columns, or the path prefix, to filter one locale.

Excluded from the Index (and Sitemap)

The `/*/` patterns match every locale root (`/en/`, `/de-de/`, ...):

Pattern	Content
`/**.json`	All sheets
`/*/references/**`	Nav, footer, fragments and reference pages of every locale
`/*/error-pages/**`	Error pages of every locale
`/*/data/**`	Data sheets of every locale
`/*/nav`, `/*/footer`	Nav and footer at a locale root
`/*/block-library`, `/*/block-library/**`	Each locale's Block Library (not published, excluded as a safe-guard)
`/site-global-templates/**`	Templates (not published, excluded as a safeguard)
`/**/fragments/**`, `/**/modals/**`	Fragment and modal pages anywhere

Sitemap

`/sitemap.xml` lists all published, indexed pages of all locales in one file. It has no language alternates. A follow-up could split it into per-language sitemaps with `hreflang` alternates (a `languages` section in `helix-sitemap.yaml` that links matching pages across locales), plus a sitemap index. This needs matching page paths across locales or an alternate-path mapping, so plan it with the developer. Until then, submit `/sitemap.xml` in Google Search Console for the production domain.

Indexed Properties

Property	Source
`lastModified`	`last-modified` header
`robots`, `title`, `description`, `image`, `tags`	Standard head tags (`robots`, `og:title`, `description`, `og:image`, `article:tag`)
`metaTitle`, `metaDescription`	`meta-title`, `meta-description`
`pageType`, `contentType`	`page-type`, `content-type`
`authorId`, `publishDate`, `modifiedDate`, `readingTime`	`author-id`, `publish-date`, `modified-date`, `reading-time`
`thumbnailImage`, `featuredImage`	`thumbnail-image`, `featured-image`
`region`, `country`, `language`, `persona`	Same-named metadata columns
`campaignId`, `featured`, `priority`	`campaign-id`, `featured`, `priority`

Reindex After Changes (Required Now)

The published `/query-index.json` still has the previous column set and no entries. After the new code is on `main`, do these steps in order:

1. Apply the path mapping (see Configure Path Mapping) and set `metadata.source` (see Bulk Metadata Sources).
2. Publish the **metadata sheets of all 13 locales**, so pages get their `page-type`, `author-id`, `publish-date` and other values.
3. Republish all pages from AEM, so they are published at their new language paths (`/en/...`, `/de-de/...`) and indexed. Or use the Admin API:

```
# Reindex a single page (published path)
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/index/sradha-tcs/tcs-corp/main/de-de/{path}"

# Or republish one locale (repeat for each of the 13 prefixes) ...
curl -X POST -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/live/sradha-tcs/tcs-corp/main/de-de/*"

# ... or everything, which also updates the index
curl -X POST -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/preview/sradha-tcs/tcs-corp/main/*"
curl -X POST -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/live/sradha-tcs/tcs-corp/main/*"
```

4. If any entries are now excluded or outdated (references, error pages, data, or pages under the old paths `/us/en/...`), remove them. At generation the index had no entries and `/us/en/` returned 404, so there may be nothing to clean up. Unpublish the old paths (`DELETE /live/sradha-tcs/tcs-corp/main/us/en/{path}`), then reindex them. If old URLs had traffic, add CDN redirects (`/us/en/{path}` → `/en/{path}`, see Redirects).
5. Check `https://main--tcs-corp--sradha-tcs.aem.live/query-index.json` (new columns such as `pageType` and `authorId`, paths under `/en/`, `/de-de/`, ..., no references or error pages) and `/sitemap.xml`.

Pages are added to the index when they are **published**. Reindex again whenever `helix-query.yaml` changes or metadata sheet changes affect many pages.

Code Operations

Item	Value
Repository	https://github.com/sradha-tcs/tcs-corp
Default branch	`main`
CI	GitHub Actions `.github/workflows/main.yaml` runs lint on every push
Code sync	The AEM Code Sync GitHub App syncs every push automatically

Every branch gets its own preview: `https://{branch}--tcs-corp--sradha-tcs.aem.page/`.

Sync Code

If an automatic sync did not happen, trigger it manually:

```
curl -X POST \
  -H "x-auth-token: {your-auth-token}" \
  "https://admin.hlx.page/code/sradha-tcs/tcs-corp/main"
```

Configuration Files with Admin Impact

File	Admin Impact
`paths.json`	Reference path mapping (13 locales), generated by `npm run build:paths`. Apply changes to the Config Service (`public.json`)
`utils/site.js`	`LOCALES`: the 13 locales (AEM folder, published code, language tag). `paths.json` is generated from it
`tools/paths/generate-paths.mjs`	Generator behind `npm run build:paths`
`helix-query.yaml`	Index definition. Reindex after changes
`helix-sitemap.yaml`	Sitemap definition (from the query index)
`404.html`	404 page. Loads the locale's authored `error-pages/404`
`fstab.yaml`	Content source mount (AEM author `franklin.delivery`)
`head.html`	Strict nonce-based Content Security Policy, moved to an HTTP header
`.hlxignore`	Files never served: `.*`, `*.md`, `karma.config.js`, `LICENSE`, `package*.json`, `test/*`, `_*`
`tools/sidekick/config.json`	Sidekick **AEM Editor** button that opens the page in AEM
`well-known/adobe/cloudmanager-challenge.txt`	Cloud Manager domain verification. Keep while domain setup is active

Project-Specific Configuration

These configurations could not be read because the API returned 401. Check them after logging in:

Configuration	Endpoint
Path mapping	`GET /config/sradha-tcs/sites/tcs-corp/public.json` (or public / `config.json`)
Metadata sources	`GET /config/sradha-tcs/sites/tcs-corp/metadata.json` (should list all 13 sheets)
Custom HTTP headers	`GET /config/sradha-tcs/sites/tcs-corp/headers.json`
CDN (production domain)	`GET /config/sradha-tcs/sites/tcs-corp/cdn.json`
robots.txt	`GET /config/sradha-tcs/sites/tcs-corp/robots.txt`
Access control	`GET /config/sradha-tcs/sites/tcs-corp/access.json`

When the production domain goes live, record the CDN type, the purge credentials setup, and the 403 / 500 error page configuration here.

Common Tasks

Task	Steps
Add new admin	POST to `/config/sradha-tcs/sites/tcs-corp/access/admin.json`
Republish site	POST to `/preview/sradha-tcs/tcs-corp/main/*` then `/live/sradha-tcs/tcs-corp/main/*`
Clear all cache	POST to `/cache/sradha-tcs/tcs-corp/main/*`
Deploy code changes	Merge to `main` (auto-sync), or POST to `/code/sradha-tcs/tcs-corp/main`
Change path mapping	Developer regenerates `paths.json` (`npm run build:paths`), then POST it as `paths` to `/config/sradha-tcs/sites/tcs-corp/public.json`. Check `/config.json`
Add a locale	AEM folder, then `utils/site.js` `LOCALES` and `npm run build:paths` (developer), apply the path mapping, add the sheet to `metadata.source`, extend the CDN redirect rules, publish the pages and sheets (see Adding a Locale)
Activate bulk metadata	POST the full 13-entry `source` list (`/en/metadata.json`, `/de-de/metadata.json`, …) to `/config/sradha-tcs/sites/tcs-corp/metadata.json`. Without it, no bulk metadata applies
Redirect the site root	CDN rule `/` → `/en/` (Edge Delivery Services does not apply it, see Site Root Redirect)
Add or change a redirect	Edit the locale's `redirects` sheet (full published paths), publish. Takes effect only through the CDN redirect rules; test on the production domain
Republish one locale	POST to `/live/sradha-tcs/tcs-corp/main/{locale}/*` (for example `de-de/*`)
Change UI text	Edit the locale's `placeholders` sheet (Key / Text), publish
Set metadata for a group of pages	Add a `url` pattern row in the locale's metadata sheet, publish it, republish the affected pages

Task	Steps
Use a different nav / footer for a section	Create the page under `references/`, set the `nav` / `footer` column for the URL pattern in the metadata sheet, publish both
Show a new tag label	Create the tag in the Tagging console, include it in the taxonomy page, republish the taxonomy
Update authors, partners, locations, social links, media contacts	Edit the sheet under the locale's `data/`, publish
Fix a missing listing entry	Republish the page so it is reindexed

Troubleshooting

Issue	Solution
401 Unauthorized	Token expired or missing: log in again at https://admin.hlx.page/login/sradha-tcs/tcs-corp
403 Forbidden	Insufficient permissions: check your role in `access.json`
404 Not Found (Admin API)	Check org/site/path spelling. Use the published path (`/de-de/...`), and check that the AEM page is inside one of the 13 locale folders and not excluded
Site root `/` shows 404	Expected on `*.aem.page` / `*.aem.live`. On the production domain, add the CDN rule `/` → `/en/`
Pages still under `/us/en/...`	The path mapping is not applied yet. POST `paths.json` to `public.json`, then republish. Unpublish the old paths
Page outside a locale folder cannot be published	Expected: only the 13 locale roots are in `includes`
429 Rate Limited	Wait and retry, and batch bulk operations
Cache not clearing	Try with `forceUpdate: true`
Code not syncing	POST to `/code/sradha-tcs/tcs-corp/main`, and check that the AEM Code Sync app is installed on the repo
Content not updating from AEM	Check that the `franklin.delivery` mount is reachable and the page was published in AEM
Block Library or template page cannot be published	Expected: they are excluded in the path mapping and used on author only
`/de-de/redirects.json`, `/de-de/metadata.json` or `/de-de/taxonomy.json` returns 404	Check that the path mapping is applied in the Config Service (`/config.json`), that the sheet or page is at the expected AEM path (`/content/tcs-corp/de/de-de/...`), and that it is published. `/metadata.json` and `/redirects.json` at the root are expected to return 404
Bulk metadata (of any locale, English included) not applied	Add its sheet (`/en/metadata.json`, `/de-de/metadata.json`) to `metadata.source` (Admin API), publish the sheet, republish the pages
One locale's metadata changes another locale	A `url` pattern in that sheet is not limited to its locale (`/**`). Use `/de-de/**`
Redirect not working	Edge Delivery Services does not apply the per-locale sheets. Check that the CDN redirect rules are in place and read `/{locale}/redirects.json`, that the sheet is published, that `source` uses full published paths (`/de-de/old`), and test on the production domain, not `*.aem.live`
Wrong language for nav, placeholders or `<html lang>`	Check that `utils/site.js` LOCALES and `paths.json` list the locale with the same code (regenerate with `npm run build:paths`)
Header or footer empty	Publish the locale's `references/nav` / `references/footer` (or the configured nav / footer page)

Issue	Solution
Built-in 404 instead of the authored one	Publish the locale's `error-pages/404`
403 / 500 show generic CDN pages	Configure the CDN to serve the locale's `/{locale}/error-pages/403` and `/500` (fallback `/en/...`)
UI text shows the English default	The key is missing or misspelled, or the locale's placeholders sheet is not published
Tags show IDs or ID-derived labels	The tag is not in the taxonomy page, or the taxonomy was not republished
Author, contacts or social links missing	Publish the matching sheet under the locale's `data/` and check the IDs (`author-id`, `region`)
References or error pages in the sitemap / query index	Reindex those paths after the new `helix-query.yaml` is on `main`
Query index has old columns	Reindex (see Reindex After Changes)
Lint failure blocks PR	Run `npm run lint:fix` locally and push again

Resources

Resource	URL
Admin API Docs	https://www.aem.live/docs/admin.html
Config Service	https://www.aem.live/docs/config-service-setup
Path Mapping	https://www.aem.live/developer/authoring-path-mapping
AEM Authoring	https://www.aem.live/docs/aem-authoring
Spreadsheets with AEM authoring	https://www.aem.live/docs/authoring-tabular-data
Taxonomy with AEM authoring	https://www.aem.live/docs/authoring-taxonomy
Bulk Metadata	https://www.aem.live/docs/bulk-metadata
Placeholders	https://www.aem.live/docs/placeholders
Redirects	https://www.aem.live/docs/redirects
Custom Error Pages	https://www.aem.live/docs/custom-error-pages
Indexing	https://www.aem.live/developer/indexing
Sitemaps	https://www.aem.live/developer/sitemap