

```
show databases;
```

```
create database windowsdb;
```

```
use windowsdb;
```

```
CREATE TABLE orders (  
    order_id INT,  
    order_date DATE,  
    customer_id INT,  
    customer_name VARCHAR(50),  
    city VARCHAR(30),  
    category VARCHAR(30),  
    product VARCHAR(50),  
    quantity INT,  
    amount DECIMAL(10,2)  
);
```

```
INSERT INTO orders
```

```
(order_id, order_date, customer_id, customer_name, city, category, product, quantity,  
amount)
```

```
VALUES
```

```
(1001, '2026-01-05', 201, 'Amit', 'Jaipur', 'Electronics', 'Laptop', 1, 65000),
```

```
(1002, '2026-01-10', 202, 'Neha', 'Delhi', 'Electronics', 'Mobile', 2, 50000),
```

```
(1003, '2026-01-15', 201, 'Amit', 'Jaipur', 'Furniture', 'Chair', 4, 12000),
```

```
(1004, '2026-01-20', 203, 'Rahul', 'Mumbai', 'Electronics', 'Headphones', 3, 9000),
```

```
(1005, '2026-01-25', 204, 'Priya', 'Delhi', 'Clothing', 'Jacket', 2, 8000),
```

```
(1006, '2026-02-03', 201, 'Amit', 'Jaipur', 'Electronics', 'Mobile', 1, 28000),
```

```
(1007, '2026-02-08', 202, 'Neha', 'Delhi', 'Furniture', 'Table', 1, 15000),
```

```

(1008, '2026-02-12', 203, 'Rahul', 'Mumbai', 'Clothing', 'Shoes', 2, 10000),
(1009, '2026-02-18', 205, 'Vikas', 'Pune', 'Electronics', 'Laptop', 1, 70000),
(1010, '2026-02-25', 204, 'Priya', 'Delhi', 'Furniture', 'Sofa', 1, 35000),

(1011, '2026-03-02', 201, 'Amit', 'Jaipur', 'Clothing', 'Shirt', 5, 7500),
(1012, '2026-03-07', 202, 'Neha', 'Delhi', 'Electronics', 'Headphones', 2, 6000),
(1013, '2026-03-11', 203, 'Rahul', 'Mumbai', 'Electronics', 'Laptop', 1, 68000),
(1014, '2026-03-16', 205, 'Vikas', 'Pune', 'Furniture', 'Chair', 6, 18000),
(1015, '2026-03-21', 204, 'Priya', 'Delhi', 'Clothing', 'Shoes', 1, 5500),

(1016, '2026-04-04', 201, 'Amit', 'Jaipur', 'Electronics', 'Tablet', 1, 22000),
(1017, '2026-04-09', 202, 'Neha', 'Delhi', 'Clothing', 'Jacket', 1, 4500),
(1018, '2026-04-14', 203, 'Rahul', 'Mumbai', 'Furniture', 'Table', 2, 30000),
(1019, '2026-04-20', 205, 'Vikas', 'Pune', 'Electronics', 'Mobile', 2, 52000),
(1020, '2026-04-27', 204, 'Priya', 'Delhi', 'Electronics', 'Laptop', 1, 72000);

```

```
select * from orders;
```

```
select customer_id, customer_name, order_id, order_date, row_number()
over(partition by customer_id) from orders ;
```

```
select order_id, customer_id, amount, row_number() over(order by amount desc)
from orders ;
```

```
select category , order_id, amount, rank() over(partition by category order by amount
desc) from orders;
```

```
select order_id, category , amount, avg(amount) over(partition by category),
round(amount-avg(amount) over(partition by category) )
from orders;
```

```
select * from  
( select customer_name, order_id, amount, max(amount) over(partition by  
customer_id ) as customer_max  
from orders)as t  
where amount = customer_max;
```

-- or

```
select * from  
( select customer_name, order_id, amount, rank() over(partition by customer_id  
order by amount desc) as customer_rank  
from orders)as t  
where customer_rank = 1 ;
```

```
select * from  
( select customer_name, order_id, amount, rank() over(partition by customer_id  
order by amount desc) as customer_rank  
from orders)as t  
where customer_rank <= 2 ;
```

```
select * from  
( select customer_name, order_id, amount, rank() over(partition by customer_id  
order by amount desc) as customer_rank  
from orders)as t  
where customer_rank = 2;
```

```
select customer_name, order_id, amount , sum(amount) over(partition by  
customer_id),
```

```
round( amount / sum(amount) over(partition by customer_id) *100,2)
from orders;
```