

```
drop database if exists newdb2;
```

```
create database newdb2;
```

```
use newdb2;
```

```
CREATE TABLE Customers (  
    customer_id INT PRIMARY KEY,  
    customer_name VARCHAR(50),  
    city VARCHAR(30)  
);
```

```
INSERT INTO Customers VALUES  
(101, 'Alice', 'New York'),  
(102, 'Bob', 'Chicago'),  
(103, 'Charlie', 'Dallas'),  
(104, 'David', 'Seattle'),  
(105, 'Emma', 'Boston'),  
(106, 'Frank', 'Chicago'),  
(107, 'Grace', 'Dallas'),  
(108, 'Henry', 'Miami');
```

```
CREATE TABLE Orders (  
    order_id INT PRIMARY KEY,  
    customer_id INT,  
    order_date DATE,  
    amount DECIMAL(10,2),  
    status VARCHAR(20)
```

);

INSERT INTO Orders VALUES

(1001, 101, '2025-01-05', 1200, 'Delivered'),
(1002, 101, '2025-02-15', 800, 'Cancelled'),
(1003, 102, '2025-01-20', 3500, 'Delivered'),
(1004, 102, '2025-03-10', 600, 'Pending'),
(1005, 103, '2025-02-18', 900, 'Delivered'),
(1006, 104, '2025-03-05', 4500, 'Delivered'),
(1007, 104, '2025-04-01', 700, 'Pending'),
(1008, 105, '2025-01-11', 1500, 'Cancelled'),
(1009, 105, '2025-04-12', 2200, 'Delivered'),
(1010, 107, '2025-05-01', 1800, 'Pending');

select * from orders;

-- exist and in

select * from customers where customer_id in (select customer_id from orders);

select * from Customers where exists

(select 1 from orders where orders.customer_id = customers.customer_id);

-- find the customer who at lest one delivered order.

```
select * from customers where exists
```

```
(select 1 from orders where orders.customer_id = customers.customer_id and  
orders.status='delivered');
```

```
-- find customer who have both delivered and pending orders.
```

```
select c.customer_id,
```

```
       c.customer_name
```

```
from customers c
```

```
where exists (
```

```
    select 1
```

```
    from orders o
```

```
    where o.customer_id=c.customer_id
```

```
          and o.status = 'delivered'
```

```
)
```

```
and exists (
```

```
    select 1
```

```
    from orders o
```

```
    where o.customer_id=c.customer_id
```

```
          and o.status = 'pending'
```

```
)
```