

-- root connection

create database tcldb2;

use tcldb2;

create table tcldb2.test(id int, name varchar(20));

insert into tcldb2.test values(18,'abhinav');

select @@autocommit;-- by default autocommit is 1 means file will be automatically;

start transaction;

insert into tcldb2.test values(19,'raj');

select * from tcldb2.test; -- two rows here

commit; -- you save the change in the database

start transaction;

insert into tcldb2.test values(20,'japan');

insert into tcldb2.test values(21,'north korea');

select * from tcldb2.test;

start transaction;

insert into tcldb2.test values(22,'japan');

rollback; -- to revert the two lines insert

select * from tcldb2.test;

start transaction;

insert into tcldb2.test values(23,'shubh');

```
delete from tcldb2.test;  
rollback; -- to revert the two lines insert  
select * from tcldb2.test;
```

```
start transaction;  
insert into tcldb2.test values(25,'shgsd');  
savepoint tcldb2_test ; -- creating a reference point to revert to this transaction only  
rollback to tcldb2_test; -- revert to specific point
```

```
select * from tcldb2.test;
```

```
start transaction;  
insert into tcldb2.test values(26,'shgvdsd');  
savepoint tcldb2_test ; -- creating a reference point to revert to this transaction only  
rollback to tcldb2_test; -- revert to specific point  
select * from tcldb2.test;
```